Pipeline for RNA sequencing data analysis by combination of Nextflow and R

Jia-Hua Qu[1,2,*]

1. Department of Pathology, University of California San Francisco, San Francisco, CA 94143, USA
2. Department of Immunology, St. Jude Children's Research Hospital, Memphis, TN 38105, USA

Address correspondence to:

Dr. Jia-Hua Qu, MD, PhD*

Department of Pathology

University of California San Francisco

513 Parnassus Ave, HSW 518

San Francisco, CA 94143

USA

Tel: +1 571-523-6876

jiahuaqu@hotmail.com

Abstract

With the development of high-throughput technologies, RNA sequencing (RNA-seq) has become a widely used technology in biological studies and thus a large number of RNA-seq data are emerging and remain to be analyzed. Although there are many different options for analysis methods and tools, a unified pipeline for RNA-seq data analysis is always necessary for a laboratory. Given the update of new methods and tools, I summarized my customized analysis codes to generate an updated pipeline for RNA-seq data analysis. During aging, gene mutations accumulate, and hormone regulation is disrupted, which may exacerbate age-related diseases. Therefore, we generated a dataset from mice with a gene mutation or not and under different hormone treatments to study the effects of two factors, i.e., hormone and gene mutation, on the transcriptome. Based on the Nextflow nf-core rnaseq pipeline, this project established this pipeline consisting of three stages: (1) upstream analysis containing quality control of fastq files before and after trimming, trimming, alignment, and quantification; (2) midstream analysis containing count normalization, differentially expressed genes analysis, and visualization via boxplot, PCA, t-SNE, sample distance heatmap, MA plot, volcano plot, and gene expression heatmap; and (3) downstream analysis containing functional enrichments of KEGG pathways and GO terms. Results showed distinct effects of the single factor as well as interactive effects of the two factors. Codes are also provided for readers who want to customize their analysis pipeline adapted from this pipeline easily.

Introduction

In the field of modern biological studies, omics are widely used, and thus high-throughput data are generated every day in need of customized analysis. There are many different options for analysis methods and tools. They can be classified into two major types: graphical user interface and command line interface. The former can be divided into website applications and local computer applications; the latter can be divided into programs written in different programming languages, such as Bash, R, Python, Perl, Groovy, etc.

The graphical user interface is convenient for a broad range of scientists who want to make full use of omics but don't have programming skills to analyze high-throughput data, whereas the command line interface is more flexible in customizing analysis and helps save time in repeated procedures. Website applications are usually updated more frequently than local computer applications, so website applications often provide access to the latest version of databases, but they may be unstable. In contrast, local computer applications are more stable and can be used to reproduce results better than website applications. Partek Flow is a representative website application with a graphical user interface, and it provides convenience in omics data analysis, particularly useful in single-cell RNA-seq data analysis[1]. JMP and GraphPad Prism are two well-used local computer applications with graphical user interfaces with statistical functions as well[2].

Despite the advantages and convenience of the graphical user interface, professional bioinformaticians prefer the command line interface because of its more powerful functions that can also be extendible and scalable. For example, fastq files of a larger

number of samples are usually analyzed in the Linux system, because the Linux system can be used to process high-throughput data in parallel and fast[3]. R and Python are more and more popular because both are open-sourced and free[4]. A lot of R packages and Python libraries are available and provide conveniences for bioinformatics analysis.

In addition, there are some tools invented especially for building pipelines, such as Nextflow[5], Snakemake[6], WDL and Cromwell[7], etc. For example, Nextflow is well-used, because it enables scalable and reproducible scientific workflows and allows the adaptation of pipelines written in the most common scripting languages. In addition, Nextflow has a very active user community which released many curated nf-core pipelines (https://nf-co.re/)[8] that can be modified for customized use.

Given a typical pipeline for RNA sequencing (RNA-seq) data analysis consists of multiple steps, this project divided it into three stages: (1) upstream data process; (2) midstream visualization of count matrix; and (3) downstream functional analysis. Different tools have different advantages at different stages and different sets of data require customized analysis, so the combination of different tools is a better choice in a practical project.

Because of the advantages of different tools, the combination of various tools allows us to customize our bioinformatics analysis flexibly[9]. My pipeline was built by the combination of Nextflow nf-core rnaseq pipeline and R with many R packages.

Aging is a heavy burden to the modern society. The recent review proposed ten aspects of biomarkers of aging, including epigenetic changes, genetic instability, telomere shortening, nuclear body disorders, cell cycle arrest, mitochondrial malfunction, proteostatic stress, metabolic alterations, signaling pathway rerouting, and senescence-associated secretory phenotype (SASP)[10]. In the aspect of genetic instability, mutations that are caused by genomic instability and impaired DNA repair exhibit an age-related increase in a tissue-specific manner[11, 12]. In addition, the endocrine and exocrine in multiple organs are closely related to aging[13]. For example, during aging, gene mutations are accumulated, and hormone regulation is disrupted, which may exacerbate age-related diseases in return. I applied this pipeline to our in-house dataset that was generated from mice with a gene mutation or not and under different hormone treatments. My results showed distinct effects of a single factor as well as interactive effects of the two factors, i.e., hormone and gene mutation, on mouse transcriptome.

Tools

Linux system
Wynton HPC (https://wynton.ucsf.edu/hpc/index.html) - UCSF Research Computing at Scale, based upon the CentOS 7.

Pipeline tool
The nf-core/rnaseq pipeline (https://nf-co.re/rnaseq/3.10.1)[8], based upon Nextflow (https://www.nextflow.io/)[5].

129 R
130 R version: 4.1.3 or 4.2.2
131 RStudio version: 2023.09.0 Build 463
132 R packages versions:

```
1.  package.version("dplyr")   # "1.1.0"[14]
2.  package.version("tidyr")   # "1.3.0"[14]
3.  package.version("DESeq2")   # "1.34.0"[15]
4.  package.version("tibble")   # "3.1.8"[14]
5.  package.version("ggplot2")   # "3.4.1"[14]
6.  package.version("RColorBrewer")   # "1.1-3"
7.  package.version("pheatmap")   # "1.0.12"
8.  package.version("Rtsne")   # "0.16"[16, 17]
9.  package.version("readr")   # "2.1.4"[14]
10. package.version("clusterProfiler")   # "4.2.2"[18]
11. package.version("org.Mm.eg.db")   # "3.14.0"
12. package.version("EnhancedVolcano")   # "1.12.0"
```

Dataset

In this project, our in-house RNA-seq dataset was used as a demo. Sequencing type: SE.
Library Kit: Nugen Universal Plus. Machine: HiSeq4000. Because our in-house RNA-seq
dataset is unpublished and the application of this pipeline is not restricted to this dataset,
the detailed meta information is hidden. In brief, this dataset was obtained from mice
with a gene mutation (mut) and their wild-type littermates (con), both of whom received
treatment of two hormones singly (E2, P4) or combinedly (E2P4) or placebo (Plac). In
total, this dataset contains eight groups of samples: Plac_con, Plac_mut, E2_con,
E2_mut, P4_con, P4_mut, E2P4_con, and E2P4_mut. This project did not intend to
describe the gene mutation within this dataset or to explain the definition of different
hormone treatments explicitly. When this pipeline is applied in other projects, *mut* can
represent any other gene mutation, and *E2* or *P4* can represent any other internal or
external stimuli or disease states.

Workflow

162
163 Figure 1. Workflow of RNA-seq data analysis. Upstream analysis of fastq files via
164 Nextflow, midstream analysis of count matrix and differentially expressed genes in R,
165 and downstream analysis of functional enrichment.
166
167

Based on the Nextflow nf-core rnaseq pipeline, this project established this pipeline
(Figure 1) consisting of three stages: (1) upstream analysis containing quality control of
fastq files before and after trimming, trimming, alignment, and quantification; (2)
midstream analysis containing count normalization, boxplot, PCA, t-SNE, sample
distance heatmap, differentially expressed genes analysis, MA plot, volcano plot, and
gene expression heatmap; and (3) downstream analysis containing functional enrichments
of KEGG pathways and GO terms.
175

Upstream analysis with Bash and Nextflow

177 1. Create a conda environment.
178   The virtual environment technique is an ideal way to manage systems and software, so
179 I recommended creating a virtual environment via conda
180 (https://docs.conda.io/en/latest/).

```
1. cd ~
2. mkdir 01-Nextflow
3. cd ~/01-Nextflow
4. module load Sali anaconda
5. conda create -n NextFlow-nf-core
6. source activate NextFlow-nf-core
7. python -V      # Python 3.8.10
```

189 2. Install Nextflow, nf-core, and rnaseq pipeline.
190   Singularity is a scientific container for the mobility of computing[19], so it is strongly
191 recommended to use a singular image of the nf-core/rnaseq program to reproduce the
192 analysis.

```
1. # install nextflow
2. conda install nextflow -y
3. conda list | grep nextflow   # version: 22.10.6
```

```
4.
5. # install nf-core
6. conda search nf-core
7. conda install nf-core -y
8. conda list | grep nf-core    # 2.7.2
9.
10.# install rnaseq pipeline
11.nf-core download nf-core/rnaseq
12.# select version: 3.10.1
13.# download singularity
```

3. Prepare the reference genome.

Because the data were obtained from mice, the GRCm38 reference genome and its accompanied annotation were downloaded from iGenome (https://support.illumina.com/sequencing/sequencing_software/igenome.html) and used in this project.

```
1. cd ~/01-Nextflow
2. mkdir -p reference_genome/mouse/Ensembl/GRCm38
3. cd reference_genome/mouse/Ensembl/GRCm38
4. nohup aws s3 --no-sign-request --region eu-west-
   1 sync s3://ngi-
   igenomes/igenomes/Mus_musculus/Ensembl/GRCm38/Annotation/Genes
   / . --exclude "*" --include "genes.gtf" &
5. nohup aws s3 --no-sign-request --region eu-west-
   1 sync s3://ngi-
   igenomes/igenomes/Mus_musculus/Ensembl/GRCm38/Sequence/WholeGe
   nomeFasta/ ./ &
```

4. Prepare fastq files.

```
1. cd ~/01-Nextflow
2. mkdir data
```

Copy fastq files that need to be analyzed into the folder ~/01-Nextflow/data.

5. Make a sample sheet.

Download the Python script to make a sample sheet for the subsequent analysis.

```
1. cd ~/01-Nextflow/data
2. wget -L https://raw.githubusercontent.com/nf-
   core/rnaseq/master/bin/fastq_dir_to_samplesheet.py
3. chmod a+x fastq_dir_to_samplesheet.py
4. ./fastq_dir_to_samplesheet.py -
   r1 _R1_001.fastq.gz ~/data/fastq samplesheet.csv
```

6. Customize a config file.

```
1. cd ~/01-Nextflow
2. mkdir analysis
3. mkdir output
4. cd ~/01-Nextflow/analysis
```

```
5. vim nextflow.config
```

Customized analysis includes:

- FastQC – Raw read QC
- TrimGalore – Adapter and quality trimming
- STAR – Alignment
- Salmon – Quantification
- RSeQC – Various RNA-seq QC metrics
- DESeq2 – PCA plot and sample pairwise distance heatmap and dendrogram
- MultiQC – Present QC for raw reads, alignment, read counting, and sample similarity

In addition, in the config file, we specified the paths to the input sample sheet of fastq files to be analyzed, reference genome files, and folder to save the output.

```
1.  // Global default params, used in configs
2.  params {
3.
4.      // Input options
5.      input = '~/data/fastq/samplesheet.csv'
6.
7.      // References
8.      fasta = '~/reference_genome/mouse/Ensembl/GRCm38/genome.fa'
9.      gtf = '~/reference_genome/mouse/Ensembl/GRCm38/genes.gtf'
10.     gencode = false
11.     save_reference = true
12.
13.     // QC
14.     skip_bigwig = true
15.     skip_stringtie = true
16.     skip_preseq = true
17.     skip_qualimap = true
18.     deseq2_vst = true
19.
20.     // Boilerplate options
21.     outdir = '~/output'
22.     email = "jiahua.qu@hotmail.com"
23.
24.     // Max resource options
25.     // Defaults only, expecting to be overwritten
26.     max_memory = '500.GB'
27.     max_cpus = 12
28.     max_time = '240.h'
29. }
```

7. Make a bash script.

```
1. cd ~/01-Nextflow/analysis
2. vim my_script.sh
```

In the bash script, we specified: (1) required computation resources including core number, memory, and running time; (2) paths to input files including log file that records progress, Nextflow workflow program, singularity profile, and config file with customized settings.

```bash
1. #! /usr/bin/env bash
2. #
3. #$ -S /bin/bash
4. #$ -cwd
5. #$ -r y
6. #$ -j y
7. #$ -pe smp 6
8. #$ -l mem_free=45G
9. #$ -l scratch=270G
10.#$ -l h_rt=24:00:00
11.
12.module load Sali anaconda
13.source activate NextFlow-nf-core
14.
15.# set path
16.log=~/01-Nextflow/analysis/my.log
17.workflow=~/01-Nextflow/nf-core-rnaseq-3.10.1/workflow
18.profile=singularity
19.config=~/01-Nextflow/analysis/nextflow.config
20.
21.# run pipeline
22.nextflow -log $log run $workflow -profile $profile -resume -
   c $config
23.
24.conda deactivate
25.
26.[[ -n "$JOB_ID" ]] && qstat -j "$JOB_ID"
```

8. Submit a job to run in the background.
```bash
1. qsub my_script.sh
```

9. Output.
   The output contains two major parts: (1) star_salmon output including count matrix and metadata, and (2) MultiQC report showing quality control of fastq files before and after trimming (Figure 2).

Figure 2. Screenshot of MultiQC report. The report summarizes quality control results of fastq files before and after each process.

Midstream analysis with R

10. Read in rds object generated in the last step.

```
1. ### create a folder
2. setwd("~/")
3. if (!file.exists("02-QC")){
4.   dir.create("02-QC")
5. }
6. setwd("~/02-QC")
7.
8. ### read in rds
9. # use the salmon.merged.gene_counts.rds
10.gene_counts <- readRDS("~/01-
   Nextflow/output/star_salmon/salmon.merged.gene_counts.rds")
11.
12.# extract and process count matrix
13.counts <- gene_counts@assays@data$counts
14.# round non-integer to integer for loading into DESeq2
15.counts_round <- round(counts, digits = 0)
16.# remove rows whose values are all zero
17.library(dplyr)
18.counts_round <- counts_round %>%
19.   filter(rowSums(.) > 0)
20.
21.# extract meta_data
22.library(tidyr)
23.meta_data <- data.frame(sample=gene_counts@colData@rownames) %
   >%
```

```
24.  separate(sample, into=c("treatment","genotype","num"), sep =
       "\\.", remove = FALSE) %>%
25.  unite(col = "condition", treatment,genotype, remove = FALSE)
26.meta_data$condition <- factor(meta_data$condition)
27.meta_data$treatment <- factor(meta_data$treatment)
28.meta_data$genotype <- factor(meta_data$genotype, levels = c("c
       on", "mut"))
29.saveRDS(meta_data, "meta_data.rds", compress = T)
```

11. Generate a dds object with the DESeq2 R package.

```
1. library(DESeq2)
2. # Load in Salmon output
3. dds_new <- DESeqDataSetFromMatrix(countData = counts_round,
4.                                     colData = meta_data,
5.                                     design= ~ condition)
6.
7. # Normalization
8. dds_new <- estimateSizeFactors(dds_new)
9. dds_rlog <- rlog(dds_new)
10.dds_vst <- varianceStabilizingTransformation(dds_new)
11.assay(dds_new, "rlog") <- assay(dds_rlog)
12.assay(dds_new, "vst") <- assay(dds_vst)
13.saveRDS(dds_new, "dds_new.rds", compress = T)
14.saveRDS(dds_rlog, "dds_rlog.rds", compress = T)
15.saveRDS(dds_vst, "dds_vst.rds", compress = T)
```

12. Plot to visualize the read counts.

```
1. ### create a folder
2. setwd("~/02-QC")
3. if (!file.exists("QCplots")){
4.   dir.create("QCplots")
5. }
6.
7. ### 1. boxplot
8. library(DESeq2)
9. ## 1.1. counts_vst
10.counts_vst <- dds_new@assays@data$vst
11.
12.library(tibble)
13.dat <- counts_vst %>%
14.   as.data.frame() %>%
15.   rownames_to_column(var="gene") %>%
16.   gather(key = "sample", value = "counts_vst", -gene) %>%
17.   left_join(meta_data, by="sample")
18.
19.library(ggplot2)
```

```
407  20. p_1 <- ggplot(data=dat,aes(x=sample,y=counts_vst,fill=conditio
408      n)) +
409  21.   geom_boxplot()+
410  22.   labs(x="Sample",y="VST Normalized Read Counts")+
411  23.   ggtitle("VST Normalized Read Count by Sample") +
412  24.   theme(axis.text.x=element_text(angle = 90, vjust = 0.5, hjus
413      t = 1))
414  25. ggsave(filename = "QCplots/boxplot-
415      counts_vst.pdf", plot = p_1, width = 10, height = 5)
416  26.
417  27. ## 1.2. counts_rlog
418  28. counts_rlog <- dds_new@assays@data$rlog
419  29.
420  30. library(tibble)
421  31. dat <- counts_rlog %>%
422  32.   as.data.frame() %>%
423  33.   rownames_to_column(var="gene") %>%
424  34.   gather(key = "sample", value = "counts_rlog", -gene) %>%
425  35.   left_join(meta_data, by="sample")
426  36.
427  37. library(ggplot2)
428  38. p_2 <- ggplot(data=dat,aes(x=sample,y=counts_rlog,fill=conditi
429      on)) +
430  39.   geom_boxplot()+
431  40.   labs(x="Sample",y="rlog Normalized Read Counts")+
432  41.   ggtitle("rlog Normalized Read Count by Sample") +
433  42.   theme(axis.text.x=element_text(angle = 90, vjust = 0.5, hjus
434      t = 1))
435  43. ggsave(filename = "QCplots/boxplot-
436      counts_rlog.pdf", plot = p_2, width = 10, height = 5)
437  44.
438  45. ### 2. sample correlation heatmap
439  46. sampleDists <- dist(t(counts_vst))
440  47. sampleDistMatrix <- as.matrix(sampleDists)
441  48.
442  49. library(RColorBrewer)
443  50. colors <- colorRampPalette( rev(brewer.pal(9, "Oranges")) )(25
444      5)
445  51. mydata_col = data.frame(condition=meta_data$condition, row.nam
446      es = meta_data$sample)
447  52.
448  53. library(pheatmap)
449  54. p_3 <- pheatmap(
450  55.   sampleDistMatrix,
451  56.   clustering_distance_rows=sampleDists,
452  57.   clustering_distance_cols=sampleDists,
453  58.   col=colors,
454  59.   annotation_col = mydata_col,
```

```
455   60.    main="Euclidean distance between samples"
456   61. )
457   62.
458   63. ### make my customized function to save heatmap
459   64. save_pheatmap_pdf <- function(x, filename, width, height) {
460   65.    stopifnot(!missing(x))
461   66.    stopifnot(!missing(filename))
462   67.    pdf(filename, width=width, height=height)
463   68.    grid::grid.newpage()
464   69.    grid::grid.draw(x$gtable)
465   70.    dev.off()
466   71. }
467   72. save_pheatmap_pdf(p_3, "QCplots/sample_heatmap.pdf", 7, 6.5)
468   73.
469   74. ### 3. gene expression heatmap of top 1000 variable genes
470   75. counts_vst_var <- as.data.frame(counts_vst)
471   76. counts_vst_var$var <- apply(counts_vst,1,var)
472   77. counts_vst_var <- counts_vst_var %>%
473   78. saveRDS(counts_vst_var, "counts_vst_var.rds", compress=T)
474   79. counts_vst_var <- counts_vst_var %>%
475   80.    slice(1:1000) %>%
476   81.    as.matrix()
477   82.
478   83. p_4 <- pheatmap(counts_vst_var[,1:24],
479   84.                scale="row",
480   85.                color = colorRampPalette(c("darkblue", "white",
481        "darkred"))(1000),
482   86.                annotation_col = mydata_col,
483   87.                main="Gene Expression (VST) of Top 1000 Variable
484        Genes",
485   88.                show_rownames = F)
486   89. save_pheatmap_pdf(p_4, "QCplots/gene_heatmap.pdf", 7, 6.5)
487   90.
488   91. ### 4. PCA plots
489   92. # make my customized function to plot PCA
490   93. plotPCA_vst <- function (object, assay, ntop = 1000) {
491   94.    rv <- rowVars(assay(object, assay))
492   95.    select <- order(rv, decreasing = TRUE)[seq_len(min(ntop, len
493        gth(rv)))]
494   96.    pca <- prcomp(t(assay(object, assay)[select, ]), center=TRUE
495        , scale=FALSE)
496   97.    percentVar <- pca$sdev^2/sum(pca$sdev^2)
497   98.    df <- cbind( as.data.frame(colData(object)), pca$x)
498   99.    # order points so extreme samples are more likely to get lab
499        el
500   100.       ord <- order(abs(rank(df$PC1)-
501        median(df$PC1)), abs(rank(df$PC2)-median(df$PC2)))
502   101.       df <- df[ord,]
```

```
503  102.         attr(df, "percentVar") <- data.frame(PC=seq(along=perc
504      entVar), percentVar=100*percentVar)
505  103.         return(df)
506  104.       }
507  105.
508  106.     pca.data <- plotPCA_vst(dds_new, assay="vst", ntop=1000)
509  107.     saveRDS(pca.data, "pca.data.rds", compress = T)
510  108.
511  109.     for (i in c(1:4)) {
512  110.       for (j in c((i+1):5)) {
513  111.         percentVar <- round(attr(pca.data, "percentVar")$per
514      centVar)
515  112.         p <- ggplot(pca.data, aes_string(x=paste0("PC",i), y
516      =paste0("PC",j), color="condition")) +
517  113.           geom_point(size=3) +
518  114.           xlab(paste0("PC",i,": ",percentVar[i],"% variance"
519      )) +
520  115.           ylab(paste0("PC",j,": ",percentVar[j],"% variance"
521      )) +
522  116.           theme_bw()
523  117.         ggsave(filename = paste0("QCplots/PCAplot.","PC",i,"
524      vs","PC",j,".pdf"), plot = p, width=6, height=5)
525  118.       }
526  119.     }
527  120.
528  121.     ### 5. t-SNE plots
529  122.     library(Rtsne)
530  123.     # make my customized function to plot t-SNE
531  124.     plottsne_vst <- function (object, assay, perpl, ntop = 1
532      000) {
533  125.       rv <- rowVars(assay(object, assay))
534  126.       select <- order(rv, decreasing = TRUE)[seq_len(min(nto
535      p, length(rv)))]
536  127.       set.seed(123)
537  128.       tsne <- Rtsne(t(assay(object, assay)[select, ]), perpl
538      exity=perpl)
539  129.       df <- as.data.frame(tsne$Y)
540  130.       names(df) <- c("Dimention1","Dimention2")
541  131.       df <- cbind(df, meta_data)
542  132.       return(df)
543  133.     }
544  134.
545  135.     for (i in 1:6) {
546  136.       tsne.data <- plottsne_vst(dds_new, assay="vst", perpl=
547      i, ntop=1000)
548  137.       saveRDS(tsne.data, paste0("tsne.data-
549      perplexity_",i,".rds"), compress = T)
550  138.
```

```
551   139.        p <- ggplot(tsne.data, aes_string(x="Dimention1", y="D
552      imention2", color="condition")) +
553   140.          geom_point(size=3) +
554   141.           xlab("Dimention 1") +
555   142.           ylab("Dimention 2") +
556   143.           theme_bw()
557   144.         ggsave(filename = paste0("QCplots/tSNEplot-
558      perplexity_",i,".pdf"), plot = p, width=6, height=5)
559   145.      }
```

560
561 13. Visualization results of read counts.
562   The raw data in the count matrix were normalized via two methods, rlog and vst, and
563 were displayed in two box plots (Figure 3 and 4).
564

565
566 Figure 3. Box plot of read counts normalized by the rlog method. Samples in different
567 groups are in different colors. The X-axis represents each sample. The Y-axis represents
568 read counts normalized by the rlog method.
569
570
571

572
573 Figure 4. Box plot of read counts normalized by the vst method. Samples in different
574 groups are in different colors. The X-axis represents each sample. The Y-axis represents
575 read counts normalized by the vst method.
576
577
578   To observe the correlation among samples, the distance between each pair of samples
579 was calculated and the Euclidean distance was visualized in the heatmap (Figure 5).
580

Figure 5. Heatmap of Euclidean distance between samples. Samples in different groups are in different colors. The color of the crossing square between two samples indicates the distance between those two samples. The darker the crossing square is, the smaller the distance between those two samples is.

In addition to the correlation at the sample level, the correlation across all samples was also calculated and visualized at the gene expression level (Figure 6).

591
Figure 6. Heatmap of gene expression across samples. Samples in different groups are in
different colors. The color of each gene indicates the scaled level of gene expression
across samples. The redder indicates the higher level while the bluer indicates the lower
level.

To further observe the distribution of samples, the dimension of read counts was reduced
via principal component analysis (PCA) and visualized the results within combinations of
each two of the first five principal components, i.e., PC1 and PC2, PC1 and PC3, PC1
and PC4, PC1 and PC5, PC2 and PC3, PC2 and PC4, PC2 and PC5, PC3 and PC4, PC3
and PC5, PC4 and PC5. The first two PCA plots were displayed here as examples (Figure
7A and 7B). In addition, the read counts were projected into the t-distributed Stochastic
Neighbor Embedding (t-SNE) projection with a perplexity value from 1 to 6. The first
and the last t-SNE plots were displayed here as examples (Figure 7C and 7C). Both PCA
and t-SNE plots demonstrated the separation of samples by genotype and hormone
treatment. Particularly, the E2 treatment affected gene expression the most significantly,
and the P4 treatment regulated gene expression in a strikingly different way from the E2
treatment, while the inner group heterogeneity could not be ignored. The correlation

observed in PCA and t-SNE plots was consistent with that in heatmaps at the sample
distance level (Figure 5) and gene expression level (Figure 6).
612

613
614   Figure 7. Sample distribution in projections of reduced dimension. A-B. PCA plots with
615   PC1 and PC2 (A), and PC1 and PC3 (B). C-D. t-SNE plots with perplexity = 1 (C) and
616   perplexity = 6 (D).
617

14. Convert gene ID from gene symbol to ENTREZID.
The default gene IDs in the STAR output are gene symbols that are intuitive and
convenient to read and understand. However, ENTREZID is preferred by many advanced
bioinformatic software[18] because it is unique and more accurate than gene symbols.
Therefore, I converted gene IDs from gene symbols to ENTREZIDs, which were required
in subsequent analyses.

```
1. ### create folders
2. setwd("~/")
3. if (!file.exists("03-DE")){
```

```r
4.   dir.create("03-DE")
5. }
6. setwd("~/03-DE")
7.
8. ### read in gene information obtained from Nextflow
9. library(readr)
10.bg_ID <- read_delim("~/01-
   Nextflow/output/star_salmon/salmon_tx2gene.tsv",
11.                    delim = "\t", escape_double = FALSE,
12.                    col_names = FALSE, trim_ws = TRUE)
13.names(bg_ID) <- c("transcript", "gene", "gene_name")
14.bg_ID <- bg_ID[,-1] %>% unique()
15.
16.library(clusterProfiler)
17.library(org.Mm.eg.db)
18.#keytypes(org.Mm.eg.db)
19.bg_ENTREZID <- bitr(bg_ID$gene_name,
20.                    fromType = "SYMBOL",
21.                    toType = "ENTREZID",
22.                    OrgDb = "org.Mm.eg.db")
23.bg_ID <- left_join(bg_ID, bg_ENTREZID, by=c("gene_name"="SYMBO
   L"))
24.saveRDS(bg_ID, "bg_ID.rds", compress = T)
```

15. Differentially expressed gene (DEG) analysis.

In this project, we aimed to compare the difference between mutant mice (mut) and their wild-type littermates (con) in each condition (hormone treatment or placebo) separately, but the same analysis codes can be used to compare every two groups of samples with minor adjustments.

```r
1. ### create folders
2. setwd("~/03-DE")
3.
4. if (!file.exists("DEfiles")){
5.   dir.create("DEfiles")
6. }
7.
8. if (!file.exists("MAplots")){
9.   dir.create("MAplots")
10.}
11.
12.if (!file.exists("Volcanoplots")){
13.  dir.create("Volcanoplots")
14.}
15.
16.if (!file.exists("Heatmaps")){
17.  dir.create("Heatmaps")
18.}
```

```
19.
20. ### generate FC and FDR via DESeq2
21. library(DESeq2)
22. library(EnhancedVolcano)
23. # read in dds object and metadata
24. dds_new <- readRDS("~/02-QC/dds_new.rds")
25. meta_data <- readRDS("~/02-QC/meta_data.rds")
26.
27. ### run DESeq to get result objects in loop
28. library(ggplot2)
29. library(readr)
30. library(tibble)
31. library(pheatmap)
32. counts_vst <- dds_new@assays@data$vst
33. dds_new_res <- DESeq(dds_new)
34. saveRDS(dds_new_res, "dds_new_res.rds", compress = T)
35.
36. for (i in levels(meta_data$treatment)) {
37.
38.   ### 1. DE results
39.   sampleA <- paste(i, "con", sep = "_")
40.   sampleB <- paste(i, "mut", sep = "_")
41.   condition <- "condition"
42.   contrastV <- c(condition, sampleA, sampleB)
43.   res <- results(dds_new_res,  contrast=contrastV)
44.   saveRDS(res, paste0("DEfiles/DE-
     ",sampleB,"vs",sampleA,".rds"), compress = T)
45.
46.   # join gene_name
47.   res_df <- as.data.frame(res)
48.   res_symbol <- res_df %>%
49.     as.data.frame() %>%
50.     rownames_to_column(var="gene") %>%
51.     left_join(bg_ID, by="gene")
52.
53.   ### 2. MA plots
54.   pdf(file = paste0("MAplots/MAplot-
     ",sampleB,"vs",sampleA,".pdf"),
55.       width=7, height=5)
56.   MAplot <- plotMA(object=res, alpha=0.05,
57.                    main=paste0(sampleB,"vs",sampleA),
58.                    colNonSig="black",
59.                    colSig="red",
60.                    colLine="blue")
61.   dev.off()
62.
63.   ### 3. volcano plots
64.   vol <- EnhancedVolcano(res_symbol,
```

```
65.                    lab = NA,
66.                    x = 'log2FoldChange',
67.                    y = 'padj',
68.                    ylab = bquote(~-Log[10] ~ italic(FDR)),
69.                    pCutoff = 0.05,
70.                    FCcutoff = 2,
71.                    title = paste0(sampleB,"vs",sampleA),
72.                    legendLabels=c('Not DE &\nabsolute FC < 2',
73.                                   'Not DE &\nabsolute FC > 2',
74.                                   'FDR < 0.05 &\nabsolute FC <
   2',
75.                                   'FDR < 0.05 &\nabsolute FC >
   2'),
76.                    legendPosition = 'right')
77.   ggsave(filename = paste0("Volcanoplots/Volcanoplot-
   ",sampleB,"vs",sampleA,".pdf"), plot=vol, width = 7, height =
   7)
78.
79.   vol_lab <- EnhancedVolcano(res_symbol,
80.                            lab = res_symbol$gene_name,
81.                            x = 'log2FoldChange',
82.                            y = 'padj',
83.                            ylab = bquote(~-
   Log[10] ~ italic(FDR)),
84.                            pCutoff = 0.05,
85.                            FCcutoff = 2,
86.                            title = paste0(sampleB,"vs",sampl
   eA),
87.                            legendLabels=c('Not DE &\nabsolut
   e FC < 2',
88.                                           'Not DE &\nabsolut
   e FC > 2',
89.                                           'FDR < 0.05 &\nabs
   olute FC < 2',
90.                                           'FDR < 0.05 &\nabs
   olute FC > 2'),
91.                            legendPosition = 'right')
92.   ggsave(filename = paste0("Volcanoplots/Volcanoplot_gene_name
   -
   ",sampleB,"vs",sampleA,".pdf"), plot=vol_lab, width = 7, heigh
   t = 7)
93.
94.   ### 4. heatmaps
95.   res_symbol <- res_symbol %>%
96.     mutate(change=case_when(padj < 0.05 ~ "DE",
97.                             TRUE ~ "Not")) %>%
98.     mutate(direction=case_when(change == "DE" & log2FoldChange
   > 0 ~ "Up",
```

```
99.                                    change == "DE" & log2FoldChange
    < 0 ~ "Down",
100.                                    TRUE ~ "Not"))
101.        write.csv(res_symbol, paste0("DEfiles/DE-
    ",sampleB,"vs",sampleA,".csv"))
102.
103.        counts_vst_DE <- counts_vst[res_symbol$change=="DE",]
104.        mydata_col <- data.frame(condition=meta_data$condition
    , row.names = meta_data$sample)
105.        heat_DE_1 <- pheatmap(counts_vst_DE,
106.                            scale="row",
107.                            color = colorRampPalette(c("dark
    blue", "white", "darkred"))(1000),
108.                            annotation_col = mydata_col,
109.                            main=paste0(sampleB,"vs",sampleA
    ," FDR < 0.05"),
110.                            show_rownames = F)
111.        save_pheatmap_pdf(heat_DE_1, paste0("Heatmaps/Heatmap-
    ",sampleB,"vs",sampleA,".pdf"), 7, 6.5)
112.
113.        # row names
114.        tree_row <- data.frame(gene = rownames(counts_vst_DE[h
    eat_DE_1$tree_row[["order"]],])) %>%
115.            left_join(bg_ID, by="gene")
116.        saveRDS(tree_row, paste0("Heatmaps/Heatmap-
    ",sampleB,"vs",sampleA,".rds"), compress = T)
117.        write.csv(tree_row, paste0("Heatmaps/Heatmap-
    ",sampleB,"vs",sampleA,".csv"))
118.
119.        meta_data_2 <- meta_data[meta_data$treatment==i,]
120.        mydata_col_2 = data.frame(condition=meta_data_2$condit
    ion, row.names = meta_data_2$sample)
121.        counts_vst_DE_2 <- counts_vst_DE[,meta_data_2[,1]]
122.        heat_DE_2 <- pheatmap(counts_vst_DE_2,
123.                            scale="row",
124.                            color = colorRampPalette(c("dark
    blue", "white", "darkred"))(1000),
125.                            annotation_col = mydata_col_2,
126.                            main=paste0(sampleB,"vs",sampleA
    ," FDR < 0.05"),
127.                            show_rownames = F)
128.        save_pheatmap_pdf(heat_DE_2, paste0("Heatmaps/Heatmap2
    -",sampleB,"vs",sampleA,".pdf"), 7, 6.5)
129.
130.        # row names
131.        tree_row_2 <- data.frame(gene = rownames(counts_vst_DE
    [heat_DE_2$tree_row[["order"]],])) %>%
132.            left_join(bg_ID, by="gene")
```

```
819   133.        saveRDS(tree_row_2, paste0("Heatmaps/Heatmap2-
820      ",sampleB,"vs",sampleA,".rds"), compress = T)
821   134.        write.csv(tree_row_2, paste0("Heatmaps/Heatmap2-
822      ",sampleB,"vs",sampleA,".csv"))
823   135.     }
```

16. Visualization results of DEG analysis.
Four sub-folders, i.e., Plac_mutvPlac_con, E2_mutvsE2_con, P4_mutvsP4_con, and
E2P4_mutvsE2P4_con, were created inside the folder of ~/03-DE/DEfiles containing
results of DEG analysis. In addition, the results were visualized in various plots that were
saved into sub-folders.
MA plots suggested that the fold changes of genes between mut and con were
distributed evenly and independent of mean values of normalized counts (Figure 8).
832

833
Figure 8. MA plots of DEG analysis results. X-axis represents the mean values of vst
normalized counts. The Y-axis represents the log-transformed fold change in mut vs. con
in each condition of hormone treatment.

In addition to MA plots, volcano plots were also generated to observe the significant
changes between mut and con. Because the above analyses suggested that E2 treatment
had the most obvious effect on mut vs. con, the volcano plots of DEGs in mut vs. con
under the E2 treatment were displayed here as examples (Figure 9). The panel on the
right also labeled symbols of the most significantly changed genes (Figure 9B).

845
846 Figure 9. Volcano plots of DEGs in mut vs. con under the E2 treatment. The X-axis
847 represents the log2 transformed fold change in mut vs. con. The Y-axis represents the
848 minus log10 transformed FDR. Each dot represents one gene and is colored
849 corresponding to the cutoffs shown in the legend.
850
851
852 To observe the gene expression across samples, heatmaps were also generated for two
853 groups of samples (Figure 10A) and all groups of samples (Figure 10B). The heatmap
854 showed the two distinct clusters of genes that were upregulated or downregulated in
855 E2_mut vs. E2_con (Figure 10A).
856

857
858 Figure 10. Heatmap of expression of significantly changed genes in mut vs. con under the
859 E2 treatment. A. Heatmaps of comparison between two groups of samples. B. Heatmap
860 across all samples. Samples in different groups are in different colors. The color of each
861 gene indicates the scaled level of gene expression across samples. The redder indicates
862 the higher level while the bluer indicates the lower level.

863
864

Downstream analysis with R

17. Functional analyses including Gene Ontology (GO) – Biological Process (BP),
Cellular Component (CC), and Molecular Function (MF), and KEGG analyses.

```
1. ### Create folders
2. setwd("~")
3. if (!file.exists("04-Pathway")){
4.   dir.create("04-Pathway")
5. }
6. setwd("~/04-Pathway")
7.
8. if (!file.exists("Pathways_tables")){
9.   dir.create("Pathways_tables")
10.}
11.
12.if (!file.exists("Pathways_figures")){
13.  dir.create("Pathways_figures")
14.}
15.
16.library(clusterProfiler)
17.library(org.Mm.eg.db)
18.library(ggplot2)
19.library(readr)
20.
21.bg_ID <- readRDS("../03-DE/bg_ID.rds")
22.bg <- bg_ID$ENTREZID
23.meta_data <- readRDS("../02-QC/meta_data.rds")
24.treatment <- levels(meta_data$treatment)
25.
26.### Loops
27.for (i in treatment) {
28.   sampleA <- paste(i, "con", sep = "_")
29.   sampleB <- paste(i, "mut", sep = "_")
30.   # Read in DE table
31.   res_symbol <- read.csv(paste0("../03-DE/DEfiles/DE-
     ",sampleB,"vs",sampleA,".csv"))
32.
33.   ## Inner loop for Up or Down
34.   for (j in c("Up", "Down")){
35.     DEG <- res_symbol[res_symbol$direction == j,]$ENTREZID %>%
36.       as.character()
37.
38.     # KEGG
39.     KEGG <- enrichKEGG(gene = DEG,
40.                        universe = bg,
```

```
41.                         organism ='mmu',
42.                         pvalueCutoff = 0.1,
43.                         qvalueCutoff = 0.1,
44.                         use_internal_data =FALSE)
45.   KEGG <- setReadable(KEGG, OrgDb = org.Mm.eg.db, keyType="E
   NTREZID")
46.    write_csv(as.data.frame(KEGG@result),paste0("Pathways_tabl
   es/",sampleB,"vs",sampleA,".",j,".KEGG.csv"))
47.    saveRDS(KEGG,paste0("Pathways_tables/",sampleB,"vs",sample
   A,".",j,".KEGG.rds"),compress=T)
48.   dot_KEGG <- dotplot(KEGG)
49.   ggsave(filename = paste0("Pathways_figures/",sampleB,"vs",
   sampleA,".",j,".KEGG.pdf"), plot = dot_KEGG, width = 7, height
    = 7)
50.
51.    # GO sub-categories
52.   for (GO in c("CC", "MF", "BP")) {
53.     GO_enrich <- enrichGO(gene = DEG,
54.                           universe = bg,
55.                           OrgDb = "org.Mm.eg.db",
56.                           keyType = "ENTREZID",
57.                           ont = GO,
58.                           pvalueCutoff  = 0.1,
59.                           pAdjustMethod = "BH",
60.                           qvalueCutoff  = 0.1,
61.                           readable=T)
62.    GO_enrich <- simplify(GO_enrich,cutoff=0.7,
63.                           by="p.adjust",
64.                           select_fun=min,
65.                           measure = "Wang")
66.     write_csv(as.data.frame(GO_enrich@result),paste0("Pathwa
   ys_tables/",sampleB,"vs",sampleA,".",j,".",GO,".csv"))
67.     saveRDS(GO_enrich,paste0("Pathways_tables/",sampleB,"vs"
   ,sampleA,".",j,".",GO,".rds"),compress=T)
68.    dot_GO <- dotplot(GO_enrich)
69.    ggsave(filename = paste0("Pathways_figures/",sampleB,"vs
   ",sampleA,".",j,".",GO,".pdf"), plot = dot_GO, width = 7, heig
   ht = 7)
70.       }
71.  }
72.}
```

18. Visualization of results of functional enrichment analysis.

DEGs were divided into two parts, i.e., upregulated (Up) and downregulated (Down) genes in mut vs. con under individual hormone treatment. The two parts were separately loaded into the clusterProfiler R package for functional enrichment of KEGG pathways and GO terms including BP, MF, and CC sub-categories. Here, the bubble charts of

956 KEEG pathways and GO terms enriched from DEGs in mut vs. con under the E2
957 treatment were displayed as examples (Figure 11).
958

959
960

961
962

963
964

965
Figure 11. Functional enrichments. IDs of significantly upregulated and downregulated
genes in E2_mut vs. E2_con were converted into the ENTREZ IDs and imported into the
clusterProfiler R package to conduct functional enrichment. The top ten terms with
adjusted p-values < 0.05 were displayed in bubble charts. Four categories were KEGG
pathways from the KEGG pathway database (A and B), GO_BP terms from the
Biological Process (Gene Ontology) database (C and D), GO_MF terms from Molecular
Function (Gene Ontology) database (E and F), and GO_CC from Cellular Component
(Gene Ontology) database (G and H). Color represents significance: the redder, the more
significant.

975
976

Discussion

This pipeline started from processing raw fastq files obtained from the Illumina HiSeq4000 sequencing machine, aligned reads to the Ensembl/GRCm38 reference genome via STAR, quantified to count matrix via Salmon, visualized normalized counts, analyzed and visualized DEGs, enriched and visualized KEGG pathways and GO terms to deduce changed functions in R.

This pipeline combined the advantages of Nextflow and R from upstream to midstream, and to downstream analyses. In the upstream analysis, different reference genomes can be downloaded from the igenomes repository (https://support.illumina.com/sequencing/sequencing_software/igenome.html) provided by Illumina. In addition to STAR and Salmon, other alignment and quantification software can be selected as a substitution. Addition parameters can be adjusted in the Nextflow config file. Therefore, this pipeline that was built based on Nextflow can be extended to analyze RNA-seq data generated from other species and with different qualities.

In the midstream and downstream analyses, this pipeline took advantage of R in statistics and visualization. In addition to the pairs of comparisons that were demonstrated here as examples, samples from any two groups can be compared via DESeq2 by this pipeline. I am considering expanding this pipeline to provide other options such as EdgeR and Limma which are also widely used. Of note, this pipeline inherited one of the best advantages of R, i.e., the customized and fast visualization. I provided codes to observe the data and results in many most popular plots. The generated figures can be combined and trimmed flexibly. All figures can be exported to PDF files which are editable and can be transformed into any other formats in graph edition software like Illustrator.

In summary, this pipeline provides an easy and convenient way to analyze RNA-seq data and reproduce bioinformatics analysis. Particularly, the enriched KEGG pathways and GO terms are very useful in the interpretation of biological functions and the discovery of regulatory mechanisms. The results demonstrated that age-associated alterations of mutation and hormones reprogram the transcriptome significantly. In addition to the age-related factors studied in this project, this pipeline can also be broadly applied in other RNA-seq data analyses in the future.

References

1.   Qu, J.H., et al., *Characterization of diverse populations of sinoatrial node cells and their proliferation potential at single nucleus resolution.* Heliyon, 2023. **9**(1): p. e12708.
2.   Qu, J.H., et al., *Transcriptome of left ventricle and sinoatrial node in young and old C57 mice.* Fortune Journal of Health Sciences, 2023. **6**: p. 332 - 356.
3.   Qu, J.H., et al., *Proteomic Landscape and Deduced Functions of the Cardiac 14-3-3 Protein Interactome.* Cells, 2022. **11**(21).

4. Agrimi, J., et al., *Cardiac AC8 Over-Expression Increases Locomotion by*
Altering Heart-Brain Communication. JACC Clin Electrophysiol, 2023.
5. Di Tommaso, P., et al., *Nextflow enables reproducible computational workflows.*
Nat Biotechnol, 2017. **35**(4): p. 316-319.
6. Köster, J. and S. Rahmann, *Snakemake-a scalable bioinformatics workflow*
engine. Bioinformatics, 2018. **34**(20): p. 3600.
7. Voss, K., G. Van der Auwera, and J. Gentry, *Full-stack genomics pipelining with*
GATK4 + WDL + Cromwell F1000Research, 2017. **6**: p. 1381.
8. Ewels, P.A., et al., *The nf-core framework for community-curated bioinformatics*
pipelines. Nat Biotechnol, 2020. **38**(3): p. 276-278.
9. Tarasov, K.V., et al., *A remarkable adaptive paradigm of heart performance and*
protection emerges in response to marked cardiac-specific overexpression of
ADCY8. Elife, 2022. **11**.
10. Bao, H., et al., *Biomarkers of aging.* Sci China Life Sci, 2023. **66**(5): p. 893-1066.
11. Dollé, M.E., et al., *Rapid accumulation of genome rearrangements in liver but not*
in brain of old mice. Nat Genet, 1997. **17**(4): p. 431-4.
12. Stuart, G.R., et al., *Mutation frequency and specificity with age in liver, bladder*
and brain of lacI transgenic mice. Genetics, 2000. **154**(3): p. 1291-300.
13. Broekmans, F.J., M.R. Soules, and B.C. Fauser, *Ovarian aging: mechanisms and*
clinical consequences. Endocr Rev, 2009. **30**(5): p. 465-93.
14. Wickham, H., et al., *Welcome to the Tidyverse.* Journal of Open Source Software,
2019. **4**(43).
15. Love, M.I., W. Huber, and S. Anders, *Moderated estimation of fold change and*
dispersion for RNA-seq data with DESeq2. Genome Biol, 2014. **15**(12): p. 550.
16. Van der Maaten, L. and G. Hinton, *Visualizing data using t-SNE.* Journal of
machine learning research, 2008. **9**(11).
17. Van Der Maaten, L., *Accelerating t-SNE using tree-based algorithms.* The journal
of machine learning research, 2014. **15**(1): p. 3221-3245.
18. Wu, T., et al., *clusterProfiler 4.0: A universal enrichment tool for interpreting*
omics data. Innovation (Camb), 2021. **2**(3): p. 100141.
19. Kurtzer, G.M., V. Sochat, and M.W. Bauer, *Singularity: Scientific containers for*
mobility of compute. PLoS One, 2017. **12**(5): p. e0177459.
1054