Pipeline for RNA sequencing data analysis by combination of Nextflow and R

Jia-Hua Qu[1,2,3,*]

1. Department of Pathology, University of California San Francisco, San Francisco, CA 94143, USA
2. Department of Immunology, St. Jude Children's Research Hospital, Memphis, TN 38105, USA
3. Department of Host-Microbe Interactions, St. Jude Children's Research Hospital, Memphis, TN 38105, USA

Address correspondence to:

Dr. Jia-Hua Qu, MD, PhD*

Department of Pathology

University of California San Francisco

513 Parnassus Ave, HSW 518

San Francisco, CA 94143

USA

Tel: +1 571-523-6876

jiahuaqu@hotmail.com

37
38
39

Abstract

With the development of high-throughput technologies, RNA sequencing (RNA-seq) has
become a widely used technology in biological studies and thus a large number of RNA-
seq data are emerging and remain to be analyzed. Although there are many different
options for analysis methods and tools, a unified pipeline for RNA-seq data analysis is
always necessary for a laboratory. Given the update of new methods and tools, I
summarized my customized analysis codes to generate an updated pipeline for RNA-seq
data analysis. During aging, gene mutations accumulate, and hormone regulation is
disrupted, which may exacerbate age-related diseases. Therefore, we generated a dataset
from mice with a gene mutation or not and under different hormone treatments to study
the effects of two factors, i.e., hormone and gene mutation, on the transcriptome. Based
on the Nextflow nf-core rnaseq pipeline, this project established this pipeline consisting
of three stages: (1) upstream analysis containing quality control of fastq files before and
after trimming, trimming, alignment, and quantification; (2) midstream analysis
containing count normalization, differentially expressed genes analysis, and visualization
via boxplot, PCA, t-SNE, sample distance heatmap, MA plot, volcano plot, and gene
expression heatmap; and (3) downstream analysis containing functional enrichments of
KEGG pathways and GO terms. Results showed distinct effects of the single factor as
well as interactive effects of the two factors. Codes are also provided for readers who
want to customize their analysis pipeline adapted from this pipeline easily.

Introduction

In the field of modern biological studies, omics are widely used, and thus high-
throughput data are generated every day in need of customized analysis. There are many
different options for analysis methods and tools. They can be classified into two major
types: graphical user interface and command line interface. The former can be divided
into website applications and local computer applications; the latter can be divided into
programs written in different programming languages, such as Bash, R, Python, Perl,
Groovy, etc.

The graphical user interface is convenient for a broad range of scientists who want to
make full use of omics but don't have programming skills to analyze high-throughput
data, whereas the command line interface is more flexible in customizing analysis and
helps save time in repeated procedures. Website applications are usually updated more
frequently than local computer applications, so website applications often provide access
to the latest version of databases, but they may be unstable. In contrast, local computer
applications are more stable and can be used to reproduce results better than website
applications. Partek Flow is a representative website application with a graphical user
interface, and it provides convenience in omics data analysis, particularly useful in
single-cell RNA-seq data analysis[1]. JMP and GraphPad Prism are two well-used local
computer applications with graphical user interfaces with statistical functions as well[2].

Despite the advantages and convenience of the graphical user interface, professional
bioinformaticians prefer the command line interface because of its more powerful
functions that can also be extendible and scalable. For example, fastq files of a larger
number of samples are usually analyzed in the Linux system, because the Linux system
can be used to process high-throughput data in parallel and fast[3]. R and Python are
more and more popular because both are open-sourced and free[4]. A lot of R packages
and Python libraries are available and provide conveniences for bioinformatics analysis.
89

In addition, there are some tools invented especially for building pipelines, such as
Nextflow[5], Snakemake[6], WDL and Cromwell[7], etc. For example, Nextflow is well-
used, because it enables scalable and reproducible scientific workflows and allows the
adaptation of pipelines written in the most common scripting languages. In addition,
Nextflow has a very active user community which released many curated nf-core
pipelines (https://nf-co.re/)[8] that can be modified for customized use.
96

Given a typical pipeline for RNA sequencing (RNA-seq) data analysis consists of
multiple steps, this project divided it into three stages: (1) upstream data process; (2)
midstream visualization of count matrix; and (3) downstream functional analysis.
Different tools have different advantages at different stages and different sets of data
require customized analysis, so the combination of different tools is a better choice in a
practical project.
103

104 Because of the advantages of different tools, the combination of various tools allows us
105 to customize our bioinformatics analysis flexibly[9]. My pipeline was built by the
106 combination of Nextflow nf-core rnaseq pipeline and R with many R packages.
107

Aging is a heavy burden to the modern society. The recent review proposed ten aspects of
biomarkers of aging, including epigenetic changes, genetic instability, telomere
shortening, nuclear body disorders, cell cycle arrest, mitochondrial malfunction,
proteostatic stress, metabolic alterations, signaling pathway rerouting, and senescence-
associated secretory phenotype (SASP)[10]. In the aspect of genetic instability, mutations
that are caused by genomic instability and impaired DNA repair exhibit an age-related
increase in a tissue-specific manner[11, 12]. In addition, the endocrine and exocrine in
multiple organs are closely related to aging[13]. For example, during aging, gene
mutations are accumulated, and hormone regulation is disrupted, which may exacerbate
age-related diseases in return. I applied this pipeline to our in-house dataset that was
generated from mice with a gene mutation or not and under different hormone treatments.
My results showed distinct effects of a single factor as well as interactive effects of the
two factors, i.e., hormone and gene mutation, on mouse transcriptome.
121

122 Tools

123 Linux system
124 Wynton HPC (https://wynton.ucsf.edu/hpc/index.html) - UCSF Research Computing at
125 Scale, based upon the CentOS 7.

Pipeline tool
The nf-core/rnaseq pipeline (https://nf-co.re/rnaseq/3.10.1)[8], based upon Nextflow (https://www.nextflow.io/)[5].

R
R version: 4.1.3 or 4.2.2
RStudio version: 2023.09.0 Build 463
R packages versions:

```
1.  package.version("dplyr")   # "1.1.0"[14]
2.  package.version("tidyr")   # "1.3.0"[14]
3.  package.version("DESeq2")   # "1.34.0"[15]
4.  package.version("tibble")   # "3.1.8"[14]
5.  package.version("ggplot2")   # "3.4.1"[14]
6.  package.version("RColorBrewer")   # "1.1-3"
7.  package.version("pheatmap")   # "1.0.12"
8.  package.version("Rtsne")   # "0.16"[16, 17]
9.  package.version("readr")   # "2.1.4"[14]
10. package.version("clusterProfiler")   # "4.2.2"[18]
11. package.version("org.Mm.eg.db")   # "3.14.0"
12. package.version("EnhancedVolcano")   # "1.12.0"
```

Dataset
In this project, our in-house RNA-seq dataset was used as a demo. Sequencing type: SE. Library Kit: Nugen Universal Plus. Machine: HiSeq4000. Because our in-house RNA-seq dataset is unpublished and the application of this pipeline is not restricted to this dataset, the detailed meta information is hidden. In brief, this dataset was obtained from mice with a gene mutation (mut) and their wild-type littermates (con), both of whom received treatment of two hormones singly (E2, P4) or combinedly (E2P4) or placebo (Plac). In total, this dataset contains eight groups of samples: Plac_con, Plac_mut, E2_con, E2_mut, P4_con, P4_mut, E2P4_con, and E2P4_mut. This project did not intend to describe the gene mutation within this dataset or to explain the definition of different hormone treatments explicitly. When this pipeline is applied in other projects, *mut* can represent any other gene mutation, and *E2* or *P4* can represent any other internal or external stimuli or disease states.

Workflow

164
165 Figure 1. Workflow of RNA-seq data analysis. Upstream analysis of fastq files via
166 Nextflow, midstream analysis of count matrix and differentially expressed genes in R,
167 and downstream analysis of functional enrichment.
168
169
Based on the Nextflow nf-core rnaseq pipeline, this project established this pipeline
(Figure 1) consisting of three stages: (1) upstream analysis containing quality control of
fastq files before and after trimming, trimming, alignment, and quantification; (2)
midstream analysis containing count normalization, boxplot, PCA, t-SNE, sample
distance heatmap, differentially expressed genes analysis, MA plot, volcano plot, and
gene expression heatmap; and (3) downstream analysis containing functional enrichments
of KEGG pathways and GO terms.
177

Upstream analysis with Bash and Nextflow

178
179 1. Create a conda environment.
180   The virtual environment technique is an ideal way to manage systems and software, so
181 I recommended creating a virtual environment via conda
182 (https://docs.conda.io/en/latest/).

```
1. cd ~
2. mkdir 01-Nextflow
3. cd ~/01-Nextflow
4. module load Sali anaconda
5. conda create -n NextFlow-nf-core
6. source activate NextFlow-nf-core
7. python -V      # Python 3.8.10
```

190
191 2. Install Nextflow, nf-core, and rnaseq pipeline.
192   Singularity is a scientific container for the mobility of computing[19], so it is strongly
193 recommended to use a singular image of the nf-core/rnaseq program to reproduce the
194 analysis.

```
1. # install nextflow
2. conda install nextflow -y
3. conda list | grep nextflow   # version: 22.10.6
```

```
4.
5. # install nf-core
6. conda search nf-core
7. conda install nf-core -y
8. conda list | grep nf-core   # 2.7.2
9.
10.# install rnaseq pipeline
11.nf-core download nf-core/rnaseq
12.# select version: 3.10.1
13.# download singularity
```

3. Prepare the reference genome.

Because the data were obtained from mice, the GRCm38 reference genome and its accompanied annotation were downloaded from iGenome (https://support.illumina.com/sequencing/sequencing_software/igenome.html) and used in this project.

```
1. cd ~/01-Nextflow
2. mkdir -p reference_genome/mouse/Ensembl/GRCm38
3. cd reference_genome/mouse/Ensembl/GRCm38
4. nohup aws s3 --no-sign-request --region eu-west-
   1 sync s3://ngi-
   igenomes/igenomes/Mus_musculus/Ensembl/GRCm38/Annotation/Genes
   / . --exclude "*" --include "genes.gtf" &
5. nohup aws s3 --no-sign-request --region eu-west-
   1 sync s3://ngi-
   igenomes/igenomes/Mus_musculus/Ensembl/GRCm38/Sequence/WholeGe
   nomeFasta/ ./ &
```

4. Prepare fastq files.

```
1. cd ~/01-Nextflow
2. mkdir data
```

Copy fastq files that need to be analyzed into the folder ~/01-Nextflow/data.

5. Make a sample sheet.

Download the Python script to make a sample sheet for the subsequent analysis.

```
1. cd ~/01-Nextflow/data
2. wget -L https://raw.githubusercontent.com/nf-
   core/rnaseq/master/bin/fastq_dir_to_samplesheet.py
3. chmod a+x fastq_dir_to_samplesheet.py
4. ./fastq_dir_to_samplesheet.py -
   r1 _R1_001.fastq.gz ~/data/fastq samplesheet.csv
```

6. Customize a config file.

```
1. cd ~/01-Nextflow
2. mkdir analysis
3. mkdir output
4. cd ~/01-Nextflow/analysis
```

```
5. vim nextflow.config
```

Customized analysis includes:

- FastQC – Raw read QC
- TrimGalore – Adapter and quality trimming
- STAR – Alignment
- Salmon – Quantification
- RSeQC – Various RNA-seq QC metrics
- DESeq2 – PCA plot and sample pairwise distance heatmap and dendrogram
- MultiQC – Present QC for raw reads, alignment, read counting, and sample similarity

In addition, in the config file, we specified the paths to the input sample sheet of fastq files to be analyzed, reference genome files, and folder to save the output.

```
1.  // Global default params, used in configs
2.  params {
3.
4.      // Input options
5.      input = '~/data/fastq/samplesheet.csv'
6.
7.      // References
8.      fasta = '~/reference_genome/mouse/Ensembl/GRCm38/genome.fa
   '
9.      gtf = '~/reference_genome/mouse/Ensembl/GRCm38/genes.gtf'
10.     gencode = false
11.     save_reference = true
12.
13.     // QC
14.     skip_bigwig = true
15.     skip_stringtie = true
16.     skip_preseq = true
17.     skip_qualimap = true
18.     deseq2_vst = true
19.
20.     // Boilerplate options
21.     outdir = '~/output'
22.     email = "jiahua.qu@hotmail.com"
23.
24.     // Max resource options
25.     // Defaults only, expecting to be overwritten
26.     max_memory = '500.GB'
27.     max_cpus = 12
28.     max_time = '240.h'
29. }
```

7. Make a bash script.

```
1. cd ~/01-Nextflow/analysis
2. vim my_script.sh
```

In the bash script, we specified: (1) required computation resources including core number, memory, and running time; (2) paths to input files including log file that records progress, Nextflow workflow program, singularity profile, and config file with customized settings.

```
1.  #! /usr/bin/env bash
2.  #
3.  #$ -S /bin/bash
4.  #$ -cwd
5.  #$ -r y
6.  #$ -j y
7.  #$ -pe smp 6
8.  #$ -l mem_free=45G
9.  #$ -l scratch=270G
10. #$ -l h_rt=24:00:00
11.
12. module load Sali anaconda
13. source activate NextFlow-nf-core
14.
15. # set path
16. log=~/01-Nextflow/analysis/my.log
17. workflow=~/01-Nextflow/nf-core-rnaseq-3.10.1/workflow
18. profile=singularity
19. config=~/01-Nextflow/analysis/nextflow.config
20.
21. # run pipeline
22. nextflow -log $log run $workflow -profile $profile -resume -
    c $config
23.
24. conda deactivate
25.
26. [[ -n "$JOB_ID" ]] && qstat -j "$JOB_ID"
```

8. Submit a job to run in the background.

```
1.  qsub my_script.sh
```

9. Output.

The output contains two major parts: (1) star_salmon output including count matrix and metadata, and (2) MultiQC report showing quality control of fastq files before and after trimming (Figure 2).

Figure 2. Screenshot of MultiQC report. The report summarizes quality control results of fastq files before and after each process.

Midstream analysis with R

10. Read in rds object generated in the last step.

```r
1. ### create a folder
2. setwd("~/")
3. if (!file.exists("02-QC")){
4.   dir.create("02-QC")
5. }
6. setwd("~/02-QC")
7.
8. ### read in rds
9. # use the salmon.merged.gene_counts.rds
10.gene_counts <- readRDS("~/01-
   Nextflow/output/star_salmon/salmon.merged.gene_counts.rds")
11.
12.# extract and process count matrix
13.counts <- gene_counts@assays@data$counts
14.# round non-integer to integer for loading into DESeq2
15.counts_round <- round(counts, digits = 0)
16.# remove rows whose values are all zero
17.library(dplyr)
18.counts_round <- counts_round %>%
19.  filter(rowSums(.) > 0)
20.
21.# extract meta_data
22.library(tidyr)
23.meta_data <- data.frame(sample=gene_counts@colData@rownames) %
   >%
```

```
363    24.    separate(sample, into=c("treatment","genotype","num"), sep =
364        "\\.", remove = FALSE) %>%
365    25.    unite(col = "condition", treatment,genotype, remove = FALSE)
366    26.meta_data$condition <- factor(meta_data$condition)
367    27.meta_data$treatment <- factor(meta_data$treatment)
368    28.meta_data$genotype <- factor(meta_data$genotype, levels = c("c
369        on", "mut"))
370    29.saveRDS(meta_data, "meta_data.rds", compress = T)
371
```

11. Generate a dds object with the DESeq2 R package.

```
373    1. library(DESeq2)
374    2. # Load in Salmon output
375    3. dds_new <- DESeqDataSetFromMatrix(countData = counts_round,
376    4.                                      colData = meta_data,
377    5.                                      design= ~ condition)
378    6.
379    7. # Normalization
380    8. dds_new <- estimateSizeFactors(dds_new)
381    9. dds_rlog <- rlog(dds_new)
382    10.dds_vst <- varianceStabilizingTransformation(dds_new)
383    11.assay(dds_new, "rlog") <- assay(dds_rlog)
384    12.assay(dds_new, "vst") <- assay(dds_vst)
385    13.saveRDS(dds_new, "dds_new.rds", compress = T)
386    14.saveRDS(dds_rlog, "dds_rlog.rds", compress = T)
387    15.saveRDS(dds_vst, "dds_vst.rds", compress = T)
388
```

12. Plot to visualize the read counts.

```
390    1. ### create a folder
391    2. setwd("~/02-QC")
392    3. if (!file.exists("QCplots")){
393    4.    dir.create("QCplots")
394    5. }
395    6.
396    7. ### 1. boxplot
397    8. library(DESeq2)
398    9. ## 1.1. counts_vst
399    10.counts_vst <- dds_new@assays@data$vst
400    11.
401    12.library(tibble)
402    13.dat <- counts_vst %>%
403    14.    as.data.frame() %>%
404    15.    rownames_to_column(var="gene") %>%
405    16.    gather(key = "sample", value = "counts_vst", -gene) %>%
406    17.    left_join(meta_data, by="sample")
407    18.
408    19.library(ggplot2)
```

```r
20. p_1 <- ggplot(data=dat,aes(x=sample,y=counts_vst,fill=conditio
    n)) +
21.   geom_boxplot()+
22.   labs(x="Sample",y="VST Normalized Read Counts")+
23.   ggtitle("VST Normalized Read Count by Sample") +
24.   theme(axis.text.x=element_text(angle = 90, vjust = 0.5, hjus
    t = 1))
25. ggsave(filename = "QCplots/boxplot-
    counts_vst.pdf", plot = p_1, width = 10, height = 5)
26.
27. ## 1.2. counts_rlog
28. counts_rlog <- dds_new@assays@data$rlog
29.
30. library(tibble)
31. dat <- counts_rlog %>%
32.   as.data.frame() %>%
33.   rownames_to_column(var="gene") %>%
34.   gather(key = "sample", value = "counts_rlog", -gene) %>%
35.   left_join(meta_data, by="sample")
36.
37. library(ggplot2)
38. p_2 <- ggplot(data=dat,aes(x=sample,y=counts_rlog,fill=conditi
    on)) +
39.   geom_boxplot()+
40.   labs(x="Sample",y="rlog Normalized Read Counts")+
41.   ggtitle("rlog Normalized Read Count by Sample") +
42.   theme(axis.text.x=element_text(angle = 90, vjust = 0.5, hjus
    t = 1))
43. ggsave(filename = "QCplots/boxplot-
    counts_rlog.pdf", plot = p_2, width = 10, height = 5)
44.
45. ### 2. sample correlation heatmap
46. sampleDists <- dist(t(counts_vst))
47. sampleDistMatrix <- as.matrix(sampleDists)
48.
49. library(RColorBrewer)
50. colors <- colorRampPalette( rev(brewer.pal(9, "Oranges")) )(25
    5)
51. mydata_col = data.frame(condition=meta_data$condition, row.nam
    es = meta_data$sample)
52.
53. library(pheatmap)
54. p_3 <- pheatmap(
55.   sampleDistMatrix,
56.   clustering_distance_rows=sampleDists,
57.   clustering_distance_cols=sampleDists,
58.   col=colors,
59.   annotation_col = mydata_col,
```

```r
60.   main="Euclidean distance between samples"
61.)
62.
63.### make my customized function to save heatmap
64.save_pheatmap_pdf <- function(x, filename, width, height) {
65.   stopifnot(!missing(x))
66.   stopifnot(!missing(filename))
67.   pdf(filename, width=width, height=height)
68.   grid::grid.newpage()
69.   grid::grid.draw(x$gtable)
70.   dev.off()
71.}
72.save_pheatmap_pdf(p_3, "QCplots/sample_heatmap.pdf", 7, 6.5)
73.
74.### 3. gene expression heatmap of top 1000 variable genes
75.counts_vst_var <- as.data.frame(counts_vst)
76.counts_vst_var$var <- apply(counts_vst,1,var)
77.counts_vst_var <- counts_vst_var %>%
78.saveRDS(counts_vst_var, "counts_vst_var.rds", compress=T)
79.counts_vst_var <- counts_vst_var %>%
80.   slice(1:1000) %>%
81.   as.matrix()
82.
83.p_4 <- pheatmap(counts_vst_var[,1:24],
84.            scale="row",
85.            color = colorRampPalette(c("darkblue", "white",
   "darkred"))(1000),
86.            annotation_col = mydata_col,
87.            main="Gene Expression (VST) of Top 1000 Variable
   Genes",
88.            show_rownames = F)
89.save_pheatmap_pdf(p_4, "QCplots/gene_heatmap.pdf", 7, 6.5)
90.
91.### 4. PCA plots
92.# make my customized function to plot PCA
93.plotPCA_vst <- function (object, assay, ntop = 1000) {
94.   rv <- rowVars(assay(object, assay))
95.   select <- order(rv, decreasing = TRUE)[seq_len(min(ntop, len
   gth(rv)))]
96.   pca <- prcomp(t(assay(object, assay)[select, ]), center=TRUE
   , scale=FALSE)
97.   percentVar <- pca$sdev^2/sum(pca$sdev^2)
98.   df <- cbind( as.data.frame(colData(object)), pca$x)
99.   # order points so extreme samples are more likely to get lab
   el
100.        ord <- order(abs(rank(df$PC1)-
   median(df$PC1)), abs(rank(df$PC2)-median(df$PC2)))
101.        df <- df[ord,]
```

```
505    102.          attr(df, "percentVar") <- data.frame(PC=seq(along=perc
506        entVar), percentVar=100*percentVar)
507    103.          return(df)
508    104.      }
509    105.
510    106.      pca.data <- plotPCA_vst(dds_new, assay="vst", ntop=1000)
511    107.      saveRDS(pca.data, "pca.data.rds", compress = T)
512    108.
513    109.      for (i in c(1:4)) {
514    110.          for (j in c((i+1):5)) {
515    111.              percentVar <- round(attr(pca.data, "percentVar")$per
516        centVar)
517    112.              p <- ggplot(pca.data, aes_string(x=paste0("PC",i), y
518        =paste0("PC",j), color="condition")) +
519    113.                  geom_point(size=3) +
520    114.                  xlab(paste0("PC",i,": ",percentVar[i],"% variance"
521        )) +
522    115.                  ylab(paste0("PC",j,": ",percentVar[j],"% variance"
523        )) +
524    116.                  theme_bw()
525    117.              ggsave(filename = paste0("QCplots/PCAplot.","PC",i,"
526        vs","PC",j,".pdf"), plot = p, width=6, height=5)
527    118.          }
528    119.      }
529    120.
530    121.      ### 5. t-SNE plots
531    122.      library(Rtsne)
532    123.      # make my customized function to plot t-SNE
533    124.      plottsne_vst <- function (object, assay, perpl, ntop = 1
534        000) {
535    125.          rv <- rowVars(assay(object, assay))
536    126.          select <- order(rv, decreasing = TRUE)[seq_len(min(nto
537        p, length(rv)))]
538    127.          set.seed(123)
539    128.          tsne <- Rtsne(t(assay(object, assay)[select, ]), perpl
540        exity=perpl)
541    129.          df <- as.data.frame(tsne$Y)
542    130.          names(df) <- c("Dimention1","Dimention2")
543    131.          df <- cbind(df, meta_data)
544    132.          return(df)
545    133.      }
546    134.
547    135.      for (i in 1:6) {
548    136.          tsne.data <- plottsne_vst(dds_new, assay="vst", perpl=
549        i, ntop=1000)
550    137.          saveRDS(tsne.data, paste0("tsne.data-
551        perplexity_",i,".rds"), compress = T)
552    138.
```

```
139.        p <- ggplot(tsne.data, aes_string(x="Dimention1", y="D
   imention2", color="condition")) +
140.            geom_point(size=3) +
141.            xlab("Dimention 1") +
142.            ylab("Dimention 2") +
143.            theme_bw()
144.        ggsave(filename = paste0("QCplots/tSNEplot-
   perplexity_",i,".pdf"), plot = p, width=6, height=5)
145.    }
```

13. Visualization results of read counts.

The raw data in the count matrix were normalized via two methods, rlog and vst, and were displayed in two box plots (Figure 3 and 4).

Figure 3. Box plot of read counts normalized by the rlog method. Samples in different groups are in different colors. The X-axis represents each sample. The Y-axis represents read counts normalized by the rlog method.

574
575 Figure 4. Box plot of read counts normalized by the vst method. Samples in different
576 groups are in different colors. The X-axis represents each sample. The Y-axis represents
577 read counts normalized by the vst method.
578
579

580   To observe the correlation among samples, the distance between each pair of samples
581 was calculated and the Euclidean distance was visualized in the heatmap (Figure 5).
582

583
584 Figure 5. Heatmap of Euclidean distance between samples. Samples in different groups
585 are in different colors. The color of the crossing square between two samples indicates
586 the distance between those two samples. The darker the crossing square is, the smaller the
587 distance between those two samples is.
588
589
590 In addition to the correlation at the sample level, the correlation across all samples was
591 also calculated and visualized at the gene expression level (Figure 6).
592

593
594　Figure 6. Heatmap of gene expression across samples. Samples in different groups are in
595　different colors. The color of each gene indicates the scaled level of gene expression
596　across samples. The redder indicates the higher level while the bluer indicates the lower
597　level.
598
599

To further observe the distribution of samples, the dimension of read counts was reduced
via principal component analysis (PCA) and visualized the results within combinations of
each two of the first five principal components, i.e., PC1 and PC2, PC1 and PC3, PC1
and PC4, PC1 and PC5, PC2 and PC3, PC2 and PC4, PC2 and PC5, PC3 and PC4, PC3
and PC5, PC4 and PC5. The first two PCA plots were displayed here as examples (Figure
7A and 7B). In addition, the read counts were projected into the t-distributed Stochastic
Neighbor Embedding (t-SNE) projection with a perplexity value from 1 to 6. The first
and the last t-SNE plots were displayed here as examples (Figure 7C and 7C). Both PCA
and t-SNE plots demonstrated the separation of samples by genotype and hormone
treatment. Particularly, the E2 treatment affected gene expression the most significantly,
and the P4 treatment regulated gene expression in a strikingly different way from the E2
treatment, while the inner group heterogeneity could not be ignored. The correlation

observed in PCA and t-SNE plots was consistent with that in heatmaps at the sample distance level (Figure 5) and gene expression level (Figure 6).

Figure 7. Sample distribution in projections of reduced dimension. A-B. PCA plots with PC1 and PC2 (A), and PC1 and PC3 (B). C-D. t-SNE plots with perplexity = 1 (C) and perplexity = 6 (D).

14. Convert gene ID from gene symbol to ENTREZID.

The default gene IDs in the STAR output are gene symbols that are intuitive and convenient to read and understand. However, ENTREZID is preferred by many advanced bioinformatic software[18] because it is unique and more accurate than gene symbols. Therefore, I converted gene IDs from gene symbols to ENTREZIDs, which were required in subsequent analyses.

```
1. ### create folders
2. setwd("~/")
3. if (!file.exists("03-DE")){
```

```
630   4.    dir.create("03-DE")
631   5. }
632   6. setwd("~/03-DE")
633   7.
634   8. ### read in gene information obtained from Nextflow
635   9. library(readr)
636  10. bg_ID <- read_delim("~/01-
637      Nextflow/output/star_salmon/salmon_tx2gene.tsv",
638  11.                     delim = "\t", escape_double = FALSE,
639  12.                     col_names = FALSE, trim_ws = TRUE)
640  13. names(bg_ID) <- c("transcript", "gene", "gene_name")
641  14. bg_ID <- bg_ID[,-1] %>% unique()
642  15.
643  16. library(clusterProfiler)
644  17. library(org.Mm.eg.db)
645  18. #keytypes(org.Mm.eg.db)
646  19. bg_ENTREZID <- bitr(bg_ID$gene_name,
647  20.                     fromType = "SYMBOL",
648  21.                     toType = "ENTREZID",
649  22.                     OrgDb = "org.Mm.eg.db")
650  23. bg_ID <- left_join(bg_ID, bg_ENTREZID, by=c("gene_name"="SYMBO
651      L"))
652  24. saveRDS(bg_ID, "bg_ID.rds", compress = T)
```

15. Differentially expressed gene (DEG) analysis.

In this project, we aimed to compare the difference between mutant mice (mut) and their wild-type littermates (con) in each condition (hormone treatment or placebo) separately, but the same analysis codes can be used to compare every two groups of samples with minor adjustments.

```
659   1. ### create folders
660   2. setwd("~/03-DE")
661   3.
662   4. if (!file.exists("DEfiles")){
663   5.   dir.create("DEfiles")
664   6. }
665   7.
666   8. if (!file.exists("MAplots")){
667   9.   dir.create("MAplots")
668  10. }
669  11.
670  12. if (!file.exists("Volcanoplots")){
671  13.   dir.create("Volcanoplots")
672  14. }
673  15.
674  16. if (!file.exists("Heatmaps")){
675  17.   dir.create("Heatmaps")
676  18. }
```

```
19.
20. ### generate FC and FDR via DESeq2
21. library(DESeq2)
22. library(EnhancedVolcano)
23. # read in dds object and metadata
24. dds_new <- readRDS("~/02-QC/dds_new.rds")
25. meta_data <- readRDS("~/02-QC/meta_data.rds")
26.
27. ### run DESeq to get result objects in loop
28. library(ggplot2)
29. library(readr)
30. library(tibble)
31. library(pheatmap)
32. counts_vst <- dds_new@assays@data$vst
33. dds_new_res <- DESeq(dds_new)
34. saveRDS(dds_new_res, "dds_new_res.rds", compress = T)
35.
36. for (i in levels(meta_data$treatment)) {
37.
38.   ### 1. DE results
39.   sampleA <- paste(i, "con", sep = "_")
40.   sampleB <- paste(i, "mut", sep = "_")
41.   condition <- "condition"
42.   contrastV <- c(condition, sampleA, sampleB)
43.   res <- results(dds_new_res,  contrast=contrastV)
44.   saveRDS(res, paste0("DEfiles/DE-
     ",sampleB,"vs",sampleA,".rds"), compress = T)
45.
46.   # join gene_name
47.   res_df <- as.data.frame(res)
48.   res_symbol <- res_df %>%
49.     as.data.frame() %>%
50.     rownames_to_column(var="gene") %>%
51.     left_join(bg_ID, by="gene")
52.
53.   ### 2. MA plots
54.   pdf(file = paste0("MAplots/MAplot-
     ",sampleB,"vs",sampleA,".pdf"),
55.       width=7, height=5)
56.   MAplot <- plotMA(object=res, alpha=0.05,
57.                    main=paste0(sampleB,"vs",sampleA),
58.                    colNonSig="black",
59.                    colSig="red",
60.                    colLine="blue")
61.   dev.off()
62.
63.   ### 3. volcano plots
64.   vol <- EnhancedVolcano(res_symbol,
```

```
65.                 lab = NA,
66.                 x = 'log2FoldChange',
67.                 y = 'padj',
68.                 ylab = bquote(~-Log[10] ~ italic(FDR)),
69.                 pCutoff = 0.05,
70.                 FCcutoff = 2,
71.                 title = paste0(sampleB,"vs",sampleA),
72.                 legendLabels=c('Not DE &\nabsolute FC < 2',
73.                                'Not DE &\nabsolute FC > 2',
74.                                'FDR < 0.05 &\nabsolute FC < 2',
75.                                'FDR < 0.05 &\nabsolute FC > 2'),
76.                 legendPosition = 'right')
77.  ggsave(filename = paste0("Volcanoplots/Volcanoplot-",sampleB,"vs",sampleA,".pdf"), plot=vol, width = 7, height = 7)
78.
79.  vol_lab <- EnhancedVolcano(res_symbol,
80.                             lab = res_symbol$gene_name,
81.                             x = 'log2FoldChange',
82.                             y = 'padj',
83.                             ylab = bquote(~-Log[10] ~ italic(FDR)),
84.                             pCutoff = 0.05,
85.                             FCcutoff = 2,
86.                             title = paste0(sampleB,"vs",sampleA),
87.                             legendLabels=c('Not DE &\nabsolute FC < 2',
88.                                            'Not DE &\nabsolute FC > 2',
89.                                            'FDR < 0.05 &\nabsolute FC < 2',
90.                                            'FDR < 0.05 &\nabsolute FC > 2'),
91.                             legendPosition = 'right')
92.  ggsave(filename = paste0("Volcanoplots/Volcanoplot_gene_name-",sampleB,"vs",sampleA,".pdf"), plot=vol_lab, width = 7, height = 7)
93.
94.  ### 4. heatmaps
95.  res_symbol <- res_symbol %>%
96.    mutate(change=case_when(padj < 0.05 ~ "DE",
97.                            TRUE ~ "Not")) %>%
98.    mutate(direction=case_when(change == "DE" & log2FoldChange > 0 ~ "Up",
```

```
99.                                     change == "DE" & log2FoldChange
    < 0 ~ "Down",
100.                                        TRUE ~ "Not"))
101.        write.csv(res_symbol, paste0("DEfiles/DE-
    ",sampleB,"vs",sampleA,".csv"))
102.
103.        counts_vst_DE <- counts_vst[res_symbol$change=="DE",]
104.        mydata_col <- data.frame(condition=meta_data$condition
    , row.names = meta_data$sample)
105.        heat_DE_1 <- pheatmap(counts_vst_DE,
106.                               scale="row",
107.                               color = colorRampPalette(c("dark
    blue", "white", "darkred"))(1000),
108.                               annotation_col = mydata_col,
109.                               main=paste0(sampleB,"vs",sampleA
    ," FDR < 0.05"),
110.                               show_rownames = F)
111.        save_pheatmap_pdf(heat_DE_1, paste0("Heatmaps/Heatmap-
    ",sampleB,"vs",sampleA,".pdf"), 7, 6.5)
112.
113.        # row names
114.        tree_row <- data.frame(gene = rownames(counts_vst_DE[h
    eat_DE_1$tree_row[["order"]],])) %>%
115.          left_join(bg_ID, by="gene")
116.        saveRDS(tree_row, paste0("Heatmaps/Heatmap-
    ",sampleB,"vs",sampleA,".rds"), compress = T)
117.        write.csv(tree_row, paste0("Heatmaps/Heatmap-
    ",sampleB,"vs",sampleA,".csv"))
118.
119.        meta_data_2 <- meta_data[meta_data$treatment==i,]
120.        mydata_col_2 = data.frame(condition=meta_data_2$condit
    ion, row.names = meta_data_2$sample)
121.        counts_vst_DE_2 <- counts_vst_DE[,meta_data_2[,1]]
122.        heat_DE_2 <- pheatmap(counts_vst_DE_2,
123.                               scale="row",
124.                               color = colorRampPalette(c("dark
    blue", "white", "darkred"))(1000),
125.                               annotation_col = mydata_col_2,
126.                               main=paste0(sampleB,"vs",sampleA
    ," FDR < 0.05"),
127.                               show_rownames = F)
128.        save_pheatmap_pdf(heat_DE_2, paste0("Heatmaps/Heatmap2
    -",sampleB,"vs",sampleA,".pdf"), 7, 6.5)
129.
130.        # row names
131.        tree_row_2 <- data.frame(gene = rownames(counts_vst_DE
    [heat_DE_2$tree_row[["order"]],])) %>%
132.          left_join(bg_ID, by="gene")
```

```
821    133.        saveRDS(tree_row_2, paste0("Heatmaps/Heatmap2-
822        ",sampleB,"vs",sampleA,".rds"), compress = T)
823    134.        write.csv(tree_row_2, paste0("Heatmaps/Heatmap2-
824        ",sampleB,"vs",sampleA,".csv"))
825    135.      }
```

826
16. Visualization results of DEG analysis.
Four sub-folders, i.e., Plac_mutvPlac_con, E2_mutvsE2_con, P4_mutvsP4_con, and
E2P4_mutvsE2P4_con, were created inside the folder of ~/03-DE/DEfiles containing
results of DEG analysis. In addition, the results were visualized in various plots that were
saved into sub-folders.
MA plots suggested that the fold changes of genes between mut and con were
distributed evenly and independent of mean values of normalized counts (Figure 8).
834

835
836   Figure 8. MA plots of DEG analysis results. X-axis represents the mean values of vst
837   normalized counts. The Y-axis represents the log-transformed fold change in mut vs. con
838   in each condition of hormone treatment.
839
840

841   In addition to MA plots, volcano plots were also generated to observe the significant
842   changes between mut and con. Because the above analyses suggested that E2 treatment
843   had the most obvious effect on mut vs. con, the volcano plots of DEGs in mut vs. con
844   under the E2 treatment were displayed here as examples (Figure 9). The panel on the
845   right also labeled symbols of the most significantly changed genes (Figure 9B).
846

847
848 Figure 9. Volcano plots of DEGs in mut vs. con under the E2 treatment. The X-axis
849 represents the log2 transformed fold change in mut vs. con. The Y-axis represents the
850 minus log10 transformed FDR. Each dot represents one gene and is colored
851 corresponding to the cutoffs shown in the legend.
852
853
854 To observe the gene expression across samples, heatmaps were also generated for two
855 groups of samples (Figure 10A) and all groups of samples (Figure 10B). The heatmap
856 showed the two distinct clusters of genes that were upregulated or downregulated in
857 E2_mut vs. E2_con (Figure 10A).
858

859
860 Figure 10. Heatmap of expression of significantly changed genes in mut vs. con under the
861 E2 treatment. A. Heatmaps of comparison between two groups of samples. B. Heatmap
862 across all samples. Samples in different groups are in different colors. The color of each
863 gene indicates the scaled level of gene expression across samples. The redder indicates
864 the higher level while the bluer indicates the lower level.

Downstream analysis with R

17. Functional analyses including Gene Ontology (GO) – Biological Process (BP),
Cellular Component (CC), and Molecular Function (MF), and KEGG analyses.

```
1. ### Create folders
2. setwd("~")
3. if (!file.exists("04-Pathway")){
4.   dir.create("04-Pathway")
5. }
6. setwd("~/04-Pathway")
7.
8. if (!file.exists("Pathways_tables")){
9.   dir.create("Pathways_tables")
10.}
11.
12.if (!file.exists("Pathways_figures")){
13.  dir.create("Pathways_figures")
14.}
15.
16.library(clusterProfiler)
17.library(org.Mm.eg.db)
18.library(ggplot2)
19.library(readr)
20.
21.bg_ID <- readRDS("../03-DE/bg_ID.rds")
22.bg <- bg_ID$ENTREZID
23.meta_data <- readRDS("../02-QC/meta_data.rds")
24.treatment <- levels(meta_data$treatment)
25.
26.### Loops
27.for (i in treatment) {
28.   sampleA <- paste(i, "con", sep = "_")
29.   sampleB <- paste(i, "mut", sep = "_")
30.   # Read in DE table
31.   res_symbol <- read.csv(paste0("../03-DE/DEfiles/DE-
       ",sampleB,"vs",sampleA,".csv"))
32.
33.   ## Inner loop for Up or Down
34.   for (j in c("Up", "Down")){
35.     DEG <- res_symbol[res_symbol$direction == j,]$ENTREZID %>%
36.       as.character()
37.
38.     # KEGG
39.     KEGG <- enrichKEGG(gene = DEG,
40.                         universe = bg,
```

```
41.                    organism ='mmu',
42.                    pvalueCutoff = 0.1,
43.                    qvalueCutoff = 0.1,
44.                    use_internal_data =FALSE)
45.   KEGG <- setReadable(KEGG, OrgDb = org.Mm.eg.db, keyType="E
   NTREZID")
46.   write_csv(as.data.frame(KEGG@result),paste0("Pathways_tabl
   es/",sampleB,"vs",sampleA,".",j,".KEGG.csv"))
47.   saveRDS(KEGG,paste0("Pathways_tables/",sampleB,"vs",sample
   A,".",j,".KEGG.rds"),compress=T)
48.   dot_KEGG <- dotplot(KEGG)
49.   ggsave(filename = paste0("Pathways_figures/",sampleB,"vs",
   sampleA,".",j,".KEGG.pdf"), plot = dot_KEGG, width = 7, height
    = 7)
50.
51.   # GO sub-categories
52.   for (GO in c("CC", "MF", "BP")) {
53.     GO_enrich <- enrichGO(gene = DEG,
54.                      universe = bg,
55.                      OrgDb = "org.Mm.eg.db",
56.                      keyType = "ENTREZID",
57.                      ont = GO,
58.                      pvalueCutoff  = 0.1,
59.                      pAdjustMethod = "BH",
60.                      qvalueCutoff  = 0.1,
61.                      readable=T)
62.     GO_enrich <- simplify(GO_enrich,cutoff=0.7,
63.                      by="p.adjust",
64.                      select_fun=min,
65.                      measure = "Wang")
66.     write_csv(as.data.frame(GO_enrich@result),paste0("Pathwa
   ys_tables/",sampleB,"vs",sampleA,".",j,".",GO,".csv"))
67.     saveRDS(GO_enrich,paste0("Pathways_tables/",sampleB,"vs"
   ,sampleA,".",j,".",GO,".rds"),compress=T)
68.     dot_GO <- dotplot(GO_enrich)
69.     ggsave(filename = paste0("Pathways_figures/",sampleB,"vs
   ",sampleA,".",j,".",GO,".pdf"), plot = dot_GO, width = 7, heig
   ht = 7)
70.       }
71.   }
72.}
```

18. Visualization of results of functional enrichment analysis.

DEGs were divided into two parts, i.e., upregulated (Up) and downregulated (Down) genes in mut vs. con under individual hormone treatment. The two parts were separately loaded into the clusterProfiler R package for functional enrichment of KEGG pathways and GO terms including BP, MF, and CC sub-categories. Here, the bubble charts of

958　KEEG pathways and GO terms enriched from DEGs in mut vs. con under the E2
959　treatment were displayed as examples (Figure 11).
960

961
962

963
964

965
966

967
Figure 11. Functional enrichments. IDs of significantly upregulated and downregulated
genes in E2_mut vs. E2_con were converted into the ENTREZ IDs and imported into the
clusterProfiler R package to conduct functional enrichment. The top ten terms with
adjusted p-values < 0.05 were displayed in bubble charts. Four categories were KEGG
pathways from the KEGG pathway database (A and B), GO_BP terms from the
Biological Process (Gene Ontology) database (C and D), GO_MF terms from Molecular
Function (Gene Ontology) database (E and F), and GO_CC from Cellular Component
(Gene Ontology) database (G and H). Color represents significance: the redder, the more
significant.

977
978

Discussion

This pipeline started from processing raw fastq files obtained from the Illumina HiSeq4000 sequencing machine, aligned reads to the Ensembl/GRCm38 reference genome via STAR, quantified to count matrix via Salmon, visualized normalized counts, analyzed and visualized DEGs, enriched and visualized KEGG pathways and GO terms to deduce changed functions in R.

This pipeline combined the advantages of Nextflow and R from upstream to midstream, and to downstream analyses. In the upstream analysis, different reference genomes can be downloaded from the igenomes repository (https://support.illumina.com/sequencing/sequencing_software/igenome.html) provided by Illumina. In addition to STAR and Salmon, other alignment and quantification software can be selected as a substitution. Addition parameters can be adjusted in the Nextflow config file. Therefore, this pipeline that was built based on Nextflow can be extended to analyze RNA-seq data generated from other species and with different qualities.

In the midstream and downstream analyses, this pipeline took advantage of R in statistics and visualization. In addition to the pairs of comparisons that were demonstrated here as examples, samples from any two groups can be compared via DESeq2 by this pipeline. I am considering expanding this pipeline to provide other options such as EdgeR and Limma which are also widely used. Of note, this pipeline inherited one of the best advantages of R, i.e., the customized and fast visualization. I provided codes to observe the data and results in many most popular plots. The generated figures can be combined and trimmed flexibly. All figures can be exported to PDF files which are editable and can be transformed into any other formats in graph edition software like Illustrator.

In summary, this pipeline provides an easy and convenient way to analyze RNA-seq data and reproduce bioinformatics analysis. Particularly, the enriched KEGG pathways and GO terms are very useful in the interpretation of biological functions and the discovery of regulatory mechanisms. The results demonstrated that age-associated alterations of mutation and hormones reprogram the transcriptome significantly. In addition to the age-related factors studied in this project, this pipeline can also be broadly applied in other RNA-seq data analyses in the future.

References

1.   Qu, J.H., et al., *Characterization of diverse populations of sinoatrial node cells and their proliferation potential at single nucleus resolution.* Heliyon, 2023. **9**(1): p. e12708.
2.   Qu, J.H., et al., *Transcriptome of left ventricle and sinoatrial node in young and old C57 mice.* Fortune Journal of Health Sciences, 2023. **6**: p. 332 - 356.
3.   Qu, J.H., et al., *Proteomic Landscape and Deduced Functions of the Cardiac 14-3-3 Protein Interactome.* Cells, 2022. **11**(21).

1024   4.   Agrimi, J., et al., *Cardiac AC8 Over-Expression Increases Locomotion by*
1025   *Altering Heart-Brain Communication.* JACC Clin Electrophysiol, 2023.
1026   5.   Di Tommaso, P., et al., *Nextflow enables reproducible computational workflows.*
1027   Nat Biotechnol, 2017. **35**(4): p. 316-319.
1028   6.   Köster, J. and S. Rahmann, *Snakemake-a scalable bioinformatics workflow*
1029   *engine.* Bioinformatics, 2018. **34**(20): p. 3600.
1030   7.   Voss, K., G. Van der Auwera, and J. Gentry, *Full-stack genomics pipelining with*
1031   *GATK4 + WDL + Cromwell* F1000Research, 2017. **6**: p. 1381.
1032   8.   Ewels, P.A., et al., *The nf-core framework for community-curated bioinformatics*
1033   *pipelines.* Nat Biotechnol, 2020. **38**(3): p. 276-278.
1034   9.   Tarasov, K.V., et al., *A remarkable adaptive paradigm of heart performance and*
1035   *protection emerges in response to marked cardiac-specific overexpression of*
1036   *ADCY8.* Elife, 2022. **11**.
1037   10.   Bao, H., et al., *Biomarkers of aging.* Sci China Life Sci, 2023. **66**(5): p. 893-1066.
1038   11.   Dollé, M.E., et al., *Rapid accumulation of genome rearrangements in liver but not*
1039   *in brain of old mice.* Nat Genet, 1997. **17**(4): p. 431-4.
1040   12.   Stuart, G.R., et al., *Mutation frequency and specificity with age in liver, bladder*
1041   *and brain of lacI transgenic mice.* Genetics, 2000. **154**(3): p. 1291-300.
1042   13.   Broekmans, F.J., M.R. Soules, and B.C. Fauser, *Ovarian aging: mechanisms and*
1043   *clinical consequences.* Endocr Rev, 2009. **30**(5): p. 465-93.
1044   14.   Wickham, H., et al., *Welcome to the Tidyverse.* Journal of Open Source Software,
1045   2019. **4**(43).
1046   15.   Love, M.I., W. Huber, and S. Anders, *Moderated estimation of fold change and*
1047   *dispersion for RNA-seq data with DESeq2.* Genome Biol, 2014. **15**(12): p. 550.
1048   16.   Van der Maaten, L. and G. Hinton, *Visualizing data using t-SNE.* Journal of
1049   machine learning research, 2008. **9**(11).
1050   17.   Van Der Maaten, L., *Accelerating t-SNE using tree-based algorithms.* The journal
1051   of machine learning research, 2014. **15**(1): p. 3221-3245.
1052   18.   Wu, T., et al., *clusterProfiler 4.0: A universal enrichment tool for interpreting*
1053   *omics data.* Innovation (Camb), 2021. **2**(3): p. 100141.
1054   19.   Kurtzer, G.M., V. Sochat, and M.W. Bauer, *Singularity: Scientific containers for*
1055   *mobility of compute.* PLoS One, 2017. **12**(5): p. e0177459.
1056