Distinct neural mechanisms underlying perceptual and attentional impairments of conscious access

Samuel Noorman[1,2,*], Timo Stein[1,2], Johannes J. Fahrenfort[1,2,3,**], Simon van Gaal[1,2,**]

[1]Department of Psychology, University of Amsterdam, Amsterdam, The Netherlands
[2]Amsterdam Brain and Cognition, University of Amsterdam, Amsterdam, The Netherlands
[3]Department of Applied and Experimental Psychology, Vrije Universiteit Amsterdam, Amsterdam, The Netherlands
[*]Correspondence: sgnoorman@gmail.com
[**]Shared senior authorship

This research was supported by a grant from the H2020 European Research Council (ERC STG 715605, SVG).

Abstract

This study investigates failures in conscious access resulting from either weak sensory input (perceptual blindness) or unattended input (attentional blindness). Participants viewed a Kanizsa stimulus with or without an illusory triangle within a rapid serial visual presentation of distractor stimuli. We designed a novel Kanizsa stimulus that contained additional ancillary features of different complexity (local contrast and collinearity) that were independently manipulated. Perceptual performance on the Kanizsa stimulus (presence vs. absence of an illusion) was equated between the perceptual (masking) and attentional (attentional blink) manipulation to circumvent common confounds related to conditional differences in task performance. We trained and tested classifiers on electroencephalogram (EEG) data to reflect the processing of specific stimulus features, with increasing levels of complexity. We show that late stages of processing (~200-250 ms), reflecting the integration of complex stimulus features (collinearity, illusory triangle), were impaired by masking but spared by the attentional blink. In contrast, decoding of local contrast (the spatial arrangement of stimulus features) was observed early in time (~80 ms) and was left largely unaffected by either manipulation. These results replicate previous work showing that feedforward processing is largely preserved under both perceptual and attentional blindness. Crucially however, under matched levels of performance, only attentional blindness left the processing of more complex visual features relatively intact, likely related to spared lateral and local feedback processes during inattention. These findings reveal distinct neural mechanisms associated with perceptual and attentional blindness and thus contribute to a comprehensive understanding of distinct neural stages leading to conscious access.

Introduction

Conscious access to sensory input can be impaired in two distinct ways (Dehaene et al., 2006; Lamme, 2010; Mashour et al., 2020; Northoff & Lamme, 2020). Sensory input may lack sufficient bottom-up strength, or top-down attention may be directed elsewhere. Despite both cases resulting in a failure to perceive a stimulus, their underlying neural mechanisms are thought to be remarkably different. Influential theories of consciousness such as global neuronal workspace and recurrent processing theory propose four stages of neural information processing associated with distinct levels of bottom-up signal strength and top-down attention. These four stages can be investigated empirically by crossing "perceptual" manipulations that degrade the strength of sensory input (e.g., reducing stimulus contrast, masking, continuous flash suppression) with "attentional" manipulations that affect top-down attention (e.g., attentional blink, inattentional blindness, **Fig. 1A**).

According to these theoretical models, all stimuli elicit feedforward information transfer from lower- to higher-level brain regions (**Fig. 1A**, bottom row), but recurrent interactions are initiated only for stimuli with sufficient bottom-up strength (**Fig. 1A**, top row). If stimuli are sufficiently strong and top-down attention is available, neural processing crosses a threshold, triggering a process termed global ignition, facilitating widespread recurrent interactions between frontal, parietal and sensory cortices, yielding conscious access (**Fig. 1A**, top left). Crucially, when top-down attention is lacking, frontoparietal network ignition is prevented, while local recurrent interactions within sensory brain regions remain relatively intact ("attentional blindness", **Fig. 1A**, top right) (Dehaene et al., 2003; Marti et al., 2015; Sergent et al., 2005; Zivony & Lamy, 2022). Weak stimuli result in the absence, or a substantial reduction, of local recurrent interactions ("perceptual blindness", **Fig. 1A**, bottom left) (Fahrenfort et al., 2007; Joglekar et al., 2018; van Gaal et al., 2008; van Vugt et al., 2018).

Although this framework is at the heart of influential theories of consciousness, the four stages of the model and their underlying neural mechanisms have rarely been investigated simultaneously within the same study (for an exception see Fahrenfort et al., 2017). One challenge with comparing results across different studies, or even within a study, is that perceptual manipulations tend to impair overall task performance more than attentional manipulations, so that it may not be surprising to find that perceptual manipulations interrupt recurrent interactions to a greater extent than attentional manipulations. Given the right parameter settings, perceptual manipulations can be used to induce chance-level performance, while it is not possible to use attentional manipulations to drive behavioral performance down to chance, even when they are optimized fully. For this reason, attentional manipulations are often combined with post-hoc selection of a subset of "blind" trials (e.g., attentional blink) or subjects (e.g., inattentional blindness), a methodologically questionable practice that introduces criterion confounds, sampling bias, and underestimates consciousness (Peters & Lau, 2016; T. Schmidt, 2015; Shanks, 2017). Thus, when comparing perceptual to attentional manipulations, any (neural) effect could reflect differences in task performance rather than genuine differences between manipulations and hence stages in the model depicted in **Figure 1A**. While these issues with comparing conditions that differ in task performance in consciousness research have been acknowledged (Lau, 2022), they have rarely been addressed experimentally (Kanai et al., 2010; Lau & Passingham, 2006; Meuwese et al., 2014). To test and further refine the

four-stage model of consciousness in humans, we compared all stages within the same
experimental setup, matching task performance between a perceptual manipulation (masking)
and an attentional manipulation (attentional blink).
To reveal neural mechanisms associated with perceptual and attentional blindness, we
combined a novel visual stimulus with features of different complexity with time-resolved
decoding of these visual features from electroencephalogram (EEG) data (**Fig. 1B**). The target
stimulus differed along three dimensions (illusory triangle, non-illusory triangle, and local
contrast) that were independently manipulated. First, "Pac-Man" stimuli could create either the
perception of an illusory surface in the shape of a Kanizsa triangle when aligned, or not, when
misaligned. Second, additional "two-legged white circles" could form either a non-illusory
triangle when their line segments were aligned, or not, when the legs were misaligned. Third, for
the local contrast manipulation, the whole stimulus was rotated by 180 degrees, so that the
same retinotopic positions had high contrast in one spatial configuration and low contrast when
flipped 180 degrees. Direct neural recordings in animals have shown that the Kanizsa illusion is
supported by both lateral and feedback connections (Halgren et al., 2003; Kok et al., 2016; Kok
& de Lange, 2014; Lee & Nguyen, 2001; Pak et al., 2020; Wokke et al., 2013), while the
processing of collinear line elements (as in the non-illusory triangle) primarily relies on lateral
connections (Bosking et al., 1997; Gilbert & Wiesel, 1979; Li, 1998; Liang et al., 2017; K. E.
Schmidt et al., 1997; Stettler et al., 2002). Differences in local contrast are processed early in
the visual system through feedforward connections and are resistant to masking (Fahrenfort et
al., 2007, 2017; Kandel et al., 2000; Lamme & Roelfsema, 2000). Decoding the stimulus
conditions of the illusory triangle, non-illusory triangle, and local contrast at different points in
time, in combination with the associated topography, therefore served as putative markers of
these distinct neural processes (**Fig. 1B)** and allowed us to test whether the effects of masking
and the attentional blink followed the predictions of the four-stage model of consciousness.
105

106
107
Figure 1. Experimental design and behavior. *(A) Perceptual vs. attentional blindness in the four-stage*
model. A stimulus with low bottom-up strength (masked) is thought to interrupt local recurrent processing
in sensory areas while leaving feedforward processing largely intact, while inattention (induced by the
attentional blink) is thought to interrupt global recurrent processing between frontoparietal areas and
sensory areas, while leaving local recurrent processing within sensory areas largely intact. Reprinted from
Dehaene et al. (2006) *with permission from Elsevier. (B) Target stimulus set and decoding analyses. (C)*
Trial design. (D) Perceptual performance refers to participants' ability to detect the Kanizsa illusion.
Metacognition refers to participants' ability to evaluate their own performance using confidence
judgments. Both perceptual performance and metacognition are measured as the area under the receiver
operating characteristic curve (AUC). Error bars are mean ± standard error of the mean. Individual data
points are plotted using low contrast. Ns is not significant (P≥0.477, BF$_{01}$≥4.05). *P≤0.001.

Results

Masking and the attentional blink were matched in perceptual performance and
metacognition

We recorded the EEG signal of 30 participants who identified the presence or absence of an
illusory surface (triangle) in two black target stimuli (T1 and T2) that were presented amongst
red distractors in a rapid serial visual presentation task (**Fig. 1C**). We manipulated the visibility
of T2 in two ways: masking the stimulus and manipulating attention, resulting in a 2×2 factorial
design (**Fig. 1A**). Specifically, T2 could be either masked or unmasked (perceptual

manipulation), and T2 could be presented at either a long interval (900 ms) or a short interval
(200 or 300 ms) after T1, inducing an attentional blink (AB) effect for the short T1-T2 intervals
(Raymond et al., 1992). This design resulted in four conditions, which we from now on refer to
as the masked condition (T2 masked at the long T1-T2 interval), AB condition (T2 unmasked at
the short T1-T2 interval), no manipulations condition (T2 unmasked at the long T1-T2 interval),
and both manipulations condition (T2 masked at the short T1-T2 interval). At the end of a trial,
participants indicated whether each target (T1 and T2) contained an illusory surface or not.
Importantly, mask contrast in the masked condition was individually adjusted using a staircasing
procedure to match participants' performance in the AB condition, ensuring comparable
perceptual performance in the masked and the AB condition (see Methods for more details).
Conscious access can be assessed not only based on perceptual performance but also
through metacognitive sensitivity, the ability to evaluate one's own performance (Brown et al.,
2019; Dienes, 2007; Fleming & Lau, 2014; Lau & Passingham, 2006; Merikle et al., 2001; Seth
et al., 2008). Participants in our study provided confidence ratings on a 3-point scale (low,
medium, high) for their responses to T2. To ensure that the distribution of confidence ratings
was not influenced by overall differences in perceptual performance between conditions,
conditions that were matched in perceptual performance (masked and AB condition) were
presented in the same experimental block, while the other block type included the unmatched
conditions (no and both manipulations condition).
We used area under the receiver operating characteristic (ROC) curve (AUC) as a
shared metric for perceptual performance (detection of the Kanizsa illusion), metacognitive
sensitivity, and EEG decoding (see Methods for details on the calculation of these measures).
Repeated-measures (rm) ANOVA with the factors masking (present/absent) and T1-T2 lag
(short/long) revealed, as expected, that both masking and the short T1-T2 lag impaired
perceptual performance ($F_{1,29}$=344.24, $P<10^{-15}$ and $F_{1,29}$=427.54, $P<10^{-15}$) as well as
metacognitive sensitivity ($F_{1,29}$=50.78, $P<10^{-7}$ and $F_{1,29}$=47.83, $P<10^{-6}$). Importantly, paired t-tests
showed that we successfully matched the key conditions, the masked condition (masked, long
lag) and the AB condition (unmasked, short lag) for perceptual performance (t_{29}=0.62, P=0.537,
BF_{01}=4.30, **Fig. 1D**, left) as well as for metacognitive sensitivity (t_{29}=0.72, P=0.477, BF_{01}=4.05;
Fig. 1D, right, see **Fig. S1** for signal detection theory related measures of performance). Thus,
the two performance matched conditions were indistinguishable from each other in both
measures of conscious access.

Masking and the attentional blink leave local contrast decoding largely intact

To derive our markers of the different neural processes from our EEG data, for each stimulus
feature we trained linear discriminant classifiers on the T1 data and tested them on the T2 data.
Classifiers used raw EEG activity across all electrodes. To leverage the similarities between T1
and T2 in task and stimulus context, all main analyses used T1 training data for T2 decoding.
This approach minimized possible differences in conscious access and working memory
demands between the training and test datasets.
For local contrast decoding, the classifier categorized stimuli as either pointing upwards
or pointing downwards, thereby effectively decoding the stimuli's local differences in contrast at
the top vs. bottom of the stimulus. Classification performance (AUC) over time was obtained,

with peak decoding accuracy in a 75-95 ms time window (**Fig. 2A** and **Fig. S2A**, top). The peak
in decoding accuracy was occipital in nature (see the covariance/class separability map of **Fig.
2A**) (Haufe et al., 2014), consistent with our previous findings (Fahrenfort et al., 2017). We
focused our analyses on the averages of this time window. An rm ANOVA with the factors
masking (present/absent) and T1-T2 lag (short/long) revealed only a marginal effect of masking
on local contrast decoding ($F_{1,29}$=6.51, P=0.016), while the T1-T2 lag had no significant effect
($F_{1,29}$=0.32, P=0.578). A paired t-test yielded no evidence for a difference between the
performance matched conditions (masked vs. AB; t_{29}=1.42, P=0.166, BF_{01}=2.08; **Fig. 2C**, "Local
contrast: 75-95 ms"). These results are in line with theoretical proposals and empirical findings
that suggest limited effects of masking and attentional manipulations on perceptual processes
that rely on feedforward connections (Dehaene et al., 2006; Fahrenfort et al., 2007, 2017;
Lamme, 2010).

Stronger effect of masking than the attentional blink on early but not on late
illusion decoding

Next, we trained a linear classifier on the T1 data to discriminate between the absence and
presence of the Kanizsa illusion and tested it on each of the four conditions of the T2 data. The
average of all four conditions revealed two prominent peaks in decoding accuracy, consistent
with previous research (**Fig. S2C**, top) (Fahrenfort et al., 2017). Based on this previous study,
our analyses focused on the averages of the two time windows that encompassed these two
peaks: specifically, from 200 to 250 ms and from 375 to 475 ms after target stimulus onset. The
covariance/class separability maps (**Fig. 2B**) indicated that during the earlier time window (200–
250 ms) classification mainly relied on occipital electrodes. Considering its timing, topology and
previous findings, this neural event likely reflects early sensory processes and may thus
represent a marker for local recurrent processing (Fahrenfort et al., 2017; Kok et al., 2016;
Roelfsema, 2006; Wokke et al., 2013; Wyatte et al., 2014). The timing and topology of the later
neural event (375–475 ms) overlapped with the event-related potential component P300, which
is associated with conscious access (Fahrenfort et al., 2017; Sergent et al., 2005; Weaver et al.,
2019) and may thus represent a marker for global recurrent processing.
We tested how the consciousness manipulations affected these putative markers of local
and global recurrent processing (**Fig. 2C**), again conducting rm ANOVAs with the factors
masking (present/absent) and T1-T2 lag (short/long) that we followed-up on with paired t-tests
comparing the matched conditions (masked vs. AB). Importantly, we observed a distinct
difference between the performance matched conditions in the first decoding peak, which was
significantly impaired by both masking ($F_{1,29}$=162.62, P<10^{-12}) and T1-T2 lag ($F_{1,29}$=78.07, P<10^{-8}), but importantly, it was more affected by masking than T1-T2 lag ($F_{1,29}$=18.67, P<0.001) (**Fig.
2C**, "Illusory triangle: 200-250 ms"). Directly comparing the performance matched conditions,
the first decoding peak was more strongly impaired by masking than by the AB (t_{29}=4.66, P<10^{-4}, BF_{01}=0.003).
The pattern of results of the second peak was notably different. The second decoding
peak was impaired by both masking ($F_{1,29}$=49.75, P<10^{-7}) and T1-T2 lag ($F_{1,29}$=78.48, P<10^{-9}),
and the matched conditions (masked and AB condition) did not differ significantly from each
other (t_{29}=0.21, P=0.837, BF_{01}=5.04) (**Fig. 2C**, "Illusory triangle: 375-475 ms"). Furthermore,

another rm ANOVA comparing the first and second decoding peak between the matched
conditions (masked/AB) revealed a significant interaction, reflecting a larger difference between
the AB and the masked condition in the first than in the second decoding peak ($F_{1,29}$=31.53,
P<10⁻⁵). Across the four conditions, the pattern of behavioral results, both for perceptual
performance and metacognitive sensitivity, closely resembled the second decoding peak (**Fig.
2C**), indicating that global recurrent processing reflected conscious access to the Kanizsa
illusion.
Additional rm ANOVAs comparing the effect of the consciousness manipulations on local
contrast decoding with their effects on the first and second illusion decoding peak showed that,
compared to contrast decoding, both manipulations had stronger effects on the first illusion
decoding peak (masking: $F_{1,29}$=99.35, P<10⁻¹⁰; AB: $F_{1,29}$=38.95, P<10⁻⁶) and on the second
illusion decoding peak (masking: $F_{1,29}$=22.25, P<10⁻⁴; AB: $F_{1,29}$=49.60, P<10⁻⁷). This suggests
that masking and the AB specifically influenced local and global recurrent processing
respectively, while early feedforward processing was less affected.
225

Figure 2. Local contrast and illusory triangle decoding using first targets as training data. *(A) Local*
contrast decoding. (B) Illusory Kanizsa triangle decoding. For both features, covariance/class separability
maps reflecting underlying neural sources are shown. Below these maps: mean decoding performance,
area under the receiver operating characteristic curve (AUC), over time ± standard error of the mean
(SEM). Thick lines differ from chance: P<0.05, cluster-based permutation test. (C) Normalized (Z-scored)
AUC for every measure: mean decoding time windows and two types of behavior. Each measure is Z-

 scored separately. Perceptual performance refers to participants' ability to detect the Kanizsa illusion.
235 *Metacognition refers to participants' ability to evaluate their own performance using confidence*
236 *judgments. See Figure S3 for the same analyses but then for off-diagonal decoding profiles. Error bars*
237 *are mean ± SEM. Individual data points are plotted using low contrast. Ns is not significant (P≥0.166,*
238 *$BF_{01}≥2.07$). *P≤0.002.*

Distinguishing collinearity and illusion-specific processing

The performance matched masked and AB condition differed only in the first illusion decoding
peak, our putative marker of local recurrent processing, which was markedly more impaired in
the masked than the AB condition. Next, we determined whether this effect reflected relatively
preserved processing of collinearity or the Kanizsa illusion during attentional blindness. In our
target stimulus, collinearity was present when the Pac-Man stimuli aligned, inducing the illusory
Kanizsa triangle. Notably, collinearity was also present when the line segments of the "two-
legged white circles" of the stimulus aligned, forming the non-illusory triangle. Note that the line
segments making up the triangle were equally long, and the spaces between them equally
large, for the illusory and non-illusory triangles. Thus, by comparing non-illusory triangle
decoding to illusory triangle decoding we distinguished between collinearity and illusion-specific
processing.
However, in the main RSVP task the illusory triangle was task-relevant, while non-
illusory triangles were always task-irrelevant. To equate the effect of task-relevance in the
comparison, classifiers were trained on an independent training set in which each relevant
stimulus feature was task-relevant. Specifically, in different experimental blocks, participants
focused either on local contrast, the non-illusory triangle, or the illusory triangle (**Fig. S4**). We
trained a classifier to distinguish between the presence and absence of the task-relevant non-
illusory triangle (collinearity-only) and the same was done for the task-relevant illusory triangle
(collinearity-plus-illusion). Then, both classifiers were used to decode the presence vs. absence
of the illusory triangle in the main RSVP task (cross-task-decoding approach), which ensured
that both training and testing were always performed on task-relevant stimuli. By comparing
Kanizsa decoding performance in the RSVP task based on the collinearity-only classifier with
decoding performance based on the collinearity-plus-illusion classifier, we effectively subtracted
out the contribution of collinearity processing to illusion decoding, thereby isolating illusion-
specific processing.

Preserved collinearity and illusion-specific processing during the attentional blink

To determine a time window for (the start of) collinearity-only processing, we first trained and
tested classifiers to distinguish present vs. absent non-illusory triangles (training and testing on
non-illusory triangles only). We trained two classifiers, one on the T1 in the RSVP task and one
on the independent training set and tested their performance in decoding the non-illusory
triangle in the T2 data, where this non-illusory triangle was always task-irrelevant. The results of
both classifiers converged and these analyses revealed a peak in decoding accuracy at ~164
ms, right before the 200-250 ms time window of the first illusion decoding peak (**Fig. S2B**). This
peak was also evident when these classifiers were used to categorize the presence vs. absence

of the Kanizsa illusion (**Fig. S2C**, first time window), as well as in previous research (Fahrenfort
et al., 2017), suggesting that collinearity processing also contributes to Kanizsa decoding.
We examined how decoding the presence vs. absence of the Kanizsa illusion in the
RSVP task was affected by the consciousness manipulations, while training classifiers either on
the illusory (collinearity-plus-illusion) or non-illusory (collinearity-only) triangle from the
independent training set. **Figure 3A** shows the decoding accuracies of these analyses across
the entire time window (purple and green lines). Follow-up analyses were performed using the
140-190 ms window, the peak of collinearity-only processing (see the previous paragraph). An
rm ANOVA with the factors masking (present/absent), T1-T2 lag (short/long), and training set
(illusory/non-illusory triangle) revealed that both masking and the short T1-T2 lag impaired
decoding accuracy (masking: $F_{1,29}$=58.95, $P<10^{-7}$; T1-T2 lag: $F_{1,29}$=24.90, $P<10^{-4}$). Furthermore,
paired t-tests comparing the matched conditions (masked vs. AB condition) confirmed that
decoding accuracy was more impaired in the masked than AB condition, both when training was
done on the illusory (t_{29}=2.26, P=0.031, BF_{01}=0.58) and non-illusory triangle (t_{29}=2.78, P=0.009,
BF_{01}=0.21; **Fig. 3B**, "140-190 ms"). Focusing on the performance matched conditions and the
role of the training set, an rm ANOVA with the factors condition (masked/AB) and training set
(illusory/non-illusory triangle) on T2 illusory triangle decoding revealed no significant effect of
training set ($F_{1,29}$=0.09, P=0.766), i.e., no evidence for illusion-specific processing, and no
significant interaction ($F_{1,29}$=0.04, P=0.837). This demonstrates that neural processing in the
140-190 ms window indeed reflects collinearity-only rather than illusion-specific processing.
The marker for illusion-specific processing emerged later, namely in the 200-250 ms
time window that encompassed the first illusion decoding peak reported above. As can be seen
in **Figure 3A**, when no consciousness manipulations were applied (unmasked, long T1-T2 lag),
there was significant illusion-specific processing, i.e., T2 illusory triangle decoding was better
after training a classifier on the Kanizsa illusion (collinearity-plus-illusion, green line) than after
training a classifier on the non-illusory triangle (collinearity-only, purple line) (t_{29}=4.22, $P<0.001$,
BF_{01}=0.008). Turning to the performance matched conditions, an rm ANOVA with the factors
condition (masked/AB) and training set (illusory/non-illusory triangle) on T2 illusory triangle
decoding yielded a significant effect of condition ($F_{1,29}$=16.59, $P<0.001$), with overall better
decoding for the AB than for the masked condition, and importantly, a significant interaction
($F_{1,29}$=4.65, P=0.039). **Figure 3A** shows that decoding after training on illusory triangles
(collinearity-plus-illusion) was better than after training on non-illusory triangles (collinearity-
only) for the AB (t_{29}=2.51, P=0.018, BF_{01}=0.36, **Fig. 3A**, top right) but not for the masked
condition (t_{29}=-0.02, P=0.982, BF_{01}=5.14, **Fig. 3A**, bottom left). Thus, while illusion-specific
processing was evident in the AB condition, it was fully abolished in the masked condition.
Illusion-specific processing was not even affected by the AB, as an rm ANOVA with the factors
condition (no manipulations/AB) and training set (illusory/non-illusory triangle) revealed no
significant interaction ($F_{1,29}$=1.33, P=0.259). The classifier trained on non-illusory triangles
(collinearity-only) also performed better during the AB than masking (t_{29}=2.85, P=0.008,
BF_{01}=0.18; **Fig. 3B**, "200-250 ms", purple line), hence both collinearity-only and illusion-specific
processing were most strongly impaired by masking. Control analyses presented in the
Supplementary information (Fig. S6) demonstrate that cross-feature-decoding can indeed
isolate illusion-specific processes and does not reflect other, e.g., task- or attention-related,

processes (for further control analyses testing the effect of task-relevance on local contrast
processing, see **Supplementary Information** and **Fig. S7**).
Finally, we focused on the late 375-475 ms window, encompassing the second illusion
decoding peak, which was directly linked to behavioral performance (see above, **Fig. 3A**, last
time window). Similarly as above, illusory triangle decoding was now based on training the
decoder on the illusory triangles from the independent training set. Replicating our main
analysis, classifier performance was impaired by both masking ($F_{1,29}$=6.01, P=0.020) and T1-T2
lag ($F_{1,29}$=10.10, P=0.004), with no significant differences between the two performance
matched conditions (t_{29}=-0.63, P=0.531, BF_{01}=4.27) (**Fig. 3B**, "375-475 ms").
327

328
329
Figure 3. Separating collinearity and illusion-specific processes using the independent training
dataset. *(A) Illusory triangle decoding, after training classifiers on the independent training set on either*
the non-illusory (collinearity-only, purple lines) or illusory triangle (collinearity-plus-illusion, green lines).
For comparison, training and testing on local contrast is shown in light blue. Mean decoding performance,
area under the receiver operating characteristic curve (AUC), over time ± standard error of the mean

(SEM) is shown. Thick lines differ from chance: P<0.05, cluster-based permutation test. The highlighted
time windows are 75-95, 140-190, 200-250, and 375-475 ms, corresponding to separate panels in (B),
which shows normalized (Z-scored) mean AUC for every time window. Each window is Z-scored
separately. Error bars are mean ± SEM. Individual data points are plotted using low contrast. Ns is not
significant (P≥0.084, BF_{01}≥1.26). *P≤0.048.

Discussion

We demonstrate that perceptual and attentional manipulations, despite similarly impairing
conscious access, exhibit distinct neural profiles in the brain. To investigate this difference, we
decoded different visual features targeting distinct stages of visual processing from human EEG
activity, while carefully matching a masked condition and an attentional blink (AB) condition in
perceptual and metacognitive performance. While decoding of local contrast was barely affected
by the two consciousness manipulations, early (200–250 ms, occipital) decoding of the illusory
Kanizsa triangle was markedly more impaired in the masked than the AB condition (Fahrenfort
et al., 2017), even though task performance was matched. By contrast, later (375–475 ms,
centroparietal) illusion decoding was similarly impaired by masking and the AB, closely
resembling their matched effects on behavioral performance. Furthermore, we differentiated
between collinearity-only and illusion-specific processing and found that both processes were
more strongly impaired by masking than the AB. Notably, illusion-specific processing was
unaffected by the AB, but completely abolished by masking.
Decoding of these different stimulus features at different points in time, together with
their topography, may be regarded as markers of distinct neural processes. Based on
neurophysiology and previous neuroimaging studies, our early decoding peak for local contrast
decoding (75–95 ms) likely reflects feedforward processing (Fahrenfort et al., 2007, 2017;
Kandel et al., 2000; Lamme & Roelfsema, 2000). The first illusion decoding peak may be
regarded as a marker of local recurrent processing, while the second illusion decoding peak
likely reflects global recurrent processing (Fahrenfort et al., 2017). Thus, our findings suggest
that both perceptual and attentional blindness leave feedforward processing largely intact and
similarly impair global recurrent processing, while local recurrent processing is markedly more
impaired by perceptual than attentional blindness.
Furthermore, based on neurophysiological evidence that collinearity processing primarily
relies on lateral connections (Bosking et al., 1997; Gilbert & Wiesel, 1979; Li, 1998; Liang et al.,
2017; K. E. Schmidt et al., 1997; Stettler et al., 2002), while processing of the Kanizsa illusion
involves both lateral and feedback connections (Halgren et al., 2003; Kok et al., 2016; Kok & de
Lange, 2014; Lee & Nguyen, 2001; Pak et al., 2020; Wokke et al., 2013), the comparison of
collinearity-only to illusion-specific processing may provide insight into the components of local
recurrent processing: lateral and feedback connections (Lamme et al., 1998; Roelfsema, 2006).
Both feedback and lateral processing were more strongly impaired by masking than the AB.
Notably, illusion-specific feedback processes were unaffected by the AB, but completely
abolished by masking. These findings confirm and enrich empirical and theoretical work on
perceptual vs. attentional mechanisms of consciousness (Block, 2005; Dehaene et al., 2006;
Hatamimajoumerd et al., 2022; Lamme, 2010; Pitts et al., 2018; Sergent & Dehaene, 2004),

clearly distinguishing and specifying the neural profiles of each processing stage of the
influential four-stage model of conscious experience.
To our knowledge, this is the first study to examine the neural mechanisms underlying
conscious access in which behavioral measures of conscious perception are carefully matched
between the attentional blink and masking within a single experimental design. Previous
investigations have typically employed separate paradigms for perceptual and attentional
manipulations, often using different stimuli associated with distinct neural mechanisms, which
complicates direct comparisons between manipulations and across studies. Further, inattention
approaches generally use stronger sensory input (e.g., stimuli of longer duration, higher
contrast) than perceptual manipulations (Stein et al., 2021). Here, we introduced a novel
stimulus that allowed us to isolate four distinct stages of visual processing by decoding different
features while holding visual stimulation and task context constant. Furthermore, measurement
of conscious perception often differs between perceptual and attentional manipulations. In
particular, inattention approaches, which have previously tended to reveal more extensive
neural processing, frequently involve post-hoc selection of "blind" trials or participants based on
subjective awareness reports, which is susceptible to criterion confounds and introduces
sampling biases that lead to underestimation of awareness in the selected sample (Peters &
Lau, 2016; T. Schmidt, 2015; Shanks, 2017). In contrast, our study analyzed all trials and
included all participants while carefully matching perceptual performance and metacognition
between masking and the AB. Therefore, any observed neural difference between masking and
the AB can be unequivocally attributed to differences between attentional and perceptual
manipulations of conscious access.
Our results suggest that, compared to masking, the AB left local recurrent processing
intact, while feedforward processing did not differ between the two manipulations. Local
recurrent processing plays a critical role in perceptual integration, facilitating the organization of
fragmented sensory information, such as lines, surfaces, and objects, into a coherent whole
(Roelfsema, 2023). Our EEG decoding results support this notion, demonstrating that the AB
allows for greater processing of collinearity and the illusion specifically within a time window
spanning 140 to 250 ms after stimulus onset, likely reflecting sparing of local recurrent
processes in visual cortex (Fahrenfort et al., 2017; Kok et al., 2016). This aligns with established
models of the AB phenomenon, in which the AB reflects a late post-perceptual central
bottleneck characterized by limited attentional capacity (Shapiro et al., 1997), so that sensory
information presented during the AB can nevertheless undergo extensive processing, allowing
for perceptual integration, possibly even leading up to semantic analysis (Luck et al., 1996).
Preserved local recurrent processing during the AB is also consistent with classic load
theory (Lavie & Dalton, 2014), where increasing perceptual load (Lavie & de Fockert, 2003)
more strongly reduces distractor processing than increasing cognitive load (e.g., by engaging
working memory, as in our AB condition). According to this theory, perceptual and attentional
manipulations serve as early and late filters for incoming sensory information, respectively,
resulting in more extensive processing under inattention. Indeed, one of the few neuroimaging
studies that included both manipulations found that only perceptual but not cognitive (working
memory) load decreased fMRI activity in the parahippocampal place area in response to
distractor scenes (Yi et al., 2004). However, not all neuroimaging evidence is consistent with a
stronger effect of perceptual than cognitive load (Brockhoff et al., 2022). Furthermore, previous

research has shown that the impact of inattention vs. masking can depend on the neural
architecture required for the task at hand. For example, processes related to the detection of
conflicting response tendencies, a hallmark of cognitive control and strongly associated with the
prefrontal cortex (Ridderinkhof et al., 2004), are more susceptible to inattention, which reduces
the depth of stimulus processing (Nuiten et al., 2021) than to masking, restricting recurrent
interactions, but allowing for deep feedforward processing (all the way up to prefrontal cortex)
(Jiang et al., 2018; van Gaal et al., 2008). Thus, the preservation of local recurrent interactions
appears to be particularly important for perceptual integration, aligning with the influential notion
that perceptual segmentation and organization may represent the mechanism of conscious
experience (Lamme, 2020).
Local recurrent interactions in visual cortex encompass both lateral and feedback
connections. The distinct roles of lateral and feedback connections to visual function have
received limited attention in human cognitive neuroscience and remain unaddressed in theories
of consciousness. Here we sought to distinguish between lateral processing reflecting basic
collinearity processing and feedback processing reflecting illusion-specific processing. Our
results suggest that lateral processing occurred earlier (between 140 and 190 ms after target
stimulus onset) than illusion-specific feedback processing (between 200 and 250 ms), in line
with animal research (Angelucci & Bressloff, 2006; Lamme et al., 1998; Roelfsema, 2006). Both
lateral and feedback processing appeared to be more strongly affected by masking than by the
AB, indicating that the "attentional blindness" stage of the four-stage model of consciousness
(**Fig. 1A**) involves both lateral and feedback connections. Interestingly, masking had a stronger
effect on illusion-specific feedback processing than on lateral processing. Along with the distinct
temporal and spatial EEG decoding patterns associated with lateral and feedback processing,
this suggests a processing sequence from feedforward processing to local recurrent interactions
encompassing lateral-to-feedback connections, ultimately leading to global recurrency and
conscious report.
Having delineated these distinct stages of feedforward, lateral, feedback and global
recurrent processing, one important avenue for future research is to distinguish between
unconscious and conscious perceptual processes at these stages. Having opted to equate
performance across manipulations in our study, behavioral performance was above chance
level for both consciousness manipulations. Follow-up research investigating perceptual
integration of fully unconscious stimuli could address ongoing debates between influential
theories of consciousness (Cogitate Consortium et al., 2023; Mudrik et al., 2014). The global
neuronal workspace theory suggests a durable, yet unconscious processing stage (referred to
as preconscious), where the input is not globally available, and amplification through top-down
attention is required for conscious access and report (Dehaene et al., 2006). In contrast, others
have argued that already local recurrent interactions reflect subjective phenomenal experience
(Block, 2005; Lamme, 2010). Moreover, markers like the P300 and ours for global recurrent
processing may reflect functions not directly related to conscious experience, like report or
decision-making (Alilović et al., 2023; Canales-Johnson et al., 2023; Pitts et al., 2018). Another
way forward therefore consists in combining no-report paradigms (Sergent et al., 2021;
Tsuchiya et al., 2015) with our EEG markers to examine whether local or global recurrent
processing more accurately reflects consciousness in the absence of report.

Methods

Participants

Thirty-three participants took part in the first two sessions (independent EEG training set and practice). Three of them met the practice session's pre-established criteria for exclusion (see "Procedure"). The remaining 30 participants (22±3 years old, 10 men, 2 left-handed) took part in the final (main experimental) session. They all had normal or corrected-to-normal vision. The study was approved by the local ethics committee. Participants gave informed consent and received research credits or 15 euros per hour.

Stimuli

The target stimulus set had a 2 (illusory Kanizsa triangle: present/absent) × 2 (non-illusory triangle: present/absent) × 2 (rotation: present/absent) design, resulting in eight stimuli (**Fig. 1B**). Three aligned Pac-Man elements induced the Kanizsa illusion. The non-illusory triangle was present when the stimuli's three other elements (the "two-legged white circles") were aligned. The controls for both the illusory and non-illusory triangle were created by rotating their elements by 90 degrees. Differences in local contrast were created by rotating the entire stimulus by 180 degrees. The targets spanned 7.5 degrees by 8.3 degrees of visual angle. The distance between the three Pac-Man stimuli as well as between the three aligned two-legged white circles was 2.8 degrees of visual angle. Although neuronal responses to collinearity in primary visual cortex are most robust when this distance is smaller (Kapadia et al., 1995, 2000), longer-range lateral connections between neurons with similar orientation selectivity can span distances corresponding to visual angles considerably greater than 2.8 degrees (Bosking et al., 1997; Stettler et al., 2002).

The distractor stimulus set was the same as the target stimulus set, with two exceptions. First, the distractors were red instead of black. Second, the distractors' six elements were rotated by 180 degrees relative to the targets', so neither the illusory nor non-illusory triangle was ever present in the distractors. Masks consisted of six differently shaped elements, all capable of covering the targets' elements. Six masks were created by rotating the original mask five times by 60 degrees. They spanned 8.5 degrees by 9.1 degrees of visual angle. The fixation cross, which was always present, was adapted from Thaler et al. (2013).

Procedure

The experiment consisted of three separate sessions conducted on different days: a three-hour session to collect EEG data for the independent training set, a 1.5-hour practice session, and a three-hour experimental session. Tasks were programmed in Presentation software (Neurobehavioral Systems) and displayed on a 23-inch, 60 Hz, 1920×1080 pixels monitor. On each trial of the experimental session, participants were shown two targets (T1 and T2) within a rapid serial visual presentation (RSVP) of distractors (**Fig. 1C**). The targets and distractors had a stimulus onset asynchrony of 100 ms. T2 and distractors were presented for 17 ms each. To improve the decoding analyses' training dataset, T1 was presented for 67 ms. The longer

presentation duration facilitated attending to T1, which should result in greater deployment of
attentional resources and thereby increase the size of the AB. T1 was preceded by five
distractors and T2 was followed by six distractors.
T2 visibility was manipulated in two ways, using a perceptual and an attentional
manipulation (**Fig. 1A**). The perceptual manipulation consisted in masking T2 with three masks,
each presented for 17 ms with an interstimulus interval of 0 ms. The three masks were selected
randomly, but all differed from each other. Half of the T2s were masked; for the other half no
masks were presented (unmasked condition). The attentional manipulation consisted in
shortening the T1–T2 lag from a long interval of eight distractors (900 ms) to a short interval of
one or two distractors (200 or 300 ms). Half the trials had a long lag, the other half had a short
lag. The short lag duration was determined for each participant individually during the training
session. Short lags were expected to result in an AB. Participants were instructed to fixate on
the fixation cross. After the RSVP, they indicated for each target whether it contained the
Kanizsa illusion or not. For T2, participants simultaneously reported their confidence in their
response: low, medium, or high, resulting in six response options. To get accurate ratings,
participants first responded to T2 and then to T1. Response screens lasted until the response.
In short, the experimental session had an 8 (T1 stimulus conditions) × 8 (T2 stimulus conditions)
× 2 (masked/unmasked) × 2 (short/long T1–T2 lag) task design, resulting in 256 conditions.
Each condition was presented four times, totaling 1024 trials.
The experimental session was preceded by the practice session, in which participants
were familiarized with the task. To proceed to the experimental session, participants had to
score above 80% correct for both T1 and unmasked, long lag T2. One participant was excluded
for failing to achieve this. The training session was also used to determine for each participant
the duration of the short lag (200 or 300 ms T1–T2 interval) that induced the largest AB (lowest
T2 accuracy) and that was used in the subsequent experimental session. Two participants were
excluded due to their AB size falling below the predetermined criterion. Specifically, their T2
accuracy at both short lags did not exhibit a decrease of more than 5% compared to long lags.
One of the main goals of this study was to match perceptual performance between the
perceptual and the attentional manipulation. We did this in two ways. First, during the training
session, the matching was done by staircasing mask contrast using the weighted up-down
method (Kaernbach, 1991). Contrast levels ranged from 0 (black) to 255 (white). Mask contrast
started at level 220. Each correct response made the task more difficult: masks got darker by
downward step size S_{down}. Each incorrect response made the task easier: masks got lighter by
upward step size S_{up}. Step sizes were determined by $S_{up} \times p = S_{down} \times (1 - p)$, where p is the
accuracy at short lags. The smallest step size was always nine contrast levels. A reversal is
making a mistake after a correct response, or vice versa. The staircase ended after 25
reversals. The mask contrast with which the experimental session started was the average
contrast level of the last 20 reversals. Second, during the experimental session, after every 32
masked trials, mask contrast was updated in accordance with our goal to match performance
over participants, while also matching performance within participants as well as possible.
To ensure that confidence ratings for these matched conditions (masked, long lag and
unmasked, short lag) were not contaminated by differences in perceptual performance, one type
of block only contained the matched conditions, while the other block type contained the two
remaining, unmatched conditions (masked, short lag and unmasked, long lag). To ensure every

confidence rating would have enough trials for creating receiver operating characteristic curves,
participants were instructed to distribute their responses evenly over all ratings within a block.
Participants received feedback about the distribution of their responses. The mask contrasts
from a performance matched block were used in the subsequent non-performance matched
block to ensure that masking remained orthogonal to the AB manipulation. The experimental
session therefore always started with a performance matched block.
We wanted to compare illusory triangle decoding to non-illusory triangle decoding.
However, during the experimental session, the non-illusory triangle was never task-relevant,
only the illusory one was. During the independent EEG classification training session, we
therefore made each visual feature, one after the other, task-relevant. A target was presented
for 33 ms every 900-1100 ms (**Fig. S4**). Participants had to fixate on the fixation cross and
indicate whether the current task-relevant feature was absent or present. For each feature, each
target was presented 64 times, totaling 512 trials. The order of the task-relevant features was
counterbalanced over participants. For all sessions, response button mapping was
counterbalanced within tasks.

Behavioral analysis

To quantify perceptual performance, we constructed receiver operating characteristic (ROC)
curves by plotting objective hit rates against objective false alarm rates. We used the six
response options to get five inflection points (Green & Swets, 1966). We also quantified
metacognitive sensitivity: the ability to know whether you were right or wrong. Performance is
high when you are confident in objectively correct responses and not confident in objectively
incorrect responses. We again constructed ROC curves, now by plotting the rate of high-
confidence correct responses (subjective hit rates) against the rate of high-confidence incorrect
responses (subjective false alarm rates). We used the three confidence ratings to get two
inflection points. To ensure that T1 was attended, trials with incorrect T1 responses were
excluded. Repeated measures ANOVAs and Bayesian t-tests were used to test the differences
between experimental conditions.

EEG recording and preprocessing

EEG was recorded at 1024 Hz using a 64 channel ActiveTwo system (BioSemi). Four
electrooculographic (EOG) electrodes measured horizontal and vertical eye movements. The
data were analyzed with MATLAB (MathWorks). For most of the preprocessing steps, EEGLAB
was used (Delorme & Makeig, 2004). The data were re-referenced to the earlobes. Poor
channels were interpolated. High-pass filtering can cause artifacts in decoding analyses; we
therefore removed slow drifts using trial-masked robust detrending (van Driel et al., 2021). Each
target was epoched from -250 to 1000 ms relative to target onset. To improve the results from
the independent component analysis (ICA), baseline correction was applied using the whole
epoch as baseline (Groppe et al., 2009). ICA was used to remove blinks. Blink components
were removed manually. Baseline correction was applied, now using a -250 to 0 ms window
relative to target onset. Trials with values outside of a -300 to 300 microvolts range were
removed. We used an adapted version of FieldTrip's ft_artifact_zvalue function to detect and

remove trials with muscle artifacts (Oostenveld et al., 2011). As in the behavioral analyses, trials
with incorrect T1 responses were excluded. Finally, the data were downsampled to 128 Hz.

Multivariate pattern analyses

We decoded the different visual features (local contrast, non-illusory triangle, and illusory
Kanizsa triangle, respectively; **Fig. 1B**) using the Amsterdam Decoding and Modeling (ADAM)
toolbox (Fahrenfort et al., 2018). For each participant and each visual feature, a linear
discriminant classifier was trained on the T1 data and tested on each condition of the T2 data.
The classifier was trained to discriminate between the feature's (e.g., the illusory triangle's)
absence and presence based on the raw EEG activity across all electrodes. AUC was again
used as the performance measure. This procedure was executed for every time sample in a
trial, yielding classification performance over time. For the time samples from -100 to 700 ms
relative to target onset, we used a two-sided t-test to evaluate whether classifier performance
differed from chance. We used cluster-based permutation testing (1000 iterations at a threshold
of 0.05) to correct for multiple comparisons (Maris & Oostenveld, 2007). To obtain topographic
maps showing the neural sources of the classifier performance, we multiplied the classifier
weights with the data covariance matrix, yielding covariance/class separability maps (Haufe et
al., 2014).
In the decoding analyses described in the results, we applied "diagonal decoding":
classifiers were tested on the same time sample they were trained on. We did the same
analyses again, now by applying "off-diagonal decoding": classifiers trained on a particular time
point are tested on all time points (King & Dehaene, 2014). Off-diagonal decoding allowed us to
investigate whether patterns of activity during the time windows of interest were stable over time
(**Fig. S3**). For the illusory triangle, classifiers were trained on the 200-250 ms window and then
averaged. The same was done for the local contrast 75-95 ms window.
To distinguish between collinearity-only and illusion-specific processing, we trained
classifiers on independent data based on collinearity-only (the non-illusory triangle was task-
relevant) or collinearity-plus-illusion (the illusory triangle was task-relevant) and then decoded
the Kanizsa illusion in T2s of the main RSVP task. The rationale for this analysis is that
collinearity is present both when the Pac-Man stimuli align to form the illusory Kanizsa triangle
and when the two-legged white circles align to from a non-illusory triangle, but only in the case
of the Kanizsa triangle do participants experience an illusion. The comparison of T2 illusion
decoding between the classifiers trained on the illusion and on collinearity-only in the training
set may therefore isolate illusion-specific (likely involving feedback processing) from basic
collinearity processing (likely involving lateral connections; **Fig. 3**). In the **Supplementary**
information (Fig. S5), we compare the independent training set to the training set used for the
main analyses, the T1 data from the RSVP task.
As described in the **Supplementary information** as well, a tenfold cross-validation
scheme was applied to the data from the independent training set to decode local contrast.
Individual participants' data were split into ten equal-sized folds after randomizing the task's trial
order. A classifier was then trained on nine folds and tested on the tenth one, ensuring
independence of the training and testing sets. This procedure was repeated until each fold

served as the test set once. Classifier performance, AUC, was averaged across all ten iterations

(**Fig. S7**).

628   As in the behavioral analyses, repeated measures ANOVAs and Bayesian t-tests were

629   used to test the differences between experimental conditions.

References

Alilović, J., Lampers, E., Slagter, H. A., & van Gaal, S. (2023). Illusory object recognition is
either perceptual or cognitive in origin depending on decision confidence. *PLoS Biology*,
21(3), e3002009.

Angelucci, A., & Bressloff, P. C. (2006). Contribution of feedforward, lateral and feedback
connections to the classical receptive field center and extra-classical receptive field
surround of primate V1 neurons. *Progress in Brain Research*, *154*, 93–120.

Block, N. (2005). Two neural correlates of consciousness. *Trends in Cognitive Sciences*, *9*(2),
46–52.

Bosking, W. H., Zhang, Y., Schofield, B., & Fitzpatrick, D. (1997). Orientation selectivity and the
arrangement of horizontal connections in tree shrew striate cortex. *The Journal of
Neuroscience: The Official Journal of the Society for Neuroscience*, *17*(6), 2112–2127.

Brockhoff, L., Schindler, S., Bruchmann, M., & Straube, T. (2022). Effects of perceptual and
working memory load on brain responses to task-irrelevant stimuli: Review and implications
for future research. *Neuroscience and Biobehavioral Reviews*, *135*, 104580.

Brown, R., Lau, H., & LeDoux, J. E. (2019). Understanding the Higher-Order Approach to
Consciousness. *Trends in Cognitive Sciences*. https://doi.org/10.1016/j.tics.2019.06.009

Canales-Johnson, A., Beerendonk, L., Chennu, S., Davidson, M. J., Ince, R. A. A., & van Gaal,
S. (2023). Feedback information transfer in the human brain reflects bistable perception in
the absence of report. *PLoS Biology*, *21*(5), e3002120.

Cogitate Consortium, Ferrante, O., Gorska-Klimowska, U., Henin, S., Hirschhorn, R., Khalaf, A.,
Lepauvre, A., Liu, L., Richter, D., Vidal, Y., Bonacchi, N., Brown, T., Sripad, P., Armendariz,
M., Bendtz, K., Ghafari, T., Hetenyi, D., Jeschke, J., Kozma, C., … Melloni, L. (2023). An
adversarial collaboration to critically evaluate theories of consciousness. In *bioRxiv* (p.
2023.06.23.546249). https://doi.org/10.1101/2023.06.23.546249

655   Dehaene, S., Changeux, J.-P., Naccache, L., Sackur, J., & Sergent, C. (2006). Conscious,

656   preconscious, and subliminal processing: a testable taxonomy. *Trends in Cognitive*

657   *Sciences*, *10*(5), 204–211.

658   Dehaene, S., Sergent, C., & Changeux, J.-P. (2003). A neuronal network model linking

659   subjective reports and objective physiological data during conscious perception.

660   *Proceedings of the National Academy of Sciences of the United States of America*,

661   *100*(14), 8520–8525.

662   Delorme, A., & Makeig, S. (2004). EEGLAB: an open source toolbox for analysis of single-trial

663   EEG dynamics including independent component analysis. *Journal of Neuroscience*

664   *Methods*, *134*(1), 9–21.

665   Dienes, Z. (2007). Subjective measures of unconscious knowledge. In R. Banerjee & B. K.

666   Chakrabarti (Eds.), *Progress in Brain Research* (Vol. 168, pp. 49–269). Elsevier.

667   Fahrenfort, J. J., Scholte, H. S., & Lamme, V. A. F. (2007). Masking disrupts reentrant

668   processing in human visual cortex. *Journal of Cognitive Neuroscience*, *19*(9), 1488–1497.

669   Fahrenfort, J. J., van Driel, J., van Gaal, S., & Olivers, C. N. L. (2018). From ERPs to MVPA

670   Using the Amsterdam Decoding and Modeling Toolbox (ADAM). *Frontiers in Neuroscience*,

671   *12*, 368.

672   Fahrenfort, J. J., van Leeuwen, J., Olivers, C. N. L., & Hogendoorn, H. (2017). Perceptual

673   integration without conscious access. *Proceedings of the National Academy of Sciences of*

674   *the United States of America*, *114*(14), 3744–3749.

675   Fleming, S. M., & Lau, H. C. (2014). How to measure metacognition. *Frontiers in Human*

676   *Neuroscience*, *8*, 443.

677   Gilbert, C. D., & Wiesel, T. N. (1979). Morphology and intracortical projections of functionally

678   characterised neurones in the cat visual cortex. *Nature*, *280*(5718), 120–125.

679   Green, D. M., & Swets, J. A. (1966). *Signal detection theory and psychophysics. 455*.

680   https://psycnet.apa.org/fulltext/1967-02286-000.pdf

Groppe, D. M., Makeig, S., & Kutas, M. (2009). Identifying reliable independent components via

split-half comparisons. *NeuroImage*, *45*(4), 1199–1211.

Halgren, E., Mendola, J., Chong, C. D. R., & Dale, A. M. (2003). Cortical activation to illusory

shapes as measured with magnetoencephalography. *NeuroImage*, *18*(4), 1001–1009.

Hatamimajoumerd, E., Ratan Murty, N. A., Pitts, M., & Cohen, M. A. (2022). Decoding

perceptual awareness across the brain with a no-report fMRI masking paradigm. *Current*

Biology: CB. https://doi.org/10.1016/j.cub.2022.07.068

Haufe, S., Meinecke, F., Görgen, K., Dähne, S., Haynes, J.-D., Blankertz, B., & Bießmann, F.

(2014). On the interpretation of weight vectors of linear models in multivariate

neuroimaging. *NeuroImage*, *87*, 96–110.

Jiang, J., Correa, C. M., Geerts, J., & van Gaal, S. (2018). The relationship between conflict

awareness and behavioral and oscillatory signatures of immediate and delayed cognitive

control. *NeuroImage*, *177*, 11–19.

Joglekar, M. R., Mejias, J. F., Yang, G. R., & Wang, X.-J. (2018). Inter-areal Balanced

Amplification Enhances Signal Propagation in a Large-Scale Circuit Model of the Primate

Cortex. *Neuron*, *98*(1), 222-234.e8.

Kaernbach, C. (1991). Simple adaptive testing with the weighted up-down method. *Perception &*

Psychophysics, *49*(3), 227–229.

Kanai, R., Walsh, V., & Tseng, C.-H. (2010). Subjective discriminability of invisibility: a

framework for distinguishing perceptual and attentional failures of awareness.

Consciousness and Cognition, *19*(4), 1045–1057.

Kandel, E. R., Schwartz, J. H., Jessell, T. M., & Siegelbaum, S. (2000). *Principles of neural*

science. academia.edu.

https://www.academia.edu/download/30536508/neuroscience_syllabus.pdf

Kapadia, M. K., Ito, M., Gilbert, C. D., & Westheimer, G. (1995). Improvement in visual

sensitivity by changes in local context: parallel studies in human observers and in V1 of

707 alert monkeys. *Neuron*, *15*(4), 843–856.

708 Kapadia, M. K., Westheimer, G., & Gilbert, C. D. (2000). Spatial distribution of contextual

709  interactions in primary visual cortex and in visual perception. *Journal of Neurophysiology*,

710  *84*(4), 2048–2062.

711 King, J.-R., & Dehaene, S. (2014). Characterizing the dynamics of mental representations: the

712  temporal generalization method. *Trends in Cognitive Sciences*, *18*(4), 203–210.

713 Kok, P., Bains, L. J., van Mourik, T., Norris, D. G., & de Lange, F. P. (2016). Selective Activation

714  of the Deep Layers of the Human Primary Visual Cortex by Top-Down Feedback. *Current*

715  *Biology: CB*, *26*(3), 371–376.

716 Kok, P., & de Lange, F. P. (2014). Shape perception simultaneously up- and downregulates

717  neural activity in the primary visual cortex. *Current Biology: CB*, *24*(13), 1531–1535.

718 Lamme, V. A. F. (2010). How neuroscience will change our view on consciousness. *Cognitive*

719  *Neuroscience*, *1*(3), 204–220.

720 Lamme, V. A. F. (2020). Visual Functions Generating Conscious Seeing. *Frontiers in*

721  *Psychology*, *11*, 83.

722 Lamme, V. A. F., & Roelfsema, P. R. (2000). The distinct modes of vision offered by

723  feedforward and recurrent processing. *Trends in Neurosciences*, *23*(11), 571–579.

724 Lamme, V. A. F., Supèr, H., & Spekreijse, H. (1998). Feedforward, horizontal, and feedback

725  processing in the visual cortex. *Current Opinion in Neurobiology*, *8*(4), 529–535.

726 Lau, H. C. (2022). *In Consciousness we Trust: The Cognitive Neuroscience of Subjective*

727  *Experience*. Oxford University Press.

728 Lau, H. C., & Passingham, R. E. (2006). Relative blindsight in normal observers and the neural

729  correlate of visual consciousness. *Proceedings of the National Academy of Sciences of the*

730  *United States of America*, *103*(49), 18763–18768.

731 Lavie, N., & Dalton, P. (2014). Load theory of attention and cognitive control. *The Oxford*

732  *Handbook of Attention*, 56–75.

Lavie, N., & de Fockert, J. W. (2003). Contrasting effects of sensory limits and capacity limits in

visual selective attention. *Perception & Psychophysics*, *65*(2), 202–212.

Lee, T. S., & Nguyen, M. (2001). Dynamics of subjective contour formation in the early visual

cortex. *Proceedings of the National Academy of Sciences of the United States of America*,

98(4), 1907–1911.

Li, Z. (1998). A neural model of contour integration in the primary visual cortex. *Neural*

Computation, *10*(4), 903–940.

Liang, H., Gong, X., Chen, M., Yan, Y., Li, W., & Gilbert, C. D. (2017). Interactions between

feedback and lateral connections in the primary visual cortex. *Proceedings of the National*

Academy of Sciences of the United States of America, *114*(32), 8637–8642.

Luck, S. J., Vogel, E. K., & Shapiro, K. L. (1996). Word meanings can be accessed but not

reported during the attentional blink. *Nature*, *383*(6601), 616–618.

Maris, E., & Oostenveld, R. (2007). Nonparametric statistical testing of EEG- and MEG-data.

Journal of Neuroscience Methods, *164*(1), 177–190.

Marti, S., King, J.-R., & Dehaene, S. (2015). Time-Resolved Decoding of Two Processing

Chains during Dual-Task Interference. *Neuron*, *88*(6), 1297–1307.

Mashour, G. A., Roelfsema, P., Changeux, J.-P., & Dehaene, S. (2020). Conscious Processing

and the Global Neuronal Workspace Hypothesis. *Neuron*, *105*(5), 776–798.

Merikle, P. M., Smilek, D., & Eastwood, J. D. (2001). Perception without awareness:

perspectives from cognitive psychology. *Cognition*, *79*(1–2), 115–134.

Meuwese, J. D. I., van Loon, A. M., Lamme, V. A. F., & Fahrenfort, J. J. (2014). The subjective

experience of object recognition: comparing metacognition for object detection and object

categorization. *Attention, Perception & Psychophysics*, *76*(4), 1057–1068.

Mudrik, L., Faivre, N., & Koch, C. (2014). Information integration without awareness. *Trends in*

Cognitive Sciences, *18*(9), 488–496.

Northoff, G., & Lamme, V. A. F. (2020). Neural signs and mechanisms of consciousness: Is

there a potential convergence of theories of consciousness in sight? *Neuroscience and*

Biobehavioral Reviews, *118*, 568–587.

Nuiten, S. A., Canales-Johnson, A., Beerendonk, L., Nanuashvili, N., Fahrenfort, J. J.,

Bekinschtein, T., & van Gaal, S. (2021). Preserved sensory processing but hampered

conflict detection when stimulus input is task-irrelevant. *ELife*, *10*.

https://doi.org/10.7554/eLife.64431

Oostenveld, R., Fries, P., Maris, E., & Schoffelen, J.-M. (2011). FieldTrip: Open source software

for advanced analysis of MEG, EEG, and invasive electrophysiological data. *Computational*

Intelligence and Neuroscience, *2011*, 156869.

Pak, A., Ryu, E., Li, C., & Chubykin, A. A. (2020). Top-Down Feedback Controls the Cortical

Representation of Illusory Contours in Mouse Primary Visual Cortex. *The Journal of*

Neuroscience: The Official Journal of the Society for Neuroscience, *40*(3), 648–660.

Peters, M. A., & Lau, H. (2016). Correction: Human observers have optimal introspective access

to perceptual processes even for visually masked stimuli. *ELife*, *5*.

https://doi.org/10.7554/eLife.16332

Pitts, M. A., Lutsyshyna, L. A., & Hillyard, S. A. (2018). The relationship between attention and

consciousness: an expanded taxonomy and implications for 'no-report' paradigms.

Philosophical Transactions of the Royal Society of London. Series B, Biological Sciences,

373(1755), 20170348.

Raymond, J. E., Shapiro, K. L., & Arnell, K. M. (1992). Temporary suppression of visual

processing in an RSVP task: an attentional blink? *Journal of Experimental Psychology.*

Human Perception and Performance, *18*(3), 849–860.

Ridderinkhof, K. R., Ullsperger, M., Crone, E. A., & Nieuwenhuis, S. (2004). The role of the

medial frontal cortex in cognitive control. *Science*, *306*(5695), 443–447.

Roelfsema, P. R. (2006). Cortical algorithms for perceptual grouping. *Annual Review of*

Neuroscience, *29*, 203–227.

Roelfsema, P. R. (2023). Solving the binding problem: Assemblies form when neurons enhance

their firing rate-they don't need to oscillate or synchronize. *Neuron*, *111*(7), 1003–1019.

Schmidt, K. E., Goebel, R., Löwel, S., & Singer, W. (1997). The perceptual grouping criterion of

colinearity is reflected by anisotropies of connections in the primary visual cortex. *The*

European Journal of Neuroscience, *9*(5), 1083–1089.

Schmidt, T. (2015). Invisible Stimuli, Implicit Thresholds: Why Invisibility Judgments Cannot be

Interpreted in Isolation. *Advances in Cognitive Psychology / University of Finance and*

Management in Warsaw, *11*(2), 31–41.

Sergent, C., Baillet, S., & Dehaene, S. (2005). Timing of the brain events underlying access to

consciousness during the attentional blink. *Nature Neuroscience*, *8*(10), 1391–1400.

Sergent, C., Corazzol, M., Labouret, G., Stockart, F., Wexler, M., King, J. -R., Meyniel, F., &

Pressnitzer, D. (2021). Bifurcation in brain dynamics reveals a signature of conscious

processing independent of report. *Nature Communications*, *12*(1), 1149.

Sergent, C., & Dehaene, S. (2004). Is consciousness a gradual phenomenon? Evidence for an

all-or-none bifurcation during the attentional blink. *Psychological Science*, *15*(11), 720–728.

Seth, A. K., Dienes, Z., Cleeremans, A., Overgaard, M., & Pessoa, L. (2008). Measuring

consciousness: relating behavioural and neurophysiological approaches. *Trends in*

Cognitive Sciences, *12*(8), 314–321.

Shanks, D. R. (2017). Regressive research: The pitfalls of post hoc data selection in the study

of unconscious mental processes. *Psychonomic Bulletin & Review*, *24*(3), 752–775.

Shapiro, K. L., Raymond, J. E., & Arnell, K. M. (1997). The attentional blink. *Trends in Cognitive*

Sciences, *1*(8), 291–296.

Stein, T., Kaiser, D., Fahrenfort, J. J., & van Gaal, S. (2021). The human visual system

differentially represents subjectively and objectively invisible stimuli. *PLoS Biology*, *19*(5),

e3001241.

Stettler, D. D., Das, A., Bennett, J., & Gilbert, C. D. (2002). Lateral connectivity and contextual

interactions in macaque primary visual cortex. *Neuron*, *36*(4), 739–750.

Thaler, L., Schütz, A. C., Goodale, M. A., & Gegenfurtner, K. R. (2013). What is the best fixation

target? The effect of target shape on stability of fixational eye movements. *Vision*

Research, *76*, 31–42.

Tsuchiya, N., Wilke, M., Frässle, S., & Lamme, V. A. F. (2015). No-Report Paradigms:

Extracting the True Neural Correlates of Consciousness. *Trends in Cognitive Sciences*,

19(12), 757–770.

van Driel, J., Olivers, C. N. L., & Fahrenfort, J. J. (2021). High-pass filtering artifacts in

multivariate classification of neural time series data. *Journal of Neuroscience Methods*, *352*,

109080.

van Gaal, S., Ridderinkhof, K. R., Fahrenfort, J. J., Scholte, H. S., & Lamme, V. A. F. (2008).

Frontal cortex mediates unconsciously triggered inhibitory control. *The Journal of*

Neuroscience: The Official Journal of the Society for Neuroscience, *28*(32), 8053–8062.

van Vugt, B., Dagnino, B., Vartak, D., Safaai, H., Panzeri, S., Dehaene, S., & Roelfsema, P. R.

(2018). The threshold for conscious report: Signal loss and response bias in visual and

frontal cortex. *Science, 360*(6388), 537–542.

Weaver, M. D., Fahrenfort, J. J., Belopolsky, A., & van Gaal, S. (2019). Independent Neural

Activity Patterns for Sensory- and Confidence-Based Information Maintenance during

Category-Selective Visual Processing. *ENeuro*, *6*(1).

https://doi.org/10.1523/ENEURO.0268-18.2018

Wokke, M. E., Vandenbroucke, A. R. E., Scholte, H. S., & Lamme, V. A. F. (2013). Confuse

your illusion: feedback to early visual cortex contributes to perceptual completion.

Psychological Science, *24*(1), 63–71.

Wyatte, D., Jilk, D. J., & O'Reilly, R. C. (2014). Early recurrent feedback facilitates visual object

recognition under challenging conditions. *Frontiers in Psychology*, *5*, 674.

Yi, D.-J., Woodman, G. F., Widders, D., Marois, R., & Chun, M. M. (2004). Neural fate of

ignored stimuli: dissociable effects of perceptual and working memory load. *Nature*

Neuroscience, *7*(9), 992–996.

Zivony, A., & Lamy, D. (2022). What processes are disrupted during the attentional blink? An

integrative review of event-related potential research. *Psychonomic Bulletin & Review*,

29(2), 394–414.