Perceptual versus attentional impairments of conscious access: Distinct neural mechanisms despite equal task performance

Samuel Noorman[1,2,*], Timo Stein[1,2], Johannes J. Fahrenfort[1,2,3,**], Simon van Gaal[1,2,**]

[1]Department of Psychology, University of Amsterdam, Amsterdam, The Netherlands
[2]Amsterdam Brain and Cognition, University of Amsterdam, Amsterdam, The Netherlands
[3]Department of Applied and Experimental Psychology, Vrije Universiteit Amsterdam, Amsterdam, The Netherlands
[*]Correspondence: sgnoorman@gmail.com
[**]Shared senior authorship

This research was supported by a grant from the H2020 European Research Council (ERC STG 715605, SVG).

Abstract

This study investigates failures in conscious access resulting from either weak sensory input (perceptual impairments) or unattended input (attentional impairments). Participants viewed a Kanizsa stimulus with or without an illusory triangle within a rapid serial visual presentation of distractor stimuli. We designed a novel Kanizsa stimulus that contained additional ancillary features of different complexity (local contrast and collinearity) that were independently manipulated. Perceptual performance on the Kanizsa stimulus (presence vs. absence of an illusion) was equated between the perceptual (masking) and attentional (attentional blink) manipulation to circumvent common confounds related to conditional differences in task performance. We trained and tested classifiers on electroencephalogram (EEG) data to reflect the processing of specific stimulus features, with increasing levels of complexity. We show that late stages of processing (~200-250 ms), reflecting the integration of complex stimulus features (collinearity, illusory triangle), were impaired by masking but spared by the attentional blink. In contrast, decoding of local contrast (the spatial arrangement of stimulus features) was observed early in time (~80 ms) and was left largely unaffected by either manipulation. These results replicate previous work showing that feedforward processing is largely preserved under both perceptual and attentional impairments. Crucially however, under matched levels of performance, only attentional impairments left the processing of more complex visual features relatively intact, likely related to spared lateral and local feedback processes during inattention. These findings reveal distinct neural mechanisms associated with perceptual and attentional impairments and thus contribute to a comprehensive understanding of distinct neural stages leading to conscious access.

Introduction

Conscious access to sensory input can be impaired in two distinct ways (Dehaene et al., 2006; Lamme, 2010; Mashour et al., 2020; Northoff & Lamme, 2020). Sensory input may lack sufficient bottom-up strength, or top-down attention may be directed elsewhere. Despite both cases resulting in a failure to perceive a stimulus, their underlying neural mechanisms are thought to be remarkably different. Influential theories of consciousness such as global neuronal workspace and recurrent processing theory propose four stages of neural information processing associated with distinct levels of bottom-up signal strength and top-down attention. These four stages can be investigated empirically by crossing "perceptual" manipulations that degrade the strength of sensory input (e.g., reducing stimulus contrast, masking, continuous flash suppression) with "attentional" manipulations that affect top-down attention (e.g., attentional blink, inattentional blindness, **Fig. 1A**).

According to these theoretical models, all stimuli elicit feedforward information transfer from lower- to higher-level brain regions (**Fig. 1A**, bottom row), but recurrent interactions are initiated only for stimuli with sufficient bottom-up strength (**Fig. 1A**, top row). If stimuli are sufficiently strong and top-down attention is available, neural processing crosses a threshold, triggering a process termed global ignition, facilitating widespread recurrent interactions between frontal, parietal and sensory cortices, yielding conscious access (**Fig. 1A**, top left). Crucially, when top-down attention is lacking, frontoparietal network ignition is prevented, while local recurrent interactions within sensory brain regions remain relatively intact ("attentional blindness", **Fig. 1A**, top right) (Dehaene et al., 2003; Marti et al., 2015; Sergent et al., 2005; Zivony & Lamy, 2022). Weak stimuli result in the absence, or a substantial reduction, of local recurrent interactions ("perceptual blindness", **Fig. 1A**, bottom left) (Fahrenfort et al., 2007; Joglekar et al., 2018; van Gaal et al., 2008; van Vugt et al., 2018).

Although this framework is at the heart of influential theories of consciousness, the four stages of the model and their underlying neural mechanisms have rarely been investigated simultaneously within the same study (for an exception see Fahrenfort et al., 2017). One challenge with comparing results across different studies, or even within a study, is that perceptual manipulations tend to impair overall task performance more than attentional manipulations, so that it may not be surprising to find that perceptual manipulations interrupt recurrent interactions to a greater extent than attentional manipulations. Given the right parameter settings, perceptual manipulations can be used to induce chance-level performance, while it is not possible to use attentional manipulations to drive behavioral performance down to chance, even when they are optimized fully. For this reason, attentional manipulations are often combined with post-hoc selection of a subset of "blind" trials (e.g., attentional blink [AB]) or subjects (e.g., inattentional blindness) based on subjective awareness reports, a methodologically questionable practice that is susceptible to criterion confounds and introduces sampling bias that leads to underestimation of consciousness (Fahrenfort et al., 2024; Peters & Lau, 2016; T. Schmidt, 2015; Shanks, 2017).

Thus, when comparing perceptual to attentional manipulations, any (neural) effect could reflect differences in task performance rather than genuine differences between manipulations and hence stages in the model depicted in **Figure 1A**. While these issues with comparing conditions that differ in task performance in consciousness research have been acknowledged

(Lau, 2022), they have rarely been addressed experimentally (Kanai et al., 2010; Lau &
Passingham, 2006; Meuwese et al., 2014). For example, Fahrenfort and colleagues (2017)
found that illusory surfaces could be decoded from electroencephalogram (EEG) data during the
AB but not during masking. This was taken as evidence that local recurrent interactions,
supporting perceptual integration, were preserved during inattention but abolished by masking.
However, masking had a much stronger behavioral effect than the AB, effectively reducing task
performance to chance level. Indeed, a control experiment using weaker masking, which
resulted in behavioral performance well above chance similar to the main experiment's AB
condition, revealed some evidence for preserved local recurrent interactions also during
masking. However, these conditions were tested in separate experiments with small samples,
precluding a direct comparison of perceptual vs. attentional impairments at matched levels of
behavioral performance. To test and further refine the four-stage model of consciousness in
humans, the present study compared all stages within the same experimental setup, analyzing
all trials and including all participants while carefully matching task performance between a
perceptual manipulation (masking) and an attentional manipulation (attentional blink).
To reveal neural mechanisms associated with perceptual and attentional impairments,
we combined a novel visual stimulus with features of different complexity with time-resolved
decoding of these visual features from EEG data (**Fig. 1B**). The target stimulus differed along
three dimensions (illusory triangle, non-illusory triangle, and local contrast) that were
independently manipulated. First, "Pac-Man" stimuli could create either the perception of an
illusory surface in the shape of a Kanizsa triangle when aligned, or not, when misaligned.
Second, additional "two-legged white circles" could form either a non-illusory triangle when their
line segments were aligned, or not, when the "legs" were misaligned. Third, for the local contrast
manipulation, the whole stimulus was rotated by 180 degrees, so that the same retinotopic
positions had high contrast in one spatial configuration and low contrast when flipped 180
degrees.
Human neuroimaging and direct neural recordings in animals have shown that the
Kanizsa illusion is supported by both lateral and feedback connections (Halgren et al., 2003;
Kok et al., 2016; Kok & de Lange, 2014; Lee & Nguyen, 2001; Pak et al., 2020; Wokke et al.,
2013), while the processing of collinear line elements (as in the non-illusory triangle) primarily
relies on lateral connections (Bosking et al., 1997; Gilbert & Wiesel, 1979; Li, 1998; Liang et al.,
2017; K. E. Schmidt et al., 1997; Stettler et al., 2002). Differences in local contrast are
processed early in the visual system through feedforward connections and are resistant to
masking (Fahrenfort et al., 2007, 2017; Kandel et al., 2000; Lamme & Roelfsema, 2000).
Decoding the stimulus conditions of the illusory triangle, non-illusory triangle, and local contrast
at different points in time, in combination with the associated topography, therefore served as
putative markers of these distinct neural processes (**Fig. 1B)** and allowed us to test whether the
effects of masking and the attentional blink followed the predictions of the four-stage model of
consciousness.
120

121
122
Figure 1. Experimental design and behavior. *(A) Perceptual vs. attentional blindness in the four-stage*
model. A stimulus with low bottom-up strength (masked) is thought to interrupt local recurrent processing
in sensory areas while leaving feedforward processing largely intact, while inattention (induced by the
attentional blink) is thought to interrupt global recurrent processing between frontoparietal areas and
sensory areas, while leaving local recurrent processing within sensory areas largely intact. Reprinted from
Dehaene et al. (2006) *with permission from Elsevier. (B) Target stimulus set and decoding analyses. (C)*
Trial design. Note that the central fixation cross is not displayed for readability. (D) Perceptual
performance refers to participants' ability to detect the Kanizsa illusion. Metacognition refers to
participants' ability to evaluate their own performance using confidence judgments. Both perceptual
performance and metacognition are measured as the area under the receiver operating characteristic
curve (AUC). Error bars are mean ± standard error of the mean. Individual data points are plotted using
*low contrast. Ns is not significant (P≥0.477, BF_{01}≥4.05). *P≤0.001.*

135 Results

136 Masking and the attentional blink were matched in perceptual performance and
137 metacognition

We recorded the EEG signal of 30 participants who identified the presence or absence of an
illusory surface (triangle) in two black target stimuli (T1 and T2) that were presented amongst
red distractors in a rapid serial visual presentation task (**Fig. 1C**). We manipulated the visibility
of T2 in two ways: masking the stimulus and manipulating attention, resulting in a 2×2 factorial

design (**Fig. 1A**). Specifically, T2 could be either masked or unmasked (perceptual
manipulation), and T2 could be presented at either a long interval (900 ms) or a short interval
(200 or 300 ms) after T1, inducing an attentional blink (AB) effect for the short T1-T2 intervals
(Raymond et al., 1992). This design resulted in four conditions, which we from now on refer to
as the masked condition (T2 masked at the long T1-T2 interval), AB condition (T2 unmasked at
the short T1-T2 interval), no-manipulations condition (T2 unmasked at the long T1-T2 interval),
and both-manipulations condition (T2 masked at the short T1-T2 interval). At the end of a trial,
participants indicated whether each target (T1 and T2) contained an illusory surface or not.
Importantly, mask contrast in the masked condition was adjusted using a staircasing procedure
to match performance in the AB condition, ensuring comparable perceptual performance in the
masked and the AB condition across participants (see Methods for more details).
Conscious access can be assessed not only based on perceptual performance but also
through metacognitive sensitivity, the ability to evaluate one's own performance (Brown et al.,
2019; Dienes, 2007; Fleming & Lau, 2014; Lau & Passingham, 2006; Merikle et al., 2001; Seth
et al., 2008). Participants in our study provided confidence ratings on a 3-point scale (low,
medium, high) for their responses to T2. To ensure that the distribution of confidence ratings in
the performance-matched masked and AB condition was not influenced by participants
anchoring their confidence ratings to the unmatched very easy and very difficult conditions (no
and both manipulations condition, respectively), the masked and AB condition were presented
in the same experimental block, while the other block type included the no- and both-
manipulations condition.
We used area under the receiver operating characteristic (ROC) curve (AUC) as a
shared metric for perceptual performance (detection of the Kanizsa illusion), metacognitive
sensitivity, and EEG decoding (see Methods for details on the calculation of these measures). A
repeated-measures (rm) ANOVA with the factors masking (present/absent) and T1-T2 lag
(short/long) revealed, as expected, that both masking and the short T1-T2 lag impaired
perceptual performance ($F_{1,29}$=344.24, P<10^{-15}, BF$_{10}$=2.76×10^{13} and $F_{1,29}$=427.54, P<10^{-15},
BF$_{10}$=3.67×10^{13}) as well as metacognitive sensitivity ($F_{1,29}$=50.78, P<10^{-7}, BF$_{10}$=1.18×10^{5} and
$F_{1,29}$=47.83, P<10^{-6}, BF$_{10}$=3.28×10^{4}). Importantly, paired t-tests showed that we successfully
matched the key conditions, the masked condition (masked, long lag) and the AB condition
(unmasked, short lag) for perceptual performance (t_{29}=0.62, P=0.537, BF$_{01}$=4.30, **Fig. 1D**, left)
as well as for metacognitive sensitivity (t_{29}=0.72, P=0.477, BF$_{01}$=4.05; **Fig. 1D**, right, see **Fig. S1**
for signal detection theory related measures of performance). Thus, whereas in previous studies
task performance was considerably higher during the AB than during masking (e.g., Fahrenfort
et al., 2017), in the present study the masked and the AB condition were matched in both
measures of conscious access.

Masking and the attentional blink leave local contrast decoding largely intact

To derive markers of the different neural processes from the EEG data, for each stimulus
feature we trained linear discriminant classifiers on the T1 data and tested them on the T2 data.
Classifiers used preprocessed EEG activity (see Methods) across all electrodes. To leverage
the similarities between T1 and T2 in task and stimulus context, all main analyses used T1

training data for T2 decoding. This approach minimized possible differences in conscious
access and working memory demands between the training and test datasets.
For local contrast decoding, the classifier categorized stimuli as either pointing upwards
or pointing downwards, thereby effectively decoding the stimuli's local differences in contrast at
the top vs. bottom of the stimulus. Classification performance (AUC) over time was obtained,
with peak decoding accuracy in a 75-95 ms time window (**Fig. 2A** and **Fig. S2A**, top). The peak
in decoding accuracy was occipital in nature (see the covariance/class separability map of **Fig.**
2A) (Haufe et al., 2014), consistent with previous findings (Fahrenfort et al., 2017). We focused
our analyses on the averages of this time window. An rm ANOVA with the factors masking
(present/absent) and T1-T2 lag (short/long) revealed a weak but statistically significant effect of
masking on local contrast decoding, with the Bayes factor indicating only "anecdotal" evidence
($F_{1,29}$=6.51, P=0.016, BF_{10}=1.31), while the T1-T2 lag had no significant effect ($F_{1,29}$=0.32,
P=0.578, BF_{01}=3.45). A paired t-test yielded no evidence for a difference between the
performance matched conditions (masked vs. AB; t_{29}=1.42, P=0.166, BF_{01}=2.08; **Fig. 2C**, "Local
contrast: 75-95 ms"). These results are in line with theoretical proposals and empirical findings
that suggest limited effects of masking and attentional manipulations on perceptual processes
that rely on feedforward connections (Dehaene et al., 2006; Fahrenfort et al., 2007, 2017;
Lamme, 2010), contrasting with the robust effects of these consciousness manipulations on
feedback processes reported in the following section.

Stronger effect of masking than the attentional blink on early but not on late illusion decoding

Next, we trained a linear classifier on the T1 data to discriminate between the presence and
absence of the Kanizsa illusion and tested it on each of the four conditions of the T2 data. The
average of all four conditions revealed two prominent peaks in decoding accuracy, consistent
with previous research (**Fig. S2C**, top) (Fahrenfort et al., 2017). Based on this previous study,
our analyses focused on the averages of the two time windows that encompassed these two
peaks: specifically, from 200 to 250 ms and from 375 to 475 ms after target stimulus onset. The
covariance/class separability maps (**Fig. 2B**) indicated that during the earlier time window (200–
250 ms) classification mainly relied on occipital electrodes. Considering its timing, topology and
previous findings, this neural event likely reflects early sensory processes and may thus
represent a marker for local recurrent processing (Fahrenfort et al., 2017; Kok et al., 2016;
Roelfsema, 2006; Wokke et al., 2013; Wyatte et al., 2014). The timing and topology of the later
neural event (375–475 ms) overlapped with the event-related potential component P300 (**Fig.**
S4), which is associated with conscious access (Fahrenfort et al., 2017; Sergent et al., 2005;
Weaver et al., 2019) and may thus represent a marker for global recurrent processing.
We tested how the consciousness manipulations affected these putative markers of local
and global recurrent processing (**Fig. 2C**), again conducting rm ANOVAs with the factors
masking (present/absent) and T1-T2 lag (short/long) that we followed-up on with paired t-tests
comparing the matched conditions (masked vs. AB). Importantly, we observed a distinct
difference between the performance matched conditions in the first decoding peak, which was
significantly impaired by both masking ($F_{1,29}$=162.62, P<10^{-12}, BF_{10}=5.86×10^{10}) and T1-T2 lag
($F_{1,29}$=78.07, P<10^{-8}, BF_{10}=6.03×10^{6}), but importantly, it was more affected by masking than by

T1-T2 lag (interaction, $F_{1,29}=18.67$, $P<0.001$, $BF_{10}=149.92$) (**Fig. 2C**, "Illusory triangle: 200-250
ms"). Directly comparing the performance matched conditions, the first decoding peak was more
strongly impaired by masking than by the AB ($t_{29}=4.66$, $P<10^{-4}$, $BF_{10}=3.81$). This suggests that
the AB allowed for greater residual local recurrent processing than masking, replicating the key
finding by Fahrenfort and colleagues (2017). Importantly, the present result demonstrates that
this effect reflects the difference between the perceptual vs. attentional manipulation rather than
differences in behavior, as the masked condition and the AB condition were matched for
perceptual performance and metacognition.
The pattern of results of the second peak was notably different. The second decoding
peak was impaired by both masking ($F_{1,29}=49.75$, $P<10^{-7}$, $BF_{10}=8.60\times10^4$) and T1-T2 lag
($F_{1,29}=78.48$, $P<10^{-9}$, $BF_{10}=4.32\times10^5$), and the matched conditions (masked and AB condition)
did not differ significantly from each other ($t_{29}=0.21$, $P=0.837$, $BF_{01}=5.04$) (**Fig. 2C**, "Illusory
triangle: 375-475 ms"). Furthermore, another rm ANOVA comparing the first and second
decoding peak between the matched conditions (masked/AB) revealed a significant interaction,
reflecting a larger difference between the AB and the masked condition in the first than in the
second decoding peak ($F_{1,29}=31.53$, $P<10^{-5}$, $BF_{10}=1693.17$). The pattern of behavioral results,
both for perceptual performance and metacognitive sensitivity, closely resembled the second
decoding peak: sensitivity in all three metrics dropped from the no-manipulations condition to
the masked and AB conditions, while sensitivity did not differ significantly between these
performance-matched conditions (**Fig. 2C**). Two additional rm ANOVAs with the factors
measure (behavior, second EEG decoding peak) and condition (no-manipulations, masked,
AB)[1] for perceptual performance and metacognitive sensitivity revealed no significant interaction
(performance: $F_{2,58}=0.27$, $P=0.762$, $BF_{01}=8.47$; metacognition: $F_{2,58}=0.54$, $P=0.586$, $BF_{01}=6.04$).
This similarity between behavior and EEG decoding replicates the findings of Fahrenfort and
colleagues (2017) who also found a striking similarity between late Kanizsa decoding (at 406
ms) and behavioral Kanizsa detection. These results indicate that global recurrent processing at
these later points in time reflected conscious access to the Kanizsa illusion.
Additional rm ANOVAs comparing the effect of the consciousness manipulations on local
contrast decoding with their effects on the first and second illusion decoding peak showed that,
compared to contrast decoding, both manipulations had stronger effects on the first illusion
decoding peak (masking: $F_{1,29}=99.35$, $P<10^{-10}$, $BF_{10}=1.73\times10^8$; AB: $F_{1,29}=38.95$, $P<10^{-6}$,
$BF_{10}=1.43\times10^4$) and on the second illusion decoding peak (masking: $F_{1,29}=22.25$, $P<10^{-4}$,
$BF_{10}=477.25$; AB: $F_{1,29}=49.60$, $P<10^{-7}$, $BF_{10}=3.59\times10^4$). In the light of evidence showing that
unconscious processing is susceptible to conscious top-down influences (Kentridge et al., 2004;
Kiefer & Brendel, 2006; Naccache et al., 2002), we ran control analyses showing that early local
contrast decoding was not improved by rendering contrast task-relevant (see **Supplementary
Information** and **Fig. S5**), indicating that these differences between illusion and contrast
decoding did not reflect differences in task-relevance. This suggests that masking and the AB
specifically influenced local and global recurrent processing respectively, while early
feedforward processing was less affected.

---

[1] We excluded the both-manipulations condition from this analysis due to scale restrictions: in this
condition, EEG decoding at the second peak was at chance, while behavioral performance was above
chance, leaving more room for behavior to drop from the masked and AB condition.

265   While the findings presented so far used the T1 data to train the classifiers, we
266 replicated all key findings when training the classifiers on an independent training set where
267 individual stimuli were presented in isolation (**Fig. 3A,** results in the **Supplementary**
268 **Information** and **Fig. S6**).

269
270

271
272

Figure 2. Local contrast and illusory triangle decoding using first targets as training data. (A) Local
contrast decoding. (B) Illusory Kanizsa triangle decoding. For both features, covariance/class separability
maps reflecting underlying neural sources are shown. Below these maps: mean decoding performance,
area under the receiver operating characteristic curve (AUC), over time ± standard error of the mean
(SEM). Thick lines differ from chance: P<0.05, cluster-based permutation test. (C) Normalized (Z-scored)
AUC for every measure: mean decoding time windows and two types of behavior. Each measure is Z-
scored separately. Perceptual performance refers to participants' ability to detect the Kanizsa illusion.
Metacognition refers to participants' ability to evaluate their own performance using confidence
judgments. See Figure S3 for the same analyses but then for off-diagonal decoding profiles. Error bars
are mean ± SEM. Individual data points are plotted using low contrast. Ns is not significant (P≥0.166,
*BF_{01}≥2.07). *P≤0.002.*

Distinguishing collinearity and illusion-specific processing

The performance matched masked and AB condition differed only in the first illusion decoding
peak, our putative marker of local recurrent processing, which was markedly more impaired in

the masked than in the AB condition. Next, we determined whether this effect reflected relatively
preserved processing of collinearity or of the Kanizsa illusion during attentional impairment
specifically. In our target stimulus, collinearity was present when the Pac-Man stimuli aligned,
inducing the illusory Kanizsa triangle. Notably, collinearity was also present when the line
segments of the "two-legged white circles" of the stimulus aligned, forming the non-illusory
triangle. Note that the line segments making up the triangle were equally long, and the spaces
between them equally large, for the illusory and non-illusory triangles. The addition of this
element of collinearity to our stimuli was a key difference to the study by Fahrenfort and
colleagues (2017), allowing us to compare non-illusory triangle decoding to illusory triangle
decoding in order to distinguish between collinearity and illusion-specific processing.
However, in the main RSVP task the illusory triangle was task-relevant, while non-
illusory triangles were always task-irrelevant. To equate the effect of task-relevance in the
comparison, classifiers were trained on an independent training set in which each relevant
stimulus feature was task-relevant. Specifically, in different experimental blocks participants
focused either on local contrast, the non-illusory triangle, or the illusory triangle (**Fig. 3A**). We
trained a classifier to distinguish between the presence and absence of the task-relevant non-
illusory triangle (collinearity-only) and the same was done for the task-relevant illusory triangle
(collinearity-plus-illusion). Then, both classifiers were used to decode the presence vs. absence
of the illusory triangle in the main RSVP task (cross-task-decoding approach), which ensured
that both training and testing were always performed on task-relevant stimuli. By comparing
Kanizsa decoding performance in the RSVP task based on the collinearity-only classifier with
decoding performance based on the collinearity-plus-illusion classifier, we effectively subtracted
out the contribution of collinearity processing to illusion decoding, thereby isolating illusion-
specific processing.

Preserved collinearity and illusion-specific processing during the attentional blink

To determine a time window for (the start of) collinearity-only processing, we first trained and
tested classifiers to distinguish present vs. absent non-illusory triangles (training and testing on
non-illusory triangles only). We trained two classifiers, one on the T1 in the RSVP task and one
on the independent training set (**Fig. S2**) and tested their performance in decoding the non-
illusory triangle in the T2 data, where this non-illusory triangle was always task-irrelevant. The
results of both classifiers converged, and these analyses revealed a peak in decoding accuracy
at ~164 ms (yielding a collinearity-only time window between 140–190 ms), right before the 200-
250 ms time window of the first illusion decoding peak (**Fig. S2B**). This 140-190 ms collinearity-
only time window was also evident when classifiers were used to categorize the presence vs.
absence of the Kanizsa illusion (**Fig. S2C**, first time window), as well as in previous research
(Fahrenfort et al., 2017), suggesting that collinearity processing also contributes to Kanizsa
decoding.
We examined how decoding the presence vs. absence of the Kanizsa illusion in the
RSVP task was affected by the consciousness manipulations, while training classifiers either on
the illusory (collinearity-plus-illusion) or non-illusory (collinearity-only) triangle from the
independent training set (as described above). **Figure 3B** shows the decoding accuracies of

these analyses across the entire time window (purple and green lines). Follow-up analyses were
performed using the 140-190 ms collinearity-only window (see the previous paragraph). An rm
ANOVA with the factors masking (present/absent), T1-T2 lag (short/long), and training set
(illusory/non-illusory triangle) revealed that both masking and the short T1-T2 lag impaired
decoding accuracy (masking: $F_{1,29}$=58.95, P<10^{-7}, BF_{10}=8.22×10^5; T1-T2 lag: $F_{1,29}$=24.90, P<10^{-4}, BF_{10}=776.00). Furthermore, paired t-tests comparing the matched conditions (masked vs. AB
condition) confirmed that decoding accuracy was more impaired in the masked than AB
condition, both when training was done on the illusory (t_{29}=2.26, P=0.031, BF_{01}=0.58) and non-
illusory triangle (t_{29}=2.78, P=0.009, BF_{01}=0.21; **Fig. 3C**, "140-190 ms"). Focusing on the
performance matched conditions and the role of the training set, an rm ANOVA with the factors
condition (masked/AB) and training set (illusory/non-illusory triangle) on T2 illusory triangle
decoding revealed no significant effect of training set ($F_{1,29}$=0.09, P=0.766, BF_{01}=4.22), i.e., no
evidence for illusion-specific processing, and no significant interaction ($F_{1,29}$=0.04, P=0.837,
BF_{01}=3.74). This demonstrates that neural processing in the 140-190 ms window indeed
reflected collinearity-only rather than illusion-specific processing.
The marker for illusion-specific processing emerged later, namely in the 200-250 ms
time window that encompassed the first illusion decoding peak reported above. As can be seen
in **Figure 3B**, when no consciousness manipulations were applied (unmasked, long T1-T2 lag),
there was significant illusion-specific processing, i.e., T2 illusory triangle decoding was better
after training a classifier on the Kanizsa illusion (collinearity-plus-illusion, green line) than after
training a classifier on the non-illusory triangle (collinearity-only, purple line) (t_{29}=4.22, P<0.001,
BF_{10}=128.47). Turning to the performance matched conditions, an rm ANOVA with the factors
condition (masked/AB) and training set (illusory/non-illusory triangle) on T2 illusory triangle
decoding yielded a significant effect of condition ($F_{1,29}$=16.59, P<0.001, BF_{10}=90.73), with
overall better decoding for the AB than for the masked condition, and importantly, a significant
interaction ($F_{1,29}$=4.65, P=0.039, BF_{10}=2.19). **Figure 3B** shows that decoding after training on
illusory triangles (collinearity-plus-illusion) was better than after training on non-illusory triangles
(collinearity-only) for the AB (t_{29}=2.51, P=0.018, BF_{10}=2.78, **Fig. 3B**, top right) but not for the
masked condition (t_{29}=-0.02, P=0.982, BF_{01}=5.14, **Fig. 3B**, bottom left). Thus, while illusion-
specific processing was evident in the AB condition, it was fully abolished in the masked
condition. Illusion-specific processing was not even affected by the AB, as an rm ANOVA with
the factors condition (no manipulations/AB) and training set (illusory/non-illusory triangle)
revealed no significant interaction ($F_{1,29}$=1.33, P=0.259, BF_{01} =2.30). The classifier trained on
non-illusory triangles (collinearity-only) also performed better during the AB than during the
masked condition (t_{29}=2.85, P=0.008, BF_{10}=5.43 **Fig. 3C**, "200-250 ms", purple line), hence both
collinearity-only and illusion-specific processing were most strongly impaired by masking.
Control analyses presented in the **Supplementary information (Fig. S7)** demonstrate that
cross-feature-decoding can indeed isolate illusion-specific processes and does not reflect other,
e.g., task- or attention-related, processes (for further control analyses testing the effect of task-
relevance on local contrast processing, see **Supplementary Information** and **Fig. S5**).
Finally, we focused on the late 375-475 ms window, encompassing the second illusion
decoding peak, which was directly linked to behavioral performance (see above, **Fig. 3B**, last
time window). Similarly, as above, illusory triangle decoding was now based on training the
decoder on the illusory triangles from the independent training set. Replicating our main

analysis, classifier performance was impaired by both masking ($F_{1,29}$=6.01, P=0.020, BF_{10}=2.37)
and T1-T2 lag ($F_{1,29}$=10.10, P=0.004, BF_{10}=10.12), with no significant differences between the
two performance matched conditions (t_{29}=-0.63, P=0.531, BF_{01}=4.27) (**Fig. 3C**, "375-475 ms").
376

377
378
379 *Figure 3. Separating collinearity and illusion-specific processes using the independent training*
380 *dataset. (A) Trial design used for obtaining the independent training dataset. (B) Illusory triangle*
381 *decoding, after training classifiers on the independent training set on either the non-illusory (collinearity-*

Discussion

We demonstrate that perceptual and attentional manipulations, despite similarly impairing conscious access, exhibit distinct neural profiles in the brain. To investigate this difference, we decoded different visual features targeting distinct stages of visual processing from human EEG activity, while carefully matching a masked condition and an attentional blink (AB) condition in perceptual and metacognitive performance. Therefore, any observed neural difference between the masked and the AB condition could be unequivocally attributed to differences between attentional and perceptual manipulations of conscious access. While decoding of local contrast was barely affected by the two consciousness manipulations, early (200–250 ms, occipital) decoding of the illusory Kanizsa triangle was markedly more impaired in the masked than in the AB condition (Fahrenfort et al., 2017), even though behavior was matched. By contrast, later (375–475 ms, centroparietal) illusion decoding was similarly impaired by masking and by the AB, closely resembling their matched effects on behavior. Furthermore, we differentiated between collinearity-only and illusion-specific processing and found that both processes were more strongly impaired by masking than by the AB. Notably, illusion-specific processing was unaffected by the AB, but completely abolished by masking.

Decoding of these different stimulus features at different points in time, together with their topography, may be regarded as markers of distinct neural processes. Based on neurophysiology and previous neuroimaging studies, the early decoding peak for local contrast decoding (75–95 ms after target stimulus onset) likely reflects feedforward processing (Fahrenfort et al., 2007, 2017; Kandel et al., 2000; Lamme & Roelfsema, 2000). The first illusion decoding peak (200–250 ms) may be regarded as a marker of local recurrent processing, while the second illusion decoding peak (375–475 ms) likely reflects global recurrent processing (Fahrenfort et al., 2017). Thus, our findings suggest that both perceptual and attentional impairments leave feedforward processing largely intact and similarly impair global recurrent processing, while local recurrent processing is markedly more impaired by perceptual than by attentional impairments.

This pattern of results is consistent with a previous study that used EEG to decode Kanizsa-like illusory surfaces during masking and the AB (Fahrenfort et al., 2017). However, the present study also revealed some effects where Fahrenfort and colleagues (2017) failed to obtain statistical significance, likely reflecting the present study's considerably larger sample size and greater statistical power. For example, in the present study the marker for feedforward processing was weakly but significantly impaired by masking, and the marker for local recurrency was significantly impaired not only by masking but also by the AB, although to a

lesser extent. Most importantly, however, we replicated the key findings that local recurrent
processing was more strongly impaired by masking than by the AB, and that global recurrent
processing was similarly impaired by masking and the AB and closely linked to task
performance, reflecting conscious access. Crucially, having matched the key conditions
behaviorally, the present finding of greater local recurrency during the AB can now
unequivocally be attributed to the attentional vs. perceptual manipulation of consciousness.
Furthermore, the addition of line segments forming a non-illusory triangle to the stimulus
employed in the present study allowed us to distinguish between collinearity and illusion-specific
processing. Although the present EEG decoding measures cannot provide direct evidence for
feedback vs. lateral processes, based on neurophysiological evidence that collinearity
processing primarily relies on lateral connections (Bosking et al., 1997; Gilbert & Wiesel, 1979;
Li, 1998; Liang et al., 2017; K. E. Schmidt et al., 1997; Stettler et al., 2002), while processing of
the Kanizsa illusion involves both lateral and feedback connections (Halgren et al., 2003; Kok et
al., 2016; Kok & de Lange, 2014; Lee & Nguyen, 2001; Pak et al., 2020; Wokke et al., 2013),
the comparison of collinearity-only to illusion-specific processing may provide insight into the
components of local recurrent processing: lateral and feedback connections (Lamme et al.,
1998; Roelfsema, 2006). It should be noted that not all neurophysiological evidence
unequivocally links processing of collinearity and of the Kanizsa illusion to lateral and feedback
processing, respectively (Angelucci et al., 2002; Bair et al., 2003; Chen et al., 2014), so that
overlap in decoding the illusory and non-illusory triangle may reflect other mechanisms, for
example feedback processes representing the triangular shapes as well. However, following our
reasoning, the decoding results suggest that lateral processing occurred earlier (140–190 ms
after target stimulus onset) than illusion-specific feedback processing (200–250 ms), in line with
animal research (Angelucci & Bressloff, 2006; Lamme et al., 1998; Roelfsema, 2006).
Both lateral and feedback processing were more strongly affected by masking than by
the AB, indicating that the "attentional blindness" stage of the four-stage model of
consciousness (**Fig. 1A**) involves both lateral and feedback connections. Furthermore, masking
had a stronger effect on illusion-specific feedback processing than on lateral processing.
Notably, illusion-specific feedback processes were unaffected by the AB, but completely
abolished by masking. As current theories do not distinguish between the roles of lateral vs.
feedback connections for consciousness, the present findings may enrich empirical and
theoretical work on perceptual vs. attentional mechanisms of consciousness (Block, 2005;
Dehaene et al., 2006; Hatamimajoumerd et al., 2022; Lamme, 2010; Pitts et al., 2018; Sergent
& Dehaene, 2004), clearly distinguishing the neural profiles of each processing stage of the
influential four-stage model of conscious experience (**Fig. 1A**). Along with the distinct temporal
and spatial EEG decoding patterns associated with lateral and feedback processing, our
findings suggest a processing sequence from feedforward processing to local recurrent
interactions encompassing lateral-to-feedback connections, ultimately leading to global
recurrency and conscious report.
Our results suggest that, compared to masking, the AB left local recurrent processing
intact, while feedforward processing did not differ between the two manipulations. Local
recurrent processing plays a critical role in perceptual integration, facilitating the organization of
fragmented sensory information, such as lines, surfaces, and objects, into a coherent whole
(Roelfsema, 2023). Our EEG decoding results support this notion, demonstrating that the AB

allows for greater processing of collinearity and the illusion specifically within a time window
spanning 140 to 250 ms after stimulus onset, likely reflecting sparing of local recurrent
processes in visual cortex (Fahrenfort et al., 2017; Kok et al., 2016). This aligns with established
models of the AB phenomenon, in which the AB reflects a late post-perceptual central
bottleneck characterized by limited attentional capacity (Shapiro et al., 1997), so that sensory
information presented during the AB can nevertheless undergo extensive processing, allowing
for perceptual integration, possibly even leading up to semantic analysis (Luck et al., 1996).
Clearly, these findings do not imply that unconscious high-level (e.g., semantic) processing can
only occur during inattention, nor do they necessarily generalize to other forms of inattention.
Indeed, while the AB represents a prime example of late attentional filtering, other ways of
inducing inattention or distraction (e.g., by manipulating spatial attention) may filter information
earlier in the processing hierarchy (e.g., Luck & Hillyard, 1994 vs. Vogel et al., 1998).
Preserved local recurrent processing during the AB is also consistent with classic load
theory (Lavie & Dalton, 2014), where increasing perceptual load (Lavie & de Fockert, 2003)
more strongly reduces distractor processing than increasing cognitive load (e.g., by engaging
working memory, as in our AB condition). According to this theory, perceptual and attentional
manipulations serve as early and late filters for incoming sensory information, respectively,
resulting in more extensive processing under inattention. Indeed, one of the few neuroimaging
studies that included both manipulations found that only perceptual but not cognitive (working
memory) load decreased fMRI activity in the parahippocampal place area in response to
distractor scenes (Yi et al., 2004), although not all neuroimaging evidence is consistent with a
stronger effect of perceptual than cognitive load (Brockhoff et al., 2022).
Furthermore, previous research has shown that the impact of inattention vs. masking
can depend on the neural architecture required for the task at hand. For example, processes
related to the detection of conflicting response tendencies, a hallmark of cognitive control and
strongly associated with the prefrontal cortex (Ridderinkhof et al., 2004), are more susceptible to
inattention, which reduces the depth of stimulus processing (Nuiten et al., 2021) than to
masking, restricting recurrent interactions, but allowing for deep feedforward processing (all the
way up to prefrontal cortex) (Jiang et al., 2018; van Gaal et al., 2008). Such deep feedforward
processing can be sufficient for unconscious high-level processing, as indicated by a rich
literature demonstrating high-level (e.g., semantic) processing during masking (Kouider &
Dehaene, 2007; Van den Bussche et al., 2009; van Gaal & Lamme, 2012). Thus, rather than
enabling deep unconscious processing, preserved local recurrency during inattention may afford
other processing advantages linked to its proposed role in perceptual integration (Lamme,
2020), such as integration of stimulus elements over space or time.
Having delineated these distinct stages of feedforward, lateral, feedback and global
recurrent processing, one important avenue for future research is to distinguish between
unconscious and conscious perceptual processes at these stages. Having opted to equate
performance across manipulations in our study, behavioral performance was above chance
level for both consciousness manipulations. Follow-up research investigating perceptual
integration of fully unconscious stimuli could address ongoing debates between influential
theories of consciousness (Cogitate Consortium et al., 2023; Mudrik et al., 2014). The global
neuronal workspace theory suggests a durable, yet unconscious processing stage (referred to
as "preconscious"), where the input is not globally available, and amplification through top-down

attention is required for conscious access and report (Dehaene et al., 2006). In contrast, others
have argued that already local recurrent interactions reflect subjective phenomenal experience
(Block, 2005; Lamme, 2010). Moreover, markers like the P300 and ours for global recurrent
processing may reflect functions not directly related to conscious experience, like report or
decision-making (Alilović et al., 2023; Canales-Johnson et al., 2023; Pitts et al., 2018). Another
way forward therefore consists in combining no-report paradigms (Sergent et al., 2021;
Tsuchiya et al., 2015) with our EEG markers to examine whether local or global recurrent
processing more accurately reflects consciousness in the absence of report.

Methods

Participants

Thirty-three participants took part in the first two sessions (independent EEG training set and
practice). Three of them met the practice session's pre-established criteria for exclusion (see
"Procedure"). The remaining 30 participants (22±3 years old, 10 men, 2 left-handed) took part in
the final (main experimental) session. They all had normal or corrected-to-normal vision. The
study was approved by the local ethics committee. Participants gave informed consent and
received research credits or 15 euros per hour.

Stimuli

The target stimulus set had a 2 (illusory Kanizsa triangle: present/absent) × 2 (non-illusory
triangle: present/absent) × 2 (rotation: present/absent) design, resulting in eight stimuli (**Fig.**
1B). Three aligned Pac-Man elements induced the Kanizsa illusion. The non-illusory triangle
was present when the stimuli's three other elements (the "two-legged white circles") were
aligned. The controls for both the illusory and non-illusory triangle were created by rotating their
elements by 90 degrees. Differences in local contrast were created by rotating the entire
stimulus by 180 degrees. The targets spanned 7.5 degrees by 8.3 degrees of visual angle. The
shortest distance between the edges of the three Pac-Man stimuli as well as between the edges
of the three aligned two-legged white circles was 2.8 degrees of visual angle. Although neuronal
responses to collinearity in primary visual cortex are most robust when this distance is smaller
(Kapadia et al., 1995, 2000), longer-range lateral connections between neurons with similar
orientation selectivity can span distances corresponding to visual angles considerably greater
than 2.8 degrees (Bosking et al., 1997; Stettler et al., 2002).
The distractor stimulus set was the same as the target stimulus set, with two exceptions.
First, the distractors were red instead of black. Second, the distractors' six elements were
rotated by 180 degrees relative to the targets', so neither the illusory nor non-illusory triangle
was ever present in the distractors. Masks consisted of six differently shaped elements, all
capable of covering the targets' elements. Six masks were created by rotating the original mask
five times by 60 degrees. They spanned 8.5 degrees by 9.1 degrees of visual angle. The
fixation cross, which was always present, was adapted from Thaler et al. (2013).

Procedure

The experiment consisted of three separate sessions conducted on different days: a three-hour session to collect EEG data for the independent training set, a 1.5-hour practice session, and a three-hour experimental session. Tasks were programmed in Presentation software (Neurobehavioral Systems) and displayed on a 23-inch, 60 Hz, 1920×1080 pixels monitor. On each trial of the experimental session, participants were shown two targets (T1 and T2) within a rapid serial visual presentation (RSVP) of distractors (**Fig. 1C**). The targets and distractors had a stimulus onset asynchrony of 100 ms. T2 and distractors were presented for 17 ms each. To improve the decoding analyses' training dataset, T1 was presented for 67 ms. The longer presentation duration facilitated attending to T1, which should result in greater deployment of attentional resources and thereby increase the size of the AB. T1 was preceded by five distractors and T2 was followed by six distractors.

T2 visibility was manipulated in two ways, using a perceptual and an attentional manipulation (**Fig. 1A**). The perceptual manipulation consisted in masking T2 with three masks, each presented for 17 ms with an interstimulus interval of 0 ms. The three masks were selected randomly, but all differed from each other. Half of the T2s were masked; for the other half, no masks were presented (unmasked condition). The attentional manipulation consisted in shortening the T1–T2 lag from a long interval of eight distractors (900 ms) to a short interval of one or two distractors (200 or 300 ms). Half the trials had a long lag, the other half had a short lag. The short lag duration was determined for each participant individually during the training session. Short lags were expected to result in an AB. Participants were instructed to fixate on the fixation cross. After the RSVP, they indicated for each target whether it contained the Kanizsa illusion or not. For T2, participants simultaneously reported their confidence in their response: low, medium, or high, resulting in six response options. To get accurate ratings, participants first responded to T2 and then to T1. Response screens lasted until the response. In short, the experimental session had an 8 (T1 stimulus conditions) × 8 (T2 stimulus conditions) × 2 (masked/unmasked) × 2 (short/long T1–T2 lag) task design, resulting in 256 conditions. Each condition was presented four times, totaling 1024 trials.

The experimental session was preceded by the practice session, in which participants were familiarized with the task. To proceed to the experimental session, participants had to score above 80% correct for both T1 and unmasked, long lag T2. One participant was excluded for failing to achieve this. The training session was also used to determine for each participant the duration of the short lag (200 or 300 ms T1–T2 interval) that induced the largest AB (lowest T2 accuracy) and that was used in the subsequent experimental session. Two participants were excluded due to their AB size falling below the predetermined criterion. Specifically, their T2 accuracy at both short lags did not exhibit a decrease of more than 5% compared to long lags.

One of the main goals of this study was to match perceptual performance between the perceptual and the attentional manipulation. We did this in two ways. First, during the training session, the matching was done by staircasing mask contrast using the weighted up-down method (Kaernbach, 1991). Contrast levels ranged from 0 (black) to 255 (white). Mask contrast started at level 220. Each correct response made the task more difficult: masks got darker by downward step size S_{down}. Each incorrect response made the task easier: masks got lighter by upward step size S_{up}. Step sizes were determined by $S_{up} \times p = S_{down} \times (1 - p)$, where p is the accuracy at short lags. The smallest step size was always nine contrast levels. A reversal is

making a mistake after a correct response, or vice versa. The staircase ended after 25
reversals. The mask contrast with which the experimental session started was the average
contrast level of the last 20 reversals. Second, during the experimental session, after every 32
masked trials, mask contrast could be updated in accordance with our goal to match accuracy
over participants, while also matching accuracy within participants as well as possible.
To ensure that confidence ratings for these matched conditions (masked, long lag and
unmasked, short lag) were not influenced by participants anchoring their confidence ratings to
the very easy and very difficult unmatched conditions (no and both manipulations, respectively),
one type of block only contained the matched conditions, while the other block type contained
the two remaining, unmatched conditions (masked, short lag and unmasked, long lag). To
ensure every confidence rating would have enough trials for creating receiver operating
characteristic curves, participants were instructed to distribute their responses evenly over all
ratings within a block. Participants received feedback about the distribution of their responses.
The mask contrasts from a performance matched block were used in the subsequent non-
performance matched block to ensure that masking remained orthogonal to the AB
manipulation. The experimental session therefore always started with a performance matched
block.
We wanted to compare illusory triangle decoding to non-illusory triangle decoding.
However, during the experimental session, the non-illusory triangle was never task-relevant,
only the illusory one was. During the independent EEG classification training session, we
therefore made each visual feature, one after the other, task-relevant. A target was presented
for 33 ms every 900-1100 ms (**Fig. 3A**). Participants had to fixate on the fixation cross and
indicate whether the current task-relevant feature was absent or present. For each feature, each
target was presented 64 times, totaling 512 trials. The order of the task-relevant features was
counterbalanced over participants. For all sessions, response button mapping was
counterbalanced within tasks.

Behavioral analysis

To quantify perceptual performance, we constructed receiver operating characteristic (ROC)
curves by plotting objective hit rates against objective false alarm rates. We used the six
response options to get five inflection points (Green & Swets, 1966). We also quantified
metacognitive sensitivity: the ability to know whether you were right or wrong. Performance is
high when you are confident in objectively correct responses and not confident in objectively
incorrect responses. We again constructed ROC curves, now by plotting the rate of high-
confidence correct responses (subjective hit rates) against the rate of high-confidence incorrect
responses (subjective false alarm rates). We used the three confidence ratings to get two
inflection points. To ensure that T1 was attended, trials with incorrect T1 responses were
excluded. Frequentist and Bayesian repeated measures ANOVAs and t-tests were used to test
the differences between experimental conditions. Bayesian statistics were calculated in JASP
(JASP Team, 2024) with default prior scales (Cauchy distribution, scale 0.707).

EEG recording and preprocessing

EEG was recorded at 1024 Hz using a 64 channel ActiveTwo system (BioSemi). Four electrooculographic (EOG) electrodes measured horizontal and vertical eye movements. The data were analyzed with MATLAB (MathWorks). For most of the preprocessing steps, EEGLAB was used (Delorme & Makeig, 2004). The data were re-referenced to the earlobes. Poor channels were interpolated. High-pass filtering can cause artifacts in decoding analyses; we therefore removed slow drifts using trial-masked robust detrending (van Driel et al., 2021). Each target was epoched from -250 to 1000 ms relative to target onset. To improve the results from the independent component analysis (ICA), baseline correction was applied using the whole epoch as baseline (Groppe et al., 2009). ICA was used to remove blinks. Blink components were removed manually. Baseline correction was applied, now using a -250 to 0 ms window relative to target onset. Trials with values outside of a -300 to 300 microvolts range were removed. We used an adapted version of FieldTrip's ft_artifact_zvalue function to detect and remove trials with muscle artifacts (Oostenveld et al., 2011). As in the behavioral analyses, trials with incorrect T1 responses were excluded. Finally, the data were downsampled to 128 Hz.

Multivariate pattern analyses

We decoded the different visual features (local contrast, non-illusory triangle, and illusory Kanizsa triangle, respectively; **Fig. 1B**) using the Amsterdam Decoding and Modeling (ADAM) toolbox (Fahrenfort et al., 2018). For each participant and each visual feature, a linear discriminant classifier was trained on the T1 data and tested on each condition of the T2 data. The classifier was trained to discriminate between the feature's (e.g., the illusory triangle's) absence and presence based on the preprocessed EEG activity across all electrodes. AUC was again used as the performance measure. This procedure was executed for every time sample in a trial, yielding classification performance over time. For the time samples from -100 to 700 ms relative to target onset, we used a two-sided t-test to evaluate whether classifier performance differed from chance. We used cluster-based permutation testing (1000 iterations at a threshold of 0.05) to correct for multiple comparisons (Maris & Oostenveld, 2007). To obtain topographic maps showing the neural sources of the classifier performance, we multiplied the classifier weights with the data covariance matrix, yielding covariance/class separability maps (Haufe et al., 2014).

In the decoding analyses described in the results, we applied "diagonal decoding": classifiers were tested on the same time sample they were trained on. We did the same analyses again, now by applying "off-diagonal decoding": classifiers trained on a particular time point are tested on all time points (King & Dehaene, 2014). Off-diagonal decoding allowed us to explore whether patterns of activity during the time windows of interest were stable over time (**Fig. S3**), which is especially interesting for illusion decoding. For the illusory triangle, classifiers were trained on the 200-250 ms window and then averaged, and then decoding AUC was plotted from -100 to 700 ms off-diagonally. Note that for this analysis, late off-diagonal decoding (e.g., in the 375-475 ms time-window shown in panel C) is thought to reflect (longer-lasting) local recurrent interactions as well (Alilović et al., 2023). A similar off-diagonal analysis was done for the local contrast trained on the 75-95 ms time-window.

To distinguish between collinearity-only and illusion-specific processing, we trained
classifiers on independent data based on collinearity-only (the non-illusory triangle was task-
relevant) or collinearity-plus-illusion (the illusory triangle was task-relevant) and then decoded
the Kanizsa illusion in T2s of the main RSVP task. The rationale for this analysis is that
collinearity is present both when the Pac-Man stimuli align to form the illusory Kanizsa triangle
and when the two-legged white circles align to from a non-illusory triangle, but only in the case
of the Kanizsa triangle do participants experience an illusion. The comparison of T2 illusion
decoding between the classifiers trained on the illusion and on collinearity-only in the training
set may therefore isolate illusion-specific (likely involving feedback processing) from basic
collinearity processing (likely involving lateral connections; **Fig. 3**). In the **Supplementary**
information (Fig. S6), we compare the independent training set to the training set used for the
main analyses, the T1 data from the RSVP task.

As described in the **Supplementary information** as well, a tenfold cross-validation
scheme was applied to the data from the independent training set to decode local contrast.
Individual participants' data were split into ten equal-sized folds after randomizing the task's trial
order. A classifier was then trained on nine folds and tested on the tenth one, ensuring
independence of the training and testing sets. This procedure was repeated until each fold
served as the test set once. Classifier performance, AUC, was averaged across all ten iterations
(**Fig. S5**).

As in the behavioral analyses, frequentist and Bayesian repeated measures ANOVAs
and t-tests were used to test the differences between experimental conditions.

Data availability

695   All code and data related to this paper are available at
696   https://uvaauas.figshare.com/projects/Perceptual_versus_attentional_impairments_of_consciou
697   s_access_Distinct_neural_mechanisms_despite_equal_task_performance/230501.

References

Alilović, J., Lampers, E., Slagter, H. A., & van Gaal, S. (2023). Illusory object recognition is either perceptual or cognitive in origin depending on decision confidence. *PLoS Biology*, *21*(3), e3002009.

Angelucci, A., & Bressloff, P. C. (2006). Contribution of feedforward, lateral and feedback connections to the classical receptive field center and extra-classical receptive field surround of primate V1 neurons. *Progress in Brain Research*, *154*, 93–120.

Angelucci, A., Levitt, J. B., Walton, E. J. S., Hupe, J.-M., Bullier, J., & Lund, J. S. (2002). Circuits for local and global signal integration in primary visual cortex. *The Journal of Neuroscience: The Official Journal of the Society for Neuroscience*, *22*(19), 8633–8646.

Bair, W., Cavanaugh, J. R., & Movshon, J. A. (2003). Time course and time-distance relationships for surround suppression in macaque V1 neurons. *The Journal of Neuroscience: The Official Journal of the Society for Neuroscience*, *23*(20), 7690–7701.

Block, N. (2005). Two neural correlates of consciousness. *Trends in Cognitive Sciences*, *9*(2), 46–52.

Bosking, W. H., Zhang, Y., Schofield, B., & Fitzpatrick, D. (1997). Orientation selectivity and the arrangement of horizontal connections in tree shrew striate cortex. *The Journal of Neuroscience: The Official Journal of the Society for Neuroscience*, *17*(6), 2112–2127.

Brockhoff, L., Schindler, S., Bruchmann, M., & Straube, T. (2022). Effects of perceptual and working memory load on brain responses to task-irrelevant stimuli: Review and implications for future research. *Neuroscience and Biobehavioral Reviews*, *135*, 104580.

Brown, R., Lau, H., & LeDoux, J. E. (2019). Understanding the Higher-Order Approach to Consciousness. *Trends in Cognitive Sciences*. https://doi.org/10.1016/j.tics.2019.06.009

Canales-Johnson, A., Beerendonk, L., Chennu, S., Davidson, M. J., Ince, R. A. A., & van Gaal, S. (2023). Feedback information transfer in the human brain reflects bistable perception in the absence of report. *PLoS Biology*, *21*(5), e3002120.

Chen, M., Yan, Y., Gong, X., Gilbert, C. D., Liang, H., & Li, W. (2014). Incremental integration of global contours through interplay between visual cortical areas. *Neuron*, *82*(3), 682–694.

Cogitate Consortium, Ferrante, O., Gorska-Klimowska, U., Henin, S., Hirschhorn, R., Khalaf, A., Lepauvre, A., Liu, L., Richter, D., Vidal, Y., Bonacchi, N., Brown, T., Sripad, P., Armendariz, M., Bendtz, K., Ghafari, T., Hetenyi, D., Jeschke, J., Kozma, C., … Melloni, L. (2023). An adversarial collaboration to critically evaluate theories of consciousness. In *bioRxiv* (p. 2023.06.23.546249). https://doi.org/10.1101/2023.06.23.546249

Dehaene, S., Changeux, J.-P., Naccache, L., Sackur, J., & Sergent, C. (2006). Conscious, preconscious, and subliminal processing: a testable taxonomy. *Trends in Cognitive Sciences*, *10*(5), 204–211.

Dehaene, S., Sergent, C., & Changeux, J.-P. (2003). A neuronal network model linking subjective reports and objective physiological data during conscious perception. *Proceedings of the National Academy of Sciences of the United States of America*, *100*(14), 8520–8525.

Delorme, A., & Makeig, S. (2004). EEGLAB: an open source toolbox for analysis of single-trial EEG dynamics including independent component analysis. *Journal of Neuroscience Methods*, *134*(1), 9–21.

Dienes, Z. (2007). Subjective measures of unconscious knowledge. In R. Banerjee & B. K. Chakrabarti (Eds.), *Progress in Brain Research* (Vol. 168, pp. 49–269). Elsevier.

Fahrenfort, J. J., Johnson, P. A., Kloosterman, N. A., Stein, T., & van Gaal, S. (2024). Criterion placement threatens the construct validity of neural measures of consciousness. In *bioRxiv*. https://doi.org/10.1101/2024.02.22.581517

Fahrenfort, J. J., Scholte, H. S., & Lamme, V. A. F. (2007). Masking disrupts reentrant processing in human visual cortex. *Journal of Cognitive Neuroscience*, *19*(9), 1488–1497.

Fahrenfort, J. J., van Driel, J., van Gaal, S., & Olivers, C. N. L. (2018). From ERPs to MVPA Using the Amsterdam Decoding and Modeling Toolbox (ADAM). *Frontiers in Neuroscience*, *12*, 368.

Fahrenfort, J. J., van Leeuwen, J., Olivers, C. N. L., & Hogendoorn, H. (2017). Perceptual integration without conscious access. *Proceedings of the National Academy of Sciences of the United States of America*, *114*(14), 3744–3749.

Fleming, S. M., & Lau, H. C. (2014). How to measure metacognition. *Frontiers in Human Neuroscience*, *8*, 443.

Gilbert, C. D., & Wiesel, T. N. (1979). Morphology and intracortical projections of functionally characterised neurones in the cat visual cortex. *Nature*, *280*(5718), 120–125.

Green, D. M., & Swets, J. A. (1966). *Signal detection theory and psychophysics*. *455*. https://psycnet.apa.org/fulltext/1967-02286-000.pdf

Groppe, D. M., Makeig, S., & Kutas, M. (2009). Identifying reliable independent components via split-half comparisons. *NeuroImage*, *45*(4), 1199–1211.

Halgren, E., Mendola, J., Chong, C. D. R., & Dale, A. M. (2003). Cortical activation to illusory shapes as measured with magnetoencephalography. *NeuroImage*, *18*(4), 1001–1009.

Hatamimajoumerd, E., Ratan Murty, N. A., Pitts, M., & Cohen, M. A. (2022). Decoding perceptual awareness across the brain with a no-report fMRI masking paradigm. *Current Biology: CB*. https://doi.org/10.1016/j.cub.2022.07.068

Haufe, S., Meinecke, F., Görgen, K., Dähne, S., Haynes, J.-D., Blankertz, B., & Bießmann, F. (2014). On the interpretation of weight vectors of linear models in multivariate neuroimaging. *NeuroImage*, *87*, 96–110.

JASP Team. (2024). *JASP (Version 0.19.0)[Computer software]*. https://jasp-stats.org/

Jiang, J., Correa, C. M., Geerts, J., & van Gaal, S. (2018). The relationship between conflict awareness and behavioral and oscillatory signatures of immediate and delayed cognitive control. *NeuroImage*, *177*, 11–19.

Joglekar, M. R., Mejias, J. F., Yang, G. R., & Wang, X.-J. (2018). Inter-areal Balanced Amplification Enhances Signal Propagation in a Large-Scale Circuit Model of the Primate Cortex. *Neuron*, *98*(1), 222-234.e8.

Kaernbach, C. (1991). Simple adaptive testing with the weighted up-down method. *Perception & Psychophysics*, *49*(3), 227–229.

Kanai, R., Walsh, V., & Tseng, C.-H. (2010). Subjective discriminability of invisibility: a framework for distinguishing perceptual and attentional failures of awareness. *Consciousness and Cognition*, *19*(4), 1045–1057.

Kandel, E. R., Schwartz, J. H., Jessell, T. M., & Siegelbaum, S. (2000). *Principles of neural science*. academia.edu.

https://www.academia.edu/download/30536508/neuroscience_syllabus.pdf

Kapadia, M. K., Ito, M., Gilbert, C. D., & Westheimer, G. (1995). Improvement in visual sensitivity by changes in local context: parallel studies in human observers and in V1 of alert monkeys. *Neuron*, *15*(4), 843–856.

Kapadia, M. K., Westheimer, G., & Gilbert, C. D. (2000). Spatial distribution of contextual interactions in primary visual cortex and in visual perception. *Journal of Neurophysiology*, *84*(4), 2048–2062.

Kentridge, R. W., Heywood, C. A., & Weiskrantz, L. (2004). Spatial attention speeds discrimination without awareness in blindsight. *Neuropsychologia, 42*(6), 831–835.

Kiefer, M., & Brendel, D. (2006). Attentional Modulation of Unconscious "Automatic" Processes: Evidence from Event-related Potentials in a Masked Priming Paradigm. *Journal of Cognitive Neuroscience*, *18*(2), 184–198.

King, J.-R., & Dehaene, S. (2014). Characterizing the dynamics of mental representations: the temporal generalization method. *Trends in Cognitive Sciences*, *18*(4), 203–210.

Kok, P., Bains, L. J., van Mourik, T., Norris, D. G., & de Lange, F. P. (2016). Selective Activation of the Deep Layers of the Human Primary Visual Cortex by Top-Down Feedback. *Current Biology: CB*, *26*(3), 371–376.

Kok, P., & de Lange, F. P. (2014). Shape perception simultaneously up- and downregulates neural activity in the primary visual cortex. *Current Biology: CB*, *24*(13), 1531–1535.

Kouider, S., & Dehaene, S. (2007). Levels of processing during non-conscious perception: a critical review of visual masking. *Philosophical Transactions of the Royal Society B: Biological Sciences*, *362*(1481), 857–875.

Lamme, V. A. F. (2010). How neuroscience will change our view on consciousness. *Cognitive Neuroscience*, *1*(3), 204–220.

Lamme, V. A. F. (2020). Visual Functions Generating Conscious Seeing. *Frontiers in Psychology*, *11*, 83.

Lamme, V. A. F., & Roelfsema, P. R. (2000). The distinct modes of vision offered by feedforward and recurrent processing. *Trends in Neurosciences*, *23*(11), 571–579.

Lamme, V. A. F., Supèr, H., & Spekreijse, H. (1998). Feedforward, horizontal, and feedback processing in the visual cortex. *Current Opinion in Neurobiology*, *8*(4), 529–535.

Lau, H. C. (2022). *In Consciousness we Trust: The Cognitive Neuroscience of Subjective Experience*. Oxford University Press.

Lau, H. C., & Passingham, R. E. (2006). Relative blindsight in normal observers and the neural correlate of visual consciousness. *Proceedings of the National Academy of Sciences of the United States of America*, *103*(49), 18763–18768.

Lavie, N., & Dalton, P. (2014). Load theory of attention and cognitive control. *The Oxford Handbook of Attention*, 56–75.

Lavie, N., & de Fockert, J. W. (2003). Contrasting effects of sensory limits and capacity limits in visual selective attention. *Perception & Psychophysics*, *65*(2), 202–212.

Lee, T. S., & Nguyen, M. (2001). Dynamics of subjective contour formation in the early visual cortex. *Proceedings of the National Academy of Sciences of the United States of America*, *98*(4), 1907–1911.

Li, Z. (1998). A neural model of contour integration in the primary visual cortex. *Neural Computation*, *10*(4), 903–940.

829   Liang, H., Gong, X., Chen, M., Yan, Y., Li, W., & Gilbert, C. D. (2017). Interactions between
830   feedback and lateral connections in the primary visual cortex. *Proceedings of the*
831   *National Academy of Sciences of the United States of America*, *114*(32), 8637–8642.
832   Luck, S. J., & Hillyard, S. A. (1994). Electrophysiological correlates of feature analysis during
833   visual search. *Psychophysiology*, *31*(3), 291–308.
834   Luck, S. J., Vogel, E. K., & Shapiro, K. L. (1996). Word meanings can be accessed but not
835   reported during the attentional blink. *Nature*, *383*(6601), 616–618.
836   Maris, E., & Oostenveld, R. (2007). Nonparametric statistical testing of EEG- and MEG-data.
837   *Journal of Neuroscience Methods*, *164*(1), 177–190.
838   Marti, S., King, J.-R., & Dehaene, S. (2015). Time-Resolved Decoding of Two Processing
839   Chains during Dual-Task Interference. *Neuron*, *88*(6), 1297–1307.
840   Mashour, G. A., Roelfsema, P., Changeux, J.-P., & Dehaene, S. (2020). Conscious Processing
841   and the Global Neuronal Workspace Hypothesis. *Neuron*, *105*(5), 776–798.
842   Merikle, P. M., Smilek, D., & Eastwood, J. D. (2001). Perception without awareness:
843   perspectives from cognitive psychology. *Cognition*, *79*(1–2), 115–134.
844   Meuwese, J. D. I., van Loon, A. M., Lamme, V. A. F., & Fahrenfort, J. J. (2014). The subjective
845   experience of object recognition: comparing metacognition for object detection and
846   object categorization. *Attention, Perception & Psychophysics*, *76*(4), 1057–1068.
847   Mudrik, L., Faivre, N., & Koch, C. (2014). Information integration without awareness. *Trends in*
848   *Cognitive Sciences*, *18*(9), 488–496.
849   Naccache, L., Blandin, E., & Dehaene, S. (2002). Unconscious masked priming depends on
850   temporal attention. *Psychological Science*, *13*(5), 416–424.
851   Northoff, G., & Lamme, V. A. F. (2020). Neural signs and mechanisms of consciousness: Is
852   there a potential convergence of theories of consciousness in sight? *Neuroscience and*
853   *Biobehavioral Reviews*, *118*, 568–587.
854   Nuiten, S. A., Canales-Johnson, A., Beerendonk, L., Nanuashvili, N., Fahrenfort, J. J.,
855   Bekinschtein, T., & van Gaal, S. (2021). Preserved sensory processing but hampered
856   conflict detection when stimulus input is task-irrelevant. *ELife*, *10*.
857   https://doi.org/10.7554/eLife.64431
858   Oostenveld, R., Fries, P., Maris, E., & Schoffelen, J.-M. (2011). FieldTrip: Open source software
859   for advanced analysis of MEG, EEG, and invasive electrophysiological data.
860   *Computational Intelligence and Neuroscience*, *2011*, 156869.
861   Pak, A., Ryu, E., Li, C., & Chubykin, A. A. (2020). Top-Down Feedback Controls the Cortical
862   Representation of Illusory Contours in Mouse Primary Visual Cortex. *The Journal of*
863   *Neuroscience: The Official Journal of the Society for Neuroscience*, *40*(3), 648–660.
864   Peters, M. A., & Lau, H. (2016). Correction: Human observers have optimal introspective access
865   to perceptual processes even for visually masked stimuli. *ELife*, *5*.
866   https://doi.org/10.7554/eLife.16332
867   Pitts, M. A., Lutsyshyna, L. A., & Hillyard, S. A. (2018). The relationship between attention and
868   consciousness: an expanded taxonomy and implications for 'no-report' paradigms.
869   *Philosophical Transactions of the Royal Society of London. Series B, Biological*
870   *Sciences*, *373*(1755), 20170348.
871   Raymond, J. E., Shapiro, K. L., & Arnell, K. M. (1992). Temporary suppression of visual
872   processing in an RSVP task: an attentional blink? *Journal of Experimental Psychology.*

Human Perception and Performance, *18*(3), 849–860.

Ridderinkhof, K. R., Ullsperger, M., Crone, E. A., & Nieuwenhuis, S. (2004). The role of the medial frontal cortex in cognitive control. *Science*, *306*(5695), 443–447.

Roelfsema, P. R. (2006). Cortical algorithms for perceptual grouping. *Annual Review of Neuroscience*, *29*, 203–227.

Roelfsema, P. R. (2023). Solving the binding problem: Assemblies form when neurons enhance their firing rate-they don't need to oscillate or synchronize. *Neuron*, *111*(7), 1003–1019.

Schmidt, K. E., Goebel, R., Löwel, S., & Singer, W. (1997). The perceptual grouping criterion of colinearity is reflected by anisotropies of connections in the primary visual cortex. *The European Journal of Neuroscience*, *9*(5), 1083–1089.

Schmidt, T. (2015). Invisible Stimuli, Implicit Thresholds: Why Invisibility Judgments Cannot be Interpreted in Isolation. *Advances in Cognitive Psychology / University of Finance and Management in Warsaw*, *11*(2), 31–41.

Sergent, C., Baillet, S., & Dehaene, S. (2005). Timing of the brain events underlying access to consciousness during the attentional blink. *Nature Neuroscience*, *8*(10), 1391–1400.

Sergent, C., Corazzol, M., Labouret, G., Stockart, F., Wexler, M., King, J. -R., Meyniel, F., & Pressnitzer, D. (2021). Bifurcation in brain dynamics reveals a signature of conscious processing independent of report. *Nature Communications*, *12*(1), 1149.

Sergent, C., & Dehaene, S. (2004). Is consciousness a gradual phenomenon? Evidence for an all-or-none bifurcation during the attentional blink. *Psychological Science*, *15*(11), 720–728.

Seth, A. K., Dienes, Z., Cleeremans, A., Overgaard, M., & Pessoa, L. (2008). Measuring consciousness: relating behavioural and neurophysiological approaches. *Trends in Cognitive Sciences*, *12*(8), 314–321.

Shanks, D. R. (2017). Regressive research: The pitfalls of post hoc data selection in the study of unconscious mental processes. *Psychonomic Bulletin & Review*, *24*(3), 752–775.

Shapiro, K. L., Raymond, J. E., & Arnell, K. M. (1997). The attentional blink. *Trends in Cognitive Sciences*, *1*(8), 291–296.

Stettler, D. D., Das, A., Bennett, J., & Gilbert, C. D. (2002). Lateral connectivity and contextual interactions in macaque primary visual cortex. *Neuron*, *36*(4), 739–750.

Thaler, L., Schütz, A. C., Goodale, M. A., & Gegenfurtner, K. R. (2013). What is the best fixation target? The effect of target shape on stability of fixational eye movements. *Vision Research*, *76*, 31–42.

Tsuchiya, N., Wilke, M., Frässle, S., & Lamme, V. A. F. (2015). No-Report Paradigms: Extracting the True Neural Correlates of Consciousness. *Trends in Cognitive Sciences*, *19*(12), 757–770.

Van den Bussche, E., Van den Noortgate, W., & Reynvoet, B. (2009). Mechanisms of masked priming: a meta-analysis. *Psychological Bulletin*, *135*(3), 452–477.

van Driel, J., Olivers, C. N. L., & Fahrenfort, J. J. (2021). High-pass filtering artifacts in multivariate classification of neural time series data. *Journal of Neuroscience Methods*, *352*, 109080.

van Gaal, S., & Lamme, V. A. F. (2012). Unconscious high-level information processing: implication for neurobiological theories of consciousness: Implication for neurobiological theories of consciousness. *The Neuroscientist: A Review Journal Bringing Neurobiology,*

Neurology and Psychiatry, *18*(3), 287–301.

van Gaal, S., Ridderinkhof, K. R., Fahrenfort, J. J., Scholte, H. S., & Lamme, V. A. F. (2008).
Frontal cortex mediates unconsciously triggered inhibitory control. *The Journal of*
Neuroscience: The Official Journal of the Society for Neuroscience, *28*(32), 8053–8062.

van Vugt, B., Dagnino, B., Vartak, D., Safaai, H., Panzeri, S., Dehaene, S., & Roelfsema, P. R.
(2018). The threshold for conscious report: Signal loss and response bias in visual and
frontal cortex. *Science*, *360*(6388), 537–542.

Vogel, E. K., Luck, S. J., & Shapiro, K. L. (1998). Electrophysiological evidence for a
postperceptual locus of suppression during the attentional blink. *Journal of Experimental*
Psychology. Human Perception and Performance, *24*(6), 1656–1674.

Weaver, M. D., Fahrenfort, J. J., Belopolsky, A., & van Gaal, S. (2019). Independent Neural
Activity Patterns for Sensory- and Confidence-Based Information Maintenance during
Category-Selective Visual Processing. *ENeuro*, *6*(1).
https://doi.org/10.1523/ENEURO.0268-18.2018

Wokke, M. E., Vandenbroucke, A. R. E., Scholte, H. S., & Lamme, V. A. F. (2013). Confuse
your illusion: feedback to early visual cortex contributes to perceptual completion.
Psychological Science, *24*(1), 63–71.

Wyatte, D., Jilk, D. J., & O'Reilly, R. C. (2014). Early recurrent feedback facilitates visual object
recognition under challenging conditions. *Frontiers in Psychology*, *5*, 674.

Yi, D.-J., Woodman, G. F., Widders, D., Marois, R., & Chun, M. M. (2004). Neural fate of
ignored stimuli: dissociable effects of perceptual and working memory load. *Nature*
Neuroscience, *7*(9), 992–996.

Zivony, A., & Lamy, D. (2022). What processes are disrupted during the attentional blink? An
integrative review of event-related potential research. *Psychonomic Bulletin & Review*,
29(2), 394–414.