Exploring the bounded rationality in human decision anomalies through an assemblable computational framework

Yi-Long Lu[1], Yang-Fan Lu[2,3], Xiangjuan Ren[1,3,4,7], Hang Zhang[1,3,4,5,6]*

[1] School of Psychological and Cognitive Sciences and Beijing Key Laboratory of Behavior and Mental Health, Peking University, Beijing, China

[2] Academy for Advanced Interdisciplinary Studies, Peking University, Beijing, China

[3] Peking-Tsinghua Center for Life Sciences, Peking University, Beijing, China

[4] PKU-IDG/McGovern Institute for Brain Research, Peking University, Beijing, China

[5] Key Laboratory of Machine Perception, Ministry of Education, Peking University, Beijing, China

[6] Chinese Institute for Brain Research, Beijing, China

[7] Max Planck Research Group NeuroCode, Max Planck Institute for Human Development, Berlin, Germany

*: corresponding author.

* Correspondence should be addressed to: Hang Zhang, School of Psychological and Cognitive Sciences, Peking University, Beijing, China. E-mail: hang.zhang@pku.edu.cn

ABSTRACT

Some seemingly irrational decision behaviors (anomalies), once seen as flaws in human

cognition, have recently received explanations from a rational perspective. The basic idea is that

the brain has limited cognitive resources to process the quantities (e.g., value, probability, time,

etc.) required for decision making, with specific biases arising as byproducts of the resource

allocation that is optimized for the environment. While appealing for providing normative

accounts, the existing resource-rational models have limitations such as inconsistent

assumptions across models, a focus on single environmental factors, and limited coverage of

decision anomalies. One challenging anomaly is the peanuts effect, a pervasive phenomenon in

decision-making under risk that implies an interdependence between the processing of value

and probability. To extend the resource rationality approach to explain the peanuts effect, here

we develop a computational framework—the Assemblable Resource-Rational Modules

(ARRM)—that integrates ideas from different lines of boundedly-rational decision models as

freely assembled modules. The framework can accommodate the joint functioning of multiple

environmental factors, and allow new models to be built and tested along with the existing ones,

potentially opening a wider range of decision phenomena to bounded rationality modeling. For

one new and three published datasets that cover two different task paradigms and both the gain

and loss domains, our boundedly-rational models reproduce two characteristic features of the

peanuts effect and outperform previous models in fitting human decision behaviors.

Keywords: resource rationality, efficient coding, rate-distortion theory, decision under risk,

probability distortion, peanuts effect

INTRODUCTION

Many decision problems in the real world can be framed as choice among gambles whose

outcomes are probabilistic. What principles do human decisions follow? An early influential

theory was the Expected Utility Theory (EUT; von Neumann & Morgenstern, 1944), which

assumes that humans maximize expected utility, as any rational agents would do. However,

following the pioneering experimental work of Allais (1953), significant violations of EUT were

identified in human decisions. These anomalies motivated Kahneman and Tversky's Cumulative

Prospect Theory (CPT; Kahneman & Tversky, 1979; Tversky & Kahneman, 1992), which retains

EUT's assumption of expected utility maximization but introduces a distortion of probability in

the computation of expected utility, typically an overestimation of small probability and

underestimation of large probability (i.e., an inverted-S-shaped distortion curve). With probability

distortion modeled by a one- or two-parameter function (Gonzalez & Wu, 1999; Kahneman &

Tversky, 1979; Prelec, 1998), CPT provides a good fit to a variety of human decision behaviors,

including those that challenge EUT, and thus becomes one of most widely used decision models

in economics, psychology, and neuroscience (Glimcher & Fehr, 2014).

From a cognitive view, CPT is unsatisfying in its lack of mechanistic explanation for the

observed value or probability distortions. Even as a descriptive model for human behaviors, it

has some critical limitations. For example, it assumes a separability of value and probability, that

is, neither does the utility function depend on probability, nor does the probability distortion

function depend on value. This separability assumption turns out to be oversimplified, failing to

capture the rich interaction of value and probability in human decisions (Peterson et al., 2021). A

well-documented phenomenon is known as the "peanuts effect": People tend to take more risk

when the value at stake is small (Estle et al., 2006; Fehr-Duda et al., 2010; Green et al., 1999;

Jones & Oaksford, 2011; Kachelmeier & Shehata, 1992; Prelec & Loewenstein, 1991; Weber &

Chapman, 2005).

These highly patterned violations of EUT and even CPT lead some researchers to consider

an entirely different possibility: people may not compute or maximize expected utility at all, but

instead rely on simple heuristic algorithms to make decisions (Gigerenzer et al., 2011), often

discarding part of the available information. For example, the maximax heuristic compares the

best outcome of each gamble and chooses the one whose best outcome is the best (Coombs et

al., 1970); the similarity heuristic ignores the dimension that is similar for different gambles and

focuses on the other dimension (Rubinstein, 1988). Numerous different heuristic decision

models have been proposed (Birnbaum & LaCroix, 2008; Brandstätter et al., 2006; Leland,

1998). However, one problem with heuristic models is a lack of consensus on which heuristic to

use in which situation (Callaway et al., 2022). An even more serious problem is that these

heuristics may not produce the same types of decision biases as humans do (Birnbaum, 2008).

Indeed, no known heuristic models have outperformed CPT in capturing the comprehensive

patterns of human decision behaviors (Erev et al., 2010).

A third modeling approach for human decisions, alternative to CPT and heuristics, is

bounded rationality (Anderson, 1990; Simon, 1955), where humans are modeled as agents who

have limited computational power, but who use it efficiently to achieve adaptive behaviors, with

decision biases arising as byproducts. An early model along this line is Decision by Sampling

(Stewart et al., 2006), which explains the inverted-S-shaped probability distortion as the

consequence of an adaptive representation of probability according to the event probabilities in

the environment. More recently, such bounded rationality has been formulated within the

framework of information theory (C. J. Bates et al., 2019; C. A. Sims, 2003; C. R. Sims, 2016),

providing normative explanations for the subjective distortions of value (C. J. Bates et al., 2019;

Gershman & Bhui, 2020; C. R. Sims, 2016), probability (Bhui & Gershman, 2018; Zhang et al.,

2020), numerosity (Heng et al., 2020), and temporal delay (Gershman & Bhui, 2020). What lies

at the heart of these models is the assumption of limited cognitive resources and a rational use

of these resources. This approach, as a branch of bounded rationality, is thus called resource

rationality (Bhui et al., 2021; Lewis et al., 2014; Lieder & Griffiths, 2020).

The resource rationality approach is appealing, because it can provide normative accounts

for how human decisions may be determined by both the environmental and cognitive

constraints. Meanwhile, it is faced with some challenges. First, most of its applications focus on

rational resource allocation controlled by one single dimension of the environment, which could

be an oversimplification of human decision problems. A full treatment needs to deal with the joint

influence of multiple environmental factors. Second, it is common for different alternative

assumptions to be used in the resource-rational modeling of different phenomena. Because

most studies do not compare across alternative resource-rational models, it is often unknown

whether a specific assumption is necessary for a specific phenomenon and which assumption

best describes the optimalization problem posed on and solved by human cognition. Third, only

a small portion of known decision anomalies have been addressed by the approach (Frydman &

Jin, 2021; Gershman & Bhui, 2020; Summerfield & Parpart, 2022). It can hardly explain a wider

range of decision phenomena unless its model space is significantly expanded.

The peanuts effect, briefly mentioned earlier, is a pervasive anomaly in decision-making

under risk that has long challenged traditional explanations. As we will demonstrate later, this

phenomenon implies an interdependence between the processing of value and probability,

necessitating more powerful resource-rational models. Building on previous resource-rational

work that models cognitive processing as information transmission through a constrained

communication channel (Bhui et al., 2021; Dayan & Abbott, 2001; C. R. Sims, 2018; Wei &

Stocker, 2015), we developed the Assemblable Resource-Rational Modules (ARRM) framework,

which specifies each module of resource-rational models (e.g., cognitive resources, prior in

memory, encoding and decoding schemes) and provides a taxonomy to classify their variants.

This framework enables us to formulate the joint effects of multiple environmental factors on

resource allocation and to assemble assumptions from different previous models into new

resource-rational models. To test which assumptions best explain the peanuts effect, we applied

ARRM to decision under risk to construct 10 new models and compared their goodness-of-fit to

human data in one new and three published datasets spanning two task paradigms and both

gain and loss domains. The resource-rational model that best explained the peanuts effect was

the bounded log-odds model (Zhang et al., 2020) enhanced with the assumptions of rational

inattention (Gershman & Bhui, 2020; C. A. Sims, 2003) and structural prior (Pleskac & Hertwig,

2014), which provides a complete description of human risky decision behaviors including two

characteristic features of the peanuts effect. The model also outperformed a representative set

of traditional decision models. We close with a discussion of ARRM's other potential applications

and its relationship to heuristic-based or attention-dependent decision models.

THE PEANUTS EFFECT IN DECISION UNDER RISK

Before diving into the resource-rational modeling of the peanuts effect, we briefly review the

history of the anomaly and why it poses a challenge to almost all previous decision models. The

peanuts effect was first presented by Markowitz (1952) as an (informal) observation that people

may reverse their preferences between a sure reward and a gamble when the rewards of the

two are proportionally enlarged. The set of choices constructed by Markowitz have the common

format "X with certainty or one chance in ten of getting Y?"[1], where Y=10X and X can be 10

cents, $1, $10, $100, $1,000, or $1,000,000. In all these choice pairs, the sure reward and the

gamble have the same expected gain. The puzzling phenomenon is that most people seem to

prefer the gamble for small X and Y but the sure reward for large X and Y. It receives the name

"peanuts effect" in Prelec and Loewenstein (1991), defined as an elevated risk aversion for

large gambles. The phenomenon has been repeatedly replicated in later studies on decision

under risk (Binswanger, 1981; Estle et al., 2006; Fehr-Duda et al., 2010; Kachelmeier &

Shehata, 1992; Weber & Chapman, 2005), for rating as well as choice tasks (Weber &

Chapman, 2005), for real as well as virtual monetary rewards (Binswanger, 1981; Fehr-Duda et

al., 2010; Kachelmeier & Shehata, 1992). As we will soon see, this phenomenon also widely

exists in previous datasets that were not intended to test it, often unnoticed in the original

publications.

The theoretical difficulty in explaining the peanuts effect

Although the peanuts effect has been documented for decades, it has no satisfactory

explanation yet. Below we briefly describe the theoretical explanations that have been proposed

---

[1] Markowitz (1952) constructed a parallel set of choices for the loss domain in a similar format as "X with certainty or take one chance in ten of owing Y?". Contrary to the gain domain, most people seem to prefer the sure loss for small X and Y but the gamble for large X and Y. As we will see, the peanuts effect in both the gain and loss domains can be explained by the same model developed in the ARRM framework.

for the peanuts effect as well as decision theories that seem to have potential to explain it.

Convex-concave utility functions

In his original paper, Markowitz (1952) attributes the peanuts effect to utility functions that

are convex in small values but concave in large values. According to such utility functions, the

higher value of a small gamble is much more appealing than its paired sure reward, while for

large gambles the appeal is weaker. However, there is little empirical evidence for such utility

functions; what are widely accepted (Tversky & Kahneman, 1992) and agree with the non-

parametric measurement (Gonzalez & Wu, 1999) of human decisions are power utility functions.

Fehr-Duda et al. (2010) examined human choices for gambles with a range of different

probabilities and argued that no utility functions may fully explain the peanuts effect.

The peanuts effect poses an anomaly not only for the expected utility theory, but also for

CPT (Tversky & Kahneman, 1992) and many other theories (Prelec & Loewenstein, 1991;

Wakker, 2010), because it challenges the *separability assumption* that value and probability are

independently processed before their integration, that is, the utility function $u(x)$ is determined

only by value, and the probability weighting function $w(p)$ only by probability. If such separability

held, scaling up the values proportionally for the sure reward and gambles should not have

influenced human preference between the two, at least under the widely accepted power utility

function. In our Study 1, we will present an even stronger objection to Markowitz's (1952)

explanation, proving that no utility or probability weighting functions may explain the observed

peanuts effect, unless the separability assumption is loosened.

Value-dependent dimension importance

What is difficult to explain in the peanuts effect is not just the existence of an interaction

between value and probability (which issue may be readily fixed by loosening the assumption of

independence), but the particular direction of the interaction. Parallel to decision under risk,

there is an interaction effect between value and delay in temporal discounting, where humans

discount future values less for higher values (Prelec & Loewenstein, 1991). This magnitude

effect is explained by Prelec and Loewenstein's (1991) decision theory, which assumes that

higher values on one dimension increase the relative importance of the dimension in decision

making. It may also be understood from the resource-rational perspective (Gershman & Bhui,

2020), where discounting is assumed to be consequence of noisy representation of future value,

with higher values attracting more cognitive resources and thus associated with less

discounting.

However, similar logic cannot explain the peanuts effect. Suppose for gambles of a higher

stake, the value dimension is assigned a higher importance and accordingly the probability

dimension a lower importance. Following this reasoning, the decision maker would be more

attracted to the stake of the gamble and less sensitive to its risk. As a result, the theory predicts

people would take more risks for larger gambles, which runs in the opposite direction of the

peanuts effect.

Greater disappointment for larger gambles

That is why Prelec and Loewenstein's (1991) decision theory could explain 9 out of 10

anomalies summarized in their paper but not the peanuts effect. This failure led Prelec and

Loewenstein (1991) to resort to a distinctively different perspective to explain the peanuts effect,

that people may maximize their own emotional experience instead of the expected utility, as

formulated in the decision affect theory (Mellers et al., 1997). They reasoned that when the

value of the gamble is higher, people would face greater disappointment for choosing the

gamble but losing it. As a result, people may reverse their preference between gamble and sure

reward when the value of the gamble increases. A similar idea was revisited in Weber and

Chapman (2005).

Though intuitively appealing, this reasoning is missing the fact that the utility difference

scales up with the disappointment when the value of the gamble becomes larger. For a smaller

gamble where an individual prefers the gamble over the sure reward, the decision affect theory

implies that the utility difference between the gamble and the sure reward outweighs the

potential disappointment of choosing the gamble. When the gamble and the sure reward are

proportionally amplified, the individual would switch their preference to the sure reward only if

the disappointment function is an increasingly accelerating function of the utility difference.

However, this does not receive empirical support from experiments measuring affective

responses to gamble outcomes (Mellers et al., 1997). In fact, the empirical measurement of the

affective response function even suggests a reverse effect.

Attention-dependent decision theories

There is increasing evidence from eye movement measurements that human decisions are

influenced by the attention they allocate to available options. A natural question is whether the

peanuts effect can be explained by attention-dependent decision theories such as the salience

theory (Bordalo et al., 2012).

Fiedler and Glöckner (2012) found that the number of fixations to an outcome of a gamble

increases with both its value and probability. He and Bhatia (2023) re-analyzed the eye

movement data of Fiedler and Glöckner and further found that when the value of the recently

fixated outcome is higher, participants are more likely to fixate on the winning probability of that

outcome, indicating the cross-dimensional influence of value on the attention to probability.

Consistent with these empirical findings, the salience theory (Bordalo et al., 2012) assumes that

the decision maker's attention is attracted to outcomes of higher value, and as the result, they

would overweight probabilities accompanying higher values. Consequently, the salience theory

would predict an effect in the reverse direction of the peanuts effect and thus cannot explain it.

The two components of the peanuts effect

Though most previous studies (Binswanger, 1981; Estle et al., 2006; Kachelmeier &

Shehata, 1992; Prelec & Loewenstein, 1991; Weber & Chapman, 2005) frame the peanuts

effect as something about risk attitude, Fehr-Duda et al. (2010) find it to be more adequately

described as a modulation of outcome value on the probability distortion function. A closer

examination of the effect reveals two sub-effects (illustrated in Figure 1): (1) the sensitivity

(slope) of subjective probability increases with value, and (2) the elevation (cross-over point) of

subjective probability decreases with value.

Figure 1. The Peanuts Effect on Probability Distortion. Illustration of the peanuts effect in

decision under risk. Subjective probability (aka decision weight) $w(p)$ is plotted as a function of

objective probability p. Compared to that of small gambles (light blue curve), the subjective

probability of large gambles (dark blue curve) has a steeper slope and a lower crossover point

(i.e., where $w(p) = p$).

Though several resource-rational models have treated the distortion of probability (Bhui &

Gershman, 2018; Zhang et al., 2020) or value (Heng et al., 2020; Polanía et al., 2019), the

previous treatments are about probability or value alone and cannot explain why probability

distortion may be influenced by the associated value. To explain such cross-modality influence,

we extended previous work on resource-rational modeling and developed the ARRM framework.

THE ASSEMBLABLE RESOURCE-RATIONAL MODULES FRAMEWORK

One bottleneck of human cognitive processing is its limited resources which may be framed

as information transmission through a constrained communication channel (Bhui et al., 2021;

Dayan & Abbott, 2001; C. R. Sims, 2018; Wei & Stocker, 2015). Following previous work, we

developed the Assemblable Resource-Rational Modules (ARRM) framework (see Figure 2A for

an overview) to model resource-rational agents who use their limited communication channel

adaptively to process the information needed for decision making.

Without loss of generality, the processing of a specific stimulus can be decomposed into an

encoding process (from stimulus s to a noisy internal representation m) and a decoding process

(from representation m to a subjective estimate $\hat{s}$). The encoding and decoding schemes

chosen by a resource-rational agent may depend on the agent's cognitive resources, prior

beliefs about the environment, and optimization goal (loss function). These "modules" together

constitute the ARRM framework. The framework has multiple variants for each module, and as

the "assemblable" in its name suggests, allows the variants from different modules to be

combined in an unconventional way to form new resource-rational models. Below we specify the

possible variants for each module, focusing on how the model space may be systematically

expanded to cover a broader range of decision phenomena.

Cognitive resource module: three allocation problems

Resource-rational models of decision making share the assumption that the brain optimizes

information transmission through a constrained communication channel, but differ in their

assumptions about resource constraints or optimization goals. These models descend from two

theoretical lines: efficient coding (Attneave, 1953; Barlow, 1961; Simoncelli & Olshausen, 2001;

Wei & Stocker, 2015) and the rate-distortion theory (C. J. Bates et al., 2019; Gershman & Bhui,

2020; MacKay, 2003; C. R. Sims, 2016). The resource assumptions in these two lines of models

are analogous to the charges in two types of mobile data plans: Efficient-coding models

resemble plans with a fixed monthly fee, where each bit of transmitted information counts as a

gain; in contrast, rate-distortion models are like plans charged by data usage, where each bit of

information adds to the cost. Regardless of how cognitive resources are defined, the higher the

resource used to encode a stimulus, the more precise the representation (Figure 2C).

Resource-rational agents face three types of allocation problems. The first is the classic

coding problem of how to allocate cognitive resources across different possible values of the to-

be-encoded stimulus. This is also the problem most of previous efficient coding models (Bhui &

Gershman, 2018; Polanía et al., 2019; Wei & Stocker, 2015) focus on, that is, to adjust the

encoding scheme according to the prior distribution (or information source) of the stimulus to

fulfill specific goals.

The second problem considers a more dynamic view: How to allocate cognitive resources

available across time? In 2003, C. A. Sims proposed the hypothesis of *rational inattention* that

people should invest more of their limited cognitive resources in choices that are more important

(C. A. Sims, 2003), which has been used to model a variety of decision phenomena (Gershman

& Bhui, 2020; Grujic et al., 2022; Mikhael et al., 2021; C. A. Sims, 2003). The rational inattention

hypothesis is also consistent with qualitative observations that people tend to take more

cognitive effort when the task incentives increase (Kleinsorge & Rinkenauer, 2012; Otto &

Vassena, 2021). One difference between the first (classic-coding) and the second (dynamic-

view) resource-allocation problems is that the former is only about the to-be-encoded stimulus

itself, whereas the latter may allow influences from other stimulus dimensions, such as

allocating more resources to a probability stimulus when it is in a gamble associated with a

more valuable outcome (Figure 2C), potentially relevant to cross-modality effects like the

peanuts effect.

The third problem addresses resource allocation among different dimensions in multi-

dimensional decision-making scenarios, such as allocating resources between value and

probability in a gamble. Rational agents should allocate more resources to dimensions that are

more uncertain (Dewan, 2020) or contribute more to the task goal (C. J. Bates et al., 2019; C. J.

Bates & Jacobs, 2021). Though we will not cover such cross-dimension resource allocation in

our modeling of the peanuts effect, it is an important part of real-world decisions that can be

integrated into resource-rational modeling.

Figure 2. The ARRM framework of stimulus processing. (**A**) Schema of the framework,

where a resource-rational agent's encoding and decoding processes are constrained by limited

cognitive resources and optimized under specific prior in memory and optimization goal (loss

function). The allocation of cognitive resources may also be optimized. (**B**) Illustration of two

possible origins of the prior information in memory: the stimulus distribution in the current task

(task distribution) and the distribution from long-term life experience (long-term distribution). The

prior distribution can either be a marginal distribution over the stimulus in question (e.g., the

probability of an outcome), or a conjunctive distribution of multiple attributes (e.g., the

conjunctive distribution of value and probability), as implied by the saying "the higher the risk,

the greater the return" (illustrated in the plot for long-term distribution). (**C**) Illustration of

channels with different levels of cognitive resources. Higher cognitive resources lead to higher

representational precision (i.e., lower noise).

Priors in memory module: two sources of distributions

A resource-rational agent must also consider the stimulus distribution of the environment.

More precisely, it is the agent's subjective beliefs about the distribution instead of the objective

distribution that defines its optimization problem. To emphasize that these prior beliefs are

maintained in memory and themselves resource-constrained, we call them *priors in memory*.

These priors can be based on the stimulus distribution in the current task environment (task

distribution) or the long-term environmental statistics (long-term distribution). While using priors

learned from the task distribution seems self-evident for maximizing task performance (Heng et

al., 2020; Jazayeri & Shadlen, 2010), using priors based on the long-term distribution is also

justified by accounting for a wide range of human behaviors in judgment and decision making

(Girshick et al., 2011; Griffiths & Tenenbaum, 2006; Stewart et al., 2015; Wei & Stocker, 2015),

especially when learning the stimulus distribution separately for each task is costly or

implausible due to limited samples (Binz et al., 2022; Dasgupta et al., 2020).

Using the conjunctive distribution of reward and probability in gambles to illustrate these

two sources of priors (Figure 2B), we emphasize two facts. First, these priors are not

necessarily only about one stimulus dimension, as widely assumed in previous resource-rational

models, but may reflect the covariation of multiple dimensions. Second, even when reward and

probability are independent in the task distribution, the long-term distribution from life

experience may exhibit a negative correlation between reward and probability (Pleskac &

Hertwig, 2014), echoing "the higher the risk, the greater the return". Such structural long-term

prior has the potential to explain the interdependence between value and probability in the

peanuts effect.

Possible variants of other modules

Having discussed the modules of cognitive resources and priors in memory, whose

extensions are essential to explaining the peanuts effects, we now briefly summarize the

possible variants of other modules in the ARRM framework.

Encoding schemes, which map stimuli to internal representations, can be classified into

three levels of adaptiveness based on their flexibility in adapting to cognitive resources and

priors in memory: fixed, boundedly-adaptive, and fully-adaptive. Fixed encoding schemes,

assumed in traditional Bayesian observer models (Petzschner et al., 2015), do not change with

cognitive resources or priors. Boundedly-adaptive encoding schemes, such as the Bounded

Log-Odds (BLO) model (Ren et al., 2021; Zhang et al., 2020), may adapt to cognitive resources

or priors but in a constrained way, with fixed functional forms and adaptive parameters. Fully-

adaptive encoding schemes, used in many efficient coding models and rate-distortion models

(Bhui & Gershman, 2018; Heng et al., 2020; Wei & Stocker, 2015), allow for flexible changes in

the encoding mapping and precision based on the prior distribution and available cognitive

resources. The adaptation of encoding schemes to the environment may occur on multiple time

scales, with slow adaptation to long-term environmental statistics shaping the functional form

and fast adjustments within that form. While the speed of adaptation to the task distribution in

general is still largely unknown, there is stronger evidence for trial-by-trial changes in encoding

precision (C. J. Bates & Jacobs, 2021; Gershman & Bhui, 2020).

Decoding schemes, while omitted in some efficient coding models (Bhui & Gershman,

2018; Heng et al., 2020; Stewart et al., 2006), are necessary for cases where a stimulus needs

to be explicitly estimated or integrated with stimuli on other dimensions (Polanía et al., 2019;

Wei & Stocker, 2015; Zhang et al., 2020), such as the represented probability is to be integrated

with value. For a rational agent, a statistically principled decoding method is Bayesian inference

(Petzschner et al., 2015; Wei & Stocker, 2015), which combines the noisy representation with

prior information to calculate the posterior distribution of the stimulus. Alternatively, in rate-

distortion models, the mapping from the stimulus to its estimate can be directly obtained based

on the rate-distortion theory, without specifying the details of encoding and decoding. Even so, a

Bayesian decoding process is implicitly assumed, because it constitutes the only optimal

solution to the optimization problem.

The optimization goal (or loss function) is indispensable for defining any resource-rational

agent. The loss function can be a function of the deviation between stimulus and its subjective

estimate, or refers to the loss that is explicitly defined by the task (e.g., error rate or monetary

loss). In previous efficient coding models, the goal is often to maximize the mutual information

between stimulus and representation (Bhui & Gershman, 2018; Wei & Stocker, 2015). Using the

explicit task goal to define loss function is common in previous rate-distortion models (C. J.

Bates & Jacobs, 2021) but less popular in previous efficient coding models (see Heng et al.,

2020 for an exception), though it is applicable to both lines of resource-rational models.

Solving the exact optimization problem can be difficult or even intractable for the brain,

especially in complex environments and on fast time scales. As a result, humans may adapt to

the environment in a more bounded way than perfect resource-rational agents. The ARRM

framework can model this boundedness in several ways. First, the encoding scheme may be

only partially adaptive to the environment, as assumed in the bounded log-odds model (Zhang

et al., 2020), and approximate implementations of resource rationality, such as the Decision by

Sampling model (Stewart et al., 2006), may better capture human behavior than exact resource-

rational agents (Heng et al., 2020). Second, the encoding scheme typically adapts to the

environment over the long run (Stewart et al., 2006; Wei & Stocker, 2015) rather than on shorter

time scales of minutes or hours (Alempaki et al., 2019; Bujold et al., 2021; Frydman & Jin, 2021;

Ren et al., 2018), while the adaptation of the decoding scheme may be much faster, as

suggested by the Bayesian literature (Maloney & Zhang, 2010; Petzschner et al., 2015). What is

explored in the ARRM framework above are theoretical possibilities, while how humans may

behave like resource-rational agents is an empirical question. Next, we apply the framework to

decision under risk to explain the peanuts effect and examine which set of theoretical

possibilities best fits human behaviors.

ARRM MODELS FOR EXPLAINING THE PEANUTS EFFECT

In the following, we apply the ARRM framework to modeling human decision under risk. By

combining the rational inattention hypothesis of cognitive resource allocation (Gershman & Bhui,

2020; Grujic et al., 2022; C. A. Sims, 2003) with a hypothesis of value-probability covariation in

prior beliefs (Pleskac & Hertwig, 2014), we are able to provide a full explanation for the peanuts

effect in probability distortion.

We use $g\colon (x_1, p; x_2)$ to denote a monetary gamble with two outcomes, that is, receiving x_1

with probability p, or x_2 otherwise, where $|x_1| > |x_2|$. A sure payoff (gain or loss) is a special

case of this two-outcome gamble with $p = 1$. Following CPT (Tversky & Kahneman, 1992), we

assume that the expected utility of gamble g can be computed as[2]

407
$$U(g) = w(p)u(x_1) + \big(1 - w(p)\big)u(x_2), \tag{1}$$

where $u(\cdot)$ denotes the utility function and $w(\cdot)$ denotes the probability weighting (distortion)

function. What differs our following modeling from standard applications of CPT is that we

replace the probability weighting function $w(\cdot)$ of p with the subjective estimate $\hat{p}$, which is

decoded from a noisy representation of p and may vary from gamble to gamble as the

consequence of resource-rational encoding and decoding.

The Rational Inattention (RI) hypothesis

As shown in Figure 2C, the resource-allocation problem can be understood as a tradeoff

between task performance and cognitive effort: A higher encoding precision would lead to a

more accurate estimation and thus better task performance, but at a cost of higher demand for

cognitive resources. To balance task performance and cognitive effort, a resource-rational agent

should allocate cognitive resources among different stimuli according to their potential rewards.

---

[2] This equation holds when both outcomes are gains or losses, i.e., $x_1 > x_2 \geq 0$ or $x_1 < x_2 \leq 0$. When one is gain and the other is loss, they need two separate weighting functions.

In behavioral economics, this is known as the rational inattention (RI) hypothesis (Grujic et al.,

2022; Matějka & McKay, 2015; Mikhael et al., 2021; C. A. Sims, 2003). It addresses the problem

of how to allocate cognitive resources over time to maximize expected reward (i.e., the dynamic

allocation problem): stimuli associated with a larger reward receive more attention, while those

that are worthless are ignored (Kool & Botvinick, 2018; Matějka & McKay, 2015).

When applied to the representation of probability, the RI hypothesis implies that the

cognitive resource increases with the potential gain of the gamble. For gamble $(x_1, p; x_2)$, the

resource allocated to the probability p should increase with its associated potential gain (or

saved loss) $|x_1 - x_2|$:

434
$$R_g = R_0 + \beta \ln(|x_1 - x_2| + 1) \ , \tag{2}$$

where $R_0 \geq 0$ is a parameter for the baseline resource (i.e., when $x_1 - x_2 = 0$), and $\beta \geq 0$ is a

slope parameter controlling how steep the allocated resource changes with value. This

assumption of linear relationship is an approximation to the optimal resource allocation (see

Supplemental Text S3 and Figure S3 for more details). Similar linear-log forms of rational

inattention assumptions have been used in previous studies (Gershman & Bhui, 2020; Mikhael

et al., 2021).

The Structural Prior (SP) hypothesis

According to the module of priors in memory of the ARRM framework, one source for prior

beliefs is the long-term experience in everyday life (figure 2B). Such everyday statistics have

been used by previous resource-rational models to explain human distortion of value, probability

or time (Bhui & Gershman, 2018; Stewart et al., 2006, 2015), but the priors used in these

practices are limited to one single dimension of stimuli.

However, as the saying "the higher the risk, the greater the return" suggests, a structural

relationship of reward and probability—the two dimensions of a gamble—widely exists in

everyday life, ranging from financial investment to the submission of academic papers (Pleskac

& Hertwig, 2014). That is, when the potential value is large, the probability of success tends to

be small. Indeed people may use value as a contextual cue to infer the associated probability

(Leuker et al., 2018, 2019). In the structural prior (SP) hypothesis, we hypothesize that people

have prior beliefs about the probabilistic interdependence between value and probability.

Following previous studies (Khaw et al., 2021), we model the agent's prior belief for p as a

Gaussian distribution on the log-odds scale:

456 $$\lambda(p) \sim N\left(\lambda_{\mathcal{g}}, \sigma_s^2\right),\qquad(3)$$

where $\lambda(p) = \ln\frac{p}{1-p}$ is the log-odds of p. The $\lambda_{\mathcal{g}}$ and σ_s^2 respectively denote the mean and

variance of the Gaussian prior, with the subscript $\mathcal{g}$ of $\lambda_{\mathcal{g}}$ to emphasize its dependence on the

gamble in question. When transformed back to the probability scale, the prior would be *U*-

shaped for large variance and inverted-*U*-shaped for small variance, resembling the beta

distribution used to model the real-world statistics of probability (Stewart et al., 2006; Zhu et al.,

2020).

The SP hypothesis for gamble $\mathcal{g}: (x_1, p; x_2)$, can then be formulated as

462 $$\lambda_{\mathcal{g}} = \lambda_0 - \theta \ln(|x_1 - x_2| + 1) ,\qquad(4)$$

where λ_0 is a baseline parameter, $|x_1 - x_2|$ (as before) is the potential gain (or saved loss) of the

gamble, and θ is a slope parameter controlling the direction and extent that probability is

expected to change with value , with $\theta > 0$ indicating an assumed negative correlation between

probability and value, $\theta = 0$ for no correlation, and $\theta < 0$ for positive correlation.

Probability estimation models

To implement the resource rational framework for probability estimation, we adopt three

previous resource-rational decision models as the "base" models and combine them with the RI

and SP hypotheses ("modifiers") to produce a set of 10 different models. Below we briefly

review each of the base models and how they may be enhanced by the RI and SP hypotheses

(see Tables 1 and 2 for a summary of model notations).

Table 1. General Notations

Symbol	
s	Stimulus to be represented.
m	Mental representation of the stimulus.
ε	Mental representation noise.
$g: (x_1, p; x_2)$	Monetary gamble with two outcomes, that is, receiving x_1 with probability p, or x_2 otherwise, where $|x_1| > |x_2|$.
$\widehat{CE}$	Measured certainty equivalent (CE) in the task, that is, the value of sure payoffs that is equally preferred to the gamble g.
$\widehat{NCE}$	Normalized certainty equivalent, $\widehat{NCE} = (\widehat{CE} - x_2)/(x_1 - x_2)$.
$u(\cdot)$	Utility function.
α	Exponent parameter of the power utility function.
$U(g)$	Expected utility of gamble g.
$w(\cdot)$	Probability weighting (distortion) function.
R_g	Cognitive resources allocated to represent the probability in gamble g.
R_0	Parameter indicating the baseline resource.
β	Slope parameter controlling the effect of value on resource allocation.
m_p	Noisy representation of probability p.
$\hat{p}$	Subjective estimate of probability p.
$\lambda(\cdot)$	Log-odds function, $\lambda(p) = \ln \frac{p}{1-p}$.
$\lambda^{-1}(\cdot)$	The inverse function of $\lambda(\cdot)$.
$\lambda(p)$	Log-odds of p.
$\widehat{\lambda_m}$	The estimate of $\lambda(p)$ given m.
$\widehat{\lambda_p}$	The expected estimate for $\lambda(p)$ over different values of m.
$N(\lambda_g, \sigma_s^2)$	The prior Gaussian distribution assumed for $\lambda(p)$, where λ_g denotes the mean and σ_s^2 the variance.
θ	Slope parameter controlling the relationship between prior mean probability λ_g and the associated potential gain.
λ_0	Parameter indicating the baseline prior mean.

473   **Table 2. Model Notations**

Decision by Sampling (DbS) Model	
$\Phi(\cdot)$	The cumulative distribution function of the standard Gaussian distribution.
λ_s	Parameter for the mean of the Gaussian prior for $\lambda(p)$, which is replaced by λ_0 and θ in the SP hypothesis.
σ_s^2	Parameter for the variance of the Gaussian prior for $\lambda(p)$.

Rate-Distortion (RD) Model	
R	Parameter for the channel capacity, which is replaced by R_0 and β in the RI hypothesis.
λ_s	Parameter for the mean of the Gaussian prior for $\lambda(p)$, which is replaced by λ_0 and θ in the SP hypothesis.

Bounded Log-Odds (BLO) Model	
Δ^+, Δ^-	Parameters controlling the bounds of the log-odds representation.
Ψ	Parameter for the half-range of the internal representation scale (resource), which is replaced by R_0 and β in the RI hypothesis.
$\widehat{p_m}$	The estimated probability given representation m, that is, $\widehat{p_m} = \lambda^{-1}(\widehat{\lambda_m})$.
$V(\widehat{p_m})$	Variance of $\widehat{p_m}$ due to Gaussian noise on the log-odds scale.
κ	Parameter that controls the effect of $V(\widehat{p_m})$.
λ_s	Parameter for mean of the Gaussian prior, which is replaced by λ_0 and θ in the SP hypothesis.

Decision Model for Certainty Equivalent Task	
NCE	Predicted normalized certainty equivalent of the model.
ε_{NCE}	Log-odds scale Gaussian estimation noise of $\lambda(NCE)$, $\varepsilon_{NCE} \sim N(0, \sigma_{NCE}^2)$.
σ_{NCE}^2	Variance parameter of estimation noise.

Decision Model for Binary Choice Task	
$Pr(\mathcal{g}_i)$	Probability of choose gamble $\mathcal{g}_i$.
b	Inverse temperature parameter of the choice.

Decision by Sampling (DbS) model

The DbS model (Bhui & Gershman, 2018; Stewart et al., 2006) belongs to the theoretical

line of efficient coding, assuming fully-adaptive encoding scheme, no decoding scheme and the

optimization goal of maximizing mutual information. As its name suggests, it starts with sampling

from memory. It assumes that the agent compares the stimulus with each sample and

calculates the proportion of times the former is larger than the latter as the subjective estimation

of the stimulus. When sample size is sufficiently large, this subjective estimation approximates

the cumulative distribution function of the prior distribution of the samples (Bhui et al., 2021;

Bhui & Gershman, 2018; Stewart et al., 2015). Given prior $\lambda(p) \sim N(\lambda_s, \sigma_s^2)$ (Eq. 3, with λ_g set

to a constant λ_s), the subjective estimation of probability p can be written as:

487
$$\hat{p} = \Phi(\frac{\lambda(p) - \lambda_s}{\sigma_s}),$$
(5)

where $\Phi(\cdot)$ denotes the cumulative distribution function of the standard Gaussian distribution.

There is no obvious way that the DbS model can be enhanced by the RI hypothesis,

because its subjective estimation (Eq. 5) is not influenced by the available cognitive resource (in

fact, the model assumes a sufficiently large sample size to approximate the cumulative

probability function). Therefore, we only consider the SP hypothesis for DbS, which is simply to

replace the λ_s in Eq. 5 with the λ_g in Eq. 4. In the special case of $\theta = 0$, it reduces to the original

DbS without the SP hypothesis. The original DbS model has two free parameters: λ_s, and σ_s.

The DbS+SP model replaces the parameter λ_s with two parameters: λ_0 and θ. Unless otherwise

specified, our count of model parameters does not include the parameters of the decision model

(introduced later), which are shared across all 10 models.

Rate-Distortion (RD) model

The RD model assumes a constraint on the rate of transmitted information and optimizes

encoding and decoding schemes under this constraint to minimize the expected loss incurred by

distorted subjective estimation of the stimulus. It has a fully-adaptive encoding scheme and a

Bayesian decoding scheme, whose optimization goal may be defined by the task.

Similar to previous RD models (C. J. Bates et al., 2019; Gershman & Bhui, 2020), we

assume a Gaussian information source and a squared-error loss function, for which the optimal

encoding scheme is a linear mapping with homogeneous Gaussian noise (Berger & Gibson,

1998). We further assume that the encoding of probability is on the log-odd scale (Khaw et al.,

2021; Zhang et al., 2020; Zhang & Maloney, 2012), so the representation can be written as

507
$$m = \lambda(p) + \varepsilon. \tag{6}$$

508 Here $\lambda(p)$ is the log-odds of probability p, and $\varepsilon \sim N(0, \sigma_\varepsilon^2)$ is a noise term with mean 0 and

509 variance σ_ε^2.

510 The optimal decoding scheme is Bayesian decoding. Given the Gaussian prior $\lambda(p) \sim$

511 $N(\lambda_s, \sigma_s^2)$ and representation m, the posterior estimate of $\lambda(p)$ follows a Gaussian distribution:

518
$$\lambda(p)|m \sim N\left(\frac{\sigma_s^2 m + \sigma_\varepsilon^2 \lambda_s}{\sigma_s^2 + \sigma_\varepsilon^2}, \frac{\sigma_s^2 \sigma_\varepsilon^2}{\sigma_s^2 + \sigma_\varepsilon^2}\right). \tag{7}$$

512 Given m, the optimal estimate for $\lambda(p)$ that minimizes squared error on the log-odds scale is the

513 posterior mean,

519
$$\widehat{\lambda_m} = \frac{\sigma_s^2 m + \sigma_\varepsilon^2 \lambda_s}{\sigma_s^2 + \sigma_\varepsilon^2}. \tag{8}$$

514 Marginalizing out m, we have the expected estimate for $\lambda(p)$:

520
$$\begin{aligned} \widehat{\lambda_p} &= \mathbb{E}_{m|\lambda(p)} \frac{\sigma_s^2 m + \sigma_\varepsilon^2 \lambda_s}{\sigma_s^2 + \sigma_\varepsilon^2} \\ &= (1 - \frac{1}{\frac{\sigma_s^2}{\sigma_\varepsilon^2} + 1})\lambda(p) + \frac{1}{\frac{\sigma_s^2}{\sigma_\varepsilon^2} + 1}\lambda_s. \end{aligned} \tag{9}$$

515 According to information theory, for a Gaussian source (variance σ_s^2) transmitted through a

516 Gaussian channel (variance σ_ε^2), the rate of information flow, R, equals the channel capacity,

517 which satisfies

521
$$R = \frac{1}{2}\ln\left(1 + \frac{\sigma_s^2}{\sigma_\varepsilon^2}\right). \tag{10}$$

522 Substituting Eq. 10 into Eq. 9, we have

529
$$\widehat{\lambda_p} = (1 - e^{-2R})\lambda(p) + e^{-2R}\lambda_s \,. \tag{11}$$

This form is consistent with Linear in Log-Odds—a two-parameter descriptive model of

probability distortion widely used in previous studies (Gonzalez & Wu, 1999; Zhang & Maloney,

2012)—and provides a cognitive explanation for its two parameters. The cognitive resource R

controls the sensitivity parameter (slope) of the distortion curve, with higher resource associated

with higher sensitivity (steeper slope); the prior λ_s controls the elevation parameter (intercept) of

the curve.

The combinations of the RD model with the RI and SP hypotheses are straightforward,

which respectively replace the R and λ_s in Eq. 11 with the R_g in Eq. 2 and the λ_g in Eq. 4. The

original RD model has two free parameters: R and λ_s. The RD+RI and RD+RI+SP models

replace the parameter R with two parameters: R_0 and β. The RD+SP and RD+RI+SP models

replace the parameter λ_s with two parameters: λ_0 and θ.

Bounded Log-Odds (BLO) model

Similar to DbS, the BLO model (Ren et al., 2021; Zhang et al., 2020) is an efficient coding

model and assumes mutual information maximization as the optimization goal. But different

from DbS, it has a boundedly-adaptive encoding scheme that uses fixed functional forms and

adaptive parameters to approximate optimal encoding solutions, and an approximately

Bayesian decoding scheme.

The model assumes an agent who encodes probability in log-odds on an internal scale with

finite length and homogeneous Gaussian noise. Define a bounded transformation of log-odds

545
$$\Gamma(p) = \begin{cases} \Delta^-, & \lambda(p) < \Delta^- \\ \lambda(p), & \Delta^- \le \lambda(p) \le \Delta^+ \\ \Delta^+, & \lambda(p) > \Delta^+ \end{cases} , \tag{12}$$

543 where $\lambda(p)$ (as before) is the log-odds of p, and Δ^- and Δ^+ are the bounds parameters

544 specifying the encoded stimulus range. A mapping of the transformed $\Gamma(p)$ to the internal

546   representation scale $[-\Psi, \Psi]$ is:

548
$$\Lambda(p) = \frac{2\Psi}{\Delta^+ - \Delta^-}[\Gamma(p) - (\Delta^+ + \Delta^-)/2].\tag{13}$$

547   The noisy internal representation is

549
$$m = \Lambda(p) + \varepsilon.\tag{14}$$

where $\varepsilon \sim N(0, \sigma_\varepsilon^2)$ is a noise term with mean 0 and variance σ_ε^2.

A subjective log-odds $\widehat{\lambda_m}$ can be decoded from the representation m and further

transformed back to the probability scale to obtain $\widehat{p_m} = \lambda^{-1}(\widehat{\lambda_m})$. The decoding goal of the BLO

model is not to minimize the squared error for $\widehat{\lambda_m}$ on the log-odds scale, but to minimize the

squared error for $\widehat{p_m}$ on the probability scale, whose Bayesian inference has no known

analytical form. The BLO model adopts the following form to compensate for the

representational noise:

560
$$\widehat{\lambda_m} = \frac{1}{1 + \kappa V(\widehat{p_m})}m + (1 - \frac{1}{1 + \kappa V(\widehat{p_m})})\lambda_s,\tag{15}$$

557   where λ_s, as before, is the mean of the Gaussian prior, κ is a free parameter, $V(\widehat{p_m})$ is the

558   variance of $\widehat{p_m}$ due to Gaussian noise on the log-odds scale, whose approximation has the

559   form:

561
$$V(\widehat{p_m}) \approx \frac{3\sigma_\varepsilon^2}{2\pi^2}p(1 - p).\tag{16}$$

562   The agent is assumed to have a separate estimate of this variance without knowing the exact

563   value of p. The parameter σ_ε is redundant with κ and thus omitted in model fitting.

564   Similar to the proof for Eq. 9, we can write the expected estimate of λ_m given p as

565
$$\widehat{\lambda_p} = \frac{1}{1 + \kappa V(\widehat{p_m})}\Lambda(p) + (1 - \frac{1}{1 + \kappa V(\widehat{p_m})})\lambda_s,\tag{17}$$

To apply the RI hypothesis to BLO, we replace Ψ with the R_g in Eq. 2. Similar to the

enhancement of the DbS and RD models, the SP hypothesis is applied to BLO through

replacing the λ_s in Eq. 17 with the λ_g in Eq. 4.

Decision model

All the probability estimation models above are combined with the same decision model to

produce responses in a specific task. We assume a power utility function

572
$$u(x) = x^\alpha, \tag{18}$$

573 where $\alpha > 0$ is a free parameter, which may be different for gain and loss. Substituting it into Eq.

574 1 and substituting the probability weighting function $w(p)$ in Eq. 1 with the subjective estimate $\hat{p}$,

575 the expected utility of gamble g can be written as

577
$$U(g) = \hat{p}x_1^\alpha + (1 - \hat{p})x_2^\alpha. \tag{19}$$

576 where $\hat{p}$ follows Eq. 5 for the DbS model and computed as

579
$$\hat{p} = \lambda^{-1}(\widehat{\lambda_p}) \tag{20}$$

for the RD and BLO models.

Two typical tasks of decision under risk, certainty equivalent task and binary choice task,

are modeled as the following.

Certainty Equivalent Task

On each trial, participants choose between a gamble and an array of sure payoffs of

varying values so that their certainty equivalent (CE)—the value of sure payoffs that is equally

preferred—to each gamble can be estimated for individual participants. The decision model

above predicts

591
$$CE = [\hat{p}x_1^\alpha + (1 - \hat{p})x_2^\alpha]^{1/\alpha}. \tag{21}$$

587 We define normalized certainty equivalent

592
$$\text{NCE} = (\text{CE} - x_2)/(x_1 - x_2) \tag{22}$$

588 as a measure of subjective probability and compute a log-odds transformation of the measure

589 for both participants' and model-predicted NCEs. Participants' $\lambda(\widehat{NCE})$ is modeled as model

590 prediction plus a Gaussian noise:

593
$$\lambda(\widehat{NCE}) = \lambda(NCE) + \varepsilon_{NCE} , \tag{23}$$

594   where $\varepsilon_{NCE} \sim N(0, \sigma_{NCE}^2)$ and σ_{NCE} is a free parameter.

595   ***Binary Choice Task***

596   On each trial, participants choose between two gambles, or between one gamble and one

597   sure payoff. We model the probability of choosing gamble $\mathcal{g}_i$ as a SoftMax function determined

598   by its utility difference with the other gamble:

599
$$Pr(\mathcal{g}_i) = \frac{e^{bU(\mathcal{g}_i)}}{\sum_{j=1}^2 e^{bU(\mathcal{g}_j)}} \, , \tag{24}$$

where b is an inverse temperature parameter that controls the stochasticity of the choice.

Participants' binary choice on each trial is modeled as a Bernoulli random variable based on

$Pr(\mathcal{g}_i)$.

STUDY 1: MODELING THE PEANUTS EFFECT IN THE ARRM FRAMEWORK

To see how well the resource-rational models we constructed in the ARRM framework can

explain human decision behaviors, we first need a model-free quantification of the phenomenon

in question. For the peanuts effect, which reflects the influence of outcome value on probability

distortion (Fehr-Duda et al., 2010), the ideal experimental design shall allow us to measure the

probability distortion curve separately for different values. Fortunately, two previously published

datasets satisfy our requirement, one from Gonzalez and Wu (1999) and the other from Zhang

et al. (2020), which used an almost identical design of 165 different two-outcome gambles from

a factorial combination of 11 different probabilities and 15 different sets of values (see Methods

in Appendix). For each of the 10 or 75 participants, the authors of the studies measured the

certainty equivalent (CE) for each gamble, that is, the sure reward that is perceived as equally

preferable as the gamble. Based on these certainty equivalents, we elicited the probability

distortion curve for each set of values and quantified the two aspects of the peanuts effect—how

the sensitivity and elevation parameters of probability distortion change with value.

The peanuts effect in the GW99 and ZRM20 datasets

Non-parametric estimation of probability distortions had been performed for the GW99

(Gonzalez & Wu, 1999) and ZRM20 (JDA and JDB) datasets (Zhang et al., 2020) in their

original studies. Such estimation, however, had collapsed data across gambles with different

outcome values.

The normalized certainty equivalent, $\mathrm{NCE} = (\mathrm{CE} - x_2)/(x_1 - x_2)$, was used as a measure of

subjective probability, which could be computed for each gamble based on the estimated CE for

the participant (denoted $\widehat{NCE}$ as estimation). Though $\widehat{NCE}$ is not strictly equal to subjective

probability unless the utility function is linear, it served as a useful measure to visualize the

influence of outcome value on probability distortion. Figure 3 plots the mean $\widehat{NCE}$ across

participants for each dataset (GW99, n=10) or sub-dataset (JDA, n=51; JDB, n=24), separately

for gambles with different x_1 (Only gambles with $x_2 = 0$ is plotted for visualization purposes).

The observations in all these datasets confirmed the peanuts effect and its two sub-effects,

whose descriptions had been scattered in different previous studies (Fehr-Duda et al., 2010;

Green et al., 1999; Prelec & Loewenstein, 1991). Other than exhibiting the typical inverted *S*-

shape (linear in the log-odds scale) as in the original analyses of the datasets, the probability

distortion curve had (1) *greater sensitivity* (i.e., steeper slope) and (2) *lower elevation* (i.e.,

smaller crossover point) for larger gambles (darker curves in Figure 3). The sensitivity effect and

elevation effect were supported by linear mixed-effect model (LMM) analysis for participants'

$\widehat{NCE}$ (Eq. 11 in Methods of Appendix). When the potential gain ($D = |x_1 - x_2|$) was greater,

participants were more sensitive to the differences between different probabilities (D by

probability interaction, GW99: *b* = 0.084, 95% CI [0.055, 0.114], *P* < 0.001; JDA: *b* = 0.067, 95%

CI [0.060, 0.074], *P* < 0.001; JDB: *b* = 0.050, 95% CI [0.019, 0.081], *P* = 0.002), and had lower

$\widehat{NCE}$ (main effect of D, GW99: *b* = −0.211, 95% CI [−0.270, −0.153], *P* < 0.001; JDA: *b* =

−0.090, 95% CI [−0.114, −0.066], *P* < 0.001; JDB: *b* = −0.093, 95% CI [−0.131, −0.055], *P* <

0.001).

Figure 3. The peanuts effect in the GW99 and ZRM20 (JDA and JDB) datasets. For each

dataset or sub-dataset (one column), participants' normalized certainty equivalent ($\widehat{NCE}$, a

measure of subjective probability) is plotted against objective probability (p), separately

visualized for gambles ($x_1, p; 0$) with different x_1 (color-coded in different darkness). The upper

and lower rows are respectively for probability and log-odds plots. Shadings denote standard

error. Both sub-effects of the peanuts effect are visible in all the datasets: the larger the gamble

(darker curves), (1) the greater the sensitivity of subjective probability, and (2) the lower the

elevation of subjective probability.

Exchangeability test: rejecting the separability assumption of value and

probability

If participants' choices had followed the prospect theory with power utility function $u(x) = $

x^α and any probability weighting function $w(p)$, for gamble ($x_1, p; x_2$) with $x_2 = 0$, we would

have $NCE = w(p)^\alpha$. If so, NCE would simply be a function of p and have nothing to do with

outcome value. However, as shown in the sensitivity and elevation effects above, NCE changed

systematically with outcome value. In other words, the peanuts effect violates the separability

assumption widely accepted in previous decision models—utility is only determined by value

and subjective probability only by probability. This has motivated us to develop resource-rational

models to capture the cross-dimensional influence of outcome value on probability distortion.

But one may wonder whether some non-power utility function, such as the four-fold function

proposed by Markowitz (1952), could explain the peanuts effect without modifying the

separability assumption. To exclude this possibility, we developed a model-free test for

separability, termed the *exchangeability test*, whose conclusion can apply to any forms of utility

and probability weighting functions.

The basic idea of the test is to navigate in a space of gambles through two different paths,

analogous to first going west then north vs. first north then west in the physical space. If the

separability between value and probability held, the two paths would lead to the same

destination. In particular, the test (illustrated in Figure 4A) is based on the CE measured in the

GW99 and ZRM20 datasets for different gambles (Figure 3). For gamble $(x_1, p; 0)$, the

separability assumption implies

682
$$U(x_1, p) = w(p)u(x_1) = U(CE, 1), \tag{25}$$

where $U(x_1, p)$ is the expected utility of the gamble, and $U(CE, 1)$ is the utility of the CE. For any

$x_a > x_b > x_c$, we could find probabilities p_b and p_c so that the CE of gamble $(x_a, p_b; 0)$ is x_b and

the CE of gamble $(x_a, p_c; 0)$ is x_c. Using these two probabilities we can construct two new

gambles $(x_c, p_b; 0)$ and $(x_b, p_c; 0)$. It is easy to prove that these two gambles have the same CE

(by applying Eq. 25). Significant differences between the two gambles would allow us to reject

separability (see Methods in Appendix for more details).

The GW99 and ZRM20 datasets allowed us to test 40 pairs of equivalence, across which

the measured CE for $(x_c, p_b; 0)$ and $(x_b, p_c; 0)$ were significantly different from each other (paired

t-test, $t(39) = 2.79$, p=0.008), thus rejecting the separability assumption (Figure 4B). That is, no

utility or probability weighting functions would explain the observed peanuts effect, unless value

and probability are allowed to influence the processing of each other.

Figure 4. The exchangeability test in the GW99 and ZRM20 datasets. (**A**) Illustration of the

rational of the exchangeability test. The test was based on the 8 certainty equivalents (CE)

curves estimated from the datasets, separately for gambles with $x_1 = 25, 50, 75, 100, 150,$

$200, 400, 800$. From these 8 different values of x_1, we drew 40 combinations of x_a, x_b, x_c that

satisfy $(x_a, p_b; 0) \sim x_b$, $(x_a, p_c; 0) \sim x_c$, and $0.01 \leq p_b, p_c \leq 0.99$, where $\sim$ denotes "equally

preferred" (**left panel**). We then tested whether the equivalence pair predicted by the

separability of value and probability—$(x_c, p_b; 0)$ and $(x_b, p_c; 0)$—were equivalent in CE (**right**

panel). (**B**) Results of the exchangeability test: the histogram of the 40 equivalence pairs' CE

differences. The mean $(CE_{x_b, p_c} - CE_{x_b, p_c})/x_a$ of the 40 equivalence pairs were significantly

greater than 0.

Testing 10 resource-rational models in the ARRM framework

Next, we will show resource-rational models could provide a full explanation for the peanuts

effect. Meanwhile, by comparing models with or without a specific resource-rational hypothesis,

we can see whether the hypothesis holds for human decision behavior.

We constructed 10 resource-rational models in the ARRM framework, using three different

base models with or without the RI or SP hypothesis, and fit the models to each participant's

$\widehat{NCE}$ using maximum likelihood estimates (see Appendix and Supplemental Methods for

details). The three base models were the Bounded Log-Odds model (BLO, Zhang et al., 2020),

the Decision by Sampling model (DbS, Bhui & Gershman, 2018; Stewart et al., 2006), and the

Rate-Distortion Model (RD, Bates et al., 2019; Gershman & Bhui, 2020), which have different

resource-rational assumptions (see Methods). We used the Akaike Information Criterion (AIC;

Akaike, 1974) as the metric of goodness-of-fit for model comparison. Unlike the Bayesian

Information Criterion (BIC, Schwarz, 1978), AIC does not rely on the unrealistic assumption that

the "true model" must be one of the models we tested (Gelman & Shalizi, 2013); AIC is also

more robust than BIC for finite sample size (Vrieze, 2012). As shown in Figure 5A, the

BLO+RI+SP model was the best-fitting model, achieving the lowest summed ΔAIC (the lower

the better) in the JDA and JDB datasets. For participants collapsed across all the datasets, the

group-level Bayesian model selection (Rigoux et al., 2014; Stephan et al., 2009) also shows that

the BLO+RI+SP model outperformed the other models (higher protected exceedance probability

in pairwise comparison).

By comparing models that only differ in one dimension of assumptions, we can see which

assumption best agrees with human data. In most cases, models based on the coding scheme

of BLO were better than those based on DbS or RD, though the AIC difference was moderate.

Regardless of the choice of the base models (DbS, RD, or BLO), the models enhanced with the

RI or SP hypothesis always fit better than those without them. The structural prior parameter θ

(Eq. 4) in the winning model (BLO+RI+SP) was significantly greater than 0 (one-sample *t*-test,

one-sided: $t(84) = 2.506$, $p = 0.007$), implying a prior belief consistent with the saying "the higher

the risk, the greater the return".

Figure 5. Model comparison results of the GW99 and ZRM20 (JDA and JDB) datasets. (**A**)

Summed ΔAIC. The ΔAIC (with the BLO+RI+SP model as the reference) summed over

participants is plotted as the metric of goodness-of-fit for each of the 10 models constructed in

the ARRM framework. Smaller summed ΔAIC indicates better fit. To highlight the differences

between models with and without the RI or SP hypothesis, models are color coded into four

categories: base models (without RI or SP), RI models (with RI, without SP), SP models (with

SP, without RI), and full models (with both RI and SP). Each panel is for one dataset or sub-

dataset. In all datasets, the full models (orange) performed the best. (**B**) Results of group-level

pairwise model comparison for participants collapsed across the GW99 and ZRM20 datasets.

The protected exceedance probability (P_{exc}, the probability that a specific model outperforms the

other models), a group-level Bayesian measure of goodness-of-fit is calculated for comparison

between each pair of the models. The darkest red and darkest blue respectively code that the

row model outperforms the column model at a probability of 1 and 0.

746  The BLO+RI+SP model can well capture both sub-effects of the peanuts effect as well as

747 the inverted-*S*-shaped probability distortion (Figure 6). Intuitively, the sensitivity effect—the

748 increase of sensitivity with gamble outcome—is explained by the RI hypothesis, which assumes

749 that people would invest more cognitive resources to gambles of higher values. The elevation

750 effect—the decrease of crossover point with gamble outcome—is explained by the SP

751 hypothesis that assumes a negative correlation between probability and outcome value.

752 According to the exchangeability test, the predictions of the BLO+RI+SP model show similar

753 rejection of the separability assumption as the data do (Supplemental Figure S4).

756 **Figure 6. Data versus model predictions, pooled over the GW99 and ZRM20 datasets**.

757 Participants' probability distortion curves ($\widehat{NCE}$, upper-left panel) versus model-predicted

758 distortion curves (NCE, other three panels), separately visualized for gambles $(x_1, p; 0)$ with

759 different x_1. The prediction of the best-fit BLO+RI+SP model well captured both the sensitivity

760 and elevation effect. Those of the BLO+RI and BLO+SP respectively captured the sensitivity

and elevation effect, but not both, illustrating the necessity of both hypotheses. Conventions

follow Figure 3.

To summarize, the BLO model enhanced by the RI and SP hypotheses provided a full

explanation for the peanuts effect in decision under risk, with the hypotheses respectively

accounting for the two sub-effects. Though the 10 models we considered above were all

resource-rational models, a comprehensive set of non-resource-rational models were tested on

the GW99 and ZRM20 (JDA and JDB) datasets by Zhang et al. (2020), according to which BLO

outperformed all of a large set of decision models they tested, including the conventional CPT

model and several heuristic-based models.. To further verify that decision theories based on

other psychological mechanisms such as disappointment (disappointment theory, Loomes &

Sugden, 1986), regret (regret theory, Loomes & Sugden, 1982), or attention (salience theory,

Bordalo et al., 2012) could not provide a better fit to the data, we constructed three additional

models (see Appendix and Table 3 for details). Consistent with our reasoning earlier in the

introduction of the peanuts effect, all three models fit much worse than our resource-rational

models (Supplemental Figures S5 and S6).

STUDY 2: REPLICATING THE PEANUTS EFFECT AND ITS ARRM MODELING IN A

BINARY CHOICE TASK

Both the GW99 and ZRM20 datasets we reanalyzed above were collected with the

certainty equivalent task, where the options were presented in a tabular form, contrasting one

gamble with a list of sure rewards in an ascending or descending order. This tabular

presentation is efficient in eliciting certainty equivalents but is not the most typical scenario in

decision making. To exclude the possibility that our findings only apply to the certainty

equivalent task, we performed a new experiment of decision under risk using a binary choice

task, where participants chose between a two-outcome gamble $(x_1, p; 0)$ and a sure reward on

each trial. There were 8 levels of value x_1 (25, 50, 75, 100, 150, 200, 400 or 800 Chinese Yuan)

and 5 levels of winning probability p (0.05, 0.25, 0.5, 0.75 of 0.95), combining into 40 different

gambles. Each gamble was repeated for 10 times, paired with different sure rewards that were

selected by an adaptive procedure (see Methods in Appendix for details).

In this binary choice task (Figure 7AB, $n = 21$), we replicated the peanuts effect found in

the certainty equivalent task of Study 1. According to the LMM analysis on participants' $\widehat{NCE}$,

when the potential gain D of the gamble was greater, participants were more sensitive to the

differences between different probabilities (D by probability interaction, b = 0.039, 95% CI

[0.006, 0.071], P = 0.020), and had lower subjective estimates of the probabilities (main effect of

D, b = −0.084, 95% CI [−0.128, −0.041], P < 0.001).

Figure 7. Task and results of the binary choice experiment (*n*=21). (**A**) The binary choice

task. On each trial, participants chose whether to receive a gamble or a sure reward. The "元"in

the display is the Chinese character for Yuan. (**B**) The measured peanuts effects (left) versus

the predictions of the BLO+RI+SP model (right). To facilitate comparison with the results of the

certainty equivalent task (Figure 3), participants' choices were used to derive certainty

equivalents, which were then transformed into normalized certainty equivalent ($\widehat{NCE}$, upper

panels) and its log-odds ($\lambda(\widehat{NCE})$, lower panels) for visualization. Conventions follow Figure 3.

Similar to the results of the certainty equivalent task, gambles with a higher potential gain were

associated with higher sensitivity and lower elevation in subjective probability (i.e., the two sub-

effects of the peanuts effect). (**C**) Protected exceedance probability (P_{exc}) for pairwise model

comparisons. The darkest red and darkest blue respectively code that the row model

outperforms the column model at a probability of 1 and 0. (**D**) Model comparison results.

Conventions follow Figure 5. Again, the BLO+RI+SP model outperformed all other models in

goodness-of-fit.

Similar to Study 1, the BLO+RI+SP model was the best model among the 10 resource-

rational models in fitting participants' binary choices (Figure 7CD). Again, the BLO base (coding

scheme) outperformed the other two, and the models with the RI or SP hypothesis

outperformed those without them, other things being the same. The structural prior parameter θ

in the winning model (BLO+RI+SP) was again significantly greater than 0 (one-sample t-test,

one-sided: $t(19) = 3.597$, $p < 0.001$). An additional LMM analysis on decision variability provides

further support for the RI hypothesis (see Supplemental Figure S11 and its legend for details).

Similar to Study 1, all the 10 resource-rational models outperformed the models based on the

disappointment theory, regret theory, or salience theory (Supplemental Figures S7 and S8).

STUDY 3: USING ARRM TO MEASURE PROBABILITY DISTORTIONS UNDER GAIN

AND LOSS

We have shown that the peanuts effect in decision under risk can be fully explained by

resource-rational models developed in the ARRM framework, as the consequence of allocating

more resources to higher-valued gambles (the RI hypothesis) and compensating for the

covariation of value and probability in life experience (the SP hypothesis). But the datasets we

analyzed in Studies 1 and 2 were limited to the gain domain (i.e., participants chose between

risky and sure rewards). In Study 3, we extend our findings to the loss domain, reanalyzing the

FD05 dataset from Fehr-Duda et al. (2010), where 153 participants were tested on both gain

gambles and loss gambles. The dataset was also among the few decision studies that involved

"real money" for participants instead of imaginary or small monetary payoffs.

As we introduced earlier, Fehr-Duda et al. (2010) were the first to propose that the peanuts

effect reflects the effect of outcome value on probability distortion; they further measured the

change of the probability distortion curve under different levels of values, separately for the gain

and loss domains. In our reanalysis, we fit their dataset using the winning ARRM model, the

BLO model enhanced with the RI and SP hypotheses. On one hand, we could see how well the

model can explain probability distortion patterns in the loss domain. On the other hand, the

model parameters would allow us to understand why probability distortion may differ between

gain and loss, that is, whether the allocation of cognitive resources or compensation for prior

beliefs may differ between the two domains.

Figure 8. Modeling results for the FD05 Dataset (n=153). (A) Model comparison results for

the FD05 dataset (153 participants, each of whom completed 56 trials). Different utility functions

were used for gain and loss. Smaller ΔAIC indicates better fit. We did not (as for Studies 1 and

2) plot the results of group-level Bayesian model comparison, which shows negligible

differences across the models. (**B**) Participants' probability distortion curves (upper row) versus

model-predicted distortion curves (lower row). The left and right columns are respectively for the

gain and loss domains. Similar to Figure 6, participants' normalized certainty equivalent ($\widehat{NCE}$) is

plotted against objective probability (p). For visualization purposes, the gambles in the FD05

dataset were divided into two categories according to whether the potential gain $D = |x_1 - x_2|$ of

the gamble $(x_1, p; x_2)$ was greater than 65 Yuan (darker curve) or not (lighter curve).

Similar to Studies 1 and 2, we visualized probability distortions separately for gambles with

different outcomes (Figure 8B) and ran an LMM analysis to verify the possible main and

interaction effects of potential gain (D), probability, and outcome domain (gain or loss) on

participants' $\widehat{NCE}$. As to the elevation effect, participants' subjective estimates of the probabilities

decreased with the potential gain D ($b = -0.141$, 95% CI [-0.165, -0.117], $P < 0.001$), with an

attenuated decreasing trend in the loss domain (D by IsLoss interaction, b = 0.121, 95% CI

[0.090, 0.151], P < 0.001). Though participants' sensitivity to probability did not change with D

(D by probability interaction, b = −0.011, 95% CI [−0.028, 0.007], P = 0.239), a three-way

interaction with the outcome domain (D by probability by IsLoss interaction, b = 0.048, 95% CI

[0.023, 0.073], P < 0.001) indicates that the sensitivity effect might exist in the loss domain. The

lack of sensitivity effect in the gain domain might reflect a lack of statistical power, because a

significant sensitivity effect was identified in our following modeling analysis.

Again, according to the summed AIC, the best-fitting model to participants' choices was the

BLO+RI+SP model (Figure 8A), though group-level Bayesian model selection shows negligible

differences between different models (the probability that the null hypothesis is true, BOR =

0.996). Resource-rational models still outperformed the disappointment, regret, or salience

theory models (Supplemental Figures S9 and S10). To obtain reliable parameter estimates for

further analysis, we also performed a hierarchical Bayesian fit for the BLO+RI+SP model. The

fitted model can well capture participants' behaviors, including the peanuts effect, in both the

gain and loss domains (Figure 8B). Consist with our findings in Studies 1 and 2, participants

tended to invest more cognitive resources to gambles involving larger stakes, with the group-

level rational-inattention parameters (Eq. 2) in both the gain (μ_{β_G}) and loss (μ_{β_L}) domains to be

greater than 0 (95% HDI > 0; see Figure 9A, left panel). The group-level structural-prior

parameters (Eq. 4) μ_{θ_G} and μ_{θ_L} were also both greater than 0 (95% HDI > 0; see Figure 9B, left

panel), as if participants held a prior belief that higher risk shall accompany higher gain or loss.

Figure 9. Gain versus loss: group-level rational inattention and structural prior

parameters in FD05. The posterior distribution of each parameter (with 95% HDI) was

estimated from hierarchical Bayesian modeling for the group of participants, separately for the

gain and loss domains. (**A**) The posterior distribution of the rational inattention parameters μ_{β_G},

μ_{β_L} and their difference. Participants' resource allocation was less sensitive to the change of

outcome value for gain than for loss. (**B**) The posterior distribution of the structural prior

parameters μ_{θ_G}, μ_{θ_L} and their difference. Participants' adjustment to the structural prior was

more sensitive to the change of outcome value for gain than for loss.

The sizes of these effects were different for gain and loss gambles. Participants increased

their resource investment less quickly for one unit of potential gain than for one unit of potential

loss (the 95% HDI of $\mu_{\beta_G} - \mu_{\beta_L} < 0$, see Figure 9A, right panel). The extent to which participants

compensated for a structural prior also differed between gain and loss, with a stronger negative

relationship assumed for probability and gain than for probability and loss (the 95% HDI of $\mu_{\theta_G} -$

$\mu_{\theta_L} > 0$, see Figure 9B, right panel).

Herbert Simon had a famous metaphor that the structure of the environment and the

computational capabilities of the mind are the two blades of the scissors, together shaping

human rational behavior (Simon, 1990). This idea of bounded rationality has motivated

numerous studies on human heuristics and biases (Anderson, 1990; Lieder & Griffiths, 2020),

but only recently been applied to modeling classic decision-making tasks such as decision

under risk (Zhang et al., 2020) or intertemporal choice (Gershman & Bhui, 2020), tasks not

traditionally perceived to be cognitively demanding.

Extending this approach, we developed ARRM as a computational framework to model

rational agents who have limited cognitive resources to process the stimuli used for decision

making but who use these resources appropriately to maximize task performance. In one new

and three published datasets, we further demonstrated that ARRM can provide a full and

normative explanation for human behavioral patterns in decision under risk, including a decision

anomaly (the peanuts effect) that was difficult to be explained by previous decision theories. The

seemingly inconsistency in human risk attitude turns out to reflect the allocation of more

resources to more important probabilities and the compensation for the believed covariation of

value and probability in the environment. The ARRM models can also serve as useful

computational measures, providing insights into the differences in risk attitude between the gain

and loss domains. The resource allocation is more sensitive to the change in loss than in gain,

while the believed value-probability covariation is stronger in gain than in loss.

Below we discuss our work and its implications in the context of a broader range of decision

theories and problems.

Relationship of attention-dependent decision models to resource rationality

Some decision theories model human decision making as an attention-modulated valuation

process, with the amount of attention allocated to a specific outcome determining its decision

weight. For example, the transfer of attention exchange model assumes that the lower-valued

outcomes in an option receive a larger proportion of attention than the higher-valued outcomes

in the same option, when their probabilities are identical (Birnbaum, 2005). In contrast, the

salience theory assumes that the same attributes of different options compete for attention in

the decision process, during which higher-valued outcomes receive more attention due to their

saliency and are thus endowed with higher decision weights (Bordalo et al., 2012; Mormann,

2016). Similarly, the parallel constraint satisfaction theory proposes that gambles with higher

value and winning probability would lead to higher neural activation (Glöckner & Herbold, 2011).

Further examples may include the decision field theory, which assumes decisions based on a

dynamic sampling process, during which attention shifts among outcomes according to their

associated probabilities (Busemeyer & Townsend, 1993; Johnson & Busemeyer, 2005).

Although attention is often viewed as a limited cognitive resource, these attention-

dependent decision models are different from resource-rational models in two important ways.

First, they often do not have normative motivations for why attention should be allocated in a

particular way. As shown in the examples above, the attention allocation strategies assumed in

different models often conflict with each other (Fiedler & Glöckner, 2012; Glöckner & Herbold,

2011; Johnson & Busemeyer, 2005). Second and more important, attention-dependent models

often assume that attention directly influences decision weight, instead of influencing the

precision of representation or information capacity as in resource-rational models. With more

attention for larger gambles, attention-dependent models would not explain the peanuts effect

but rather counterfactually predict that people would be more risk-seeking for larger gambles.

In our study, we found that the saliency theory model fit much worse than the resource-

rational models to human decision behaviors. Other empirical findings are also more consistent

with the assumption of our models that attention may influence the representational precisions

of probability and value. On the individual level (Pachur et al., 2018), individuals who devote a

higher proportion of attention to the probabilities of gambles have a steeper slope of probability

distortion, implying more precise representation of probability, whereas those who allocate

higher attention to the outcomes of gambles have higher sensitivity to the differences in

outcomes. On the option level (Zilker & Pachur, 2021), people have a shallower slope of

distortion for the probability in the risky option when they spend a larger proportion of time

fixating the safe option.

The resource-rational and attention-dependent models do not necessarily conflict with each

other but may reflect different levels of explanations. Recent analyses of eye-tracking and

mouse-tracking data (He & Bhatia, 2023) suggest a resource-rational-like allocation of attention

in decision under risk: Attention to the probability of a gamble is more likely when the previously

attended gamble value is higher. If attention is assumed to influence the precision of

representation instead of directly controlling decision weights as in the salience theory,

attention-dependent models may serve as an algorithmic implementation of resource rationality.

The relationship between attention and resource rationality may be elucidated in future

experiments with eye-tracking or mouse-tracking recordings.

Relationship of heuristic-based decision models to resource rationality

Heuristic-based models, which assume that human decision behaviors follow simple

decision rules instead of maximizing expected utility, have been used to explain human decision

biases that are unexplainable to CPT. Heuristic-based decisions often ignore part of the

available information (Pachur et al., 2017). This can be viewed as a scenario where a resource-

limited rational agent allocates resources exclusively to dimensions perceived as most crucial.

For example, the similarity heuristic (Rubinstein, 1988) ignores the similar dimension of gamble

options and focuses on their dissimilar dimension, which can be viewed as the extreme case of

a rational cross-dimension resource allocation that invests more cognitive resources to the

dimension with higher variance (C. J. Bates et al., 2019; Dewan, 2020). The more extreme

maximax heuristic (Coombs et al., 1970) simply ignores the probability dimension and focuses

on the option with the highest value, which yields suboptimal choices in general but might be

rational when the contribution of probability to expected reward is small or the cognitive

resource is extremely limited. Indeed, these heuristic-based decision algorithms are claimed to

satisfy *ecological rationality* (Hertwig et al., 2022; Mata et al., 2012), according to which the

heuristics are crystallized adaptive solutions of the brain to specific decision problems in the

environment.

But unlike resource-rational solutions, these heuristic algorithms *per se* cannot vary with

decision problems. In other words, each of them may approximate a resource-rational agent

under specific resource constraints and task goals, but is not equivalent to the latter in general.

Indeed, compared with heuristic-based decision models, resource-rational models can better

explain human behaviors across different task environments (Callaway et al., 2022).

What were treated as heuristics in previous studies may enter the ARRM framework as

prior beliefs. When people are found to judge the unknown probability of winning a larger reward

to be smaller (Leuker et al., 2018; Pleskac & Hertwig, 2014) and respond faster in environments

with negative correlations between outcome value and probability (Leuker et al., 2019), these

behaviors were explained as a use of heuristics—higher risk often accompanies higher return.

In our models, the same structural relationship is defined as a two-dimensional joint prior that

contributes to a more precise estimation of probability. The prior, according to our taxonomy,

belongs to a long-term prior that is likely learned through one's life experience.

In our work, we did not directly compare the ARRM models with any specific heuristic-

based models, but Zhang et al. (2020) have shown that the BLO model outperforms a

representative set of heuristic-based models in fitting two of the datasets we reanalyzed here.

Our best model (BLO+RI+SP), in turn, performed much better than the BLO model in fitting

these datasets, and thus would outperform the set of heuristic-based models by transitivity.

Biological plausibility of resource rationality

It is unclear whether or how an exact resource-rational agent may be implemented in the

nervous system. As we argued earlier, approximate (or "bounded") solutions to the resource

allocation problems are more feasible than exact ones. For example, consistent with the

hypothesis of rational inattention, larger incentives lead to higher arousal of the nervous system,

which further modulates the encoding precision (Grujic et al., 2022; Mikhael et al., 2021).

Approximate resource-rational solutions may also be implemented by divisive

normalization, a canonical neural computation originally found in the perceptual system

(Carandini & Heeger, 2012) and later extended to higher-level neural circuits (e.g., valuation) as

well (Louie et al., 2015). According to divisive normalization, the firing rate of a neuron to a

specific stimulus is normalized by a population of neurons responding to similar stimuli, which

allows neuron responses to adapt to the environmental statistics and achieve efficient coding

(Simoncelli & Olshausen, 2001; Valerio & Navarro, 2003). In decision making, divisive

normalization has been used to account for how the valuation of an option may change with the

simultaneously (Louie et al., 2013) or recently (Khaw et al., 2017) presented options. Given that

higher firing rate implies higher signal-to-noise ratio and thus higher representational precision,

divisive normalization may be understood as allocation of cognitive resources (a total number of

firing rates) among different options.

Reconciling the different magnitude effects in different decision tasks

As we reviewed earlier, the magnitude effects in decision under temporal delay and

decision under risk have seemingly opposite directions (Estle et al., 2006; Prelec &

Loewenstein, 1991), if delay and risk are considered as parallel dimensions. However, we

conjecture that these two types of magnitude effects arise from different cognitive algorithms. In

our resource-rational model, the peanuts effect is treated as influences of value on probability

distortion, partly arising from the prior belief "the higher the risk, the greater the return" (Leuker

et al., 2018, 2019). Unlike us, Gershman and Bhui (2020) do not explain the magnitude effect

as influences of value on temporal discounting. Instead, they argue that temporal discounting is

an "as-if" phenomenon that originates from deteriorated precision of value under mental

simulation of longer delay. Gershman and Bhui's (2020) model for temporal discounting implies

similar magnitude effects in different value domains, while our model for probability distortion

implies domain-dependent peanut effects. Indeed, Jones and Oaksford (2011) found that the

magnitude effect for cost is similar to their counterparts for gain or loss, but the peanuts effect

for cost can be opposite to those of gain or loss.

Other decision problems where ARRM may apply

When introducing the ARRM framework, we have summarized three different resource

allocation problems and two different types of prior beliefs. These different modules, when

assembled as needed, would allow us to provide normative explanations for a wider range of

decision phenomena than previous resource-rational decision models did. Our modeling of the

peanuts effect in decision under risk is just an example. Below we briefly discuss a few decision

problems where ARRM may apply.

Decoy effects

One potential application concerns the decoy effects, that is, the probability of choosing one

option against another may be dramatically changed by the presence of a third option (decoy)

even when the decoy itself is rarely chosen (Louie et al., 2015). A memorizable example from

Dan Ariely's book "Predictably Irrational" (Ariely, 2010) is as follows. The reader of the journal

The Economist was offered three subscription options: inexpensive e-copy, expensive hard-

copy, or a bundle of hard-copy and e-copy of the same price as the hard-copy alone. Most

people would choose the last option, though they would probably find the first option more

attractive if the middle option did not exist. The decoy effects have diverse variants, depending

on how the attributes of the decoy are related to those of the major options. Louie and

colleagues (Louie et al., 2013, 2015) proposed that the decoy effects reflect context-dependent

encoding of option values. From the perspective of resource rationality, the decoy effects may

arise from the agent's solutions to two resource allocation problems: how to allocate resources

across options and across different attribute dimensions. These two problems can be

interrelated; just as in our modeling of the peanuts effect, the value of one dimension (outcome)

may influence the resource allocation on the other dimension (probability).

Decisions involving both delay and risk

The ARRM framework may also be applied to decision problems that involve both delay

and risk, such as choosing among delayed gambles (e.g., 10% probability to receive $1M after

10 months). Including our models in the present article, the existing resource-rational models

only apply to decision situations with delay or risk, but not both. When delay and risk are both

involved, there turn out to be more sophisticated interactive patterns (Luckman et al., 2020;

Vanderveldt et al., 2015, 2017), whose explanation is still elusive. The difficulty of modeling the

effect, similar to the decoy effect discussed above, lies in the necessity to model the interrelated

resource allocations across options and across attribute dimensions. ARRM can serve as a

framework for developing such resource-rational models.

Limitations and Future Directions

Similar to existing resource-rational studies, we have only tested our models on tasks that

are simple enough to be precisely predicted—choosing between a two-outcome gamble and a

(or a series of) sure payoff(s). For gambles with more than two outcomes or tasks with multiple

gambles, the resource-rational models are still to be worked out, due to the increased

complexity of the resource allocation problems in more complex scenarios.

As a second limitation, we have only considered the influence of outcome value on the

probability distortion process while keeping the utility function fixed, which follows the theoretical

convention in the literature but is not necessarily the only possibility. Similar ARRM models may

be constructed for the processing of value, with the value-probability interaction being the other

way around: the decreased risk preference for larger outcome may be interpreted as increased

sensitivity of value (i.e., greater exponent for the utility function) for larger probability. In which

direction the interaction actually occurs will be a question for future studies.

A third limitation is the oversimplification in our modeling of noise. To make our resource-

rational models computationally more tractable, we added a constant decision noise to each trial

while neglecting the variation of representational noises across trials due to varied resource

allocation. Moreover, we only considered the encoding noise in one dimension (probability) but

neglected that of the other dimension (value). Though these are common practices in previous

resource-rational models (Gershman & Bhui, 2020; Zhang et al., 2020), it would be valuable to

develop more realistic models that include all sources of noises (Vieider, 2024) and test them

using targeted experimental designs.

We assume people have limited cognitive resources and allocate their resources rationally

for decision making. Though the behavior of such a resource-rational agent is derivable as the

solution to an optimization problem, how to define the optimization problem is an empirical

question. What are the cognitive resources, what are people's prior beliefs for the environment,

and how flexible the encoding and decoding schemes can be are all fundamental empirical

questions that are still largely unknown. The module combinations tested in the present work

are still limited. For example, for rate-distortion models, we chose the optimization problem to be

minimizing squared error on the log-odds scale for analytical tractability, but did not know

whether minimizing the squared error on the probability scale would better fit human data. The

ARRM framework will enable us to develop new resource-rational models as well as to test

them along with existing models to explore alternative theoretical possibilities. Further

behavioral and neurophysiological measures to test these theoretical possibilities are also what

the field calls for.

1102

APPENDIX

Methods of Study 1

Experimental Design of the Datasets

Gonzalez & Wu's dataset (GW99). The GW99 dataset (Gonzalez & Wu, 1999) includes the

certainty equivalents (CEs) for 165 different virtual gambles from each of 10 US participants. In

their experiment, each gamble was in the form of $(x_1, p; x_2)$, that is, a probability of p to win $\$x_1$

and otherwise $\$x_2$, where $x_1 > x_2 \geq 0$. There were 15 pairs of (x_1, x_2): (25, 0), (50, 0), (75, 0),

(100, 0), (150,0), (200, 0), (400, 0), (800, 0), (50, 25), (75, 50), (100, 50), (150, 50), (150, 100),

(200, 100) and (200, 150). These outcome pairs were combined with 11 probabilities (0.01,

0.05, 0.1, 0.25, 0.4, 0.5, 0.6, 0.75, 0.9, 0.95 and 0.99) to generate $15 \times 11 = 165$ gambles. For

each gamble, the participant chose between the gamble and 12 different sure rewards

(presented as two successive tables) in an adaptive two-stage procedure (see Gonzalez & Wu,

1999 for details), based on which the CE was estimated.

Zhang, Ren, & Maloney's dataset (ZRM20: JDA and JDB). This decision dataset (Zhang et

al., 2020) contains the CEs for 165 different virtual gambles from each of 75 Chinese

participants from two sub-experiments (JDA: 51 participants; JDB: 24 participants). The JDA

and JDB had almost identical procedures and designs as GW99, except that the outcomes were

in Chinese Yuan instead of US dollars and participants were also tested on a separate task of

relative frequency judgment (not analyzed here) in the experiment. The two sub-experiments

differed from each other mainly in whether the trials of the decision and judgment tasks were

interleaved (JDA) or in different blocks (JDB). Our purpose of presenting the two sub-

experiments separately was to demonstrate the robustness of the results.

Statistical Analysis

For each participant and gamble, we calculated the normalized certainty equivalent ($\widehat{NCE}$)

based on the measured CE, and then obtained its log-odds $\lambda(\widehat{NCE})$. The $\widehat{NCE}$ and $\lambda(\widehat{NCE})$ were

used as nonparametric measures of the subjective probability. For each dataset, we performed

the following linear mixed-effects model (LMM) analysis on $\lambda(\widehat{NCE})$ to test the potential

influence of outcome values on probability distortion (as suggested by the peanuts effect):

1139 $$\lambda(\widehat{NCE}) \sim 1 + \lambda(p) * D + (1 + \lambda(p) * D | \text{paticipant}), \quad\quad (26)$$

where $\lambda(p)$ denotes the log-odds of the probability p in gamble $(x_1, p; x_2)$, $D = |x_1 - x_2|$ denotes

the potential gain, 1 denotes the intercept term, $\lambda(p) * D$ denotes the main effects of $\lambda(p)$ and D

as well as their interaction, and $(\cdot | \text{paticipant})$ denotes the random-effects terms. In the case the

full model could not converge (which rarely occurred), we simplified the random effects structure

following statistical guidelines (Barr et al., 2013; D. Bates et al., 2018; Brauer & Curtin, 2018).

Data were normalized on the group level before entering LMMs. All the LMMs were

implemented in python 3.8 with the statsmodels (v0.13.1) package and then replicated in R

4.0.3.

Model Fitting and Comparison

We fit the 10 models (described earlier) to the $\widehat{NCE}$ of each participant using maximum

likelihood estimates. The Akaike Information Criterion (AIC; Akaike, 1974) was used to compare

the goodness-of-fit among different models. We used the AIC of model BLO+RI+SP as a

reference and calculated each model's ΔAIC as its difference from the reference. Smaller ΔAIC

indicates better fit. For each dataset or sub-dataset, we also performed the group-level

Bayesian model selection (Rigoux et al., 2014; Stephan et al., 2009) and calculated the

protected exceedance probability for each pair of models. We chose to use AIC instead of the

Bayesian Information Criterion (BIC, Schwarz, 1978) as the major metric for model comparison,

because BIC could measure how close a model comes to ground truth only when the "true

model" is in the candidate set while AIC does not rely on such unrealistic assumption (Gelman &

Shalizi, 2013). Besides, BIC can be less robust than AIC when the number of data points are

relatively small (Vrieze, 2012). But for the reader's reference, we still included the BIC results in

the Supplement (Figures S6, S8, and S10).

The Exchangeability Test

The GW99 and ZRM20 datasets measured the CE for each gamble, this enabled us to

conduct the model free exchangeability test. The measured CE curve for each gamble value x_1

only has 11 probabilities, thus we first conduct a linear interpolation to approximate the full CE

cure in probability range 0.01~0.99. Given these CE curves, for any $x_a > x_b > x_c$, we could find

probabilities p_b and p_c so that the CE of gamble $(x_a, p_b; 0)$ is x_b and the CE of gamble $(x_a, p_c; 0)$

is x_c. By applying Eq. 25, we have

$$U(x_b, p_c) = w(p_c)u(x_b) = w(p_c)w(p_b)u(x_a) = U(x_c, p_b), \tag{1}$$

thus the gambles $(x_c, p_b; 0)$ and $(x_b, p_c; 0)$ should have the same CE.

For the GW99 and ZRM20 datasets, we draw 56 combinations from gamble values (x_1, x_2):

(25, 0), (50, 0), (75, 0), (100, 0), (150,0), (200, 0), (400, 0), (800, 0). The value combinations

$[x_a, x_b, x_c]$ were then passed into the interpolated CE curve of x_a to get the probability p_b and

p_c. Combinations with p_b and p_c outside the probability range 0.01~0.99 (16 combinations) were

excluded from analysis. The probabilities p_b and p_c were further passed into the CE curve of x_c

and x_b respectively to get the measured CE_{x_c, p_b} and CE_{x_b, p_c}. The measure CEs were scaled by

x_a and then passed into paired t-test.

1170

Methods of Study 2

Participants

Twenty-one students (15 females, mean age = 20.6, SD = 2.2) in Peking University

participated in our study. The experiment took approximately 1 hour and participants received

60 Chinese Yuan for their time. The study had been approved by the Committee for Protecting

Human and Animal Subjects of School of Psychological and Cognitive Sciences at Peking

University. All participants provided written informed consent and were paid for their time.

Design and Procedure

On each trial, a two-outcome gamble, denoted $(x_1, p; x_2)$, and a sure reward were

presented side by side on the screen. Participants need to choose between the two by pressing

the "F" (left) or "J" (right) on the keyboard. The value of x_1 had 8 levels: 25, 50, 75, 100, 150,

200, 400 and 800 (in Chinese Yuan). The value of x_2 was always 0. The winning probability p

had 5 levels: 0.05, 0.25, 0.5, 0.75 and 0.95. A combination of x_1 with p led to 40 different

gambles in total.

The sure reward paired with a specific gamble was selected according to the following two-

round adaptive procedure. In the first round of 200 trials, the sure rewards for each gamble were

set to 5 different levels, which were 0.1, 0.3, 0.5, 0.7 or 0.9 times of the x_1 in the gamble. After

the first round, for each gamble, the participant's 5 choices were entered into a logistic

regression against the sure-reward-to-x_1 ratio to estimate a location parameter where the

participant would be indifferent between the gamble and the sure reward (i.e., with a probability

of 0.5 to choose sure reward). The location parameter was rounded to one decimal and added

by −0.08, −0.04, 0, 0.4 or 0.08. The resulting ratio was then used to generate the 5 sure

rewards for the gamble in the second round of 200 trials. In both rounds, trials for different

gambles and sure rewards were interleaved in random order. For each participant, this two-

round procedure was repeated twice, thus leading to 800 trials in total and 20 trials for each

gamble.

Statistical Analysis

To make the results of this binary choice task comparable to those of the certainty

equivalent task presented earlier, we estimated the certainty equivalent (CE) for each gamble

using a logistic regression of choices against the sure rewards, based on all the 20 trials for the

gamble. This estimated NCE ($\lambda(\widehat{NCE})$) was used for visualization and further statistical

analysis—an LMM similar to that used for the certainty equivalent task (Eq. 26).

Model Fitting and Comparison

Instead of fitting the estimated NCE, we fit the 10 models directly to participants' binary

choices (see the Decision Model section for details) using maximum likelihood estimates. As

before, ΔAIC and protected exceedance probability were calculated for model comparison in

goodness-of-fit.

The experiment design and statistical analyses were preregistered at OSF

(https://osf.io/p76rg) for testing the peanuts effect. The modeling analysis (with the 10 models)

were not preregistered[3].

Methods of Study 3

Fehr-Duda et al.'s dataset (FD05)

The experiment was performed in Beijing in 2005 on 153 Chinese participants, for each of

whom the certainty equivalents for 56 different gambles (28 gain gambles and 28 loss gambles)

were measured (Fehr-Duda et al., 2010). For each gamble, participants were asked to mark out

---

[3] When we preregistered the experiment, we had not known about the work by Fehr-Duda et al. (2010), who reasoned that the peanuts effect should be understood as the influence of outcome value on probability distortion. Instead, we had framed the peanuts effect as the influence of winning probability on the utility function, an alternative mathematical form to describe the peanuts effect (see Supplemental Text S1 and Figures S1 and S2). We later switched to the view of Fehr-Duda et al. (2010) to make a better connection to the decision literature.

their choices on a paper sheet where on the left side was the gamble and on the right side were

20 equally spaced sure payoffs. All gambles in FD05 had two outcomes, denoted $(x_1, p; x_2)$ as

before, where $x_1 > x_2 \geq 0$ (gain gamble) or $x_1 < x_2 \leq 0$ (loss gamble). The probability p had 7

levels: 0.05, 0.10, 0.25, 0.50, 0.75, 0.9, or 0.95. Half of the 28 gain gambles offered outcomes

ranging from 4 to 55 Yuan (low-stake) and the other half offered 65 to 950 Yuan (high-stake).

The 28 loss gambles had the same settings as the gain gambles except for reversing the sign of

the outcomes. The highest gain or loss in the gambles amounted to several times of

participants' average monthly income at that time. Participants received monetary payoffs based

on a random draw from their choices.

Statistical Analysis

Unlike the original paper (Fehr-Duda et al., 2010) that tested the effect of outcome value by

dividing gambles into two categories according to the value of x_2, we computed the potential

gain $(D = |x_1 - x_2|)$ for each gamble and used it as a continuous regressor. We used the

following linear mixed-effects model (LMM) to examine the effects of outcome value and domain

on the estimated NCE ($\lambda(\widehat{NCE})$, calculated as before):

1235
$$\lambda(\widehat{NCE}) \sim 1 + \lambda(p) * D * \text{IsLoss} + (1 + \lambda(p) * D * \text{IsLoss} | \text{Participant}), \tag{28}$$

where (as before) $\lambda(p)$ denotes the log-odds of the probability p in gamble $(x_1, p; x_2)$, IsLoss

denotes a dummy variable for outcome domain (0 for gain, 1 for loss), 1 denotes the intercept

term, $\lambda(p) * D * \text{IsLoss}$ denotes the main effects of $\lambda(p)$, D and IsLoss as well as their

interactions, and $(\cdot | \text{paticipant})$ denotes the random-effects terms.

Hierarchical Bayesian Modeling

Because the gamble set for each participant and domain (28 gambles) was much smaller

than that of Study 1 (165 gambles) or Study 2 (40 gambles), we fit the BLO+RI+SP model to

participants' NCEs using the hierarchical Bayesian method (Lee & Wagenmakers, 2013; Martin

& Wiecki, 2018) instead of maximum likelihood estimates to obtain more reliable parameter

estimates.

To extend our model to loss domain, we assumed that RI parameter β (i.e., the sensitivity of

resource allocation to potential gain) and SP parameter θ (i.e., the sensitivity of compensating

for the covariation between value and probability) could be different for gain and loss. We

assumed each participant had two RI parameters (β_G and β_L) and SP parameters (θ_G and θ_L),

with the subscripts G and L respectively denoting gain and loss. Following CPT, we assumed

two different exponents α_G and α_L respectively for the power utility functions (Eq. 18) in gain and

loss.

The model parameters were estimated using the Markov Chain Monte Carlo method (See

Supplemental Text S2 and Table S4 for details), implemented by PyMC package on python 3.8.

Four independent chains were run, each had 10000 samples after an initial burn-in of 5000

samples. The model had a good convergence with $\hat{R} \leq 1.01$ for all estimated parameters. The

95% highest density interval (HDI) was calculated for the group-level RI and SP parameters as

well as their differences between the gain and loss domains.

Alternative models tested outside resource rationality

Besides the 10 resource-rational models, we tested three models that represent the

psychological mechanisms thought to be able to explain the peanuts effect: disappointment

theory, regret theory, and salience theory. Each model enhances the computation of gamble

utility with the influence of a specific psychological mechanism.

The disappointment theory (DT) assumes that participants' choices are influenced by both

the utility difference and the anticipated disappointment experienced when the realized outcome

of a chosen gamble is worse than its expected outcome (Loomes & Sugden, 1986). The regret

theory (RT) assumes that participants' choices are affected by the potential regret they might

feel if the outcome of the chosen option turns out to be worse than the outcome of the unchosen

option (Loomes & Sugden, 1982). The salience theory proposes that the attention allocated to

each outcome is proportional to its value, leading to an overweighting of the probability

associated with the more salient (higher-value) outcome (Bordalo et al., 2012). We used the

model forms summarized in He et al. (2022), with each model's definition of gamble utility listed

in Table 3. The definitions of their utility function and decision model are the same as those of

the 10 resource-rational models.

1271

1272   **Table 3. Models based on the disappointment theory, regret theory, and saliency theory**

Model	Definition of gamble utility
Disappointment Theory (DT)	$U(\mathscr{g}) = EU + \kappa_1 \sum_{j=1}^{2} p_j \text{sign}(u(x_j) - EU)\lvert u(x_j) - EU\rvert^{\alpha_1}$
Regret Theory (RT)	$U(\mathscr{g}) = EU + \sum_{i=1}^{2}\sum_{j=1}^{2} p_i q_j\, R(u(x_i) - u(y_j))$, where $R(d) = I(d > 0)\kappa_1\lvert d\rvert^{\alpha_1} - I(d < 0)\kappa_2\lvert d\rvert^{\alpha_2}$ is the regret function, $I(\cdot)$ is an indicator function.
Salience Theory (SA)	$U(\mathscr{g}) = \sum_{i=1}^{2}\sum_{j=1}^{2} \frac{\beta^{r_{ij}} p_i q_j}{\sum_{k=1}^{2}\sum_{l=1}^{2} \beta^{r_{kl}} p_k q_l} u(x_i)$, where the relative salience of x_i to y_j defined as $s_{ij} = \frac{\lvert x_i - y_j\rvert}{x_i + y_j + \alpha_1 + \kappa_1 I(x_i + y_j \geq 0)}$, and r_{ij} is the ranking of s_{ij} among the four pairs of relative salience.

1273   *Note*. Model definitions are adapted from He et al.(2022). For two-outcome gamble $\mathscr{g}:(x_1, p; x_2)$,
1274 $EU = \sum_{i=1}^{2} p_i u(x_i)$ is its expected utility, where $u(\cdot)$ is a power utility function and $x_1 > x_2$. In the
1275   models, $\alpha_1, \alpha_2, \kappa_1, \kappa_2, \beta \in [0, +\infty)$ are free parameters. In RT and SA, the variables y_j and q_j
1276   respectively denote the value and probability of the *j*-th outcome of the other gamble.
1277

1278

ACKNOWLEDGMENTS

1280   HZ was supported by National Natural Science Foundation of China grants (32171095 and

1281   32471152) and funding from Peking-Tsinghua Center for Life Sciences. Part of the analysis was

1282   performed on the High-performance Computing Platform of Peking University.

1283

DATA AND CODE AVAILABILITY STATEMENT

1285   The data and codes that support the findings of this study are available in the Open

1286   Science Framework (OSF) repository upon publication of this article.

1287

REFERENCES

Akaike, H. (1974). A new look at the statistical model identification. *IEEE Transactions on Automatic Control*, *19*(6), 716–723. https://doi.org/10.1109/TAC.1974.1100705

Alempaki, D., Canic, E., Mullett, T. L., Skylark, W. J., Starmer, C., Stewart, N., & Tufano, F. (2019). Reexamining How Utility and Weighting Functions Get Their Shapes: A Quasi-Adversarial Collaboration Providing a New Interpretation. *Management Science*, *65*(10), 4841–4862. https://doi.org/10.1287/mnsc.2018.3170

Allais, M. (1953). Le Comportement de l'Homme Rationnel devant le Risque: Critique des Postulats et Axiomes de l'Ecole Americaine. *Econometrica*, *21*(4), 503–546. https://doi.org/10.2307/1907921

Anderson, J. R. (1990). *The adaptive character of thought*. L. Erlbaum Associates.

Ariely, D. (2010). *Predictably irrational: The hidden forces that shape our decisions* (rev. and expanded ed., 1. Harper Perennial ed). Harper Perennial.

Attneave, F. (1953). Psychological probability as a function of experienced frequency. *Journal of Experimental Psychology*, *46*(2), 81–86. https://doi.org/10.1037/h0057955

Barlow, H. B. (1961). Possible Principles Underlying the Transformations of Sensory Messages. In W. A. Rosenblith (Ed.), *Sensory Communication* (pp. 216–234). The MIT Press. https://doi.org/10.7551/mitpress/9780262518420.003.0013

Barr, D. J., Levy, R., Scheepers, C., & Tily, H. J. (2013). Random effects structure for confirmatory hypothesis testing: Keep it maximal. *Journal of Memory and Language*, *68*(3), 255–278. https://doi.org/10.1016/j.jml.2012.11.001

Bates, C. J., & Jacobs, R. A. (2021). Optimal attentional allocation in the presence of capacity constraints in uncued and cued visual search. *Journal of Vision*, *21*(5), 3. https://doi.org/10.1167/jov.21.5.3

Bates, C. J., Lerch, R. A., Sims, C. R., & Jacobs, R. A. (2019). Adaptive allocation of human visual working memory capacity during statistical and categorical learning. *Journal of Vision*, *19*(2), 11. https://doi.org/10.1167/19.2.11

Bates, D., Kliegl, R., Vasishth, S., & Baayen, H. (2018). *Parsimonious Mixed Models* (arXiv:1506.04967). arXiv. http://arxiv.org/abs/1506.04967

Berger, T., & Gibson, J. D. (1998). Lossy Source Coding. *IEEE Transactions on Information Theory*, *44*, 2693–2723. https://doi.org/10.1109/18.720552

Bhui, R., & Gershman, S. J. (2018). Decision by sampling implements efficient coding of psychoeconomic functions. *Psychological Review*, *125*(6), 985–1001. https://doi.org/10.1037/rev0000123

Bhui, R., Lai, L., & Gershman, S. J. (2021). Resource-rational decision making. *Current Opinion in Behavioral Sciences*, *41*, 15–21. https://doi.org/10.1016/j.cobeha.2021.02.015

Binswanger, H. P. (1981). Attitudes Toward Risk: Theoretical Implications of an Experiment in Rural India. *The Economic Journal*, *91*(364), 867–890. https://doi.org/10.2307/2232497

Binz, M., Gershman, S. J., Schulz, E., & Endres, D. (2022). Heuristics from bounded meta-learned inference. *Psychological Review*, *129*(5), 1042–1077. https://doi.org/10.1037/rev0000330

Birnbaum, M. H. (2005). Three New Tests of Independence That Differentiate Models of Risky Decision Making. *Management Science*, *51*(9), 1346–1358. https://doi.org/10.1287/mnsc.1050.0404

Birnbaum, M. H. (2008). Evaluation of the priority heuristic as a descriptive model of risky decision making: Comment on Brandstätter, Gigerenzer, and Hertwig (2006). *Psychological Review*, *115*(1), 253–260. https://doi.org/10.1037/0033-295X.115.1.253

Birnbaum, M. H., & LaCroix, A. R. (2008). Dimension integration: Testing models without trade-offs. *Organizational Behavior and Human Decision Processes*, *105*(1), 122–133. https://doi.org/10.1016/j.obhdp.2007.07.002

Bordalo, P., Gennaioli, N., & Shleifer, A. (2012). Salience Theory of Choice Under Risk. *The Quarterly Journal of Economics*, *127*(3), 1243–1285. https://doi.org/10/gf7965

Brandstätter, E., Gigerenzer, G., & Hertwig, R. (2006). The priority heuristic: Making choices without trade-offs. *Psychological Review*, *113*(2), 409–432. https://doi.org/10.1037/0033-295X.113.2.409

Brauer, M., & Curtin, J. J. (2018). Linear mixed-effects models and the analysis of nonindependent data: A unified framework to analyze categorical and continuous independent variables that vary within-subjects and/or within-items. *Psychological Methods*, *23*(3), 389–411. https://doi.org/10.1037/met0000159

Bujold, P. M., Ferrari-Toniolo, S., & Schultz, W. (2021). Adaptation of utility functions to reward distribution in rhesus monkeys. *Cognition*, *214*, 104764. https://doi.org/10.1016/j.cognition.2021.104764

Busemeyer, J. R., & Townsend, J. T. (1993). Decision field theory: A dynamic-cognitive approach to decision making in an uncertain environment. *Psychological Review*, *100*(3), 432–459. https://doi.org/10.1037/0033-295X.100.3.432

Callaway, F., van Opheusden, B., Gul, S., Das, P., Krueger, P. M., Griffiths, T. L., & Lieder, F. (2022). Rational use of cognitive resources in human planning. *Nature Human Behaviour*, *6*(8), 1112–1125. https://doi.org/10.1038/s41562-022-01332-8

Carandini, M., & Heeger, D. J. (2012). Normalization as a canonical neural computation. *Nature Reviews Neuroscience*, *13*(1), 51–62. https://doi.org/10.1038/nrn3136

Coombs, C. H., Dawes, R. M., & Tversky, A. (1970). *Mathematical psychology: An elementary*
introduction. Prentice-Hall.

Dasgupta, I., Schulz, E., Tenenbaum, J. B., & Gershman, S. J. (2020). A theory of learning to
infer. *Psychological Review*, *127*(3), 412–441. https://doi.org/10.1037/rev0000178

Dayan, P., & Abbott, L. F. (2001). *Theoretical neuroscience: Computational and mathematical*
modeling of neural systems. Massachusetts Institute of Technology Press.

Dewan, A. (2020). *Costly Multidimensional Information* (p. 55).

Estle, S. J., Green, L., Myerson, J., & Holt, D. D. (2006). Differential effects of amount on
temporal and probability discounting of gains and losses. *Memory & Cognition*, *34*(4),
914–928. https://doi.org/10/bbkw7x

Fehr-Duda, H., Bruhin, A., Epper, T., & Schubert, R. (2010). Rationality on the rise: Why relative
risk aversion increases with stake size. *Journal of Risk and Uncertainty*, *40*(2), 147–180.
https://doi.org/10/dgmr2s

Fiedler, S., & Glöckner, A. (2012). The dynamics of decision making in risky choice: An eye-
tracking analysis. *Frontiers in Psychology*, *3*, 335.
https://doi.org/10.3389/fpsyg.2012.00335

Frydman, C., & Jin, L. J. (2021). Efficient Coding and Risky Choice. *The Quarterly Journal of*
Economics, *137*(1), 161–213. https://doi.org/10.1093/qje/qjab031

Gelman, A., & Shalizi, C. R. (2013). Philosophy and the practice of Bayesian statistics. *British*
Journal of Mathematical and Statistical Psychology, *66*(1), 8–38.
https://doi.org/10.1111/j.2044-8317.2011.02037.x

Gershman, S. J., & Bhui, R. (2020). Rationally inattentive intertemporal choice. *Nature*
Communications, *11*(1), 3365. https://doi.org/10.1038/s41467-020-16852-y

Gigerenzer, G., Hertwig, R., & Pachur, T. (Eds.). (2011). *Heuristics: The foundations of adaptive*
behavior. Oxford University Press.

Girshick, A. R., Landy, M. S., & Simoncelli, E. P. (2011). Cardinal rules: Visual orientation
perception reflects knowledge of environmental statistics. *Nature Neuroscience*, *14*(7),
926–932. https://doi.org/10.1038/nn.2831

Glimcher, P. W., & Fehr, E. (Eds.). (2014). *Neuroeconomics: Decision making and the brain* (2nd
edition). Academic Press.

Glöckner, A., & Herbold, A.-K. (2011). An eye-tracking study on information processing in risky
decisions: Evidence for compensatory strategies based on automatic processes. *Journal*
of Behavioral Decision Making, *24*(1), 71–98. https://doi.org/10.1002/bdm.684

Gonzalez, R., & Wu, G. (1999). On the Shape of the Probability Weighting Function. *Cognitive*
Psychology, *38*(1), 129–166. https://doi.org/10.1006/cogp.1998.0710

Green, L., Myerson, J., & Ostaszewski, P. (1999). Amount of reward has opposite effects on the discounting of delayed and probabilistic outcomes. *Journal of Experimental Psychology: Learning, Memory, and Cognition*, *25*(2), 418–427. https://doi.org/10/ckgjz8

Griffiths, T. L., & Tenenbaum, J. B. (2006). Optimal Predictions in Everyday Cognition. *Psychological Science*, *17*(9), 767–773. https://doi.org/10.1111/j.1467-9280.2006.01780.x

Grujic, N., Brus, J., Burdakov, D., & Polania, R. (2022). Rational inattention in mice. *Science Advances*, *8*(9), eabj8935. https://doi.org/10.1126/sciadv.abj8935

He, L., & Bhatia, S. (2023). Complex economic decisions from simple neurocognitive processes: The role of interactive attention. *Proceedings. Biological Sciences*, *290*(1992), 20221593. https://doi.org/10.1098/rspb.2022.1593

He, L., Zhao, W. J., & Bhatia, S. (2022). An ontology of decision models. *Psychological Review*, *129*(1), 49–72. https://doi.org/10.1037/rev0000231

Heng, J. A., Woodford, M., & Polania, R. (2020). Efficient sampling and noisy decisions. *eLife*, *9*, e54962. https://doi.org/10.7554/eLife.54962

Hertwig, R., Leuker, C., Pachur, T., Spiliopoulos, L., & Pleskac, T. J. (2022). Studies in Ecological Rationality. *Topics in Cognitive Science*, *14*(3), 467–491. https://doi.org/10.1111/tops.12567

Jazayeri, M., & Shadlen, M. N. (2010). Temporal context calibrates interval timing. *Nature Neuroscience*, *13*(8), 1020–1026. https://doi.org/10.1038/nn.2590

Johnson, J. G., & Busemeyer, J. R. (2005). A Dynamic, Stochastic, Computational Model of Preference Reversal Phenomena. *Psychological Review*, *112*(4), 841–861. https://doi.org/10.1037/0033-295X.112.4.841

Jones, S., & Oaksford, M. (2011). Transactional problem content in cost discounting: Parallel effects for probability and delay. *Journal of Experimental Psychology: Learning, Memory, and Cognition*, *37*(3), 739–747. https://doi.org/10.1037/a0022219

Kachelmeier, S. J., & Shehata, M. (1992). Examining Risk Preferences Under High Monetary Incentives: Experimental Evidence from the People's Republic of China. *The American Economic Review*, *82*(5), 1120–1141. JSTOR.

Kahneman, D., & Tversky, A. (1979). Prospect Theory: An Analysis of Decision under Risk. *Econometrica*, *47*(2), 263–292. https://doi.org/10.2307/1914185

Khaw, M. W., Glimcher, P. W., & Louie, K. (2017). Normalized value coding explains dynamic adaptation in the human valuation process. *Proceedings of the National Academy of Sciences*, *114*(48), 12696–12701. https://doi.org/10/gcn9gg

Khaw, M. W., Li, Z., & Woodford, M. (2021). Cognitive Imprecision and Small-Stakes Risk Aversion. *The Review of Economic Studies*, *88*(4), 1979–2013.

https://doi.org/10.1093/restud/rdaa044

Kleinsorge, T., & Rinkenauer, G. (2012). Effects of Monetary Incentives on Task Switching.
Experimental Psychology, *59*(4), 216–226. https://doi.org/10.1027/1618-3169/a000146

Kool, W., & Botvinick, M. (2018). Mental labour. *Nature Human Behaviour*, *2*(12), 899–908.
https://doi.org/10.1038/s41562-018-0401-9

Lee, M. D., & Wagenmakers, E.-J. (2013). *Bayesian cognitive modeling: A practical course*.
Cambridge University Press.

Leland, J. W. (1998). Similarity Judgments in Choice Under Uncertainty: A Reinterpretation of
the Predictions of Regret Theory. *Management Science*, *44*(5), 659–672.
https://doi.org/10.1287/mnsc.44.5.659

Leuker, C., Pachur, T., Hertwig, R., & Pleskac, T. J. (2018). Exploiting risk–reward structures in
decision making under uncertainty. *Cognition*, *175*, 186–200.
https://doi.org/10.1016/j.cognition.2018.02.019

Leuker, C., Pachur, T., Hertwig, R., & Pleskac, T. J. (2019). Do people exploit risk–reward
structures to simplify information processing in risky choice? *Journal of the Economic*
Science Association, *5*(1), 76–94. https://doi.org/10/gmhksb

Lewis, R. L., Howes, A., & Singh, S. (2014). Computational Rationality: Linking Mechanism and
Behavior Through Bounded Utility Maximization. *Topics in Cognitive Science*, *6*(2), 279–
311. https://doi.org/10.1111/tops.12086

Lieder, F., & Griffiths, T. L. (2020). Resource-rational analysis: Understanding human cognition
as the optimal use of limited computational resources. *Behavioral and Brain Sciences*,
43, e1. https://doi.org/10.1017/S0140525X1900061X

Loomes, G., & Sugden, R. (1982). Regret Theory: An Alternative Theory of Rational Choice
Under Uncertainty. *The Economic Journal*, *92*(368), 805–824.
https://doi.org/10.2307/2232669

Loomes, G., & Sugden, R. (1986). Disappointment and Dynamic Consistency in Choice under
Uncertainty. *The Review of Economic Studies*, *53*(2), 271–282.
https://doi.org/10.2307/2297651

Louie, K., Glimcher, P. W., & Webb, R. (2015). Adaptive neural coding: From biological to
behavioral decision-making. *Current Opinion in Behavioral Sciences*, *5*, 91–99.
https://doi.org/10/gdq732

Louie, K., Khaw, M. W., & Glimcher, P. W. (2013). Normalization is a general neural mechanism
for context-dependent decision making. *Proceedings of the National Academy of*
Sciences, *110*(15), 6139–6144. https://doi.org/10.1073/pnas.1217854110

Luckman, A., Donkin, C., & Newell, B. R. (2020). An evaluation and comparison of models of
risky intertemporal choice. *Psychological Review*, *127*(6), 1097–1138.

1465    https://doi.org/10/gnbd5x

1466 MacKay, D. J. C. (2003). *Information theory, inference, and learning algorithms*. Cambridge
1467    University Press.

1468 Maloney, L. T., & Zhang, H. (2010). Decision-theoretic models of visual perception and action.
1469    *Vision Research*, *50*(23), 2362–2374. https://doi.org/10.1016/j.visres.2010.09.031

1470 Markowitz, H. (1952). The Utility of Wealth. *Journal of Political Economy*, *60*(2), 151–158.
1471    https://doi.org/10.1086/257177

1472 Martin, O., & Wiecki, T. (2018). *Bayesian analysis with Python: Introduction to statistical*
1473    *modeling and probabilistic programming using PyMC3 and ArviZ* (2nd Edition). Packt
1474    Publishing Limited.

1475 Mata, R., Pachur, T., von Helversen, B., Hertwig, R., Rieskamp, J., & Schooler, L. (2012).
1476    Ecological Rationality: A Framework for Understanding and Aiding the Aging Decision
1477    Maker. *Frontiers in Neuroscience*, *6*, 19. https://doi.org/10.3389/fnins.2012.00019

1478 Matějka, F., & McKay, A. (2015). Rational Inattention to Discrete Choices: A New Foundation for
1479    the Multinomial Logit Model. *American Economic Review*, *105*(1), 272–298.
1480    https://doi.org/10.1257/aer.20130047

1481 Mellers, B. A., Schwartz, A., Ho, K., & Ritov, I. (1997). Decision Affect Theory: Emotional
1482    Reactions to the Outcomes of Risky Options. *Psychological Science*, *8*(6), 423–429.
1483    https://doi.org/10.1111/j.1467-9280.1997.tb00455.x

1484 Mikhael, J. G., Lai, L., & Gershman, S. J. (2021). Rational inattention and tonic dopamine.
1485    *PLOS Computational Biology*, *17*(3), e1008659.
1486    https://doi.org/10.1371/journal.pcbi.1008659

1487 Mormann, M. M. (2016). The Role of Salience and Attention in Choice under Risk: An
1488    Experimental Investigation. *SSRN Electronic Journal*. https://doi.org/10/gnnz8d

1489 Otto, A. R., & Vassena, E. (2021). It's all relative: Reward-induced cognitive control modulation
1490    depends on context. *Journal of Experimental Psychology: General*, *150*(2), 306–313.
1491    https://doi.org/10.1037/xge0000842

1492 Pachur, T., Schulte-Mecklenbeck, M., Murphy, R. O., & Hertwig, R. (2018). Prospect theory
1493    reflects selective allocation of attention. *Journal of Experimental Psychology: General*,
1494    *147*(2), 147–169. https://doi.org/10.1037/xge0000406

1495 Pachur, T., Suter, R. S., & Hertwig, R. (2017). How the twain can meet: Prospect theory and
1496    models of heuristics in risky choice. *Cognitive Psychology*, *93*, 44–73.
1497    https://doi.org/10.1016/j.cogpsych.2017.01.001

1498 Peterson, J. C., Bourgin, D. D., Agrawal, M., Reichman, D., & Griffiths, T. L. (2021). Using large-
1499    scale experiments and machine learning to discover theories of human decision-making.
1500    *Science*, *372*(6547), 1209–1214. https://doi.org/10.1126/science.abe2629

Petzschner, F. H., Glasauer, S., & Stephan, K. E. (2015). A Bayesian perspective on magnitude estimation. *Trends in Cognitive Sciences*, *19*(5), 285–293. https://doi.org/10.1016/j.tics.2015.03.002

Pleskac, T. J., & Hertwig, R. (2014). Ecologically rational choice and the structure of the environment. *Journal of Experimental Psychology: General*, *143*(5), 2000–2019. https://doi.org/10.1037/xge0000013

Polanía, R., Woodford, M., & Ruff, C. C. (2019). Efficient coding of subjective value. *Nature Neuroscience*, *22*(1), 134–142. https://doi.org/10.1038/s41593-018-0292-0

Prelec, D. (1998). The Probability Weighting Function. *Econometrica*, *66*(3), 497–527. https://doi.org/10.2307/2998573

Prelec, D., & Loewenstein, G. (1991). Decision Making Over Time and Under Uncertainty: A Common Approach. *Management Science*, *37*(7), 770–786. https://doi.org/10.1287/mnsc.37.7.770

Ren, X., Luo, H., & Zhang, H. (2021). Automatic and Fast Encoding of Representational Uncertainty Underlies the Distortion of Relative Frequency. *The Journal of Neuroscience*, *41*(16), 3692–3706. https://doi.org/10.1523/JNEUROSCI.2006-20.2021

Ren, X., Wang, M., & Zhang, H. (2018). Context Effects in the Judgment of Visual Relative-Frequency: Trial-by-Trial Adaptation and Non-linear Sequential Effect. *Frontiers in Psychology*, *9*, 1691. https://doi.org/10.3389/fpsyg.2018.01691

Rigoux, L., Stephan, K. E., Friston, K. J., & Daunizeau, J. (2014). Bayesian model selection for group studies—Revisited. *NeuroImage*, *84*, 971–985. https://doi.org/10.1016/j.neuroimage.2013.08.065

Rubinstein, A. (1988). Similarity and decision-making under risk (is there a utility theory resolution to the Allais paradox?). *Journal of Economic Theory*, *46*(1), 145–153. https://doi.org/10.1016/0022-0531(88)90154-8

Schwarz, G. (1978). Estimating the Dimension of a Model. *The Annals of Statistics*, *6*(2), 461–464. https://doi.org/10.1214/aos/1176344136

Simon, H. A. (1955). A Behavioral Model of Rational Choice. *The Quarterly Journal of Economics*, *69*(1), 99–118. https://doi.org/10.2307/1884852

Simon, H. A. (1990). Invariants of Human Behavior. *Annual Review of Psychology*, *41*(1), 1–20. https://doi.org/10.1146/annurev.ps.41.020190.000245

Simoncelli, E. P., & Olshausen, B. A. (2001). Natural Image Statistics and Neural Representation. *Annual Review of Neuroscience*, *24*(1), 1193–1216. https://doi.org/10.1146/annurev.neuro.24.1.1193

Sims, C. A. (2003). Implications of rational inattention. *Journal of Monetary Economics*, *50*(3), 665–690. https://doi.org/10.1016/S0304-3932(03)00029-1

1537   Sims, C. R. (2016). Rate–distortion theory and human perception. *Cognition, 152*, 181–198.
1538   https://doi.org/10.1016/j.cognition.2016.03.020

1539   Sims, C. R. (2018). Efficient coding explains the universal law of generalization in human
1540   perception. *Science*, *360*(6389), 652–656. https://doi.org/10.1126/science.aaq1118

1541   Stephan, K. E., Penny, W. D., Daunizeau, J., Moran, R. J., & Friston, K. J. (2009). Bayesian
1542   model selection for group studies. *NeuroImage*, *46*(4), 1004–1017.
1543   https://doi.org/10.1016/j.neuroimage.2009.03.025

1544   Stewart, N., Chater, N., & Brown, G. D. A. (2006). Decision by sampling. *Cognitive Psychology*,
1545   *53*(1), 1–26. https://doi.org/10.1016/j.cogpsych.2005.10.003

1546   Stewart, N., Reimers, S., & Harris, A. J. L. (2015). On the Origin of Utility, Weighting, and
1547   Discounting Functions: How They Get Their Shapes and How to Change Their Shapes.
1548   *Management Science*, *61*(3), 687–705. https://doi.org/10.1287/mnsc.2013.1853

1549   Summerfield, C., & Parpart, P. (2022). Normative Principles for Decision-Making in Natural
1550   Environments. *Annual Review of Psychology*, *73*(1), 53–77.
1551   https://doi.org/10.1146/annurev-psych-020821-104057

1552   Tversky, A., & Kahneman, D. (1992). Advances in prospect theory: Cumulative representation of
1553   uncertainty. *Journal of Risk and Uncertainty*, *5*(4), 297–323.
1554   https://doi.org/10.1007/BF00122574

1555   Valerio, R., & Navarro, R. (2003). Optimal coding through divisive normalization models of V1
1556   neurons. *Network: Computation in Neural Systems*, *14*(3), 579–593.
1557   https://doi.org/10.1088/0954-898X_14_3_310

1558   Vanderveldt, A., Green, L., & Myerson, J. (2015). Discounting of monetary rewards that are both
1559   delayed and probabilistic: Delay and probability combine multiplicatively, not additively.
1560   *Journal of Experimental Psychology: Learning, Memory, and Cognition*, *41*(1), 148–162.
1561   https://doi.org/10/gfv884

1562   Vanderveldt, A., Green, L., & Rachlin, H. (2017). Discounting by Probabilistic Waiting:
1563   Discounting by Probabilistic Waiting. *Journal of Behavioral Decision Making*, *30*(1), 39–
1564   53. https://doi.org/10/f9sjf4

1565   Vieider, F. M. (2024). Decisions Under Uncertainty as Bayesian Inference on Choice Options.
1566   *Management Science*, mnsc.2023.00265. https://doi.org/10.1287/mnsc.2023.00265

1567   von Neumann, J., & Morgenstern, O. (1944). *Theory of games and economic behavior*.
1568   Princeton University Press.

1569   Vrieze, S. I. (2012). Model selection and psychological theory: A discussion of the differences
1570   between the Akaike information criterion (AIC) and the Bayesian information criterion
1571   (BIC). *Psychological Methods*, *17*(2), 228–243. https://doi.org/10.1037/a0027127

1572   Wakker, P. P. (2010). *Prospect Theory: For Risk and Ambiguity* (1st ed.). Cambridge University

1573   Press. https://doi.org/10.1017/CBO9780511779329

1574 Weber, B. J., & Chapman, G. B. (2005). Playing for peanuts: Why is risk seeking more common
1575   for low-stakes gambles? *Organizational Behavior and Human Decision Processes*,
1576   *97*(1), 31–46. https://doi.org/10.1016/j.obhdp.2005.03.001

1577 Wei, X.-X., & Stocker, A. A. (2015). A Bayesian observer model constrained by efficient coding
1578   can explain "anti-Bayesian" percepts. *Nature Neuroscience*, *18*(10), 1509–1517.
1579   https://doi.org/10.1038/nn.4105

1580 Zhang, H., & Maloney, L. T. (2012). Ubiquitous Log Odds: A Common Representation of
1581   Probability and Frequency Distortion in Perception, Action, and Cognition. *Frontiers in*
1582   *Neuroscience*, *6*, 1. https://doi.org/10.3389/fnins.2012.00001

1583 Zhang, H., Ren, X., & Maloney, L. T. (2020). The bounded rationality of probability distortion.
1584   *Proceedings of the National Academy of Sciences*, *117*(36), 22024–22034.
1585   https://doi.org/10.1073/pnas.1922401117

1586 Zhu, J.-Q., Sanborn, A. N., & Chater, N. (2020). The Bayesian sampler: Generic Bayesian
1587   inference causes incoherence in human probability judgments. *Psychological Review*,
1588   *127*(5), 719–748. https://doi.org/10.1037/rev0000190

1589 Zilker, V., & Pachur, T. (2021). Nonlinear probability weighting can reflect attentional biases in
1590   sequential sampling. *Psychological Review*. https://doi.org/10.1037/rev0000304

1591