# Protein Language Model Supervised Scalable Approach for Diverse and Designable Protein Motif-Scaffolding with GPDL

Bo Zhang[#], Kexin Liu[#], Zhuoqi Zheng[#], Junjie Zhu, Zhengxin Li,

Yunfeiyang Liu, Junxi Mu, Ting Wei*, Hai-Feng Chen*

State Key Laboratory of Microbial metabolism, Joint International Research Laboratory of Metabolic & Developmental Sciences, Department of Bioinformatics and Biostatistics, National Experimental Teaching Center for Life Sciences and Biotechnology, School of Life Sciences and Biotechnology, Shanghai Jiao Tong University, Shanghai, 200240, China

**\*Corresponding Author**

**Hai-Feng Chen (Full Professor)**

State Key Laboratory of Microbial metabolism, Joint International Research Laboratory of Metabolic & Developmental Sciences, Department of Bioinformatics and Biostatistics, National Experimental Teaching Center for Life Sciences and Biotechnology, School of Life Sciences and Biotechnology, Shanghai Jiao Tong University, Shanghai, 200240, China
**Tel**: 86-21-34204073; **Fax**: 86-21-34204073; **Email**: haifengchen@sjtu.edu.cn ; weitinging@sjtu.edu.cn

**Notes**

The authors declare that there is no conflict of interest.

**Author Contributions**

[#]These authors contributed equally to this work.

**ABSTRACT**

Proteins perform essential roles in numerous biological processes, largely driven by the three-dimensional structure of several key motif residues. Recently, a variety of energy-based and machine learning backbone generation methods have been developed to solve the motif-scaffolding task. However, it is still challenging to generate diverse and accurate scaffold structures around motifs for models either fine-tuned pre-trained multiple sequence alignment-based (MSA-based) structure prediction models or trained from scratch. Here, we introduced Generative Protein Design by Language model (GPDL) for effectively replacing traditional MSA-based pretraining. Using our scalable design strategy, GPDL successfully solved 22 out of 24 benchmark problems and outperformed other methods by generating 33.5% more unique designable clusters than RFdiffusion. This demonstrates that our approach can generate accurate and physically plausible structures across diverse protein design scenarios. GPDL also showed strong robustness in orphan proteins that have low sequence similarity with the training set. Our approach underscores the promise of protein language models in protein design and has the potential to accelerate the discovery of novel functional proteins for a wide range of biological and therapeutic applications.

**Keywords**: Protein backbone design; Motif-scaffolding problem; Protein language model; GPDL

## Introduction

Protein design has advanced significantly in recent years, especially with deep learning breakthroughs like AlphaFold2 [1]. Many of these approaches follow a motif-scaffolding paradigm, which enables the creation of functional novel proteins, including enzymes [2], binders[3], and antibodies [4]. Within this approach, functional motifs are defined as specific spatial arrangements of amino acid segments, and these works generate new protein backbones to accurately position these regions in their original place.

The primary challenge in motif-scaffolding lies in generating diverse yet consistent scaffolds while preserving the original motif 3D structures with sub-angstrom accuracy. Achieving this requires stabilizing interactions both within and outside the motif regions. Current state-of-the-art methods typically address this challenge by fine-tuning pretrained protein structure models, such as RFdiffusion [5] and RFjoint [6]. While these approaches have significantly improved design accuracy, they often lead to low diversity in scaffolds. This limitation may arise from the inability of MSA-based pretrained models to effectively sample the structural space when fine-tuned for de novo designed proteins, which typically lack co-evolutionary information. Other methods trained from scratch are capable of generating diverse structures to some extent, while often at the cost of lower accuracy[7,8]. On the other hand, several approaches have also explored the use of Markov Chain Monte Carlo (MCMC) or gradient-based algorithms for *de novo* protein design, typically referred to as "hallucination-based" approach, such as restrained hallucination [6], relaxed sequence optimization [9] and BindCraft[10]. However, none of these approaches have yet applied language models as prompts for generating functional proteins.

To address this challenge, we leveraged protein language models, trained solely on amino acid sequences without homologous information, to effectively sample the protein space. Protein language models are large pre-trained models utilized for sequence representation[11–14] which can be fine-tuned for various downstream tasks, including protein structure prediction [15,16], *de novo* sequence generation[17–19], protein function annotation, and protein-protein interactions [20]. These models inherently

capture long-range dependencies within protein sequences due to their extensive
parameters and large-scale training datasets.

We initialized a structure seeding module with a fine-tuned structure module adapted
from ESMFold [15], resulting in a prompt structure. ESM-IF1 [21] was later applied to
encode this structure into possible sequences. These sequences were then fed into a
structure optimization module, refining sequences through a MCMC-based simulated
annealing schedule. Our seeding and optimization module offers enhanced efficiency
compared to optimization methods based on purely random sequences. The results
demonstrated that our model solved more problems and generated more unique
designable clusters compared to other methods.

**Results**

**Overview**

In this study, we used the protein language model ESM2 along with the folding trunk
and structure module from ESMFold to develop GPDL (Generative Protein Design by
Language model). GPDL consists of two main components: the structure seeding
module, which identifies an optimal prompt structure; and the structure optimization
module, which iteratively refines this into a highly plausible structure. The model
architecture is illustrated in **Fig. 1**, with training details provided in the materials and
methods.

The structure seeding module (**Fig. 1B**) takes as input a specified motif sequence and
its distance map to produce an initial, prompt structure, which is subsequently encoded
into sequences using ESM-IF1. This module was fine-tuned under an inpainting task,
and we extended the original architecture, enabling the retrieval of motif information
and facilitating the generation of corresponding structures and sequences. The structure
optimization module (**Fig. 1C**) was then utilized to iteratively refine this sequence
under the supervision of loss functions regards to structure deviation and prediction
confidence, which finally resulted in a highly optimal scaffold.

**Accurate and scalable motif-scaffolding with GPDL**

To rigorously evaluate GPDL's performance, we used a benchmark set covering diverse motif-scaffolding cases from RFdiffusion [5]. We additionally compared the performances along with other outstanding methods including RFdiffusion [5], RFdesign [6], Chroma [8], and TDS [22]. GPDL successfully solved 22 out of the 24 cases (**Fig. 2A**), achieving the highest success rate among all tested methods. Notably, GPDL reached at least the same level of accuracy compared to RFdiffusion but was capable of generating more diverse structure clusters (**Tables S1-S2**).

In order to consider the designability and diversity in the meantime, we used unique designable clusters [23] to quantify the variety of successful design clusters, which better reflects the generalization of the models and the extension of protein space beyond measuring designability and diversity separately. Under this scenario, GPDL generated the highest number of unique designable clusters among all methods (**Fig. 2B**), with a 33.5% increase over RFdiffusion, underscoring its capacity to produce a diverse range of viable designs. Results further showed that the seeding module can provide prompt structures with greater diversity (**Table S1**). Notably, when no prompt structures were introduced, GPDL generated less unique designable clusters, underlining the significant role of the seeding module. We hypothesize that this might arise from the inherent features of protein language models trained using an enormous number of protein sequences, while the MSA-based models trained with limited protein crystal structures potentially lack this prior knowledge of protein space.

While GPDL benefits from the seeding module in terms of diversity, the structure optimization module plays a crucial role in generating more refined and confident backbones, improving both success rates of design and computational efficiency with greater scalability of GPDL. Key metrics, such as motif RMSD, self-consistency TMscore (sc-TMscore), and PAE, demonstrated consistent convergence throughout our optimization trajectories. We noted that metric converged at a significantly different speed with respect of the motif hardness. For challenging cases like a curved beta-sheet protein (PDB ID: 5TRV), as optimization rounds increased, we observed a shift in a subset of the prompt protein designs given by the seeding module towards more

favorable outcomes, evidenced by a peak in higher TMscore and lower PAE values,

and a gradually convergence in several key metrics (**Fig. S1 and Fig. 2C**). This

indicates that the optimization module effectively refined the initial prompt structures

toward optimal results (**Fig. S2 and Fig. S3**).

In the previous methods, scaffolding the active site KSI, a catalytic triad composed of

an aspartic acid, an asparagine, and a tyrosine (PDB ID: 1QJG) presents also

challenging due to its conformational flexibility and extremely limited number of motif

residues (**Table S2**). Optimization module is crucial for accurately reconstructing this

catalytic triad with sub-angstrom accuracy, maintaining the orientation of the side-

chains where other methods such as RFdiffusion and RFdesign-inpainting failed to

scaffold it. It's worth mentioning that the generated backbone adopts a fold distinct

from the native reference, positioning aspartic acid and tyrosine in α-helix, whereas

they reside in α-helix and β-sheet in the native structure. The loop supporting asparagine

remains intact, which, given the loop's high flexibility, helps to retain the catalytic

potential of the designed protein (**Fig. S4**). Moreover, the reduced backbone size

compared to the reference highlights the potential of our method to search for smaller

functional protein backbones, a promising feature for applications in medical research

and healthcare.

In simpler cases, such as the EF-hand motif with a helix-loop-helix secondary structure

(PDB ID: 1PRW), fewer optimization rounds were sufficient to achieve favorable

results, accelerating the design process and reducing computational costs while

maintaining high-precision, reliable protein structures (**Fig. 2D and Fig. S1**). In

contrast, harder cases required more iterations to reach convergence (**Fig. 2E**). For

previously challenging cases where GPDL default had failed—such as the PD-L1 with

a binding interface on PD-1 (PDB ID: 5IUS), characterized by a two-segment, double-

layer beta-strand motif—RFdiffusion generated only one successful design, while our

method produced four successful designs with an iteration count of 5000 (**Fig. S5**).

The user-specified iteration cycles enhance both the scalability and efficiency of the

method. In ablation experiments, the seeding and optimization modules independently

performed well, accurately reconstructing the motif and overall backbones (**Fig. S4**).

Integrating these modules enables GPDL to achieve an optimal balance between design

accuracy and computational efficiency (**Fig. 2F**).

**Designed Backbones of GPDL showed diverse and reasonable topologies**

We further analyzed the designs in each case, focusing particularly on diversity,

stability, and other metrics relevant to designability. We randomly sampled 50

successful backbones from both GPDL and RFdiffusion across a same benchmark case

with different lengths. Diversity was quantified through multi-dimensional scaling

(MDS) based on pairwise backbone TMscore among successful designs. The pairwise

TMscore distribution for GPDL shifted to the left with a lower peak, indicating greater

diversity in successful designs (**Fig. 3A and Fig. 3D**). And the MDS plot for GPDL

covered a broader range of topologies compared to RFdiffusion (**Fig. 3B and Fig. 3E**).

These results suggest that, although RFdiffusion has a higher success rate, GPDL is

more likely to explore a wider structure space.

The ability to design optimal short scaffolds is especially valuable as it suggests

potential for creating functional proteins with smaller backbones, which is significant

for applications in drug delivery and therapy (**Fig. 3G-I**). GPDL demonstrated robust

performance in designing scaffolds across various lengths, particularly for the barnase

ribonuclease inhibitor protein (PDB ID: 7MRX), where it consistently outperformed

RFdiffusion regardless of scaffold length. For the ferredoxin protein (PDB ID: 6E6R)

long and medium scaffold tasks, both GPDL and RFdiffusion performed comparably,

but in short scaffold tasks, GPDL held a notable advantage. For the RNA export factor

(PDB ID: 6EXZ) motif, GPDL's performance varied with scaffold length, likely due to

the helix-loop-sheet topology of motif, which may require longer scaffolds for adequate

support (**Fig. S6-S11**). With extended scaffolds, GPDL also achieved higher design

diversity, with the resulting structures covering a broader range of optimal backbones.

Metal-binding proteins exhibit a broad distribution in biological systems and perform

significant roles across numerous biological processes [24] . Thereupon, we investigated

the design of di-iron binding protein (PDB ID: 1BCF) and a double EF-hand motif with

two calcium ions (PDB ID: 1PRW). We first utilized ProteinMPNN [25] to generate

sequences compatible with backbones designed by GPDL and used AlphaFold3 (AF3)

[26] to predict three-dimensional structures with corresponding ions. The resulting

structures showcased that the designed motifs successfully hold metal ions with stable

binding interactions (**Fig. S12**). In order to further explore the stability of designed

motifs, we performed all-atom molecular dynamics (MD) simulations upon these

structures and analyzed the fluctuations of key biophysical properties during

simulations. Rg (Radius of Gyration) reflects the compactness of simulated structures

and is a commonly-used metric to indicate the overall stability of protein structures

during MD simulation. Our results show a tendency of convergence after 200 ns MD

simulation, demonstrating the stability of the overall structures. Additionally, the small

fluctuations of motif regions could be observed from the results of residue-wise RMSF

(Root Mean Square Fluctutation), further suggesting the stability of metal-binding

motifs, which exhibit significant relevance to biological applications of metal-binding

proteins.

### Model showed strong robustness in low homologous sequences

To test the generalizability of GPDL, we used an orphan protein benchmark set derived

from RFdiffusion [5]. Among these 30 proteins, we classified them into two groups: the

orphan group, with a maximum sequence similarity of less than 30% to the training

sequences using MMseqs2 [27] , and the training group, which includes the remaining

proteins. Results obtained using the same evaluation pipeline indicate robust

performance across both orphan and training proteins, with comparable outcomes in

global TMscore, PAE, motif RMSD, and pLDDT (**Fig. 4A-D**). Our model

demonstrated strong robustness to proteins with low sequence similarity to those in the

training set. Notably, orphan proteins achieved even higher success rates than training

proteins (**Fig. 4E**), aligning with findings from RFdiffusion's orphan protein

evaluations. This preference may be attributed to inconsistency between the training

and inference stages: during training, the model is tasked with recovering full-length

original structures, whereas in inference, it generates new structures and focuses on

recovering motif regions only.

Additionally, our generated orphan proteins possessed significantly lower TMscore

with native structures compared to design backbone structures (**Fig. 4F**), indicating a

high level of diversity among orphan proteins. We illustrated this with two examples:

an orphan protein containing a helical motif (PDB ID: 7S5L, **Fig. 4G**) and a protein

from the training set (PDB ID: 3FKA, **Fig. 4H**). Overall, GPDL is capable of generating

a wide variety of protein backbones, including all-alpha structures, all-beta structures,

and alpha-beta hybrid structures (**Fig. 4G-H and Fig. S13-S17**).

**Discussion**

While our methods enhance computational efficiency and sample diversity, certain

limitations persist. The capability for generating scaffolds around motifs consisting of

a few number of residues has yet to be explored. For instance, it could be observed that

most methods struggled to scaffold very short motifs[28], such as the case catalytic triad

(PDB ID: 1QJG), which has only three discontiguous residues served as motif (**Fig. S4**).

This is a representative problem for scaffolding active sites of enzymes, which plays a

crucial role in protein engineering.

Moreover, the ability of controllable generation is one potential limitation of our present

study. Improving control over the designed structures by integrating prior knowledge,

such as secondary structures and small molecule positions, is one promising future

direction of GPDL. Groundbreaking methods like AlphaFold3[26] and RFdiffusion-AA

[29] have significantly advanced the modeling of complex macromolecule systems,

incorporating various conditional inputs would benefit the current generation process

of  GPDL. In our optimization model, we experimented including the Van der Waals

radius of ligands in the loss function to maintain the locations of binding molecules.

However, while this penalty increased the distance between side-chain atoms and

ligands, it did not significantly enhance generation accuracy (**Fig. S18**). Future work

will focus on explicitly integrating functional information into the design process.

In addition, GPDL and most of the current methods only count for sequence and
structure. However, the incorporation of sequences, structures and functions in the same
space would benefit a lot for further applications. Notably, numerous high quality
predicted protein structures from AlphaFold and ESMFold have made it possible to
align structure embedding with current sequence-only language models. Furthermore,
ESM3[11] has emerged as a powerful tool for multimodal protein language modeling. Its
prompt generation capabilities demonstrate that we can leverage more biological
information to enhance guidance in protein design.

Besides, while GPDL reveals the promise of deep learning and fine-tuning in protein
design, we solely validate our results *in silico*. Due to computational resource
constraints, we did not extensively investigate the criteria for generation success.
However, several experiments indicate that different metrics, such as TMscore or global
RMSD as filters, indeed impact the success rates (**Fig. S19**). In this study, we follow
the RFdiffusion benchmark protocol, setting the TMscore cutoff at 0.5 to evaluate
additional properties and use ESMFold as the final filter. We observe that GPDL
remains robust across different methods, including OmegaFold and the single-sequence
version of AlphaFold2 (**Fig. S20**). This robustness is likely due to our use of
ProteinMPNN for sequence redesign, aligning with findings in other research studies[30].
It is also worthwhile to note that further wet-lab validation of these computational
methods remains essential as most of the artificial intelligence models try to please
users by generating a computational reasonable protein but show deficient biophysical
properties[31].

Our exploration of motif scaffolding has sparked several research interests for future
studies. At first, since one goal of backbone generation is to produce smaller, more
stable proteins with specific functions by including other potential functional sites, it is
essential to investigate the optimal sequence length. In this study, we investigated the
quality of the backbones with different lengths. Our evaluation on the performance of
backbones with varying sequence length on motif recapitulation and structure
confidence represents an initial exploration of the problem of minimal

backbone. Then, we observed a tendency for generated structures to reflect a bias

toward the motif length. New methods are needed to precisely generate these short

motif regions.

Our study underscores the significant impact of deep learning and protein language

models on protein design. Many new powerful models derived from pre-trained

language models have been a game changer in protein function annotation[32], prediction

of protein-protein interaction [20] and other biological applications[33]. Notably, numerous

high quality predicted protein structures from AlphaFold [34] and ESMFold [15] have made

it possible to add the current sequence-only language models [11,35].

In protein design, recent advances in deep learning tools have proven complementary

to Rosetta [36], a widely used physics-based approach. Since many deep learning methods

may lack robustness compared with physics-based approaches, several studies have

successfully combined deep learning models with physical knowledge to achieve more

plausible protein designs [37,38]. This integrative approach leverages the strengths of both

methodologies, resulting in improved design outcomes and a deeper understanding of

protein engineering.

**Conclusion**

In this study, we leveraged protein language models to develop a scalable motif-

scaffolding method (GPDL) consisting of two lightweight and complementary modules.

Our results demonstrate that GPDL can generate accurate and diverse scaffolds across

various cases. Although recent deep generative models like diffusion models and flow

matching shine in the protein design field, our methods and other works [10,39] proved that

by converting structure prediction methods can still generate diverse and accurate

proteins without heavily training resources.

**Materials and Methods**

**Structure Seeding Module**

**Model architectures**

The model input consists of two parts: firstly, the language model is fed with active site sequences and "alanine padding mask" in ather positins, and the structure module takes the input of the distance matrix of active site residues in three-dimensional space. The distance matrix information includes the distances between each pair of amino acids for the 4 backbone atoms (N, CA, C, O) and 1 virtual atom, Virtual CB, totaling 25 distance measurements. The definition of the CB atom is as follows:

$$CB = -0.58273431 * a + 0.56802827 * b - 0.54067466 * c + CA \qquad (1)$$

$$b = CA - N, c = C - CA, a = cross\_product(b, c) \qquad (2)$$

In this study, we adopt the Gaussian radial basis function to convert each distance into a 16-dimensional vector, following the same approach as employed in ProteinMPNN[25] . The $L_2$ distance between two distinct atoms, denoted as $m$ and $n$, located in separate residues $i$ and $j$ is defined as follows:

$$d(i_m, j_n) = \sqrt{\left(i_{m_x} - j_{n_x}\right)^2 + \left(i_{m_y} - j_{n_y}\right)^2 + \left(i_{m_z} - j_{n_z}\right)^2} \qquad (3)$$

Then this distance will be transformed by 16 Gaussian radial functions (mean value from 2Å to 22Å)

$$r < d(i_m, j_n) >_k = exp^{-\left(\frac{d(i_m, j_n) - k}{\sigma}\right)^2}, \forall k \in [2.0, 3.33, 4.667, \dots, 22.0] \qquad (4)$$

Main advantage of utilizing distance matrix is to achieve rotation and translation invariance and provides valuable three-dimensional protein prior knowledge. Any SE3 transformation $T$ for the input structure $\tilde{x}$ will not change the final output.

$$s, x \sim p_\theta(s, x | \tilde{s}, \tilde{x}) = p_\theta(s, x | \tilde{s}, T \circ \tilde{x}) \qquad (5)$$

GPDL seeding module preserves most of the default configurations in ESMFold. The language model is esm2_t36_3B_UR50D version, folding trunk and structure module adopt esmfold_v1 version. We used an additive adapter to add the embedded distance matrix $d_{ij}$ into the pair representation $z_{ij}$ as follows. $W, b$ represents the weight and bias in a single layer feed-forward network.

$$329 \qquad FFN(d_{ij}) = W_1 d_{ij} + b_1 \qquad (6)$$

$$330 \qquad z_{ij} = z_{ij} + FFN(d_{ij}) \qquad (7)$$

331 In the last recycle the single sequence representation $s_i$ will be projected into the

332 probabilities of 20 amino acid. This module sequence predictor is defined as follow.

$$333 \qquad FFN(s_i) = W_2 s_i + b_2 \qquad (8)$$

$$334 \qquad softmax(s_i) = \frac{e^{s_i}}{\sum_{j=1}^{20} e^{(s_i)_j}} \qquad (9)$$

$$335 \qquad s_i = \log softmax(FFN(s_i)) \qquad (10)$$

**Dataset and loss function**

Seeding model employed the CATH4.3 [40] protein structure database as the dataset,

ensuring that the redundancy among sequences did not exceed fourteen percent, which

aligns with the ESM_IF [21] training dataset. During model training, for each protein

sample, a random masking ratio between 0.3 and 0.6 was chosen, and accordingly, a

portion of the sequences was masked with the alanine token, while some random chosen

structural positions were masked with coordinates zero. As the sequence masking and

structural masking are independent processes, we used a hybrid loss function to

combine the global protein sequence cross-entropy loss and the frame-aligned point

error (FAPE) for protein coordinates. The formulas are presented as follows:

$$346 \qquad \mathcal{L} = \frac{1}{|B|} \sum_{i=1}^{|B|} [\beta_1 FAPE(x_i, \tilde{x}_i) + \beta_2 CSE(s_i, \tilde{s}_i)] \qquad (14)$$

FAPE loss is initially proposed by AlphaFold2[1] for protein structure prediction and

demonstrate good performance in many downstream tasks such as protein diffusion

models. The main idea is to align all the rigid groups and atoms between prediction

results and target proteins. Here we only use one backbone rigid group and 3 atoms N,

CA and C for each residue as follow. $T_i, \widetilde{T_j}$ represents the backbone frame for the

predicted residue $i$ residue and the target residue $j$.

$$FAPE\left(x_{i,m}, \widetilde{x_{j,n}}\right) = \sqrt{\left\|T_i^{-1} \circ x_{i,m} - \widetilde{T_j}^{-1} \circ \widetilde{x_{j,n}}\right\|^2} \tag{15}$$

In this study, due to computational limitations we only fine-tune the structure module

which is nearly 2 million parameters. We use Pytorch distributed data parallel and 4

graphics processing units (GPU) for the larger batch size. All the feature extraction

from the PDB file is written by Biotite [41,42], Numpy [43] and Biopython [44] .

**Structure Optimization Module**

**Loss function**

For a given functional motif, structure optimization module utilizes random flanking

sequences as scaffolds and initiates the design by introducing the initial sequence into

a cyclic optimization process. During the optimization process, the initial sequence

undergoes the structure prediction module ESMFold. Since the prediction result at this

stage stems from a random sequence, the initial prediction often yields an unfavorable

disordered structure. To guide the design, a loss function is defined taking the desired

property of the designs into account.

In this study, two key factors were considered when determining the loss function: the

maintenance of motif conformation and the reliability of the generated backbone. The

loss function is formulated as follows:

$$\text{Loss} = 100 - \text{pLDDT} + 10 \times \text{RMSD} \tag{16}$$

where the pLDDT (predicted Local Distance Difference Test) represents a measure of

the confidence of the structure prediction, assessing the reliability of the designed

backbone, and the Root Mean Square Deviation (RMSD) measures the root square

mean deviation between the functional sites of the designed backbone and of the native

structure.

By incorporating both pLDDT and RMSD in the loss function, the optimization process

can effectively give protein backbones that not only retain the desired motif

conformation but also exhibit higher reliability. This comprehensive approach ensures

that the designed proteins are more likely to maintain their intended functionality while

possessing a different structure to the native functional protein.

**MCMC Optimization**

The optimization procedure guided by the loss function is based on MCMC (Markov

Chain Monte Carlo) simulated annealing. After the initial round of structure prediction,

random mutations are introduced into the scaffold sequence, and the structure

prediction is performed on the updated sequences. The acceptance of updated sequence

is according to the metropolis criterion:

387
$$n < e^{(-\frac{L_{new} - L_{old}}{T})} \tag{17}$$

388 Where n is a value randomly sampled between 0 and 1, $L_{old}$ and $L_{new}$ are the losses

389 calculated for the predicted results before and after the current round of mutation, and

390 T is determined as:

391
$$T = (e^{\ln 0.5/500})^{step} \tag{18}$$

Where the step represents the current optimization round and the total number of

optimization cycles for experiments in this study is determined as 1500. MCMC allows

non-differentiable constraints to be a component of the loss function, making it

applicated to other complex protein design problems beyond functional motif

scaffolding.

As the loss function decreased, the designed backbone had optimized. After the final

round of update and structure prediction, the optimized result was output. Through this

interative optimization process, our model provided diverse backbones with high

accuracy of the scaffolded functional motif.

**Sequence design and evaluation**

While both methods were effective in generating the backbones and providing

corresponding sequences, ProteinMPNN[12] was used to refine the sequences

corresponding to the acquired backbones, aiming to enhance the overall success rates

during the subsequent evaluation process. During fixed backbone sequence design, all

amino acid types within motif regions were fixed, identical to the original motifs.

For each case within the benchmark set, we used GPDL to generate 100 initial

backbones. ProteinMPNN was then used to produce 10 sequences for each backbone.

Afterwards, we used ESMFold to predict the 3D structures of each sequence and

calculated the structural similarity with initially generated backbones, of which the

procedure is commonly referred as designable evaluation or self-consistency test. We

consider three metrics as designability definition: Motif reconstruction, with RMSD

between ESMFold predicted motif and native motif less than 1.0 Å; backbone

reconstruction, with TMscore between ESMFold predicted structure and initially

generated backbone larger than 0.5; and a structure prediction confidence metric, where

the predicted aligned error (PAE) value less than 5 Å. Under this criteria, a backbone

is considered designable if at least one out of 10 ProteinMPNN generated sequences

meet all of these criteria. Notably, our definition slightly deviates from the original

method[5], which employs a single sequence AlphaFold prediction for self-consistency.

We hypothesized that the current state-of-the-art single sequence prediction model

ESMFold shows better performance than AlphaFold2 with no MSA information. By

collectively applying these evaluation metrics, we gain valuable insights into the quality

and reliability of the generated protein structures, enabling a comprehensive assessment

of their performance.

**Design on metal-binding proteins**

426 The sequences of metal-binding proteins 1BCF and 1PRW were designed using

427 ProteinMPNN and then predicted using the online server of AlphaFold3. All-atom MD

428 simulations were carried out using the AMBER 22 package [45] . The Amber *ff03CMAP*

429 force field [46] and TIP4PEW water model [47] were used, with parameters of metal ions

generated using *gaff2* force field. All systems were neutralized and solvated in water with cubic boxes ensuring a minimum distance of 10 Å between the box edges and the protein. All bonds involving hydrogen atoms were constrained with the SHAKE algorithm. The particle mesh Ewald (PME) algorithm was used to calculate long-range electrostatic interactions. Initial structures were relaxed with 10,000 steps of minimization, then subjected to heating for 50 ps from 0 K to 300 K and equilibration for 100 ps in NPT ensemble with PMEMD. The simulation was later conducted with the temperature set to 300K.

**ACKNOWLEDGMENTS**

This work was supported by Shanghai Municipal Science and Technology Major Project, partially by SJTU Kunpeng&Ascend Center of Excellence, the Center for HPC at Shanghai Jiao Tong University, and the National Key Research and Development Program of China (2023YFF1205102 and 2020YFA0907700), the Fundamental Research Funds for the Central Universities (YG2023LC03), and the National Natural Science Foundation of China (32171242).

**Code Availability**

The source code of GPDL is available at https://github.com/sirius777coder/GPDL.

**References**

1. Jumper, J. *et al.* Highly accurate protein structure prediction with AlphaFold. *Nature* **596**, 583–589 (2021).

2. Yeh, A. H.-W. *et al.* De novo design of luciferases using deep learning. *Nature* **614**, 774–780 (2023).

3. Vázquez Torres, S. *et al.* De novo design of high-affinity binders of bioactive helical peptides. *Nature* **626**, 435–442 (2024).

4.    Bennett, N. R. *et al.* Atomically accurate de novo design of single-domain

antibodies. 2024.03.14.585103 Preprint at https://doi.org/10.1101/2024.03.14.585103

(2024).

5.    Watson, J. L. *et al.* De novo design of protein structure and function with

RFdiffusion. *Nature* 1–3 (2023).

6.    Wang, J. *et al.* Scaffolding protein functional sites using deep learning. *Science*

**377**, 387–394 (2022).

7.    Yim, J. *et al.* SE(3) diffusion model with application to protein backbone

generation. (2023).

8.    Ingraham, J. B. *et al.* Illuminating protein space with a programmable generative

model. *Nature* **623**, 1070–1078 (2023).

9.    Frank, C. *et al.* Scalable protein design using optimization in a relaxed sequence

space. *Science* (2024).

10. Pacesa, M. *et al.* BindCraft: one-shot design of functional protein binders. *bioRxiv*

(2024) doi:10.1101/2024.09.30.615802.

11. Hayes, T. *et al.* Simulating 500 million years of evolution with a language model.

*bioRxiv* (2024) doi:10.1101/2024.07.01.600583.

12. Rao, R. M. *et al.* MSA Transformer. in *Proceedings of the 38th International*

*Conference on Machine Learning* (eds. Meila, M. & Zhang, T.) 8844–8856 (PMLR,

2021).

13. Rives, A. *et al.* Biological structure and function emerge from scaling unsupervised

learning to 250 million protein sequences. *Proceedings of the National Academy of*

*Sciences* e2016239118 (2021).

14. Elnaggar, A. *et al.* Prottrans: Toward understanding the language of life through

self-supervised learning. *IEEE transactions on pattern analysis and machine*

*intelligence* **44**, 7112–7127 (2021).

15. Lin, Z. *et al.* Evolutionary-scale prediction of atomic-level protein structure with a

language model. *Science* **379**, 1123–1130 (2023).

16. Wu, R. *et al.* High-resolution de novo structure prediction from primary sequence.
*bioRxiv* (2022).

17. Madani, A. *et al.* Large language models generate functional protein sequences
across diverse families. *Nat Biotechnol* **41**, 1099–1106 (2023).

18. Nijkamp, E., Ruffolo, J. A., Weinstein, E. N., Naik, N. & Madani, A. ProGen2:
Exploring the boundaries of protein language models. *cels* **14**, 968-978.e3 (2023).

19. Ferruz, N., Schmidt, S. & Höcker, B. ProtGPT2 is a deep unsupervised language
model for protein design. *Nat Commun* **13**, 4348 (2022).

20. Yang, A. *et al.* Deploying synthetic coevolution and machine learning to engineer
protein-protein interactions. *Science* **381**, eadh1720 (2023).

21. Hsu, C. *et al.* Learning inverse folding from millions of predicted structures. in
*Proceedings of the 39th International Conference on Machine Learning* (eds.
Chaudhuri, K. et al.) 8946–8970 (PMLR, 2022).

22. Wu, L., Trippe, B. L., Naesseth, C. A., Blei, D. M. & Cunningham, J. P. Practical
and Asymptotically Exact Conditional Sampling in Diffusion Models. Preprint at
https://doi.org/10.48550/arXiv.2306.17775 (2023).

23. Yim, J. *et al.* Improved motif-scaffolding with SE(3) flow matching. Preprint at
https://doi.org/10.48550/arXiv.2401.04082 (2024).

24. Zeng, X. *et al.* Discovery of metal-binding proteins by thermal proteome profiling.
*Nat Chem Biol* **20**, 770–778 (2024).

25. Dauparas, J. *et al.* Robust deep learning–based protein sequence design using
ProteinMPNN. *Science* **378**, 49–56 (2022).

26. Abramson, J. *et al.* Accurate structure prediction of biomolecular interactions with
AlphaFold 3. *Nature* 1–3 (2024) doi:10.1038/s41586-024-07487-w.

27. Steinegger, M. & Söding, J. MMseqs2 enables sensitive protein sequence
searching for the analysis of massive data sets. *Nature Biotechnology* **35**, 1026–1028
(2017).

28. Scaffold-Lab: Critical Evaluation and Ranking of Protein Backbone Generation Methods in A Unified Framework | bioRxiv. https://www.biorxiv.org/content/10.1101/2024.02.10.579743v3.

29. Krishna, R. *et al.* Generalized biomolecular modeling and design with RoseTTAFold All-Atom. *Science* **384**, eadl2528.

30. Wicky, B. I. M. *et al.* Hallucinating symmetric protein assemblies. *Science* **378**, 56–61 (2022).

31. Reardon, S. Five protein-design questions that still challenge AI. *Nature* **635**, 246–248 (2024).

32. Bileschi, M. L. *et al.* Using deep learning to annotate the protein universe. *Nature Biotechnology* **40**, 932–937 (2022).

33. Shanker, V. R., Bruun, T. U. J., Hie, B. L. & Kim, P. S. Unsupervised evolution of protein and antibody complexes with a structure-informed language model. *Science* **385**, 46–53 (2024).

34. Varadi, M. *et al.* AlphaFold Protein Structure Database in 2024: providing structure coverage for over 214 million protein sequences. *Nucleic Acids Research* **52**, D368–D375 (2024).

35. Su, J. *et al.* SaProt: Protein Language Modeling with Structure-aware Vocabulary. in *The Twelfth International Conference on Learning Representations* (2024).

36. Alford, R. F. *et al.* The Rosetta All-Atom Energy Function for Macromolecular Modeling and Design. *J. Chem. Theory Comput.* **13**, 3031–3048 (2017).

37. Gainza, P. *et al.* De novo design of protein interactions with learned surface fingerprints. *Nature* **617**, 176–184 (2023).

38. Ovchinnikov, S. & Huang, P.-S. Structure-based protein design with deep learning. *Current Opinion in Chemical Biology* **65**, 136–144 (2021).

39. Frank, C. *et al.* Scalable protein design using optimization in a relaxed sequence space. *Science* (2024).

40. Orengo, C. A. *et al.* CATH–a hierarchic classification of protein domain structures. *Structure* **5**, 1093–1109 (1997).

41. Kunzmann, P. & Hamacher, K. Biotite: a unifying open source computational

biology framework in Python. *BMC bioinformatics* **19**, 1–8 (2018).

42. Kunzmann, P. *et al.* Biotite: new tools for a versatile Python bioinformatics library.

*BMC Bioinformatics* **24**, 236 (2023).

43. Harris, C. R. *et al.* Array programming with NumPy. *Nature* **585**, 357–362 (2020).

44. Cock, P. J. *et al.* Biopython: freely available Python tools for computational

molecular biology and bioinformatics. *Bioinformatics* **25**, 1422 (2009).

45. Case, D. *et al. Amber 2022*. (2022). doi:10.13140/RG.2.2.31337.77924.

46. Zhang, Y., Liu, H., Yang, S., Luo, R. & Chen, H.-F. Well-Balanced Force Field

ff03CMAP for Folded and Disordered Proteins. *J. Chem. Theory Comput.* **15**, 6769–

6780 (2019).

47. Horn, H. W. *et al.* Development of an improved four-site water model for

biomolecular simulations: TIP4P-Ew. *The Journal of Chemical Physics* **120**, 9665–

9678 (2004).

**Figure legends:**

**Figure 1. Model architecture.** (A) The GPDL workflow. (B) The structure seeding model. (C) The structure optimization model. The input structure on the left has the motif region (pink) and scaffold region (gray). The output on the right is a designed structure with the conserved motif (pink) and a newly designed scaffold (blue). The PDB ID in the plot is 2KL8.

**Figure 2. Overall performance.** (**A**) Success rates of 24 benchmark cases from each method. (**B**) Unique designable clusters for each method. The attached numbers denote the number of clusters within designable backbones averaged across the whole benchmark. (**C**) Optimization trajectories in different steps, with metrics representing the mean values of the backbones during optimization: top, motif RMSD; middle, sc-TMscore; bottom, PAE. (**D-E**) Loss curves for benchmark cases 1PRW and 5TRV (short) during optimization. (**F**) Design pipeline from an initial motif structure to a prompt structure generated by seeding module, followed by an optimized structure with 1500 MCMC mutations. The displayed structure is based on the 1PRW motif. The final refolded structure has a motif RMSD of 0.58 Å relative to the native motif, an sc-TMscore of 0.99 compared to the designed structure, pLDDT of 90.66 and max PAE of 2.43. The designed and refolded structure are coloured by the pLDDT confidence score, with blue in high-confidence regions.

**Figure 3. GPDL generates diverse and physically reasonable structures for different lengths.** (A-C) Results for 6E6R_long: (A) Pairwise TMscore distribution, (B) MDS plot of pairwise TMscore, (C) Visualizations of designed backbones exhibiting distinct topologies. (D-F) Results for 6E6R_medium: (D) Pairwise TM-score distribution, (E) MDS plot of pairwise TMscore, (F) Visualizations of designed backbones with varied topologies. (G-I) Comparative metrics across lengths: (G) sc-TMscore, (H) PAE score, and (I) motif RMSD. (J-K) AlphaFold3 predictions and MD simulations for selected designs. The

AF3-predicted structures are shown on the left, where fluctuations during
simulation are displayed on the right. The statistics are collected from MD
simulation with 200 ns. (J) Results for 1BCF.   (K) Results for 1PRW. Colors of
protein structures: Native functional motifs aligned to designed structure,
orange; designed scaffold, pink; designed motif, purple; predicted ions, blue.

**Figure 4. The robust performance of GPDL in orphan and training proteins.**
(**A-D**) sc-TMscore, motif RMSD, PAE and pLDDT distribution for orphan
proteins (yellow) and proteins in the training set (blue). (**E**) Box plot and the
scatter plot of  the success rates for each orphan protein and the training
protein.  (**F**) Box plot of the TMscore for each successfully designed structure
with respect to native structures.  (**G-H)** Designed successful orphan protein
(PDB ID: 7S5L) and training protein (PDB ID: 3FKA). Colors: native functional
motif aligned to designed structure,orange; designed scaffold,pink; designed
motif, purple.

**A**

Structure Seeding → ESM-IF1 → Structure Optimization

motif        motif

scaffold

**B**

Distance Map → Structure Module

Folding Trunk

ESM-2

Native structure and sequence

Output structure

**C**

Structure Module

Folding Trunk

ESM-2

Native structure

Intermediate structure → Confidence Loss → Output structure

MCMC mutation

ESM-IF1 sequence

612        **Figure 1.**

**Figure 2.**

**Figure 3.**

620 **Figure 4.**