A single changing hypernetwork to represent (social-)ecological dynamics

Gaucherel C.[1]*, Cosme M. [1], Noûs C. [2] & Pommereau F.[3]

[1] UMR AMAP – INRAE, University of Montpellier, CNRS, CIRAD, IRD, Montpellier, France
[2] Cogitamus Laboratory, France
[2] IBISC – University of Evry-Val d'Essonne, Unviersity of Paris-Saclay, Evry, France

*Corresponding author
Correspondence: cedric.gaucherel@inrae.fr

ABSTRACT

To understand and manage (social-)ecological systems, we need an intuitive and rigorous way to represent them. Recent ecological studies propose to represent interaction networks into modular graphs, multiplexes and higher-order interactions. Along these lines, we argue here that non-dyadic (non-pairwise) interactions are common in ecology and environmental sciences, necessitating fresh concepts and tools for handling them. In addition, such interaction networks often change sharply, due to appearing and disappearing species and components. We illustrate in a simple example that any ecosystem can be represented by a single hypergraph, here called the ecosystem hypernetwork. Moreover, we highlight that any ecosystem hypernetwork exhibits a changing topology summarizing its long term dynamics (e.g., species extinction/invasion, pollutant or human arrival/migration). Qualitative and discrete-event models developed in computer science appear suitable for modeling hypergraph (topological) dynamics. Hypernetworks thus also provide a conceptual foundation for theoretical as well as more applied studies in ecology (at large), as they form the qualitative backbone of ever-changing ecosystems.

Keywords: Ecosystems, interaction networks, hypergraphs, Petri nets, discrete-event models.

Introduction

Ecosystems are under threat and we need to think carefully about their representations for many reasons. A sound representation helps to conceptualize the study, to understand and ultimately, to manage ecosystems. Ecological and epistemological works continually propose new representations of these complex objects (Gignoux et al., 2011; Schwartz & Jax, 2011), such as class diagrams and interaction networks (Strogatz, 2001; Loreau et al., 2003; Proulx et al., 2005), to name but two. Such representations should firstly be useful and provide relevant insights. Secondly, even in case of well-understood ecosystems, tracking their changes and managing them efficiently, necessitates dealing with a reliable and intuitive representation. While redefining the ecosystem is outside the scope of this paper, we at least acknowledge that all ecosystems are made up of biotic, abiotic and often anthropogenic components. These components continuously interact through various (bio-ecological, social-economic, physicochemical) processes (e.g., S. Frontier et al., 2008; Gignoux et al., 2011; Gaucherel, 2018). Defined as such, the ecosystem may be, and often is, represented as a set of (material) variables and (abstract) processes (Fontaine et al., 2011; Pilosof et al., 2017; Landi et al., 2018). While a set-based representation does not assign an order to ecosystem content, matrix or graph representations more explicitly specify their complex, directed (oriented) interconnections. Such representations often exhibit specific structures, such as multiple interactions between variables (Sonia Kéfi et al., 2017; Gaucherel & Pommereau, 2019) or nested (Bastolla et al., 2009) and modular sets (Dicks et al., 2002) of variables.

Species networks and social networks provide two textbook cases of network representations. It is common to represent species communities in the form of a graph in which the main variables (species or populations) are represented by nodes and their ecological interactions by edges. Species networks generally consist in sub-systems of an ecosystem, including e.g., food webs, plant-pollinator networks, host-parasite networks and competition networks. Some of these graphical models have also been combined with a dynamic model to examine variations in species abundances and process flows (fluxes) on the graph (Proulx et al., 2005; Delmas et al., 2018; Landi et al., 2018). The use of multilayer, multiplex and multilevel networks has recently been proposed to merge distinct sub-systems in the same network (S Kéfi et al., 2016; Pilosof et al., 2017). These multigraphs are representations combining several initially separate graphs involving the same variables into a multilayered graph.

Latterly, it has been proposed to study *hypergraphs* for their ability to grasp non-dyadic (i.e., non-pairwise) interactions between species, also called *Higher-Order Interactions*, as many ecological interactions appear to be mediated by a third (or more) species (Werner & Peacor, 2003; Golubski et al., 2016; Delmas et al., 2018). Such multi-component interactions thus play an important role in system dynamics. Hypergraphs have rarely been used in biology and ecology (but see Billick & Case, 1994; Klamt et al., 2009 ; Valverde et al., 2020). Several definitions have been proposed for the higher-order interactions they capture: a dyadic interaction modulated by (i.e., in the context of) a third species, a non-additive effect of two species on the per-capita growth of another, or the failure of a null dyadic model (Sanchez, 2019). However, the hypergraphs and higher-order interactions found in the literature are mainly confined to interactions made up of three components and are static. Here, we venture to generalize that i) higher-order interactions not only concern species interactions, ii) are not at all restricted to three-way interactions and, ultimately, iii) often change sharply in the long term. In parallel, social networks are also much used and studied.

In the same vein as species networks, anthropogenic nets can be plotted in graph form, with which humans or human groups shown as nodes and each human-related process (e.g., communication, trading, financial exchange) as an edge connecting the concerned nodes (e.g., Buldyrev et al., 2010;

Brummitt et al., 2012). Depending on the question being addressed, such human-related graphs are
sometimes purposefully biased by more social, more economic or political processes. Rarely, these
interaction networks are merged into the same larger graph for study, such as in decision systems (Tixier
et al., 2013; Battiston et al., 2020; Felipe-Lucia et al., 2021). As humans in a society, we understand that
social networks are highly dynamic, frequently losing or gaining new components (individuals or groups)
and interactions, such as in ecosystem services (Scholes et al., 2013; Mao et al., 2021). In principle, there
is nothing to prevent the merging of interaction networks involving human groups with networks
involving species once they interact (Felipe-Lucia et al., 2021), and so on with any other (e.g.,
physicochemical) variable in the same social-ecological system.

In this paper, we will build on the representations above to put forward three interlinked
propositions: i) any ecosystem may be efficiently represented by a single graph, here called the
ecosystem network, whatever the interactions it involves; ii) this single graph would gain from being a
hypergraph (called *hypernetwork*), made up of non-dyadic interactions; and iii) the single hypernetwork
changes in the long term, hence the need to formally document these changes to improve our
understanding of ecosystem dynamics. In other words, we aim to show that the whole (social-)ecological
system (i.e., with all the processes and components it involves) can be represented by a single
comprehensive graph which may be more accurately defined as a changing hypergraph. In addition,
many ecological interactions are non-dyadic, i.e., they involve more than two variables and, reciprocally,
most variables are simultaneously involved in many interactions (Billick & Case, 1994; Valverde et al.,
2020). In this paper, we will not present new models and new results, rather than exemplify the
proposed concepts with our past basic (Gaucherel & Pommereau, 2019; Pommereau et al., 2022a) and
applied studies (Mao et al., 2021; Cosme et al., 2022). As a simple illustration, we will model a termite
population that is eating, producing mushrooms and reproducing through various processes (Turner,
2009). We will show the numerous advantages of representing the ecosystem as a changing
hypernetwork, and will discuss the conceptual, explanatory and practical insights it provides.

Methods and Results

A single graph for the ecosystem
To summarize any ecosystem on the basis of its interactions and interaction networks implies an
understanding, first and foremost, of what an interaction is. An interaction can be defined in several
ways, although most ecologists would accept that it is an abstraction of "real relationships" between
species or between any other ecosystem components (Delmas et al., 2018; Landi et al., 2018). For
example, a "predation interaction" takes the form of the catching and eating by (at least) one predator
individual of (at least) one prey individual (Nakazawa, 2020). Hence, what is usually called predation is an
abstract concept, a kind of immaterial process, with a duration in time and aggregating many events.
When ecologists study interaction networks to understand or predict their dynamics, they mostly explore
quantitative variations in variables (abundances) through various flows (matter and energy exchanges)
connecting them (Lobry & Sari, 2015; Nakazawa, 2020) (Fig. 1a).

Everything that has been said about species may pertain to any other component of a social-
ecological system, depending on the question being addressed. For example, the economic interaction
stating that "a producer sells their productions to a consumer" is composed of a number of occurrences
of isolated and observable sales between two social units (Strogatz, 2001; Gross & Sayama, 2009).
Similarly, the social interaction "a scientist communicates their results" is composed of a number of
utterances or sentences between the scientist and the audience. The fact that the scientist may

simultaneously be communicator, consumer and predator eating a salad for lunch, strongly militates in
favor of merging the respective social, economic and ecological networks in which they are involved
(Felipe-Lucia et al., 2021). The reverse is also true: many processes require several components to be
applied. To "communicate their results", the scientist may use a computer, the salad they have eaten and
potentially studied, and the audience. Hence, as a first step, a single graph can be built in each social-
ecological system, depending on the question being addressed (Fig. 1b).

Figure 1

132
Figure 1 - Tentative representations of corresponding quantitative (a) and qualitative (b)
predator/prey dynamics. The total biomasses of predator (in black) and prey (blue) populations
fluctuate until they collapse (a). In the long term, the trophic network may be represented as a
qualitative graph, potentially involving other species (in grey), shifting sharply from one discrete
state to the next, lacking the corresponding prey and predator nodes.

In previous studies, we suggested calling this comprehensive graph the *ecosystem network* (EN)
(Gaucherel & Pommereau, 2019; Cosme et al., 2022), as it represents flows and is not simply an abstract
mathematical graph. This EN usually concerns a social-ecological system interaction network with no
limitations on the natures of its components and processes, insofar as the question being addressed
requires all these components. We illustrate here this proposed ecosystem representation with a
simplified theoretical termite colony (Table 1). Details of the models can be found in the literature
(Gaucherel & Pommereau, 2019; Gaucherel et al., 2020), and minimal information only will be given here
for understanding. The termite colony model consists in eight components (graph nodes, Fig. 2a)
connected through nine processes (edges), directed from the condition variables to the consequence
variables (Table 1). The same graph representing the system may be displayed with several algorithms for
highlighting distinct features (Fig. 2a-b), such as ecosystem boundaries or multiscale (nested) structures
(Montiglio et al., 2020).
All the graphs examined so far in various disciplines are indeed "sub-graphs" or modules of the same
single "super-graph" of the whole social-ecological system. Often, this is the same node of the EN,
representing a material component, which is potentially involved in highly distinct (trophic,
physicochemical and/or human-related) interaction networks (Fontaine et al., 2011; Gaucherel, 2019).
The reasons that we usually avoid merging all these modular graphs are: specific monodisciplinary
questions being addressed; data, knowledge or skills being unavailable; to avoid time-consuming analyses
often with limited capabilities; or for all these reasons combined. As seen recently in multilayer, multiplex
and multilevel analyses, individual graphs of the same system may be merged into a single larger graph
(Fontaine et al., 2011; Pilosof et al., 2017). This observation strongly suggests that each node is
connected to nodes of distinct natures, through interactions of various natures too (S Kéfi et al., 2016;
Gaucherel et al., 2020). In contrast to these studies, though, we do not make any hypothesis here about
the shape of the EN. It may be layered, modular, nested or have another specific structure: we do not
need to assume its shape, but instead allow the graph topology (i.e., the neighboring relationships) to
emerge from the purported, observed and known interactions (Mao et al., 2021; Cosme et al., 2022).

a)

b)

Figure 2

Furthermore, it follows from this observation that every node, as a component, is a super-graph
(made up of finer sub-nodes) in itself. Indeed, it is always possible, and sometimes relevant, to subdivide
a population node into individuals or groups (e.g., population stages, age-wise, sex-wise), and to

emphasize their various actions, at various levels of organization. All these representations need to be
useful for the question being addressed, though, as it is often pointless to subdivide a component into a
new subgraph to achieve a more detailed representation of the system. This remains valid for a specific
interaction which it is pointless to subdivide into several (dyadic) processes. Whenever it is relevant for
the question being addressed to zoom in (to "unfold") and/or zoom out ("fold") part of the single graph
under examination, it is possible to split nodes into sub-nodes connected to other nodes already present
with distinct processes (Gaucherel, 2019; Montiglio et al., 2020). Such a procedure obviously requires
caution as it quickly encompasses distinct levels of organization (or scales) too.
185
From graph to hypergraph
In real systems, most variables are connected to many others, such as the aforementioned scientist
who interacts with other scientists for the purpose of communication, with salads as food and with
producers for shopping, through the processes of talking, eating and buying. Conversely, most processes
involve many components (variables) simultaneously, such as the communication process requiring the
scientist, potentially an organism under examination (the salad), and the audience. This observation
remains valid for any subgraph and discipline such as, for example, a physicochemical graph of chemical
reactions requiring reactants and catalyzers (Fontana & Buss, 1994; Cumming et al., 2014; Fages et al.,
2018). For these reasons, most interactions are called non-dyadic (i.e., not reduced to dyadic
interactions), a point that has been made recently for ecological networks too (Werner & Peacor, 2003;
Golubski et al., 2016; Delmas et al., 2018). In ecology and elsewhere, it may be that such non-dyadic
interactions are the norm rather than the exception. This leads to complex ENs with a large number of
complex interactions, which require appropriate concepts for disentangling them. Computer science has
developed conceptual and technical tools to handle such non-dyadic interactions and compute their
dynamic consequences. Known as *hypergraphs*, a number of associated tools have been developed to
handle them (e.g., Reisig, 2013; Battiston et al., 2020), although they remain somewhat limited,
especially for non-specialist practitioners, as compared to traditional dyadic graphs.
203
A *hypergraph* is a generalization of a graph in which edges, called *hyperedges*, may have several
incoming and outgoing nodes. In ecology, any variable may be connected through many processes and,
above all, any process may connect many variables, as in the case of the termite colony (Table 1). In our
studies, we use hypergraphs by dictating that nodes are the material components of social-ecological
systems and that edges are the abstract processes involving these components (e.g., Mao et al., 2021;
Cosme et al., 2022). Hence, any hypergraph is a means of representing the state of the ecosystem via the
composition of its components, while still considering their associated interactions. In addition, it is
possible to define the processes involved on the basis of equations or rules that represent the
components' interactions. Such process definitions, be they dyadic or not, naturally direct the associated
EN hyperedges in most environmental studies. Any hypergraph may be represented by a Petri net,
among other convenient tools developed in computer science (Fig. 3b). Petri nets were developed in the
1930s for modeling chemical reactions requiring precisely such connections and have since been used in
many other fields (Pommereau, 2010; Reisig, 2013; Pommereau et al., 2022b). In such a representation,
variables are known as *places* (round-shaped nodes) and interact through processes called *transitions*
(square-shaped nodes), shown as arcs. Any hyperedge may be represented by the set of arcs (or
hyperarcs) of a Petri net, connecting the nodes as the pre-condition and other nodes as the post-
condition of the focal transition (Fig. 3b). Petri net arcs may be weighted, and places may be multi-
valued, holding varied numbers of tokens, thus constraining their flows in the Petri net. Such bipartite
graphs are equivalent to hypergraphs as they allow an arbitrary number of nodes to be connected to an
arbitrary number of edges and vice versa (e.g., the termite colony EN, Fig. 3c).

Shifting to the termite hypergraph, we define specific symbols to signify the Boolean nature of each
node (component) in the rule (process) (Fig. 3a-b). Circular nodes are variables and represent social-
ecological components. A node is drawn with double lines if it is initially present in the system (Boolean
value +), or a single line otherwise (-). When a variable is present, its node has a token (not shown),
otherwise it does not. Square-shaped nodes are transitions and represent social-ecological processes.
Each process is defined graphically by a condition, arcs (round-tipped arrows, Fig. 3b), a transition node
and a consequence, and forms a directed hyperedge. A transition node "reads" and "writes" the values
(tokens) of variables. When an incoming arc (from a variable node to a transition node) has a black (resp.
white) dot, then the transition node "expects" the variable to have a token, i.e., to be present (resp.
absent). Conversely, when an outgoing arc (from transition node to variable) has a black (resp. white)
dot, then the action activates (resp. inactivates) the variable. In the Petri net, a variable activation (resp.
inactivation) corresponds to token production (resp. consumption). A variable may be present in the
condition and in the consequence of the same action. In this case, there will be a dot at each end of the
arc connecting the action to the variable. The resulting graph (Fig. 3c) unambiguously represents the
termite ecosystem EN, and thus explicitly links network structure and dynamics.
An example of non-dyadic interaction may be found in the last process (R9): Ac+, Sd- >> Wk-, Rp-;
stating that termite workers (Wk) and reproductives (Rp) may both die when competitors (Ac) attack the
termite colony in the absence of soldiers (Sd) to defend it. Using the model's terminology, the condition
"presence of competitors and absence of soldiers" enables and triggers the consequence "absence of
workers and reproductives". In this case, a traditional graph representation (Fig. 3a) is not appropriate, as
it hides the exact connections of this four-node interaction. To be rigorous and to retain all the
ecosystemic information, we need a graph that explicitly shows which variables interact with each other,
and how. Inspired by Petri net notations, we propose to replace hyper-arcs (initially connecting nodes)
with another node type (like transitions in Petri nets, Fig. 3b). The resulting graph (Fig. 3c) unambiguously
represents the termite ecosystem EN (Fig. 2b), and thus explicitly links network structure and its potential
dynamics.

Figure 3

Simultaneously, it becomes relevant to analyze the EN structure itself and to highlight the graph topology for ecological insights (Fig. 2b-3b). Here, no shape is assumed for the EN; instead, the graph topology is allowed to emerge from the chosen variables and known interactions, bringing interacting variables closer and moving non-interacting variables further out. With an appropriate graph layout (Fig.

2b), algorithms and graph analyses (Kamada & Kawai, 1989), it is possible to produce representations
that help in understanding node properties (e.g., whether they influence or are influenced by other
nodes) and many other properties (e.g., betweenness, connectivity index) as is already routinely the case
in ecology (e.g., Urban & Keitt, 2001; Foltête & Giraudoux, 2012). For example, a relevant *boundary* of
the ecosystem under examination may be computed by excluding nodes that influence others but are not
influenced in turn (e.g., the sun and other so-called *control variables*), and including all the others (e.g., a
species simultaneously eating and being eaten) (dashed ellipse, Fig. 2b).

Qualitative ecosystem dynamics
Graphs and hypergraphs are by definition discrete. However, the interaction network they represent
might not be (Dicks et al., 2002; Landi et al., 2018; Valverde et al., 2020), as their nodes may represent
continuous variables and their edges continuous flows between them (Fig. 1a). In this paper, we propose
to approximate the interaction network of any ecosystem with a qualitative hypergraph (still generically
denoted as 'EN' hereafter). This hypergraph carries information about the potential qualitative dynamics
of components, namely their appearance and disappearance (Fig. 1b). This description is relevant for
long-term dynamics, as an observer who waits long enough will no longer measure flows and
abundances, but appearance and disappearance of system components (and processes). In this spirit, we
define a system component as a *Boolean* variable, i.e. having two discrete values, describing the
functional presence/absence of the component in the system. A component that is functionally present is
considered to pass a predefined threshold, present in most non-linear processes (R. Thomas, 1973), and
to be able to influence (or be influenced by and possibly, no more influence) other components (Fig. 1b).
Conversely, a process (potentially generating an *event*) is defined as a discrete change in the values of
certain variables (the consequence) triggered by other variables (the condition). According to Petri net
formalism (Pommereau, 2010; Pommereau et al., 2022b), these events are represented by *rules* written
as "condition >> consequence" (Table 1). The change in one (or more) variable(s) is called a transition,
which creates a new system *state*.

Table 1 - List of the eight termite colony variables with their acronyms, initial states (+ or − beside
each variable) and descriptions (columns 1 and 2), and the ten termite colony processes with their
descriptions (columns 3 and 4). Simplified from the initial publications (Gaucherel et al., 2017;
Gaucherel & Pommereau, 2019; Gaucherel et al., 2020).

inhabitants:	Descriptions	rules:	Descriptions
Rp+:	Reproductives	R1: Rp+ >> Ec+	Reproductives lay eggs
Wk-:	Workers	R2: Rp+, Ec+ >> Wk+	Eggs grow into workers
Sd-:	Soldiers	R3: Wk+ >> Wd+, Te+, Fg+, Ec+	Workers collect wood resource and maintain termitomyces and their gardens
Te-:	Termitomyces	R4: Wk+, Wd+ >> Sd+, Rp+	Workers and resources supply soldiers and maintain reproductives
(spatial) structures:		R5: Wk+, Te+ >> Wd-	Workers and termitomyces consume wood resources
Ec-:	Egg chambers	R6: Wd- >> Wk-, Te-	Without wood resources, workers and termitomyces die
Fg-:	Fungal gardens	R7: Wk- >> Fg-, Te-, Sd-	Without workers, fungal gardens (and thus termitomyces) and soldiers disappear
Resources and competitors:		R8: Wk-, Rp- >> Ec-	Without workers and reproductives, eggs cannot be laid
Wd-:	Wood	R9: Ac+, Sd- >> Wk-, Rp-	When competitors attack the termite colony without soldiers, workers and reproductives die

Ac+:	Ant competitors

The sequences of states and transitions are the system *dynamics*. The dynamics of a qualitative EN would enable the sharp changes in the long-term dynamics of the ecosystem to be understood. In a way, the single qualitative EN constitutes the *skeleton*, a kind of backbone of the (social-)ecological system under study, intentionally neglects subtle variations and flows (Gaucherel & Pommereau, 2019; Cosme et al., 2022), i.e., the component dynamics, and enables the computing of qualitative ecosystem dynamics, the network dynamics (Gaucherel et al., 2017; Gaucherel, 2019). An EN hosts the tangled dynamics of species abundances and other components and of flows between them. Many studies have developed powerful models to simulate and understand such dynamics in networks with frozen topology (Thébault & Fontaine, 2010; S. Kéfi et al., 2015). Using discrete-event models, it becomes possible to model changing networks and their discrete dynamics (i.e., state and transitions). A system state is defined by the values of all the variables. In the graph, a system state corresponds to a given token distribution (called the *marking* in Petri nets) among the nodes (Fig 4a). A state transition occurs when the marking changes, that is to say, when one or more tokens are produced and/or consumed in the graph.

Starting from an initial state (blue hexagon in Fig 4a, and column 1 in Table 1), the graph enables the computation of all reachable system states and transitions (following green and pink states). The modelled system may then bifurcate in state n°4 by following rule R1 ("Reproductives lay eggs", Table 1) or in state n°14 by following rule R9 ("workers and reproductives die"), and so on. These states and transitions are usually represented as a State-Transition Graph (STG, Fig. 4a) (Berthomieu et al., 2004; Reisig, 2013). In this STG, any cycle (i.e., a set of mutually reachable states, also called structural stabilities) or fixed state (a state with no outgoing transition, also called deadlocks) becomes now identifiable and informative (Gaucherel & Pommereau, 2019; Gaucherel et al., 2020) (colors in Fig. 4a). Hence, it is possible to automatically compute the discrete-event dynamics of the system from the hypergraph structure (Fig 4b).

This is precisely what we modeled in several studies from a chosen EN of temperate and tropical social-ecological systems (Mao et al., 2021; Cosme et al., 2022). By using specific tools, it is also possible to formalize specific questions about the dynamics displayed in the STG, without explicitly computing them, a relevant advantage when it becomes too large to be fully computed (Fages et al., 2004; Largouët et al., 2012; C. Thomas et al., 2022). In addition to an intelligible visualization of ecosystem structure and dynamics, we now have the benefit of the whole toolbox associated with such representations (Fig. 4b), as with the Petri nets that computer science has developed (Berthomieu et al., 2004; Rodríguez & Schwoon, 2013; Pommereau et al., 2022b). The demonstration of the relevance and application of Petri nets and related concepts is outside the scope of this conceptual paper, but interested readers may refer to recent papers (e.g., Gaucherel & Pommereau, 2019; Mao et al., 2021; Cosme et al., 2022). Such models automatically produce STGs comparable to those already developed in many empirical ecological studies (Stringham et al., 2003; Bestelmeyer et al., 2017). Looking ahead, several computing tools are even able to automatically detect various kinds of topological structures and regularities/invariants directly within the EN (Rodríguez & Schwoon, 2013; C. Thomas et al., 2022). For example, in theory, individuals or populations that may exhibit cycles or that may collapse could be detected by such invariants directly within the EN representation (Fig. 4b). This view supports an innovative conceptual representation of the ecosystem.

Figure 4

Figure 4 - The termite ecosystem state spaces (or STGs), full (a) and merged (b), i.e., the dynamics computed from its corresponding ecosystem network hypergraph (Gaucherel & Pommereau, 2019; Pommereau et al., 2022a). The pathways start from the initial state (hexagon), follow various states according to process rules (defined in Table 1), cycle into sets of states (colors), and finally reach deadlocks (squares). The node labels are arbitrary identifiers of each state (a) and of each structural stability (in brackets, b), while each edge is labeled by the rule (Table 1) responsible for the system change.

A changing (and spatial) hypergraph

Disregarding for a moment variable abundances and process flows, this EN is in no way frozen. In the long term, each component and each process potentially disappears and (re)appears in line with the presence/absence of its material components (Fig. 1b). They can enter (e.g., species invasions or pollutants) and/or leave (species extinctions or migrations) the system being studied. Our aim is to model

network dynamics, i.e., a changing topology, not to be confused with the dynamics of components in a
static network (i.e., flows "carried" by the frozen graph). In the long term, the nodes and edges of the
graphical representation themselves become fragile and ephemeral, depending on the other connected
variables, what previous studies have called *ecosystem development* (Gaucherel et al., 2017; Gaucherel,
2018). Conversely, in short-term dynamics with a similar level of detail, the EN retains the same structure
(Fig. 1 or any state in Fig 4a). This assumption of a fixed topology is still widely used in most ecological
studies today (e.g., Proulx et al., 2005; Golubski et al., 2016; S Kéfi et al., 2016). We posit that such
topological changes, or ecosystem development, strongly differ in nature to ecosystem *functioning*. We
developed a number of models and tools to analyze such qualitative dynamics. In the termite colony toy-
model, the STG computed from the chosen initial state is well suited to detecting stabilities, collapses,
and tipping points (Fig. 4b) in ecosystem pathways (Gaucherel et al., 2020), if any. Today, we are applying
this framework to large and more realistic observed social-ecological systems (e.g., Cosme et al., 2022;
Cosme et al., 2023), sometimes made up of dozens of components and hundreds of interactions of
contrasting nature.
In the long term, the (qualitative) EN topology is continuously changing, and these structural (or
network) dynamics may be largely disconnected from short-term component dynamics. Any sharp
change in the system will change the network topology, which is modeled by the token flow. Modeling
such a changing topology is highly difficult, however, because it implies anticipating any disappearance
and (above all) appearance of components. Practically, it is easier to initially assume the *maximal* EN
topology by including all possible components, and then mimicking their possible disappearance by
removing their associated nodes and/or tokens. For example, in our past studies, we model structural
changes in the EN representing the appearance and disappearance of components by changing the
Boolean values of their associated variables and nodes (Fig. 1b). This is known as the EDEN (for Ecological
and Social Discrete-Event Network) framework (Gaucherel & Pommereau, 2019; Pommereau et al.,
2022a). Such changes are generated by certain rules representing system processes and their related
transition events. The STG precisely computes the successive topologies of the EN, considering the
present and absent components and processes of the termite colony (nodes in Fig. 4a). Hence, any STG
state displays a distinct EN topology, mimicked by the variables changing states (Fig. 3). This makes the
EN an ever-changing hypergraph whose topology needs to be reconstructed for an understanding of the
long-term dynamics.
The EN representation does not fit with the traditional interaction networks in ecology or
environmental sciences as, firstly, we proposed to collect all the interaction networks present in an
ecosystem via qualitative approximation (Fig. 2); and secondly, as we proposed rigorous conventions for
this representation (Fig. 3), inspired by Petri nets which are well adapted for handling such mathematical
objects (Pommereau, 2010; Rodríguez & Schwoon, 2013). It is striking that most models used in ecology
today (mainly ordinary differential equation systems) are not appropriate for handling dynamic systems
on dynamic structures (called DS^2, Giavitto, 2003). Here, the central idea was to integrate all relevant
interactions for the question being addressed into the same graph, and to study the coarse (topological)
graph dynamics.
387
The EN is a coherent and convenient concept for summarizing all ecosystem components, whatever
their nature and complex interactions. It provides a way to achieve the often sought and rarely attained
integration of social-ecological systems (Ostrom, 2009; Mao et al., 2021). Another advantage of
qualitative ENs is their intelligibility (Dambacher et al., 2003; Thébault & Fontaine, 2010), even at larger
sizes, while quantitative models generally require a numerical analysis and act like black boxes. It is
possible to define extensions of the notation presented above that would use as many tokens as required
to model quantitative variations for each (multi-valued) variable, but at the cost of an explosion in STG

sizes and in the model's computation. And nothing prevents, then, the transformation of hypergraphs
into hybrid models combined with systems of differential equations for more quantitative analysis
(Samaga & Klamt, 2013). While most traditional models in ecology and environmental sciences are
limited to a dozen or so variables, with numerical computations, our qualitative models often handle
dozens of variables (Cosme et al., 2023).

In addition, the EN appears heuristic in that, in common with traditional interaction networks, it
reveals the ecosystem's internal structure: the EN topology collects internal variables and their specific
interactions, while highlighting external variables too (Fig. 2b, dashed ellipse). Such external nodes are
control variables that influence (toward ecosystem centrality) without being influenced in turn. In other
words, the boundaries of the ecosystem or the "skin", become visible on the skeleton. Nonetheless, i) the
ecosystem boundary is not necessarily a spatial or specific (e.g., species-centered) boundary, rather than
a multidimensional functional boundary (Fig. 2b), and ii) the hypergraph representation is not hampered
by the boundary definition so often debated (Gignoux et al., 2011; Gaucherel, 2018). It naturally emerges
here from the processes listed in the model, and from the question being addressed. When conceived in
this way, it becomes obvious that the ecosystem does not conserve matter and energy, and is
thermodynamically open (Jorgensen, 2001; S. P.-V. Frontier, D. et al., 2008). Conversely, ecosystem
variables located in the center of the EN hypergraph (e.g., termite workers in Fig. 2b), interact with more
variables in more diversified ways. They do not play a higher role, but they are more closely related to
the question being addressed, as the modeler explicitly considers its possible impacts and influences on
the rest of the system.

In parallel, providing another perspective, all the points discussed previously may be included in
spatially implicit or explicit ecosystem models. Indeed, space itself is easily represented as a graph: in the
case of a spatially explicit ecosystem, the localities involved are potentially represented as nodes or
(unfolded as) a set of nodes themselves, and may be either individualized or merged into the same EN.
Space has long been modeled in this way, as a graph with changing topologies (Burel & Baudry, 2003;
Gaucherel et al., 2012). Conceptually, there is nothing to prevent the merging of the spatial
representation in the graph with the more functional EN we have described here: whenever various
localities need to be described in the same extensive overall super-graph (Felipe-Lucia et al., 2021), their
own EN (but not their corresponding spatial node) may be merged with neighboring ENs too. Hence, each
ecosystem may be represented as a changing single hypergraph, including its spatial structure. Although
such a single hypernetwork would seem huge, it brings the conceptual advantage to provide a coherent
view of any (social-)ecological system, as already mentioned in previous theoretical discussions
(Gaucherel, 2019).

430   **Conclusion**

The so-called ecosystem hypernetwork (EN, i.e., the social-ecological interaction hypergraph) fits our
need for efficient representation of any complex ecosystem, and provides several additional advantages.
It summarizes the internal structure of the system, a kind of synthetic skeleton of the components and
processes involved. In this study, we highlighted three points, illustrated with specific Petri net models.
Firstly, it is possible to collect all the ecosystem's interactions into a single EN, regardless of their nature,
number and how they intertwine. This proposed representation still shows intentional limitations: for
example, in this representation, components never interact directly; here, interactions are always
connected to a process. Similarly, no process can impact directly another process without being

connected to a component. This single EN is possibly not unique, as ecosystem models are driven by a
research question, thus leading to various representations of the same system.
Secondly, the EN is modelled as a hypergraph, which represents non-dyadic interactions more
explicitly. Events and components defining the system can be represented as distinct nodes of a bipartite
graph, as in Petri nets or, in our case, a qualitative hypernetwork (Fig. 3). Thirdly, the EN representing any
ecosystem is dynamic, with a changing topology. We provided an example of a framework (EDEN)
computing qualitative ecosystem dynamics based on transitions producing/consuming tokens in the
hypergraph. This enables a State-Transition Graph to be computed, collecting all the ecosystem states
reachable from the initial state, according to predefined events. This provides a coherent and effective
overview of the dynamics of any ecosystem.

Acknowledgements

451   We wish to thank Colin Thomas for useful discussions on an early draft of this paper.

Data, scripts, code, and supplementary information availability

453   Scripts and code are available online: No data were used in this study; the method sources are
454 archived at https://github.com/fpom/ecco

Conflict of interest disclosure

456   The authors declare that they comply with the PCI rule of having no financial conflicts of interest in
457 relation to the content of the article.

Funding

459   This paper has been started during the project SERVICESCALES, funded by INRA (ECOSERV Meta-
460 program). We thank the SESASA project (ERA-Net LEAP-Agri n°465) for funding our related studies.

References

Bastolla U, Fortuna MA, Pascual-Garcia A, Ferrera A, Luque B, Bascompte J (2009) The architecture of mutualistic networks minimizes competition and increases biodiversity. *Nature,* **458**, 1018-1020

Battiston F, Cencetti G, Iacopini I, Latora V, Lucas M, Patania A, Young J-G, Petri G (2020) Networks beyond pairwise interactions: Structure and dynamics. *Physics Reports,* **874** 1-92. https://doi.org/https://doi.org/10.1016/j.physrep.2020.05.004

Berthomieu B, Ribet P-O, Vernadat F (2004) The tool TINA -- Construction of Abstract State Spaces for Petri Nets and Time Petri Nets. *International Journal of Production Research,* **42**

Bestelmeyer BT, Ash A, Brown JR, Densambuu B, Fernández-Giménez M, Johanson J, Levi M, Lopez D, Peinetti R, Rumpff L, Shaver P (2017) State and Transition Models: Theory, Applications, and Challenges. In: *Rangeland systems*, pp. 303-345. Springer.

Billick I, Case TJ (1994) Higher Order Interactions in Ecological Communities: What Are They and How Can They be Detected? *Ecology,* **75**, 1530-1543

Brummitt CD, D'Souza RM, Leicht EA (2012) Suppressing cascades of load in interdependent networks. *Proceedings of the National Academy of Sciences,* **109**, E680-E689

Buldyrev SV, Parshani R, Paul G, Stanley HE, Havlin S (2010) Catastrophic cascade of failures in interdependent networks. *Nature,* **464**, 1025-1028

Burel F, Baudry J (2003) *Landscape ecology: concepts, methods, and applications*. Science Publishers, Enfield.

Cosme M, Bernardoff O, Hély C, Tiberi C, Parat F, Gautier S, Treydte AC, Colombo G, Ceppi S, Pommereau F, Gaucherel C (2023) Risk assessment and recovery trajectories of a social-ecological system with a discrete-event model after a volcanic eruption. *International Journal of Disaster Risk Reduction,* **92**. https://doi.org/https://doi.org/10.1016/j.ijdrr.2023.103741

487   Cosme M, Hély C, Pommereau F, Pasquariello P, Tiberi C, Treydte AC, Gaucherel C (2022)
488   Qualitative Modeling for Bridging Expert-Knowledge and Social-Ecological Dynamics of an
489   East African Savanna. *Land,* **11**, https://doi.org/10.3390/land11010042
490   Cumming GS, Buerkert A, Hoffmann EM, Schlecht E, Cramon-Taubadel Sv, Tscharntke T (2014)
491   Implications of agricultural transitions and urbanization for ecosystem services. *Nature,* **515**
492   50-57
493   Dambacher JM, Luh H-K, Li HW, Rossignol PA (2003) Qualitative Stability and Ambiguity in
494   Model Ecosystems. *The American Naturalist,* **161**, 876–888
495   Delmas E, Besson M, Brice M-H, Burkle LA, Dalla Riva GV, Fortin M-J, Gravel D, Guimarães Jr.
496   PR, Hembry DH, Newman EA, Olesen JM, Pires MM, Yeakel JD, Poisot T (2018) Analysing
497   ecological networks of species interactions. *Biological Reviews,* **94**, 16-36.
498   https://doi.org/10.1111/brv.12433
499   Dicks LV, Corbet SA, Pywell RF (2002) Compartmentalization in plant–insect flower visitor webs.
500   *Journal of Animal Ecology,* **71**, 32-43. https://doi.org/https://doi.org/10.1046/j.0021-
501   8790.2001.00572.x
502   Fages F, Martinez T, Rosenblueth D, Soliman S (2018) Influence Networks compared with Reaction
503   Networks: Semantics, Expressivity and Attractors. *IEEE/ACM Transactions on*
504   *Computational Biology and Bioinformatics, Institute of Electrical and Electronics Engineers,*
505   **99**, 1-14. https://doi.org/10.1109/TCBB.2018.2805686
506   Fages F, Soliman S, Chabrier-Rivier N (2004) Modelling and querying interaction networks in the
507   biochemical abstract machine BIOCHAM. *Journal of Biological Physics and Chemistry,* **4**,
508   64-73
509   Felipe-Lucia MR, Guerrero AM, Alexander SM, Ashander J, Baggio JA, Barnes ML, Bodin Ö, Bonn
510   A, Fortin M-J, Friedman RS, Gephart JA, Helmstedt KJ, Keyes AA, Kroetz K, Massol F,
511   Pocock MJO, Sayles J, Thompson RM, Wood SA, Dee LE (2021) Conceptualizing ecosystem
512   services using social–ecological networks. *Trends in Ecology & Evolution,* **2944**, 12.
513   https://doi.org/https://doi.org/10.1016/j.tree.2021.11.012
514   Foltête JC, Giraudoux P (2012) A graph-based approach to investigating the influence of the
515   landscape on population spread processes. *Ecological Indicators,* **18**, 684-692
516   Fontaine C, Guimaraes Jr PR, Kéfi S, Loeuille N, Memmott J, van der Putten WH, van Veen FJF,
517   Thébault E (2011) The ecological and evolutionary implications of merging different types of
518   networks. *Ecology Letters,* **14**, 1170-1181
519   Fontana W, Buss LW (1994) What would be conserved if "the tape were played twice"? *Proceedings*
520   *of the National Academy of Sciences (PNAS),* **91**, 757-761
521   Frontier S, Pichod-Viale D, Lepêtre A, Davoult D, Luczak C (2008) *Ecosystèmes. Structure,*
522   *Fonctionnement, Evolution*. Sciences SUP. Dunod, Paris.
523   Frontier SP-V, D., Lepêtre A, Davoult D, Luczak C (2008) *Ecosystèmes. Structure, Fonctionnement,*
524   *Evolution*. Sciences SUP. Dunod, Paris.
525   Gaucherel C (2018) Physical concepts and ecosystem ecology: a revival? *Journal of Ecosystem and*
526   *Ecography,* **8**, DOI: 10.4172/2157-7625.1000259. https://doi.org/10.4172/2157-
527   7625.1000259
528   Gaucherel C (2019) *The Languages of Nature. When nature writes to itself*. Lulu editions, Paris,
529   France.
530   Gaucherel C, Boudon F, Houet T, Castets M, Godin C (2012) Understanding Patchy Landscape
531   Dynamics: Towards a Landscape Language. *PLoS One,* **7**, e46064. https://doi.org/DOI
532   10.1007/s10980-009-9400-6
533   Gaucherel C, Pommereau F (2019) Using discrete systems to exhaustively characterize the dynamics
534   of an integrated ecosystem. *Methods in Ecology and Evolution,* **00**, 1–13.
535   https://doi.org/10.1111/2041-210X.13242
536   Gaucherel C, Pommereau F, Hély C (2020) Understanding ecosystem complexity via application of a
537   process-based state space rather than a potential. *Complexity,* **Article ID 7163920,**.
538   https://doi.org/https://doi.org/10.1155/2020/7163920
539   Gaucherel C, Théro H, Puiseux A, Bonhomme V (2017) Understand ecosystem regime shifts by
540   modelling ecosystem development using Boolean networks. *Ecological Complexity,* **31**, 104-
541   114

Giavitto JL (2003) *Topological collections, transformations and their application to the modeling and*
the simulation of dynamical systems In: Rewriting Technics and Applications (RTA'03): pp.
208 – 233, Springer, Valencia.
Gignoux J, Davies ID, Flint SR, Zucker J-D (2011) The ecosystem in practice: interest and problems
of an old definition for constructing ecological models. *Ecosystems,* **14** 1039-1054
Golubski AJ, Westlund EE, Vandermeer J, Pascual M (2016) Ecological Networks over the
Edge:Hypergraph Trait-Mediated Indirect Interaction (TMII) Structure *trends in Ecology &*
Evolution, **31**, 344-354. https://doi.org/http://dx.doi.org/10.1016/j.tree.2016.02.006
Gross T, Sayama H (2009) *Adaptive Networks: Theory, Models and Applications*. Understanding
Complex Systems. Springer.
Jorgensen SE (2001) *Thermodynamics and Ecological Modelling*. Lewis Publishers, New York.
Kamada T, Kawai S (1989) An algorithm for drawing general undirected graphs. *Information*
Processing Letters, **31**, 7-15
Kéfi S, Berlow EL, Wieters EA, Joppa LN, Wood SA, Brose U, Navarrete SA (2015) Network
structure beyond food webs: mapping non-trophic and trophic interactions on Chilean rocky
shores. *Ecology,* **96**, 291-303
Kéfi S, Miele V, Wieters E, Navarrete S, Berlow E (2016) How Structured Is the Entangled Bank?
The Surprisingly Simple Organization of Multiplex Ecological Networks Leads to Increased
Persistence and Resilience. *PLoS Biology,* **14**, e1002527.
https://doi.org/10.1371/journal.pbio.1002527
Kéfi S, Thébault E, Eklöf A, Lurgi M, Davis AJ, Kondoh M, Krumins JA (2017) Toward Multiplex
Ecological Networks: Accounting for Multiple Interaction Types to Understand Community
Structure and Dynamics. In: *Adaptive Food Webs. Stability and Transitions of Real and*
Model Ecosystems eds Moore JC, Ruiter PCd, McCann KS, & Wolters V). Cambridge
University Press, Published online.
Klamt S, Haus U-U, Theis F (2009) Hypergraphs and Cellular Networks. *PLoS Computational*
Biology, **5**, e1000385
Landi P, Minoarivelo HO, Brännström Å, Hui C, Dieckmann U (2018) Complexity and stability of
ecological networks: a review of the theory. *Population Ecology,* **60**, 319-345.
https://doi.org/https://doi.org/10.1007/s10144-018-0628-3
Largouët C, Cordier M-O, Bozec Y-M, Zhao Y, Fontenelle G (2012) Use of timed automata and
model-checking to explore scenarios on ecosystem models. *Environmental Modelling &*
Software, **30** 123-138
Lobry C, Sari T (2015) Migrations in the Rosenzweig-MacArthur model and the "atto-fox" problem.
ARIMA Journal, **20**, 95-125
Loreau M, Mouquet N, Holt RD (2003) Meta-ecosystems: a theoretical framework for a spatial
ecosystem ecology. *Ecology Letters,* **6**, 673-679
Mao Z, Centanni J, Pommereau F, Stokes A, Gaucherel C (2021) Maintaining biodiversity promotes
the multifunctionality of social-ecological systems: Holistic modelling of a mountain system.
Ecosystem services, **47**, 101220
Montiglio PO, Gotanda KM, Kratochwil CF, Laskowski KL, Farineg DR (2020) Hierarchically
embedded interaction networks represent a missing link in the study of behavioral and
community ecology. *Behavioral Ecology,* **31**, 279–286. https://doi.org/10.1093/beheco/arz168
Nakazawa T (2020) Species interaction: Revisiting its terminology and concept. *Ecological Research,*
35, 1106-1113. https://doi.org/10.1111/1440-1703.12164
Ostrom E (2009) A general framework for analyzing sustainability of social-ecological systems.
Science, **325**, 419-422
Pilosof S, Porter MA, Pascual M, Kéfi S (2017) The multilayer nature of ecological networks. *Nature*
Ecology and Evolution, **1**, 1-9. https://doi.org/10.1038/s41559-017-0101
Pommereau F (2010) Algebras of coloured Petri nets. *Lambert Academic Publishing (LAP)*
Pommereau F, Thomas C, Gaucherel C (2022a) *EDEN framework for interactive analysis of*
ecosystems models. In: PNSE'22: International Workshop on Petri Nets and Software
Engineering, Bergen, NW.

Pommereau F, Thomas C, Gaucherel C (2022b) *Petri Nets Semantics of Reaction Rules: A Language for Ecosystems Modelling.* In: Application and Theory of Petri Nets and Concurrency (PTRE NETS): pp. 175-194, Bergen, Norway.

Proulx SR, Promislow DEL, Phillips PC (2005) Network thinking in ecology and evolution. *TRENDS in Ecology and Evolution,* **20**, 345-353

Reisig W (2013) *Understanding Petri Nets.* Springer Berlin Heidelberg, Berlin, Heidelberg.

Rodríguez C, Schwoon S (2013) *Cunf: A tool for unfolding and verifying Petri nets with read arcs.* ATVA, volume of LNCS (Vol. 8172). Springer.

Samaga R, Klamt S (2013) Modeling approaches for qualitative and semi-quantitative analysis of cellular signaling networks. *Cell Communication and Signaling,* **11**, 1-19

Sanchez A (2019) Defining Higher-Order Interactions in Synthetic Ecology: Lessons from Physics and Quantitative Genetics *Cell Systems,* **9**, 519-520. https://doi.org/https://doi.org/10.1016/j.cels.2019.11.009

Scholes R, Reyers B, Biggs R, Spierenburg M, Duriappah A (2013) Multi-scale and cross-scale assessments of social-ecological systems and their ecosystem services. *Current Opinion in Environmental Sustainability,* **5**, 16-25

Schwartz A, Jax K (2011) *Ecology revisited. Reflecting on Concepts, Advancing Science.* Springer.

Stringham TK, Krueger WC, Shaver PL (2003) State and transition modeling: An ecological process approach. *Journal of Range Management* **56**, 106 -113

Strogatz SH (2001) Exploring complex networks. *Nature,* **410**, 268-276

Thébault E, Fontaine C (2010) Stability of Ecological Communities and the Architecture of Mutualistic and Trophic Networks. *Science* **329**, 853 -856. https://doi.org/10.1126/science.1188321

Thomas C, Cosme M, Gaucherel C, Pommereau F (2022) Model-checking ecological state-transition graphs. *PLoS Computational Biology,* **18**, e1009657

Thomas R (1973) Boolean formalization of genetic control circuits. *Journal of Theoretical Biology,* **42**, 563-585

Tixier P, Peyrard N, Aubertot J-N, Gaba S, Radoszycki J, Caron-Lormier G, Vinatier F, Mollot G, Sabbadin R (2013) Modelling Interaction Networks for Enhanced Ecosystem Services in Agroecosystems. In: *Advances in Ecological Research*, pp. 437-480. Elsevier Ltd

Turner JS (2009) *The extended organism: the physiology of animal-built structures.* Harvard University Press.

Urban D, Keitt T (2001) Landscape Connectivity: A Graph-Theoretic Perspective. *Ecology,* **82**, 1205-1218

Valverde S, Vidiella B, Montañez R, Fraile A, Sacristán S, García-Arenal F (2020) Coexistence of nestedness and modularity in host–pathogen infection networks. *Nature Ecology & Evolution*, https://doi.org/10.1038/s41559-41020-41130-41559. https://doi.org/https://doi.org/10.1038/s41559-020-1130-9

Werner EE, Peacor SD (2003) A review of trait-mediated indirect interactions in ecological communities. *Ecology,* **84**, 1083–1100