The validated touch-video database

Sophie Smit[1,2,3,#] & Anina N. Rich[2,3]

1 The MARCS Institute for Brain, Behaviour and Development, Western Sydney University, Australia
2 School of Psychological Sciences, Macquarie University, Sydney, Australia
3 Performance and Expertise Research Centre, Macquarie University, Sydney, Australia

[#]corresponding author: s.smit@westernsydney.edu.au

Abstract

Visually observing a touch quickly reveals who is being touched, how it might feel, and the broader social or emotional context, shaping our interpretation of such interactions. Exploring these different dimensions is crucial for understanding how we process tactile experiences in ourselves and empathise with others. However, much of the existing research on visual touch perception has relied on simplified or static stimuli, which fail to capture the dynamic complexity of real-world tactile interactions. To address this, we introduce the Validated Touch-Video Database (VTD), a set of 90 videos depicting tactile interactions with a stationary left hand, viewed from a first-person perspective. In each video, a second hand makes contact either directly (e.g., with fingers or an open palm) or using an object (e.g., a soft brush or scissors), with variations across dimensions such as arousal, threat, hedonic qualities, touch type, and the object used. Validation by 350 participants (283 women, 66 men, 1 non-binary) involved categorising the videos as 'neutral', 'pleasant', 'unpleasant', or 'painful' and rating levels of arousal and threat. Our findings reveal high inter-subject agreement, with painful touch eliciting the highest arousal and threat ratings, while neutral touch served as a baseline. Women rated the videos as more threatening and painful compared to men, suggesting potential gender differences in assessing touch stimuli with negative valence. The VTD provides a comprehensive resource for researchers investigating the sensory and emotional dimensions of observed touch.

Introduction

Visually perceiving touch allows us to quickly gather important information about who is being touched (whether oneself or another person), the sensory qualities of the touch, and the broader emotional or social context (Smit, Ramírez-Haro, et al. 2024; Lee Masson and Isik 2023; Hertenstein et al. 2006). Much of the research on visual touch perception has focused on vicarious touch, where individuals report feeling tactile sensations in their own body simply by observing touch in others (for reviews see Gillmeister et al. 2017; Bufalari and Ionta 2013; Peled-Avron and Woolley 2022). This phenomenon is linked to the activation of the observer's somatosensory cortex (Bufalari et al. 2007; Rigato et al. 2019; Bolognini et al. 2011; 2013; Blakemore et al. 2005), suggesting that we may simulate observed touch as though we are experiencing it ourselves (Decety and Jackson 2004; Gallese, Keysers, and Rizzolatti 2004; Keysers and Gazzola 2009; Smit et al. 2023). However, despite the importance of visual touch perception in interpreting sensory and emotional experiences in ourselves and others, we still lack a comprehensive understanding of how we process the detailed sensory qualities of observed touch, as well as emotional-affective dimensions like arousal and threat.

Different aspects have been shown to influence how observed touch is perceived and processed. For instance, stimuli depicting more threatening or painful experiences elicit stronger vicarious responses compared to neutral or non-threatening touch (Holle et al. 2011; Ward, Schnakenberg, and Banissy 2018; Li and Jamie Ward 2022; Smit, Crossley, et al. 2024). Physical factors, such as the body part touched, congruent posture, viewing perspective, and the realism of the stimuli, also play a role (Holle et al. 2011; Medina and DePasquale 2017). However, because many studies use stimuli that differ across multiple dimensions simultaneously, it is difficult to isolate the specific influence of these factors. Research using more controlled stimuli is needed to systematically investigate how individual elements, such as arousal, threat, and valence, shape responses to observed touch.

Gender differences in vicarious sensory perception have also been observed, particularly in neural responses to observed pain (Grice-Jackson et al. 2017; Singer et al. 2006; Li and Jamie Ward 2022; Yang et al. 2009; Smit, Crossley, et al. 2024). This raises the question of whether men and women evaluate the observed touch itself differently. While a previous study found no gender differences in how valence, arousal, and naturalness were rated for observed touch in broader social contexts (Masson and Beeck 2018), such differences may emerge when focusing on specific sensory qualities, particularly in painful touch contexts. Examining how men and women rate various dimensions of detailed visual touch stimuli could reveal differences at the initial stage of stimulus evaluation.

Existing research on visual touch perception has often relied on simplified stimuli, such as a pencil touching a hand or face (Rigato et al. 2019; Adler et al. 2016; Ward, Schnakenberg, and Banissy 2018; Bufalari et al. 2007; Walker et al. 2017; Smit et al. 2023; Bolognini et al. 2011; Smit, Rich, and Zopf 2019). While these stimuli are valuable for studying basic sensory processes, they do not capture the complexity of real-world touch interactions. Studies incorporating more complex touch stimuli tend to rely on static images (Peled-Avron et al. 2016; Bolognini et al. 2013), which fail to reflect the dynamic nature of touch. Further, much of the current research has focused on social touch, where participants observe broader touch interactions rather than specific sensory details (Lee Masson et al. 2020; 2018; Lee Masson and Isik 2023; Peled-Avron et al. 2016; Peled-Avron and Shamay-Tsoory 2017; Schirmer and McGlone 2019). For this, validated databases such as the Social Touch Picture Set (SToPS) (Schirmer et al. 2015) and the Socio-Affective Touch Expression Database (SATED) (Masson and Beeck 2018) have been developed. These databases are useful for comparing social and non-social touch, but lack the sensory diversity and detail required for a more fine-grained investigation of visual touch perception. Advancing this area of research requires a standardised database of dynamic visual touch stimuli that emphasises sensory details while varying key dimensions, such as valence, arousal, threat, and pain, and controls for factors like the body part being touched and the visual context.

To address this gap, we developed the Validated Touch-Video Database (VTD), which includes 90 systematically controlled videos depicting a range of close-up tactile interactions between two hands. These interactions vary across key dimensions, including valence, arousal, threat, pain, the object used for touch, and the type of touch (e.g., pressing, stroking). Consistency is maintained by using a standardised setup, featuring a single female left hand viewed from a first-person perspective. The VTD is designed as a comprehensive resource for investigating the processing of visually perceived touch, focusing on both sensory qualities and emotional-affective dimensions. To validate the VTD, 350 participants were recruited to categorise each video as neutral, pleasant, unpleasant, or painful, and to rate the strength of its hedonic quality. Participants also assessed perceived levels of arousal and threat for each video.

Our analysis demonstrated very strong consistency in arousal and threat ratings between participants, with less but still substantial agreement for categorising the hedonic qualities of the videos. When comparing genders, men were more likely to categorise observed touch videos as 'neutral', while women more often classified them as 'painful' and rated painful videos as more intense. Additionally, women rated the videos as more threatening overall, with no evidence for a difference in arousal ratings between genders. These findings suggest

a gender bias in the initial evaluation of observed touch, particularly for stimuli with negative valence. All videos, along with their validation data, are freely accessible online, providing a resource for future research on the sensory and emotional dimensions of touch.

Materials and methods

Data, code & video availability
OSF: Videos, analysis code, and validation data https://osf.io/jvkqa/
YouTube: Video playlist https://bit.ly/YouTubeVTD
GitHub: Supplementary materials https://sophiesmit1.github.io/VTD/

Creation of the videos
The aim of this study was to create and validate a set of close-up touch videos that capture a wide range of tactile interactions to a hand, varying systematically across the dimensions of valence, arousal, and threat. We produced 90 short videos, each featuring a Caucasian female hand placed on a dark background, with the hand always viewed from a first-person perspective, palm facing down (see Fig. 1). The videos varied in duration from 1.4 seconds to 11.8 seconds (mean duration: 3.8 seconds).

In each video, a second hand touches the stationary hand, either directly (e.g., using fingers or a flat hand) or using an object (e.g., a soft brush, scissors). To create neutral videos, we depicted gentle touches with minimal pressure using non-threatening objects or another hand. The pleasant videos show slow, stroking movements across the hand using either a soft brush or fingers, aiming to evoke a positive, comforting sensation. Unpleasant and painful videos show potentially aversive interactions, such as using a syringe to touch the hand or pinching the skin with tweezers. These interactions appeared realistic enough to suggest discomfort or pain without causing any actual harm or distress to the model. We carefully constructed each video to represent a distinct tactile experience while maintaining consistency in presentation. The dark background and consistent camera angle helped focus attention on the tactile interactions, minimising external distractions.

Figure 1. Still frames for a subset of videos from the Validated Touch-Video Database. These frames illustrate a variety of touch interactions captured from a first-person perspective, depicting different hedonic qualities including neutral, pleasant, unpleasant, and painful touch. The database includes 90 systematically controlled videos that vary across dimensions such as arousal, threat, and touch type, providing a comprehensive resource for investigating the emotional and sensory dimensions of observed touch.

Validation of the videos

Participants

Participants were recruited via the Macquarie University subject pools and consisted of undergraduate students naïve to the purpose of the study (N = 350; 283 women, 66 men; 1 non-binary, mean age = 24 years, SD = 8.66 years, range = 17-63 years). As we only had one non-binary participant, we could not include their data in our analyses of gender.

We asked participants to evaluate the videos based on hedonic qualities, arousal, and perceived threat. Due to the large number of videos, some of which were unpleasant to watch, we set up two separate questionnaires with 45 videos each, each questionnaire comprising of an equal number of neutral, pleasant, unpleasant, and painful videos. Each questionnaire took

approximately 15 minutes to complete. Participants were free to decide whether they wanted to participate in one or both questionnaires and received course credit accordingly. The study was approved by the Macquarie University Human Research Ethics committee and participants provided written consent.

Experimental procedure

Participants completed the questionnaire remotely via the Qualtrics online platform. To ensure the videos were displayed at an appropriate size, participants were instructed to use a desktop computer or laptop, rather than a phone or tablet. The videos were presented in a random order, and auto-play was disabled to ensure participant readiness and engagement. Each video began with a white screen displaying the instruction, "Press play to start video", requiring participants to actively initiate the onset. After watching each video, participants categorised the touch based on its hedonic quality, then rated the strength of the chosen category, perceived threat, and arousal, all on a 1-10 scale (from not at all to extremely). The following four questions were presented after each video:

- **Q1**: How would you categorise the touch in this video? [Options: neutral, pleasant, unpleasant, painful]
- **Q2**: How [pleasant/unpleasant/painful] (based on the previous response) was the touch?
- **Q3**: How threatening was the touch?
- **Q4**: How arousing was this video? (Arousal in terms of a feeling, emotion, or response)

Analyses

In this study, we used Bayesian statistical methods for all analyses, including t-tests, ANOVAs, correlation assessments, and contingency tables. The analyses were conducted using the R programming environment (R Core Team 2023), with the Bayes Factor R package (Morey, Rouder, and Jamil 2018) to calculate Bayes factors (BF). We adopted a default prior based on a Cauchy distribution centred at zero with a scale parameter of $r = 0.707$, allowing for a range of possible effect sizes. Bayes factors provide a quantitative assessment of the evidence in favour of the alternative hypothesis relative to the null hypothesis. For instance, a Bayes factor of 3 indicates that the evidence from our data is three times stronger for the alternative hypothesis than for the null hypothesis. Generally, a Bayes factor greater than 1 indicates support for the alternative hypothesis, while a factor less than 1 favours the null hypothesis, but values between 1 and 3 are considered insufficient for making a definitive conclusion (Jeffreys and Jeffreys 1998; Dienes 2011; Morey, Romeijn, and Rouder 2016; Rouder et al. 2009).

We assessed the consistency of participant ratings for arousal and threat across the 90 videos in our database using the Intraclass Correlation Coefficient (ICC). Specifically, we used a two-way mixed-effects model (ICC3k) to calculate the mean-rating consistency, providing a robust measure of agreement (Koo and Li 2016). ICC estimates were computed along with 95% confidence intervals using the R package Psych (Revelle 2024). A high ICC value indicates strong agreement among participants, which would confirm that the ratings are reliable and consistent across participants.

We used Fleiss' Kappa (Landis and Koch 1977) to assess the consistency of participants' categorisation of the videos into four distinct hedonic categories: neutral, pleasant, unpleasant, and painful. For each of the 90 videos, we calculated the proportion of participants who classified the video into each of the four categories. Fleiss' Kappa values range from -1 to 1 and provide a scale for interpreting the strength of agreement among participants. Negative values suggest less agreement than expected by chance, 0 indicates chance-level agreement, and positive values indicate better agreement than chance. Fleiss' Kappa values can be interpreted as follows: < 0 poor; 0 - 0.20 slight; 0.21 - 0.40 fair; 0.41 - 0.60 moderate; 0.61 - 0.80 substantial; 0.81 - 1 almost perfect agreement (Landis and Koch 1977).

Recognising potential overlap in hedonic categorisation—where some videos may be classified as unpleasant by certain participants and painful by others—we also conducted a focused analysis on a subset comprising the top 10 videos from each category (40 videos total). This subset was selected to provide clear distinctions between hedonic categories, ensuring that the hedonic quality of touch is well-defined for subsequent research. We also examined the arousal and threat ratings for this clearly categorised subset to gain a deeper understanding of how these dimensions vary across different hedonic qualities.

To explore potential gender-specific differences in the assessment of our video stimuli, we examined the dimensions of arousal, threat, and hedonic qualities across all 90 videos, stratified by participant gender.

Results

High agreement across participants for arousal and threat ratings

The ICC analysis yielded high values for both arousal and threat ratings, suggesting a strong level of agreement among participants' ratings (values greater than 0.81 indicate almost perfect agreement; Koo and Li, 2016). Across all participants, the ICC values were very high for both arousal (ICC 0.98, 95% CI: 0.98 - 0.99) and threat (ICC 0.99, 95% CI: 0.99 - 1.00).

These findings suggest that the participants' rating consistency for arousal and threat levels in the video stimuli is robust. Overall, women rated threat (mean 3.50) higher than men (mean 2.99; BF > 1000) but there was no difference in arousal ratings (woman mean 3.83; men 3.76; BF = 0.05; see Fig. 2)

Figure 2. Arousal and threat ratings by gender. The box plots display the median ratings for arousal and threat across all 90 videos, separated by gender. Participants rated the touch on a scale from 1 (not at all) to 10 (extremely), with a total of 283 women and 66 men.

Fair agreement across participants for hedonic categorisation

Most videos were categorised by participants as neutral (35%), followed by unpleasant (33%), pleasant (17%) and painful (14%). We assessed the inter-rater reliability for categorising the 90 videos into four hedonic categories: neutral, pleasant, unpleasant, or painful. The Fleiss' Kappa value for the full set of videos was 0.274, indicating 'fair' agreement. This somewhat lower reliability is due to a subset of videos being categorised equally as neutral/pleasant or unpleasant/painful (see supplementary materials: https://sophiesmit1.github.io/VTD/).

A Bayesian contingency table showed an overall difference in how the genders categorised the videos (BF > 1000) with a higher percentage of men categorising videos as neutral (BF = 884.9) and a higher percentage of women categorising videos as painful (BF > 1000) (see Fig. 3).

Figure 3. Hedonic categorisation of touch videos by gender. The bar graphs display the categorisation of all 90 videos into one of four hedonics categories, separated by gender.

To provide researchers with a subset of videos that clearly depict one of the hedonic categories, we selected the top 10 videos from each category—those with the highest percentage of participants agreeing on their categorisation—creating a 40-video subset. Agreement levels were as follows: neutral videos (70% to 85%), pleasant videos (63% to 91%), unpleasant videos (58% to 70%), and painful videos (45% to 83%) (see Table 1). For example, in the neutral category, the most clearly categorised video had 85% agreement, while the 10th video had 70%. This indicates consistent categorisation and clear distinctions in hedonic qualities within this subset of 40 videos, with only some of the painful videos also being categorised as unpleasant. For this subset, the Fleiss' Kappa value increased to 0.387.

Table 1. Percentage of sample agreement in categorising top 10 videos by hedonic quality, with corresponding mean arousal and threat ratings for these videos; 1-10 scale (not at all - extremely).

Top 10	Description: neutral videos	Neutral (%)	Pleasant (%)	Unpleasant (%)	Painful (%)	Threat (1-10)	Arousal (1-10)
1	single touch with finger	**85**	6	8	1	1.4	1.8
2	single touch with pen	**79**	4	17	0	4.2	3.6
3	single push with a spoon	**79**	7	14	0	3.2	3.7
4	single touch with cotton bud	**78**	19	2	1	1.3	4.5

5	repeated tap with finger	**77**	11	12	0	2.6	3.0
6	single touch with flat hand	**75**	14	11	0	5.2	4.0
7	single touch with plastic brush	**75**	23	2	0	1.3	4.2
8	repeated touch with cotton bud	**73**	20	6	1	1.4	2.7
9	single push with a plastic whisk	**71**	10	19	1	6.5	5.3
10	Repeated touch with finger	**70**	6	24	0	1.8	2.2
Top 10	**Description: pleasant videos**	**Neutral**	**Pleasant**	**Unpleasant**	**Painful**	**Threat**	**Arousal**
1	long stroke with soft brush all over the hand	6	**91**	3	0	1.5	3.0
2	single stroke top to bottom with soft brush	8	**88**	4	0	3.5	3.7
3	stroke top to bottom with shawl	12	**81**	4	2	2.6	2.8
4	single stroke top to bottom with plastic brush	17	**81**	2	0	1.4	3.4
5	stroke with soft sock	11	**79**	10	0	3.5	3.8
6	repeated stroke with plastic brush	15	**79**	5	1	1.2	2.2
7	single stroke top to bottom with cotton pad	26	**73**	1	1	1.4	3.8
8	(long) stroke with multiple fingers all over the hand	18	**71**	10	1	6.6	5.6
9	stroke top to bottom with sponge	33	**63**	3	1	2.6	4.0
10	touch top to bottom with fabric	33	**63**	3	1	1.3	2.1
Top 10	**Description: unpleasant videos**	**Neutral**	**Pleasant**	**Unpleasant**	**Painful**	**Threat**	**Arousal**
1	touch top to bottom with scissors	6	6	**70**	18	4.8	4.2
2	repeated touch with pencil	22	1	**67**	10	4.7	4.7
3	touch top to bottom with hammer	30	4	**63**	3	3.3	3.1
4	hand grabbing wrist	12	6	**61**	21	3.5	3.3
5	repeated touch with metal chopstick	23	5	**59**	12	2.4	2.6
6	scratching with fingernails	18	17	**59**	6	1.8	3.2
7	stroke top to bottom with stanley knife	6	3	**59**	32	4.5	5.0
8	repeated touch with rolling pin	20	2	**58**	20	8.0	6.7
9	single touch with screwdriver	11	0	**58**	31	2.5	2.7
10	touch top to bottom with nail file	8	6	**58**	28	1.4	2.6
Top 10	**Description: painful videos**	**Neutral**	**Pleasant**	**Unpleasant**	**Painful**	**Threat**	**Arousal**
1	single stab with nail file	2	1	14	**83**	1.2	4.7
2	single stab with scissors	1	2	14	**83**	2.9	3.6
3	scratch top to bottom with scissors	3	1	31	**65**	1.5	4.1
4	single pinch with tweezers	2	2	33	**63**	6.0	4.9
5	repeated touch with nail file	2	1	36	**61**	1.4	2.4
6	single injection with sharp needle	3	0	38	**59**	5.2	4.7

7	repeated touch with nail file	5	1	46	**49**	5.9	4.6
8	repeated punch with hand	8	3	42	**46**	1.5	3.3
9	single punch with hand	10	1	44	**45**	1.5	4.0
10	repeated touch with hammer	9	0	46	**45**	5.1	4.3

Strength of hedonic quality

For the subset of 40 videos based on the highest hedonic categorisation, we assessed how intense participants perceived the hedonics of the touch to be (see Fig. 4). We focused on non-neutral touch videos (pleasant, unpleasant, or painful) and asked participants, "How pleasant/unpleasant/painful was the touch?" A Bayesian ANOVA showed a difference in ratings across categories (BF > 1000), with the highest ratings for pleasant videos (mean 4.38), followed by painful videos (4.20) and unpleasant videos (3.10). Bayes factors only provided strong evidence for a difference with unpleasant videos (pleasant vs unpleasant: BF > 1000, painful vs. unpleasant: BF > 1000), but not between pleasant and painful videos (BF = 0.12), suggesting these were rated as equally intense. Women rated the painful videos as more painful than men (BF = 12.36) (see Fig. 5).

Figure 4. Hedonic quality strength ratings for the top 10 videos in each category. Each bar graph displays the average hedonic strength ratings for the entire sample, accompanied by 95% CI error bars. Participants rated the touch on a scale from 1 (not at all) to 10 (extremely). The top 10 most distinctly categorised videos are organised from left to right, with pleasant (green), unpleasant (orange), and painful (red).

Figure 5. Hedonic strength ratings for each category divided by gender. Each bar shows the average hedonic strength ratings for a subset of videos (top 10 per category), differentiated by gender (light bars for men and dark bars for women) with 95% CI error bars. Videos are grouped as pleasant (green), unpleasant (orange), and painful (red).

Correlation between hedonic qualities and arousal and threat ratings

Our goal was to create a database of videos that depicted touch with varying hedonic qualities and substantial variety in arousal levels. Ideally this would allow for a selection of videos that differ in whether they are pleasant or unpleasant while being matched on arousal. We also aimed to include videos with a range of threat levels, as this remains an underexplored dimension of visual touch perception. While arousal and threat are often correlated, pleasant videos may have high arousal but low threat. Additionally, we wanted to include videos perceived as truly neutral—neither pleasant, unpleasant, nor painful—while also being low in arousal and threat. To evaluate whether we achieved this, we examined the interplay between the hedonic qualities of touch and participants' ratings for arousal and threat (see Fig. 6, including Bayes factors for pairwise comparisons). Bayesian ANOVAS showed that both arousal (BF > 1000) and threat (BF > 1000) ratings differed across the hedonic categories. Pleasant and unpleasant videos were rated as similarly arousing (mean 4.06 vs. 4.09) with the highest ratings for painful videos (mean 5.50). Painful videos were most threatening (mean 6.35) followed by unpleasant videos (mean 4.29), both with substantial variability within the hedonic categories (unpleasant range = 2.45 - 6.58; painful range = 4.54 - 7.93). Neutral videos were low in arousal (mean 2.06) and both neutral and pleasant videos were similarly low in threat (mean 1.53 vs. 1.39).

Figure 6. Average ratings for arousal and threat across the top 10 videos in each hedonic category. Participants rated each video on a scale from 1 (not at all) to 10 (extremely). Scatter plots within the violins represent mean scores for individual videos.

Videos & validation data

We combined the results into an easily navigable summary table that features both a touch description for each video and the corresponding YouTube link (https://sophiesmit1.github.io/VTD/). Within this table, users can sort the collection of 90 videos based on key metrics—such as hedonic quality, threat, and arousal—either ascending or descending (see Fig. 7). It also allows users to find videos that align with specific keywords or criteria. The table is also downloadable in multiple formats, including CSV, Excel, and PDF. This feature streamlines the process for users who wish to curate videos based on targeted characteristics.

YouTube video	Description of touch	Link to YouTube	Neutral % pts	Pleasant % pts	Unpleasant % pts	Painful % pts	Mean Threat	Mean Arousal
1	repeated touch with finger (fast)	mvZ-J93FhB8	70	8	22	0	1.8	2.0
2	single touch with finger	DGrxS_mWwDg	85	8	8	0	1.4	1.7
3	single push with finger	X7TYV3JlDGg	61	4	34	1	2.2	2.4
4	repeated tap with finger (slow)	4LCl3lFTI5A	76	12	11	0	1.5	1.9
5	repeated tap with finger moving from top to bottom	VGk7DAEMUqY	61	31	6	1	1.4	2.5
6	single touch with flat hand	hZUtrE-RKm4	76	14	10	0	1.6	2.2
7	repeated touch with hairbrush	jj9cYYLwz3c	34	9	54	4	2.6	2.7
8	single touch with hairbrush	lK5uo4vyk4o	51	8	40	1	2.0	2.3
9	single touch with hammer	UihTe8un04c	34	2	50	14	5.1	3.8

Figure 7. Overview of the videos along with their validation data. Preview of the overview table which can be found on GitHub (https://sophiesmit1.github.io/VTD/). The 90 videos in this table can be arranged based on the highest or lowest values for each index, such as hedonic quality (percentage of participants), threat, and arousal (1 = not at all, 10 = extremely).

Discussion

The aim of this study was to create a systematically defined database of videos depicting a diverse range of tactile interactions to a hand, enabling researchers to investigate the nuances of visual touch perception while controlling for specific dimensions. By assessing inter-subject agreement, we found that participants rated arousal and threat levels consistently across the videos, indicating that the videos effectively captured varying levels of these dimensions. A subset of 40 videos was reliably categorised into neutral, pleasant, unpleasant, and painful touch, with differences observed in perceived arousal and threat levels across these categories. Videos depicting very painful or pleasant touch were associated with the highest arousal ratings, reflecting the previously documented relationship between valence and arousal (Bradley and Lang 1994; Masson and Beeck 2018). The inclusion of a neutral category in the database allows researchers to draw meaningful comparisons between emotionally charged touch interactions and neutral touch.

Our study highlights several gender-related differences in the evaluation of observed tactile interactions. Although both genders provided similar arousal ratings, women rated the videos as more threatening and were more likely to classify them as painful, while men tended to categorise them as neutral. Women also reported higher intensity ratings for painful videos. These findings suggest that women may have heightened sensitivity to visual touch stimuli with negative valence, aligning with previous research showing stronger vicarious responses in women to observed pain (Grice-Jackson et al. 2017; Singer et al. 2006; Li and Jamie Ward 2022; Yang et al. 2009; Smit, Crossley, et al. 2024). Notably, an earlier study reported no gender differences in ratings for valence, arousal, and naturalness of observed touch in broader social contexts (Masson and Beeck 2018), though the sample size was small. In contrast, our study, with a large sample size, reveals that gender differences emerge when participants assess detailed touch videos, particularly in negative contexts. These results suggest it may be useful to consider gender as a factor when evaluating responses to visually perceived touch and pain stimuli.

In the VTD, we included a large number of stimuli depicting various tactile interactions with a hand, enabling nuanced exploration of how different types of touch affect individuals prone to vicarious tactile sensations. Most research on vicarious sensory perception has focused on reactions to observed neutral or threatening touch and pain (Giummarra et al., 2015; Grice-Jackson et al., 2017; Osborn and Derbyshire, 2010; Vandenbroucke et al., 2013; Ward et al., 2018; Ward and Li, 2022), with relatively little attention to pleasant touch. While fMRI studies have enhanced our understanding of the neural correlates of empathy for pleasant and unpleasant sensations (Ebisch et al., 2011; Lamm et al., 2015; Morrison et al., 2011; Riva et al., 2018), they leave room to explore subjective experiences tied to observing touches with different hedonic qualities (e.g., Smit, Crossley, et al. 2024). A recent review identified soft materials and slow, gentle stroking as key factors eliciting pleasurable sensations during direct touch (Taneja et al., 2021). Here, we incorporated such elements to create pleasant visual touch stimuli, which can be used in research settings ranging from therapeutic applications of vicarious touch (Giummarra et al., 2016; Makary et al., 2018; Ramachandran and Altschuler, 2009; Ramachandran and Rodgers-Ramachandran, 1996) to digital marketing and virtual environments (Luangrath et al., 2022). Access to a collection of video stimuli showing diverse touch interactions, including both pleasant and unpleasant touch, allows for a fuller understanding of vicarious tactile experiences.

In the current study, video durations varied, with pleasant videos often featuring slower, longer strokes, while neutral videos displayed brief, simple touches. Researchers may wish to modify these videos in terms of duration, presentation size, or orientation to suit their study's needs.

For instance, in studies examining time-locked responses to observed touch using electroencephalography (EEG), it may be beneficial to standardise the video length. Some studies may also require the hand to be presented from a first- or third-person perspective to suggest touch to oneself or another. In a separate study (Smit, Ramírez-Haro, et al. 2024), we shortened and standardised the videos to 600 milliseconds, presented them in a smaller size, and varied the orientation (flipped horizontally, vertically, or both). Results from an independent participant sample revealed strong correlations between ratings for the original and modified videos across valence, arousal, and threat (mean across modifications: $r = 0.89$), indicating that ratings remain robust even when stimuli are adapted. Both the original and adapted videos are available online (https://osf.io/jvkqa/).

It is important to note that our participant pool consisted primarily of Psychology undergraduate students, which may somewhat limit the generalisability of these validation data. Additionally, while the sample included a substantial number of men, the higher proportion of women may have introduced potential biases in overall responses, particularly given the gender differences evident in the data. Future research could consider a more diverse participant pool to enhance the applicability of findings across various demographics.

In conclusion, the VTD provides a comprehensive resource for researchers to systematically explore the complexities of how visually presented touch is perceived and processed. The inclusion of a large number of videos depicting a wide range of tactile interactions with a hand can be used to study both the affective-emotional and detailed sensory aspects of observed touch.

CRediT authorship contribution statement
Sophie Smit: Conceptualisation, Methodology, Project administration, Data curation, Formal analysis, Visualisation, Writing – original draft, Writing – review & editing. **Anina N. Rich:** Conceptualisation, Methodology, Writing – review & editing, Supervision.

Additional information
This work was supported by a Commonwealth funded Research Training Program and Macquarie University Research Excellence Scholarship awarded to SS, and an ARC Future Fellowship (FT230100119) awarded to ANR. Authors declare no competing interests.

References

Adler, Julia, Nadine Schabinger, Matthias Michal, Manfred E. Beutel, and Helge Gillmeister. 2016. "Is That Me in the Mirror? Depersonalisation Modulates Tactile Mirroring Mechanisms." *Neuropsychologia* 85 (May):148–58. https://doi.org/10.1016/j.neuropsychologia.2016.03.009.

Blakemore, S.-J., D. Bristow, G. Bird, C. Frith, and J. Ward. 2005. "Somatosensory Activations during the Observation of Touch and a Case of Vision–Touch Synaesthesia." *Brain* 128 (7): 1571–83. https://doi.org/10.1093/brain/awh500.

Bolognini, Nadia, Angela Rossetti, Silvia Convento, and Giuseppe Vallar. 2013. "Understanding Others' Feelings: The Role of the Right Primary Somatosensory Cortex in Encoding the Affective Valence of Others' Touch." *The Journal of Neuroscience* 33 (9): 4201–5. https://doi.org/10.1523/JNEUROSCI.4498-12.2013.

Bolognini, Nadia, Angela Rossetti, Angelo Maravita, and Carlo Miniussi. 2011. "Seeing Touch in the Somatosensory Cortex: A TMS Study of the Visual Perception of Touch." *Human Brain Mapping* 32 (12): 2104–14. https://doi.org/10.1002/hbm.21172.

Bradley, Margaret M., and Peter J. Lang. 1994. "Measuring Emotion: The Self-Assessment Manikin and the Semantic Differential." *Journal of Behavior Therapy and Experimental Psychiatry* 25 (1): 49–59. https://doi.org/10.1016/0005-7916(94)90063-9.

Bufalari, Ilaria, Taryn Aprile, Alessio Avenanti, Francesco Di Russo, and Salvatore Maria Aglioti. 2007. "Empathy for Pain and Touch in the Human Somatosensory Cortex." *Cerebral Cortex* 17 (11): 2553–61. https://doi.org/10.1093/cercor/bhl161.

Bufalari, Ilaria, and Silvio Ionta. 2013. "The Social and Personality Neuroscience of Empathy for Pain and Touch." *Frontiers in Human Neuroscience* 7. https://www.frontiersin.org/articles/10.3389/fnhum.2013.00393.

Decety, Jean, and Philip Jackson. 2004. "The Functional Architecture of Human Empathy." *Behavioral and Cognitive Neuroscience Reviews* 3 (June):71–100. https://doi.org/10.1177/1534582304267187.

Dienes, Zoltan. 2011. "Bayesian Versus Orthodox Statistics: Which Side Are You On?" *Perspectives on Psychological Science* 6 (3): 274–90. https://doi.org/10.1177/1745691611406920.

Gallese, Vittorio, Christian Keysers, and Giacomo Rizzolatti. 2004. "A Unifying View of the Basis of Social Cognition." *Trends in Cognitive Sciences* 8 (9): 396–403. https://doi.org/10.1016/j.tics.2004.07.002.

Gillmeister, Helge, Natalie Bowling, Silvia Rigato, and Michael J. Banissy. 2017. "Inter-Individual Differences in Vicarious Tactile Perception: A View across the Lifespan in Typical and Atypical Populations." *Multisensory Research* 30 (6): 485–508. https://doi.org/10.1163/22134808-00002543.

Grice-Jackson, Thomas, Hugo D. Critchley, Michael J. Banissy, and Jamie Ward. 2017. "Common and Distinct Neural Mechanisms Associated with the Conscious Experience of Vicarious Pain." *Cortex* 94 (September):152–63. https://doi.org/10.1016/j.cortex.2017.06.015.

Hertenstein, Matthew J., Dacher Keltner, Betsy App, Brittany A. Bulleit, and Ariane R. Jaskolka. 2006. "Touch Communicates Distinct Emotions." *Emotion* 6 (3): 528–33. https://doi.org/10.1037/1528-3542.6.3.528.

Holle, Henning, Michael Banissy, Thomas Wright, Natalie Bowling, and Jamie Ward. 2011. "'That's Not a Real Body': Identifying Stimulus Qualities That Modulate Synaesthetic Experiences of Touch." *Consciousness and Cognition* 20 (3): 720–26. https://doi.org/10.1016/j.concog.2010.12.002.

Jeffreys, Sir Harold, and Sir Harold Jeffreys. 1998. *The Theory of Probability*. Third Edition, Third Edition. Oxford Classic Texts in the Physical Sciences. Oxford, New York: Oxford University Press.

Keysers, Christian, and Valeria Gazzola. 2009. "Expanding the Mirror: Vicarious Activity for Actions, Emotions, and Sensations." *Current Opinion in Neurobiology*, Motor systems • Neurology of behaviour, 19 (6): 666–71. https://doi.org/10.1016/j.conb.2009.10.006.

Koo, Terry K., and Mae Y. Li. 2016. "A Guideline of Selecting and Reporting Intraclass Correlation Coefficients for Reliability Research." *Journal of Chiropractic Medicine* 15 (2): 155–63. https://doi.org/10.1016/j.jcm.2016.02.012.

Landis, J. Richard, and Gary G. Koch. 1977. "An Application of Hierarchical Kappa-Type Statistics in the Assessment of Majority Agreement among Multiple Observers." *Biometrics* 33 (2): 363–74. https://doi.org/10.2307/2529786.

Lee Masson, Haemy, and Leyla Isik. 2023. "Rapid Processing of Observed Touch through Social Perceptual Brain Regions: An EEG-fMRI Fusion Study." *The Journal of Neuroscience* 43 (45): 7700–7711. https://doi.org/10.1523/JNEUROSCI.0995-23.2023.

Lee Masson, Haemy, Ineke Pillet, Bart Boets, and Hans Op de Beeck. 2020. "Task-Dependent Changes in Functional Connectivity during the Observation of Social and Non-Social Touch Interaction." *Cortex* 125 (April):73–89. https://doi.org/10.1016/j.cortex.2019.12.011.

Lee Masson, Haemy, Stien Van De Plas, Nicky Daniels, and Hans Op de Beeck. 2018. "The Multidimensional Representational Space of Observed Socio-Affective Touch Experiences." *NeuroImage* 175 (July):297–314. https://doi.org/10.1016/j.neuroimage.2018.04.007.

Li, Mengze, and Jamie Ward. 2022. "The Vicarious Experiences Questionnaire(s): Online Tools for Measuring Mirror-Touch and Vicarious Pain." https://doi.org/10.31234/osf.io/ae6x4.

Masson, Haemy Lee, and Hans Op de Beeck. 2018. "Socio-Affective Touch Expression Database." *PLOS ONE* 13 (1): e0190921. https://doi.org/10.1371/journal.pone.0190921.

Medina, Jared, and Carrie DePasquale. 2017. "Influence of the Body Schema on Mirror-Touch Synesthesia." *Cortex* 88 (March):53–65. https://doi.org/10.1016/j.cortex.2016.12.013.

Morey, Richard D., Jan-Willem Romeijn, and Jeffrey N. Rouder. 2016. "The Philosophy of Bayes Factors and the Quantification of Statistical Evidence." *Journal of Mathematical Psychology*, Bayes Factors for Testing Hypotheses in Psychological Research: Practical Relevance and New Developments, 72 (June):6–18. https://doi.org/10.1016/j.jmp.2015.11.001.

Morey, Richard D., Jeffrey N. Rouder, and Tahira Jamil. 2018. "BayesFactor: Computation of Bayes Factors for Common Designs."

Peled-Avron, Leehe, Einat Levy-Gigi, Gal Richter-Levin, Nachshon Korem, and Simone G. Shamay-Tsoory. 2016. "The Role of Empathy in the Neural Responses to Observed Human Social Touch." *Cognitive, Affective, & Behavioral Neuroscience* 16 (5): 802–13. https://doi.org/10.3758/s13415-016-0432-5.

Peled-Avron, Leehe, and Simone G. Shamay-Tsoory. 2017. "Don't Touch Me! Autistic Traits Modulate Early and Late ERP Components during Visual Perception of Social Touch." *Autism Research* 10 (6): 1141–54. https://doi.org/10.1002/aur.1762.

Peled-Avron, Leehe, and Joshua D Woolley. 2022. "Understanding Others through Observed Touch: Neural Correlates, Developmental Aspects, and Psychopathology." *Current Opinion in Behavioral Sciences* 43 (February):152–58. https://doi.org/10.1016/j.cobeha.2021.10.002.

R Core Team. 2023. "R: A Language and Environment for Statistical Computing." https://www.R-project.org/.

Revelle, William. 2024. "Psych: Procedures for Psychological, Psychometric, and Personality Research." https://cran.r-project.org/web/packages/psych/index.html.

Rigato, Silvia, Andrew J. Bremner, Helge Gillmeister, and Michael J. Banissy. 2019. "Interpersonal Representations of Touch in Somatosensory Cortex Are Modulated by

Perspective." *Biological Psychology* 146 (September):107719.
https://doi.org/10.1016/j.biopsycho.2019.107719.

Rouder, Jeffrey N., Paul L. Speckman, Dongchu Sun, Richard D. Morey, and Geoffrey
Iverson. 2009. "Bayesian t Tests for Accepting and Rejecting the Null Hypothesis."
Psychonomic Bulletin & Review 16 (2): 225–37.
https://doi.org/10.3758/PBR.16.2.225.

Schirmer, Annett, and Francis McGlone. 2019. "A Touching Sight: EEG/ERP Correlates for
the Vicarious Processing of Affectionate Touch." *Cortex* 111 (February):1–15.
https://doi.org/10.1016/j.cortex.2018.10.005.

Schirmer, Annett, Christy Reece, Claris Zhao, Erik Ng, Esther Wu, and Shih-Cheng Yen.
2015. "Reach out to One and You Reach out to Many: Social Touch Affects Third-
Party Observers." *British Journal of Psychology* 106 (1): 107–32.
https://doi.org/10.1111/bjop.12068.

Singer, Tania, Ben Seymour, John P. O'Doherty, Klaas E. Stephan, Raymond J. Dolan, and
Chris D. Frith. 2006. "Empathic Neural Responses Are Modulated by the Perceived
Fairness of Others." *Nature* 439 (7075): 466–69.
https://doi.org/10.1038/nature04271.

Smit, Sophie, Matthew J. Crossley, Regine Zopf, and Anina N. Rich. 2024. "Characteristics
of Vicarious Touch Reports in a General Population." bioRxiv.
https://doi.org/10.1101/2024.01.30.577948.

Smit, Sophie, Denise Moerel, Regine Zopf, and Anina N. Rich. 2023. "Vicarious Touch:
Overlapping Neural Patterns between Seeing and Feeling Touch." *NeuroImage* 278
(September):120269. https://doi.org/10.1016/j.neuroimage.2023.120269.

Smit, Sophie, Almudena Ramírez-Haro, Genevieve L. Quek, Manuel Varlet, Denise Moerel,
and Tijl Grootswagers. 2024. "Rapid Visual Engagement in Neural Processing of
Detailed Touch Interactions." https://doi.org/10.1101/2024.08.29.610402.

Smit, Sophie, Anina N. Rich, and Regine Zopf. 2019. "Visual Body Form and Orientation
Cues Do Not Modulate Visuo-Tactile Temporal Integration." *PLOS ONE* 14 (12):
e0224174. https://doi.org/10.1371/journal.pone.0224174.

Walker, Susannah C., Paula D. Trotter, Andy Woods, and Francis McGlone. 2017.
"Vicarious Ratings of Social Touch Reflect the Anatomical Distribution & Velocity
Tuning of C-Tactile Afferents: A Hedonic Homunculus?" *Behavioural Brain Research*
320 (March):91–96. https://doi.org/10.1016/j.bbr.2016.11.046.

Ward, Jamie, Patricia Schnakenberg, and Michael J Banissy. 2018. "The Relationship
between Mirror-Touch Synaesthesia and Empathy: New Evidence and a New
Screening Tool." *Cognitive Neuropsychology* 35 (5–6): 314–32.
https://doi.org/10.1080/02643294.2018.1457017.

Yang, Chia-Yen, Jean Decety, Shinyi Lee, Chenyi Chen, and Yawei Cheng. 2009. "Gender
Differences in the Mu Rhythm during Empathy for Pain: An Electroencephalographic
Study." *Brain Research* 1251 (January):176–84.
https://doi.org/10.1016/j.brainres.2008.11.062.