Genome-scale annotation of protein binding sites via language model and geometric deep learning

Qianmu Yuan, Chong Tian, Yuedong Yang[*]

School of Computer Science and Engineering, Sun Yat-sen University, Guangzhou 510000, China

[*]For correspondence: yangyd25@mail.sysu.edu.cn

Abstract

Revealing protein binding sites with other molecules, such as nucleic acids, peptides, or small ligands, sheds light on disease mechanism elucidation and novel drug design. With the explosive growth of proteins in sequence databases, how to accurately and efficiently identify these binding sites from sequences becomes essential. However, current methods mostly rely on expensive multiple sequence alignments or experimental protein structures, limiting their genome-scale applications. Besides, these methods haven't fully explored the geometry of the protein structures. Here, we propose GPSite, a multi-task network for simultaneously predicting binding residues of DNA, RNA, peptide, protein, ATP, HEM, and metal ions on proteins. GPSite was trained on informative sequence embeddings and predicted structures from protein language models, while comprehensively extracting residual and relational geometric contexts in an end-to-end manner. Experiments demonstrate that GPSite substantially surpasses state-of-the-art sequence-based and structure-based approaches on various benchmark datasets, even when the structures are not well-predicted. The low computational cost of GPSite enables rapid genome-scale binding residue annotations for over 568,000 sequences, providing opportunities to unveil unexplored associations of binding sites with molecular functions, biological processes, and genetic variants. The GPSite webserver and annotation database can be freely accessed at https://bio-web1.nscc-gz.cn/app/GPSite.

Introduction

Proteins perform most biological functions by specifically interacting with other molecules such as nucleic acids, peptides, proteins, or small ligands of various kinds [1-3]. Knowledge of these binding interfaces benefits protein function prediction, disease mechanism understanding, and novel drug design [4-6]. Although experimental techniques such as X-ray crystallography and nuclear magnetic resonance spectroscopy can solve the native complex structures to detect binding sites, they are costly, time-consuming, and unsuitable for proteins with unknown binding partners. With the explosive growth of proteins in sequence databases [7,8], developing effective and efficient computational methods to recognize potential binding regions from sequences in a large-scale manner is imperative to fill the gap between genome and phenome.

A conventional way to predict binding interfaces is comparative modeling, which employs alignment algorithms to transfer known binding residues from similar templates to the query proteins [9-11]. Nevertheless, this strategy will be seriously restricted when no high-quality template exists. Therefore, methods based on machine learning and deep learning have prevailed in recent years, which

can be divided into sequence-based and structure-based approaches according to their used protein information. Sequence-based methods leverage machine learning classifiers (e.g., support vector machine) to learn local binding characteristics from sequence contexts in a sliding window [12-15], or employ deep learning models like transformer [16] to capture global dependencies [17,18]. Despite requiring only readily available protein sequences, these predictors are of limited accuracy due to the lack of tertiary structure information. On the other hand, experimental structure-based approaches are often more effective. Earlier methods encode protein structures as 2D images [19] or 3D voxels [20], which are processed via grid-based convolutional neural networks. Current approaches tend to handle protein structures as graphs composed of surface point clouds [21,22], atoms [23,24] or residues [25,26], and adopt geodesic convolution or graph neural networks (GNNs) to learn the binding-relevant spatial patterns. Unfortunately, the expressive capacities of most methods remain restricted, as the geometry of the structure is not yet fully explored. More importantly, both present sequence- and structure-based predictors are hampered for high-throughput practices at the genome scale for two reasons. Firstly, the dependency on evolutionary profiles from multiple sequence alignments (MSA) for most methods leads to high computational expense and occasionally subpar performance for shallow sequence alignments. Secondly, albeit powerful when native structures are available, structure-based methods will exhibit performance declines for unbound or predicted structures, probably owing to their sensitivity towards details and errors in the structures.

Our previous work [27] has validated the feasibility of exploiting predicted structures from AlphaFold2 [28] for training to enhance the model's robustness, yet the computationally intensive structure prediction pipeline still restrains its application to novel sequences absent from the AlphaFold Protein Structure Database [29]. Since protein sequence can be regarded as a language in biology, unsupervised pre-training with language models has recently been applied to protein sequence representation learning and has displayed competitive or better results than manually-engineered evolutionary features in different downstream tasks [18,30-33]. Based on this, ESMFold [34] replaces evolutionary information from MSA with a large-scale pre-trained protein language model to directly infer atomic-level protein structure from single sequence. This results in an order-of-magnitude acceleration of prediction while maintaining accuracy nearly as alignment-based methods including AlphaFold2. Therefore, it is promising to develop a fast and accurate model tailored for large-scale sequence-based binding site prediction based on the recent advances in protein representation learning and structure prediction with language models.

To facilitate protein structure modeling, geometric deep learning techniques have recently flourished in protein docking [35], protein structure pre-training [36], protein design [37,38], and binding site prediction [21-24], since they can better manipulate data with no natural grid-like topology than 3D convolutional neural networks. Among these, current geometric binding site predictors are mostly built on surface point clouds [21,22] or atom graphs [23,24]. However, although the binding interface is mainly comprised of surface atoms, the global structure of the protein in general influences how the interface is formulated and how the binding partner is interacted with, which should be modeled. Besides, the calculation of protein surfaces and mapping of their properties are usually time-consuming, while methods based on full atom graphs are memory-consuming and thus difficult to process long

sequences. Consequently, designing a geometry-aware message passing mechanism on residue graphs to synergistically integrate sequence and structure information is potentially more suitable for the binding site prediction task.

In this study, we propose GPSite (Geometry-aware Protein binding Site predictor), a fast, accurate and versatile network for concurrently predicting binding residues of ten types of biologically relevant molecules including DNA, RNA, peptide, protein, ATP, HEM, and metal ions (Zn^{2+}, Ca^{2+}, Mg^{2+}, Mn^{2+}) in a multi-task framework. GPSite was trained on informative sequence embeddings and predicted structures generated by pre-trained protein language models, and thus does not rely on MSA or native structures. To better capture the high-level bio-physicochemical characteristics in the predicted structures, a comprehensive geometric featurizer along with an edge-enhanced graph neural network is designed to extract the residual and relational geometric contexts in an end-to-end manner. Experiments demonstrate that GPSite substantially surpasses state-of-the-art sequence-based and structure-based approaches on various benchmark datasets, even under conditions where the predicted structures are of lower quality. GPSite runs fast enough to process genome-scale sequence databases such as the entire Swiss-Prot [7], allowing for rapid binding residue annotations for over 568,000 sequences. Further analyses indicate that such annotations can promote discoveries in associations of binding sites with molecular functions, biological processes, and genetic variants. Besides the standalone code, we also provide the GPSite webserver and annotation database at https://bio-web1.nscc-gz.cn/app/GPSite.

Results

The geometry-aware protein binding site predictor (GPSite)

GPSite is a geometry-aware versatile protein binding site predictor that can fast and accurately identify binding residues of DNA, RNA, peptide, protein, ATP, HEM, and metal ions (Zn^{2+}, Ca^{2+}, Mg^{2+}, Mn^{2+}) from protein sequences. As shown in **Figure 1** and detailed in Methods, an input protein sequence is fed to the pre-trained language model ProtTrans [31] and the folding model ESMFold to generate informative sequence embedding and predicted structure, respectively. From the predicted structure, the coordinates of the N, C_α, C and O atoms as well as the centroid of the heavy sidechain atoms are gathered, and DSSP [39] is employed to calculate the relative solvent accessibility and secondary structure for each residue. Then, a protein radius graph is built where residues constitute the nodes and adjacent nodes are connected by edges. In addition to the residue features by ProtTrans and DSSP, an end-to-end geometric featurizer is designed to construct a local coordinate system for each residue and extract geometric features capturing the arrangements of backbone and sidechain atoms in or between residues. Specifically, the geometric node features consist of intra-residue distances between two atoms (including the sidechain centroid), relative directions of other inner atoms or sidechain centroid to C_α, as well as the bond and torsion angles. Similarly, the geometric edge features comprise inter-residue distances between atoms from the two neighboring residues, relative directions of all atoms in the adjacent residue to C_α of the central residue, and spatial orientation between the two reference frames of the neighboring nodes.

To learn the residue representations by considering multi-scale interactions in node, edge, and

global context levels, we design a GNN with message passing, edge update and global node update
acting on this geometric-aware attributed graph. The message passing layer adopts the multi-head
attention in transformer enhanced by edge features to aggregate information from the local
neighborhood and update the central node. Then the features of an edge are updated using its
connecting nodes. Finally, a gated attention is applied to update the node states using the global context
information. Benefiting from the above pipeline, GPSite is invariant to rotation and translation.
Besides, GPSite leverages the multi-task learning strategy, where the GNN is shared among different
ligands to capture the common binding-relevant characteristics, followed by ten ligand-specific
multilayer perceptrons (MLPs) to mine the binding patterns of particular molecules. This framework
also reduces the time for inference of multiple ligands by the concurrent prediction fashion. In
conclusion, GPSite is distinguished from the previous approaches in several aspects. First, profiting
from the effectiveness and low computational cost of ProtTrans and ESMFold, GPSite is liberated from
the reliance on MSA and native structures, thus enabling genome-wide binding site prediction. Second,
unlike methods that only explore the C_α models of proteins [25,40], GPSite exploits a comprehensive
geometric featurizer to fully refine knowledge in the backbone and sidechain atoms. Third, the
employed message propagation on residue graphs is global structure-aware and time-efficient
compared to the methods based on surface point clouds [21,22], and memory-efficient unlike methods
based on full atom graphs [23,24]. Last but not least, instead of predicting binding sites for a single
molecule type or learning binding patterns separately for different molecules, GPSite applies multi-task
learning to better model the latent relationships among different binding partners.

Figure 1. The overview of GPSite. The protein sequence is input to the pre-trained language model ProtTrans and the folding model ESMFold to generate the sequence embedding and predicted structure, respectively. According to the structure, a protein radius graph is constructed where residues constitute the nodes and adjacent nodes are connected by edges. In addition to the pre-computed residue features of ProtTrans embedding and DSSP structural properties, a comprehensive, end-to-end geometric featurizer is employed to extract the geometric node features including distance, direction and angle, as well as geometric edge features between residues including distance, direction and orientation. Here, the R group denotes the centroid of the heavy sidechain atoms. The resulting geometric-aware attributed graph is input to a shared GNN to perform edge-enhanced message passing for capturing the common binding-relevant characteristics among different molecules. Finally, ten ligand-specific MLPs are adopted to learn the binding patterns of particular molecules in a multi-task manner. Examples of the applications of GPSite include binding site identification and protein-level Gene Ontology (GO) [41] function prediction.

GPSite outperforms state-of-the-art methods

We collected ten binding site benchmark datasets for the ten ligands from Protein Data Bank (PDB) [42] as detailed in Methods and Appendix 2-table 1, which were combined to train and evaluate GPSite using the five-fold cross-validation and independent test sets. As shown in Appendix 2-table 2, GPSite obtains average area under the receiver operating characteristic curve (AUC) values over the ten ligand types of 0.918 and 0.921; as well as average area under the precision-recall curve (AUPR) values of 0.603 and 0.594 on the cross-validation and independent tests, respectively. The consistent performance on the validation and test sets indicates the robustness of our model. In **Figure 2**A, the receiver operating characteristic (ROC) curves and the precision-recall curves on the ten test sets are plotted to overview the performance of GPSite for different ligands.

   To demonstrate the effectiveness of our method, we compared GPSite with 8 sequence-based predictors including DRNApred [12], NCBRPred [43], SVMnuc [44], PepBind [14], PepNN-Seq [45], PepBCL [17], TargetS [15], and LMetalSite [18], as well as 15 structure-based predictors including NucBind [44], COACH-D [46], GraphBind [25], GeoBind [22], aaRNA [47], PepNN-Struct [45], DeepPPISP [48], SPPIDER [49], MaSIF-site [21], GraphPPIS [26], ScanNet [23], PeSTo [24], DELIA [19], MIB [50], and IonCom[51] (see Appendix 1-'Brief introductions to the competitive methods' for more details). For most competitive methods, we used their webservers or standalone programs for evaluation. Note that since our test sets may partly overlap with the training sets of these methods, the results reported here should be the upper limits for the existing methods. Figure 2B and 2C show the results of the top-performing predictors in the test sets, where GPSite surpasses all other sequence-based and even experimental structure-based methods in AUPR for more than 16.5%, 13.2%, 55.4%, 1.7%, 27.7%, 10.8%, 7.0%, 14.8%, 17.1%, and 13.4% in the DNA, RNA, peptide, protein, ATP, HEM, Zn^{2+}, Ca^{2+}, Mg^{2+}, and Mn^{2+} binding site test sets, respectively. The results of more contending methods and criteria (e.g., AUC and F1-score) are tabulated in Appendix 2-table 3. Since 358 of the 375 proteins in our protein-binding site test set share > 30% identity with the training sequences of PeSTo, we re-split our protein-binding dataset to generate a test set of 65 proteins sharing < 30% identity with the training set of PeSTo for a fair evaluation. Using this new dataset while fixing the other nine to re-train our model with the same hyperparameters, GPSite achieves better performance than PeSTo (AUPR of 0.610 against 0.433) for

predicting protein-binding sites while retaining similar performance for the other ligands (Appendix 2-
table 4).

Though trained on predicted protein structures, GPSite can also adopt native structures as input
for prediction whenever applicable. By doing this, extra performance boosts can be gained with
average AUPR increase of 7.8% (Appendix 3-figure 1). However, experimental structures are not
always available in real-world scenarios, such as genome-scale sequence databases. To this end, for the
best structure-based method (measured by AUPR) in each test set, we also investigated the impact on
performance when using ESMFold-predicted structures as input. As expected, the performance of these
methods mostly decreases substantially utilizing predicted structures for testing, because they were
trained with high-quality native structures. For example, the AUPR of GraphBind for predicting RNA-
binding sites decreases from 0.506 to 0.433, compared to the AUPR of 0.573 by GPSite. Similarly, the
AUPR of ScanNet drops from 0.476 to 0.399, compared to the AUPR of 0.484 by GPSite for predicting
protein-binding sites. Therefore, in the practical situations where experimental structures are
unavailable, the superiority of our method will be further reflected.

195
196 **Figure 2.** The performance of GPSite and the state-of-the-art methods. (**A**) The ROC and precision-recall curves
197 of GPSite on the ten binding site test sets. (**B**-**C**) The AUPR values of the top-performing methods in each test set.
198 The methods marked with * denote evaluations using the ESMFold-predicted structures as input.

199
200 **GPSite is robust for low-quality predicted structures**
201 Since GPSite is built on ESMFold, it is necessary to examine the quality of the predicted structures and
202 its impact on the model performance. **Figure 3**B and Appendix 3-figure 2 show the distributions of the
203 TM-scores between native and predicted structures calculated by US-align [52] in the ten benchmark

datasets, where most proteins are accurately predicted with TM-score > 0.7 (see also Appendix 2-table 5). Overall, ESMFold achieves median TM-scores of 0.89, 0.76, 0.93, 0.93, 0.94, 0.94, 0.93, 0.94, 0.95, and 0.96 for the DNA, RNA, peptide, protein, ATP, HEM, Zn^{2+}, Ca^{2+}, Mg^{2+}, and Mn^{2+} datasets, respectively (Appendix 2-table 6). We next explored whether GPSite can maintain its performance on low-quality predicted structures. Figure 3A presents the performance of GPSite on ESMFold-predicted structures with TM-score > 0.7 or ≤ 0.7, and the comparisons with the leading structure-based methods in the test sets of DNA, RNA and peptide. Reasonably, compared to the well-predicted proteins, the performance of GPSite is inferior on the subsets of proteins with TM-score ≤ 0.7. Nevertheless, GPSite continues to outshine the most advanced structure-based methods input with ESMFold-predicted structures or even experimental structures. Similar trends are also observed for the rest of the ligands in Appendix 3-figure 3. Furthermore, we took a closer inspection of the 104 proteins with predicted structures of TM-score < 0.5 in the RNA test set (since this type of proteins is rare in the test sets of other ligands). In this subset, GraphBind achieves AUPR values of 0.455 and 0.376 using native and predicted structures, respectively, compared to the AUPR of 0.516 by GPSite. As shown in Figure 3C with lines fit to the per-protein TM-score and AUPR using linear regression, GPSite consistently outperforms GraphBind using predicted structures despite the prediction quality of ESMFold, and is only surpassed by GraphBind input with native structures on proteins of extremely low quality (TM-score < 0.3). To sum up, ESMFold could produce high-quality structures in most cases, and even for the low-quality predicted structures, GPSite is robust enough to generate reliable predictions better than current state-of-the-art structure-based methods.

We finally illustrate a potential reason for the robustness of GPSite by an example from the test set where GPSite is able to discern among various interfaces even though the structure is not perfectly predicted. Figure 3D shows the structure of the human glucocorticoid receptor (GR), a transcription factor that binds DNA and assembles a coactivator peptide to regulate gene transcription (PDB: 7PRW, chain A). The DNA-binding domain of GR also consists of two C4-type zinc fingers to bind Zn^{2+} ions. Although the structure of this protein is not perfectly predicted (TM-score = 0.72), the binding domains of peptide and DNA are actually predicted accurately as viewed by the superpositions of the native and predicted structures in Figure 3D and 3E. Therefore, GPSite can correctly predict all Zn^{2+} binding sites and precisely identify the binding sites of DNA and peptide with AUPR values of 0.949 and 0.924, respectively (Figure 3F, G and H).

Figure 3. The performance of GPSite on low-quality predicted structures. (**A**) The performance of GPSite on structures of different qualities, and the comparisons with the best structure-based methods in the test sets of DNA, RNA and peptide. The experimental structure-based methods input with ESMFold-predicted structures are marked with *. (**B**) Distributions of the TM-scores between native and predicted structures in the DNA, RNA and peptide datasets. (**C**) The correlations between the prediction quality of ESMFold and the performance of GPSite and GraphBind on the RNA-binding site test set when TM-score < 0.5. The scatters denote the average TM-score and AUPR for each bin after sorting the proteins according to the TM-scores and evenly dividing them into 20 discrete bins. The lines are fit to the original data (without binning) using linear regression. (**D**) The glucocorticoid receptor (GR) in complex with DNA, a coactivator peptide, and Zn^{2+} ions (PDB: 7PRW). The ESMFold-predicted protein structure (gray) is superimposed to the native structure (cyan) using US-align (TM-score = 0.72). The ligands are colored in orange. (**E**) Superposition of the native (cyan) and predicted (gray) DNA-binding domains of GR (TM-score = 0.96). (**F-H**) The Zn^{2+}, DNA and peptide binding site predictions by GPSite for the predicted GR structure in cartoon or surface view. True positives, false positives and false negatives are colored in green, red and yellow, respectively. The ligands in orange were subsequently added based on the native complex structure to show the quality of the predictions by GPSite.

The effects of protein features and model designs

To reveal the roles of distinct protein features and model designs in GPSite, we conducted comprehensive ablation studies. As shown in **Figure 4**A and Appendix 2-table 7, when removing the

ProtTrans embeddings from GPSite, the model yields inadequate performance (average AUPR of 0.516

among the ten test sets) due to the complete neglect of the sequence information in proteins. The

introduction of one-hot sequence encodings or MSA profiles (elaborated in Appendix 1-'Generation of

the evolutionary features from MSA') partially restores the performance to average AUPR of 0.545 or

0.568, respectively. Nevertheless, the utilization of language model representations in GPSite attains

the highest average AUPR of 0.594. To further understand the advantages of ProtTrans over the

evolutionary features from MSA, we compared their performance against the number of effective

homologous sequences (Neff) of the proteins from the combined test set of the ten ligands. Neff is an

HHblits [53] parameter quantifying the effective size of homologous sequence cluster. As evidenced in

Figure 4B, ProtTrans consistently obtains competitive or superior performance compared to the MSA

profiles, particularly for the target proteins with few homologous sequences (Neff < 2). On the other

hand, removing the structure information (implemented by a transformer model solely input with

ProtTrans sequence features) obtains the worst performance with an average AUPR of 0.484 (Figure

4A). This observation indicates that the knowledge of protein structure may be more critical than

sequence information in binding site prediction tasks. Additionally, the removal of the geometric

featurizer within GPSite also causes a substantial decline in performance (average AUPR from 0.594 to

0.533), attesting to the significance of GPSite's perception of protein geometry.

We next elucidate the benefits of the multi-task framework in GPSite by comparing it with a

baseline approach in which a model is trained and evaluated for each dataset separately. As depicted in

Figure 4C and Appendix 2-table 7, GPSite consistently outperforms the single-task baseline, especially

for the ligands with limited training data. For instance, directly fitting a model on the HEM training set

with only 176 proteins reaches an AUPR of 0.716 for the test set. Alternatively, combining datasets of

diverse ligands in a multi-task framework brings an AUPR increase of 0.086 for HEM. This suggests

that multi-task learning can compensate for the scarcity of training data by leveraging a shared network

trained on a larger dataset encompassing different types of ligand-binding proteins that potentially

share similar binding patterns.

Residues that are conserved during evolution, exposed to solvent, or inside a pocket-shaped

domain are inclined to participate in ligand binding. During the multi-task training process, the shared

network in GPSite should have learned to capture such common binding mechanisms. Here we show

how GPSite can be easily extended to the binding site prediction for other unseen ligands by adopting

the pre-trained shared network as a feature extractor. We considered a carbohydrate-binding site dataset

from [54] which contains 100 proteins for training and 49 for testing. We first visualized the distributions

of residues in this dataset using t-SNE [55], where the residues are encoded by raw feature vectors

encompassing ProtTrans embeddings and DSSP structural properties, or latent embedding vectors from

the shared network of GPSite. As shown in Figure 4D, the binding and non-binding residues overlap

and are indistinguishable when encoded by raw feature vectors. On the contrary, the latent

representations from GPSite effectively improve the discriminability between the binding and non-

binding residues. Employing these informative hidden embeddings as input features to train a simple

MLP exhibits remarkable performance with an AUC of 0.881 (Figure 4E), higher than that of training a

single-task version of GPSite from scratch (AUC of 0.853) or other state-of-the-art methods such as

MTDsite [54] and SPRINT-CBH [56]. These results highlight the effectiveness of multi-task learning and

the scalability of GPSite to unseen ligands.

Figure 4. The effects of protein features and model designs. (**A**) Ablation studies on sequence and structure
information in the DNA, RNA and peptide test sets. The average performance of the ten test sets is also shown. (**B**)
Performance comparison between GPSite and the baseline model using MSA profiles for proteins with different
Neff values in the combined test set of the ten ligands. (**C**) Performance boosts in AUPR using GPSite compared to
the single-task baseline. (**D**) Visualization of the distributions of residues encoded by raw feature vectors (left) or
hidden embedding vectors from the pre-trained shared network in GPSite (right) for the unseen carbohydrate-
binding site dataset using t-SNE. The binding and non-binding residues are colored in red and gray, respectively.
(**E**) The performance when using the hidden embeddings from GPSite as input features to train an MLP for
carbohydrate-binding site prediction, and its comparisons with other methods.

Large-scale binding site annotation for Swiss-Prot

In light of the efficiency and effectiveness of GPSite, we sought to annotate and analyze the potential

binding interfaces of various kinds for the entire Swiss-Prot database. For this task, we applied

ESMFold to predict the structures of 568,326 sequences in Swiss-Prot, which required approximately

8.5 days as described in Methods. Typically, it takes 16 seconds to predict the structure of a protein

with 500 residues, or 100 seconds for 1000 residues (Appendix 3-figure 4). The feature extraction and

GPSite inference procedures overall cost about 5 hours. All ESMFold-predicted structures

accompanied by the binding site annotations for Swiss-Prot are freely available in our user-friendly

GPSiteDB database (https://bio-web1.nscc-gz.cn/database/GPSiteDB). Appendix 3-figure 5 further

illustrates the distributions of the protein length and the predicted TM-score (pTM) estimated by

ESMFold for the Swiss-Prot sequences, where most proteins are no longer than 500 residues and

predicted with high confidence (pTM > 0.8). For the subsequent downstream analyses, we only

considered the predicted structures with pTM > 0.7, resulting in a total of 370,140 structures.

Exploiting the residue-level binding site annotations, we could readily extend GPSite to

discriminate between binding and non-binding proteins of various ligands. Specifically, a protein-level

binding score can be generated for each ligand by averaging the top k predicted scores among all

residues. Empirically, we set k to 5 for metal ions and 10 for other ligands, considering that the binding

interfaces of metal ions are usually smaller. As depicted in **Figure 5**A, the GPSite binding scores for

proteins with the corresponding ligand-binding molecular functions are significantly higher than those

without such annotations in Swiss-Prot (P-value < 10^{-165} for all ligands according to Mann–Whitney U

test [57]). The accuracy of the GPSite protein-level binding scores is further validated by the ROC curves

in Figure 5B, where GPSite achieves satisfactory AUC values for all ligands except protein (AUC of

0.608). This may be ascribed to the fact that protein-protein interactions are ubiquitous in living

organisms while the Swiss-Prot function annotations are incomplete. Moreover, we attempted to gather

the top 20,000 proteins with the highest GPSite binding scores for each ligand to expand the binding

function annotations in Swiss-Prot. We could immediately notice that the GPSite-predicted binding

proteins are involved in biological processes consistent with existing knowledge as shown in Figure 5C

and Appendix 3-figure 6. For instance, the DNA-binding proteins predicted by GPSite are prone to

participate in DNA repair, DNA-templated transcription, DNA recombination and replication, while the

RNA-binding proteins are inclined to perform translation and RNA modification.

Capitalizing on the predicted structures and annotations within GPSiteDB, cell biologists are

empowered to easily locate the genetic variants and assess their potential disruptions in protein-ligand

interactions and pathogenicity. This facilitates the establishment of rational working hypotheses to

propel therapeutic development in a more informed manner. Here we conduct analyses on the

associations between binding sites and genetic variants for the human proteome as an example.

Notably, 20.67% of the pathogenic variant sites on the surfaces of the predicted structures fall in the

GPSite-predicted interfaces, higher than the benign variants (11.97%) or the random baseline (16.35%)

as described in Figure 5D. Consistent trend is observed in Appendix 3-figure 7 when considering

variants in the entire structure (rather than solely on surface). Besides, we investigated the pathogenic

probabilities of variants in different locations in Figure 5E. As expected, the pathogenicity of variants

located in the predicted binding sites is higher than those in the non-binding sites. Interestingly, our

analysis uncovered that the pathogenic probabilities of variants in the predicted binding sites of ATP

and metal ions surpass those of other ligands. One possible reason is that the binding interfaces of ATP

and metal ions typically comprise small pockets formed by a limited number of residues. Consequently,

variants affecting even a single residue within such pockets may exert a substantial influence on the

overall pocket functionality and lead to diseases.

Figure 5. Analyses of Swiss-Prot based on the binding site annotations by GPSite. (**A**) The distributions of the binding scores assigned by GPSite for proteins with or without certain ligand-binding molecular function in GO. (**B**) The ROC curves when using the GPSite binding scores to distinguish between binding and non-binding proteins of various ligands. (**C**) The percentage of proteins predicted as binding to DNA and RNA by GPSite to be annotated with certain biological process in Swiss-Prot. Only the specific biological process terms with depth ≥ 8 in the GO directed acyclic graph are considered, among which the top 15 terms with the highest percentages are displayed. (**D**) The percentage of surface pathogenic or benign natural variant sites within GPSite-predicted interfaces. The baseline is the probability of a random surface residue being annotated as an interface residue. (**E**) The pathogenic probabilities of variants located in non-binding sites or different types of binding sites predicted by GPSite.

Discussion

In this study, we present GPSite to accurately and efficiently predict protein binding sites of diverse biologically relevant molecules including DNA, RNA, peptide, protein, ATP, HEM, and metal ions. By leveraging the informative sequence embeddings and predicted structures from pre-trained language models, GPSite is liberated from the reliance on MSA or experimental protein structures. To encapsulate the high-level bio-physicochemical characteristics in the predicted structures, GPSite incorporates a comprehensive geometric featurizer and an edge-enhanced graph neural network to refine both residual and relational geometric contexts in an end-to-end manner. GPSite also stands out from the previous approaches by applying a multi-task framework to effectively model the intrinsic

relationships among different binding partners. Results across various benchmark datasets indicate that GPSite substantially outperforms state-of-the-art sequence-based and structure-based methods, even under conditions where the predicted structures are of lower quality. Finally, we demonstrate GPSite's scalability to genome-scale sequence databases by annotating binding sites for over 568,000 sequences in Swiss-Prot within 9 days. Further analyses suggest that these annotations are not only accordant with existing knowledge but also capable of facilitating discoveries of unexplored biology in protein function and genetic variant.

Despite the noteworthy advancements achieved by GPSite, there remains scope for further improvements. Given that the ESM Metagenomic Atlas [34] provides 772 million predicted protein structures along with pre-computed language model embeddings, self-supervised learning can be employed to train a GPSite model for predicting masked sequence and structure attributes, or maximizing the similarity between the learned representations of substructures from identical proteins while minimizing the similarity between those from different proteins using a contrastive loss function [36]. Fine-tuning this pre-trained model on binding site datasets may realize better performance than training from scratch. Additional opportunities for upgrade exist within the network architecture. For example, a variational Expectation-Maximization (EM) framework [58] can be adopted to handle the hierarchical graph structure inherent in proteins, which contains the top view of the residue graph and the bottom view of the atom graph inside a residue. Such EM procedure enables training two separate graph neural networks for the two views while simultaneously allowing interaction and mutual enhancement between the two modules. Meta-learning [59] could also be explored in this multi-task scenario, which allows fast adaptation to unseen tasks with limited labels.

As the gap between unannotated and annotated sequences is expanding at an unparalleled rate, GPSite serves as a reliable, efficient, versatile and user-friendly tool for unraveling the extensive and dynamic landscape of protein-ligand interactions. By harnessing the capabilities of GPSite, researchers can readily uncover fresh biological functions of proteins, gain valuable insights into the underlying pathogenic mechanisms of gene mutations, or design novel drugs targeting specific binding pockets.

Methods

Benchmark datasets

The benchmark datasets for evaluating binding site predictions of DNA, RNA, peptide, ATP, and HEM are constructed from BioLiP [60], a database of biologically relevant protein-ligand complexes primarily from PDB. For each ligand, we collected the corresponding binding proteins with resolutions of ≤ 3.0 Å and lengths of 50–1500 from BioLiP released on 29 March 2023. A binding residue is defined if the smallest atomic distance between the target residue and the ligand is <0.5 Å plus the sum of the Van der Waal's radius of the two nearest atoms. We combined the binding site annotations of identical sequences and then removed redundant proteins sharing sequence identity > 25% over 30% alignment coverage using CD-HIT [61]. Finally, each benchmark dataset was split into a training set with proteins released before 1 January 2021, as well as an independent test set with proteins released from 1 January 2021 to 29 March 2023. Besides, the benchmark dataset of protein-protein binding sites is directly from [26], which contains non-redundant transient heterodimeric protein complexes dated up to May 2021. The

benchmark datasets of metal ion (Zn^{2+}, Ca^{2+}, Mg^{2+} and Mn^{2+}) binding sites are directly from [18], which contain non-redundant proteins dated up to December 2021. Combining all these ten datasets results in a total of 8441 training sequences and 1838 test sequences. Details of the statistics of these benchmark datasets are given in Appendix 2-table 1.

Structure prediction and preprocessing

We harnessed ESMFold, a fast and accurate end-to-end model to predict protein structures from sequences. ESMFold is based on a language model with 3B parameters pre-trained over sequences in UniRef50 [62], and a folding head similar to AlphaFold2 trained on experimental structures from PDB and predicted structures from AlphaFold2. The structure prediction for our whole benchmark datasets (~10,200 sequences, ~300 amino acids on average) cost only ~28 h on an NVIDIA A100 GPU. For each residue in the predicted structures, we gathered the coordinates of the N, C_α, C and O atoms as well as the centroid of the heavy sidechain atoms (denoted as R). In this way, the structure of a protein can be represented by a coordinate matrix $X \in \mathbb{R}^{n \times 5 \times 3}$, with n denoting the number of residues.

Protein features

GPSite leverages the pre-trained protein language model ProtTrans (version: ProtT5-XL-U50) to generate sequence features efficiently, thus bypassing slow sequence alignments. ProtTrans is a transformer-based auto-encoder named T5 [63] pre-trained with the BERT's denoising objective [64], essentially learning to predict the masked amino acids. Concretely, ProtTrans contains 3B parameters, which was first trained on BFD [65] and then fine-tuned on UniRef50. We extracted the output from the last ProtTrans encoder layer as sequence representations, containing a 1024-dimensional vector for each residue. The inference cost of ProtTrans is extremely low, and the embedding extraction process for our whole benchmark datasets can be done within 5 min on an NVIDIA A100 GPU. The feature values in the sequence embeddings are further normalized to scores between 0 and 1 as follows:

$$v_{norm} = \frac{v - v_{min}}{v_{max} - v_{min}} \#(1)$$

where v is the original feature value, and v_{min} and v_{max} are the minimum and maximum values of this feature type observed in the training set, respectively. In addition, we also calculated two structural properties from the predicted structures using DSSP: (i) Relative solvent accessibility (RSA), which is the normalized solvent accessible surface area (ASA) by the maximum ASA of the corresponding amino acid type. (ii) One-hot secondary structure profile representing one of the eight secondary structure states.

The architecture of GPSite

The overall architecture of GPSite is shown in Figure 1. First, the protein sequence is input to the pre-trained language model ProtTrans and the folding model ESMFold to generate the sequence embedding and predicted structure, respectively. Second, a protein radius graph is constructed from the structure, where residues constitute the nodes and adjacent nodes (distance between C_α <15Å) are connected by edges. In addition to the pre-computed residue features (ProtTrans embedding and structural properties by DSSP), a comprehensive, end-to-end geometric featurizer is employed to extract the geometric node

features including distance, direction and angle, as well as geometric edge features between residues including distance, direction and orientation. Third, the resulting geometric-aware attributed graph is input to a shared GNN with message passing, edge update and global node update, to capture the common binding-relevant characteristics among different molecules. Finally, ten ligand-specific MLPs are adopted to learn the binding patterns of particular molecules in a multi-task manner.

The geometric featurizer

GPSite represents the protein as a radius graph derived from the C_α coordinates of the residues, where the radius is equal to 15Å. An end-to-end featurizer is utilized to act directly on the atomic coordinate matrix X for geometric feature extraction similar to [38], except that we additionally encode the sidechain conformations of the residues. In this representation, a local coordinate system is first defined at each residue based on the relative position of the C_α atom to other backbone atoms. Then, several geometric node and edge features are derived to capture the arrangements of backbone and sidechain atoms in or between residues.

(i) Local coordinate system. We define a local coordinate system $\boldsymbol{Q}_i = [\boldsymbol{b}_i, \boldsymbol{n}_i, \boldsymbol{b}_i \times \boldsymbol{n}_i]$ for residue i, where $\boldsymbol{b}_i$ is the negative bisector of the angle formed by the N, C_α, and C atoms, and $\boldsymbol{n}_i$ is a unit vector normal to this plane. Formally, we have:

$$\boldsymbol{u}_i = C_{\alpha_i} - N_i, \quad \boldsymbol{v}_i = C_i - C_{\alpha_i}, \quad \boldsymbol{b}_i = \frac{\boldsymbol{u}_i - \boldsymbol{v}_i}{\|\boldsymbol{u}_i - \boldsymbol{v}_i\|}, \quad \boldsymbol{n}_i = \frac{\boldsymbol{u}_i \times \boldsymbol{v}_i}{\|\boldsymbol{u}_i \times \boldsymbol{v}_i\|} \#(2)$$

Based on the local coordinate systems, we could construct geometric features that are invariant to rotation and translation for single or pair of residues.

(ii) Geometric node features. GPSite constructs distance, direction and angle features for each residue. Given the coordinates of two atoms A and B, the distance feature is computed via $\text{RBF}(\|A - B\|)$, where $\text{RBF}(\cdot)$ is a radial basis function. For the intra-residue distance features of node i, $A, B \in \{N_i, C_{\alpha_i}, C_i, O_i, R_i\}$ and $A \neq B$. Here, R denotes the centroid of the heavy sidechain atoms. The direction features encoding relative directions of other inner atoms to C_α in residue i are computed via $\boldsymbol{Q}_i^T \frac{A - C_{\alpha_i}}{\|A - C_{\alpha_i}\|}$, where $A \in \{N_i, C_i, O_i, R_i\}$. As shown in Figure 1, we also incorporate the sine and cosine values of the bond angles $(\alpha_i, \beta_i, \gamma_i)$ and torsion angles $(\phi_i, \psi_i, \omega_i)$ to consider the backbone geometry.

(iii) Geometric edge features. Similarly, we construct geometric features between neighboring residues including distance, direction and orientation. The inter-residue distance features $\text{RBF}(\|A - B\|)$ between nodes i and j are computed with atoms $A \in \{N_i, C_{\alpha_i}, C_i, O_i, R_i\}$ and $B \in \{N_j, C_{\alpha_j}, C_j, O_j, R_j\}$. The edge direction features $\boldsymbol{Q}_i^T \frac{A - C_{\alpha_i}}{\|A - C_{\alpha_i}\|}$ consider relative directions of all atoms in residue j to C_{α_i}, namely $A \in \{N_j, C_{\alpha_j}, C_j, O_j, R_j\}$. To reflect the relative spatial rotation between the two reference frames of residue i and j, the orientation feature $\text{q}(\boldsymbol{Q}_i^T \boldsymbol{Q}_j)$ is employed, where $\text{q}(\cdot)$ is the quaternion encoding function representing 3D rotation matrices as four-element vectors [66].

The edge-enhanced graph neural network

The above-mentioned attributed graph with features from ProtTrans, DSSP and the geometric featurizer is input to several GNN layers with message passing, edge update and global node update modules, to learn the residue representations by considering multi-scale interactions in node, edge, and global context levels.

(i) Message passing with graph transformer. Since transformer is well-acknowledged as the most powerful network in modeling sequence and graph data [18,40,67], we adopt its multi-head attention mechanism while taking the edge features into account for message passing in graphs. Formally, we denote the hidden feature vectors of node i and edge $j \rightarrow i$ in layer l as h_i^l and e_{ji}^l, respectively. Before the first GNN layer, we apply an MLP to project the initial node and edge features to the d-dimensional space. To update node i, the message passing in layer l is performed as follows:

$$\hat{h}_i^{l+1} = h_i^l + \sum_{j \in N(i) \cup i} \alpha_{ji}^l \left(W_V^l h_j^l + W_E^l e_{ji}^l \right) \#(3)$$

where the attention coefficient α_{ji}^l from node j to i is calculated by:

$$\begin{cases} w_{ji}^l = \dfrac{\left(W_Q^l h_i^l \right)^T \left(W_K^l h_j^l + W_E^l e_{ji}^l \right)}{\sqrt{d}} \\ \alpha_{ji}^l = \dfrac{\exp w_{ji}^l}{\sum_{k \in N(i) \cup i} \exp w_{ki}^l} \end{cases} \#(4)$$

The learnable weight matrices W_Q^l, W_K^l and W_V^l are used to project the node feature vectors into the corresponding query, key and value representations. W_E^l is used to transform the edge features which will be subsequently added to the key and value representations. $N(i)$ denotes the neighbors of node i. In practice, we use multi-head attention to linearly project the queries, keys and values multiple times, perform the attention function in parallel and finally concatenate them together.

(ii) Edge update. To improve the model's capability, we update the features of an edge using its connecting nodes:

$$e_{ji}^{l+1} = e_{ji}^l + \text{EdgeMLP}\left(\hat{h}_j^{l+1} \parallel e_{ji}^l \parallel \hat{h}_i^{l+1} \right) \#(5)$$

where $\parallel$ denotes the vector concatenation and EdgeMLP is an MLP for edge update.

(iii) Node update with global context attention. While the local node and edge interactions play crucial roles in learning residue representations, the global information is also valuable for improving accuracy. However, global self-attention across the whole protein is computationally intensive. Alternatively, here we learn a global context vector for each protein and use it to apply gated attention for the node representations similar to [38]:

$$c^l = \frac{\sum_{k=0}^{n-1} \hat{h}_k^{l+1}}{n} \#(6)$$

$$h_i^{l+1} = \hat{h}_i^{l+1} \odot \sigma\left(\text{GateMLP}(c^l) \right) \#(7)$$

where n is the number of residues in a protein, GateMLP is an MLP for gated attention, $\sigma(\cdot)$ is the

sigmoid function, and ⊙ denotes the element-wise product operation.

Multi-task learning

To better capture the intrinsic similarities of binding patterns among different ligands and enable

efficient predictions in a concurrent fashion, GPSite employs a multi-task framework, where the shared

edge-enhanced GNN is used to model the common binding-relevant characteristics, followed by ten

ligand-specific MLPs to mine the binding patterns of particular molecules. In the training steps,

different types of ligand-binding proteins are input to the same network, and predictions for the ten

types of ligands are yielded. Nonetheless, only predictions with the corresponding known ligand-

binding sites are used to calculate loss and perform backpropagation, while the predictions of other

ligands without ground truth data are masked. That is, each protein is used to train the shared GNN and

the corresponding ligand-specific MLP(s) of its known binding partner(s) without affecting other

irrelevant MLP(s).

Implementation and evaluation

We performed five-fold cross-validation on the training data, where the ten training sets were mixed

and split into five folds randomly, and then each time a model was trained on four folds and evaluated

on the remaining fold. This process was repeated for five times and the average validation performance

was used to optimize the hyperparameters of the network. In the test phase, all five trained models from

cross-validation were used to make predictions, which were averaged as the final prediction of GPSite.

Specifically, we adopted Pytorch 1.13.1 [68] to implement GPSite, which contains a 4-layer shared GNN

with 128 hidden units and 4 attention heads. The Adam optimizer [69] with the one-cycle learning rate

policy [70] was used for model optimization on the binary cross entropy loss. Within each epoch, we

randomly drew 25,000 samples from the training data with replacement to train our model using a

batch size of 16. The training process lasted at most 25 epochs and we performed early stopping based

on the validation performance, which took ~1.5 h on an NVIDIA A100 GPU.

Similar to the previous works, we use recall, precision, accuracy, F1-score, Matthews correlation

coefficient (MCC), AUC, and AUPR to evaluate the predictive performance, whose detailed

definitions are given in Appendix 1-'Evaluation metrics'. AUC and AUPR are independent of

thresholds, thus reflecting the overall performance of a model. The other metrics are calculated by

converting the predicted binding probabilities to binary predictions with a threshold for each ligand,

which is determined by maximizing MCC on the validation sets. We adopted AUPR for

hyperparameter selections as it is more sensitive and informative than AUC in imbalanced two-class

classification tasks [71].

High-throughput annotation and analysis on Swiss-Prot

We downloaded all the available 569,516 sequences in Swiss-Prot (release: 2023-05-03) and then

removed sequences longer than 2700 residues (0.21%) due to the memory limit of GPUs, resulting in a

total of 568,326 sequences. Non-standard amino acids in these sequences were also removed. ESMFold

was applied to predict the structures from sequences on 16 NVIDIA A100 (80 GB) GPUs, which cost

~8.5 days. The structure preprocessing and feature extraction (by ProtTrans and DSSP) procedures overall cost ~4 h on the same GPU cluster, and the inference of binding sites using GPSite took ~1 h.

For the downstream analyses of protein function and variant, we only considered the predicted protein structures with length $\geq$ 50 and pTM > 0.7 evaluated by ESMFold, consisting of 370,140 structures eventually. Interface residues are defined as residues with predicted binding probabilities higher than the pre-defined thresholds described in implementation and evaluation. Surface residues on the predicted structures are defined as the residues with RSA > 5% [72] computed by DSSP. The annotated GO terms of molecular function and biological process for all sequences were downloaded from UniProt [7], and we up-propagated the annotations using all types of relationships defined in the hierarchical structure of GO (release: 2023-05-10). The binding proteins of a specific ligand were determined as those annotated with the corresponding ligand-binding molecular function, and the non-binding proteins were randomly sampled to the same number as binding proteins. Concretely, we collected 21680, 42074, 1240, 24108, 74428, 4960, 15030, 2088, 24161, and 4093 binding proteins from Swiss-Prot for DNA, RNA, peptide, protein, ATP, HEM, Zn^{2+}, Ca^{2+}, Mg^{2+}, and Mn^{2+} respectively. The pathogenicity annotations of human protein altering variants were downloaded from UniProt (release: 2023_02), which contain UniProt manually reviewed natural variants, as well as variants imported from other public resources such as Ensembl Variation [73] and ClinVar [74], and the conflicting annotations were removed.

Acknowledgements

This work was supported by the National Key R&D Program of China (2022YFF1203100), National Natural Science Foundation of China (12126610), Guangdong Key Field R&D Plan (2019B020228001 and 2018B010109006), and Guangzhou S&T Research Plan (202007030010 and 202002020047).

Competing interests

The authors declare that no competing interests exist.

Data availability

The binding site benchmark datasets, source code and trained models of GPSite are available at https://github.com/biomed-AI/GPSite. The user-friendly GPSite webserver is freely available at https://bio-web1.nscc-gz.cn/app/GPSite. All predicted structures along with the binding site annotations for the Swiss-Prot sequences are available in our GPSiteDB database at https://bio-web1.nscc-gz.cn/database/GPSiteDB.

References

1. Alipanahi, B., Delong, A., Weirauch, M.T., and Frey, B.J. (2015). Predicting the sequence specificities of DNA-and RNA-binding proteins by deep learning. Nature biotechnology *33*, 831-838.
2. Rolland, T., Taşan, M., Charloteaux, B., Pevzner, S.J., Zhong, Q., Sahni, N., Yi, S., Lemmens, I., Fontanillo, C., and Mosca, R. (2014). A proteome-scale map of the human interactome

network. Cell *159*, 1212-1226.

3.   Andreini, C., Bertini, I., and Rosato, A. (2009). Metalloproteomes: a bioinformatic approach.
Accounts of chemical research *42*, 1471-1479.

4.   Lee, D., Redfern, O., and Orengo, C. (2007). Predicting protein function from sequence and
structure. Nature reviews molecular cell biology *8*, 995-1005.

5.   Wang, S., Liang, K., Hu, Q., Li, P., Song, J., Yang, Y., Yao, J., Mangala, L.S., Li, C., and Yang,
W. (2017). JAK2-binding long noncoding RNA promotes breast cancer brain metastasis. The
Journal of clinical investigation *127*, 4498-4515.

6.   Wells, J.A., and McClendon, C.L. (2007). Reaching for high-hanging fruit in drug discovery
at protein–protein interfaces. Nature *450*, 1001-1009.

7.   The UniProt Consortium (2023). UniProt: the universal protein knowledgebase in 2023.
Nucleic Acids Research *51*, D523-D531.

8.   Sayers, E.W., Bolton, E.E., Brister, J.R., Canese, K., Chan, J., Comeau, D.C., Farrell, C.M.,
Feldgarden, M., Fine, A.M., and Funk, K. (2023). Database resources of the National Center
for Biotechnology Information in 2023. Nucleic acids research *51*, D29-D38.

9.   Zhang, Q.C., Petrey, D., Norel, R., and Honig, B.H. (2010). Protein interface conservation
across structure space. Proceedings of the National Academy of Sciences *107*, 10896-10901.

10.   Yang, J., Roy, A., and Zhang, Y. (2013). Protein–ligand binding site recognition using
complementary binding-specific substructure comparison and sequence profile alignment.
Bioinformatics *29*, 2588-2595.

11.   Esmaielbeiki, R., Krawczyk, K., Knapp, B., Nebel, J.-C., and Deane, C.M. (2016). Progress
and challenges in predicting protein interfaces. Briefings in bioinformatics *17*, 117-131.

12.   Yan, J., and Kurgan, L. (2017). DRNApred, fast sequence-based method that accurately
predicts and discriminates DNA-and RNA-binding residues. Nucleic acids research *45*, e84-
e84.

13.   Taherzadeh, G., Yang, Y., Zhang, T., Liew, A.W.C., and Zhou, Y. (2016). Sequence-based
prediction of protein–peptide binding sites using support vector machine. Journal of
computational chemistry *37*, 1223-1229.

14.   Zhao, Z., Peng, Z., and Yang, J. (2018). Improving sequence-based prediction of protein–
peptide binding residues by introducing intrinsic disorder and a consensus method. Journal of
Chemical Information and Modeling *58*, 1459-1468.

15.   Yu, D.-J., Hu, J., Yang, J., Shen, H.-B., Tang, J., and Yang, J.-Y. (2013). Designing template-
free predictor for targeting protein-ligand binding sites with classifier ensemble and spatial
clustering. IEEE/ACM transactions on computational biology and bioinformatics *10*, 994-
1008.

16.   Vaswani, A., Shazeer, N., Parmar, N., Uszkoreit, J., Jones, L., Gomez, A.N., Kaiser, Ł., and
Polosukhin, I. (2017). Attention is all you need. Advances in neural information processing
systems *30*.

17.   Wang, R., Jin, J., Zou, Q., Nakai, K., and Wei, L. (2022). Predicting protein–peptide binding
residues via interpretable deep learning. Bioinformatics *38*, 3351-3360.

18.   Yuan, Q., Chen, S., Wang, Y., Zhao, H., and Yang, Y. (2022). Alignment-free metal ion-
binding site prediction from protein sequence through pretrained language model and multi-
task learning. Briefings in Bioinformatics *23*, bbac444.

19.   Xia, C.-Q., Pan, X., and Shen, H.-B. (2020). Protein–ligand binding residue prediction

enhancement through hybrid deep heterogeneous learning of sequence and structure data.

Bioinformatics *36*, 3018-3027.

20.   Jiménez, J., Doerr, S., Martínez-Rosell, G., Rose, A.S., and De Fabritiis, G. (2017). DeepSite:

protein-binding site predictor using 3D-convolutional neural networks. Bioinformatics *33*,

3036-3042.

21.   Gainza, P., Sverrisson, F., Monti, F., Rodola, E., Boscaini, D., Bronstein, M., and Correia, B.

(2020). Deciphering interaction fingerprints from protein molecular surfaces using geometric

deep learning. Nature Methods *17*, 184-192.

22.   Li, P., and Liu, Z.-P. (2023). GeoBind: segmentation of nucleic acid binding interface on

protein surface with geometric deep learning. Nucleic Acids Research *51*, e60-e60.

23.   Tubiana, J., Schneidman-Duhovny, D., and Wolfson, H.J. (2022). ScanNet: an interpretable

geometric deep learning model for structure-based protein binding site prediction. Nature

Methods *19*, 730-739.

24.   Krapp, L.F., Abriata, L.A., Cortés Rodriguez, F., and Dal Peraro, M. (2023). PeSTo:

parameter-free geometric deep learning for accurate prediction of protein binding interfaces.

Nature Communications *14*, 2175.

25.   Xia, Y., Xia, C.-Q., Pan, X., and Shen, H.-B. (2021). GraphBind: protein structural context

embedded rules learned by hierarchical graph neural networks for recognizing nucleic-acid-

binding residues. Nucleic acids research *49*, e51-e51.

26.   Yuan, Q., Chen, J., Zhao, H., Zhou, Y., and Yang, Y. (2022). Structure-aware protein–protein

interaction site prediction using deep graph convolutional network. Bioinformatics *38*, 125-

132.

27.   Yuan, Q., Chen, S., Rao, J., Zheng, S., Zhao, H., and Yang, Y. (2022). AlphaFold2-aware

protein–DNA binding site prediction using graph transformer. Briefings in Bioinformatics *23*,

bbab564.

28.   Jumper, J., Evans, R., Pritzel, A., Green, T., Figurnov, M., Ronneberger, O., Tunyasuvunakool,

K., Bates, R., Žídek, A., and Potapenko, A. (2021). Highly accurate protein structure

prediction with AlphaFold. Nature *596*, 583-589.

29.   Tunyasuvunakool, K., Adler, J., Wu, Z., Green, T., Zielinski, M., Žídek, A., Bridgland, A.,

Cowie, A., Meyer, C., and Laydon, A. (2021). Highly accurate protein structure prediction for

the human proteome. Nature *596*, 590-596.

30.   Rives, A., Meier, J., Sercu, T., Goyal, S., Lin, Z., Liu, J., Guo, D., Ott, M., Zitnick, C.L., and

Ma, J. (2021). Biological structure and function emerge from scaling unsupervised learning to

250 million protein sequences. Proceedings of the National Academy of Sciences *118*,

e2016239118.

31.   Elnaggar, A., Heinzinger, M., Dallago, C., Rehawi, G., Wang, Y., Jones, L., Gibbs, T., Feher,

T., Angerer, C., Steinegger, M., et al. (2022). ProtTrans: Toward Understanding the Language

of Life Through Self-Supervised Learning. IEEE Transactions on Pattern Analysis and

Machine Intelligence *44*, 7112-7127.

32.   Unsal, S., Atas, H., Albayrak, M., Turhan, K., Acar, A.C., and Doğan, T. (2022). Learning

functional properties of proteins with language models. Nature Machine Intelligence *4*, 227-

245.

33.   Yuan, Q., Xie, J., Xie, J., Zhao, H., and Yang, Y. (2023). Fast and accurate protein function

prediction from sequence through pretrained language model and homology-based label

diffusion. Briefings in Bioinformatics *24*, bbad117.

34.   Lin, Z., Akin, H., Rao, R., Hie, B., Zhu, Z., Lu, W., Smetanin, N., Verkuil, R., Kabeli, O., and
Shmueli, Y. (2023). Evolutionary-scale prediction of atomic-level protein structure with a
language model. Science *379*, 1123-1130.

35.   Stärk, H., Ganea, O., Pattanaik, L., Barzilay, R., and Jaakkola, T. (2022). Equibind: Geometric
deep learning for drug binding structure prediction. (PMLR), pp. 20503-20521.

36.   Zhang, Z., Xu, M., Jamasb, A., Chenthamarakshan, V., Lozano, A., Das, P., and Tang, J.
(2022). Protein representation learning by geometric structure pretraining. arXiv preprint
arXiv:2203.06125.

37.   Dauparas, J., Anishchenko, I., Bennett, N., Bai, H., Ragotte, R.J., Milles, L.F., Wicky, B.I.,
Courbet, A., de Haas, R.J., and Bethel, N. (2022). Robust deep learning–based protein
sequence design using ProteinMPNN. Science *378*, 49-56.

38.   Gao, Z., Tan, C., and Li, S.Z. (2022). PiFold: Toward effective and efficient protein inverse
folding. arXiv preprint arXiv:2209.12643.

39.   Kabsch, W., and Sander, C. (1983). Dictionary of protein secondary structure: pattern
recognition of hydrogen-bonded and geometrical features. Biopolymers: Original Research on
Biomolecules *22*, 2577-2637.

40.   Ingraham, J., Garg, V., Barzilay, R., and Jaakkola, T. (2019). Generative models for graph-
based protein design. Advances in neural information processing systems *32*.

41.   Ashburner, M., Ball, C.A., Blake, J.A., Botstein, D., Butler, H., Cherry, J.M., Davis, A.P.,
Dolinski, K., Dwight, S.S., and Eppig, J.T. (2000). Gene ontology: tool for the unification of
biology. Nature genetics *25*, 25-29.

42.   Berman, H.M., Westbrook, J., Feng, Z., Gilliland, G., Bhat, T.N., Weissig, H., Shindyalov,
I.N., and Bourne, P.E. (2000). The protein data bank. Nucleic acids research *28*, 235-242.

43.   Zhang, J., Chen, Q., and Liu, B. (2021). NCBRPred: predicting nucleic acid binding residues
in proteins based on multilabel learning. Briefings in bioinformatics *22*, bbaa397.

44.   Su, H., Liu, M., Sun, S., Peng, Z., and Yang, J. (2019). Improving the prediction of protein–
nucleic acids binding residues via multiple sequence profiles and the consensus of
complementary methods. Bioinformatics *35*, 930-936.

45.   Abdin, O., Nim, S., Wen, H., and Kim, P.M. (2022). PepNN: a deep attention model for the
identification of peptide binding sites. Communications biology *5*, 503.

46.   Wu, Q., Peng, Z., Zhang, Y., and Yang, J. (2018). COACH-D: improved protein–ligand
binding sites prediction with refined ligand-binding poses through molecular docking. Nucleic
acids research *46*, W438-W442.

47.   Li, S., Yamashita, K., Amada, K.M., and Standley, D.M. (2014). Quantifying sequence and
structural features of protein–RNA interactions. Nucleic acids research *42*, 10086-10098.

48.   Zeng, M., Zhang, F., Wu, F.-X., Li, Y., Wang, J., and Li, M. (2020). Protein–protein interaction
site prediction through combining local and global features with deep neural networks.
Bioinformatics *36*, 1114-1120.

49.   Porollo, A., and Meller, J. (2007). Prediction-based fingerprints of protein–protein
interactions. Proteins: Structure, Function, and Bioinformatics *66*, 630-645.

50.   Lin, Y.-F., Cheng, C.-W., Shih, C.-S., Hwang, J.-K., Yu, C.-S., and Lu, C.-H. (2016). MIB:
metal ion-binding site prediction and docking server. Journal of chemical information and
modeling *56*, 2287-2291.

51.   Hu, X., Dong, Q., Yang, J., and Zhang, Y. (2016). Recognizing metal and acid radical ion-
732   binding sites by integrating ab initio modeling with template-based transferals. Bioinformatics
733   *32*, 3260-3269.

734   52.   Zhang, C., Shine, M., Pyle, A.M., and Zhang, Y. (2022). US-align: universal structure
735   alignments of proteins, nucleic acids, and macromolecular complexes. Nature methods *19*,
736   1109-1115.

737   53.   Remmert, M., Biegert, A., Hauser, A., and Söding, J. (2012). HHblits: lightning-fast iterative
738   protein sequence searching by HMM-HMM alignment. Nature methods *9*, 173-175.

739   54.   Sun, Z., Zheng, S., Zhao, H., Niu, Z., Lu, Y., Pan, Y., and Yang, Y. (2021). To improve
740   prediction of binding residues with DNA, RNA, carbohydrate, and peptide via multi-task deep
741   neural networks. IEEE/ACM transactions on computational biology and bioinformatics *19*,
742   3735-3743.

743   55.   Van der Maaten, L., and Hinton, G. (2008). Visualizing data using t-SNE. Journal of machine
744   learning research *9*, 2579-2605.

745   56.   Taherzadeh, G., Zhou, Y., Liew, A.W.-C., and Yang, Y. (2016). Sequence-based prediction of
746   protein–carbohydrate binding sites using support vector machines. Journal of chemical
747   information and modeling *56*, 2115-2122.

748   57.   Mann, H.B., and Whitney, D.R. (1947). On a test of whether one of two random variables is
749   stochastically larger than the other. The annals of mathematical statistics, 50-60.

750   58.   Zhao, J., Qu, M., Li, C., Yan, H., Liu, Q., Li, R., Xie, X., and Tang, J. (2022). Learning on
751   large-scale text-attributed graphs via variational inference. arXiv preprint arXiv:2210.14709.

752   59.   Finn, C., Abbeel, P., and Levine, S. (2017). Model-agnostic meta-learning for fast adaptation
753   of deep networks. (PMLR), pp. 1126-1135.

754   60.   Zhang, C., Zhang, X., Freddolino, P.L., and Zhang, Y. (2023). BioLiP2: an updated structure
755   database for biologically relevant ligand–protein interactions. Nucleic Acids Research,
756   gkad630.

757   61.   Fu, L., Niu, B., Zhu, Z., Wu, S., and Li, W. (2012). CD-HIT: accelerated for clustering the
758   next-generation sequencing data. Bioinformatics *28*, 3150-3152.

759   62.   Suzek, B.E., Huang, H., McGarvey, P., Mazumder, R., and Wu, C.H. (2007). UniRef:
760   comprehensive and non-redundant UniProt reference clusters. Bioinformatics *23*, 1282-1288.

761   63.   Raffel, C., Shazeer, N., Roberts, A., Lee, K., Narang, S., Matena, M., Zhou, Y., Li, W., and
762   Liu, P.J. (2020). Exploring the limits of transfer learning with a unified text-to-text
763   transformer. The Journal of Machine Learning Research *21*, 5485-5551.

764   64.   Kenton, J.D.M.-W.C., and Toutanova, L.K. (2019). BERT: Pre-training of Deep Bidirectional
765   Transformers for Language Understanding. pp. 4171-4186.

766   65.   Steinegger, M., Mirdita, M., and Söding, J. (2019). Protein-level assembly increases protein
767   sequence recovery from metagenomic samples manyfold. Nature methods *16*, 603-606.

768   66.   Huynh, D.Q. (2009). Metrics for 3D rotations: Comparison and analysis. Journal of
769   Mathematical Imaging and Vision *35*, 155-164.

770   67.   Zheng, S., Rao, J., Zhang, Z., Xu, J., and Yang, Y. (2019). Predicting retrosynthetic reactions
771   using self-corrected transformer neural networks. Journal of chemical information and
772   modeling *60*, 47-55.

773   68.   Paszke, A., Gross, S., Massa, F., Lerer, A., Bradbury, J., Chanan, G., Killeen, T., Lin, Z.,
774   Gimelshein, N., and Antiga, L. (2019). Pytorch: An imperative style, high-performance deep

learning library. Advances in neural information processing systems *32*.

69.   Kingma, D.P., and Ba, J. (2014). Adam: A method for stochastic optimization. arXiv preprint

arXiv:1412.6980.

70.   Smith, L.N., and Topin, N. (2019). Super-convergence: Very fast training of neural networks

using large learning rates. (SPIE), pp. 369-386.

71.   Saito, T., and Rehmsmeier, M. (2015). The precision-recall plot is more informative than the

ROC plot when evaluating binary classifiers on imbalanced datasets. PloS one *10*, e0118432.

72.   Jones, S., and Thornton, J.M. (1997). Analysis of protein-protein interaction sites using

surface patches. Journal of molecular biology *272*, 121-132.

73.   Martin, F.J., Amode, M.R., Aneja, A., Austine-Orimoloye, O., Azov, A.G., Barnes, I., Becker,

A., Bennett, R., Berry, A., and Bhai, J. (2023). Ensembl 2023. Nucleic acids research *51*,

D933-D941.

74.   Landrum, M.J., Lee, J.M., Benson, M., Brown, G.R., Chao, C., Chitipiralla, S., Gu, B., Hart,

J., Hoffman, D., and Jang, W. (2018). ClinVar: improving access to variant interpretations and

supporting evidence. Nucleic acids research *46*, D1062-D1067.

75.   Yang, J., Yan, R., Roy, A., Xu, D., Poisson, J., and Zhang, Y. (2015). The I-TASSER Suite:

protein structure and function prediction. Nature methods *12*, 7-8.

76.   Roy, A., Yang, J., and Zhang, Y. (2012). COFACTOR: an accurate comparative algorithm for

structure-based protein function annotation. Nucleic acids research *40*, W471-W477.

77.   Altschul, S.F., Madden, T.L., Schäffer, A.A., Zhang, J., Zhang, Z., Miller, W., and Lipman,

D.J. (1997). Gapped BLAST and PSI-BLAST: a new generation of protein database search

programs. Nucleic acids research *25*, 3389-3402.

78.   Mirdita, M., von den Driesch, L., Galiez, C., Martin, M.J., Söding, J., and Steinegger, M.

(2017). Uniclust databases of clustered and deeply annotated protein sequences and

alignments. Nucleic acids research *45*, D170-D176.

79.   Davis, J., and Goadrich, M. (2006). The relationship between Precision-Recall and ROC

curves. pp. 233-240.

 Appendix 1

Brief introductions to the competitive methods

DRNApred [12]: DRNApred is a sequence-based DNA- and RNA-binding site predictor, which is based on a

logistic regression input with sequence features including evolutionary information, i.e., hidden Markov models

(HMM) profile and predicted structural properties including secondary structure (SS), relative solvent accessibility

(RSA), and disorder. We used its webserver (http://biomine.cs.vcu.edu/servers/DRNApred/) for performance

evaluation.

NCBRPred [43]: NCBRPred is a sequence-based DNA- and RNA-binding site predictor, which is based on a

bidirectional Gated Recurrent Units (BiGRUs) input with sequence features including the evolutionary information

PSSM (position-specific scoring matrix) and HMM, as well as the predicted RSA and SS. We used its webserver

(http://bliulab.net/NCBRPred/server) for performance evaluation.

NucBind, SVMnuc and COACH-D: NucBind [44] is a structure-based DNA- and RNA-binding site predictor,

which combines the predictions from a support vector machine (SVM) based ab-initio method SVMnuc and a

template-based method COACH-D [46]. SVMnuc was trained with sequence features from PSSM, HMM and

predicted SS. We used its webserver (http://yanglab.nankai.edu.cn/NucBind/) for evaluation.

GraphBind [25]: GraphBind is a structure-based nucleic-acid- and ligand-binding site predictor, which adopts a

hierarchical graph neural network (GNN) for massage passing on protein residue graphs. Its input features mainly

contain PSSM, HMM, SS, and atomic features. We used its standalone program with pre-trained model weights

from http://www.csbio.sjtu.edu.cn/bioinf/GraphBind/sourcecode.html for inference and evaluation.

GeoBind [22]: GeoBind is a structure-based nucleic-acid- and ligand-binding site predictor, which employs geodesic

convolution to point cloud on the protein surface. Its input features contain HMM, atom type, and local curvature

of the surface. We used its webserver (http://www.zpliulab.cn/GeoBind/) for evaluation.

aaRNA [47]: aaRNA is a structure-based RNA-binding site predictor, which employs a fully connected neural

network input with sequence features based on PSSM and HMM, as well as structural features like RSA, SS, and

curvature of the protein surface. We used its webserver (https://sysimm.ifrec.osaka-u.ac.jp/aarna/) for evaluation.

PepBind [14]: PepBind is a sequence-based peptide-binding site predictor, which combines the predictions from a

SVM-based ab-initio method SVMpep and two template-based methods S-SITE and TM-SITE [10]. SVMnuc was

trained with sequence features from PSSM, HMM, predicted SS and predicted intrinsic disorder. The structures

required by TM-SITE are predicted by the I-TASSER Suite [75]. We used its webserver

(http://yanglab.nankai.edu.cn/PepBind/) for evaluation.

PepNN-Struct and PepNN-Seq [45]: PepNN-Struct is a structure-based peptide-binding site predictor which

employs a graph transformer network to encode the protein representations and applies reciprocal multi-head

attention to model the interaction between the protein structure and peptide sequence. A one-hot encoding is used

to represent the protein and peptide sequence information. The pre-trained contextualized language model ProtBert

[31] is also used to embed the protein sequences. To perform the peptide-agnostic binding site prediction, the model

is input with random length poly-glycine peptides. PepNN-Seq is similar to PepNN-Struct, except that the graph

transformer model is substituted with an MLP. We used its standalone program with pre-trained model weights

from https://gitlab.com/oabdin/pepnn for inference and evaluation.

PepBCL [17]: PepBCL is a sequence-based peptide-binding site predictor, which fine-tuned the pre-trained protein
language model from [31] to predict peptide-binding sites. It also used contrastive learning to address the data
imbalance problem. We adopted its standalone code with pre-trained model weights for inference and evaluation
(https://github.com/Ruheng-W/PepBCL). There are two PepBCL models trained on two different datasets (1154 vs
640 training proteins), and here we report the results of the model trained on the larger dataset, since it performs
slightly better.

DeepPPISP [48]: DeepPPISP is a structure-based protein-protein binding site predictor, which utilizes one-hot
protein sequence, PSSM, and SS as input. The model adopts a convolutional neural network (CNN) to capture
local and global protein features. The predictions of DeepPPISP for the test proteins are directly obtained from our
previous work [26], which were originally produced by re-training DeepPPISP on our training set using its
standalone code in https://github.com/CSUBioGroup/DeepPPISP.

SPPIDER [49]: SPPIDER is a structure-based protein-protein binding site predictor, which is based on a fully
connected neural network input with sequence features including PSSM and structure features like RSA. The
model measures the impacts from spatially neighboring residues by adopting weighted averages over features of
spatially nearest neighbors. The predictions of SPPIDER for the test proteins are directly obtained from our
previous work [26], which were originally generated by the SPPIDER webserver (https://sppider.cchmc.org/).

MaSIF-site [21]: MaSIF-site is a structure-based protein-protein binding site predictor, which maps the geometric
and chemical features on the protein surface to patches and uses the geodesic convolutional layers to capture the
surface fingerprints. MaSIF-site does not rely on any features from multiple sequence alignments (MSA). The
predictions of MaSIF-site for the test proteins are directly obtained from our previous work [26], which were
originally generated by the standalone program with pre-trained model weights through a docker container from
https://github.com/lpdi-epfl/masif.

GraphPPIS [26]: GraphPPIS is a structure-based protein-protein binding site predictor, which exploits a deep graph
convolutional neural network (GCN) with initial residual and identity mapping to refine information in the protein
residue graphs. The input features of GraphPPIS consist of PSSM, HMM, and structural properties (RSA, SS and
torsion angles) from DSSP. The prediction results for the test proteins can be obtained from our webserver
(http://bio-web1.nscc-gz.cn/app/graphppis-v2)   or   the   standalone   program   (https://github.com/biomed-
AI/GraphPPIS).

ScanNet [23]: ScanNet is a structure-based protein-protein binding site predictor, which adopts geometric deep
learning for massage passing on protein atom graphs. Its input features mainly contain atomic features and PSSM.
We used its standalone program with pre-trained model weights from https://github.com/jertubiana/ScanNet for
inference and evaluation.

PeSTo [24]: PeSTo is a structure-based protein-protein binding site predictor, which adopts a geometric transformer
for massage passing on protein atom graphs. Its input feature only contains the atomic type. We used its standalone
program with pre-trained model weights from https://github.com/LBM-EPFL/PeSTo for inference and evaluation.

TargetS [15]: TargetS is a sequence-based ligand-binding site predictor, which extracts evolutionary information (PSSM), predicted SS and ligand-specific binding propensity from sequence context using a sliding-window strategy. It then employs several SVMs to learn the local binding patterns, which are assembled by the modified AdaBoost algorithm. We used its webserver (http://www.csbio.sjtu.edu.cn/TargetS/) for evaluation.

DELIA [19]: DELIA is a structure-based ligand-binding site predictor, which uses the bidirectional long short-term memory (BiLSTM) networks to refine sequence features including binding propensity from S-SITE, PSSM, HMM, predicted SS and predicted RSA, as well as a CNN to extract characteristics from the protein distance matrices. We used its webserver (http://www.csbio.sjtu.edu.cn/bioinf/delia/) for evaluation.

MIB [50]: MIB is a template-based metal ion-binding site predictor, where the fragment transformation method is used for structural comparison between query proteins and templates without any data training. The predictions of MIB for the test proteins are directly obtained from our previous work [18], which were originally generated from the MIB webserver (http://bioinfo.cmu.edu.tw/MIB/).

IonCom [51]: IonCom is a structure-based metal and acid radical ion-binding site predictor, which combines the predictions from an SVM-based ab-initio method IonSeq and four template-based methods including COFACTOR [76], TM-SITE, S-SITE, and COACH [10]. IonSeq was trained with sequence features from PSSM, ligand-specific binding propensity, predicted SS, predicted RSA, etc. We used its standalone program with pre-trained weights from https://zhanggroup.org/IonCom/ for inference and evaluation.

LMetalSite [18]: LMetalSite is a sequence-based alignment-free metal ion-binding site predictor where the pre-trained protein language model ProtTrans is used to extract sequence embeddings and a transformer with multi-task learning is applied to capture the intrinsic similarities between different metal ions. The prediction results of the test proteins can be obtained from our webserver (http://bio-web1.nscc-gz.cn/app/lmetalsite) or the standalone program (https://github.com/biomed-AI/LMetalSite).

Generation of the evolutionary features from MSA

Evolutionarily conserved residues may contain motifs related to important protein properties. Here, we also evaluated the widely used evolutionary features from MSA in our ablation studies, including position-specific scoring matrix (PSSM) and hidden Markov models (HMM) profile. PSSM is produced by running PSI-BLAST [77] to search the query sequence against UniRef90 [62] with three iterations and an E-value of 0.001. HMM profile is generated by running HHblits [53] against UniClust30 [78] with default parameters. Each residue is encoded into a 20-dimensional vector in PSSM or HMM. The feature values in the sequence representations from PSSM and HMM are further normalized to scores between 0 and 1 as follows:

$$v_{norm} = \frac{v - v_{min}}{v_{max} - v_{min}} \#(1)$$

where v is the original feature value, and v_{min} and v_{max} are the minimum and maximum values of this feature type observed in the training set, respectively.

Evaluation metrics

935　Following the previous studies, we use recall (Rec), precision (Pre), accuracy (Acc), F1-score (F1), Matthews

936　correlation coefficient (MCC), area under the receiver operating characteristic curve (AUC), and area under the

937　precision-recall curve (AUPR) to evaluate the predictive performance:

$$Rec = \frac{TP}{TP + FN} \#(2)$$

$$Pre = \frac{TP}{TP + FP} \#(3)$$

$$Acc = \frac{TP + TN}{TP + TN + FP + FN} \#(4)$$

$$F1 = 2 \times \frac{Precision \times Recall}{Precision + Recall} \#(5)$$

$$MCC = \frac{TP \times TN - FN \times FP}{\sqrt{(TP + FP) \times (TP + FN) \times (TN + FP) \times (TN + FN)}} \#(6)$$

where true positives (TP) and true negatives (TN) denote the number of correctly predicted binding and non-

binding residues, and false positives (FP) and false negatives (FN) denote the number of incorrectly predicted

binding and non-binding residues, respectively. AUC and AUPR are independent of thresholds, thus reflecting the

overall performance of a model. The other metrics are calculated using a threshold to convert the predicted binding

probabilities to binary predictions. We go through 101 thresholds from 0 to 1 with an interval of 0.01, and select

the best threshold that maximizes MCC on the validation sets. We adopt AUPR for hyperparameter selections as it

is more sensitive and informative than AUC in imbalanced two-class classification tasks [71,79].

Appendix 2

Appendix 2-table 1. Statistics of the ten binding site benchmark datasets used in this study

Molecule type	Training set			Test set		
	Sequences	Residues	% of binding residues	Sequences	Residues	% of binding residues
DNA	661	185,796	8.06	146	57,914	5.75
RNA	689	205,648	10.55	346	105,230	9.78
Peptide	1251	348,370	5.39	235	74,788	4.50
Protein	335	66,366	15.63	375	78,475	14.57
ATP	347	130,655	3.91	79	39,459	3.12
HEM	176	47,063	8.55	48	15,618	6.21
Zn^{2+}	1646	474,855	1.63	211	56,020	1.85
Ca^{2+}	1554	504,146	1.67	183	66,854	1.55
Mg^{2+}	1729	575,732	1.10	235	88,806	1.01
Mn^{2+}	547	181,699	1.41	57	20,419	1.10

Note: We combined the two test sets (Test_60 and Test_315) from [26] to establish our final protein-protein binding site test set.

Appendix 2-table 2. The performance of GPSite on the five-fold cross-validation and independent test sets

Molecule type	Five-fold cross-validation		Test set	
	AUC	AUPR	AUC	AUPR
DNA	0.933	0.620	0.921	0.516
RNA	0.910	0.615	0.899	0.573
Peptide	0.858	0.406	0.836	0.345
Protein	0.819	0.491	0.836	0.484
ATP	0.960	0.688	0.975	0.714
HEM	0.963	0.778	0.971	0.802
Zn^{2+}	0.984	0.808	0.981	0.859
Ca^{2+}	0.901	0.515	0.921	0.565
Mg^{2+}	0.889	0.379	0.892	0.370
Mn^{2+}	0.964	0.734	0.974	0.709
Average	0.918	0.603	0.921	0.594

Appendix 2-table 3. Performance comparison of GPSite with state-of-the-art methods on the ten binding site test sets

Test set	Method	Rec	Pre	Acc	F1	MCC	AUC	AUPR
DNA	DRNApred	0.258	0.159	0.879	0.197	0.140	0.698	0.129
	COACH-D	0.247	0.315	0.926	0.277	0.241	0.674	0.197
	NCBRPred	0.225	0.316	0.927	0.263	0.230	0.763	0.229
	SVMnuc	0.319	0.319	0.922	0.319	0.277	0.806	0.259
	NucBind	0.333	0.329	0.923	0.331	0.290	0.806	0.264
	GraphBind	0.607	0.355	0.914	0.448	0.422	0.884	0.424

	GeoBind*	0.481	0.427	0.933	0.452	0.417	0.891	0.416
	GeoBind	0.520	0.442	0.935	0.478	0.445	<u>0.896</u>	<u>0.443</u>
	GPSite	0.463	0.525	0.945	0.492	0.464	**0.921**	**0.516**
RNA	COACH-D	0.073	0.210	0.882	0.108	0.071	0.463	0.111
	DRNApred	0.092	0.236	0.882	0.133	0.093	0.530	0.142
	NucBind	0.185	0.344	0.886	0.241	0.195	0.649	0.226
	SVMnuc	0.227	0.371	0.887	0.282	0.232	0.742	0.275
	NCBRPred	0.234	0.471	0.899	0.312	0.284	0.660	0.302
	aaRNA	0.422	0.360	0.870	0.389	0.318	0.803	0.359
	GeoBind	0.562	0.455	0.891	0.503	0.446	0.804	0.459
	GraphBind*	0.576	0.342	0.850	0.429	0.365	0.828	0.433
	GraphBind	0.633	0.400	0.871	0.491	0.436	<u>0.861</u>	<u>0.506</u>
	GPSite	0.557	0.541	0.910	0.549	0.499	**0.899**	**0.573**
Peptide	PepNN-Seq	0.289	0.153	0.896	0.200	0.158	0.729	0.128
	PepBind	0.062	0.576	0.956	0.112	0.178	0.655	0.148
	PepNN-Struct*	0.351	0.180	0.899	0.238	0.202	0.765	0.163
	PepNN-Struct	0.337	0.210	0.913	0.259	0.222	<u>0.783</u>	0.187
	PepBCL	0.168	0.389	0.951	0.234	0.233	0.758	<u>0.222</u>
	GPSite	0.257	0.481	0.954	0.335	0.330	**0.836**	**0.345**
Protein	DeepPPISP	0.607	0.211	0.612	0.314	0.157	0.657	0.258
	SPPIDER	0.603	0.309	0.746	0.409	0.292	0.778	0.375
	MaSIF-site	0.584	0.330	0.767	0.421	0.308	0.777	0.384
	GraphPPIS	0.670	0.320	0.745	0.434	0.328	0.794	0.422
	ScanNet*	0.551	0.361	0.792	0.436	0.326	0.788	0.399
	ScanNet	0.568	0.442	0.832	0.497	0.403	<u>0.832</u>	<u>0.476</u>
	GPSite	0.490	0.473	0.846	0.481	0.391	**0.836**	**0.484**
ATP	TargetS	0.451	0.549	0.971	0.495	0.483	0.855	0.447
	GraphBind	0.529	0.473	0.967	0.499	0.483	0.901	0.503
	GeoBind	0.614	0.479	0.967	0.538	0.526	<u>0.927</u>	0.534
	DELIA*	0.452	0.669	0.976	0.539	0.538	0.914	0.545
	DELIA	0.453	0.689	0.977	0.547	0.548	0.918	<u>0.559</u>
	GPSite	0.618	0.742	0.981	0.675	0.668	**0.975**	**0.714**
HEM	TargetS	0.504	0.756	0.959	0.605	0.598	0.892	0.581
	GraphBind	0.733	0.505	0.939	0.598	0.578	0.926	0.638
	DELIA	0.604	0.670	0.957	0.636	0.614	0.928	0.664
	GeoBind*	0.646	0.625	0.954	0.635	0.611	0.920	0.659
	GeoBind	0.707	0.710	0.964	0.709	0.689	<u>0.932</u>	<u>0.724</u>
	GPSite	0.715	0.762	0.968	0.738	0.722	**0.971**	**0.802**
Zn^{2+}	MIB	0.744	0.219	0.946	0.339	0.385	0.935	0.394
	TargetS	0.454	0.749	0.987	0.566	0.578	0.874	0.593
	IonCom*	0.849	0.145	0.904	0.248	0.327	0.939	0.676
	IonCom	0.852	0.137	0.898	0.236	0.317	0.937	0.671
	LMetalSite	0.681	0.859	0.992	0.760	0.761	<u>0.976</u>	<u>0.803</u>
	GPSite	0.700	0.914	0.993	0.793	0.797	**0.981**	**0.859**

Ca^{2+}	MIB	0.338	0.078	0.928	0.126	0.135	0.775	0.103
	TargetS	0.121	0.490	0.984	0.194	0.238	0.776	0.163
	IonCom	0.297	0.247	0.975	0.269	0.258	0.698	0.166
	DELIA	0.172	0.633	0.986	0.271	0.325	0.785	0.248
	GeoBind	0.279	0.515	0.985	0.362	0.372	0.895	0.348
	GraphBind*	0.290	0.537	0.985	0.377	0.388	0.836	0.335
	GraphBind	0.371	0.623	0.987	0.465	0.475	0.888	0.430
	LMetalSite	0.413	0.724	0.988	0.526	0.542	<u>0.905</u>	<u>0.492</u>
	GPSite	0.435	0.820	0.990	0.569	0.593	**0.921**	**0.565**
Mg^{2+}	MIB	0.246	0.043	0.938	0.074	0.082	0.675	0.053
	TargetS	0.118	0.491	0.990	0.190	0.237	0.724	0.148
	IonCom	0.240	0.250	0.985	0.245	0.237	0.688	0.184
	DELIA	0.129	0.650	0.991	0.215	0.287	0.744	0.198
	GeoBind	0.181	0.475	0.990	0.263	0.289	0.840	0.227
	GraphBind*	0.246	0.205	0.983	0.224	0.216	0.750	0.136
	GraphBind	0.273	0.414	0.989	0.329	0.331	0.776	0.231
	LMetalSite	0.245	0.728	0.991	0.367	0.419	<u>0.865</u>	<u>0.316</u>
	GPSite	0.303	0.644	0.991	0.412	0.438	**0.892**	**0.370**
Mn^{2+}	MIB	0.462	0.096	0.946	0.159	0.193	0.856	0.168
	IonCom	0.511	0.245	0.977	0.331	0.344	0.833	0.304
	TargetS	0.271	0.496	0.989	0.351	0.362	0.864	0.322
	GeoBind	0.569	0.479	0.988	0.520	0.516	0.938	0.454
	DELIA	0.502	0.665	0.992	0.572	0.574	0.902	0.489
	GraphBind*	0.378	0.644	0.991	0.476	0.489	0.928	0.473
	GraphBind	0.427	0.706	0.992	0.532	0.545	0.930	0.555
	LMetalSite	0.613	0.719	0.993	0.662	0.661	<u>0.966</u>	<u>0.625</u>
	GPSite	0.613	0.807	0.994	0.697	0.701	**0.974**	**0.709**

958 *Note*: The best/second-best AUC and AUPR values are indicated by bold/underlined fonts. For the best structure-
959 based method (measured by AUPR) in each test set, its corresponding result when using ESMFold-predicted
960 structures as input is denoted with *.

964 **Appendix 2-table 4. The performance of GPSite and its comparison with PeSTo when re-splitting the**
965 **protein-protein binding site benchmark dataset**

Test set	Method	Rec	Pre	Acc	F1	MCC	AUC	AUPR
DNA	GPSite	0.490	0.519	0.945	0.504	0.475	0.921	0.521
RNA	GPSite	0.551	0.547	0.911	0.549	0.500	0.901	0.575
Peptide	GPSite	0.273	0.490	0.954	0.350	0.344	0.842	0.356
Protein	PeSTo*	0.252	0.416	0.858	0.314	0.250	0.788	0.336
	PeSTo	0.295	0.562	0.880	0.387	0.348	0.816	0.433
	GPSite	0.662	0.506	0.874	0.574	0.507	0.882	0.610
ATP	GPSite	0.671	0.696	0.981	0.683	0.673	0.975	0.707
HEM	GPSite	0.701	0.748	0.967	0.724	0.707	0.970	0.783

Zn^{2+}	GPSite	0.726	0.895	0.993	0.802	0.803	0.984	0.861
Ca^{2+}	GPSite	0.410	0.848	0.990	0.553	0.586	0.922	0.573
Mg^{2+}	GPSite	0.311	0.656	0.991	0.422	0.448	0.896	0.374
Mn^{2+}	GPSite	0.618	0.764	0.994	0.683	0.684	0.974	0.705

Note: PeSTo* means using the ESMFold-predicted structures as input for PeSTo.

Appendix 2-table 5. The numbers of proteins with TM-score > 0.7 or ≤ 0.7 between native and ESMFold-predicted structures in the ten binding site datasets

Molecule type	Training set		Test set	
	> 0.7	≤ 0.7	> 0.7	≤ 0.7
DNA	520	141	104	42
RNA	428	261	175	171
Peptide	1074	177	175	60
Protein	293	42	321	54
ATP	314	33	62	17
HEM	159	17	43	5
Zn^{2+}	1428	218	160	51
Ca^{2+}	1377	177	150	33
Mg^{2+}	1565	164	195	40
Mn^{2+}	512	35	52	5

Appendix 2-table 6. The prediction quality of ESMFold measured by TM-score between native and predicted structures in the ten binding site datasets

Molecule type	Training set		Test set		Total	
	Median	Mean	Median	Mean	Median	Mean
DNA	0.90	0.82	0.88	0.79	0.89	0.82
RNA	0.79	0.73	0.70	0.65	0.76	0.70
Peptide	0.93	0.86	0.88	0.78	0.93	0.85
Protein	0.94	0.87	0.93	0.85	0.93	0.86
ATP	0.95	0.89	0.90	0.83	0.94	0.88
HEM	0.95	0.89	0.94	0.87	0.94	0.88
Zn^{2+}	0.94	0.87	0.91	0.82	0.93	0.86
Ca^{2+}	0.95	0.88	0.93	0.85	0.94	0.88
Mg^{2+}	0.95	0.90	0.93	0.86	0.95	0.89
Mn^{2+}	0.96	0.92	0.95	0.91	0.96	0.91

982 **Appendix 2-table 7. The ablation studies on protein features and model designs in the ten binding site test**
983 **sets**

Method	DNA	RNA	Pep	Pro	ATP	HEM	Zn^{2+}	Ca^{2+}	Mg^{2+}	Mn^{2+}	Avg
w/o sequence	0.389	0.473	0.251	0.396	0.646	0.726	0.791	0.503	0.338	0.646	0.516
One-hot	0.429	0.506	0.254	0.427	0.645	0.755	0.840	0.564	0.359	0.673	0.545
MSA profile	0.507	0.557	0.281	0.463	0.671	0.791	0.814	0.540	0.369	0.683	0.568
w/o structure	0.437	0.503	0.242	0.394	0.544	0.565	0.793	0.468	0.288	0.607	0.484
w/o geometry	0.484	0.539	0.318	0.439	0.631	0.670	0.813	0.489	0.313	0.638	0.533
Single-task	0.506	0.549	0.338	0.455	0.669	0.716	0.843	0.557	0.326	0.632	0.559
GPSite	**0.516**	**0.573**	**0.345**	**0.484**	**0.714**	**0.802**	**0.859**	**0.565**	**0.370**	**0.709**	**0.594**

Note: The numbers in this table are AUPR values. "Pep" and "Pro" denote peptide and protein, respectively. "Avg"
means the average AUPR values among the ten test sets. "One-hot" denotes replacing the ProtTrans embedding
with one-hot sequence encoding. The generation of the MSA profile (PSSM and HMM) is detailed in Appendix 1-
'Generation of the evolutionary features from MSA'. "w/o structure" means using a transformer model only input
with the ProtTrans sequence features. "w/o geometry" means removing the geometric featurizer in GPSite.

Appendix 3

Appendix 3-figure 1. The performance of GPSite when using native or predicted structures as input during the test

phase.

994
995
996
997

999 **Appendix 3-figure 2.** Distributions of the TM-scores between native and predicted structures in the protein, ATP,

1000 HEM, Zn^{2+}, Ca^{2+}, Mg^{2+} and Mn^{2+} datasets.

1001

1002

1003   **Appendix 3-figure 3.** The performance of GPSite on structures of different qualities, and the comparisons with the
1004   best structure-based methods in the test sets of protein, ATP, HEM, Zn^{2+}, Ca^{2+}, Mg^{2+} and Mn^{2+}. The experimental
1005   structure-based methods input with ESMFold-predicted structures are marked with *. Since there are only 5
1006   proteins with TM-score $\leq$ 0.7 in the HEM and Mn^{2+} test sets (details shown in Appendix 2-table 5), the
1007   corresponding results may not be statistically significant.

1008

1009

1010 **Appendix 3-figure 4.** The run time of ESMFold with respect to the sequence length in Swiss-Prot evaluated on an
1011 NVIDIA A100 GPU. The run time is presented as mean ± standard deviation per range of number of residues
1012 (range size equals 100).

1013

1014

1015

1016 **Appendix 3-figure 5.** The univariate and bivariate distributions of the protein length and the pTM estimated by
1017 ESMFold of the Swiss-Prot sequences. The probability density curves are fit using kernel density estimation. The
1018 darker region in the bivariate heatmap corresponds to a higher number of samples.

1019

Appendix 3-figure 6. The percentage of proteins predicted as binding to peptide, protein, ATP, HEM, Zn^{2+}, Ca^{2+}, Mg^{2+} and Mn^{2+} by GPSite to be annotated with certain biological process in Swiss-Prot. Only the specific biological process terms with depth ≥ 8 in the GO directed acyclic graph are considered, among which the 15 terms with the highest percentage are displayed.

Appendix 3-figure 7. The percentage of pathogenic or benign natural variant sites within GPSite-predicted interfaces. The baseline is the probability of a random residue being annotated as an interface residue.