NASTRA: Innovative Short Tandem Repeat Analysis through Cluster-Based Structure-Aware

Algorithm in Nanopore Sequencing Data

Zilin Ren[1,2,#,*], Jiarong Zhang[3,4,#], Yixiang Zhang[1,2,#], Pingping Sun[2], Jiguo Xue[3], Jiangwei Yan[4,*],

Ming Ni[3,*]

1. Changchun Veterinary Research Institute, Chinese Academy of Agricultural Sciences,

Changchun 130122, China

2. School of Information Science and Technology, Institution of Computational Biology, Northeast

Normal University, Changchun 130117, China

3. Institute of Health Service and Transfusion Medicine, Beijing 100850, People's Republic of

China

4. School of Forensic Medicine, Shanxi Medical University, Taiyuan 030001, People's Republic of

China

* To whom correspondence should be addressed. Email: Zilin Ren, zilin.ren@outlook.com;

Jiangwei Yan, yanjw@sxmu.edu.cn; Ming Ni, niming@bmi.ac.cn.

15 Abstract

Short-tandem repeats (STRs) are type of genetic markers distinguishing individuals and

authenticating cell-lines. Nanopore sequencing is promising in STR typing for its convenience, but

lack of analysis method. Here we proposed NASTRA, a tool for accurate STR genotyping with

nanopore sequencing, which uses an STR-structure-aware algorithm to infer repeat numbers of

STR motifs. In our real-time scenario tesing, NASTRA has 100% accuracies for diploid STRs, far

exceeding method employing strategy that include all candidate STR allele sequences for

alignments. NASTRA could be useful in applications as individual identification and cell-line

authentication with nanopore sequencing. NASTRA is available via

https://github.com/renzilin/NASTRA.

Keywords: nanopore sequencing; short tandem repeat; individual identification; cell line

authentication; bioinformatics tools.

Background

Short tandem repeats (STRs) in human genome are specific DNA loci that can have high degree of

polymorphisms in the number and forms of repeat motifs among individuals. This feature makes

STRs a kind of genetic markers well-suited for individual identification [1,2], cell line

authentication [3,4], as well as relationship inferring [5–7]. In Short Tandem Repeat DNA Internet

Database maintained by the National Institute of Standards and Technology (NIST) [8], more than

70 STR genetic markers, typically with 19 (D10S1248) -114 (FGA) alleles in human populations,

are chosen as genetic markers with desirable features as high heterozygosity, regular repeat unit,

distinguishable alleles and robust amplification. These STRs have been utilized for decades by

forensic laboratories across the globe and have formed the basis of million- or even 10-million-

scale human DNA databases for public security purposes in many countries. In the realm of

biomedical research, profiling STR for cell line authentication plays a critical role in ensuring

scientific reproducibility and preventing misidentification as well as cross-contamination of cell

lines[9,10]. To establish standardized practices for cell line authentication using STRs, the

International Cell Line Authentication Committee (ICLAC, https://iclac.org) integrates numerous

online databases and search tools, including the Cellosaurus knowledge resource [11], DSMZ STR

profile database[12], CLIMA database [13], CLASTER [14].

Conventional method for STR genotyping is the use of capillary electrophoresis (CE)-based length

analysis. Besides, massively parallel sequencing (MPS) has also been validated for STR profiling,

and it provide a larger battery of STRs in a run than the CE-based method. However, the majority

of instruments of Sanger sequencing and MPS are heavy (50-186 kg), costly (50k-180k US dollars),

and have high environmental requirements as constant temperature and vibration free. Thus,

Sanger sequencing and MPS systems are usually maintained by well-equipped laboratories or

facilities, and samples are transported for analysis, which might needs days to obtain STR typing

reports.

A more rapid and affordable solution of STRs profiling thus has significance for relevant research

and applications. Nanopore sequencing provides a cheap and real-time sequencing approach.

The devices for nanopore sequencing, such as MinION Mk1B/Mk1c (Oxford Nanopore

Technologies, Oxford, UK) and the recently released QNome-3841 (Qitan Technology, Chengdu,

China), are exceptionally portable and considerably cheaper than NGS and Sanger sequencing

systems. Moreover, these portable nanopore sequencing devices are capable of generating much

longer reads than Sanger sequencing and NGS systems, and had a throughput in the Gbp range

during a single run. Therefore, nanopore sequencing has been applied in various on-site

sequencing applications as in-field genomic surveillance of pathogens [15,16] and biodiversity

investigations [17,18]. Due to the portability and high throughput, Zaaijer et al.[19] reported an

interesting pilot study that utilized MinION for whole genome sequencing to rapidly profile SNPs

and authenticate human cell lines for biological researches.

However, despite these advantages, nanopore sequencing data are noisier than these generated

by Sanger sequencing and MPS. Unlike the cases of STR expansion disorders causing diseases, in

which pathogenic alleles remarkably differ from benign alleles in sizes [20–22], alleles of STR

genetic markers for individual or cell-line identity identification are usually of a 100 – 300 nt

length and their repeat units are of 3- to 5-nt. Genotypes of STR genetic markers are defined by

the exact counts of their repeats. Many STR genetic markers consist of multiple (compound STRs

and complex STRs) and units are similar within in one STR and its flanking regions. For instance,

the repeat structure of a Combined DNA Index System (CODIS) core STR locus D3S1358 is

$TCTA[TCTG]_n[TCTA]_m$, in which n and m denotes repeat numbers. Moreover, some repeat units of

STRs contain or form 3- to 4-nt homopolymers or form homopolymers in repeats, as STR Penta D

with a repeat structure of $[AAAGA]_m$, which are particularly error-prone, systematically, in

nanopore sequencing [23].

Thus, the improvement of highly accurate typing method for genetic STR markers for nanopore

sequencing is challenging [24–27]. To tackle this issue , developing algorithms and workflows

specifically tailored for typing of genetic STR markers, considering repeat structures of specific

STR loci, might be feasible strategy. In our previous study [23], we exhibited that conventional

genotyping tools for nanopore sequencing as repeatHMM [21] are not suitable, and a simple

customized workflow that integrated the classic Smith-Waterman algorithm for repeat unit re-

alignment provided a significant improvement in the accuracy of STR typing. More than 32 STRs

could be consistently and correctly typed in a validation set involving 31 individuals, and it is a

prove-of-concept study of employing nanopore sequencing in human identity testing and cell-line

authentication. Recently, Hall et al. [27] and Tytgat et al. [24] and the very recently Jidong et al

[28], used a different and straight strategy that includes all available sequences of alleles for

alignment of nanopore sequencing reads, and to select the alleles with sequencing reads for STR

genotyping. In their validation sets, they report a higher STR typing accuracies than our previous

method, and it further indicates the promising application of nanopore sequencing in this field.

However, this strategy highly depends on the available sequences, many of which are unknown

for these highly diverse STRs and might lead to error typing. On the other side, larger validation

sample sets are also needed to example validate the STR typing methods.

We aim to develop a method for accurate STR genotyping in applications as individual

identification and cell-line authentication. We expect that the method can fully consider the

characteristics of these STR markers and have high flexibility, i.e., independent of allele

sequences databases that lack allele information. In this study, we propose NASTRA, a tool with

clustering-based structure-aware algorithm , rather than allele-dependent alignment, for

inference of repeat structure for STR genotyping. We includes a validation set involving 76

individuals and 8 cell-lines, and tested with different chemistries (R9 and R10 flow cells) as well as

STR amplification methods prior to sequencing. Meanwhile, the validation based on allele-

dependent methods were conducted and NASTRA turned out to have better performance in both

accuracy and sequencing data requirement.

Results

In this study, we firstly illustrated the overview of NASTRA. And then demonstrated how to find the

optimal thresholds: supporting reads number (SN) and the ratio of supporting reads number (SNR),

which is pivotal for STR genotype calling. Following this, we conducted an extensive evaluation of

NASTRA, comparing it with a typical alignment-based method named STRspy and investigating the

characteristics of genotyping errors. We then conducted a real-world scenario testing using eight

human cell lines. Lastly, we summarized the runtime of NASTRA. Throughout these processes, we

leveraged the MiSeq FGx™ Forensic Genomics System to carry out STR genotype calling for ground

truth construction. Specifically, we amplified 54 STR loci and 46 STR loci across 88 DNA samples

using Verogen's ForenSeq Mix A kit and Promega's PowerSeq 46GY kit and sequenced amplicons

with R9.4.1 and R10.3 flowcells (Figure 1a).

114   Overview of NASTRA

For STR genotyping, NASTRA requires BAM files, BED files containing the positional information

of STRs, and fact sheets containing the repetitive structure details of the STRs. In addition,

NASTRA performs quality control and determines homozygosity/heterozygosity on genotyped

alleles based on the SN of alleles and the SNR between different alleles. Drawing inspiration from

the ForenSeq Universal Analysis Software (UAS), we incorporated a similar mechanism to filter

loci with low coverage and stutters: if the total number of reads covering the STR locus is below

10, NASTRA doesn't output any result due to insufficient coverage; if the SN value of the major

allele does not exceed the threshold, the result is classified as "interpretation"; if the SN value of

the minor allele does not surpass the threshold but the SNR value does, the result is considered

as "imbalance". Regarding the optimal selection of SN and SNR, we provided the corresponding

configuration file for users (the relevant analysis is described in *Parameter optimization* section).

NASTRA comprise two main sub-algorithms, read clustering and repeat structure inference,

which mitigates the potential impact of subtle sequencing errors on accurate genotyping and

genotypes STR without the need for allele reference database (Figure 1b). In step 1, NASTRA

retrieves aligned reads that span a designated STR locus based on positional information from

the BAM file. Following that, in step 2, the prefix and suffix flanking sequences are individually

aligned against the extracted reads, employing an affine-gap penalty (methods section).

Subsequently, the upstream and downstream sequences of all retrieved reads will be trimmed,

retaining only the three adjacent bases flanking the core repeat region of the STR. These trimmed

reads are categorized as unique trimmed reads and their frequencies are recorded as SN. Due to

the presence of subtle sequencing errors, the trimmed reads could encompass over 100 distinct

types. Therefore, NASTRA utilizes pairwise alignment with an affine gap penalty to cluster these

reads in step 3. By permitting the exclusion of minor errors, such as single-base insertions, this

approach decreases the diversity among reads, thereby facilitating the identification of potential

candidate alleles. In step 4, we developed a recursive algorithm to infer repeat structure of allele

sequences based on the repeat units present within the STR, which ensures swift acquisition of

STR genotypes and aids in promptly identifying the locations of SNV in locus. Finally, NASTRA

conducts STR genotyping by leveraging the SN and SNR values associated with alleles.

Parameter optimization

NASTRA performs STR genotype calling based on the SN and SNR values of the alleles. Therefore,

the threshold SN and SNR need to be refined to enhance the robustness of NASTRA. In light of

this, we partitioned the samples into two distinct sets: (1) training set, comprising 20 males and

20 females, and (2) test set, consisting of 18 males, 18 females, and 4 replicates of 2800M

samples. However, two underlying issues arose that could prevent the attainment of optimal

threshold values: (1) the limited size of the training set; (2) the insensitivity of the existing

sample's deep sequencing depths towards the thresholds. To address these issues, we developed

a mini-tool called NanoTime. Leveraging sequencing summary files, we used NanoTime to

downsample Nanopore sequencing reads in accordance with sequencing durations, including 1,

2, 3, 4, 5, 6, 8, 10, 12, 16, 20, and 24 hours. This process substantially expanded both training set

and testing set from 40 samples to 480 samples.

To assess the performance, we used allele calls from UAS reports as the ground truth and

excluded results from the UAS that were labeled as "imbalanced," "allele count," "stutter," and/or

"interpretation threshold". Then, NASTRA results that failed quality control were excluded from

the evaluation. Finally, the genotyping results for each STR obtained through NASTRA can be

classified into five classes: (1) **Exact Match**: correct genotyping; (2) **Incomplete Match**: correct

genotyping when disregarding the incomplete repeat unit; (3) **One Match**: one of the alleles is

correctly genotyped in a heterozygous STR genotype; (4) **Incomplete One Match**: one of the

alleles is correctly genotyped in a heterozygous STR genotype, when disregarding the incomplete

repeat unit; (5) **Mismatch**: incorrect genotyping.

Thresholds for Autosomal STRs. A total of 12960 genotype calls for 27 autosomal STR loci on 480

samples were obtained. Initially, we explored various SN values (0, 5, 10, 15, 20, 25, 30, 35, 40,

45, and 50) as well as different SNR values (ranging from 0 to 1, in increments of 0.01). For each

SN value, we calculated the maximum genotyping accuracy for each autosomal STR locus from

expanded training set. The result showed that when SN equals or surpasses 25, the maximum

genotyping accuracy for all STR loci can surpass 95% (Figure 2a). After determining an SN value of

25, we calculated the genotyping accuracy for each autosomal STR at various SNR values. The

median value within the SNR range corresponding to the peak genotyping accuracy is designated

as the SNR threshold (Figure 2b). After the determination of the threshold SN and SNR, NASTRA

was employed to conduct STR genotype calling on expanded testing set. In summary, 9,428 of

12,960 (72.8%) STRs on 480 expanded testing set were genotyped successfully, consisting of

8,455 (89.7%) exact match, 642 (6.8%) incomplete match, 307 (3.3%) one match, 11 (0.1%)

incomplete match, and 0.1% mismatch. The rest 3,532 genotypes calling failed to pass NASTRA

quality control (2,548 calls) or UAS quality control (984 calls), due to the low coverage of short

sequencing durations. Figure 3c illustrates the accuracy of each STR across the 480 samples.

Among the 27 loci, 18 loci exhibited a calling rate of 1 (either exact match or incomplete match),

while 4 loci exceeded 95% accuracy. Additionally, we employed pairwise alignment to investigate

sequence identity for each genotyping result (Figure 2d). We found that for the majority of

"incomplete match" genotyping results, the sequence identities of allele sequences equal to 1.

This suggests that NASTRA primarily disregards the incomplete repeat units solely in terms of

repeat counting, while maintaining the true allele sequences.

Evaluation of NASTRA on ForenSeq amplicons with R9.4.1

flow cells

After having determined the optimal parameters for NASTRA, we first assessed the performance

between NASTRA and the typical alignment-based method, STRspy [27], on ForenSeq amplicon

sequencing data (test set, sequencing duration 24 hours). STRspy is an STR profiling tool tailored

for long-read sequencing, which is based on the alignment of sequencing reads with an allele

reference library. The authors have created a database containing allele sequences of 22

autosomal STRs. And thus, STRspy is unable to perform genotyping calling for 5 out of 27 STR loci

in ForenSeq data because of the absence of allele information. The results in a calling of 0 for

these loci (D17S1301, D19S433, D20S482, D4S2408, D9S1122, and D6S1043) across all samples.

Furthermore, it's crucial to emphasize that if the relevant allele sequence isn't included in the

reference database, STRspy may produce incorrect genotyping results due to wrong alignments.

We analyzed the calling ratio and genotyping accuracy for ForenSeq data across the test set

(Figure 3a-b). In addition, the genotyping results of sexual STRs were summarized.

Regarding NASTRA, it achieved a calling ratio of 1 for 7 STR loci, while for 9 STR loci, the calling

ratio ranged from 92.1% to 97.4%. Additionally, 3 STR loci had a calling ratio ranging from 71.8%

to 80.0%. The calling ratios for PentaD and PentaE are the lowest, at 22.2% and 33.3%

respectively. This is attributed to homopolymer sequencing errors causing low SN of candidate

alleles. STRspy successfully genotyped for 22 STR loci, achieving a calling ratio of 1. NASTRA

demonstrates superior accuracy compared to STRspy. NASTRA achieved a 100% genotyping

accuracy across 21 STR loci, including PentaE. Among the remaining 6 loci, the genotyping

accuracy for 3 loci (D2S1338, D1S1656, and D6S1043) exceeded 92%. As for STRspy, it exhibited

16 loci with a genotyping accuracy beyond 92%, including 12 loci with a accuracy of 100%.

208 Evaluation of NASTRA on PowerSeq amplicons with R10.3
209 flow cells

To investigate the performance of NASTRA on different amplification systems and flow cells, we

conducted a sequencing experiment on 46 samples using Promega's PowerSeq 46GY kit and

R10.3 sequencing flow cells. The PowerSeq kit is a co-amplification system consisting of 22

autosomal STR loci and 23 Y-STR loci. The ONT R10.3 flow cell represents a new version featuring

new pore design, resulting in enhanced read accuracy and quality. We conducted STR genotyping

on the sequencing data using STRspy v1.1.1 and NASTRA with default parameters.

The calling ratio and genotyping accuracy for PowerSeq data across 46 samples were shown in

Figure 4a and b. Compared to the ForenSeq amplification system, the PowerSeq system does not

include five automsomal STR loci (D17S1301, D20S482, D6S1043, and D9S1122). Regarding

NASTRA, out of the 22 autosomal STR loci, it successfully called 20 STR loci with a calling ratio of

1, while the remaining 2 loci, PentaE (94.7%) and PentaD (55.6%), exhibited slightly lower calling

ratios. For STRspy, there is only one locus, D19S433, not being included in the reference

database. In terms of genotyping accuracy, we observed a decrease in performance for both

STRspy and NASTRA on the PowerSeq dataset, which could be attributed to the overall shorter

amplicons in PowerSeq data compared to ForenSeq data. Specifically, NASTRA achieved an

accuracy exceeding 95% in 18 loci (compared to STRspy's 13 loci), with the remaining 4 loci

having accuracy ranging from 80% to 91.5%. While, STRspy achieved accuracy between 61.7% to

91.3% in the remaining 7 loci, and there was no result for one locus, D19S433. In general,

NASTRA exhibited a slightly better performance than STRspy.

229   Real-time typing of 8 human cell lines

To assess NASTRA's performance in real-world scenarios, DNA samples from eight human cell

lines were processed for amplification and sequencing using the ForenSeq Signature kit on a

MinION platform with an R9.4.1 flow cell. We then employed NanoTime to generate real-time

sequencing data at various durations (1-6, 8, 10, 12, 16, 20, and 24 hours), and utilized NASTRA

for the genotype calling of 27 autosomal STRs. The MinION platform yielded amplicon

sequencing data covering 27 autosomal STRs, 24 Y-STRs, 7 X-STRs, 94 identity SNPs, which

consumed a certain portion of sequencing throughput.

The overview of genotyping results is shown in Figure 5a. NASTRA consistently returned correct

genotyping results for all STR loci, except those that failed to pass UAS quality control and were

recognized as unreliable results (labeled with Imbalance/Interpretation). When the sequencing

duration is 1 hour, there are 8 of 27 loci were genotyped successfully and correctly across 8

samples. With the sequencing duration reaching 4 hours, at least 7 of 8 samples of all loci

belonging to the CODIS Core Loci were genotyped correctly. We found that the occurrence of

unreliable genotyping results was related to low sequencing depth (Figure 5 b-c). And when the

depth of each locus is higher than 300, the number of unreliable genotyping results is very few.

This may be crucial for the development of STR multiplex panels tailored for nanopore

sequencing.

Comparison of running time

NASTRA is built on the Python programming language and incorporates the parasail library [29], a

C-based pairwise alignment tool. Users can utilize the shell command *xargs* to achieve

parallelization of NASTRA at the sample-level, while STRspy utilizes the shell tool *parallel* for

parallelization at the locus-level.

To make a runtime comparison, we allocated 8 threads to NASTRA, aligning with the thread count

employed by STRspy. The STR genotype calling for all sequencing data was performed on a server

with a 64-Core/128-Thread Processor (AMD EPYC 7763, 2.45GHz) and 256 GB of memory. In

Table 1, we summarized the runtime comparison between NASTRA and STRspy. We found that

NASTRA is about 60X faster than STRspy on the ForenSeq amplicon sequencing data, while on the

PowerSeq amplicon sequencing data, STRspy took longer. This could potentially be attributed to

the fact that the ForenSeq data encompasses both 58 STRs and 94 SNPs, whereas the PowerSeq

data only includes 46 autosomal and Y-chromosomal STRs. Consequently, the number of reads

processed from PowerSeq data is higher than those processed from ForenSeq data. Notably,

when we conducted a real-time typing of 8 human cell-lines, NASTRA demonstrated its suitability

for handling such tasks.

While it's true that the two tools employ different programming languages, and thus, a direct

comparison of runtime might not be entirely objective, it is evident that NASTRA significantly

outperforms STRspy in terms of runtime. Based on our observations, we noted that a significant

portion of time is occupied by the alignment process during the execution of STRspy, potentially

attributed to the individual execution of Minimap2 [30,31] for each locus.

Disscussion

In this study, we developed a novel computational approach for STR genotyping, named NASTRA.

NASTRA comprises two key algorithms: read clustering and repeat structure inference.

Recognizing that sequencing errors can occur randomly occurs in each amplicon read, NASTRA

utilizes read clustering to mitigate the impact of these errors and found the candidate allele

sequences of the STR. Once the candidate allele sequences are obtained, structure-aware

algorithm will reconstruct the repeat structures of alleles based on the known repeat motifs from

fact sheets. This process transforms the allele sequences into bracket sequences, where

incomplete units or SNPs are readily discernible. Notably, in contrast to alignment-based

methods, NASTRA operates independently of allele reference database and thus won't fail to

genotype STR resulting from the lack of allele information in the database. Additionally, we have

applied NASTRA on MiSeq FGx data for ground truth construction, demonstrating it can also be

used for NGS data.

To comprehensively evaluate the performance of NASTRA, we carried out several assessment

procedures. We first created a ground truth dataset of 88 DNA samples using the MiSeq FGx

system, which is a widely accepted technology for forensic applications. Then, amplification and

sequencing experiments were carried out across these samples using various amplification kits

and flow cells. To investigate the optimal thresholds for NASTRA and its robustness under

different sequencing durations, we expanded the training and test sets using NanoTime. Our

performance evaluation encompassed ForenSeq data, PowerSeq data, and a real-world test

involving eight standard DNA cell lines. For performance comparison, we exclusively utilized the

alignment-based STRspy and did not employ well-known repeat quantification tools such as

repeatHMM [21], STRique [22], and DeepRepeat [20], as they are primarily tailored for detecting

repeat expansion disorders rather than forensic-level STR genotyping. As demonstrated in our

previous study [23], repeatHMM didn't perform well. However, DeepRepeat presents an

intriguing possibility for utilizing current signals in STR genotyping. Exploring transfer learning

with our data could be a promising avenue. In summary, the results demonstrated that NASTRA

exhibited exceptional performance in terms of accuracy and speed, making it a promising

method for real-world applications.

However, NASTRA does have several limitations. Firstly, it's worth noting that our performance

comparison was conducted using only one alignment-based method, and the reference database

for this method is still undergoing updates. Therefore, this evaluation may not provide a fully

objective assessment but rather serves as an illustrative example for reference in terms of

accuracy and runtime. Secondly, NASTRA is unable to genotype incomplete repeats. While we

have demonstrated that incomplete repeat units can be detected in the output allele, NASTRA

does not incorporate the digital information into its allele calls. Thirdly, NASTRA's read clustering

process carries the potential risk of erroneously classifying two alleles as originating from a single

allele. This may occur due to the tolerance of a single nucleotide polymorphism (SNP) or a one-

base gap when dealing with two similar alleles (differing by just one-base). Fourthly, we have

observed that the length of amplicons can impact performance based on our testing with

ForenSeq and PowerSeq data. Specifically, the flanking regions of these STRs, including their

prefix and suffix, can be quite similar, potentially leading to incorrect trimming. NASTRA requires

amplicons with long flanking regions (more than 30 bp) to ensure the accuracy of STR

genotyping. Finally, NASTRA relies on base sequences as input, and its performance is therefore

dependent on the base calling model. Given that STRs are a type of complex genomic region, the

development of an effective base calling model for STRs is necessary.

Conclusions
314

NASTRA is an innovative computational approach for STR genotyping using nanopore sequencing

data, employing a structure-aware algorithm instead of traditional alignment to a reference

database. Through tests and comparisons conducted on various flow cells and amplification kits,

NASTRA demonstrated good performance in terms of genotyping accuracy and speed. Although

not all STR loci obtained correct genotype calls, NASTRA exhibited robustness in certain specific

loci, demonstrating its significant potential for human identification and cell line authentication

using nanopore sequencing platforms. Further improvements of NASTRA through validation

studies with larger sample sizes are necessary.

Methods

Sample collection and DNA extraction

A total of 76 blood samples were collected from 76 unrelated anonymized Han Chinese

volunteers, including 38 females (ID: F01-F38) and 38 males (ID: M01-M38). Among them, 30

samples (F01-F15 and M01-M15) were used in our pervious study [23]. The rest 46 samples (F16-

F38 and M16-F38) were newly collected. Genomic DNA of newly collected 46 samples were

extracted using PureLink genomic DNA kit (Invitrogen, USA). In order to perform a real-time

scenario tesing, we collected 8 control DNA samples including 3 forensic DNA controls (2800M

from Promega, 9947A and 9948 from Origene), and 5 cell line standards (NA12878, NA24143,

NA24149, NA24694, and NA24695 from Coriell Institute). All DNA samples were quantified on

the Qubit 3.0 Fluorometer (Invitrogen) before amplification.

STR profiling using MiSeq FGx system

Newly collected DNA samples (F16-F30, M16-M30) and 8 control DNA samples were amplified

using the ForenSeq DNA Signature Prep Kit (DNA Primer Mix A). In the meantime, 2800M were

amplified as positive control using DNA Primer Mix B, which covers all STR loci in Mix A kit. To

obtain sufficient amplicons for Illumina MiSeq FGx sequencing and Nanopore sequencing, 50 ng

of template rather than recommended 1 ng were used as input. PCR amplification were

performed on ProFlex™ 3x32-Well PCR System (Thermo Fisher).

All purified amplified libraries were divided into 2 shares, which were used for both MiSeq FGx

sequencing and Nanopore sequencing. Pooled libraries were obtained combining equal volumes

(2 μL) of normalized library (10 nmol) and diluted into 4 nmol. Finally, 7 pmol of pooled libraries

were sequenced on the MiSeq FGx desktop sequencer. The above experimental steps were

carried out according to the manufacturer's protocol. Genotype calling of STR loci was performed

using ForenSeq Universal Analysis Software, UAS (v1.3.6897; Verogen), with Verogen's default

analytical threshold (1.5%), interpretation threshold (4.5%) and stutter filter (specific to each

locus).

Nanopore sequencing for ForenSeq amplicons

The concentration of PCR products was quantified with Qubit 3.0 fluorometer and Qubit dsDNA

HS assay kit according to manufacturer's instruction, before library preparation. Nanopore

libraries were prepared with Ligation Sequencing Kit (SQK-LSK109). Briefly, 0.2 pmol purified DNA

per sample was processed using NEBNext Ultra II End repair/dA-tailing Module(E7546). The

samples were multiplexed using Native Barcoding Expansion 1-12 (PCR-free) and Native

Barcoding Expansion 13-24 (PCR-free). Adapter was ligated to the pooled libraries with NEBNext

Quick Ligation Module (E6056). Finally, 0.05 pmol libraries were loaded into the R9.4.1 flowcell

and sequencing was performed with MinKNOW. In general, 48 DNA samples and 8 control DNA

samples were sequenced in 5 runs with a sequencing duration beyond 24 hours.

Nanopore sequencing for PowerSeq amplicons

According to the manufacturer's instruction, 48 DNA sample were selected and amplified using

the PowerSeq™ 46GY System (Promega, WI, USA). 1 ng template DNA of each sample was used

for PCR amplification with 29 cycles. The PCR products were clean-up with AmPure XP Bead

(Beckman Coulter, Indianapolis, USA) and DNA concentration. The library preparation process is

the same as that was described above. Finally, 0.05 pmol libraries were loaded into the R10.3

flowcell and sequencing was performed using MinKNOW. In general, 48 DNA samples were

sequenced in 2 runs with a sequencing duration beyond 24 hours.

Bioinformatic analysis for nanopore sequencing data

368 We performed the basecalling process by using Guppy v6.3.4 with high-accuracy model. Then,

369 reads were aligned to the human reference genome (assembly GRCh37, hg19) using Minimap2

370 v2.17-r941 [30,31]. Finally, SAMtools v1.6 [32] were employed to convert SAM files into BAM

371 format, which were used as input of NASTRA. Downsampled data were generated using

372 NanoTime, which is available at https://github.com/renzilin/NanoTime.

Pairwise alignment with affine-gap penalty

We used parasail-python [29] (https://github.com/jeffdaily/parasail-python) to perform pairwise

alignment with affine-gap penalty in read trimming and clustering steps. Because gap open and

extension penalties are required to be positive integers, we specified the match score of 75, the

mismatch penalty of 90, gap open penalty of 75, and gap extension penalty of 10. Consequently,

the alignment prefers to 2 continuous gaps rather than 1 mismatch. If the number of continuous

gaps exceeds 2, the alignment prefers 1 mismatch.

Recursive algorithm for repeat structure inference

To obtain the number of repeat units and finish the allele call without alignment, we developed a

recursive algorithm to infer the repeat structure by searching repeat motif in allele sequence

according to the STRBase fact sheets. The algorithm works as following: 1. for each motif, exact

match is used to search the segments consisting of a single type of motif; 2. we masked one

segment at a time and repeat step 1; 3. remove duplicated masked reads and redo step 2 until no

new segment is found; 4. if masked reads converge to the only one, then this is the optimal

inference of repeat structure. The schematic representation of algorithm is shown in Figure 6.

Declarations

Ethics approval and consent to participate

390   Our study was approved by the ethics committee of Shanxi Medical University (no. 2020GLL031).

391   Written informed consent was obtained from all participants and all authors.

Consent for publication

393   Written informed consent was obtained from the participants and all authors for publication of

394   this case report.

Availability of data and materials

396   NanoTime is available on GitHub (https://github.com/renzilin/NanoTime), NASTRA is under GPL

397   v3.0 license and is publicly available on GitHub (https://github.com/renzilin/NASTRA).

Competing interests

399   Not applicable.

Funding

401   Not applicable.

Authors' contributions

ZR developed the computational method, conducted all data analysis and drafted the manuscript. JZ and TY conducted all wet laboratory experiments, including DNA extraction, amplification, and MiSeq FGx and Nanopore sequencing. YZ conducted the test of computational test. PS revised the manuscript. JX revised the manuscripts. JY provided DNA samples and provided guidance on the study. MN offered advice and guidance on the study, and revised the manuscript. All authors approved the manuscript.

Acknowledgements

The authors would like to thank Dr. JinDing Liu, Dr. Fenglong Yang, and Dr. Juan Jia from Shanxi Medical University and Dr. Xu Liu for valuable comments of this study and support.

References

1. Chakraborty R, Stivers DN, Su B, Zhong Y, Budowle B. The utility of short tandem repeat loci beyond human identification: Implications for development of new DNA typing systems. ELECTROPHORESIS. 1999;20:1682–96.

2. Butler JM. Genetics and genomics of core short tandem repeat loci used in human identity testing. J Forensic Sci. 2006;51:253–65.

3. Masters JR, Thomson JA, Daly-Burns B, Reid YA, Dirks WG, Packer P, et al. Short tandem repeat profiling provides an international reference standard for human cell lines. Proceedings of the National Academy of Sciences. 2001;98:8012–7.

4. Dirks WG, Faehnrich S, Estella IAJ, Drexler HG. Short tandem repeat DNA typing provides an international reference standard for authentication of human cell lines. ALTEX. 2005;22:103–9.

5. Matsuo Y, Nishizaki C, Drexler HG. Efficient DNA fingerprinting method for the identification of cross-culture contamination of cell lines. Hum Cell. 1999;12:149–54.

6. Phillips C, Fondevila M, García-Magariños M, Rodriguez A, Salas A, Carracedo Á, et al. Resolving relationship tests that show ambiguous STR results using autosomal SNPs as supplementary markers. Forensic Science International: Genetics. 2008;2:198–204.

7. Kayser M, de Knijff P. Improving human forensics through advances in genetics, genomics and

molecular biology. Nat Rev Genet. 2011;12:179–92.

8. Ruitberg CM, Reeder DJ, Butler JM. STRBase: a short tandem repeat DNA database for the

human identity testing community. Nucleic Acids Research. 2001;29:320–2.

9. Freedman LP, Gibson MC, Ethier SP, Soule HR, Neve RM, Reid YA. Reproducibility: changing the

policies and culture of cell line authentication. Nat Methods. 2015;12:493–7.

10. Yu M, Selvaraj SK, Liang-Chu MMY, Aghajani S, Busse M, Yuan J, et al. A resource for cell line

authentication, annotation and quality control. Nature. 2015;520:307–11.

11. Bairoch A. The Cellosaurus, a Cell-Line Knowledge Resource. J Biomol Tech. 2018;29:25–38.

12. Dirks WG, MacLeod RAF, Nakamura Y, Kohara A, Reid Y, Milch H, et al. Cell line cross-

contamination initiative: an interactive reference database of STR profiles covering common

cancer cell lines. Int J Cancer. 2010;126:303–4.

13. Romano P, Manniello A, Aresu O, Armento M, Cesaro M, Parodi B. Cell Line Data Base:

structure and recent improvements towards molecular authentication of human cell lines.

Nucleic Acids Res. 2009;37:D925-932.

14. Robin T, Capes-Davis A, Bairoch A. CLASTR: The Cellosaurus STR similarity search tool - A

precious help for cell line authentication. Int J Cancer. 2020;146:1299–306.

15. Faria NR, Quick J, Claro IM, Thézé J, de Jesus JG, Giovanetti M, et al. Establishment and

cryptic transmission of Zika virus in Brazil and the Americas. Nature. 2017;546:406–10.

16. Quick J, Loman NJ, Duraffour S, Simpson JT, Severi E, Cowley L, et al. Real-time, portable

genome sequencing for Ebola surveillance. Nature. 2016;530:228–32.

17. Hamner S, Brown BL, Hasan NA, Franklin MJ, Doyle J, Eggers MJ, et al. Metagenomic Profiling

of Microbial Pathogens in the Little Bighorn River, Montana. International Journal of

Environmental Research and Public Health. 2019;16:1097.

18. Boykin LM, Sseruwagi P, Alicai T, Ateka E, Mohammed IU, Stanton J-AL, et al. Tree Lab:

Portable Genomics for Early Detection of Plant Viruses and Pests in Sub-Saharan Africa. Genes.

2019;10:632.

19. Zaaijer S, Gordon A, Speyer D, Piccone R, Groen SC, Erlich Y. Rapid re-identification of human

samples using portable DNA sequencing. Elife. 2017;6:e27798.

20. Fang L, Liu Q, Monteys AM, Gonzalez-Alegre P, Davidson BL, Wang K. DeepRepeat: direct

quantification of short tandem repeats on signal data from nanopore sequencing. Genome Biol.

2022;23:108.

21. Liu Q, Zhang P, Wang D, Gu W, Wang K. Interrogating the "unsequenceable" genomic

trinucleotide repeat disorders by long-read sequencing. Genome Med. 2017;9:65.

22. Giesselmann P, Brändl B, Raimondeau E, Bowen R, Rohrandt C, Tandon R, et al. Analysis of

short tandem repeat expansions and their methylation state with nanopore sequencing. Nat

Biotechnol. 2019;37:1478–81.

23. Ren Z-L, Zhang J-R, Zhang X-M, Liu X, Lin Y-F, Bai H, et al. Forensic nanopore sequencing of

STRs and SNPs using Verogen's ForenSeq DNA Signature Prep Kit and MinION. Int J Legal Med.

2021;135:1685–93.

24. Tytgat O, Škevin S, Deforce D, Van Nieuwerburgh F. Nanopore sequencing of a forensic

combined STR and SNP multiplex. Forensic Sci Int Genet. 2022;56:102621.

25. Tytgat O, Gansemans Y, Weymaere J, Rubben K, Deforce D, Van Nieuwerburgh F. Nanopore

Sequencing of a Forensic STR Multiplex Reveals Loci Suitable for Single-Contributor STR Profiling.

Genes (Basel). 2020;11:381.

26. Asogawa M, Ohno A, Nakagawa S, Ochiai E, Katahira Y, Sudo M, et al. Human short tandem

repeat identification using a nanopore-based DNA sequencer: a pilot study. J Hum Genet.

2020;65:21–4.

27. Hall CL, Kesharwani RK, Phillips NR, Planz JV, Sedlazeck FJ, Zascavage RR. Accurate profiling of

forensic autosomal STRs using the Oxford Nanopore Technologies MinION device. Forensic Sci Int

Genet. 2022;56:102629.

28. Lang J, Xu Z, Wang Y, Sun J, Yang Z. NanoSTR: A method for detection of target short tandem

repeats based on nanopore sequencing data. Front Mol Biosci. 2023;10:1093519.

29. Daily J. Parasail: SIMD C library for global, semi-global, and local pairwise sequence

alignments. BMC Bioinformatics. 2016;17:81.

30. Li H. Minimap2: pairwise alignment for nucleotide sequences. Bioinformatics. 2018;34:3094–

100.

31. Li H. New strategies to improve minimap2 alignment accuracy. Bioinformatics.

2021;37:4572–4.

32. Danecek P, Bonfield JK, Liddle J, Marshall J, Ohan V, Pollard MO, et al. Twelve years of

SAMtools and BCFtools. GigaScience. 2021;10:giab008.

Figures

a

Figure 1. Overview of the study design. **a** Nanopore sequencing were conducted on collected 84

individual samples (88 DNA samples) with different amplification methods and flow cells. With

ForenSeq data and PowerSeq data, we optimized the parameters of NASTRA, and conduted

performance evalutaion and real-time scenario tesing. **b.** The workflow of NASTRA: 1. Extracing

aligned reads from bam file; 2. Flanking regions of each read are trimmed; 3. Reads clustering are

performed to find candidate allele sequences; 4. Repeat structure of each allele is inferred by the

recursive inference algorithm; 5. Genotype calling.

Figure 2. Parameter optimization using downsampled data. **a.** The best accuracy of NASTRA on

each locus when supporting reads number (SN) is fixed. **b.** The genotype calling accuracy of

NASTRA on each locus with different ratios of supporting reads number (SNR), when SN is 25. **c.**

The distribution of genotyping result across downsampled data. **d.** The blast identity distribution

of alleles between NASTRA and truth.

Figure 3. Performance evaluation on the test set of ForenSeq data. **a.** Accuracy comparsion of

NASTRA and STRspy on ForenSeq data for 27 STR loci. **b.** The deviation of genotypes between

NASTRA and ground truth. **c.** The correlation of SN and sequencing depth (blue points represent

other loci). **d.** The difference of sequencing depth among genotyping result.

Figure 4. Performance evaluation on the test set of PowerSeq data. **a.** Overview of genotyping

results across 46 samples on 22 autosomal STRs sequenced by R10.3 flow cells. **b.** Accuracy

comparsion of NASTRA and STRspy on PowerSeq data for 22 STR loci. For D19S433, the allele

information is missing in STRspy custom database. **c.** The deviation of genotypes between

NASTRA and ground truth.

Figure 5. Performance on real-time scenario tesing. **a.** overview of genotyping results obtained

from 8 DNA standard samples across 27 autosomal STRs, with variations in sequencing durations,

using a R9.4.1 flow cell. **b.** The percentages of genotyping results achieving exact match,

incomplete match or imbalance/interpretation across all 8 samples, with different sequencing

durations. **c.** The distribution of sequencing depth in relation to different sequencing durations.

523   **Figure 6.** The schematic representation of the recursive algorithm for repeat structure inference.

Tables

525   Table 1. Runtime comparison under the same thread count (8 threads).

Data Source	Number of samples	Total reads	Total bases (Mb)	NASTRA (sec)	STRspy (sec)
ForenSeq + Guppy hac (24 hours)	16	5,722,882	1846.1	50.6	3605
	17	5,471,350	1805.6	62.1	3954
	23	4,024,251	1133.7	44.8	2690
	24	2,944,237	858.9	37.1	1664
PowerSeq + Guppy hac (24 hours)	24	4,398,698	1026.9	41.2	7481
	24	4,897,877	1281.1	48.4	6553
8 human cell lines (24 hours)	8	5,013,171	1348.7	39.0	2422

526