Acoustic inspired brain-to-sentence decoder for logosyllabic language

Chen Feng[1,2,3,4,*], Lu Cao[1,*], Di Wu[1,2,*], En Zhang[5], Ting Wang[6,7], Xiaowei Jiang[8],

Chenhao Zhou[9], Jinbo Chen[1,2], Hui Wu[1,2], Siyu Lin[1,2], Qiming Hou[1,2],

Chin-Teng Lin[8], Junming Zhu[3,#], Jie Yang[1,2,#], Mohamad Sawan[1,2,#], Yue Zhang[1,#]

Author affiliations:

[1]School of Engineering, Westlake University, Hangzhou, Zhejiang Province, China

[2]Center of Excellence in Biomedical Research on Advanced Integrated-on-chips Neurotechnologies (CenBRAIN), School of Engineering, Westlake University, Hangzhou, China

[3]Department of Neurosurgery, Zhejiang University School of Medicine Second Affiliated Hospital, Hangzhou, Zhejiang Province, China

[4]Qiushi Academy for Advanced Studies (QAAS), Zhejiang University, Hangzhou, China

[5]State Key Laboratory of Cognitive Neuroscience and Learning, Beijing Normal University, Beijing, China

[6]School of Foreign Languages, Tongji University, Shanghai, China

[7]Center for Speech and Language Processing, Tongji University, Shanghai, China

[8]Australian AI Institute, School of Computer Science, Faculty of Engineering and Information Technology, University of Technology Sydney, Sydney, Australia

[9]Department of Psychology, New York University, State of New York, USA

[*] These authors contributed equally to the work.

[#]Corresponding authors

Corresponding authors:

Junming Zhu, dr.zhujunming@zju.edu.cn

Jie Yang, yangjie@westlake.edu.cn

Mohamad Sawan, sawan@westlake.edu.cn

Yue Zhang, zhangyue@westlake.edu.cn

Abstract

Many severe neurological diseases, such as stroke and amyotrophic lateral sclerosis, can impair or destroy the ability of verbal communication. Recent advances in brain-computer interfaces (BCIs) have shown promise in restoring communication by decoding neural signals related to speech or motor activities into text. Existing research on speech neuroprosthesis has predominantly focused on alphabetic languages, leaving a significant gap of logosyllabic languages such as Mandarin Chinese which are spoken by more than 15% of the world population. Logosyllabic languages pose unique challenges to brain-to-text decoding due to extended character sets (e.g., 50,000+ for Mandarin Chinese) and complex mapping between characters and pronunciation. To address these challenges, we established a speech BCI designed for Mandarin, decoding speech-related stereoelectroencephalography (sEEG) signals into coherent sentences. We leverage the unique acoustic features of Mandarin Chinese syllables, constructing prediction models for syllable components (initials, tones, and finals), and employ a language model to resolve pronunciation to character ambiguities according to the semantic context. This method leads to a high-performance decoder with a median character accuracy of 71.00% over the full character set, demonstrating huge potentials for clinical application. To our knowledge, we are the first to report brain-to-sentence decoding for logosyllabic languages over full character set with a large intracranial electroencephalography dataset.

Key words: Stereoelectroencephalography (sEEG); Brain-Computer Interface (BCI); Logosyllabic language; Acoustic feature; Neural Networks

Main

Numerous grave neurological conditions, including stroke and amyotrophic lateral sclerosis, may result in individuals entirely losing their capacity to verbal communicate[1,2]. Previous speech neuroprosthesis effort has demonstrated the potential to restore communication for speech-impaired patients[3], particularly within the scope of alphabetic linguistic systems (e.g., English and Dutch), by establishing a mapping between text output and different activities related brain signals, such as hand-writing[4], spelling[5-7], typing[8,9], and speech[10-14]. While such attempts have shown promise, no existing research has reported investigation on logosyllabic languages, such as Chinese and Thai language, for which the speaking population is more than 1.3 billion[15]. In contrast to the alphabetic languages, where words are constructed from combinations of limited size alphabets (e.g., 26 for English), logosyllabic languages employ logographic characters to represent either entire words or single morphemes, which cannot be typed or spelled out directly. Moreover, logosyllabic languages such as Mandarin Chinese have an extensive inventory of over 50,000 logographic characters[16,17], each with its unique, complex glyph. For example, the English word "cat" is represented by a single character "猫" in Mandarin, and "hot" is denoted as "热". This complexity renders the decoding of handwriting via BCIs exceedingly challenging for such languages. Considering the fact that Mandarin pronunciation is mostly detached from its glyphs, we seek a viable solution to bypass the curse of logographic systems via decoding the pronunciation of characters.

We consider *Pinyin*[18], a widely adopted phonetic representation system based on the

Latin alphabet, as the foundation for a neuroprosthesis for Mandarin speech decoding.

Pinyin has been developed to facilitate literacy and serve as a bridge between Mandarin

pronunciation and characters[19]. It adopts a single combination of initials (initial

consonant of a Chinese syllable), finals (simple or compound vowel of a Chinese

syllable), and tones (pitch variation at the syllable level) to multiple Mandarin Chinese

characters[20]. For instance, the combination of initial 't' ([tʰ]), final 'a' ([a]) and a high-

level tone (Tone 1) can be mapped to both '他' (tā, [tʰa], he) and '塌' (tā, [tʰa],

breakdown), which are homophones. The total number of *Pinyin* syllables (excluding

variations in tone), amounts to 407. Each syllable can be combined with 4 different

tones, introduces additional intricacy to speech decoding since the alterations in a tone

of one syllable can lead to a significant shift in its semantic meaning[21]. Due to

ambiguity in mapping *Pinyin* into characters, the surrounding context plays a pivotal

role in identifying the correct character in a sentence.

We propose a Mandarin Chinese BCI system that achieves the conversion of speech-

related brain signals into sentences by decoding the pronunciation of *Pinyin* syllables.

Unlike some existing work, which covers only part of the vocabulary, our system can

handle the full set of Chinese characters, despite being trained with only 407 syllables.

This system comprises three acoustic inspired syllable element prediction models (for

the initial, tone, and final, respectively) and a language model. The former identifies

the pronunciation syllables corresponding to brain signals, while the latter,

incorporating context and semantics, converts syllable sequence into a complete

sentence with practical meanings.

Most previous studies on language prosthesis use Electrocorticography (ECoG)

electrodes[6,11,13,22-24] or Utah array electrodes[4,10,25] to acquire cortical signals. However,

some studies show that the subcortical signals have potential to enhance the

effectiveness of decoder[26,27]. The current study utilized stereo-EEG to capture both

cortical and subcortical neural signals simultaneously from four participants (two males

and two females, all young native Mandarin speakers) undergoing intracranial

monitoring for epilepsy (Fig. 1a). For training the model, participants were instructed

to read 407 monosyllabic characters, which correspond to the 407 distinct *Pinyin*

syllables (the upper panel in Fig. 1b). These 407 syllables are specially designed to

contain all the initial and final pairs, so the pronunciation of almost all Mandarin

Chinese characters is included. Additionally, the participants read 100 Mandarin

sentences varying in length from two to more than ten characters (the lower panel of

Fig. 1b), for evaluating the performance current speech BCI.

Trained using such data, the BCI system achieved the direct decoding of brain activity

directly into text sentence of logosyllabic language, where the sentences are highly

unconstrained and free from the limitations imposed by the training data, potentially

enabling the reconstruction of free language expression in patients who have lost the

ability of verbal communication. Furthermore, we found that the performance of this

acoustic-inspired decoder is driven by both cortical and subcortical signals.

Result

Fig. 1 | The pipeline and performance of the brain-to-sentence decoder designed

for logosyllabic language decoding. a, After the electrodes were implanted,

participants took part in the study on the wheelchair, speaking aloud the content

displayed on a screen. Audio data was collected using a directional microphone, and

neural signals were simultaneously recorded using a multi-channel electrophysiological

recording system. **b,** Two tasks designed for collecting training used data (upper panel,

407 *Pinyin* syllables cover almost all Mandarin Chinese characters) and evaluating used

data (lower panel, 100 sentences ranging from 2 to over 10 characters in length). **c,** The

distribution of selected decoding channels across participants is illustrated on the

standard Montreal Neurological Institute (MNI) template brain. Each participant's

channels are denoted by distinct colors, with directional indicators provided for clarity.

d, A three-phase decoder, including channel selection, syllable elements prediction and

language model correction, is designed to output whole Mandarin Chinese sentences

by decoding speech related sEEG signals. **e,** The distribution of decoding accuracy of

100 test samples (Data from participant 1). Outlines are kernel density estimates of the

distributions. **f,** The decoding accuracy (mean ± s.e.m.) of all evaluating samples, which

is the average of the proportion of correct characters in each sample. **g,** The character-

level accuracy (mean ± s.e.m.) of sentences composed of different lengths. **h,** The

comparison of decoding accuracy of characters appeared in the training reading corpus

(Included) and those absent (Excluded) with the number of correctly decoded characters

displayed on the corresponding bar. The significance was calculated by bootstrapping.

Overview of decoder design. For each participant, we used signal from the selected

channels associated with speech and excluded those located in visual cortex and white

matter (Fig. 1c). A three-phase (channel selection, syllable elements prediction and

language model) decoder were proposed for decoding the neural signal to the complete

sentences (Fig. 1d). During the syllable elements prediction phase, three convolutional

neural networks (CNNs) were trained to extract features representing the initials, tones

and finals from the preprocessed sEEG signal segments of the syllables being spoken.

For each syllable, we aligned the tone and final features with acoustic features extracted

from the corresponding audio signal using neural-audio regularization (NAR). Initial

features were mapped into articulatory features, with their relationships further refined

by a graph neural network (GNN). In the evaluating process of decoding complete

sentences, we used the above three trained models to predict initial, tone, and final

syllable by syllable, and finally formed a probability sequence. In the third phase, a

language model was established to output the most probable sentence based on the

probability sequence of predicted elements of all syllables. The language model was

trained on encyclopedia-style question-answer dialogues retrieved from Common

Crawl. The probability sequence of top 3 initials, top 3 tones and the leading final

cluster (one final cluster contains several finals with similar acoustic characteristics)

form the output of the three syllable element prediction models. Furthermore, the

language model is capable of translating *Pinyin* sequences into Mandarin sentences,

correcting errors in syllable element predictions, and enhancing the overall

performance of sentence outputs.

Performance of the brain-to-sentence decoder. To fully illustrate the decoding

capability of this system in the natural Mandarin environment, we randomly selected

sentences for daily use ranging in length from 2 characters to more than 10 characters,

taking 10 of each length for a total of 100 test samples. First, we analyzed the

distribution of the average character error rate for each sentence (Fig. 1e).

Supplementary Tab. 1 presents examples of decoded sentences across various character

error rate levels. For participant 1, the median character accuracy is 71.00%, with 30.00%

of the decoded sentences being completely accurate (Fig. 1f). The decoded sentences

exhibit a low error rate and high intelligibility, making them both meaningful and viable

for practical applications.

We calculated the character-level decoding accuracy and found that the average

accuracies for the four participants were 66.62%, 51.37%, 46.34%, and 47.56%,

respectively (Fig. 1g). Notably, sentences of moderate length (about 4-8 characters)

yielded higher accuracies. Conversely, the accuracy for decoding shorter phrases of 2-

3 characters was lower, primarily due to the lack of sufficient linguistic context. This

limitation hindered the model's ability to distinguish between phrases with identical

pronunciations but different meanings, such as '前沿' and '前言', with the same *Pinyin*

syllable (qián yán) and different meanings (frontier and preface, respectively). We

verify that the generalization performance of the model is strong, and it can solve the

parts not covered by the training data in tens of thousands of Mandarin Chinese

characters (Fig. 1h), which also highlights the effectiveness of our acoustic inspired

decoding strategy.

Fig 2. | Design motivation and performance of initial prediction model. a, Articulatory descriptions of the initials 't' and 'm' characterize acoustic-phonetic features (on the left). Within the dynamic articulation process, the gray section denotes the occlusive phase of articulation, while the blue section indicates the release phase. The multiple acoustic-phonetic features are combined to describe these two phonemes (on the right). **b,** The correlation between specific initials and the average of their corresponding category is visualized through a series of heat maps, where the color representing each initial is matched to the color of its category. **c,** Prediction accuracy (mean ± s.e.m.) of four initial features for four participants. **d,** The initial prediction model utilizes a Graph Neural Network (GNN) to integrate various acoustic-phonetic features. This Articulation Attribute Integration (AAI) approach effectively captures the complex interactions of voicing features to accurately map neural signals onto these feature spaces. **e,** The prediction accuracy (mean ± s.e.m.) of initial was measured for four participants (AAI) and compared with scenarios where acoustic-phonetic feature labels were shuffled (CNN + Shuffled) and against the performance obtained from the support vector machine (SVM). **f,** The probabilities (mean ± s.e.m.) of the correct initial being included in the top 1, top 2, and top 3 probability sequence.

Design and performance of initial prediction model. In the Mandarin Chinese *Pinyin* system, the initial consonant is termed initials, and there are a total of 21 distinct initials. The articulation of initials is produced by overcoming the obstruction of airflow as it passes through the oral or nasal cavity. Four features, place of articulation (POA,

including bilabial, labiodental, alveolar, retroflex, alveolo-palatal and velar), manner of

articulation (MOA, including plosive, affricate, fricative, nasal and lateral), devoice

(including voiced and voiceless) and aspiration (including unaspirated and aspirated)

uniquely describe the articulation process of each Mandarin initial consonants

(Supplementary Table 2). Figure 2a shows the articulation process and corresponding

articulation features of two initials, which is 't' ([tʰ]) and 'm' ([m]).

To assess the similarity in neural activity during the articulation of initials sharing

common features, we analyzed the correlation between specific initials and the average

of their corresponding category (Fig. 2b). Our findings revealed a positive correlation

for place of articulation (POA: $r = 0.52$), manner of articulation (MOA: $r = 0.54$),

devoicing ($r = 0.49$), and aspiration ($r = 0.59$). This correlation is visually represented

by four diagonal lines across the heatmap for each feature. Moreover, the correlation is

significantly higher than that with irrelevant articulation features ($P < 0.001$ for POA,

MOA, devoice and aspiration). indicating that the sEEG signals captured distinct

information related to categorical articulation features. To further explore this, we

developed classification models to decode these four articulatory features from the

sEEG signals of each initial's trial (Fig. 2c). The classifiers demonstrated that the sEEG

signals contained significant information about these features, with decoding accuracies

substantially surpassing the chance level for all participants.

Building upon these insights, we build the initial prediction model by identifying the

acoustic-phonetic features (Fig. 2d, details in method). We first map the neural signals

to representations in the acoustic-phonetic feature spaces of POA, MOA, aspiration and

devoice. Given that the voicing of initials results from the interactions among diverse

voicing features, we address this inherent relationship with a GNN as an articulation

attribute integration (AAI). As a result, the accuracy rates from the model are

significantly above the chance level for the four participants ($P < 0.001$, Fig. 2e),

achieving rates of 41.07%, 21.10%, 30.32%, and 14.65%, respectively, where the

chance level is 5%. However, the sole prediction result from the model is evidently

insufficient in accuracy for input into the language model for sentence transformation.

Therefore, we calculated the accuracy considering multiple candidate outputs from the

model. Notably, there was a significant increase in prediction accuracy as the number

of candidate results grew ($P < 0.001$). In the top 3 most probable predictions, the

probability of containing the correct initial for the four participants was 99.24%,

97.12%, 98.39%, and 95.03%, respectively (Fig. 2f). In summary, the initial prediction

model can identify accurate initial results in most trials based on sEEG signals from

selected channels, and its near-perfect top-3 accuracy narrows the possible initial

candidates from 21 down to 3. This reduces the computational burden on the third phase

of the decoder and enhances the efficiency of the selection process of language model.

Fig. 3 | Design and performance of tone and final cluster prediction models. a,

Examples of the display of Mel-frequency spectrograms and pitch curves for the four

tones, with data sourced from participant 1. **b,** Based on pitch feature extracted from

audio signal, a SVM model was used to classify the four tones (participant 1). **c,** The

visualization results of the Formant features for six single finals are shown. Since the

formants are relatively stable during the articulation of single finals, the average value

of the entire process is used to represent the corresponding formant feature. Dots of the

same color represent different samples of the same single final, with the larger dot in

the corresponding color representing the average of all the dots. **d,** Based on formant

features extracted from audio data, a SVM model was used to classify the six single

finals (participant 1). **e,** Based on formant features extracted from audio data, a SVM

model was used to classify the 35 finals (participant 1). Finals of the same color were

clustered into the same category using the k-means clustering method. **f,** The dynamic

changes of Formant 1 and Formant 2 during the articulation process of four phonetically

similar finals ('o', 'u', 'ou', and 'uo') are depicted (mean ± s.e.m.). **g,** Based on formant

features extracted from audio data, a SVM model was used to classify the eleven final

clusters (participant 1). **h,** The model design for tone and final cluster prediction. This

approach aligns the distribution of sEEG data in the neural space with the audio data

distribution, especially in terms of pitch and formant features, to improve the extraction

of neural features for tone and final cluster categorization. Particularly, we employed a

neural-audio regularization (NAR) term, based on similarity measurements, alongside

the categorical cross-entropy loss during the training of the model. **i,** The prediction

accuracy of tone was measured for four participants and compared with scenarios where

acoustic-phonetic feature labels were shuffled (Shuffled) and against a baseline of

accuracy (Chance). **j,** The probabilities (means ± s.e.m.) of the correct tone being

included in the top 1, top 2, and top 3 prediction results for each of the four participants.

k, The prediction accuracy of final cluster was measured for four participants and

compared with scenarios where acoustic-phonetic feature labels were shuffled

(Shuffled) and against a baseline of accuracy (Chance). **l,** The probabilities (means ±

s.e.m.) of the correct final cluster being included in the top 1, top 2, and top 3 prediction

results.

Design and performance of tone prediction model. Tone, a crucial aspect of

Mandarin syllables, differentiates both lexical and grammatical meanings through

variations in pitch carried by the finals[21,28]. We visualized the pitch changes over time

for the four Mandarin tones (Fig. 3a), highlighting their distinct patterns and stability

across trials of the same tone. To distinguish these tones quantitatively based on pitch

variations, we employed a support vector machine (SVM) classifier trained on pitch

data from all trials, regardless of the rhymes on which the tones were borne. The four

different tones can be distinguished from the perspective of pitch variations, and the

values on the diagonal are significantly higher than the off-diagonal values in Fig. 3b

($P = 0.017$). The final classification accuracy was 57.51%, significantly above the

chance level ($P < 0.001$). Consequently, we incorporated pitch into the training process

of the tone prediction model (Fig. 3h, details in method). Aligning the distribution of

sEEG data in the neural space with the distribution of audio data, particularly

concerning pitch features, enhances the extraction of neural features for tone

categorization. We incorporate a neural-audio regularization (NAR) term based on

similarity measurement in addition to the categorical cross-entropy loss during model

training. Audio signals will solely be utilized in the decoder training process and not

during evaluating.

The incorporation of NAR significantly enhanced the model's performance, yielding

prediction accuracies of 50.60%, 52.75%, 41.19%, and 38.48% for the four participants,

respectively, all markedly above the chance level ($P < 0.001$ for all, as shown in Fig. 3i). These accuracies also surpassed those of models trained without NAR, highlighting NAR's importance. Given that a single prediction may not capture all correct tones, we adopted a strategy of selecting the top 3 most probable tones for each prediction. This adjustment significantly improved the accuracy of the final sentence predictions, with the correct tones being included in the top 3 predictions with probabilities of 90.77%, 97.66%, 87.21%, and 84.76% for the participants, respectively (Fig. 3j). Importantly, this probabilistic information about the tones is also conveyed to the language model, providing it with richer reference data for more accurate sentence generation.

Design and performance of final prediction model. Mandarin syllables comprise 6 simple and 29 compound finals , whose articulation involves vocal cord vibration and nuanced tongue positioning. The frequency spectrum's formant features, F1 and F2, correspond to the tongue's vertical and anteroposterior positions, respectively. We visualized the formant features F1 and F2 for all trials of six simple finals, revealing a clear clustering effect (Fig. 3c). An SVM classification model trained on F1 and F2 successfully differentiated the audio of the 6 simple finals, achieving a classification accuracy of 66.35%, significantly surpassing the chance level ($P < 0.001$ Fig. 3d).

However, once the compound finals were incorporated, the classification results deteriorated (15.46%, compared to the chance level, $P = 0.14$, Fig. 3e). This decline in performance can be attributed to the dynamic nature of compound finals articulation,

which involves transitioning from one articulatory shape to another. For instance, we visualized the changes in F1 and F2 during the articulation of the simple finals 'o' and 'u' alongside the compound finals 'ou' and 'uo' (Fig. 3f). The compound final 'ou' is articulated by transitioning from the sound of 'o' to 'u', while 'uo' undergoes the opposite transition, making their articulatory configurations exceedingly similar and hence challenging to distinguish. Therefore, based on the resonance peaks of the finals in the audio, we employed the k-means algorithm to cluster finals with similar articulatory configurations, ultimately forming 11 distinct finals clusters (Fig. 3e). The SVM classification models were used to identify the final clusters, achieving an accuracy of 40.86%, which is significantly higher than the chance level ($P = 0.013$, Fig. 3g).

Extracting the formant features from audio has proven beneficial for classifying final clusters. Therefore, we also employed the model used to predict tones with NAR to predict the final clusters based on sEEG signals (Fig. 3h, details in Method). Despite the finals' complexity, the model demonstrated accuracies of 25.10%, 19.02%, 20.04%, and 17.33% across participants, all statistically significant against the chance level. As the number of candidate clusters increased, the probability of including the correct final also rose (Fig. 3i). The inclusion of multiple finals within a single predicted cluster aimed to reduce the selection burden in the decoder's third phase, acknowledging that the precision of initials and tones predominantly conveys the necessary information for accurate sentence prediction in Mandarin, thus mitigating the impact of less accurate final predictions.

Fig. 4 | The decoding accuracy and contributions of each anatomical area. a, The

prediction accuracy of initial, tone and final cluster using neural signals from cortical

and subcortical brain structures. Accuracy data are means ± S.D., and the results were

presented for only 3 participants (1, 3 and 4), as no chosen electrodes of participant 2

were in the subcortical brain structures. **b,** The prediction accuracy (means ± S.D.) of

initial, tone and final cluster using neural signals from different anatomical areas in

cortical and subcortical structures of right and left hemispheres of the brain. The regions

of the brain where the electrodes were located were different for four participants. Only

the results of some important language-related anatomical area are selected to show.

STG: superior temporal gyrus, MTG: middle temporal gyrus, ITG: inferior temporal

gyrus, postCen: postcentral gyrus, preCen: precentral gyrus, INS: insula, Tha: thalamus,

Hipp: hippocampus, Amyg: amygdala, PhG: parahippocampal gyrus.

Contributions of different brain regions. In this study, we attempted to independently utilize signals from cortical and subcortical brain regions to predict three syllable elements. Comparative results at the element level were consistent, yet notable variances at the individual participant level emerged (Fig. 4a), indicating that the decoding efficacy is highly dependent on the specific brain regions engaged and the electrode placement. Participant 1 showed enhanced decoding performance with cortical signals, whereas Participant 3 demonstrated better outcomes with subcortical signals. The results for Participant 4 indicated no significant difference between the decoding effectiveness of the signals from these two regions. Overall, this suggests that while cortical regions are influential in speech decoding, the contribution from subcortical regions is also meaningful and should not be overlooked.

To further visualize speech-related information encoded in neural signals from different brain regions, we used signals from the electrodes located in the same regions as input to separately predict the initial, tone, and final cluster. Figure 4b shows the prediction accuracy of three syllable elements from neural signals in different brain regions for four participants. Due to the variation in the brain regions and the number of electrodes implanted in different participants, cross-participant comparisons are not feasible. Results from Patient 1 indicate that within the cortical areas, the Superior Temporal Gyrus (STG), Insula (INS), and the ventral Sensorimotor Cortex (composed of the postcentral gyrus and precentral gyrus, abbreviated as vSMC), exhibit higher decoding

accuracies. This observation aligns with traditional theories of brain region function in

speech production[20,21,] and speech perception[22,23,29-31]. Within the subcortical areas, we

observed that the thalamus exhibited significantly higher accuracy in certain prediction

tasks (such as the initial prediction for participant 3) compared to other brain regions.

Previous research has reported the involvement of the thalamus in human language

processing[32,33]. Our findings further reveal that the thalamus is also engaged in human

speech processing.

Fig. 5 | The analysis of language model and three syllable element prediction

models. a, The element-level accuracy (mean ± s.e.m.) of sentences composed of

different lengths for four participants. **b,** The comparison between element-level

accuracy (mean ± s.e.m.) and the accuracy (mean ± s.e.m.) of three element prediction

models decoding along (Prediction). **c,** The syllable-level accuracy (mean ± s.e.m.) of

sentences composed of different lengths for four participants. **d,** The comparison

between character-level accuracy (mean ± s.e.m.) and syllable-level accuracy (mean ±

s.e.m.). The gray dots represent the accuracies of sentences in different lengths (ranging

from 2 to 10+ characters, with a total of 10 different conditions), where the significance

comparison is conducted using paired t-tests. **e,** Acoustic data and neural signal of

articulation process of fěn. The articulation process is divided into three periods by

phonetics experts. The first is the prearticulatory period (100ms). The second is the

initials articulation period, which is generally shorter in length. The last is the

articulation process of tones and finals. Because the tones are carried on the finals, the

pronunciation process overlaps. According to the theory of phonetics, the articulation

process of initials and finals overlap. This study divides them according to the average

position in the overlapping part. **f,** The temporal saliency on neural signals of three

syllable element prediction models used to identify the initial, tone, and final clusters,

respectively, over the entire duration of a syllable (Blue line, mean ± s.d.). The green

line indicates the appearance span distribution with respect to time for the initial, tone,

and final of all 407 syllables, with the start and end points marked by experienced

phoneticians.

Language models improve decoding accuracy. In this study, the language model is

tasked with selecting the appropriate components to form pinyin syllables from the

probability sequences of the three syllable elements (initials, tones, and finals).

Subsequently, it was required to identify the most appropriate Mandarin Chinese

characters matching each pinyin syllable's pronunciation, thereby constructing

sentences that are both semantically and grammatically coherent.

To enhance the accuracy of this process, we determined that it was necessary to input

the top 3 initials, top 3 tones, and the first final cluster as element possibility sequences

into the language model in the decoder. We calculated the accuracy of the syllable

elements converted from the final output sentences (element-level accuracy), where

each element is selected by the language model from the probability sequences. The

element-level accuracy for the four participants (Fig. 5a) are 80.98%, 66.82%, 64.98%,

and 63.80%, respectively, which are significantly higher than the top 1 accuracy of the

three element prediction models (Fig. 5b). From the aforementioned results, it is evident

that the language model plays a vital role in selecting the correct elements and

correcting erroneous ones, thereby mitigating the accuracy demands placed on the brain

signal decoding component.

Furthermore, to evaluate the language model's proficiency in transforming syllable

sequences into accurate character sequences through semantic integration, we

computed the syllable-level accuracy and compared it with the character-level accuracy.

The syllable-level accuracies for the four participants were 68.93%, 50.52%, 46.68%,

and 44.50%, respectively (Fig. 5c), which closely aligned with the character-level

accuracies (Fig. 5d). This convergence indicates that the language model adeptly

translated nearly all correct syllables into their accurate character counterparts. The few

observed instances of homophone conversion errors, such as '他' (tā, [tʰa], he) and '她'

(tā, [tʰa], she), did not detract from the overall comprehension of the sentences for

native Mandarin speakers. The ability of the language model to convert pinyin and

integrate context plays a decisive role in accurately translating syllable sequences,

enabling it to select the correct characters from a vast array of homophones.

Model attention across time. Acknowledging the challenges posed by the brief and

often ambiguous transitions between the initial and final parts of syllables (Fig. 5e), our

study approaches syllable decoding by treating the neural signals of the entire

articulation process, including a 100ms prearticulatory period, as an integrated unit.

This method allows us to preserve crucial information that might otherwise be lost

during segmentation. We investigate if the temporal focus on the brain signals of the

syllable components (initial, tone, and final) decoding models align with the

vocalization processes of these components as reflected in the corresponding speech

signals by calculating the temporal saliency of the syllable element prediction models.

Our analysis, illustrated in Figure 5f (first panel for initial and mid panel for tone),

shows a strong correlation between the temporal saliency on brain signals and

appearance span distribution with respect to time of these syllable components in terms

of audio data. This suggests that our models can effectively identify and capture syllable

element relevant brain signal segments throughout the articulation process for accurate

prediction. Compared to the initial and tone prediction models with prominent temporal

focus regions, we observed a more uniform distribution in the saliency distribution for

the finals prediction model (Fig. 5f, last panel). This indicates that the finals prediction

model struggles to pinpoint final-related brain signal segments, which in turn, might

explain the model's comparatively lower performance in predicting finals accurately.

Channel contribution. In the first phase of the decoder, the signals from all regions

related to speech are utilized for language decoding. To determine their contribution in

the trained model, we compute a saliency score for each channel as indication of

contribution for syllable components prediction (Supplementary Figure 1).

Subsequently, we also perform a correlation analysis with the decoding accuracy

obtained using channels from individual brain regions as input data. The correlation

between the prediction accuracy for three syllable elements and their contribution in

three prediction models were found to be significant across all four patients

(Supplementary Figure 2).

Discussion

We tackled the challenges posed by the complexity of logosyllabic languages in speech

BCI by taking the speech of individual character syllables as the decoding unit,

achieving the transformation of speech-related brain signals into sentences for

Mandarin Chinese with a promising performance. We show that a training dataset that

includes all 407 valid syllables in Mandarin, suffices for decoding the full Chinese

character set, when combined with a suitable language model. Additionally, we used

monosyllable with tone as the modeling unit because previous unit selection study has

proved that the use of syllable with tone effectively increases the speech recognition

accuracy of Mandarin Chinese compared to other units such as characters or

phonemes[34]. Since around 60~70% of the world's languages are tonal[35], which is not

reflected in the mainstream research on speech BCIs, our study of Mandarin Chinese

contributed fundamental insights to the broader landscape of tonal language interface

design and brain-computer system development.

Recently, numerous language neural prosthetic systems have incorporated language

models as a component of their architecture[10,11]. In this study, we have developed a

language model suitable for Mandarin Chinese speech BCI systems by integrating

Pinyin input with an N-gram model[36]. The capability of the language model for

identifying grammatical Mandarin Chinese text, resolves the ambiguity in

pronunciation to character mapping, and for the *Pinyin* predictor, which in turn

significantly improves the accuracy of the final sentence prediction. While our language

model is intended for open and unrestricted Mandarin Chinese language

communication, it is worth noting that in specific environments and scenarios, such as

in the domestic settings of individuals with disabilities, the language model can be

trained on a restricted, predefined corpus to yield more accurate output results.

Our decision to exclude the decoding of neutral tones was based on the observation that,

aside from a few particles, the majority of neutral tones evolve contextually from their

corresponding full tone counterparts[37]. This evolution alters their phonetic

characteristics depending on the preceding tones in spoken language but remains

unchanged in the written form employed in our research[38]. Nonetheless, future

investigations might delve further into the nuances of neutral tones for a more

comprehensive understanding of their role in Mandarin Chinese BCI research.

We observed notable variations in the decoding performance when distinguishing

between single finals, compound finals, and nasal finals, with the latter two showing

less favorable results. This may be attributed to the finer timing and position properties

of articulatory gestures during a continuous shift of vowels and nasals in compound

finals and nasal finals compared to single finals[39]. Thus, we implemented a k-means

clustering approach, which uses F1 and F2 frequency parameters to classify these non-

single finals into 11 clusters. These clusters share similar acoustic properties and

articulatory patterns, such as 'in' and 'ing,' grouped based on the nucleus in the structure

of finals, as the nucleus bears highest sonority scale[40], for simplifying the decoding

process. These can provide a foundation for further investigations into the complexities

of decoding compound finals and nasal finals in the context of Mandarin Chinese BCI

systems.

Addressing the challenges of mitigating the need for extensive data acquisition to

facilitate cross-day model transfer was beyond the immediate scope of this study.

Nonetheless, this endeavor stands as a pivotal requirement in the development of a

genuinely pragmatic and impactful system. Furthermore, it is essential to verify the

online decoding performance, despite the promising outcomes of our offline analyses.

Recent large language models benefit from extensive training data[41], but combining

data across subjects and time points for neurophysiological signals does not yield

commensurate enhancements due to inherent cross-participant and cross-day variations.

Considering the model adaptation in a lightweight manner to ensure cross-day accuracy

and enhancing decoder performance through the use of multi-subject data, the critical

endeavor of optimizing the efficient utilization of data from diverse days and

individuals remains a key focus for forthcoming research.

Reference

1 Beukelman, D. R., Fager, S., Ball, L. & Dietz, A. AAC for adults with acquired neurological
conditions: a review. *Augment Altern Commun* **23**, 230-242 (2007).

2 Felgoise, S. H., Zaccheo, V., Duff, J. & Simmons, Z. Verbal communication impacts quality
of life in patients with amyotrophic lateral sclerosis. *Amyotroph Lateral Scler*
Frontotemporal Degener **17**, 179-183 (2016).
https://doi.org/10.3109/21678421.2015.1125499

3 Cooney, C., Folli, R. & Coyle, D. Neurolinguistics Research Advancing Development of a
Direct-Speech Brain-Computer Interface. *iScience* **8**, 103-125 (2018).
https://doi.org/10.1016/j.isci.2018.09.016

4 Willett, F. R., Avansino, D. T., Hochberg, L. R., Henderson, J. M. & Shenoy, K. V. High-
performance brain-to-text communication via handwriting. *Nature* **593**, 249-254 (2021).
https://doi.org/10.1038/s41586-021-03506-2

5 Chaudhary, U. *et al.* Spelling interface using intracortical signals in a completely locked-
in patient enabled via auditory neurofeedback training. *Nat Commun* **13**, 1236 (2022).
https://doi.org/10.1038/s41467-022-28859-8

6 Metzger, S. L. *et al.* Generalizable spelling using a speech neuroprosthesis in an individual
with severe limb and vocal paralysis. *Nat Commun* **13**, 6510 (2022).
https://doi.org/10.1038/s41467-022-33611-3

7 Oxley, T. J. *et al.* Motor neuroprosthesis implanted with neurointerventional surgery
improves capacity for activities of daily living tasks in severe paralysis: first in-human
experience. *J Neurointerv Surg* **13**, 102-108 (2021). https://doi.org/10.1136/neurintsurg-
2020-016862

8 Vansteensel, M. J. *et al.* Fully Implanted Brain-Computer Interface in a Locked-In Patient
with ALS. *N Engl J Med* **375**, 2060-2066 (2016). https://doi.org/10.1056/NEJMoa1608085

9 Pandarinath, C. *et al.* High performance communication by people with paralysis using an
intracortical brain-computer interface. *Elife* **6** (2017). https://doi.org/10.7554/eLife.18554

10 Willett, F. R. *et al.* A high-performance speech neuroprosthesis. *Nature* **620**, 1031-1036
(2023). https://doi.org/10.1038/s41586-023-06377-x

11 Metzger, S. L. *et al.* A high-performance neuroprosthesis for speech decoding and avatar
control. *Nature* **620**, 1037-1046 (2023). https://doi.org/10.1038/s41586-023-06443-4

12   Herff, C. *et al.* Brain-to-text: decoding spoken phrases from phone representations in the
579   brain. *Front Neurosci* **9**, 217 (2015). https://doi.org/10.3389/fnins.2015.00217

580 13   Moses, D. A. *et al.* Neuroprosthesis for Decoding Speech in a Paralyzed Person with
581   Anarthria. *N Engl J Med* **385**, 217-227 (2021). https://doi.org/10.1056/NEJMoa2027540

582 14   Moses, D. A., Leonard, M. K., Makin, J. G. & Chang, E. F. Real-time decoding of question-
583   and-answer speech dialogue using human cortical activity. *Nature Communications* **10**,
584   3096 (2019). https://doi.org/10.1038/s41467-019-10994-4

585 15   Chen, N. F., Wee, D., Tong, R., Ma, B. & Li, H. Large-scale characterization of non-native
586   Mandarin Chinese spoken by speakers of European origin: Analysis on iCALL. *Speech*
587   *Communication* **84**, 46-56 (2016).

588 16   Duanmu, S. *The phonology of standard Chinese.* (OUP Oxford, 2007).

589 17   Shen, H. H. & Bear, D. R. Development of orthographic skills in Chinese children. *Reading*
590   *and Writing* **13**, 197-236 (2000). https://doi.org/10.1023/A:1026484207650

591 18   Wang, W. The Chinese Language. *Scientific American* **228**, 50-60 (1973).
592   https://doi.org/10.1038/scientificamerican0273-50

593 19   Tan, L. H., Xu, M., Chang, C. Q. & Siok, W. T. China's language input system in the digital
594   age affects children's reading development. *Proceedings of the National Academy of*
595   *Sciences* **110**, 1119-1123 (2013). https://doi.org/doi:10.1073/pnas.1213586110

596 20   Li, P. & Yip, M. C. Context effects and the processing of spoken homophones. *Reading*
597   *and Writing: An Interdisciplinary Journal* **10**, 223-243 (1998).
598   https://doi.org/10.1023/A:1008091816322

599 21   Lu, J. *et al.* Neural control of lexical tone production in human laryngeal motor cortex.
600   *Nature Communications* **14**, 6917 (2023). https://doi.org/10.1038/s41467-023-42175-9

601 22   Makin, J. G., Moses, D. A. & Chang, E. F. Machine translation of cortical activity to text with
602   an encoder-decoder framework. *Nat Neurosci* **23**, 575-582 (2020).
603   https://doi.org/10.1038/s41593-020-0608-8

604 23   Anumanchipalli, G. K., Chartier, J. & Chang, E. F. Speech synthesis from neural decoding
605   of spoken sentences. *Nature* **568**, 493-498 (2019). https://doi.org/10.1038/s41586-019-
606   1119-1

607 24   Duraivel, S. *et al.* High-resolution neural recordings improve the accuracy of speech
608   decoding. *Nature Communications* **14**, 6938 (2023). https://doi.org/10.1038/s41467-
609   023-42555-1

610 25   Wilson, G. H. *et al.* Decoding spoken English from intracortical electrode arrays in dorsal
611   precentral gyrus. *J Neural Eng* **17**, 066007 (2020). https://doi.org/10.1088/1741-
612   2552/abbfef

613 26   Verwoert, M. *et al.* Dataset of Speech Production in intracranial Electroencephalography.
614   *Scientific Data* **9**, 434 (2022). https://doi.org/10.1038/s41597-022-01542-9

615 27   Angrick, M. *et al.* Real-time synthesis of imagined speech processes from minimally
616   invasive recordings of neural activity. *Communications Biology* **4**, 1055 (2021).
617   https://doi.org/10.1038/s42003-021-02578-0

618 28   Liu, Y. *et al.* Decoding and synthesizing tonal language speech from brain activity. *Sci Adv*
619   **9**, eadh0478 (2023). https://doi.org/10.1126/sciadv.adh0478

620 29   Conant, D. F., Bouchard, K. E., Leonard, M. K. & Chang, E. F. Human Sensorimotor Cortex
621   Control of Directly Measured Vocal Tract Movements during Vowel Production. *J Neurosci*

38, 2955-2966 (2018). https://doi.org/10.1523/jneurosci.2382-17.2018

30   Mesgarani, N., Cheung, C., Johnson, K. & Chang, E. F. Phonetic feature encoding in human
superior temporal gyrus. *Science* **343**, 1006-1010 (2014).
https://doi.org/10.1126/science.1245994

31   Yi, H. G., Leonard, M. K. & Chang, E. F. The Encoding of Speech Sounds in the Superior
Temporal Gyrus. *Neuron* **102**, 1096-1110 (2019).
https://doi.org/10.1016/j.neuron.2019.04.023

32   Klostermann, F., Krugel, L. K. & Ehlen, F. Functional roles of the thalamus for language
capacities. *Frontiers in systems neuroscience* **7**, 32 (2013).

33   Wahl, M. *et al.* The human thalamus processes syntactic and semantic language violations.
Neuron **59**, 695-707 (2008).

34   Fu, L., Li, X. & Zi, L. Research on Modeling Units of Transformer Transducer for Mandarin
Speech Recognition. *ArXiv* **abs/2004.13522** (2020).

35   Yip, M. J. W. *Tone*. (Cambridge University Press, 2002).

36   Parsing, C. Speech and language processing. *Power Point Slides* (2009).

37   Shen, X. S. Mandarin neutral tone revisited. *Acta linguistica hafniensia* **24**, 131-152 (1992).

38   Chao, Y. R. *A grammar of spoken Chinese*. (Univ of California Press, 1968).

39   Cai, S., Ghosh, S. S., Guenther, F. H. & Perkell, J. S. Adaptive auditory feedback control of
the production of formant trajectories in the Mandarin triphthong/iau/and its pattern of
generalization. *The Journal of the Acoustical Society of America* **128**, 2033-2048 (2010).

40   Yavas, M. S. & Gogate, L. J. Phoneme awareness in children: A function of sonority. *Journal*
of psycholinguistic research **28**, 245-260 (1999).

41   Naveed, H. *et al.* A comprehensive overview of large language models. *arXiv preprint*
arXiv:2307.06435 (2023).

METHODS

Participants and task

Study participants. This study enrolled four participants—two females and two males, aged 20, 25, 19, and 19 years for Participants 1, 2, 3, and 4, respectively. They were undergoing epilepsy treatment at the Second Affiliated Hospital of Zhejiang University School of Medicine. As part of their treatment, they had sEEG electrodes surgically implanted (with the number of electrodes being 12, 8, 11, and 13 for Participants 1, 2, 3, and 4, respectively) to monitor epileptic seizures for 1-2 weeks. All participants were native Mandarin Chinese speakers with the left hemisphere identified as the dominant hemisphere for language processing. Prior to data collection, all patients were informed of study procedure and signed informed consent form to participate. The study was approved by the Ethics Committee of the Second Affiliated Hospital of Zhejiang University School of Medicine.

Task design. The design of this Mandarin Chinese Brain-Computer Interface (BCI) system is predicated on decoding the neural signals during the articulation process of Mandarin Chinese characters, ultimately converting them into Mandarin Chinese sentences. Hence, the tasks were specifically tailored for this purpose. We designed two distinct sets of tasks for training and evaluating the BCI system respectively. The first set of tasks involves reading 407 unique Mandarin Chinese characters aloud. Although there are only 407 characters, they encompass all the phonetic syllables of Mandarin Chinese characters. The objective is to enable the system to decode virtually all

Mandarin Chinese characters with as minimal training as possible, achieving a truly

unrestricted Mandarin Chinese decoder. The second set of tasks, aimed at assessing the

performance of the BCI system, employs Mandarin Chinese sentences of varying

lengths as evaluating samples, to closely simulate the performance of this system in

everyday life scenarios.

Task for collecting training data. During the model training data collection phase (as

depicted in Fig 1b, upper panel), participants were required to read 407 Mandarin

Chinese characters corresponding to Mandarin Chinese *Pinyin* syllables with tones,

three to five times (3 to 5 trials per syllable × 407 syllables, depending on the

monitoring duration for different participants). These 407 syllables encompass virtually

all the pronunciations of Mandarin Chinese characters. Moreover, we designed the

study to maintain as balanced a number of syllables as possible across the four tones,

as shown in Supplementary Figure 2. To mimic natural speech patterns closely, each

character was embedded within a carrier sentence by adding fixed characters before and

after the target character. Thus, in every trial, participants read a complete sentence

incorporating the designated syllable. For example, for the target syllable "ài," the

constructed sentence for reading was "我读 爱 三遍" ([ài], translating to "I read love

three times"). All participants were pre-acquainted with the reading materials.

Task for collecting evaluating data. During the data collection process for evaluating

the model (as illustrated in Fig 1b, lower panel), participants were required to read a

total of 100 common Mandarin Chinese sentences, with each word or sentence being

read only once. These 100 samples were divided into 10 groups based on character

length, ranging from 2 characters to more than 10 characters, with each group

containing 10 different samples of the same character length. Participants were

instructed to read aloud character by character at a normal pace, following prompts

displayed on a monitor in front of them. Each character was allotted a reading time of

1.5 to 2 seconds, with a preparatory period of 0.3 to 0.5 seconds before reading each

character. All evaluating data were collected within a single day.

Neural signal

Electrode anatomy localization and visualization. We utilized SPM12 for co-

registering each participant's preoperative T1 MRI with their postoperative CT (which

includes electrode locations). Subsequently, we employed the FreeSurfer neuroimaging

analysis software[42] to reconstruct the pial surface and determine the anatomical

structure where each contact (channel) is located. The standard Montreal Neurological

Institute template brain[43] was used for visualization in Fig. 1c.

Neural signal recoding. The electrode implantation plan, encompassing the location

and number of implants, was devised solely for the treatment of epilepsy. Neural signals

were recorded using a multi-channel electrophysiological recording device, specifically

the Neurofax EEG-1200 produced by Nihon Kohden Corporation, Japan, and were

recorded at a sampling rate of 2000Hz.

Preprocessing of neural signal. The neural signals collected were anti-aliased (low-pass filtered at 200 Hz) and notch filtered at 50 Hz, 100 Hz, 150 Hz, and 200 Hz to eliminate line noise, and channels exhibiting poor quality were excluded. Poor signals were defined as channels with a low signal-to-noise ratio or abnormal recordings identified during the inspection process. And downsampling was not performed during preprocessing. All neural signals were segmented according to task annotations, aligning them with the pronunciation process of individual characters.

Channel selection. To find speech-related channels, we compared the power spectral density (PSD, computed using Welch's method) of neural signals from speech and silence parts within the same trial. For each channel (without channels located in white matter), a paired t-test was conducted to compare the mean PSD values of the speech condition (after speech onset) and silence condition (before speech onset). All resultant p-values were corrected to control the false discovery rate (FDR) using the Benjamini-Hochberg procedure[44]. Finally, channels exhibiting a significant difference ($P < 0.05$) between speech and non-speech conditions were selected. In addition, based on the reconstruction and localization results of all electrodes, certain channels located in the visual cortex (such as those situated in the occipital lobe) were also excluded. This exclusion was implemented to prevent visual-related signals from contributing to the decoding process. The locations of the channels ultimately selected for participation in

the decoding process are displayed in Fig. 1c, with the channels of the four participants

represented in different colors.

Audio signal

Audio recording. Microphone recordings were obtained synchronously with the neural

recordings using a directional microphone (manufactured by Audio-Technica) at

44.1kHz. Given that the recording environment was situated within a hospital ward,

temporary soundproof barriers were erected around the patient to ensure the quality of

the recordings, aiming to isolate them from noise as much as possible (Fig. 1a).

Preprocessing of audio signal. Initially, all audio recordings were manually audibly

reviewed to identify and exclude samples with significant issues affecting recording

quality, such as noticeable noise interference and character pronunciation errors.

Correspondingly, the neural signals associated with these excluded audio samples were

also removed. For training and evaluating the model, the audio data must be labeled,

including the start and end points of each character's pronunciation, as well as the

segmentation points of the initial and final sounds during the pronunciation process of

each character. In this study, we adopted a combination of automatic labeling using

software and expert annotation. All audio materials were first automatically labeled

using the PRAAT software[45], after which all labeling results were verified and finally

confirmed by three phonetics experts.

Analysis of audio signal

Acoustic feature extraction. In the design process of the three element prediction

models, relevant acoustic features were utilized, to enhance the prediction performance.

Specifically, the initial prediction model employed acoustic-phonetic features, which

are attributes inherent to the initials themselves, rather than being related to the recorded

audio signals. Chinese is a tonal language, where speakers can modulate the pitch of

their voice by adjusting the tension of their vocal cords to produce variations in pitch

height and contour, thereby distinguishing different tones to convey various meanings.

In this study, the pitch feature F0 was extracted from the audio signal and applied to the

tone prediction model. The pronunciation characteristics of the final sounds can be

assessed through three formants, with the first two formants being related to the position

of the tongue, making them suitable for use in the final prediction model. Parselmouth[46],

a Python implementation of PRAAT was applied to obtain pitch and formant data[45].

Audio signal classification through support vector machine. In Figure 3, various

results of audio signal classification are presented, where panel b shows the outcomes

of tone classification, panel d illustrates the classification of monophthongs, panel e

displays the classification results for all vowels, and panel g reveals the classification

outcomes for final clusters. All classifications were conducted using a one-against-all

multi-class support vector machine (SVM) algorithm. The following decision function

is employed for classifying $\boldsymbol{x}_{new}$:

778
$$f(\boldsymbol{x}_{new}) = \underset{i \in \{1, \cdots, M\}}{arg\ max} \left[\sum_{support\ vectors} y_t \alpha_t^i k(\boldsymbol{x}_t, \boldsymbol{x}_{new}) + b^i \right], \quad (1)$$

where, the t represents the indexed sample, and $i \in \{1, \cdots, M\}$ denotes the total of M

binary Support Vector Machines (SVMs) that need to be trained, involving the solution

of M quadratic programming problems.

Analysis of neural signals

Neural signals similarity analysis. Figure 2b displays the Pearson correlation between

specific initials and the average of their corresponding category. We discuss two

scenarios based on whether the initial is included in the corresponding category. In the

first scenario, when the i^{th} initial does not belong to the j^{th} category of initials, we

first calculate the average neural signal all trials of the i^{th} initial and the average neural

signal all initials within the j^{th} category. The calculation of the correlation R_j^i is as

follows:

$$R_j^i = corr(\overline{\mu_\iota}, \frac{\sum_{t=1}^{N_j} \overline{\mu_t}}{N_j}), \ i \notin Cluster_j, \tag{2}$$

where, $corr$ represents the Pearson correlation between two sequences, and N_j

denotes the number of initials involved in the j^{th} category. In the second scenario,

where the i^{th} initial belongs to the j^{th} category of initials, to exclude the positive

bias introduced by self-correlation, we randomly divide the N trials of the i^{th} initial

into two groups and calculate their average neural signals, $\bar{\mu}$ and $\tilde{\mu}$, respectively. Then,

we calculate the average of $\bar{\mu}$ for all initials within the j^{th} category. The calculation

of the correlation R_j^i is as follows:

$$R_j^i = corr(\widetilde{\mu_\iota}, \frac{\sum_{t=1}^{N_j} \overline{\mu_t}}{N_j}), \ i \in Cluster_j, \tag{3}$$

Clustering of finals. We cluster similar finals together due to the difficulty of differentiation brought about by dynamic nature of compound finals articulation. We consider a total of cluster number within the range of 10 to 15 to balance the granularity of classification and the classification accuracy. We employed the k-means clustering algorithm with silhouette coefficient to determine the optimal cluster number using the averaged formant features (F1, F2 and F3) across all audio samples of each final class as input, finding the optimal cluster number of 11. We then merge the finals within one cluster as one final cluster.

Decoder performance evaluation

Character error rate (CER). The character error rate (CER) is adopted as a metric to evaluate the performance of our proposed decoder, which is defined as follows:

$$CER_i = \frac{EC_i}{N_i}, \tag{4}$$

where CER_i represents the character error rate for the i^{th} evaluating sample, EC_i denotes the number of characters in the i^{th} decoded result that do not match the ground truth, and N_i indicates the total number of characters in the i^{th} evaluating sample. Naturally, the character-level accuracy (CLA) is defined as:

$$CLA_i = 1 - \frac{EC_i}{N_i}, \tag{5}$$

Syllable-level accuracy. During the evaluation of the performance of language model, syllable-level accuracy (SLA) is used to assess the model's ability to convert pinyin syllables into Chinese characters. SLA is defined as:

$$SLA_i = \frac{AS_i}{N_i}, \tag{6}$$

where SLA_i represents the syllable-level accuracy for the i^{th} evaluating sample, AS_i denotes the number of syllables in the i^{th} decoded result that match the ground truth, and N_i indicates the total number of characters in the i^{th} evaluating sample.

Element-level accuracy. We adopt element-level accuracy (ELA) to evaluate the performance of the language model since it reflects the language model's elements correction capability within a syllable. First, each Chinese character in the decoded word or sentence is converted into a *Pinyin* syllable. Then, the initial, tone, and final components of each decoded *Pinyin* syllable are extracted. We calculate ELA as follows:

$$ELA_i = \frac{1}{3} \cdot \frac{\sum_{j=1}^{n}\left(\mathbb{1}(initial_j)+\mathbb{1}(tone_j)+\mathbb{1}(final_j)\right)}{n}, \tag{7}$$

where ELA_i represents the element-level accuracy for the i^{th} evaluating sample, n represents the total number of characters of the i^{th} evaluating sample, $\mathbb{1}(\cdot)$ is an indicator function with a value of 1 for a correct prediction of the corresponding syllable element and otherwise 0.

Syllable elements prediction

Network architecture. We adopt a simple yet effective plain convolutional neural network (CNN) architecture as the backbone for syllable elements feature extraction. The detailed architecture of the network is provided in Supplementary Table 3. The subjects' pre-processed sEEG of input channels C is first passed to a stem layer containing a 1-D convolution layer. The 1-D convolution layer adopts a kernel size of

$K \times 1$, a stride of S, and an output channel number of 64. The numbers of the kernel

size K and stride of S are adjusted for each subject. Each convolution block consists

of a 1-D convolution layer (followed by a batch normalization layer and a ReLU

activation) and a max pooling layer. The number of the output channel of the first two

blocks is set to 128, while the number of the last two blocks is set to 256. Then, we

adopt a global average pooling layer and a fully connected layer to map the output of

the last block to fit the prediction targets of different syllable elements.

Initial prediction model. We utilize the same CNN architecture **(Network**

architecture part in Method) as the backbone for initial acoustic-phonetic feature

prediction. On top of the learned hidden representation, a 2-layer multilayer perceptron

(MLP) prediction head with a hidden dimension of 256 is utilized to predict the label

of each acoustic-phonetic features of the initial. We follow the same experimental setup

as described in **Experimental setup part** and report the mean and standard deviation

of the top-1 accuracy for each acoustic-phonetic feature.

Inspired by the articulation of each Mandarin initial consonant, we proposed the

articulation attribute integration (AAI) module to better capture the acoustic-phonetic

features during the articulation process. The acoustic-phonetic features include the

place of articulation (POA), manner of articulation (MOA), devoice, and aspiration.

These acoustic-phonetic features can be considered as four attributes associated with

each initial consonant. We first decompose the initial prediction problem into four

attribute categorization subproblems. In particular, we utilize four learnable prototypes

$W^{poa} \in \mathbb{R}^{c_f \times d_{poa}}$, $W^{moa} \in \mathbb{R}^{c_f \times d_{moa}}$, $W^{asp} \in \mathbb{R}^{c_f \times d_{asp}}$, and $W^{dev} \in \mathbb{R}^{c_f \times d_{dev}}$, to

map the neural features extracted by the CNN backbone to representations in the

acoustic-phonetic attribute spaces. c_f denotes the number of output channels of the

CNN model, d_{poa}, d_{moa}, d_{asp}, and d_{dev}, represent the cardinality of the POA,

MOA, devoice and aspiration attributes, respectively. Let $z \in \mathbb{R}^{c_f}$ be the extracted

feature of the CNN; we concatenate the prototypes and perform attribute aggregation

by multiplying with an adjacency matrix $\widetilde{\mathbb{A}}$:

$$\overline{W} = \text{CONCAT}(W^{poa}, W^{moa}, W^{asp}, W^{dev})$$

$$\widetilde{W} = ReLU(\overline{W} \times \widetilde{\mathbb{A}}), \tag{8}$$

where $CONCAT$ denotes the concatenation operation and $\overline{W} \in \mathbb{R}^{c_f \times d}$ where $d =$

$d_{poa} + d_{poa} + d_{poa} + d_{poa}$. The adjacency matrix $\widetilde{\mathbb{A}}$ is defined by adding self-loop

as $\widetilde{\mathbb{A}} = \mathbb{A} + \mathbb{I}$ where $\mathbb{I} \in \mathbb{R}^{d \times d}$ is the identity matrix. $\mathbb{A}_{i,j} = 1$ if the attribute i

and attribute j coexist in the onset process of any initial consonant and $\mathbb{A}_{i,j} = 0$

otherwise. Notice that $\mathbb{A}$ is only initialized by the previous condition and updated

during training. The aggregated prototypes $\widetilde{W}$ are then multiplied with feature vector

z to predict the four attribute labels. A 2-layer multilayer perceptron (MLP) prediction

head with a hidden dimension of 256 is utilized to predict the initial label. The overall

loss function is defined as:

$$\mathcal{L} = \alpha \times \mathcal{L}_{attr} + \mathcal{L}_{init}, \tag{9}$$

where $\mathcal{L}_{attr}$ and $\mathcal{L}_{init}$ stand for categorical cross-entropy loss for attribute

classification and initial classification, respectively. α is a scaler to balance the two

losses.

Tone and final cluster prediction model. In the field of speech processing, the key

factor in tone perception relies on pitch-related features where the fundamental

frequency (F0) plays a crucial role. Likewise, each vowel is distinguished by a unique

set of resonating frequencies of the vocal tract, referred to as formants. Formant features

F1 and F2 correspond to the vertical and anteroposterior positions of the tongue,

respectively, while Formant F3 indicates the tongue's constriction in the palatal region.

The similarity of formant features among different finals serves as a valuable indicator

for measuring the articulation process, which we aim to decode using sEEG. Besides

directly predicting the tone and final using the extracted from CNN, we introduce a

neural-audio regularization (NAR) module, which enhances the CNN's ability to model

the similarity of the articulation process by using formant features as guidance. Let $Z \in$

$\mathbb{R}^{B \times C}$ be the extracted feature from a training batch of sEEG data associated with the

corresponding audio data, where B denotes the batch size. It is worth noting that for

tone prediction, we utilize the F0 feature, while for the final prediction, we use F1, F2,

and F3. Subsequently, we calculate the pairwise Euclidean distance of D_n and D_a for

both Z and F. Following this, we employ the Student's t-distribution for similarity

measurement:

$$S_{i,j} = \frac{\Gamma \times \left(\frac{v+1}{2}\right)}{\sqrt{v\pi} \times \Gamma \times \left(\frac{v}{2}\right)} \times \left(1 + \frac{D_{i,j}^2}{v}\right)^{-\frac{v+1}{2}}, \qquad (10)$$

909 where Γ and v refer to the gamma function and the degree of freedom, respectively.

910 D denotes the Euclidean distance. The objective function to train NAR is defined to be

911   the logistic loss between S_a and S_n:

912
$$\mathcal{L}_{NAR} = -\mathbb{E}_{i,j} \times \left[S_{i,j}^a \times log \frac{S_{i,j}^a}{S_{i,j}^n} + \left(1 - S_{i,j}^a\right) \times log \frac{\left(1 - S_{i,j}^a\right)}{\left(1 - S_{i,j}^n\right)} \right]. \qquad (11)$$

The overall loss function is defined to be a weighted sum of $\mathcal{L}_{NAR}$ and the

corresponding categorical cross-entropy loss for either tone or final prediction.

Experimental setup. The experiments were conducted using PyTorch[47] on NVIDIA

V100 GPUs. For investigating syllable elements level prediction, the data from three

trials were combined and divided into 80% for training and 20% for evaluating, using

20 distinct random seeds. This setup facilitated the calculation of mean and variance

for performance metrics. We carry out experiments on all four subjects with the same

experimental setup. For each subject, 20% of the training data from the first repetition

was allocated for tuning size K and stride of S. The specific choices of kernel size

and stride for each subject are detailed in Supplementary Table 4. The models were

trained using the AdamW optimizer, with a base learning rate of $lr = 0.0003$.

Momentum parameters are set to $\beta_1 = 0.9$, $\beta_2 = 0.009$, and a cosine decay approach

was adopted for the learning rate schedule. To prevent overfitting, a dropout rate of 0.3

was utilized. The training was conducted over 80 epochs, incorporating an early

stopping criterion based on a five-epoch non-improvement threshold on the validation

set. The complete list of parameters used for model training is available in

Supplementary Table 5. For sentence-level performance assessment, syllable element

prediction models were trained on the entire dataset for each subject over a fixed epoch

number of 50.

Elements prediction with support vector machine. In this study, we adopted support

vector machine (SVM) classifiers as baseline performance for syllable elements

prediction. We follow the exact same data split strategy as described in **Experimental**

setup part with the same evaluation metrics to ensure consistency across comparisons.

For training of the SVM classifiers, we adopted the radial basis function (RBF) kernel

with the regularization parameter and the kernel parameter gamma grid searched with

five-fold cross validation on the training set for each random seed. We adopted the one-

vs-the-rest (OvR) strategy for multiclass classification, as previously mentioned in

Audio signal classification through support vector machine part.

Language model

Given a sequence of syllable elements predictions, denoted as $\varepsilon = \left\{ \left(i_i^k,\ t_i^k,\ f_i^k \right) \right\}_{i=1}^N$,

a language model is designed to output the most probable sentence where N represents

the total number of characters in the sentence. The elements i_i^k, t_i^k, f_i^k represent the

top-k predictions for the initial, tone, and final elements of the i^{th} character,

respectively. The model's top-3 accuracy for tone and initial predictions, as shown in

Figure 3j and Figure 2f, reveals that the three most probable predictions often correctly

identify these elements. Our approach involves constructing a 5-gram language model

that evaluates the probability of initial and tone sequences, denoted as $\{(i_i^3, t_i^3)\}_{i=1}^N$,

using the top three predictions for each. The training of this 5-gram model utilized

CLUECorpus2020[48], a comprehensive Mandarin Chinese corpus containing 35 billion

Chinese characters retrieved from Common Crawl. CLUECorpus2020 contains a wide

range of topics, including news, entertainment, sports, health, international affairs,

movies, celebrities, and more. To develop our 5-gram model, we randomly selected 20%

of this training set and implemented the model using KenLM[49]. Instead of employing a

character-based vocabulary, we have constructed a specialized vocabulary comprising

pairs of initials and tones. This approach results in a vocabulary of 84 distinct elements,

derived from 21 initials combined with four different tones. We then utilize the Google

Pinyin API to convert the initials from the top 50 probability sequences into Mandarin

characters, forming sentences. For each initial sequence, we extract two sentence

suggestions, thereby cumulatively creating a total of 100 sentences.

The majority of current Pinyin input methods do not rectify incorrect or illogical initial

sequences. Instead, they endeavor to construct a sentence from the input, often resulting

in combinations of characters that resemble sentences but lack coherent, natural

language meaning. Consequently, it is advantageous to utilize large language models

(LLMs) to determine the most probable sentence out of 100 potential options generated,

harnessing the LLM's capacity to discern coherent and meaningful language from a

multitude of sentence possibilities. In our approach, we utilize the Chinese-LLaMA-7B

model[50] to evaluate the likelihood of different sentence options. Perplexity $\mathcal{PPL}$ of

each sentence candidate is calculated using the following equation:

$$\mathcal{PPL}(\cdot) = e^{-\sum_{i=1}^{N} \log P(ch_i|ch_1, ch_2, \cdots, ch_{i-1})}, \tag{12}$$

where $P(ch_i|ch_1, ch_2, \cdots, ch_{i-1})$ represents the probability assigned by the LLM to

the character ch_i based on the sequence of preceding characters. We then select the sentence with the lowest perplexity as the final output. This method ensures that the output is a grammatically correct sequence of characters and a coherent and contextually appropriate sentence.

Contribution of different anatomical brain regions

We analyze the contribution of brain regions from two distinct perspectives. The first perspective utilizes sEEG signals from single functional brain regions as system inputs for Mandarin Chinese decoding, where the decoding performances of these regions serves as the metric for assessing their contribution level. The second perspective involves using all channels as model inputs, where we determine the contribution of brain regions based on the significance level of different channel signals in the decoding decision channel saliency calculated by class activation maps[51].

The decoding accuracy of different brain regions. We train syllable element prediction models utilizing sEEG signals of channels that cover the specific brain regions that we aim to analyze and report the prediction performance. We follow the same experimental setup as described in Sec. 7.4 for syllable element prediction model and evaluations. This method allowed for a focused investigation of each region's role in the decoding process from the perspective of the prediction performance. We follow the same experimental setup described in **Experimental setup part** for both evaluation approaches.

The contributions of electrodes located in different brain regions to decoding.

Channel saliency score is calculated by class activation maps[51]. Given an sEEG signal

$x_{i,j} \in \mathbb{R}^{T \times C}$ where T is the length of the signal and C is the total number of

channels. We calculate a channel saliency score ζ:

$$\zeta(c) = \frac{1}{T} \times \sum_{i=1}^{T} ReLU(\frac{\partial y}{\partial x_{i,c}}), \tag{13}$$

where y is the one-hot logit vector corresponding to the true label of the underlying

prediction task, and $ReLU$ is the activation function. As illustrated in Equation 6, the

partial derivative is calculated with respect to the input sEEG signal and averaged over

the time dimension. This measure indicates how changes in the information content of

channel c influence the accurate prediction of the true label. We then normalize the

saliency score $\zeta(c)$ for each channel c to be between zero and one. The second

measurement provided a comprehensive understanding of how the change of

information from specific brain regions affects the Mandarin Chinese decoding process,

highlighting the contribution level of each channel when using all-channel sEEG for

language decoding.

Model temporal saliency of syllable prediction models

Similar to the calculation of channel saliency score in Eq. (12), we calculate the

temporal saliency score $\eta(t)$:

$$\eta(t) = \frac{1}{C} \times \sum_{i=1}^{C} ReLU\left(\frac{\partial y}{\partial x_{t,i}}\right), \tag{14}$$

where $x_{t,i}$ refers to sEEG signal of channel i at time stamp t. Different from Eq.

1021 (13), the partial derivative is averaged over the channel dimension.

1022

1023 **Data availability**

1024 The data that support the findings of this study are available from the corresponding

1025 author upon reasonable request. Source data for figures are provided with the paper

1026

1027 **Code availability**

1028 All main code can be found on GitHub at https://github.com/diwu121/sEEG2Chinese.

1029

References

42 Fischl, B. FreeSurfer. *Neuroimage* **62**, 774-781 (2012).
https://doi.org/10.1016/j.neuroimage.2012.01.021
43 Mazziotta, J. *et al.* A probabilistic atlas and reference system for the human brain:
International Consortium for Brain Mapping (ICBM). *Philos Trans R Soc Lond B Biol Sci*
356, 1293-1322 (2001). https://doi.org/10.1098/rstb.2001.0915
44 Benjamini, Y. & Hochberg, Y. Controlling the false discovery rate: a practical and powerful
approach to multiple testing. *Journal of the Royal statistical society: series B*
(Methodological) **57**, 289-300 (1995).
45 Boersma, P. in *Proceedings of the institute of phonetic sciences.* 97-110 (Amsterdam).
46 Jadoul, Y., Thompson, B. & De Boer, B. Introducing parselmouth: A python interface to
praat. *Journal of Phonetics* **71**, 1-15 (2018).
47 Paszke, A. *et al.* Pytorch: An imperative style, high-performance deep learning library.
Advances in neural information processing systems **32** (2019).
48 Xu, L. *et al.* CLUE: A Chinese language understanding evaluation benchmark. *arXiv*
preprint arXiv:2004.05986 (2020).
49 Heafield, K. in *Proceedings of the sixth workshop on statistical machine translation.* 187-
197.
50 Yang, L. *et al.* Diffusion models: A comprehensive survey of methods and applications.
ACM Computing Surveys **56**, 1-39 (2023).
51 Selvaraju, R. R. *et al.* in *Proceedings of the IEEE international conference on computer*
vision. 618-626.

1052

1053

Extended Data

Extended Data Table 1. Examples of decoded sentences

Character error rate	Decoded sentences
0%	O: 我对自己很有信心 (I have confidence in myself)
	D: 我对自己很有信心
~25%	O: 不喜欢打电话语音 (Don't like voice calls)
	D: 不喜欢打电话预约
	O: 我在自己家里 (I live in my own home)
	D: 我住自己家里
~50%	O: 家庭经济条件不是很可以 (The family financial situation is not very good)
	D: 集体经济条件不是还可以
	O: 一点自我保护意识都没有 (No sense of self-preservation at all)
	D: 有点自我保护意识一米五
~75%	O: 有时也紧张 (Sometimes I also feel nervous)
	D: 越说越紧张
	O: 多多少少也对自己有些影响 (It also has some impact on me to a certain extent)
	D: 多多少少有点着急医学影像
>75%	O: 建议尽早到医院接受治疗 (Recommend to seek treatment at the hospital as soon as possible)
	D: 建议就知道一样举手之劳

All examples are from four participants, which are shown for several character error rate levels. The 'O' represents the original sentences and the 'D' represents the decoded sentence. The translated English sentences from Mandarin Chinese are provided in parentheses. Any incorrect character in the decoded sentence is marked in red.

Extended Data Table 2. The articulation features of Mandarin Chinese *Pinyin* initials

Manner of articulation (MOA)		Plosive		Affricate		Fricative		Nasal	Lateral
Devoice		Voiceless		Voiceless		Voiceless	Voiced	Voiced	Voiced
Aspiration		Unaspirated	Aspirated	Unaspirated	Aspirated	NA	NA	NA	NA
Place of articulation (POA)	Bilabial	b [p]	p [pʰ]					m [m]	
	Labiodental					f [f]			
	Alveolar	d [t]	t [tʰ]	z [ts]	c [tsʰ]	s [s]		n [n]	l [l]
	Retroflex			zh [tʂ]	ch [tʂʰ]	sh [ʂ]	r [ʐ]		
	Alveolo-palatal			j [tɕ]	q [tɕʰ]	x [ɕ]			
	Velar	g [k]	k [kʰ]			h [x]			

1065 Extended Data **Table 3: Detailed architecture specifications for the**
1066 **convolutional neural network utilized in this work.**

	ConvNet
Stem	$K \times 1, 64, stride\ S$
Block 1	$\begin{bmatrix} 7 \times 1, 128 \\ MaxPool, stride\ 2 \end{bmatrix} \times 1$
Block 2	$\begin{bmatrix} 7 \times 1, 128 \\ MaxPool, stride\ 2 \end{bmatrix} \times 1$
Block 3	$\begin{bmatrix} 7 \times 1, 256 \\ MaxPool, stride\ 2 \end{bmatrix} \times 1$
Block 4	$[7 \times 1, 256] \times 1$

1067

1068   **Extended Data Table 4: Architecture network and training parameters for each**
1069   **participant**

Participant	1	2	3	4
Kernel size	7	7	5	7
Stride	4	5	3	5

1070

1071

1072 **Extended Data Table 5: Optimizing setup for syllable element prediction.**

Configuration	ConvNet
Training epochs	80
Optimizer	AdamW
Base learning rate	0.0003
Weight decay	0.01
Optimizer momentum	$\beta_1 = 0.9, \ \beta_2 = 0.009$
Batch size	32
Learning rate schedule	cosine decay
Dropout ratio	0.3

1073
1074

Extended Data Fig. 1 | The contributions of each anatomical area in cortical and subcortical structures of right and left hemispheres of the brain to predicting initials **(a)**, tones **(b)**, and finals **(c)**, as measured by the gradient of the loss function with respect to the input data. The contributions of different participants to the same anatomical area are grouped together.

1083

Extended Data Fig. 2 | The correlation between prediction accuracies and the corresponding contributions of each anatomical area in three syllable elements prediction models. The Pearson's correlation coefficient (R) of three syllable elements is calculated separately, with different colors representing different participants (corresponding to Fig. 1). The contributions are measured by the gradient of the loss function with respect to the input data. Each dot represents a brain region's contribution and decoding accuracy for prediction models of initial, tone, and final cluster. *$P < 0.05$; **$P < 0.01$; ***$P < 0.0001$.

1094

1095 **Extended Data Fig. 3 |** Each syllable consists of a tone, a final (rhyme), and at most
1096 one initial (with some syllables lacking an initial). The charts display the distribution
1097 of the number of initials, tones, and vowels across the 407 syllables (the experimental
1098 tasks used for training the three element prediction models).

1099