Shared representations of human actions across vision and language

Diana C. Dima[1,2*], Sugitha Janarthanan[3], Jody C. Culham[4], Yalda Mohsenzadeh[1,2]

[1]Dept of Computer Science, Western University, London, Ontario, Canada [2]Vector Institute for Artificial Intelligence, Toronto, Ontario, Canada [3]Dept of Biochemistry, Western University, London, Ontario, Canada [4]Dept of Psychology, Western University, London, Ontario, Canada

Abstract

Humans can recognize and communicate about many actions performed by others. How are actions organized in the mind, and is this organization shared across vision and language? We collected similarity judgments of human actions depicted through naturalistic videos and sentences, and tested four models of action categorization, defining actions at different levels of abstraction ranging from specific (action verb) to broad (action target: whether an action is directed towards an object, another person, or the self). The similarity judgments reflected a shared organization of action representations across videos and sentences, determined mainly by the target of actions, even after accounting for other semantic features. Language model embeddings predicted the behavioral similarity of action videos and sentences, and captured information about the target of actions alongside unique semantic information. Together, our results show how action concepts are organized in the human mind and in large language model representations.

1   Introduction

2   Daily life requires us to understand a wide range of actions performed by others, as well

3   as communicate about them. Yet actions are an incredibly heterogeneous category, linking

4   multiple visual, semantic and social domains[1–4] and varying along multiple axes. How does the

5   mind organize this rich semantic space, and does this organization differ when actions are

6   communicated visually or verbally?

7   Actions can be defined at multiple levels of abstraction and can only be understood in

relation to agents, objects, and contexts, a complexity that still challenges machine learning

algorithms for action recognition. Different brain areas have been shown to represent action

categories with different degrees of specificity[5–7]. Despite this, previous work on semantic action

representations has tended to either define action categories *a priori* (e.g. using action verbs or

broad activity types)[8–10], or to employ a behaviorally estimated semantic space[11,12]. Recent work

has investigated the taxonomy of actions using text stimuli of varying levels of abstraction[13]; but

it is unclear whether such a taxonomy would generalize to visual actions and different

categorization tasks.

16   Behavioral studies using visual actions and data-driven analyses have mapped

representational spaces along broad axes such as *communication*, *locomotion*, *food* etc.[11,14,15] or

axes related to facial traits, emotions, and action planning[16]. In a large-scale text analysis, six

dimensions organized action representations[17], some of them notably more abstract than their

visual counterparts (e.g. *abstraction*, *tradition*, *spirituality*). In light of such results, it has been

speculated that the dimensions organizing actions in the mind may be modality-dependent[14]; but

to our knowledge, no behavioral study to date has investigated semantic action representations

using both visual and text stimuli.

However, a growing body of neuroimaging research suggests that action representations

may share a neural substrate across vision and language. Adding to long-standing evidence of

overlap in neural activations elicited by action images and action verbs[10,18–24], recent

investigations have more directly revealed modality-invariant neural representations in human

occipito-temporal and parietal cortices[25,26]. These areas have also been shown to encode

invariant action category[1,11,27–33], hinting at a putative cross-modal semantic architecture.

Here, we employed semantic similarity to capture how action categories are organized in

the mind[34–36]. To capture a naturalistic action space[37–39], we curated a set of videos and sentences

depicting everyday actions defined at four levels of abstraction based on prior research: specific

action verbs[10,26] (e.g. *swimming*), everyday activities[8,9,40] (e.g. *sports*), broad action classes

inspired by primate research[41,42] (e.g. *locomotion*), and action target types, reflecting whether an

action is directed towards an object, another person, or the self[12,43].

To understand how actions are organized in the mind, we used these semantic features,

together with a rich set of contextual, perceptual, and computational features, to predict

behavioral similarity judgments of the videos and sentences within and across modalities. We

found a semantic organization shared across vision and language, reflecting the target of actions

and, to a lesser extent, their class. Pre-trained text embeddings based on OpenAI's GPT large

language models (LLM) predicted this shared semantic structure better than, and independently

of, other semantic features, while also containing information about the target of actions.

Together, these results reveal the modality-invariant organization of action concepts in minds

and machines.

Figure 1. Action features across the stimulus set. **a,** Actions were categorized at different levels of abstraction, from specific to broad, according to their action verb, everyday activity category, action class, and action target. **b,** Correlations across features of interest were low, with the notable exception of more complex computational models (CLIP, BERT, GPT embeddings) that moderately correlated with most other features. Both video- and text-based feature representational dissimilarity matrices (RDMs) are included in the correlation matrix, and only correlations over 0.1 are displayed numerically.

Results

Features in naturalistic actions: from semantic to perceptual

We curated a set of 95 videos of natural actions from the Moments in Time dataset[44]. Videos were carefully selected to ensure that semantic, contextual, and perceptual features were minimally correlated across the dataset (**Figure 1b**). For each video, a corresponding naturalistic sentence was constructed following the structure *agent + action* (+ *object* if present) + *context*, e.g. *Women are swimming in a pool*. The sentences were displayed as images matched in size to the videos (see Methods: Stimuli).

We labeled the stimuli with a set of 18 semantic, contextual, computational, and modality-specific features. First, actions were labeled with four semantic features at different

levels of abstraction based on previous research (**Figure 1a**): by their action verb[10,26,45] (e.g.

swimming), everyday activity[15,46] (e.g. *sports*), action class[41] (e.g. *locomotion*), and action

target[12,43] (e.g. *the self*). The first three roughly correspond to the subordinate, basic and

superordinate levels of categorization identified in object research[47–49], while at the same time

testing the main action definition criteria prevalent in the literature. The fourth feature (action

target) includes information about the actions' goals and their degree of sociality (person-

directedenss) and transitivity (object-directedness), features previously found to be essential in

action processing[9,12,43].

Apart from their semantic content, naturalistic actions vary along numerous axes,

including those related to the agents performing the action and the context in which the action

takes place. To capture this information, we labeled each action with contextual features: the

number and perceived gender of agents, as well as the scene setting (indoors or outdoors).

Next, to better characterize stimulus features and evaluate how well computational

models can capture human action representations, we extracted image features from different

vision-trained neural networks (the first convolutional and last fully connected layers of

AlexNet[50], the vision module of CLIP[51]) and sentence features based on large language models

(LLM: CLIP's language module, BERT[52], OpenAI GPT text embeddings[53]).

Finally, we accounted for additional sources of variance by extracting modality-specific

features encoding perceptual and action information: motion energy, effectors (body parts

involved in each action), and tool use (for videos) and the number of words and characters (for

sentences).

We generated representational dissimilarity matrices (RDMs) quantifying the pairwise

distances between all videos or sentences along each of the 18 semantic, contextual,

computational, and modality-specific features (see Methods: Feature definitions).

Correlations among different groups of features were low across both videos and

sentences (**Figure 1b**). There were moderate correlations among semantic features, particularly

between action target and class (ρ_A=0.27). Features extracted from computational models

(particularly LLMs) moderately correlated with semantic, contextual, and perceptual features,

pointing to the rich, diverse information captured by these models.

A shared organization across vision and language

To investigate how humans represent the meaning of actions, we conducted two multiple

arrangement experiments with either the video or sentence stimuli. Participants arranged the

videos or sentences inside a circular arena (**Figure 2a**) and were instructed to place similar

actions closer together and different actions further apart, focusing on the meaning of the actions.

Different sets of 3-12 videos were displayed during the task, until all pairwise distances were

reliably estimated. This method efficiently captures multi-dimensional representations by

presenting the stimuli multiple times in different contexts. On-screen distances were used to

generate behavioral RDMs for each participant using inverse MDS[54].

The resulting dissimilarity matrices reflected a semantic organization when inspected

using t-distributed Stochastic Neighbor Embedding (tSNE) plots (**Figure 2b**). The reliability of

the data, quantified by subsampling two sets of 16 participants and correlating their averaged

RDMs (1000 iterations), was higher in the video set (ρ_A=0.45±0.01) than the sentence set

(ρ_A=0.29±0.01; Wilcoxon z=38.72, p<0.001). All reliabilities were significantly above chance

(Wilcoxon z=27.39, p<0.001).

Figure 2. Multiple arrangement task and results. **a,** Examples of stimulus arrangements that could be made by participants. The videos or sentences were presented around a circular arena. Participants arranged them inside the arena according to the actions' semantic similarity. Images shown are public domain examples of the types of videos participants might see. **b,** Representational dissimilarity matrices (RDMs) were generated from each participant's arrangement. Here, the average RDM is shown in the lower-left corner, together with a t-distributed Stochastic Neighbor Embedding (tSNE) representation color-coded by action class and labeled with action verbs. **c,** Reliability of similarity judgments within and across modalities (correlation between subsets), pointing to a shared structure across modalities. Distributions are based on 1000 data splits with N = 16 across all datasets.

Across modalities, the average behavioral RDMs were substantially correlated (ρ =0.4). In a subsampling analysis drawing 16 participants from each modality 1000 times, the cross-modal correlation was ρ =0.3±0.02, slightly higher than the internal reliability of the sentence dataset (Wilcoxon z=8.42, p <0.001; **Figure 2c**) and pointing at a strong cross-modal overlap.

Figure 3. Broad semantic features and computational features best correlate with behavioral similarity

within and across modalities. Individual feature-behavior correlations are plotted against the noise ceiling (in gray).

Dots are individual subjects. Asterisks denote correlations significantly greater than zero ($p<0.005$).

Features in action categorization

We first evaluated the contribution of each feature to behavior by correlating each feature

RDM to each participant's behavioral RDM (**Figure 3a**). Among the semantic features, the

broadest (action target and class) correlated significantly with behavioral similarity across videos

and sentences. In the video set, the everyday activity category also correlated with behavioral

similarity, suggesting that this feature may be more salient in visual actions. None of the

contextual and modality-specific features contributed to behavior, except for the visual effectors

feature coding the body parts involved in each action.

Features extracted from computational models correlated with behavior across

modalities. In the video set, this included higher-level features from visual models (the last layer

of AlexNet and CLIP's vision module; see also **Supplementary Figure 1**), as well as all the

language models (CLIP, BERT, and GPT). A model trained specifically for action recognition

(ResNet-18 3D pretrained on Kinetics) did not correlate with behavior (**Supplementary Figure**

1).

In the sentence set, all LLM features, as well as visual features from CLIP, correlated

with behavior, suggesting that these models represent conceptual information about actions. GPT

model embeddings were the only feature to approach the noise ceiling in the sentence set, and

also reached the highest correlation with behavior in the video set.

Disentangling semantic features in action categorization

Even moderate correlations between related features (**Figure 1b**) could affect their

contributions to the behavioral data, making their independent roles difficult to assess. We used

cross-validated variance partitioning[12,55] to evaluate the unique and shared variance in behavior

predicted by different features. We trained and tested hierarchical regression models to predict

similarity judgments within the video and sentence sets, as well as across modalities. Leave-one-

out cross-validation was conducted across actions, with different participants' data used for

training and testing (see Methods: Variance partitioning).

First, to evaluate to what degree the behavioral datasets captured semantic information,

we grouped our feature set into three categories: semantic (action target, class, activity, and

verb); social (number of agents and agent gender); and perceptual (scene settings and selected

modality-specific features; see Methods: Variance partitioning).

Together, the three groups of features approached or reached the noise ceiling (split-half

data reliability) in predicting variance within and across modalities (**Figure 4a**). In all cases,

semantic features explained more unique variance than the other groups ($p<0.001$, randomization

testing). Social features explained a significant amount of unique variance in sentence similarity

($p<0.001$), but not video similarity ($p=0.24$) or across modalities ($p=0.19$). Perceptual features

explained unique variance in video similarity ($p<0.001$), but not sentence similarity ($p=0.15$) or

across modalities ($p=0.31$). This points to differences in the features aiding the semantic

categorization of videos and sentences, and shows that only semantic features are shared across

modalities.

Figure 4. Variance partitioning: semantic features, particularly the action target and class, predict the most

variance in behavior within and across modalities. **a,** Stacked plots and Venn diagrams showing the unique and

shared contributions of semantic, social, and perceptual features to behavior (see Methods). Error bars are ±SD and

the data reliability (min-max range, split-half ρ_A^2) is shown in gray. As expected, semantic features explain the most

variance. **b,** Unique and shared contributions of the three most predictive semantic features. The action target

explains the most variance, including variance shared with the action class.

Next, we disentangled the broad semantic features (action target, action class, and

everyday activity) that best correlated with behavior (**Figure 4b**). Both within and across

modalities, the action target explained the most unique variance ($p<0.001$), as well as a large

amount of variance shared with the action class ($p<0.001$). These results are in line with work

suggesting that action goals are essential in action categorization[12,43], and highlights the overlap

between different action taxonomies.

Large language model features predict human similarity judgments

Given how well GPT embeddings correlated with behavioral judgments in both

modalities, we conducted an additional analysis to assess whether they shared information with

the semantic features. To this end, we entered the GPT embedding RDM into a variance

partitioning analysis together with the action target and class (**Figure 5a**).

Both within and across modalities, GPT uniquely explained a large portion of the

variance in behavior ($p<0.001$), suggesting that GPT captures more information relevant to

human categorization than individual semantic features. There was also significant shared

variance between action target and class in the video dataset ($p<0.001$), and between action

target and GPT embeddings in the video dataset and across modalities($p<0.001$).

As naturalistic sentences contain rich information, it is difficult to know what features are

captured by the sentence-level GPT embeddings. To assess this, we extracted separate GPT

embeddings for the three sections of each sentence: the agent (e.g. *women*), the action (e.g. *are*

swimming), and the context (e.g. *in a pool*). We used these embeddings to predict behavior in a

variance partitioning analysis (**Figure 5b**), and found that action embeddings explained most of

the unique variance both within and across modalities ($p<0.001$). However, in the sentence

dataset, agent embeddings also contributed unique variance ($p=0.001$). Shared variance between

all three features contributed significantly in the video dataset and across modalities ($p<0.001$)

This suggests that that GPT embeddings capture both semantic and contextual information.

Figure 5. Variance partitioning: understanding GPT embeddings. **a,** Unique and shared variance in

behavior explained by GPT embeddings, action target, and action class. GPT captures more, and different, variance

in behavior than the two main semantic features, alongside shared variance with the action target and class. **b,**

Unique and shared contributions of GPT embeddings based on the agent, action, and context parts of sentences.

Most of the embeddings' explanatory power reflects action information, as well as agent information when

predicting sentence similarity.

The hypothesis-driven semantic features were binary, allowing us to compare different

levels of action categorization (see Methods: Feature definitions). However, this may have put

them at a disadvantage when compared with the GPT embeddings, despite the use of a

correlation metric that can handle differences in feature complexity. In a control analysis, we

used FastText[78], a pretrained word embedding, to generate semantic models based on text

embeddings of the action target and class. This yielded similar results (**Supplementary Figure**

2), suggesting that the findings were not driven by differences in model complexity.

Discussion

Using a naturalistic, multimodal dataset and semantic similarity judgments, we

interrogated how action concepts are organized in the mind across vision and language. We

reveal a shared organization along broad semantic axes reflecting the actions' target and

behaviorally relevant class. Furthermore, we show that language model embeddings accurately

capture this shared semantic structure.

A cross-modal organization of actions in the mind

Using a semantic similarity task and a naturalistic set of action videos and sentences, we

found a shared semantic organization of actions in the mind across vision and language. This was

reflected in the similar categorization of videos and sentences and the high reliability of

similarity judgments across modalities (**Figure 1c**).

Previous behavioral studies have focused on either visual stimuli[11,14,15] or text data[17,49] to

understand how actions are organized in the mind. However, neural investigations using both

visual and text stimuli have found modality-invariant encoding of actions in the brain[25,26]. Our

work links these findings to a shared representational space across vision and language.

Although semantic features explained most of the variance in behavior across modalities,

the contribution of contextual features was different for videos and sentences (**Figure 4a**). In the

video arrangement task, perceptual features (scene setting, motion energy, AlexNet final layer

activations, tool and effector features) made a significant unique contribution, while social

features (number and perceived gender of agents) explained little variance. Conversely, sentence

similarity reflected social features, but not perceptual features, alongside semantic information.

These differences open exciting avenues for identifying the building blocks of natural action

categorization in vision and language.

Previous work has highlighted the important role of social features, particularly sociality

(often defined as person-directedness), in intuitive visual action processing[8,9,43,56]. However,

sociality can be difficult to disentangle from other semantic and perceptual features, such as

action category and number of agents[8,11,57]. Here, the action target feature, which included

aspects of both sociality (person-directedness) and transitivity (object-directedness), explained

behavioral judgments best. In contrast, lower-level agent-related features did not capture much

variance in the video behavioral data.

While efforts were made to curate a diverse action space representing many categories at

different levels of abstraction, the choice of actions is likely to have a large impact on the

behavioral similarity judgments. Furthermore, individual variability in arrangements placed

limits on effect sizes and was reflected in the difference in reliability between visual and

language stimuli. Here, we focused on determining shared, generalizable axes for action

categorization in our dataset. Individual differences in categorization, and how these apply to

different sets of actions, remain open questions for future research.

Actions are categorized according to their target and class

Among semantic features, action target, action class, and activity category correlated best

with the individual similarity judgments (**Figure 3a**). As these features were moderately

correlated (particularly action target and class: $\rho_A = 0.27$), we performed a variance partitioning

analysis to assess their unique and shared contributions (**Figure 4b**). Action target uniquely

predicted behavioral judgments within and across modalities, in line with previous research

highlighting the importance of action goals in organizing action representations in brain and

behavior[12,32,58]. Action class, a feature inspired by a proposed human motor repertoire

distinguishing between behaviorally relevant action categories[31,41,42], shared variance with the

action target. This likely reflects the fact that motor goals are generally shared by exemplars

within each proposed action class[41]. It is interesting, however, that action class contributed little

unique variance in behavior, suggesting that we should look to broader behaviorally relevant

features as organizing axes in action understanding. Indeed, the primacy of goals can arguably

allow for more flexible handling of the vast human action space.

Video similarity judgments also correlated with the effectors feature describing what

body parts were involved in each action. This information, although highly diagnostic of action

goals and types[9,33,41], was not present in the sentence versions of the stimuli.

Language models capture human action concepts

Recently, neural networks have made significant strides in predicting human behavioral

judgments[59–62] and neural responses to naturalistic stimuli across vision[63–68] and language[69–72].

However, actions remain a difficult domain to tackle for even state-of-the-art algorithms. We

assessed both computer vision models (AlexNet, CLIP, and others; see **Supplementary Figure**

1) and natural language processing models (CLIP, BERT, and GPT text embeddings) in their

ability to capture the semantic organization of action similarity judgments. Features extracted

from both types of models were used to explain behavioral data across modalities, to assess how

well they capture the covariance between language and the visual world[73–76].

Visual and textual features extracted from CLIP, a multimodal transformer trained on

image and text pairs, captured behavioral representations well within and across modalities, but

were surpassed by GPT embeddings (**Figures 3, 5**). GPT embeddings explained behavioral

similarity better than all other language models, and better than individual semantic features.

They captured video similarity better than vision models and uniquely explained a large portion

of the variance both within and across modalities. They also shared significant variance with the

action target, highlighting the importance of this feature in structuring action representations.

While the combined semantic features (particularly action target and class) best modeled the

modality-invariant component in the behavioral data, the ability of GPT embeddings to explain

variance both within and across modalities suggests an advantage related to their

multidimensionality. Furthermore, the ability of LLM features to capture semantic

representations shared across vision and language points to the extraction of semantic

information as an important goal in human vision[77].

Furthermore, an analysis comparing GPT embeddings extracted from the agent, action,

and context parts of each sentence shows that most of their explanatory power originated from

the action itself (**Figure 5b**). While a binary verb model did not strongly correlate with behavior,

GPT embeddings based on verbs capture complex relationships that also reflect higher-level

features. In the video dataset, context-related GPT embeddings did not capture perceptual

variance as successfully as image features (**Figure 4a**), and thus did not explain all the variance

in similarity. However, in the sentence dataset, both action and agent embeddings explained

significant variance. Together, the GPT embeddings reached the noise ceiling in both sentence

and cross-modal prediction, pointing at the strength of this model in capturing the conceptual

organization of actions. Collectively, these results demonstrate the generalizability of text

representations used by LLMs across tasks and modalities, as well as the potential for using

human behavioral data and insights to better understand these models.

Features and categories in minds and machines

Since the discovery of functional selectivity for object categories in the human brain[79–81],

a growing body of work has investigated the role of visual features in explaining or supporting

categorization[61,82–84]. In action perception, evidence for categorical, invariant

representations[1,6,11,28,85,86] has grown alongside evidence for featural representations along the

ventral and dorsal streams: from bodies and their motion[81,87–91] to information about tools and

effectors[2,27,33,43] and complex social information[8,9,41,92–94]. Importantly, the use of naturalistic

stimuli has been essential in uncovering these rich representations, adding to growing evidence

of the impact of context in visual processing[37,95–98], and pointing to the importance of actions as a

step towards natural event understanding.

Here, we focused on categorical models of semantic organization, grouping actions into

classes at different levels of abstraction or according to their targets, effectors, or the

involvement of tools. Our results show that a broad categorical model (i.e., whether an action is

directed towards a person, an object, or the self) determines much of the semantic organization

of actions in the mind, which is consistent across vision and language. However, it remains to be

seen whether this organizing feature should be thought of as truly categorical or continuous,

mapping actions along a spectrum according to whether they aim to instill change in the self, the

environment, or other people.

Although the semantic similarity task ensured a focus on actions, our stimuli were

naturalistic by design, involving interactions between agents and objects in a variety of contexts.

Thus, perceptual and social features contributed to the similarity judgments, highlighting the role

of actions as a bridge between visual domains and an essential component in event

understanding. Action goals in particular are thought to play an important part in the perception

and segmentation of events[99]. These results thus open opening exciting avenues towards

understanding how natural events are processed and organized in the mind.

As artificial intelligence models make strides towards human-like performance across

tasks and domains, new questions arise about their internal representations and their alignment

with the human mind. Our results highlight the ability of language model embeddings to capture

human-like action representations, adding to recent work that suggests a key role for cognitive

science in measuring and narrowing the gap between model and human representations[62,100–102].

Together, our results characterize the semantic organization of naturalistic actions across

vision and language, and open exciting avenues for investigating conceptual representations and

their building blocks in minds and machines.

Methods

Stimuli

Videos

The stimulus set consisted of 95 short videos and sentences depicting everyday actions.

Actions were defined at four levels of abstraction from specific (action verb) to broad (action

target; **Figure 1a**; see Methods: Feature definitions).

Videos were selected from the Moments in Time dataset[44]. First, we inspected the

Moments in Time verb labels to identify actions belonging to eight main classes (defense,

ingestion, locomotion, manipulation, self-directed actions, gestures, social interactions, and

symbolic actions)[41,42]. We then curated an initial set of 249 videos with the aim of representing

each class through a variety of verbs and everyday activities (see Methods: Feature definitions).

Videos were chosen that were horizontally oriented (landscape), shot in color, and of reasonable

image quality. Each video depicted a single, continuous human action. We excluded videos

where agents interacted with the camera. The selected videos varied along multiple axes related

to the action (action target, tool use), agents (number, gender), and scene setting, which were

manually labeled by the experimenters across the video set.

Since features can covary in naturalistic stimulus sets, we performed further stimulus

selection to reduce feature correlations. To this end, we randomly drew 10,000 samples of 100

videos from the initial stimulus set. Each sample included 10 videos per action class, except for

locomotion and manipulation, which were represented by 20 videos each to reflect their action

diversity.

Out of all samples, we selected the set of stimuli with the lowest overall correlation

across a range of visual, semantic, agent and action features (mean Spearman's $\rho=0.07$,

SD=0.13). We manually adjusted this set to remove videos that were too visually similar to

others in the same category. The final set consisted of 95 videos, with 7-20 videos per action

class.

All videos were resized to 600 x 400 pixels. To achieve this, we first applied the *imresize*

function in MATLAB R2021b using bicubic interpolation. Next, the videos were cropped to the

correct aspect ratio either centrally or using manually determined coordinates to ensure the

action remained clearly visible. Using the *videoWriter* object in MATLAB R2021b, the videos

were trimmed to 2 s centered around the action and resampled to 20 fps.

Sentences

Sentences were generated to succintly describe the action in each video, using a

consistent format: Agent + Action [+ Object, if present] + Context; for example: *A girl and a boy*

are eating burgers in a kitchen. Two men are talking in a living room. (see **Appendix 1** for the

full list of sentences).

The number and perceived gender of agents were specified where clearly visible. Actions

were accompanied by their objects where applicable. There was no difference in overall length

between sentences that included an object and those that did not ($t(82.7)=1.22$, $p=0.22$). The

context was described using a single word or phrase. The most specific wording possible was

used to reflect the level of detail present in the video. Although detail was necessarily lost in the

transition between modalities, we emphasized natural phrasing and included information about

agents, actions, objects, and contexts to ensure a clear one-to-one correspondence between

actions and videos.

Sentence stimuli were 400x600 pixel images with gray borders, ensuring visual

consistency with the video stimuli (**Figure 2a**). Each image displayed a sentence in black Arial

font on a white background. For readability, each sentence was split into three lines

corresponding to the three sentence components (agent, action, and context).

Participants

A sample of 41 participants completed the video arrangement experiment (39 after

exclusions, mean age 18.08, SD 0.84, 22 female, 16 male, 1 non-binary). A different cohort of 37

participants completed the sentence arrangement experiment (32 after exclusions, mean age

18.16, SD 0.45, 19 female, 13 male). Participants were recruited through the Department of

Psychology Research Participation Pool at Western University. All procedures for online data

collection were approved by the Western University Research Ethics Board, and informed

consent was obtained from all participants.

Multiple arrangement

We conducted two multiple arrangement experiments to understand semantic action

representations across vision (Experiment 1, using videos) and language (Experiment 2, using

sentences).

The experiments were conducted on the Meadows platform (https://meadows-

research.com/). Participants were instructed to arrange the videos or sentences according to the

actions' semantic similarity, placing similar actions closer together and different actions further

apart.

The task took 90 minutes to complete and an average of 186 (videos) or 215 (sentences)

trials. The difference between the numbers of trials in the two tasks was not significant

($t(60)$=0.97, p=0.34). Each trial started with a maximum of 12 videos or sentences arranged

around a circular arena. The videos played automatically on hover. All stimuli had to be

dragged-and-dropped inside the arena before the trial ended. Participants viewed different

subsets of stimuli during each trial. Stimulus selection was guided by a 'lift-the-weakest'

algorithm so as to optimize the signal-to-noise ratio of the distance estimates[54].

Before the main task, participants completed a training trial in which they arranged the

same three videos (in Experiment 1) or sentences (in Experiment 2). Participants were excluded

if their training data correlated poorly to the average of all other participants' data (over 2 SDs

below the mean). Participants were also excluded if they responded incorrectly to a catch trial

requiring them to label the action in previously seen stimuli.

Using inverse MDS, participants' arrangements were used to generate behavioral

dissimilarity matrices quantifying the Euclidean distances between all pairs of videos. We

visualized the clustering of action categories using t-SNE representations of the average RDMs,

which display the stimuli as points in a 2D space.

Feature definitions

Semantic features

Actions can be defined at several levels of abstraction, from specific verbs to broad

classes. Which of these guides human judgments about the meaning of actions? We tested

several features to understand the structure of semantic action representations in the mind. Each

feature was converted into a representational dissimilarity matrix (RDM) quantifying the

dissimilarity between stimuli along that axis.

Our four main hypothesis-driven semantic features were: the action target (whether an

action was directed towards an object, a person, or the self); action class (based on a putative

human motor repertoire[41]); everyday activity (based on activity categories from the American

Time Use Survey[40]); and action verb (based on the Moments in Time verb labels; see **Figure 1a**

for a complete list of semantic categories). These were binary RDMs, in which distances

between stimuli belonging to the same category were set to 0, and distances between stimuli

belonging to different categories were set to 1.

Contextual features

To capture information about the agents (social features), we included the number of

agents (labeled on a three-point scale from 1, one agent present, to 3, three or more agents

present) and their perceived genders. To capture action context, we included scene setting as a

perceptual feature (indoors/outdoors). Contextual features were labeled by experimenters and

converted to binary or Euclidean distance RDMs.

Computational features

To assess whether computational models can capture human semantic judgments, we

extracted activations from computational models trained on visual and text stimuli.

As the videos were short and did not contain major visual changes across frames, we

extracted most activations using the first frame of each video. We used the AlexNet feedforward

neural network pretrained on ImageNet, and extracted features from its first convolutional layer

(Conv1, to capture low-level visual properties), and its last fully connected layer (FC8, to capture

higher-level features). We also extracted features from CLIP, a multimodal transformer trained

on publicly available image-text pairs[51]. As CLIP contains both image and text encoders, we

used it to extract features from both videos and sentences. AlexNet features were extracted using

the Deep Learning toolbox in MATLAB R2022a, while CLIP features were extracted using the

THINGSvision[103] toolbox in Python 3.10.9. Additional model features, including ResNet-50,

VGG-16, CORnet-S, CORnet-RT (all pretrained on ImageNet), and ResNet-18 3D (pretrained

on Kinetics) were extracted using the THINGSvision toolbox or PyTorch and the *torchextractor*

package in Python 3.10.9 (Supplementary Figure 1).

We also extracted embeddings (features measuring the relatedness of text strings) from

Google's BERT[52] transformer and OpenAI's embedding model associated with its GPT[51,53]

transformers. We used the latest version of GPT embeddings at the time of writing, *text-*

embedding-ada-002, which outperform previous OpenAI embedding models despite being

lower-dimensional. To assess the contributions of different sentence components, we also

extracted separate embeddings for the agent, action, and context portion of each sentence. All

text features were extracted from the Hugging Face transformers library[104] using PyTorch in

Python 3.10.9. RDMs were created using pairwise Euclidean distances between feature vectors.

Modality-specific features

Finally, we quantified modality-specific features to capture additional sources of

variance. For videos, these included motion energy computed using a pyramid of spatio-temporal

Gabor filters as implemented in the *pymoten* package[105]. We also included two video-specific

action features which were not present or discernible in the sentences: tool use (binary feature:

whether the action was tool-mediated), and effectors (binary vectors indicating the body parts

involved in each action: face/head, hands, arms, legs, and torso).

For the sentence set, we created two low-level features reflecting the number of words

and characters in each sentence.

Representational Similarity Analysis (RSA)

To assess each feature's contribution to the human similarity judgments, we calculated

Spearman's ρ_A correlations between each feature RDM and each participant's behavioral RDM.

While Spearman's ρ can favour categorical models with many tied ranks, Spearman's ρ_A solves

this issue using random tiebreaking to compute the expected correlation[106]. All RDMs were

normalized using min-max normalization.

We assessed the significance of the correlations using sign permutation testing (5000

iterations, one-tailed). P-values were omnibus-corrected for multiple comparisons using a

maximum correlation threshold across models[107,108].

A noise ceiling was calculated by correlating each participant's RDM to the average

RDM across participants (upper bound), as well as to the average RDM excluding the left-out

subject (lower bound)[109].

Variance partitioning

To disentangle the contributions of specific sets of features to the behavioral similarity

judgments, including their unique and shared contributions, we performed cross-validated

variance partitioning within and across modalities.

We first evaluated whether the behavioral data reflected semantic information more than

social and perceptual information. To this end, we selected three groups of features: semantic

(action target, action class, everyday activity, and action verb); social (number of agents and

agent gender); and perceptual (for videos: scene setting, tool use, effectors, motion energy, and

features from the FC8 layer of AlexNet; for sentences: scene setting and number of words; cross-

modal: scene setting). Each group of features was considered a separate predictor in this analysis.

We repeated this analysis with different sets of predictors to evaluate: (1) the variance

explained by each semantic feature that significantly correlated with the behavioral similarity

data (action target, action class, and everyday activity); (2) the variance explained by GPT

embeddings compared to the most predictive semantic features (action target and action class);

(3) the variance explained by GPT embeddings separately extracted from the agent, action, and

context portion of each sentence.

At each iteration, we fit seven regression models using every possible subset of the three

predictors and evaluated them using leave-one-out cross-validation. Across 95 iterations, the

models were fit using the data from 94 out of the 95 actions (4371 pairs). We then predicted the

similarity judgments for the held-out data (i.e., the dissimilarities between the held-out action

and all others, amounting to 94 pairs). To assess how well the models predicted the held-out

data, we calculated the squared Spearman's ρ_A correlation between the predicted and actual

similarity judgments, as an approximation of the amount of variance explained. We then used

this to calculate the unique and shared variance contributed by each group of features[8,55,110].

Importantly, the training and test sets were drawn from different participants. In the

within-modality analyses, we performed 100 random splits of each behavioral dataset into

training and test sets of approximately equal sizes, which were averaged before performing

leave-one-action-out cross-validation as described above. Results were averaged across 95

iterations of leave-one-out cross-validation and 100 dataset splits.

In the cross-modal analysis, we drew 100 random subsets of 20 participants from each

behavioral dataset. At each cross-validation iteration, we used video data for training and

correlated the predicted responses with the sentence data (and vice versa). We averaged results

across both directions of training and testing.

All results were tested against chance using one-tailed sign permutation testing (5000

iterations, omnibus-corrected for multiple comparisons).

Acknowledgements

The authors would like to thank Leyla Isik for helpful comments on the manuscript and

Martin Hebart for code calculating the Spearman's ρ_A. This material is based upon work

supported by BrainsCAN at Western University through the Canada First Research Excellence

Fund (CFREF) to Y.M., a Western Interdisciplinary Development Initiatives Grant to Y.M. and

J.C.C., a Vector Institute for Artificial Intelligence Research Grant to Y.M. and D.C.D., and a

Western Postdoctoral Fellowship to D.C.D.

Data availability

The data and results have been archived as an Open Science Framework repository (https://osf.io/c5bdv/).

Code availability

Analysis code is available on GitHub (https://github.com/dianadima/multi-action).

References

1. Lingnau, A. & Downing, P. E. The lateral occipitotemporal cortex in action. *Trends Cogn Sci* **19**, 268–277 (2015).
2. Leshinskaya, A., Wurm, M. F. & Caramazza, A. Concepts of Actions and their Objects. in *The Cognitive Neurosciences* (eds. Gazzaniga, M., Mangun, G. & Poeppel, D.) 757–765 (MIT Press, 2020).
3. Baker, C. L., Saxe, R. & Tenenbaum, J. B. Action understanding as inverse planning. *Cognition* **113**, 329–349 (2009).
4. Thornton, M. A. & Tamir, D. I. The brain represents situations and mental states as sums of their action affordances. *PsyArXiv* 1–52 (2023).
5. Spunt, R. P., Kemmerer, D. & Adolphs, R. The neural basis of conceptualizing the same action at different levels of abstraction. *Soc Cogn Affect Neurosci* **11**, 1141–1151 (2016).
6. Wurm, X. M. F. & Lingnau, A. Decoding Actions at Different Levels of Abstraction. *The Journal of Neuroscience* **35**, 7727–7735 (2015).
7. Zhuang, T., Kabulska, Z. & Lingnau, A. The representation of observed actions at the subordinate, basic and superordinate level. *The Journal of Neuroscience* JN-RM-0700-22 (2023) doi:10.1523/JNEUROSCI.0700-22.2023.
8. Dima, D. C., Tomita, T. M., Honey, C. J. & Isik, L. Social-affective features drive human representations of observed actions. *Elife* **11**, (2022).
9. Tarhan, L. & Konkle, T. Sociality and interaction envelope organize visual action representations. *Nat Commun* **11**, 1–11 (2020).
10. Bedny, M. & Caramazza, A. Perception, action, and word meanings in the human brain: The case from action verbs. *Annals of the New York Academy of Sciences* vol. 1224 81–95 Preprint at https://doi.org/10.1111/j.1749-6632.2011.06013.x (2011).
11. Tucciarelli, R., Wurm, M., Baccolo, E. & Lingnau, A. The representational space of observed actions. *Elife* **8**, 1–24 (2019).
12. Tarhan, L., De Freitas, J. & Konkle, T. Behavioral and Neural Representations en route to Intuitive Action Understanding. *Neuropsychologia* **163**, 108048 (2021).
13. Zhuang, T. & Lingnau, A. The characterization of actions at the superordinate, basic and subordinate level. *Psychol Res* (2021) doi:10.1007/s00426-021-01624-0.

14. Kabulska, Z. & Lingnau, A. The cognitive structure underlying the organization of observed actions. *Behav Res Methods* (2022) doi:10.3758/s13428-022-01894-5.

15. Dima, D. C., Hebart, M. N. & Isik, L. A data - driven investigation of human action representations. *Sci Rep* 1–11 (2023) doi:10.1038/s41598-023-32192-5.

16. Vinton, L. C. *et al.* Four fundamental dimensions underlie the perception of human actions. *Atten Percept Psychophys* (2023) doi:10.3758/s13414-023-02709-1.

17. Thornton, M. A. & Tamir, D. I. Six Dimensions Describe Action Understanding: The ACT-FASTaxonomy. *J Pers Soc Psychol* **122**, 577–605 (2021).

18. Martin, A., Haxby, J. V, Lalonde, F. M., Wiggs, C. L. & Ungerleider, L. G. Discrete cortical regions associated with knowledge of color and knowledge of action. *Science (1979)* **270**, 102–105 (1995).

19. Spunt, R. P. & Lieberman, M. D. Dissociating modality-specific and supramodal neural systems for action understanding. *Journal of Neuroscience* **32**, 3575–3583 (2012).

20. Aziz-Zadeh, L., Wilson, S. M., Rizzolatti, G. & Iacoboni, M. Congruent Embodied Representations for Visually Presented Actions and Linguistic Phrases Describing Actions. *Current Biology* **16**, 1818–1823 (2006).

21. Bidet-Ildei, C., Beauprez, S. A. & Badets, A. A review of literature on the link between action observation and action language: advancing a shared semantic theory. *New Ideas Psychol* **58**, 100777 (2020).

22. Beauprez, S. A. & Bidet-Ildei, C. Perceiving a Biological Human Movement Facilitates Action Verb Processing. *Current Psychology* **38**, 1355–1359 (2019).

23. Humphreys, G. F., Newling, K., Jennings, C. & Gennari, S. P. Motion and actions in language: Semantic representations in occipito-temporal cortex. *Brain Lang* **125**, 94–105 (2013).

24. Quandt, L. C., Lee, Y. S. & Chatterjee, A. Neural bases of action abstraction. *Biol Psychol* **129**, 314–323 (2017).

25. Wurm, M. F. & Caramazza, A. Distinct roles of temporal and frontoparietal cortex in representing actions across vision and language. *Nat Commun* **10**, 1–10 (2019).

26. Aflalo, T. *et al.* A shared neural substrate for action verbs and observed actions in human posterior parietal cortex. *Sci Adv* **6**, (2020).

27. Wurm, M. F. & Caramazza, A. Two 'what' pathways for action and object recognition. *Trends Cogn Sci* **26**, 103–116 (2022).

28. Tucciarelli, R., Turella, L., Oosterhof, N. N., Weisz, N. & Lingnau, A. MEG Multivariate Analysis Reveals Early Abstract Action Representations in the Lateral Occipitotemporal Cortex. *Journal of Neuroscience* **35**, 16034–16045 (2015).

29. Hafri, A., Trueswell, J. C. & Epstein, R. A. Neural representations of observed actions generalize across static and dynamic visual input. *Journal of Neuroscience* **37**, 3056–3071 (2017).

30. Culham, J. C. & Valyear, K. F. Human parietal cortex in action. *Curr Opin Neurobiol* **16**, 205–212 (2006).

31. Urgen, B. A. & Orban, G. A. The unique role of parietal cortex in action observation: Functional organization for communicative and manipulative actions. *Neuroimage* **237**, 118220 (2021).

32. Urgen, B. A., Pehlivan, S. & Saygin, A. P. Distinct representations in occipito-temporal, parietal, and premotor cortex during action perception revealed by fMRI and computational modeling. *Neuropsychologia* **127**, 35–47 (2019).

33. Jastorff, J., Begliomini, C., Fabbri-Destro, M., Rizzolatti, G. & Orban, G. A. Coding observed motor acts: Different organizational principles in the parietal and premotor cortex of humans. *J Neurophysiol* **104**, 128–140 (2010).

34. Shepard, R. N. Towards a Universal Law of Generalization for Psychological Science. *Science (1979)* **237**, 1317–1323 (1987).

35. Edelman, S. Representation is representation of similarities. *Behav Brain Sci* **21**, 449–498 (1998).

36. Murphy, G. L. *The Big Book of Concepts*. (MIT Press, Cambridge, MA, 2002).

37. Haxby, J. V., Gobbini, M. I. & Nastase, S. A. Naturalistic stimuli reveal a dominant role for agentic action in visual representation. *Neuroimage* **216**, 116561 (2020).

38. Nastase, S. A., Goldstein, A. & Hasson, U. Keep it real: rethinking the primacy of experimental control in cognitive neuroscience. *Neuroimage* **222**, 117254 (2020).

39. Redcay, E. & Moraczewski, D. Social cognition in context: A naturalistic imaging approach. *Neuroimage* **216**, 116392 (2020).

40. ATUS. *American Time Use Survey*. *United States Department of Labor. Bureau of Labor Statistics* (2019).

41. Orban, G. A., Lanzilotto, M. & Bonini, L. From Observed Action Identity to Social Affordances. *Trends Cogn Sci* **25**, 493–505 (2021).

42. Graziano, M. S. A. & Aflalo, T. N. Mapping behavioral repertoire onto the cortex. *Neuron* **56**, 239–251 (2007).

43. Wurm, M. F., Caramazza, A. & Lingnau, A. Action categories in lateral occipitotemporal cortex are organized along sociality and transitivity. *Journal of Neuroscience* **37**, 562–575 (2017).

44. Monfort, M. *et al.* Moments in Time Dataset: one million videos for event understanding. *IEEE Trans Pattern Anal Mach Intell* 1–8 (2019).

45. Peelen, M. V., Romagno, D. & Caramazza, A. Independent representations of verbs and actions in left lateral temporal cortex. *J Cogn Neurosci* **24**, 2096–2107 (2012).

46. Tarhan, L. & Konkle, T. Sociality and interaction envelope organize visual action representations. *Nat Commun* **11**, 1–11 (2020).

47. Rosch, E. Cognitive representations of semantic categories. *J Exp Psychol Gen* **104**, 192–233 (1975).

48. Iordan, M. C., Greene, M. R., Beck, D. M. & Fei-Fei, L. Basic Level Category Structure Emerges Gradually across Human Ventral Visual Cortex. *J Cogn Neurosci* **27**, 1427–1446 (2015).

49. Zhuang, T. & Lingnau, A. The characterization of actions at the superordinate, basic and subordinate level. *Psychol Res* **86**, 1871–1891 (2022).

50. Krizhevsky, A., Sutskever, I. & Hinton, G. E. ImageNet Classification with Deep Convolutional Neural Networks. *Adv Neural Inf Process Syst* 1–9 (2012) doi:http://dx.doi.org/10.1016/j.protcy.2014.09.007.

51. Radford, A. *et al.* Learning Transferable Visual Models From Natural Language Supervision. *Arxiv preprint* (2021).

52. Devlin, J., Chang, M. W., Lee, K. & Toutanova, K. BERT: Pre-training of deep bidirectional transformers for language understanding. *NAACL HLT 2019 - 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies - Proceedings of the Conference* **1**, 4171–4186 (2019).

53. Brown, T. B. *et al.* Language models are few-shot learners. *Adv Neural Inf Process Syst* **2020-Decem**, (2020).

54. Kriegeskorte, N. & Mur, M. Inverse MDS: Inferring dissimilarity structure from multiple item arrangements. *Front Psychol* **3**, 1–13 (2012).

55. Lescroart, M. D., Stansbury, D. E. & Gallant, J. L. Fourier power, subjective distance, and object categories all provide plausible models of BOLD responses in scene-selective visual areas. *Front Comput Neurosci* **9**, 1–20 (2015).

56. Wurm, M. F. & Caramazza, A. Lateral occipitotemporal cortex encodes perceptual components of social actions rather than abstract representations of sociality. *Neuroimage* **202**, (2019).

57. McMahon, E. & Isik, L. Seeing social interactions. *Trends Cogn Sci* **xx**, (2023).

58. Gallivan, J. P. & Culham, J. C. Neural coding within human brain areas involved in actions. *Curr Opin Neurobiol* **33**, 141–149 (2015).

59. Muttenthaler, L., Dippel, J., Linhardt, L., Vandermeulen, R. A. & Kornblith, S. Human alignment of neural network representations. *ICLR 2023* (2022).

60. Jozwik, K. M. *et al.* Face dissimilarity judgments are predicted by representational distance in morphable and image-computable models. *Proc Natl Acad Sci U S A* **119**, 1–11 (2022).

61. Jozwik, K. M., Kriegeskorte, N., Storrs, K. R. & Mur, M. Deep convolutional neural networks outperform feature-based but not categorical models in explaining object similarity judgments. *Front Psychol* **8**, 1726 (2017).

62. Golan, T., Siegelman, M., Kriegeskorte, N. & Baldassano, C. Testing the limits of natural language models for predicting human language judgments. *ArXiv* 1–39 (2023).

63. Kriegeskorte, N. Deep Neural Networks: A New Framework for Modeling Biological Vision and Brain Information Processing. *Annu Rev Vis Sci* **1**, 417–446 (2015).

64. Cichy, R. M., Khosla, A., Pantazis, D. & Oliva, A. Dynamics of scene representations in the human brain revealed by magnetoencephalography and deep neural networks. *Neuroimage* (2016) doi:10.1016/j.neuroimage.2016.03.063.

65. Cichy, R. M., Khosla, A., Pantazis, D., Torralba, A. & Oliva, A. Comparison of deep neural networks to spatio-temporal cortical dynamics of human visual object recognition reveals hierarchical correspondence. *Sci Rep* **6**, 1–13 (2016).

66. Jozwik, K. M., Kietzmann, T. C., Cichy, R. M., Kriegeskorte, N. & Mur, M. Deep neural networks and visuo-semantic models explain complementary components of human ventral-stream representational dynamics. 1–10 (2021).

67. Al-Tahan, H. & Mohsenzadeh, Y. Reconstructing feedback representations in the ventral visual pathway with a generative adversarial autoencoder. *PLoS Comput Biol* **17**, 1–19 (2021).

68. Mohsenzadeh, Y., Mullin, C., Lahner, B. & Oliva, A. Emergence of Visual Center-Periphery Spatial Organization in Deep Convolutional Neural Networks. *Sci Rep* **10**, 4638 (2020).

69. Kumar, S. *et al.* Shared functional specialization in transformer-based language models and the human brain.

70. Hosseini, E. A. *et al.* Artificial neural network language models align neurally and behaviorally with humans even after a developmentally realistic amount of training. *bioRxiv* 2022.10.04.510681 (2022).

71. Schrimpf, M. *et al.* The neural architecture of language: Integrative modeling converges on predictive processing. *Proc Natl Acad Sci U S A* **118**, e2105646118 (2021).

72. Caucheteux, C. & King, J. R. Brains and algorithms partially converge in natural language processing. *Commun Biol* **5**, (2022).

73. Conwell, C., Prince, J. S., Hamblin, C. & Alvarez, G. A. Controlled assessment of CLIP-style language-aligned vision models in prediction of brain and behavioral data. *ICLR 2023* 1–12 (2023).

74. Popham, S. F. *et al.* Visual and linguistic semantic representations are aligned at the border of human visual cortex. *Nat Neurosci* **24**, (2021).

75. Marjieh, R. *et al.* Words are all you need? Capturing human sensory similarity with textual descriptors. (2022).

76. Wang, A. Y., Kay, K., Naselaris, T. & Tarr, M. J. Natural language supervision with a large and diverse dataset builds better models of human high-level visual cortex. (2023).

77. Doerig, A. *et al.* Semantic scene descriptions as an objective of human vision. (2022).

78. Bojanowski, P., Grave, E., Joulin, A. & Mikolov, T. Enriching Word Vectors with Subword Information. *Trans Assoc Comput Linguist* **5**, 135–146 (2016).

79. Kanwisher, N. Domain specificity in face perception. *Nat Neurosci* **3**, 759–763 (2000).

80. Kanwisher, N., McDermott, J. & Chun, M. M. The fusiform face area: a module in human extrastriate cortex specialized for face perception. *The Journal of Neuroscience* **17**, 4302–11 (1997).

81. Downing, P. E., Jiang, Y., Shuman, M. & Kanwisher, N. A cortical area selective for visual processing of the human body. *Science (1979)* **293**, 2470–2473 (2001).

82. Bracci, S., Ritchie, J. B. & de Beeck, H. O. On the partnership between neural representations of object categories and visual features in the ventral visual pathway. *Neuropsychologia* **105**, 153–164 (2017).

83. Haxby, J. V *et al.* Distributed and overlapping representations of faces and objects in ventral temporal cortex. *Science (1979)* **293**, 2425–30 (2001).

84. Jozwik, K. M., Kriegeskorte, N. & Mur, M. Visual features as stepping stones toward semantics: Explaining object similarity in IT and perception with non-negative least squares. *Neuropsychologia* **83**, 201–226 (2016).

85. Tacchetti, A., Isik, L. & Poggio, T. Invariant recognition drives neural representations of action sequences. *PLoS Comput Biol* **13**, 1–20 (2017).

86. Isik, L., Tacchetti, A. & Poggio, T. A fast, invariant representation for human action in the visual system. *J Neurophysiol* **119**, 631–640 (2018).

87. Felleman, D. J. & Van Essen, D. C. Distributed hierachical processing in the primate cerebral cortex. *Cerebral Cortex* **1**, 1–47 (1991).

88. Dittrich, W. H. Action categories and the perception of biological motion. *Perception* **22**, 15–22 (1993).

89. Neri, P., Morrone, M. C. & Burr, D. C. Seeing biological motion. *Nature* **395**, 894–896 (1998).

90. Grossman, E. D. & Blake, R. Brain areas active during visual perception of biological motion. *Neuron* **35**, 1167–1175 (2002).

91. Giese, M. A. & Poggio, T. Cognitive neuroscience: Neural mechanisms for the recognition of biological movements. *Nat Rev Neurosci* **4**, 179–192 (2003).

92. Thornton, X. M. A., Weaverdyck, M. E. & Tamir, X. I. The social brain automatically predicts others' future mental states. *Journal of Neuroscience* **39**, 140–148 (2019).

93. Spunt, R. P., Satpute, A. B. & Lieberman, M. D. Identifying the what, why, and how of an observed action: An fMRI study of mentalizing and mechanizing during action observation. *J Cogn Neurosci* **23**, 63–74 (2011).

94. McMahon, E., Bonner, M. F. & Isik, L. Hierarchical organization of social action features along the lateral visual pathway. *Current Biology* **33**, 1–13 (2023).

95. Wurm, M. F., Cramon, D. Y. & Schubotz, R. I. The Context-Object-Manipulation triad: Cross Talk during action perception revealed by fMRI. *J Cogn Neurosci* **24**, 1548–1559 (2012).

96. Bar, M. Visual objects in context. *Nat Rev Neurosci* **5**, 617–629 (2004).

97. Willems, R. M. & Peelen, M. V. How context changes the neural basis of perception and language. *iScience* **24**, 102392 (2021).

98. Magri, C., Elmoznino, E. & Bonner, M. F. Context predicts commonsense notions of object similarity. (2020).

99. Zacks, J. M. Event Perception and Memory. *Annu Rev Psychol* **71**, 165–191 (2020).

100. Manrique, N. F., Bao, W., Herbelot, A. & Hasson, U. Enhancing Interpretability using Human Similarity Judgements to Prune Word Embeddings. *ArXiv* (2023).

101. Schwartz, D., Toneva, M. & Wehbe, L. Inducing brain-relevant bias in natural language processing models. *Adv Neural Inf Process Syst* **32**, (2019).

102. Toneva, M. & Wehbe, L. Interpreting and improving natural-language processing (in machines) with natural language-processing (in the brain). *Adv Neural Inf Process Syst* **32**, (2019).

103. Muttenthaler, L. & Hebart, M. N. THINGSvision: A Python Toolbox for Streamlining the Extraction of Activations From Deep Neural Networks. *Front Neuroinform* **15**, 1–12 (2021).

104. Wolf, T. *et al.* Transformers: State-of-the-Art Natural Language Processing. *ArXiv* 38–45 (2020) doi:10.18653/v1/2020.emnlp-demos.6.

772   105.   Nunez-Elizalde, A., Deniz, F., Dupré la Tour, T., Visconti di Oleggio
773   Castello, M. & Gallant, J. pymoten: scientific python package for computing
774   motion energy features from video. Preprint at
775   https://doi.org/https://doi.org/10.5281/zenodo.6349625 (2021).
776   106.   Schütt, H. H., Kipnis, A. D., Diedrichsen, J. & Kriegeskorte, N. Statistical
777   inference on representational geometries. *Elife* **12**, 1–46 (2023).
778   107.   Nichols, T. E. & Holmes, A. P. Nonparametric Permutation Tests For
779   Functional Neuroimaging: A Primer with Examples. *Hum Brain Mapp* **25**, 1–25
780   (2001).
781   108.   Singh, K. D., Barnes, G. R. & Hillebrand, A. Group imaging of task-
782   related changes in cortical synchronisation using nonparametric permutation
783   testing. *Neuroimage* **19**, 1589–1601 (2003).
784   109.   Nili, H. *et al.* A Toolbox for Representational Similarity Analysis. *PLoS*
785   *Comput Biol* **10**, e1003553 (2014).
786   110.   Groen, I. I. *et al.* Distinct contributions of functional and deep neural
787   network features to representational similarity of scenes in human brain and
788   behavior. *Elife* **7**, e32962 (2018).