Cross-modal Generation of Hit-like Molecules via Foundation Model Encoding of Gene Expression Signatures

Jia-Bei Cheng[1], Xiaoyong Pan[1], Kaiyuan Yang[1], Shenghao Cao[1], Bin Liu[1] and Ye Yuan[1,*]

[1]Institute of Image Processing and Pattern Recognition, Shanghai Jiao Tong University, and

Key Laboratory of System Control and Information Processing, Ministry of Education of China,

Shanghai 200240, China

*To whom correspondence should be addressed.

Contact: yuanye_auto@sjtu.edu.cn

Abstract: Designing hit-like molecules from gene expression signatures takes into account multiple targets and complex biological effects, enabling the discovery of multi-target drugs for complex diseases. Traditional methods relying on similarity searching against a database are limited by the quality and size of the databases. Instead, multimodal deep learning offers the potential to overcome this bottleneck. Additionally, the recent development of foundation models provides a new perspective to understand gene expression levels. Thus, we propose GexMolGen (Gene Expression-based Molecule Generator) based on a foundation model scGPT to generate hit-like molecules from gene expression differences. By taking the desired and control gene expression profile as inputs, GexMolGen designs molecules that can induce the required transcriptome profile. The molecules generated by GexMolGen

exhibit a high similarity to known gene inhibitors. Overall, GexMolGen explores the

chemical and biological relationships in the drug discovery process. The source code

and demo are available at https://github.com/Bunnybeibei/GexMolGen.

Keywords: Hit-like molecule design, Cross-modal generation, Foundation models,

Contrastive Learning, Autoencoder, Autoregressive Model

Introduction

Drug discovery has two main groups of approaches: phenotype-based and

target-based . Target-based drug discovery relies on identifying and selecting specific

targets based on mechanistic models, but it may not effectively consider the complex

context of human physiology. On the other hand, phenotypic drug discovery involves

observing the therapeutic effects of new drugs on disease models to verify and screen

potential drug candidates, i.e. ibuprofen and minoxidil [1]. One classic case of this

method is the L1000 project, which enables searching for small molecules with

similar gene expression signatures in a database. However, the effectiveness of this

approach largely depends on the size and quality of the database, and the number of

recorded small molecules is much smaller than the actual drug space [2]. Considering

the correlation between small molecule data and gene expression changes, multimodal

techniques are being exploited to overcome these limitations.

With the continuous advancement of multimodal learning [3] [4], many

progresses have emerged in the field of AI for Science, including text-molecule

matching [5] and text-protein sequence generation [6]. In the context of

phenotype-based drug discovery, deep learning techniques have also been employed.

For example, Xie et al., [7] utilize gene expression changes to represent drug efficacy

and screen molecules, while Oscar Méndez-Lucio [8] and Dibyajyoti Das [9] directly

generate hit-like small molecules based on gene expression signatures. However, it

should be noted that some of these approaches [7] do not fully utilize gene expression

changes, and some methods [8] [9] solely rely on multilayer perceptrons (MLPs) to

process gene expression changes. Consequently, these methods may lack

comprehensive interaction between gene information and small molecule information.

The Transformer framework, renowned for its consideration of global information and

provision of flexibility in model design and expansion, offers a promising avenue for

gene encoding.

Since Theodoris et al. first applied the Transformer to single-cell transcriptome

data to build the Geneformer[10] model, there has been a surge in the development of

large models specifically designed for transcriptome data. Prominent examples

include scBERT[11], TOSICA [12], scGPT [13], scFoundation [14], SCimilarity[15],

and GeneCompass[16]. These general large models serve as foundation models,

offering deeper insights into gene interactions and achieving impressive results in

various downstream tasks, demonstrating their zero-shot capabilities and robustness.

With the AI-driven evolution of phenotype-based drug discovery, the rapid

advancement of multimodal technologies, and the impressive performance of

foundation models, we propose GexMolGen—a model that utilizes gene

transcriptomic profiles to guide the generation of hit-like molecules. In this study, we

explore the application of the gene transcriptional profiling-based foundation model

scGPT in the field of molecule generation for the first time. Different from previous

methods that commonly rely on one-dimensional SMILES representation [8] [9], we

synergistically incorporate the two-dimensional molecular graph representation with

the gene modality, offering potential for scalability and interpretability. Compared to

traditional methods and other works, our model achieves higher similarity to known

inhibitors in the task of generating specific gene inhibitors.

74 Dataset preprocessing

The datasets used in GexMolGen are derived from the L1000 public dataset (GEO ID:

GSE70138) [17]. The L1000 technology uses microarray measurements to record the

changes in gene expression caused by over 25,200 perturbagens, including around

19,800 small molecules, in cell lines. This dataset is processed hierarchically and

divided into five levels: Levels 1-3 show the absolute expression levels of each gene

in each bead, while Levels 4-5 show the differentially expression levels of each gene

by comparing samples within each bead.

During the data preprocessing stage, three issues are considered. 1. The

pre-trained model scGPT[13] is trained on absolute gene expression levels, while

most L1000-related work primarily relies on Level 5 data. 2. The sample sizes for

each small molecule are extremely imbalanced (maximum to minimum ratio of 22:1).

3. Splitting the dataset based on SMILES representations may result in the same

molecule being included in both the training and test sets, due to the non-uniqueness

of SMILES.

To address the above issues, we process the data as follows: 1. Use Level 3 data

to encode both the experimental and control groups and subsequently calculate gene

expression signatures. 2. Average gene expression to ensure each small molecule can

be represented by a single data point. 3. Use the main layer of InChI-key to partition

the training, validation, and test sets, thus enabling unambiguous identification of

compounds.

Specifically, we first select the experimental data and control data from Level 3,

ensuring that they are from the same bead. These data belong to six major cell lines

(VCAP, PC3, A549, A375, HT29, MCF7). We then calculate the average gene

expression for each small molecule, resulting in a final dataset size of $2 \times 15156 \times$

978: 2 represents the experimental and control groups, 15156 represents the sample

size, and 978 represents the number of gene categories. Additionally, we divide the

structures by the main layer of InChI-key, resulting in a total of 6360 structures. From

this set, we randomly select 300 structures (comprising 708 types of small molecules)

as the test set, and another 300 structures (comprising 691 types of small molecules)

as the validation set. The remaining data is used for model training.

Overview of GexMolGen

GexMolGen divides the task of generating hit-like molecules from gene expression

profiles into four steps (as shown in **Figure 1**): 1. Encoding of gene and small

molecule data, 2. Matching of the gene modality and small molecule modality, 3.

Transforming gene modality to small molecule modality, 4. Decoding of small

molecule modality. To simplify the process, we use pre-trained models for both the

encoder and decoder in steps 1 and 4, respectively, namely scGPT [13] and hierVAE

[18]. We introduce step 2 to address the significant differences and complex

mechanisms between gene modality and small molecule modality. Matching and then

transforming the modalities can improve the quality and controllability of the

cross-modal generation model [19] [20].

Data Encoding

In Step 1, we encode the transcriptomic data and small molecule data separately based

on scGPT[13] and hierVAE[18].

Gene Encoder

For gene encoder, scGPT introduces gene tokens to capture additional information. It

treats a transcript as a sentence, with genes as words. This allows us to create a

specific dictionary for each gene. We obtain the gene tokens for the i-th data using a

pre-trained specific gene dictionary:

$$t_g^{(i)} = [id(g_1^{(i)}), id(g_2^{(i)}) \ldots \ldots id(g_M^{(i)})]$$

where $t_g^{(i)}$ represents the gene token encoding for the i-th data, and $id\left(g_j^{(i)}\right)$

represents the unique integer identifier for gene g_j in the i-th data. In our case, we

set M as 968 since there are 10 genes that do not appear in the pre-trained gene

dictionary.

Next, we preprocess the expression values following the same steps as scGPT:

TPM normalization and log1p transformation.

$$x^{(i)} = \left[x_1^{(i)}, x_2^{(i)} \ldots \ldots x_M^{(i)} \right]$$

130   The gene embedding is then defined as follows:

$$z_g^{(i)} = emb_g(t_g^{(i)}) + emb_x(x^{(i)})$$

where $emb_g(\cdot)$ refers to the conventional embedding layers, and $emb_x(\cdot)$

represents the fully connected layer. The experimental group and control group are

independently encoded using the same approach.

Molecule Encoder

For the molecule encoder, hierVAE regards motifs as the smallest informational units

for generating small molecules and constructs a motif dictionary. This approach

achieves high validity in molecular generation. We use the preprocessing program of

hierVAE to obtain the atom layer $\mathcal{H}_\mathcal{G}^g$, the attachment layer $\mathcal{H}_\mathcal{G}^a$, and the motif layer

$\mathcal{H}_\mathcal{G}^s$ for small molecules, where the previous layer can serve as the encoding

condition for the subsequent layer, enabling hierarchical encoding.

The input for the atom layer $\mathcal{H}_\mathcal{G}^g$ is the molecular graph $\mathcal{G}$, the edge features

$\{e(b_{uv})\}$, and the node features $\{e(a_u)\}$. Through the message passing neural

network[21][22] $MPN_\psi(\cdot)$, we obtain the encoded features:

$$c_\mathcal{G}^g = \{h_v\} = MPN_{\psi_1}(\mathcal{H}_\mathcal{G}^g, \{e(a_u)\}, \{e(b_{uv})\})$$

144   where h_v represents the updated atomic features.

145   The attachment layer $\mathcal{H}_\mathcal{G}^a$ updates its nodes using the following equation:

$$c_\mathcal{G}^a = \{h_{\mathcal{A}_i}\} = MPN_{\psi_2}(\mathcal{H}_\mathcal{G}^g, \{f_{\mathcal{A}_i}\}, \{e(d_{ij})\})$$

146   where $\{e(d_{ij})\}$ denotes the edge features for the motif layer, and $\{f_{\mathcal{A}_i}\}$ can be

147 calculated based on h_v and $\mathcal{A}_i$:

$$f_{\mathcal{A}_i} = emb_{\mathcal{A}_i}(e(\mathcal{A}_i), \sum_{v \in S_i} h_v)$$

148 Here, $emb_{\mathcal{A}_i}(\cdot)$ represents a fully connected layer, and $\mathcal{A}_i$ is the set of overlapping

149 atoms between adjacent motifs.

150   The motif layer $\mathcal{H}_{\mathcal{G}}^s$ updates its nodes using the following equation:

$$c_{\mathcal{G}}^s = \{h_{S_i}\} = MPN_{\psi_3}(\mathcal{H}_{\mathcal{G}}^s, \{f_{S_i}\}, \{e(d_{ij})\})$$

151 where $\{e(d_{ij})\}$ denotes the edge features for the motif layer, and $\{f_{S_i}\}$ can be

152 calculated based on $h_{\mathcal{A}_i}$ and S_i:

$$f_{S_i} = emb_{S_i}(e(S_i), h_{\mathcal{A}_i})$$

153 Here, $emb_{S_i}(\cdot)$ represents a fully connected layer, and S_i represents the type of the

154 motif.

155   Finally, the embedding of the i-th molecule is defined as:

$$z_m^{(i)} = \mu(h_{S_1}) + \exp(\sum(h_{S_1})) \cdot \epsilon$$

$$\epsilon \sim \mathcal{N}(0, I)$$

where $\mu(h_{S_1})$, $\sum(h_{S_1})$ are both fully connected layers representing the mean and log

variance, respectively, and S_1 represents the root motif, which is also the first motif

for decoding.

Contrastive Learning-based multimodal matching

In Step 2, to better capture the mutual information between gene and small molecule

modalities and enhance the controllability of the generation model, we adopted

contrastive learning [23] [24] for multi-modal matching. During the training process,

we encountered two challenges: 1. How to obtain gene expression signatures

encoding from the gene embeddings of the experimental and control groups. 2. How

to address model collapse.

For the first question, we tried two approaches: direct concatenation into a larger

vector (1936 x 512) and taking the difference while keeping the size as (968 x 512).

Both methods yielded similar matching results. Due to the quadratic increase in

computational complexity with vector length [25] [26], we chose the second

representation.

To address the second issue, we propose auxiliary-guided matching, which is

explained in detail below.

Auxiliary-guided matching

During the training process of step 2, we encountered model collapse, where different

input vectors would result in nearly identical output vectors. We hypothesized that this

was due to the model struggling to effectively differentiate between positive and

negative sample pairs in the early stages of training, leading to weak gradient signals

and a local optimum. Additionally, we observed two phenomena: 1. If we used

cross-entropy loss, the model would not collapse, but due to the large number of small

molecule types (13757), the model would not converge. 2. The gene encoder was

easily prone to collapse. Based on our analysis and observations, we implemented the

following steps to assist the model [23] in learning.

Hierarchical clustering of small molecules: Hierarchical clustering merges data into

clusters step by step by calculating the similarity between them, until a complete

tree-like structure is formed. We use hierarchical clustering to cluster the small

molecule embeddings into $C = \{c_1, c_2, c_3\}$ clusters. The detailed process is shown in

Algorithm 1.

Auxiliary-guided gene encoding: The output of the final layer in our gene encoder is

compared against small molecule vectors for contrastive learning. The optimization

objective is to minimize the InfoNCE loss function[27]:

191
$$\mathcal{L}_{InfoNCE} = -\frac{1}{2} E_{z_m, z_g} \left[log \frac{exp\left(E(z_m, z_g)\right)}{exp\left(E(z_m, z_g)\right) + \Sigma_{g'} exp\left(E(z_m, z_g')\right)} \right]$$

192
$$-\frac{1}{2} E_{z_m, z_g} \left[log \frac{exp\left(E(z_m, z_g)\right)}{exp\left(E(z_m, z_g)\right) + \Sigma_{m'} exp\left(E(z_m', z_g)\right)} \right]$$

Where m and g is z_m' and z_g' are unpaired molecule-gene negative sample pairs in a

batch, $E(.,.)$ is an energy (scalar) function defined on the two modalities, and we

use vector dot product for representation.

However, contrastive learning often faces model collapse, a common

phenomenon in its results. The InfoNCE loss aims to minimize the distance between

positive samples and maximize the distance between negative samples. Gradient

analysis [28] reveals that the gradients related to negative samples are proportional to

their similarity to the anchor, demonstrating that it is a hardness-aware loss function.

Therefore, exploring difficult negative samples is crucial for the effectiveness of

contrastive learning. Unfortunately, in the field of life sciences, the importance of

difficult negative samples is often overlooked due to the lack of ground truth for

cross-modal relationships. GexMolGen defines drugs with high similarity as hard

negative samples for each other's gene expression profiles. Hierarchical clustering is

employed to group molecules into clusters, and the model's learning is guided by the

cross-entropy loss function at a coarse resolution. Assuming that the small molecules

have been clustered into $C = \{c_1, c_2, c_3\}$ classes through hierarchical clustering, we

require the gene encoder to classify the corresponding perturbed drugs based on only

two states of gene expression profiles. The quality of classification is measured by the

cross-entropy loss function:

212
$$\mathcal{L}_{CE\_c} = -\sum_{i=1}^{N} y_{c,i} log\left(p_{c,i}\right)$$

213   where $y_{c,i}$ and $p_{c,i}$ denote the labels and predicted labels, respectively, for the c-th

214   cluster of small molecules based on gene embeddings.

215   During the learning process, our gene encoder optimizes two losses: InfoNCE

216   loss $\mathcal{L}_{InfoNCE}$ for contrastive learning and cross-entropy loss $\mathcal{L}_{CE\_c}$ for the auxiliary

217   guidance in the classification task.

$$\mathcal{L}_{contrast} = \mathcal{L}_{InfoNCE} + \sum_{i=1}^{C} \mathcal{L}_{CE\_c}$$

The values of c_1, c_2, and c_3 (10, 100, and 1000, respectively) are chosen based

on the following considerations: providing adequate tolerance for similar drugs by

limiting task categories, ensuring consistency in guided labels with the sufficiency of

identical fine-grained labels for identical coarse-grained labels, and prioritizing

simplicity by exponentially increasing the category count in each subsequent layer.

Facilitator-based autoregressive model

Assuming our dataset consists of sample pairs (m, g) where m represents a small

molecule and g represents its corresponding gene expression profile, we model

GexMolGen, denoted as $P(m|g)$, using a two-step process involving modality

facilitation and model generation [29]. Let z_m and z_g represent the embeddings of

the small molecule and gene, respectively. Thus, $P(m|g)$ can be decomposed as

$$P(m|g) = P(m, z_m|g) = P(m|z_m, g)P(z_m|g).$$

The first equation holds because z_m is a deterministic function of the small molecule

dataset m, and the second equation holds due to the chain rule [30] [19].

When the small molecule decoder $P(m|z_m, g)$ has been determined [18], the

primary focus is on optimizing the facilitator $P(z_m|g)$. For a straightforward

approach multi-layer perceptrons (MLPs), it obtained unsatisfactory results with

almost 30% higher loss. Additionally, it did not facilitate further exploration of the

relationship between small molecule structure and specific gene expression signatures.

Taking these limitations into account, we adopt an autoregressive model for modality

transformation [31] [32] [33].

When choosing a loss function for this module, cross-entropy is often considered

a better choice than mean squared error (MSE) because it handles probability

distributions better and its derivative directly reflects differences between probability

distributions, facilitating gradient computation and observation of significant changes.

However, when z_m is a continuous value, the cross-entropy loss function cannot be

used directly. To address this, we follow the approach of DALL·E2 [30], and reduce

the dimensionality of z_m from 64 to $L = 43$ using PCA while retaining almost all

the information (reconstruction MSE error below 1%). Subsequently, we discretize

the L-dimensional values into 1024 bins based on their magnitudes.

Figure 1 provides the details of the facilitator. Its input comprises 968 genes, a

special symbol [start], and L small molecule tokens, and it sequentially outputs

predicted values. The loss function is defined as:

251
$$\mathcal{L}_p = -\sum_{i=0}^{L} t_i log(p_i(x^{(i)}|x^{(0:i-1)})),$$

where t_i and $p_i(x^{(i)}|x^{(0:i-1)})$ represent the i-th true token and predicted token,

respectively, of the small molecule embeddings.

Beam search-based generation optimization

Beam search is a widely utilized search algorithm in the field of sequence generation

tasks [34] [35]. It leverages the concept of dynamic programming by maintaining a set

of candidate sequences, referred to as the beam, with a size of K in order to retain

promising outcomes. This algorithm effectively controls the search space while

enhancing the quality and accuracy of the generated results. Specifically, the beam

search algorithm follows the subsequent steps: 1. Initialization of the beam. 2. For

each time step, the probability of each candidate token as the subsequent token is

calculated based on the current sequence. 3. The tokens are sorted according to their

probabilities, and the top K tokens are selected to form a new sequence. Steps 2 and

3 are repeated until a complete sequence of small molecule tokens is generated. In our

model, K is set to 20. 4. These K discrete small molecule tokens are transformed

back into the original z_m through the utilization of PCA and are subsequently fed

into the small molecule decoder [18] denoted as $P(m|z_m, g)$. This decoding process

generates 20 types of hit-like small molecules' SMILES and molecular graphs.

Molecular

Result and Discussion

To demonstrate the advantages of GexMolGen, we conducted two experiments to verify the generalization ability and zero-shot ability of GexMolGen.

Generating Complex Hit-like Molecules from Compound-Induced Gene Expression

In this section, we train our model to generate drug-like small molecules from compound-induced gene expression data. We input 708 test samples into the model and obtain the molecular graphs and SMILES representations of the generated molecules. **Figure 2** illustrates a comparison between the generated molecules by GexMolGen and the actual active molecules (more details can be found in **Appendix Table 1**). The results demonstrate that our model GexMolGen successfully generates the majority of the scaffolds of the reference molecules, handles long-chain molecules (e.g., **Figure 2(4)(10)**), and effectively deals with complex structures such as cyclic structures (**Figure 2(1)**) and cross structures (**Figure 2(7)**).

To better assess the generative capabilities of GexMolGen, we compare it with two baseline methods: calculating the cosine similarity and Euclidean distance between the gene expression signatures of the test set and the training set to find the most similar hit-like small molecules [8]. To evaluate the impact of gene expression signatures on the generation of small molecules, we add a random group where the model directly samples from the molecule latent space. We use three measurement metrics: Tanimoto similarity based on Morgan fingerprints (radius=3, 1024 bits) to

capture global molecular features, Tanimoto similarity based on MACCS keys, and

Fraggle similarity to capture local structural similarities..

Figure 3 shows the distribution of the metrics for our model and three other

methods. Detailed data can be found in **Appendix Table 1-3.** The results generated by

our model significantly outperform the other three methods (p-value < 0.001 from a

one-sided Mann-Whitney U-test for the four different molecular representations).

It is worth noting that in the distribution of Tanimoto similarity based on Morgan

fingerprints (**Figure 3(b)**), the trend of the results generated by our model is similar to

the results obtained from cosine similarity search. We speculate that this similarity is

due to the use of cosine distance in the contrastive learning process to calculate the

similarity between the two modal vectors. Therefore, these two methods exhibit a

similar trend in the distribution of metrics that focus on the global similarity. However,

in the other two metrics (**Figure 3(a)** and **(c)**), our model outperforms the cosine

similarity search method, with a mean Fraggle similarity of 0.57 and a mean MACCS

similarity of 0.70. This indicates that our model generates more molecular fragments

and feature keys that are similar to the target molecules. Interestingly, for all three

metrics, the Euclidean distance search method performs worse than the cosine

similarity method. This may be due to the curse of dimensionality, where the

Euclidean distance becomes less sensitive to differences in gene expression profiles as

the dimension increases. The randomly generated method performs the worst, as it

occasionally generates molecules with high similarity scores (e.g., **Figure 3(b)**: 1.19%

with a similarity > 0.29), but also produces more molecules with very low similarity

scores (e.g., **Figure 3(b)**: 26.27% with similarity < 0.08).

Generating Complete Hit-like Molecule Scaffolds from Knock-out Gene

Expression

To demonstrate the ability of GexMolGen for generating hit-like small molecule

skeletons from knock-out gene expression data, we compare them with known target

inhibitors. The underlying hypothesis is that when a protein is knocked out, it leads to

a gene expression signature resembling that observation when the same target protein

is inhibited by a potent and selective inhibitor. This assumption is based on the notion

that both scenarios hypothetically trigger similar cellular adjustments, resulting in

equivalent changes in gene expression [8]. This experiment primarily aims to validate

the zero-shot capability of our model GexMolGen.

To ensure a fair comparison, we initially gather 10 known inhibitors of human

genes, which are the same as those used in the WGAN [8] experiments, from the

ExCape dataset [38]. These genes include AKT1, AKT2, AURKB, CTSK, EGFR,

HDAC1, MTOR, PIK3CA, SMAD3, and TP53. Our selection criteria include a Pic50

value greater than or equal to 5, InChi-key not appearing in the training set, and

compliance with valence bond rules. In the end, we obtain 2,153, 1,293, 2,122, 1,609,

4,244, 1,939, 2,858, 2,292, 23,758, and 12,860 known inhibitors for AKT1, AKT2,

AURKB, CTSK, EGFR, HDAC1, MTOR, PIK3CA, SMAD3, and TP53, respectively.

Then, we extract 100 experimental and control group transcriptome profiles for each

of these 10 genes from the CRISPR knock-out perturbation data in the L1000 dataset.

We employ the three evaluation metrics: Tanimoto similarity based on Morgan

fingerprints, Tanimoto similarity based on MACCS keys, and Fraggle similarity. We

also employ the same three comparison methods as before: cosine similarity and

Euclidean distance search to find the most similar small molecules based on gene

expression signatures, and random generation using the small molecule decoder. Each

method independently identifies 100 candidate hit-like compounds based on the

provided transcriptome. We then record the highest similarity score between each

candidate and the known inhibitors as the model's score.

Figure 4 shows the visual comparison between the molecules generated by our

model and the known inhibitors based on Morgan fingerprint similarity scores. It can

be observed that our model not only generates molecules that are overall highly

similar to the known inhibitors (the average similarity score of WGAN[8] is only 0.26,

refer to **Appendix Figure 1** and **Table 4** for detailed results) but also generates the

complete skeleton parts of the molecules (e.g., **Figure 4(4)(5)(6)**).

Next, we present the experimental results in **Figure 5** using box plots. Overall,

our model performs better than the other three methods, except for the Fraggle score

in the task of finding MTOR inhibitors, where it is slightly lower than the cosine

similarity and Euclidean distance-based methods (mean Fraggle similarity = 0.60).

However, interestingly, our model achieves the highest Fraggle score (max Fraggle

similarity = 0.96) and performs better than the traditional methods in terms of

MACCS fingerprint and Morgan fingerprint scores. We analyze this phenomenon as

the training set contains many molecular fragments similar to the MTOR inhibitors,

so directly searching the training set using traditional methods can achieve higher

Fraggle scores. However, the molecular fragments in the training set do not

necessarily have high similarity to the MTOR inhibitors in terms of molecular

fingerprints, resulting in lower MACCS fingerprint and Morgan fingerprint scores. In

addition, we find that the randomly generated method performs worse due to the

diversity of the unconditional generation model, occasionally generating molecules

with high similarity scores but also generating a larger number of molecules with very

low similarity (e.g., **Figure 5 AKT2**). Conversely, traditional methods are constrained

by the similarity of gene expression profiles. While they do not generate molecules

with very low scores, they only identify a restricted number of hit-like small

molecules for certain genes, resulting in many box plots appearing as lines (e.g.,

Figure 5 CTSK). In contrast, our generative model, achieves a trade-off between

diversity and accuracy by conditioning on gene embeddings.

Furthermore, we have organized the performance of other methods on similar

tasks. Although the tested genes may vary, it can be generally observed that our model

achieves above-average results. Moreover, our model possesses inherent advantages

such as high effectiveness and strong scalability.

Discussion

In this study, we design a model called GexMolGen to generate candidate hit-like

molecules based on gene expression signatures. We apply gene transcriptional

profiling-based foundation models for downstream multimodal molecule generation.

Unlike the SMILES-based multimodal fusion used in previous studies [8] [9], we use

more informative two-dimensional molecular representations [18]. In the training

process, we use assisted guidance to alleviate the collapse problem of the model and

improve the alignment of modalities. By using a self-attention-based autoregressive

modality transformer and beam search optimization, our model achieves good results

in generating gene inhibitors. Additionally, we explore a new gene model mask

strategy to prevent changes in the biological significance of gene spectra caused by

masking.

However, our model has some limitations. First, we do not exhaustively test all

available gene transcriptional profiling-based models. Because some models are not

open-source [14] [36], directly converting certain foundation models into gene

expression signatures is challenging [12] [11]. Taking various factors into

consideration, we select scGPT [8], but this does not imply that other large-scale

models perform worse. Second, for the sake of simplicity, we choose a unified model

for molecular encoding and decoding [18]. However, we find that advancements in

the field of molecular representation [39] [22] [40] [41] may outpace the encoding

modules in molecular generators [42] [35]. Therefore, the molecular encoding part

can be updated with other excellent works in the future.

In the future, we expect to do two things regarding GexMolGen. First, we want to

explore the interpretability between molecular fragments and specific gene expression

signatures, which is the original intention behind using autoregressive models and

discretizing molecular embedding. Second, addressing the aforementioned limitations,

we intend to investigate the potential of separating the molecular encoder and decoder

to improve cross-modal accuracy.

Funding

402 This work was supported by grants from National Natural Science Foundation of
403 China 62103262(to Y.Y.) and the Shanghai Pujiang Programme (no. 21PJ1407700 to
404 Y.Y.).

Reference

[1] F. Vincent, A. Nueda, J. Lee, M. Schenone, M. Prunotto, and M. Mercola,
"Phenotypic drug discovery: recent successes, lessons learned and new directions,"
Nat Rev Drug Discov, vol. 21, no. 12, Art. no. 12, Dec. 2022, doi:
10.1038/s41573-022-00472-w.
[2] A. Musa *et al.*, "A review of connectivity map and computational approaches in
pharmacogenomics," *Briefings in Bioinformatics*, vol. 18, no. 5, p. 903, Sep. 2017,
doi: 10.1093/bib/bbx023.
[3] J. Li, R. R. Selvaraju, A. D. Gotmare, S. Joty, C. Xiong, and S. Hoi, "Align before
Fuse: Vision and Language Representation Learning with Momentum Distillation."
arXiv, Oct. 07, 2021. doi: 10.48550/arXiv.2107.07651.
[4] J. Li, D. Li, C. Xiong, and S. Hoi, "BLIP: Bootstrapping Language-Image Pre-training
for Unified Vision-Language Understanding and Generation." arXiv, Feb. 15, 2022.
doi: 10.48550/arXiv.2201.12086.
[5] C. Edwards, C. Zhai, and H. Ji, "Text2Mol: Cross-Modal Molecule Retrieval with

Natural Language Queries," in *Proceedings of the 2021 Conference on Empirical*

Methods in Natural Language Processing, Online and Punta Cana, Dominican

Republic: Association for Computational Linguistics, 2021, pp. 595–607. doi:

10.18653/v1/2021.emnlp-main.47.

[6] S. Liu *et al.*, "A Text-guided Protein Design Framework." arXiv, Feb. 09, 2023.

Accessed: Jun. 29, 2023. [Online]. Available: http://arxiv.org/abs/2302.04611

[7] J. Zhu *et al.*, "Prediction of drug efficacy from transcriptional profiles with deep

learning," *Nat Biotechnol*, vol. 39, no. 11, Art. no. 11, Nov. 2021, doi:

10.1038/s41587-021-00946-z.

[8] O. Méndez-Lucio, B. Baillif, D.-A. Clevert, D. Rouquié, and J. Wichard, "De novo

generation of hit-like molecules from gene expression signatures using artificial

intelligence," *Nat Commun*, vol. 11, no. 1, Art. no. 1, Jan. 2020, doi:

10.1038/s41467-019-13807-w.

[9] D. Das, B. Chakrabarty, R. Srinivasan, and A. Roy, "Gex2SGen: Designing Drug-like

Molecules from Desired Gene Expression Signatures," *J. Chem. Inf. Model.*, vol. 63,

no. 7, pp. 1882–1893, Apr. 2023, doi: 10.1021/acs.jcim.2c01301.

[10] C. V. Theodoris *et al.*, "Transfer learning enables predictions in network biology,"

Nature, vol. 618, no. 7965, Art. no. 7965, Jun. 2023, doi:

10.1038/s41586-023-06139-9.

[11] F. Yang *et al.*, "scBERT as a large-scale pretrained deep language model for cell

type annotation of single-cell RNA-seq data," *Nat Mach Intell*, vol. 4, no. 10, Art. no.

10, Oct. 2022, doi: 10.1038/s42256-022-00534-z.

[12] J. Chen, H. Xu, W. Tao, Z. Chen, Y. Zhao, and J.-D. J. Han, "Transformer for one

stop interpretable cell type annotation," *Nat Commun*, vol. 14, no. 1, Art. no. 1, Jan.

2023, doi: 10.1038/s41467-023-35923-4.

[13] H. Cui, C. Wang, H. Maan, K. Pang, F. Luo, and B. Wang, "scGPT: Towards

Building a Foundation Model for Single-Cell Multi-omics Using Generative AI."

bioRxiv, p. 2023.04.30.538439, Jul. 02, 2023. doi: 10.1101/2023.04.30.538439.

[14] M. Hao *et al.*, "Large Scale Foundation Model on Single-cell Transcriptomics."

bioRxiv, p. 2023.05.29.542705, Jun. 21, 2023. doi: 10.1101/2023.05.29.542705.

[15] G. Heimberg *et al.*, "Scalable querying of human cell atlases via a foundational

model reveals commonalities across fibrosis-associated macrophages." bioRxiv, p.

2023.07.18.549537, Jul. 19, 2023. doi: 10.1101/2023.07.18.549537.

[16] X. Yang *et al.*, "GeneCompass: Deciphering Universal Gene Regulatory

Mechanisms with Knowledge-Informed Cross-Species Foundation Model." bioRxiv,

p. 2023.09.26.559542, Sep. 28, 2023. doi: 10.1101/2023.09.26.559542.

[17] A. Subramanian *et al.*, "A Next Generation Connectivity Map: L1000 Platform and

the First 1,000,000 Profiles," *Cell*, vol. 171, no. 6, pp. 1437-1452.e17, Nov. 2017, doi:

10.1016/j.cell.2017.10.049.

[18] W. Jin, R. Barzilay, and T. Jaakkola, "Hierarchical Generation of Molecular Graphs

using Structural Motifs." arXiv, Apr. 18, 2020. Accessed: Jan. 28, 2023. [Online].

Available: http://arxiv.org/abs/2002.03230

[19] A. Ramesh *et al.*, "Zero-Shot Text-to-Image Generation." arXiv, Feb. 26, 2021.

Accessed: Mar. 17, 2023. [Online]. Available: http://arxiv.org/abs/2102.12092

[20] A. Sanchez-Fernandez, E. Rumetshofer, S. Hochreiter, and G. Klambauer,

"Contrastive learning of image- and structure-based representations in drug

discovery," presented at the ICLR2022 Machine Learning for Drug Discovery, Apr.

2022. Accessed: Aug. 26, 2023. [Online]. Available:

https://openreview.net/forum?id=OdXKRtg1OG

[21] H. Dai, B. Dai, and L. Song, "Discriminative Embeddings of Latent Variable Models

for Structured Data." arXiv, Jan. 10, 2020. Accessed: Nov. 02, 2023. [Online].

Available: http://arxiv.org/abs/1603.05629

[22] M. Fey, J.-G. Yuen, and F. Weichert, "Hierarchical Inter-Message Passing for

Learning on Molecular Graphs." arXiv, Jun. 22, 2020. doi:

10.48550/arXiv.2006.12179.

[23] P. Khosla *et al.*, "Supervised Contrastive Learning." arXiv, Mar. 10, 2021. Accessed:

Jul. 05, 2023. [Online]. Available: http://arxiv.org/abs/2004.11362

[24] Y. Tian, D. Krishnan, and P. Isola, "Contrastive Multiview Coding," in *Computer*

Vision – ECCV 2020: 16th European Conference, Glasgow, UK, August 23–28,

2020, Proceedings, Part XI, Berlin, Heidelberg: Springer-Verlag, Aug. 2020, pp.

776–794. doi: 10.1007/978-3-030-58621-8_45.

[25] A. Vaswani *et al.*, "Attention is all you need," in *Proceedings of the 31st International*

Conference on Neural Information Processing Systems, in NIPS'17. Red Hook, NY,

USA: Curran Associates Inc., Dec. 2017, pp. 6000–6010.

[26] T. Dao, D. Fu, S. Ermon, A. Rudra, and C. Ré, "FlashAttention: Fast and

Memory-Efficient Exact Attention with IO-Awareness," *Advances in Neural*

Information Processing Systems, vol. 35, pp. 16344–16359, Dec. 2022.

[27]   A. van den Oord, Y. Li, and O. Vinyals, "Representation Learning with Contrastive

Predictive Coding," arXiv.org. Accessed: Sep. 01, 2023. [Online]. Available:

https://arxiv.org/abs/1807.03748v2

[28]   F. Wang and H. Liu, "Understanding the Behaviour of Contrastive Loss." arXiv, Mar.

20, 2021. doi: 10.48550/arXiv.2012.09740.

[29]   M. Ding *et al.*, "CogView: Mastering Text-to-Image Generation via Transformers."

arXiv, Nov. 05, 2021. doi: 10.48550/arXiv.2105.13290.

[30]   A. Ramesh, P. Dhariwal, A. Nichol, C. Chu, and M. Chen, "Hierarchical

Text-Conditional Image Generation with CLIP Latents." arXiv, Apr. 12, 2022. doi:

10.48550/arXiv.2204.06125.

[31]   "Radford 等 - Language Models are Unsupervised Multitask Learner.pdf."

Accessed: Aug. 26, 2023. [Online]. Available:

https://cdn.openai.com/better-language-models/language_models_are_unsupervise

d_multitask_learners.pdf

[32]   M. Lewis *et al.*, "BART: Denoising Sequence-to-Sequence Pre-training for Natural

Language Generation, Translation, and Comprehension." arXiv, Oct. 29, 2019. doi:

10.48550/arXiv.1910.13461.

[33]   C. Raffel *et al.*, "Exploring the Limits of Transfer Learning with a Unified Text-to-Text

Transformer." arXiv, Jul. 28, 2020. doi: 10.48550/arXiv.1910.10683.

[34]   OpenAI, "GPT-4 Technical Report." arXiv, Mar. 27, 2023. doi:

10.48550/arXiv.2303.08774.

[35]   X. Bresson and T. Laurent, "A Two-Step Graph Convolutional Decoder for Molecule

509   Generation." arXiv, Jun. 15, 2019. doi: 10.48550/arXiv.1906.03412.

510   [36]   J. Gong *et al.*, "xTrimoGene: An Efficient and Scalable Representation Learner for

511   Single-Cell RNA-Seq Data." bioRxiv, p. 2023.03.24.534055, Mar. 25, 2023. doi:

512   10.1101/2023.03.24.534055.

513   [37]   E. Nguyen *et al.*, "HyenaDNA: Long-Range Genomic Sequence Modeling at Single

514   Nucleotide Resolution." arXiv, Jun. 27, 2023. doi: 10.48550/arXiv.2306.15794.

515   [38]   J. Sun *et al.*, "ExCAPE-DB: an integrated large scale dataset facilitating Big Data

516   analysis in chemogenomics," *Journal of Cheminformatics*, vol. 9, no. 1, p. 17, Mar.

517   2017, doi: 10.1186/s13321-017-0203-5.

518   [39]   G. Zhou *et al.*, "Uni-Mol: A Universal 3D Molecular Representation Learning

519   Framework." ChemRxiv, May 26, 2022. doi: 10.26434/chemrxiv-2022-jjm0j.

520   [40]   K. Atz, F. Grisoni, and G. Schneider, "Geometric deep learning on molecular

521   representations," *Nat Mach Intell*, vol. 3, no. 12, Art. no. 12, Dec. 2021, doi:

522   10.1038/s42256-021-00418-8.

523   [41]   J. Xia *et al.*, "MOLE-BERT: RETHINKING PRE-TRAINING GRAPH NEURAL

524   NETWORKS FOR MOLECULES," 2023.

525   [42]   C. Zang and F. Wang, "MoFlow: An Invertible Flow Model for Generating Molecular

526   Graphs," in *Proceedings of the 26th ACM SIGKDD International Conference on*

527   *Knowledge Discovery & Data Mining*, in KDD '20. New York, NY, USA: Association

528   for Computing Machinery, Aug. 2020, pp. 617–626. doi: 10.1145/3394486.3403104.

[43]   R. Shayakhmetov *et al.*, "Molecular Generation for Desired Transcriptome Changes

With Adversarial Autoencoders," *Frontiers in Pharmacology*, vol. 11, 2020,

Accessed: Aug.   27,   2023.   [Online].   Available:

https://www.frontiersin.org/articles/10.3389/fphar.2020.00269

[44] "TRIOMPHE: Transcriptome-Based Inference and Generation of Molecules with

Desired Phenotypes by Machine Learning." Accessed: Aug. 27, 2023. [Online].

Available: https://pubs.acs.org/doi/epdf/10.1021/acs.jcim.1c00967

[45] J. Born, M. Manica, A. Oskooei, J. Cadow, and M. Rodríguez Martínez,

"PaccMannRL: Designing Anticancer Drugs From Transcriptomic Data via

Reinforcement Learning," in *Research in Computational Molecular Biology*, R.

Schwartz, Ed., in Lecture Notes in Computer Science. Cham: Springer International

Publishing, 2020, pp. 231–233. doi: 10.1007/978-3-030-45257-5_18.

[46] T. Pereira, M. Abbasi, R. I. Oliveira, R. A. Guedes, J. A. R. Salvador, and J. P. Arrais,

"Deep   generative   model   for   therapeutic   targets   using   transcriptomic

disease-associated data—USP7 case study," *Brief Bioinform*, vol. 23, no. 4, Jul.

2022, doi: 10.1093/bib/bbac270.

Caption

Figure 1: Flowchart of GexMolGen

The generation of hit-like molecules by GexMolGen mainly consists of four steps

(refer to the Model Schematic section): 1. Encoding of genes and small molecule data,

2. Matching between gene modalities and small molecule modalities, 3.

Transformation from gene modality to small molecule modality, 4. Decoding of small

molecule modality. For simplicity, both the encoder and decoder for steps 1 and 4

utilize pre-trained models, namely scGPT[13] (orange section) and hierVAE[18] (blue

section) respectively. Due to frequent collapse of the gene encoder during the model

matching stage in step 2, our auxiliary learning primarily focuses on the gene encoder

(upper orange section), while the small molecule encoder mainly provides guiding

labels through hierarchical clustering (blue arrows). In step 3 (lower green section),

we first discretize the small molecules and then reconstruct them in an autoregressive

manner.

Figure 2: Example of generating hit-like small molecules from compound-induced

gene expression

This figure showcases examples of hit-like molecules generated by GexMolGen from

compound-induced gene expression profiles, compared to reference small molecules.

The similarity calculation metric is based on the Tanimoto similarity of Morgan

fingerprints.

Figure 3: Benchmarking GexMolGen in generating hit-like molecules with

similarity-based search and random generation.

(a), (b), and (c) represent the distributions of similarity calculated using MACCS

fingerprints, Morgan fingerprints, and Fraggle, respectively. These calculations are

done between small molecules generated by GexMolGen, those found by cosine

similarity and Euclidean distance search, randomly generated small molecules, and

reference small molecules. Each method is represented by a different color.

Figure 4: Example of generating hit-like molecules from knock-out gene expression profiles

This figure presents examples of hit-like small molecules generated by GexMolGen from knock-out gene expression profiles, compared to known inhibitors. The similarity calculation metric is based on the Tanimoto similarity of Morgan fingerprints. For fair comparison, we selected the same ten experimental genes as WGAN[8], and the results of WGAN can be found in **Supplementary Figure 1**.

Figure 5: Benchmarking GexMolGen in generating potential gene inhibitors with similarity-based search and random generation.

The x-axis represents three similarity calculation metrics: Tanimoto based on MACCS fingerprints, Tanimoto based on Morgan fingerprints, and Fraggle. The y-axis represents ten genes. Different colors represent different methods.

Supplementary Figure 1: Example of generating hit-like molecules from knock-out gene expression profiles by WGAN

We used OCR technology to extract the SMILES of molecules from Figure 2 in the WGAN[8] paper and calculated the similarity results based on the Tanimoto similarity of Morgan fingerprints. For detailed results, please refer to **Supplementary Table 4**.

Table 1: Comparison of GexMolGen and other modern methods in generating potential inhibitors from knock-out transcriptomes.

The first column presents the method names and references, the second column indicates the dataset types used, and the third column specifies the Tanimoto similarity range.

Method	Input Data Type	Tanimoto Similarity
GexMolGen	L1000 dataset	**0.74 to 1.00**
WGAN[8]	L1000 dataset	0.15 to 0.70
Bidirectional Adversarial AE[43]	L1000 dataset	0.3 to 0.48
TRIOMPHE[44]	L1000 dataset	0.29 to 0.68
PaccMann[45]	GDSC/CCLE	0.27 to 0.45
Deep Generative with RL[46]	TCGA project	0.47 to 0.83

Appendix Table 1: Experimental results of four methods for generating hit-like

molecules from compound-induced gene expression using Tanomoto similarity

metric based on Morgan fingerprints.

Appendix Table 2: Experimental results of four methods for generating hit-like

molecules from compound-induced gene expression using Tanomoto similarity

metric based on MACCS fingerprints.

Appendix Table 3: Experimental results of four methods for generating hit-like

molecules from compound-induced gene expression using Fraggle similarity

metric.

Appendix Table 4: SMILES of generated molecules from the WGAN[8] in the

OCR-recognized article, along with the SMILES of known inhibitors, and the

Tanimoto similarity calculated based on Morgan fingerprints between them.

Algorithm 1: Hierarchical clustering

Input: Small molecule embedding vectors $Z_M = \{z_{m1}, z_{m2}, \ldots, z_{mN}\}$

Distance function $dist(c_1, c_2)$

Output: Categories C of small molecule embedding vectors after hierarchical clustering at each level.

: **For** $i = 1:n$

: $\quad\quad c_i = \{Z_{mi}\}$

: **end for**

: $C = \{c_1, c_2, \ldots, c_n\}$

: $I = n + 1$

: **while** $C.size > 10$ **do**

: $\quad\quad (c_{min1}, c_{min2}) = min\ dist(c_i, c_j)\ for\ all\ c_i, c_j \in C$

: $\quad\quad C = C/\{c_{min1}, c_{min2}\}$

: $\quad\quad C = C \cup \{(c_{min1}, c_{min2})\}$

: $\quad\quad I = n + 1$

: **end while**

: **return** C

Figure2

(1) Reference Generate
BRD-K99026889 Similarity:0.81

(2) Reference Generate
BRD-K54834493 Similarity:0.81

(3) Reference Generate
BRD-K50404714 Similarity:0.77

(4) Reference Generate
BRD-K36888933 Similarity:0.74

(5) Reference Generate
BRD-K76559855 Similarity:0.74

(6) Reference Generate
BRD-K37487131 Similarity:0.71

(7) Reference Generate
BRD-K25354424 Similarity:0.71

(8) Reference Generate
BRD-K22721982 Similarity:0.7

(9) Reference Generate
BRD-K73388776 Similarity:0.7

(10) Reference Generate
BRD-K83644384 Similarity:0.7

Figure3

Figure4

Figure6