Branch Length Transforms using Optimal Tree Metric Matching

Shayesteh Arasti,[1][†] Puoya Tabaghi,[2][†] Yasamin Tabatabaee[3] and Siavash Mirarab[4][*]

[1]*Department of Computer Science and Engineering, UC San Diego, CA 92093, USA*
[2]*Halıcıoğlu Data Science Institute, UC San Diego, CA 92093, USA*
[3]*Department of Computer Science, University of Illinois at Urbana-Champaign, Urbana, IL 61801, USA*
[4]*Department of Electrical and Computer Engineering, UC San Diego, CA 92093, USA*
[*]Corresponding author: smirarab@ucsd.edu

Abstract

The abundant discordance between evolutionary relationships across the genome has rekindled interest in ways of comparing and averaging trees on a shared leaf set. However, most attempts at reconciling trees have focused on tree topology, producing metrics for comparing topologies and methods for computing median tree topologies. Using branch lengths, however, has been more elusive, due to several challenges. Species tree branch lengths can be measured in many units, often different from gene trees. Moreover, rates of evolution change across the genome, the species tree, and specific branches of gene trees. These factors compound the stochasticity of coalescence times. Thus, branch lengths are highly heterogeneous across both the genome and the tree. For many downstream applications in phylogenomic analyses, branch lengths are as important as the topology, and yet, existing tools to compare and combine weighted trees are limited. In this paper, we make progress on the question of mapping one tree to another, incorporating both topology and branch length. We define a series of computational problems to formalize finding the best transformation of one tree to another while maintaining its topology and other constraints. We show that all these problems can be solved in quadratic time and memory using a linear algebraic formulation coupled with dynamic programming preprocessing. Our formulations lead to convex optimization problems, with efficient and theoretically optimal solutions. While many applications can be imagined for this framework, we apply it to measure species tree branch lengths in the unit of the expected number of substitutions per site while allowing divergence from ultrametricity across the tree. In these applications, our method matches or surpasses other methods designed directly for solving those problems. Thus, our approach provides a versatile toolkit that finds applications in similar evolutionary questions.

Keywords

Phylogenomics, Convex Optimization, Species Tree Branch Length, Phylogenetic Branch Length Estimation, Tree Comparison

Code availability

The software is available at https://github.com/shayesteh99/TCMM.git.

Data availability

Data are available on Github https://github.com/shayesteh99/TCMM-Data.git.

[†]These authors contributed equally to this work.

1　Introduction

Discordance among evolutionary histories across the genome (Maddison, 1997) is now understood to be pervasive and has motivated the study of region-specific histories (often called gene trees) and the speciation history (the species tree). This availability of alternative trees leads to mathematical questions seeking to compare and combine trees. We need metrics to quantify tree dissimilarity, algorithms for mapping gene trees to the species tree to reconcile them (Doyon et al., 2011), and median tree methods to combine gene trees into a single species tree (Barthélemy and McMorris, 1986). Solutions to these problems have been developed and are widely adopted. Measures of tree difference such as Robinson and Foulds (1981) (RF), quartet distance (Estabrook et al., 1985), and matching split (MS) (Bogdanowicz and Giaro, 2012) are commonly used to quantify gene tree differences. Biologists often use reconciliation methods in comparative genomics to understand the evolution of gene function. Finally, inferring the species tree by finding the tree with the minimum total quartet distance to gene trees (quartet median tree) has been widely adopted due to its statistical consistency under several models of gene tree discordance (Mirarab et al., 2021).

The rich literature on comparing and combining trees, however, has mostly focused on tree topology. A typical phylogenomic pipeline infers a large number of gene trees with branch lengths in the unit of the expected number of substitutions per site (SU) but ignores those branch lengths altogether in downstream tasks such as species tree inference, reconciliation, and discordance quantification. And discordance is not just limited to topology. One of the main causes of discordance is incomplete lineage sorting (ILS) as modeled by the multi-species coalescent (MSC) model (Degnan and Rosenberg, 2009). Under MSC, internal nodes of a gene tree correspond to coalescence events that *have to* predate species divergences. As a result, gene tree branch lengths are guaranteed to differ from the species tree (when both are in the unit of time) even if there is no topological discordance. In the terminology of Edwards and Beerli (2000), there is a distinction between species divergence times and the genic divergences, which predate them. Gene duplication times similarly do not match each other or the speciation times. Beyond true biological differences, challenges in inferring gene trees compound the problem. From sequences alone, we can only measure SU lengths, which are a function of not just divergence times but also mutation rates. Assuming a fixed rate (strict clock model, Zuckerkandl and Pauling, 1962) is often insufficient as accumulated evidence shows that rates can change across the tree, across the genome, or both (Kumar, 2005; Lopez et al., 2002; Rasmussen and Kellis, 2007). Furthermore, gene trees are often inferred from short sequences (to avoid recombination within a gene), which makes branch length estimates very noisy, especially for shortest branches with no substitutions.

Methods for using branch lengths in phylogenomics exist but are not widely used. Some of the first statistically consistent species tree inference methods (e.g., GLASS and STEM; Kubatko et al., 2009; Mossel and Roch, 2010) used gene tree branch lengths alone. However, these methods have proved far less accurate than topology-focused methods (DeGiorgio and Degnan, 2014; Yang and Warnow, 2011). Bayesian co-estimation methods (e.g., Boussau et al., 2013; Heled and Drummond, 2010; Liu, 2008) also consider branch length by jointly modeling gene trees and species trees with branch lengths and parameters for mutation rate, population size, and (potentially) rate heterogeneity. These methods have been highly accurate (Yang and Warnow, 2011) and readily produce a reconciliation of species trees and gene trees (since all lengths are in the same unit). However, they do not scale to large datasets (Ogilvie et al., 2017; Zimmermann et al., 2014). Also, since complex rate models further reduce scalability, these methods often model only limited rate heterogeneity. Scalable and accurate methods such as ASTRAL (Mirarab et al., 2014) and NJst/ASTRID (Liu and Yu, 2011; Vachaspati and Warnow, 2015) use gene tree topologies as input and produce only species tree topology. We can use *post hoc* calculations to infer coalescent units (CU) branch lengths for internal branches of the species tree using gene tree topologies alone, but this approach can lead to systematic under-estimation (Forthman et al., 2022; Sayyari and Mirarab, 2016).

There have been attempts to reconcile gene tree branch lengths with an inferred species tree. Since gene trees have SU branch lengths and many downstream analyses need lengths in such a unit, one can seek to transfer the SU branch lengths from gene trees onto the species tree with some form of summarization. One proposed approach, called ERaBLE, uses a least-squared optimization applied to patristic distances (pairwise path lengths) of the gene trees to estimate species tree lengths, effectively taking a weighted average. ERaBLE allows for a limited form of rate heterogeneity across loci. However, Tabatabaee et al. (2023) have shown that ERaBLE tends to overestimate terminal branches because it ignores deep coalescence. They propose an alternative coalescent-based method called CASTLES that specifically corrects for the difference between the

species and genic divergence times. While CASTLES is more accurate than ERaBLE in MSC simulations (Tabatabaee et al., 2023), ERaBLE has the advantage of having a simple objective function that does not depend on any model of gene tree discordance. This observation leads us to ask: Can other more flexible model-free methods transfer branch lengths across trees while attaining higher accuracy?

In this paper, we use a linear algebraic formulation to address the problem of matching branch lengths across two trees. Similar to ERaBLE, we form an optimization problem based on patristic distances. However, unlike ERaBLE, which estimates only one scalar parameter per gene tree, we assign one parameter per each branch of each gene tree. The optimization problem we define, called Topology-Constrained Metric Matching (TCMM), assigns branch lengths to a query tree such that its patristic distances match a reference tree as much as possible without changing the topology. We show that an extra regularization term enables the user to balance the competing goals of matching the reference tree and keeping the original branch length patterns of the query tree. We also show that TCMM extends to multiple reference trees naturally. The introduced TCMM problems are all convex and can be solved efficiently with standard techniques. Moreover, the input to the optimization problems can be computed efficiently using dynamic programming preprocessing with quadratic running time and memory. While the ability to match the metric space of one tree to another (the core of TCMM) provides a versatile tool, in this paper, we focus on a particular application: reconciling gene tree branch lengths (used as reference) against the species tree (used as the query). We show that TCMM can be paired with outlier detection to design a method that is as accurate as CASTLES in estimating species tree branch lengths, despite being agnostic to MSC. Moreover, the regularization technique allows us to pair TCMM with CASTLES to obtain a method that tends to be more accurate than either alone. We end by speculating about some of the future applications of TCMM.

2   Methods

For an unrooted tree $T = (V_T, E_T)$, we let L_T denote the leaf set and $P_T(v, v')$ denote the path between any pairs of vertices $v, v' \in V_T$. Assigning the natural orientation to the edges of a rooted tree away from the root, the structure becomes a directed rooted tree. For a weighted tree, each edge $e \in E_T$ has length $w_T(e) \in \mathbb{R}^+$. We use $\mathcal{T}(T)$ to denote the set of all weighted trees with the same topology as tree T. A weighted tree T with N vertices indexed by $[N] = \{1, \ldots, N\}$ defines a metric $d_T : V_T \times V_T \to \mathbb{R}^+$ where $\forall v, v' \in V_T : d_T(v, v') = \sum_{e \in P_T(v, v')} w(e)$. With slight abuse of notation, we define the *weight* vector w_T and the *pairwise distance* vector d_T as:

$$w_T = (w_T(e))_{e \in E_T} \in \mathbb{R}^{|E_T|} \quad \text{and} \quad d_T = (d_T(v, v'))_{v, v' \in L_T, v < v'} \in \mathbb{R}^{\binom{|L_T|}{2}} .$$

Definition 1 (Path matrix A_T). *Given a tree T, we define a binary matrix A_T of size $\binom{|L_T|}{2} \times |E_T|$ where rows correspond to pairs of vertices in L_T, columns represent the edge set. For two distinct vertices $v, v' \in L_T$ and edge $e \in E_T$, an element $((v, v'), e)$ of A_T is one if and only if that the edge e is on the path between v and $v' \in L_T$. Otherwise, it is equal to zero.*

2.1   Problem Statements

We start with a general tree matching problem, which we then successively refine.

Problem 1 (General Topology-Constrained Metric Matching). *Given is a query tree T and a reference weighted tree R, both on a shared leafset L. For any tree T' with the same topology as T, let $\mathrm{cost}(T'; R)$ measure the branch length discrepancy of T' to the reference tree R. Then, we seek $T^* \in \arg\min_{T' \in \mathcal{T}(T)} \mathrm{cost}(T'; R)$.*

The path matrix A_T completely encodes the topology of T; we can completely identify a weighted tree $T = (V_T, E_T)$ using its topology (i.e., the matrix A_T) and its weight function w_T. Thus, we can parameterize the cost in Problem 1 with respect to the weight vector w_T — since the topology is fixed. We reparameterize the objective as $\mathrm{cost}(w'; R)$ and reformulate Problem 1 as follows:

$$w^* \in \arg\min_{w'} \mathrm{cost}(w'; R),$$

where $w' \in \mathbb{R}^{+\binom{|V_T|}{2}}$ are constrained to be nonnegative. The closest tree to reference tree R has the same topology as T and edge weights w^*; i.e., $T^* = (V_T, E_T)$ and $w_{T^*} = w^*$.

One strategy in designing an appropriate cost function is to quantify the discrepancy of metric information between the two trees. To do so, we first find a separable form for pairwise distances in terms of two quantities: (1) topology, and (2) edge weights. For any distinct $v, v' \in L$, we have

$$d_T(v, v') = \sum_{e \in P_T(v,v')} w_T(e) = \langle a_{v,v'}, w_T \rangle$$

where $a_{v,v'} = \left(1_{e \in P_T(v,v')}\right)_{e \in E_T} \in \{0,1\}^{|E_T|}$ and 1_x is the indicator function. By definition, the vector $a_{v,v'}$ is the row of the path matrix A_T, corresponding to vertex pair (v, v'). Thus, for any tree $T = (V_T, E_T)$, we have $d_T = A_T w_T$. This enables us to arrive at a separable form for pairwise distances in terms of A_T, representing topology, and the weight vector w_T. We next provide a specific form of Problem 1 with the goal of transforming the weights of a tree so that its metric information best matches to a reference tree.

Problem 2 (Topology-Constrained Metric Matching— under ℓ_2^2)**.** *Let T, R be weighted trees with edge weight functions w_T and w_R on the common leafset L with at least two elements. We define the following cost to measure the discrepancy of patristic distances of T to the reference tree R:*

$$\text{cost}(w_T; R) = \sum_{v,v' \in L} |d_R(v, v') - d_T(v, v')|^2 = \|d_R - A_T w_T\|_2^2$$

The weights of the closest tree to R matching T in topology with edge weights lower bounded by $\varepsilon \geq 0$ is:

$$w^* \in \underset{w \in \mathbb{R}^{|E_T|}, w \geq \varepsilon}{\arg\min} \|d_R - A_T w\|_2^2.$$

Clearly, if both R and T have the same topology, then w_R is an optimal solution (i.e., $T^* = R$). More broadly, the cost function in Problem 2 is agnostic to the weights w_T, and thus, it can dramatically change the branch lengths of T. In particular, branches that do not match between T and R tend to become very short (as we will see in experiments). For some applications, it may be desirable to retain the original branch lengths to some extent, while making the tree similar to the other. We can accommodate that goal by adding a regularizing term. For an optimal edge weight vector w_{T^*}, we define the *adjustment rate vector* by elementwise dividing w_{T^*} and w_T, to get w_{T^*}/w_T. These adjustment rates do change with the initial weights w_T. To incorporate the information of w_T in the problem statement, we penalize the deviation of estimated w_{T^*} from the initial weight vector w_T, save for a total scaling factor shared by all branches. This is summarized in the following problem.

Problem 3 (Regularized Topology-Constrained Metric Matching — under ℓ_2^2)**.** *Let T, R be weighted trees with edge weight functions w_T and w_R on the common leafset L. We define the following regularized cost to measure the discrepancy of $T' \in \mathcal{T}(T)$ with weights w to the reference tree R:*

$$\text{cost}(w; R) = \|d_R - A_T w\|_2^2 + \lambda \sigma^2(w/w_T), \tag{1}$$

where λ is the regularization coefficient, $\sigma^2(w/w_R)$ computes the variance of the adjustment rates vector w/w_R. We seek the tree $T^* \in \mathcal{T}(T)$ with edge weights

$$w_{T^*} \in \underset{w \in \mathbb{R}^{|E_T|}, w \geq \varepsilon}{\arg\min} \text{cost}(w; R).$$

The regularizing term, which is a quadratic function of the weight vector w, leads to lowered variance in the adjustment rate vector, w/w_T, and thus, lowered change in *relative* branch lengths compared to T. Clearly, if the variance of adjustment rate values is 0, the tree T has been simply scaled up or down, without any real change to its relative branch lengths. Higher λ values encourage less change to the relative branch lengths of T. As $\lambda \to \infty$, the optimal solution will simply scale branch lengths of T with a fixed global rate $r*$. That is, $w_{T^*} \parallel w_T$ where $\parallel$ denotes parallel vectors. More precisely, as $\lambda \to \infty$, all rate multipliers converge to

$$r^* \in \underset{r \cdot \min_e w_T(e) \geq \varepsilon}{\arg\min} \|d_R - r A_T w_T\|_2^2 .$$

The use of variance of rate multipliers in the regularization term has a notable side effect. It penalizes scaling of the weights and thus prefers smaller values for w_{T^*}. Note that for any r, we have $\sigma^2((rw)/w_T) = r^2\sigma^2(w/w_T)$. Thus, compared to no regularization, regularization is expected to produce shorter branch lengths.

Note that, as stated, Problem 3 does not provide an intuitive interpretation for the regularization coefficient λ. While each edge $e \in E_T$ appears in the regularization term exactly once, the same is not true for the first term in Eq. (1). The number of times an edge $e \in E_T$ appears in this first term is equal to the number of leaf pairs $v, v' \in L_T$ where $e \in P_T(v, v')$. This quantity grows quadratically with $|E|$, and in addition, depends on the tree topology. As a result, the relative weight of the two terms in Eq. (1) varies across trees. However, the number of times e contributes to the cost is already computed in $(A_T^\top A_T)_{e,e}$. Therefore, we can mitigate the impact of T by scaling the first term of Eq. (1) by the trace of $A_T^\top A_T$ and the second term by $|E|$. Thus, Problem 3 can be reformulated as

$$\text{cost}(w; R) = \frac{\|d_R - A_T w\|_2^2}{\text{Tr}\{A_T^\top A\}} + \lambda \frac{\sigma^2(w/w_T)}{|E|},$$

where both terms are scale-free. We will adopt this revised formulation of the Regularized TCMM Problem in all subsequent experiments.

Problem 4 (Topology-Constrained Consensus Metric Matching). *Let $\{R_k = (V_{T_k}, E_{T_k}) : k \in [K]\}$ be a set of weighted reference trees such that T_k has weight function w_k, for all $k \in [K]$. Given a tree $R = (V_R, E_R)$ and the set of leaves common to all trees denoted by L, we seek to find the optimal (adjusted) tree $T^* = (V_T, E_T)$ with the same topology as tree T such that its weights minimizes the following (regularized) consensus cost:*

$$w_{T^*} \in \underset{\substack{w \in \mathbb{R}^{|E_R|} \\ w \geq \varepsilon}}{\arg\min} \sum_{k \in [K]} \alpha_k^2 \|d_{R_k} - A_T w\|_2^2 + \lambda \sigma^2(w/w_T),$$

where α_k is a nonnegative weight controlling the contribution of reference tree R_k in the cost function, $\lambda > 0$ is a regularizing coefficient, $\sigma^2(w/w_T)$ penalizes the weights that result in a large variance for the adjustment rate vector w/w_R, and $\varepsilon \geq 0$ is a lower bound for the estimated edge weights.

2.2 Solving TCMM Efficiently as Convex Optimization

2.2.1 TCMM problems are all convex

We can rewrite the cost functions in Problems 2–4 in quadratic forms. For ease of notation, we use $d = d_R$ and $A = A_T$ in Problems 2,3 and $d = d_{R_k}$, $A = A_T$ in Problem 4. Note that Problem 2 minimizes $l_1(w) \overset{\text{def.}}{=} \|d - Aw\|_2^2$. We convert l_1 to the following quadratic form

$$l_1(w) = \frac{1}{2} w^\top B w + c^\top w + \text{const}, \tag{2}$$

where $B = 2A^\top A$ is a positive semidefinite matrix, $c = -2A^\top d$, and const $= \|d\|_2^2$. Since $B \succeq 0$ by construction, l_1 is a convex function of the weight parameter w. Adding the regularization term $\sigma^2(r)$ — where $r = w/w_T$ — does not change the convexity as we can convert it to the following quadratic form:

$$l_2(w) \overset{\text{def.}}{=} \sigma^2(r) = \frac{1}{|E|}(r - 1\bar{r})^\top(r - 1\bar{r}) = \frac{1}{|E|} r^\top (P_1^\perp)^\top P_1^\perp r = \frac{1}{|E|} r^\top P_1^\perp r$$

where $1 \in \mathbb{R}^{|E|}$ is the vector of all ones, $\bar{r}$ is a scalar that is the average value of elements in r, $P_1^\perp = I - \frac{1}{|E|} 11^\top$. It is a known fact that $P_1^\perp$ is an orthogonal projection operator, $(P_1^\perp)^\top P_1^\perp = P_1^\perp$. Furthermore, it is a positive semidefinite matrix with $0 - 1$ eigenvalues. Therefore, the regularizing term $\sigma^2(w/w_T)$ is indeed a convex function of the weight parameter w. Thus, Problems 2,3, and 4 all admit globally optimal solutions.

Proposition 1. *The cost functions in Problems 2, 3, and 4 admit unique minimums but not necessarily unique minimizers. We can arrive at an optimal solution using a projected gradient descent method.*

Proof. The gradient of the cost function in Eq. (2) with respect to the weights $w \in \mathbb{R}^{|E|}$ is:

$$\nabla_w l_1(w) = Bw + c,$$

where $B \in \mathbb{R}^{|E| \times |E|}$ and $c \in \mathbb{R}^{|E|}$. The Hessian $\nabla_w^2 l_1(w) = B$ is a positive semidefinite matrix; thus, $l_1(w)$ is a convex function everywhere in its domain. We can also compute the gradient of $l_2(w)$ as follows:

$$\nabla_w l_2(w) = \frac{2}{|E|}(P_1^\perp r)(1/w_T) = \frac{2}{|E|}P_1^\perp(w/w_T^2).$$

Furthermore, its Hessian $\nabla_w^2 l_2(w) = \frac{2}{|E|}\text{diag}(1/w_T)P_1^\perp\text{diag}(1/w_T)$ is a positive semidefinite matrix, making $l_2(w)$ a convex function of w as well. Since both $l_1(w)$ and $l_2(w)$ are convex functions of weight parameter w and cost functions in Problems 2, 3, and 4 are linear functions of l_1 and l_2 with *positive coefficients* (λ and α_k^2 terms), each cost function is also a convex function of w. In Problem 2, the constraint set is $w \geq 0$ which is nonempty, closed, and convex. In Problems 3 and 4, the constraint set is $w \geq \varepsilon$ which is also nonempty, closed, and convex. Therefore, all three problems involve convex function minimizations over nonempty, closed, and convex sets. Since convex functions over nonempty, bounded, convex sets have a minimum, the projected gradient descent method converges to the global minimum of the cost functions (Wang and Xiu, 2000). $\square$

By Proposition 1, we can use the simple projected gradient descent to solve Problems 2 – 4 using the gradient terms shown above. We implemented and optimized the quadratic functions l_1 and l_2 using built-in functions in the Python package `CVXPY`. The only remaining challenge is scalability, which we next address.

2.2.2   Dynamic programming enables calculating B and c in quadratic time

Luckily, our formulation does not need to ever compute A_T and d_R — whose dimensions grow cubically with N. Rather, it needs the matrix B, which grows quadratically, and vector c, which grows linearly with N. Naively computing $A_T^\top A_T$ from its building blocks requires $O(N^4)$ time and $O(N^3)$ memory. Similarly, computing $A_T^\top d_R$ naively requires $O(N^3)$ time and $O(N^3)$ memory. However, we can compute B and c directly in quadratic time and memory using dynamic programming without ever computing A_T and d_R.

Computing $A_T^\top d_R \in \mathbb{R}^{|E_T|}$. We use a coloring scheme for the nodes of the trees T and R. Each edge $e \in E_T$ corresponds to a bipartition of taxa, dividing the leaves of T into two sets. For an arbitrary rooting of T, we define $C_T(e)$ as the set of leaves of T below e and $C_T'(e)$ as $L_T \setminus C_T(e)$. By Definition 1, the column of A_T corresponding to $e \in E_T$ has a 1 only for rows (v, v') where e is on the path $P_T(v, v')$. Therefore, The element of $c = A_T^\top d_R$ that corresponds to $e \in E_T$ is

$$c_e = \sum_{v,v' \in L_T, v < v'} d_R(v, v') 1_{e \in P_T(v,v')} = \sum_{v \in C_T(e)} \sum_{v' \in C_T'(e)} d_R(v, v') \tag{3}$$

where the second equality follows from the fact that each path in the first equation is counted only if it includes e. We color each leaf $v \in L_R$ in the reference tree R as blue if $v \in C_T(e)$ and red if $v \in C_T'(e)$ (See Figure 1). Both the query tree T and the reference tree R are induced down already to the common leaf-set L. Using this coloring scheme and a single bottom-up traversal of the reference tree (Algorithm 1), c_e can be computed in linear time for each edge $e \in E_T$ and thus quadratic time and memory for all edges.

Computing $B = A_T^\top A_T$. Given the Definition 1 of the path matrix A_T, it can be easily deduced that for two edges e and e', $B_{e,e'}$ is the number of pairs of leaves $v, v' \in L$ where $e, e' \in P_T(v, v')$. We easily pre-compute $|C_T(e)|$ and $|C_T'(e)|$ for each edge $e \in E_T$ in linear time and the least common ancestor (LCA) of all pairs of nodes of T in quadratic time. With these, we can easily compute $B_{e,e'}$ for all $e, e' \in E_T$ in quadratic time using simple calculations given in Algorithm 1.

2.3   TCMM for Reconciling Species Tree and Gene Tree Branch Lengths

Phylogenomic analyses often produce a species tree topology S and a set of gene trees with estimated SU branch lengths $\mathcal{G} = \{G_1, \ldots, G_K\}$. To be useful for downstream analyses (e.g., dating), the species tree needs SU branch lengths, which methods such as ASTRAL do not produce. TCMM can be used to draw SU branch lengths on the species tree, reconciling those of gene trees. We propose two primary approaches to do so, both of which counterintuitively use gene trees as the reference and the species tree as the query.

Algorithm 1 Computing $A_T^\top A_T$ and $A_T^\top d_R$

1: **procedure** COMPUTE_$A^\top A$(Tree T)
2: pre-compute $|C_T|$ and $|C'_T|$ for each edge of T in a bottom-up traversal
3: **for** e in E_T **do**
4:   **for** e' in E_T **do**
5:    **if** $e == e'$ **then**
6:     $A^\top A[e, e'] \leftarrow |C_T(e)| \cdot |C'_T(e)|$
7:    **else**
8:     **if** e is a descendant of e' **then**
9:      $A^\top A[e, e'] \leftarrow |C_T(e)| \cdot |C'_T(e')|$
10:     **else if** e' is a descendant of e **then**
11:      $A^\top A[e, e'] \leftarrow |C_T(e')| \cdot |C'_T(e)|$
12:     **else**
13:      $A^\top A[e, e'] \leftarrow |C_T(e)| \cdot |C_T(e')|$
14: **return** $A^\top A$
15: **procedure** COMPUTE_$A^\top d$(Tree T, Tree R)
16: **for** $e \in E_T$ **do**
17:   **for** $n \in$ bottom-up traversal of V_R **do**
18:    $e' \leftarrow$ the edge above n
19:    **if** n is leaf **then**
20:     $C_b(n), C_r(n) = 1_{n \in C_T(e)}, 1_{n \notin C_T(e)}$ ▷ Number of blue and red leaves below n
21:     $L_b(n), L_r(n) = w_{e'} \cdot C_b(n), w_{e'} \cdot C_r(n)$ ▷ Sum of the distances of blue and red leaves up to the parent of n
22:    **else**
23:     $c_l, c_r \leftarrow$ chidlren of n
24:     $A^\top d[e] = C_b(c_l) \cdot L_r(c_r) + C_r(c_l) \cdot L_b(c_r) + C_b(c_r) \cdot L_r(c_l) + C_r(c_r) \cdot L_b(c_l)$
25:     $C_b(n), C_r(n) = C_b(c_l) + C_b(c_r), C_r(c_l) + C_r(c_r)$
26:     $L_b(n), L_r(n) = L_b(c_l) + L_b(c_r) + w_{e'} \cdot C_b(n), L_r(c_l) + L_r(c_r) + w_{e'} \cdot C_r(n)$
27: **return** $A^\top d$

Our first approach runs TCMM per-gene and summarizes results at the end. We use Problem 2 to match the species tree (as query T) to each gene tree (as reference R). When S is already furnished with some branch lengths (e.g., results of running other methods), we can instead use Problem 3. The solution provides us with a set of estimated branch lengths $\tilde{w}_{e,k}$ where $e \in E_S$ and $G_k \in \mathcal{G}$. These lengths can be further summarized into a single value $\hat{w}_e$ for each branch using common averaging methods — arithmetic mean, harmonic mean, and geometric mean. By default, we will use geometric mean, which works best empirically (as shown in Section 3) and has a theoretical justification. Assume estimated $\tilde{w}_{e,k}$ values are noisy estimates of the correct length with multiplicative (as opposed to additive) noise. Thus, they follow a log-normal distribution, with the median equal to the true length. This model has worked well for dating (Mai and Mirarab, 2020) and is more reasonable than the standard additive error (i.e., a normal distribution) given that estimated branch lengths can never be negative. Under the log-normal model, the geometric mean is the appropriate estimator of the median parameter.

Using the per-gene approach has the added benefit of enabling outlier removal. TCMM tends to assign exceedingly small values to *some* branches that are in the query but not the reference tree (as we will see), creating outliers. To detect these near-zero outliers, assume that $\tilde{w}_{e,k}$ values follow an exponential distribution with a median equal to that of the observed data (using median reduces the impact of outliers). Exponential distribution is a natural choice for outlier detection because 1) its domain is positive, 2) it requires only specifying one parameter (in contrast to log-normal which needs two parameters, making parameter setting more sensitive to outliers), and 3) is leptokurtic, making outlier detection conservative. We calculate the empirical cumulative distribution function (ECDF) of the $\tilde{w}_{e,k}$ values and for each point measure the difference between ECDF and CDF of the exponential with the same median. We then identify the point p with the largest positive difference between the observed ECDF and the model CDF where $\text{ECDF}(p) < 0.5$. We eliminate all data points smaller p and compute the geometric mean of the remaining points.

The second approach, called consensus, uses Problem 4 specifically tailored to match a single query tree to multiple reference trees. The solution to Problem 4 simply requires computing weighted means of patristic distances across input gene trees used as input to the same optimization problem. Note that once again, instead of means, we can use geometric mean. The weights $\{\alpha_k : k \in [K]\}$ for the gene trees can be carefully selected to avoid overemphasizing the gene trees with overall longer branches. Here, we set the gene tree

Figure 1: (a) Tree T with $C_T(e)$ and $C'_T(e)$ highlighted in blue and red for an edge e. (b) Tree R; Recall $c_e = \sum_{v \in C_T(e)} \sum_{v' \in C'_T(e)} d_R(v, v')$. An Example path $P_T(v, v')$ corresponding to $d_R(v, v')$ is shown in blue. (c, d) For edges e, e', $B_T(e, e')$ is the number of pairs of leaves v, v' where $e, e' \in P_T(v, v')$. c) If e is a descendant of e', $B_T(e, e') = C_T(e)C'_T(e')$. d) Otherwise, $B_T(e, e') = C_T(e)C_T(e')$. (e) Assumed data generation model (blue) and branch length estimation (yellow) processes. The second panel shows the default TCMM pipeline where the input is a set of gene trees as well as the species tree topology and the output is the species tree with SU branches.

weights to the inverse of the sum of pairwise distances:

$$\forall k \in [K] : \alpha_k^{-1} = \sum_{v, v' \in L_{G_k}} d_{G_k}(v, v'). \tag{4}$$

Finally, regardless of which approach is used, we can pair TCMM with other branch length estimation tools. To do so, the species tree obtained from such tools, along with their estimated branch lengths, should be fed into the regularized version of TCMM. This approach will preserve existing branch lengths to an extent controlled by λ. One remaining difficulty is selecting the parameter λ. Here, we use an automatic approach to select a λ among a predefined set of options. We do so by picking the λ that minimizes the sum of the estimated species tree branch lengths. This choice is rooted in the minimum-evolution principle (Rzhetsky and Nei, 1993) used by a family of distance-based approaches. Consequently, TCMM in its default mode operates without asking the user to specify a λ parameter.

2.4 Experimental design

We evaluated our proposed approach, TCMM, for reconciling species tree and gene tree branch lengths using both simulated and real datasets. On simulated data, the model species tree branches have true SU lengths (w) obtained by multiplying its length (number of generations) with varying mutation rates, creating non-ultrametric trees. We compared the true w values to estimated values $\hat{w}$ to quantify the mean absolute error ($|w - \hat{w}|$) and bias ($\hat{w} - w$), both averaged across all species tree branches.

We compare TCMM to four leading methods studied by Tabatabaee et al. (2023), all run on the true species tree topology. We include the coalescent-based method CASTLES, which accounts for coalescence times predating species divergence times. This method does allow rate variation across the species tree but assumes gene trees follow the same patterns of rate variation (i.e., no heterotachy). We also examine the

method most often used by biologists in practice: After inferring the species tree using ASTRAL, we use concatenation using RAxML (Stamatakis, 2006) to estimate branch lengths of the species tree. Unlike the other models tested in this paper, this approach does not account for gene tree differences. We also include two methods that like TCMM use patristic distances. A simple alternative is averaging patristic distance matrices across gene trees and using a distance-based method (FastME, Lefort et al., 2015) to draw branch lengths on S. A more advanced version of this idea is ERaBLE (Binet et al., 2016), which uses a proportional model. It estimates a single scalar rate per gene tree by matching them simultaneously to the species tree. In comparison, TCMM estimates one scalar per branch of the species tree (in the consensus mode) or per gene × species (in the per-gene mode). Thus TCMM has far more parameters than the ERaBLE approach. We use ERaBLE in its default mode.

In addition, we compare TCMM in the per-gene and consensus modes mentioned earlier. In the per-gene mode, we test it with and without outlier removal and with both arithmetic and geometric means. In the consensus mode, we compare arithmetic and geometric means as well as weighting input trees using Eq. (4). The default version is the per-gene with outlier detection and geometric mean summarization. Finally, the Regularized version of TCMM with automatic λ selection is paired with CASTLES, referring to the result as CASTLES+TCMM.

We study two simulated datasets and a biological dataset.

S100 dataset

We reused a published (Tabatabaee et al., 2023) 101-taxon (100 ingroup and one outgroup) 1000-gene simulated dataset with species trees that have both SU and CU length. Ultrametric species trees with generation times are simulated using a birth-death model; each branch length is multiplied by a rate multiplier drawn from a Gamma distribution with mean 1 (variance ranging between 0.0153 and 2.6027) and a mutation rate to get SU length and divided by a constant population size to get CU. The 50 replicates of this dataset are highly heterogeneous in terms of ILS, with the mean RF distance between the model species tree and the true gene trees (AD) at 46%. In addition to true gene trees, we have FastTree-2 (Price et al., 2010) estimated gene trees from 200bp, 400bp, 800bp, and 1600bp alignments, leading to average RF distance between true and estimated gene trees of 23%, 31%, 42% and 55%, respectively.

HGT dataset

We generated a new 51-taxon (50 ingroups + outgroup) simulated dataset with gene tree discordance due to both ILS and Horizontal Gene Transfer (HGT). We used the parameters of Davidson et al. (2015) but generated species trees with branch lengths in SU and CU units, using a modified version of the simulation software SimPhy (Mallo et al., 2016) created by Tabatabaee et al. (2023). This dataset has six model conditions that are characterized by different rates of HGT; the base ILS level is moderate (30% AD) and the same across all model conditions. The HGT rates for the six model conditions are 0, 2×10^{-9}, 5×10^{-9}, 2×10^{-8}, 2×10^{-7}, and 5×10^{-7} corresponding to the expected number of HGT events per gene of 0, 0.08, 0.2, 0.8, 8 and 20 respectively. Total discordance is a product of both ILS and HGT. The AD levels of the six conditions are 30%, 30%, 31%, 34%, 53%, and 68%, respectively, with the increase being completely due to HGT. This dataset has 50 replicates with 1000 gene trees in each of them. We use only true gene trees for this dataset.

Biological dataset

We analyzed a prokaryotic dataset studied by Moody et al. (2022) to address a debate about a long-standing hypothesis that the domains bacteria and archaea are separated by a long branch. The authors claimed that lower divergences obtained by some recent studies (Petitjean et al., 2015; Zhu et al., 2019) were the results of highly abundant HGT in microbial datasets (Arnold et al., 2022). Moody et al. (2022) suggest that those studies that had used concatenation to infer branch lengths on the species tree have likely underestimated the length of the branch separating domains archaea and bacteria (AB branch), potentially because of high levels of inter-domain gene transfer. Here, we reanalyzed two smaller datasets analyzed by Moody et al. (2022): A 72-taxon tree (Williams et al., 2020) with 49 core genes including ribosomal proteins and other conserved genes, and a 108-taxon dataset (Petitjean et al., 2015) with 38 genes that only includes non-ribosomal proteins. We compare the length of the AB branch inferred using TCMM, CASTLES and concatenation, all drawn on species topologies built using ASTRAL-III (Zhang et al., 2018) from the two gene sets.

Figure 2: (S100 Dataset) (a) Comparison of different versions of TCMM in terms of absolute error (top) and bias (bottom), showing mean (dot) and 0.95% normal CI (box). Summarization methods are arithmetic mean (*mean*) or geometric mean (*geo mean*). The weighted consensus method used Eq. (4). The regularization coefficient (λ) was set to zero, except for the CASTLES+per-gene method where λ is selected automatically. (b) The effect of the regularization coefficient (λ) on the estimated branch lengths. TCMM output length per gene (before summarization) over the input length (CASTLES) is shown; the variance of this ratio (spread of distribution) indicates the change in the relative length of branches between input and output of TCMM. Outliers are identified by our per-gene method.

3   Results

Versions of TCMM

   Overall, the most accurate version of TCMM is the per-gene mode, used with the geometric mean, and outlier removal (Fig. 2a). All choices of the default method contribute to accuracy and are needed. Outlier removal has minimal impact on terminal branch lengths, but substantially reduces error (42%) and bias (65%) for internal branches. When comparing the branch lengths from CASTLES to those from TCMM, we observe a long tail of branches that are made much smaller (median: 2.4×10^{-19}) by TCMM (Figs. 2 and S7b). These outliers (1.7% of the per-gene estimates) are among branches that do not match between the species tree and the gene trees. Consequently, the removal of these outliers predominantly impacts the accuracy of internal branches, as validated by our results. Using the geometric mean in the default version instead of the arithmetic mean leads to an error reduction of 5.7% in the per-gene method. As expected, the geometric mean results in shorter branch estimates. In particular, the arithmetic mean tends to introduce an overestimation bias, averaging 0.0075 SU, perhaps due to ignoring the impact of coalescence. In contrast, the geometric mean introduces an underestimation bias, averaging at -0.0053 SU.

   Compared to the default per-gene version, the consensus method using a weighted mean of gene tree patristic distances has a higher under-estimation bias and higher mean absolute error (Fig. 2a). Removing the weights has an opposite impact on terminal and internal branches: it increases terminal branch length error and bias slightly, but dramatically decreases the internal length error and bias. In fact, the unweighted consensus method has the lowest bias and highest accuracy for internal lengths among all the methods. Thus, while the default method has 28% less mean error than the consensus (unweighted mean), the latter should be considered a viable alternative when the internal branch lengths are the focus. Using geometric mean instead of the arithmetic mean does not lead to an overall reduction in error for the consensus method.

   Incorporating the estimated branch lengths derived from CASTLES into the per-gene (geometric mean) method, with a regularization coefficient $\lambda = 10^{-3}$ (Problem 3) yields a further 20% reduction in error for internal branches, while maintaining accuracy for terminal branches (Fig. 2a). Examining varying λ reveals that the exact choice has a limited impact on results (Fig. S6). As expected, as λ increases, branch lengths estimated by the default TCMM method become successively more similar to initial branch lengths (from CASTLES) provided as input in terms of their relative values (Fig. 2b). Interestingly, using the regularization also reduces the extent to which results of per-gene TCMM include outliers that need to be eliminated.

Figure 3: Comparing TCMM with the alternative methods on the S100 dataset in the presence of gene tree estimation error. TCMM is run with $\lambda = 0$ (TCMM) and automatic lambda selection (CASTLES+TCMM). We show both bias (mean of estimated − true) and mean error (|estimated − true|). Top: over all branches; bottom: separating internal and terminal branches.

ILS-only S100.

Considering all branches, TCMM comes close to CASTLES in terms of error (0.5–4.3% higher error), and TCMM +CASTLES has the best accuracy averaged over all conditions (Fig. 3). Concatenation is consistently the least accurate method. The simple methods based on patristic distance (ERaBLE and AVG+FastME) exhibit errors lower than concatenation but higher than CASTLES and TCMM. Note that while TCMM is also based on patristic distances, it has far less error compared to ERaBLE and AVG+FastME (%33 and %32, respectively). Errors of all methods, except TCMM+CASTLES and concatenation tend to increase as gene trees become less accurate. While bias largely follows similar patterns as error, the impact of gene tree error is more clear on bias. Increased gene tree error tends to make estimated lengths longer, which can make some methods (e.g., CASTLES and TCMM) go from under-estimation bias to over-estimation bias.

Patterns of error and bias are quite different between terminal and internal branches. ERaBLE has very high error and bias for terminal branches but among the lowest error and bias for internal ones. For TCMM, the error levels are similar across both types of branches; there is a slight under-estimation bias for internal and a slight over-estimation bias for terminal branch lengths. CASTLES is substantially more accurate for internal branches than terminal ones. Thus, compared to CASTLES, TCMM has 16–55% higher error for internal branches and 3–20% lower error for terminal ones. The bias on internal branches (and not terminal ones) of CASTLES is strongly dependent on gene tree error, changing from under-estimation bias to over-estimation bias (Fig. 3). TCMM+CASTLES is more similar to TCMM than to CASTLES: it loses some of

Figure 4: Comparing TCMM with the alternative methods on the HGT dataset with different rates of HGT (x-axis). TCMM is run with $\lambda = 0$ (TCMM) and automatic lambda selection (CASTLES+TCMM).

the advantages of CASTLES on the internal branches but has the advantages of TCMM in terms of accuracy on the terminal lengths.

HGT dataset

On this dataset, all methods have similar levels of error for lower HGT rates, but error increases at the highest two HGT rate levels (Fig. 4). The increase is much more dramatic for ERaBLE and AVG+FastME (and especially for their terminal branches) than for other methods. At the highest levels of HGT, CASTLES and TCMM have similar levels of overall error, though CASTLES is more accurate for terminal branches and TCMM for internal branches. In these conditions, CASTLES+TCMM has considerably lower error than CASTLES and TCMM overall; it matches CASTLES on terminal branches and improves on both methods in terms of internal branches.

Both patristic methods, ERaBLE and AVG+FastME, over-estimate branch lengths overall, with the bias concentrated on terminal branches (Fig. 4). In contrast, TCMM and CASTLES both have an underestimation bias. This underestimation tends to be slightly larger for internal branches and, in the case of CASTLES, the underestimation increases (by up to 74%) for the highest two levels of HGT. TCMM has an under-estimation bias similar to CASTLES for low HGT, but its bias does not increase (and in fact decreases) with higher HGT. Overall, for low levels of HGT, no method is clearly better than others while for high HGT levels, TCMM +CASTLES has the lowest bias and error.

Figure 5: The distribution of the TCMM estimated length for the branch separating bacteria and archaea per gene tree using the 49 core gene (a) and the 38 non-ribosomal genes (b). Vertical dashed lines show the geometric mean estimate by TCMM, estimates of CASTLES (orange), concatenation (grey).

AB branch length

On the biological dataset, ERaBLE fails to return an output and AVG+FastME returns an estimated tree with several long negative branches around the root; we exclude those methods and compare CAS-TLES, TCMM, and CASTLES+TCMM ($\lambda = 10^{-3}$). Using 49 core genes (including ribosomal genes) CASTLES estimates a length of 1.91 SU for the AB branch separating bacteria and archaea, while TCMM and CASTLES+TCMM estimate 1.39 and 1.44 SU, respectively. In contrast, on the 38 non-ribosomal genes (presumably with more HGT), the AB branch is much shorter, as Moody et al. (2022) have found; TCMM estimates AB length to be 0.67 or 0.69 SU (depending on λ), which is higher than concatenation (0.43) but lower than CASTLES (1.01). The fact that both gene tree-based methods have higher length than concatenation for non-ribosomal genes is consistent with the observation by Moody et al. (2022) that concatenation can under-estimate length in the face of HGT. However, the large difference between ribosomal and non-ribosomal genes even using methods that account for gene tree discordance supports the observation by Zhu et al. (2019) that ribosomal genes have very different AB lengths than other proteins. In the per-gene mode, TCMM also estimates a separate branch length per each gene tree (Fig. 5). Examining the distribution shows that there is substantial diversity among genes, with some indicating an AB length of more than 3 SU, while others lead to a length below 0.5 SU. While our study alone is insufficient to settle this debate, we note that AB estimates based on ribosomal genes are distributed around those proposed by Moody et al. (2022) while those based on non-ribosomal genes are closer to the Zhu et al. (2019) estimate. We leave a more thorough exploration of this question with more marker genes and large trees for future work.

4   Discussion and future work

We have introduced TCMM, a versatile framework for reconciling branch lengths of a query tree to one or more reference trees. Our paper focused on a particular application, species tree branch length estimation, where we showed TCMM performs comparably to specialized tools designed for this purpose. Notably, TCMM does not directly model coalescence, in contrast to methods like CASTLES. A useful feature of our framework is that, through regularization, it can be used as a complementary step alongside alternative tools such as CASTLES. However, our empirical results showed that even without that pairing, the default TCMM manages to estimate species tree branch lengths without the anticipated overestimation bias due to gene tree coalescence events predating speciation events. Since using the arithmetic mean across genes did result in an over-estimation bias (Fig. 2a), the lack of over-estimation bias in the default version is likely due to the use of the geometric mean, which is always lower than the arithmetic mean. We leave the further theoretical question of whether the geometric mean used with TCMM is biased to future work.

When paired with CASTLES, the accuracy of TCMM tended to increase compared to both methods. It should be kept in mind that this pairing also benefited from automatic selection of lambda using the minimum evolution principle. It is not true that any choice of lambda will lead to a CASTLES+TCMM method that is better than either method. Thus, it appears that the increased accuracy of TCMM+CASTLES is a result of combining three approaches: coalescent-based method of CASTLES, the patristic distance matching of TCMM, and the minimum evolution principle.

More broadly, the per-gene mode of TCMM provides a length *distribution* for each species tree branch. Allowing one rate per branch per gene is effectively modeling across-genes heterotachy in the evolutionary process (Lopez et al., 2002), a feature missing from other methods. ERaBLE has only one mutation rate per gene, making it far less versatile in dealing with rate changes. CASTLES models rate heterogeneity across the species tree and overall rate changes across genes; however, it assumes that all genes have the same relative rates for species tree branches. Our biological results showed evidence (Fig. 5) for heterotachy at the root of the Tree of Life. Part of the reason why TCMM is as accurate as alternatives despite the lack of direct modeling of coalescence can also be its modeling of heterotachy, which is present across all of our Simphy-simulated datasets.

While we focused on species tree branch length estimation, the TCMM framework can have wide-ranging applications beyond what we explored. The TCMM formulation may be used in embedding tree leaves in unified spaces, as has been done previously for detecting outlier leaves of gene trees (de Vienne et al., 2012). The linear algebraic approach used here is effectively comparing two trees by matching one to the other. Unlike many commonly used phylogenetic metrics, this matching incorporates both tree topology and branch lengths. It appears that the results of the matching can be translated to new metrics of tree distance and perhaps new median tree problems. Future work should explore those metrics and whether they provide additional insights.

5   Acknowledgement

This work was supported by the National Institutes of Health (1R35GM142725) grant to S.M.

References

Arnold, B. J., Huang, I.-T., and Hanage, W. P. (2022). Horizontal gene transfer and adaptive evolution in bacteria. *Nature Reviews Microbiology*, 20(4):206–218.

Barthélemy, J.-P. and McMorris, F. R. (1986). The median procedure for n-trees. *Journal of Classification*, 3(2):329–334. Publisher: Springer.

Binet, M., Gascuel, O., Scornavacca, C., P. Douzery, E. J., and Pardi, F. (2016). Fast and accurate branch lengths estimation for phylogenomic trees. *BMC Bioinformatics*, 17(1):23.

Bogdanowicz, D. and Giaro, K. (2012). Matching split distance for unrooted binary phylogenetic trees. *IEEE/ACM Transactions on Computational Biology and Bioinformatics*.

Boussau, B., Szöllősi, G. J., and Duret, L. (2013). Genome-scale coestimation of species and gene trees. *Genome Research*, 23(2):323–330.

Davidson, R., Vachaspati, P., Mirarab, S., and Warnow, T. (2015). Phylogenomic species tree estimation in the presence of incomplete lineage sorting and horizontal gene transfer. *BMC Genomics*, 16(Suppl 10):S1.

de Vienne, D. M., Ollier, S., and Aguileta, G. (2012). Phylo-MCOA: A Fast and Efficient Method to Detect Outlier Genes and Species in Phylogenomics Using Multiple Co-inertia Analysis. *Molecular Biology and Evolution*, 29(6):1587–1598.

DeGiorgio, M. and Degnan, J. H. (2014). Robustness to Divergence Time Underestimation When Inferring Species Trees from Estimated Gene Trees. *Systematic Biology*, 63(1):66–82.

Degnan, J. H. and Rosenberg, N. A. (2009). Gene tree discordance, phylogenetic inference and the multispecies coalescent. *Trends in Ecology and Evolution*, 24(6):332–340. ISBN: 0169-5347 Publisher: Department of Human Genetics, University of Michigan, Ann Arbor, MI 48109, USA. j.degnan@math.canterbury.ac.nz.

Doyon, J.-P. J., Ranwez, V., Daubin, V., and Berry, V. (2011). Models, algorithms and programs for phylogeny reconciliation. *Briefings in Bioinformatics*, 12(5):392–400.

Edwards, S. and Beerli, P. (2000). Perspective: gene divergence, population divergence, and the variance in coalescence time in phylogeographic studies. *Evolution*, 54(6):1839–1854.

Estabrook, G. F., McMorris, F. R., and Meacham, C. A. (1985). Comparison of Undirected Phylogenetic Trees Based on Subtrees of Four Evolutionary Units. *Systematic Biology*, 34(2):193–200.

Forthman, M., Braun, E. L., and Kimball, R. T. (2022). Gene tree quality affects empirical coalescent branch length estimation. *Zoologica Scripta*, 51(1):1–13.

Heled, J. and Drummond, A. J. (2010). Bayesian inference of species trees from multilocus data. *Molecular Biology and Evolution*, 27(3):570–580.

Kubatko, L. S., Carstens, B. C., and Knowles, L. L. (2009). STEM: species tree estimation using maximum likelihood for gene trees under coalescence. *Bioinformatics*, 25(7):971–973.

Kumar, S. (2005). Molecular clocks: four decades of evolution. *Nature Reviews Genetics*, 6(8):654–662.

Lefort, V., Desper, R., and Gascuel, O. (2015). FastME 2.0: A comprehensive, accurate, and fast distance-based phylogeny inference program. *Molecular Biology and Evolution*, 32(10):2798–2800. ISBN: 1537-1719 (Electronic)\r0737-4038 (Linking).

Liu, L. (2008). BEST: Bayesian estimation of species trees under the coalescent model. *Bioinformatics*, 24(21):2542–2543. ISBN: 1367-4803 Publisher: Musuem of Comparative Zoology, Harvard University, Cambridge, MA, USA. lliu@oeb.harvard.edu.

Liu, L. and Yu, L. (2011). Estimating Species Trees from Unrooted Gene Trees. *Systematic Biology*, 60(5):661–667. ISBN: 1063-5157\r1076-836X.

Lopez, P., Casane, D., and Philippe, H. (2002). Heterotachy, an Important Process of Protein Evolution. *Molecular Biology and Evolution*, 19(1):1–7.

Maddison, W. P. (1997). Gene Trees in Species Trees. *Systematic Biology*, 46(3):523–536.

Mai, U. and Mirarab, S. (2020). Log Transformation Improves Dating of Phylogenies. *Molecular Biology and Evolution*, 38(3):1151–1167.

Mallo, D., De Oliveira Martins, L., and Posada, D. (2016). SimPhy : Phylogenomic Simulation of Gene, Locus, and Species Trees. *Systematic Biology*, 65(2):334–344.

Mirarab, S., Nakhleh, L., and Warnow, T. (2021). Multispecies Coalescent: Theory and Applications in Phylogenetics. *Annual Review of Ecology, Evolution, and Systematics*, 52(1):247–268.

Mirarab, S., Reaz, R., Bayzid, M. S., Zimmermann, T., Swenson, M. S., and Warnow, T. (2014). ASTRAL: genome-scale coalescent-based species tree estimation. *Bioinformatics*, 30(17):i541–i548.

Moody, E. R., Mahendrarajah, T. A., Dombrowski, N., Clark, J. W., Petitjean, C., Offre, P., Szöllősi, G. J., Spang, A., and Williams, T. A. (2022). An estimate of the deepest branches of the tree of life from ancient vertically evolving genes. *eLife*, 11:e66695.

Mossel, E. and Roch, S. (2010). Incomplete lineage sorting: consistent phylogeny estimation from multiple loci. *IEEE/ACM Transactions on Computational Biology and Bioinformatics (TCBB)*, 7(1):166–171.

Ogilvie, H. A., Bouckaert, R. R., and Drummond, A. J. (2017). StarBEAST2 Brings Faster Species Tree Inference and Accurate Estimates of Substitution Rates. *Molecular Biology and Evolution*, 34(8):2101–2114. ISBN: 0737-4038.

Petitjean, C., Deschamps, P., López-García, P., and Moreira, D. (2015). Rooting the domain archaea by phylogenomic analysis supports the foundation of the new kingdom proteoarchaeota. *Genome biology and evolution*, 7(1):191–204.

Price, M. N., Dehal, P. S., and Arkin, A. P. (2010). FastTree-2 – Approximately Maximum-Likelihood Trees for Large Alignments. *PLoS ONE*, 5(3):e9490. Publisher: Public Library of Science.

Rasmussen, M. D. and Kellis, M. (2007). Accurate gene-tree reconstruction by learning gene- and species-specific substitution rates across multiple complete genomes. *Genome Research*, 17(12):1932–1942. ISBN: 1088-9051.

Robinson, D. and Foulds, L. (1981). Comparison of phylogenetic trees. *Mathematical Biosciences*, 53(1-2):131–147.

Rzhetsky, A. and Nei, M. (1993). Theoretical foundation of the minimum-evolution method of phylogenetic inference. *Molecular Biology and Evolution*, 10(5):1073–1095.

Sayyari, E. and Mirarab, S. (2016). Fast Coalescent-Based Computation of Local Branch Support from Quartet Frequencies. *Molecular Biology and Evolution*, 33(7):1654–1668.

Stamatakis, A. (2006). RAxML-VI-HPC: maximum likelihood-based phylogenetic analyses with thousands of taxa and mixed models. *Bioinformatics*, 22(21):2688–2690.

Tabatabaee, Y., Zhang, C., Warnow, T., and Mirarab, S. (2023). Phylogenomic branch length estimation using quartets. *Bioinformatics*, 39(Supplement_1):i185–i193.

Vachaspati, P. and Warnow, T. (2015). ASTRID: Accurate Species TRees from Internode Distances. *BMC Genomics*, 16(Suppl 10):S3. Publisher: BioMed Central Ltd.

Wang, C. and Xiu, N. (2000). Convergence of the gradient projection method for generalized convex minimization. *Computational optimization and applications*, 16(2):111–120.

Williams, T. A., Cox, C. J., Foster, P. G., Szöllősi, G. J., and Embley, T. M. (2020). Phylogenomics provides robust support for a two-domains tree of life. *Nature ecology & evolution*, 4(1):138–147.

Yang, J. and Warnow, T. (2011). Fast and accurate methods for phylogenomic analyses. *BMC Bioinformatics*, 12(Suppl 9):S4. Publisher: BioMed Central Ltd.

Zhang, C., Rabiee, M., Sayyari, E., and Mirarab, S. (2018). ASTRAL-III: polynomial time species tree reconstruction from partially resolved gene trees. *BMC Bioinformatics*, 19(S6):153.

Zhu, Q., Mai, U., Pfeiffer, W., Janssen, S., Asnicar, F., Sanders, J. G., Belda-Ferre, P., Al-Ghalith, G. A., Kopylova, E., McDonald, D., Kosciolek, T., Yin, J. B., Huang, S., Salam, N., Jiao, J.-Y., Wu, Z., Xu, Z. Z., Cantrell, K., Yang, Y., Sayyari, E., Rabiee, M., Morton, J. T., Podell1, S., Knights, D., Li1, W.-J., Huttenhower, C., Segata, N., Smarr, L., Mirarab, S., and Knight, R. (2019). WoL: reference phylogeny for microbes (data pre-release).

Zimmermann, T., Mirarab, S., and Warnow, T. (2014). BBCA: Improving the scalability of *BEAST using random binning. *BMC genomics*, 15(Suppl 6):S11.

Zuckerkandl, E. and Pauling, L. (1962). Molecular disease, evolution, and genic heterogeneity. *Horizons in biochemistry*, pages 189–225.

Supplementary figures and tables

Figure S6: (S100 Dataset) Error of different lambda values for the two methods per gene and consensus. Orange line indicates CASTLES. For $\lambda \neq 0$ CASTLES branch lengths were used in the regularization term. Plots are partitioned based on $\log_{10}(true)$

Figure S7: The distribution of the estimated branch lengths by two version of TCMM divided by the CASTLES branch lengths.