Original Article
Firefighter Helmets and Cervical Intervertebral Kinematics: An OpenSim-Based Biomechanical Study

Authors:

Gustavo M. Paulon
Department of Industrial, Manufacturing and Systems Engineering
Texas Tech University
Lubbock, Texas, USA

S. Sudeesh, PhD
Department of Industrial, Manufacturing and Systems Engineering
Texas Tech University
Lubbock, Texas, USA

Suman K. Chowdhury, PhD
Assistant Professor
Department of Industrial, Manufacturing and Systems Engineering
Texas Tech University
Lubbock, Texas, USA

Corresponding author:
Suman K. Chowdhury, PhD
Assistant Professor
Department of Industrial, Manufacturing and Systems Engineering
Texas Tech University
905 Canton Ave, Lubbock 79409-3061, Texas, USA.
E-mail: suman.chowdhury@ttu.edu;
Tel: +1 (806)-834-7908

Word Count: 3,432

Keywords: OpenSim Musculoskeletal Model, Firefighter Helmet, Cervical Spine Kinematics, Neck Range of Motion

Abstract

The assessment of cervical intervertebral kinematics can serve as the basis for understanding any degenerative changes in the cervical spine due to the prolonged wear of a heavyweight, imbalanced firefighting helmet. Therefore, this study aimed to analyze cervical intervertebral kinematics using OpenSim musculoskeletal modeling platform in order to provide much-needed insights of how the inertial properties of firefighter helmet affect cervical spinal mobility. A total of 36 firefighters (18 males and 18 females) were recruited to perform static and dynamic neck flexion, extension, and left and right lateral bending tasks for three conditions: 1) no-helmet, 2) US-style helmet with a comparatively superior center of mass (COM), and 3) European-style helmet with relatively higher mass but an inferior COM. Three custom-made OpenSim head-neck models were created to calculate cervical intervertebral kinematics for each helmet condition. Results showed that the helmet use significantly ($p<0.001$) affects neck and cervical spinal kinematics. Especially, the superior COM placement in the US-style helmet, despite its lighter weight, caused more pronounced kinematic changes and quicker attainment of peak flexion and extension angles compared to the European-style helmet across all cervical joints. Moreover, results also revealed discrepancies between OpenSim-derived neck and cervical range-of-motion and those reported in previous in-vivo studies. In conclusion, the present study underscores the importance of designing firefighter helmets with a lower profile (less superior COM) to enhance neck range of motion and minimize potential neck injuries.

Introduction

Neck pain is a multifactorial musculoskeletal health condition with a high global prevalence. According to the 2019 Global Burden of Disease (GBD) Study, neck pain was among the top four most prevalent musculoskeletal disorders (MSDs) and affected 222.7 million people (2.9% of total population) worldwide (GBD, 2019). Various factors, ranging from ergonomic factors in the workplace to daily lifestyle and recreational activities, contribute to the onset and persistence of neck pain. For instances, prolonged static postures (Christensen et al., 2023), repetitive neck motions (Guidotti, 1992), heavy lifting or working in awkward neck postures (Ariens et al., 2000), sedentary lifestyle and poor sleep quality (Peterson and Pihlström, 2021), and chronic stress and certain mental health conditions (Kim et al., 2013) have been associated with work-related neck MSDs. In addition to these causes, the usage of helmets and other head mounted devices in medical surgery (Nimbarte et al., 2013), military (Hanks et al., 2018), firefighting (Park et al., 2014; Wang et al., 2021), sports (Kent et al., 2020), and vehicle safety applications (Diyana et al., 2019) were found to increase the likelihood of neck MSDs.

Previous biomechanical studies have primarily associated excessive weight and shifted center of mass (COM) of helmets with the risks of neck injuries. For instance, Van Dijke et al. (1993) and Newman et al. (2022) studied the influence of jet pilot helmets' inertial properties on the risk of neck injury and found that helmets significantly increase the neck joint reaction moments. Barrett et al. (2023) showed that the inertial properties (i.e., COM, mass, and moment of inertia) of a military helmet resulted in higher compressive forces in the cervical spine. Other studies on construction (Boschman et al., 2015), mining (Torma-Krajewski et al., 2006), and firefighting (Wang et al., 2021) helmets also emphasized the importance of enhancing the ergonomic aspects

(i.e., inertial properties) of helmets in order to reduce neck discomfort and MSDs. Among them,

firefighter helmets are usually heavier than other helmet types because they include two shells and

other padding materials to provide high flame and impact protection to the users. Additionally, the

modern firefighter helmets include other supporting accessories, such as face-shield, visor, and

lighting equipment. Their additions can further increase the likelihood of cervical spinal injuries

due to the increase in the total helmet weight and a potential shift of the helmet COM. Especially,

these changes can make female users more vulnerable to neck pain as they have weaker neck

muscles (Vasavada et al., 2008) and smaller cervical vertebra (Stemper et al., 2008) than males. It

was also reported that about 23 % of all firefighter injuries (27,150 cases out of 118,070 cases)

are related to the head, neck, and shoulder – out of which, 5.5% involved strains or overexertion

on the head and neck (Campbell and Molis, 2022). As firefighter helmets are worn daily for a

prolonged duration, their repetitive usages over time can result in degenerative neck injuries, such

as spinal cord spondylosis, degenerative disc diseases, and ossification of the ligamentum flavum

(Echarri and Forriol, 2005).

As indicated in previous clinical (Hino et al., 1999; Hirsch et al., 1967) and biomechanical (Panjabi

et al., 2001) studies, the assessment of cervical intervertebral kinematics can be used as surrogate

measures of degenerative changes occurring in the cervical spine because these changes can

adversely affect the neck joint mobility. Thus, an accurate information about the cervical

intervertebral joint mobility under the effects of no-helmet and helmet conditions can serve as the

basis to evaluate how the helmet inertial properties may cause abnormal neck conditions. A number

of in-vivo experimental studies using dynamic fluoroscopic system (Zhou et al., 2020), dynamic

stereo-radiographic system (Anderst et al., 2015b), and three-dimensional MRI (Ishii et al., 2006)

have reported neck and cervical intervertebral ROM. As these in-vivo studies are labor-, time-, and

technology-intensive, a handful of studies used in-silico methods, such as OpenSim (an open-

source musculoskeletal modeling platform) (Barrett et al., 2022a; Barrett et al., 2022b; Mathys and

Ferguson, 2012; Newman et al., 2022) because of their non-invasiveness nature and ease-of-use in

modeling the head-helmet dynamics. Nevertheless, they overlooked the influence of helmet on

cervical intervertebral kinematics, especially during dynamic neck movements. Additionally, our

systematic literature review showed only one survey-based study on the firefighter helmet by

Wang et al. (2021). They reported that a poorly-fitting, imbalanced helmet can restrict firefighter's

neck mobility, which motivates us to conduct a thorough biomechanical investigation to assess the

impacts of firefighter helmets on cervical intervertebral kinematics — the potential surrogate

measures of degenerative neck injuries.

Therefore, this study aimed to investigate the effects of firefighter helmet inertial properties on

neck and cervical intervertebral kinematics, especially during various neck dynamic movements.

Two types of helmets are frequently used by firefighters: 1) US-style helmet (resemblance to hats)

and 2) European-style helmet (resemblance to aviation helmets). A quantitative analysis of their

inertial properties and how their variations affect cervical intervertebral kinematics would provide

an unprecedented understanding of firefighter's neck MSD mechanisms and assist practitioners to

design an injury-mitigating firefighter helmet that can be worn for prolonged time.

Methods

Participants

We recruited eighteen male (weight: 88.5 ± 18.9 kg; height: 1.77 ± 0.09 m; BMI: 28.8 ± 5.39; Age:

39.2 ± 7.23 years) and eighteen female (weight: 69.5 ± 12.2 kg; height: 1.64 ± 0.05 m; BMI: 24.2

± 2.85; Age: 31.2 ± 8.62 years) firefighters from the local fire departments. The inclusion criteria

required all participants to be healthy and did not have any recent history of neck, shoulder, and

back injury. Prior to their participation, they signed an informed consent form approved by the

local Institutional Review Board (IRB2020-708).

Experiment

Participants primarily performed two repetitions of static task—holding a static head-neck position

in full flexion, extension, and left and right lateral bending for five seconds—and two repetitions

of dynamic task—self-paced, controlled (using a digital metronome) full flexion-extension and

left-right lateral bending movements, each separately for 3 seconds— using three different helmet

conditions: 1) baseline, no-helmet, 2) US-style helmet (Bullard UM6WH), and 3) European-style

(Cairns XF1) helmet in a random order (Figure 1). We collected full-body movements using a 10-

camera motion capture system at 60 Hz (Krestel 1300; Motion Analysis, California, USA) and

ground reaction forces using two force plates (Bertec, Ohio, USA) at 600 Hz. We also used a

handheld, rotating 3D scanner (EinScan HX, Shining 3D, Hangzhou, China) to image individual

helmets at 20 Hz frame rate. The kinematics data were pre-processed in Cortex-9 software (Motion

Analysis Corporation, Rohnert Park, California, USA). Though we used full-body plug-in gait

marker set (Vicon, 2023) consisting of 44 markers in the experimental protocol, we created

additional 32 virtual markers in Cortex to measure link-segment anthropometric measures

accurately. The force plate data were exported from Cortex-9 as C3D format and then converted

to motion (.mot) files using C3Dtools (Mokhtarzadeh and Bagheri, 2023) in order to input them

into OpenSim.

Insert Figure 1

OpenSim Modeling

The MASI (Musculoskeletal model for the Analysis of Spinal Injury) model, a validated full-body

model developed by Cazzola et al. (2017), was used as a base model for our study. Then, we added

infra-hyoid muscles to the base model—taken from HYOID model (Mortensen et al., 2018)—to

achieve more biofidelic cervical intervertebral kinematic results. The modified model included 35

rigid body segments, 34 body joints, 23 torque actuators, 98 Hill's type neck muscles, and

inherited head and neck models of Vasavada et al. (1998) that implements three rotational (row,

pitch, and yaw) degrees of freedom (DoF) to C0-C1(atlanto-occipital), C1-C2 (atlanto-axial), C2-

C3, C3-C4, C4-C5, C5-C6, C6-C7, and C7-T1 joints. We also added an additional 65 model

markers in OpenSim to make the model compatible with the Cortex marker set up.

Three different versions of our modified model—a no-helmet, a US-style helmet, and a European-

style helmet model—were created. Prior to the creation of head-helmet OpenSim interfacing, the

geometrical shape of each helmet type was created in NMSBuilder (Valente et al., 2017) software

and their inertial properties (Table 1) were estimated in ANSA (BETA CAE Systems SA, Greece)

finite element pre-processor platform. It was observed that the COM of the US-style helmet is 5.8

cm superior and 1.7 cm posterior than the European-style helmet. However, the European-style

helmet was 250 g heavier than the US-style helmet. Additionally, we calculated the combined

moment of inertia (MOI) of head and helmet with respect to the C0-C1 joint by applying the

parallel axis theorem.

*** Insert Table 1 ***

OpenSim Simulation

Though we controlled the pace and duration of the experimental tasks using a metronome, slight

discrepancies remained across the tasks and the subjects. Therefore, we down-sampled both

kinematics and force plate data to 100 data points for between-task and between-subject

comparisons. In OpenSim, we implemented inverse pipelines (Figure 2) that include subject-

specific model scaling, inverse kinematics (IK), inverse dynamics (ID), and static optimization

(SO) processes. We scaled (RMS:< 1cm; maximum: < 2 cm) each custom-made OpenSim model

by using marker data collected during corresponding baseline, static head-neck neutral posture for

each helmet condition. In head-helmet OpenSim models, we applied a welded joint to the head-

helmet interface. We then used task-specific motion capture data to perform Inverse Kinematics

(IK) simulations. In some trials, adjustments were made to the model markers and their weightages

in order to keep the root mean square (RMS) < 2 cm and maximum marker errors < 4 cm during

the IK analysis. The IK and the ground reaction force data were then used as inputs to perform SO.

We accepted the IK results if both the SO and the OpenSim forward pipelines were successfully

run and the moment and kinematic errors between forward and inverse solutions remained below

acceptable thresholds.

The neck angle was calculated by summing the kinematics of all cervical intervertebral joints (C0-

C1 to C7-T1). The flexion-extension and lateral bending ROM of individual cervical joints and

the neck was calculated by taking the difference between their maximum positive and negative

angular values during respective dynamic motions. Due primarily to poor marker (pelvis and other

markers of some subjects moved or fall off during the experimental tasks) data and some

challenges during experimental data collection, we abled to simulate OpenSim models of a total

of 24 subjects—12 males (weight: 90.6 ± 19.1 kg; height: 1.77 ± 0.066 m; BMI: 28.8 ± 2.85 kg/m^2;

Age: 38.2 ± 7.97 years) and 12 females (weight: 67.4 ± 8.28 kg; height: 1.67 ± 0.055 m; BMI:

24.2 ± 2.85 kg/m^2; Age: 31.2 ± 8.62 years)—and the further analysis of this study was based on

these 24 best subject's data.

*** Insert Figure 2 ***

Statistical Analysis

We calculated the descriptive statistics (mean and standard error) of peak flexion, peak extension,

peak left bending, peak right bending, flexion-extension ROM, and lateral bending ROM of

individual cervical intervertebral joints and the neck (C0-T1) as a whole for all static and dynamic

exertion trials across all subjects (males and females separately). In order to investigate the effects

of helmets and sex and their interaction on neck and cervical intervertebral peak angles and ROM

data, we first evaluated data normality and homoscedasticity conditions. As the majority of the

peak angle data violated these two conditions even after logarithmic, exponential, and power

transformations, we employed Friedman non-parametric test wherein the effects of *helmet*

condition (no-helmet, US-style helmet, and European-style helmet) and *subject* were respectively

treated as fixed and randomized block variables. Additionally, we considered Kruskal-Walis non-

parametric test to study the *sex* (male and female) effect. In both Kruskal-Walis and Friedman

tests, peak flexion, extension, left bending, and right bending angles of C0-C1, C1-C2, C2-C3, C3-

C4, C4-C5, C5-C6, C6-C7, and C7-T1 joints and the neck (C0-T1) during static and dynamic tasks

(task conditions) were treated as dependent variables. As the ROM data of the neck and the cervical

joints met the normality assumption, we performed multi-factor Analysis of Variance (ANOVA)

tests wherein *helmet condition*, *sex,* and their interaction were independent variables and the

subject was treated as a random block. All statistical tests were performed at 95% confidence level

($\alpha = 0.05$).

Results

Helmet Effect

Peak Neck Angle Data

Friedman tests showed that, the helmet use led to a significant increase in neck flexion (static:

p<0.001, 9.55% for US-style and 5.90% for European-style; dynamic: p<0.001, 6.79% for US-

style and 3.93% for European-style) and a significant decrease in neck extension (static: p=0.004,

10.7% for US-style and 2.67% for European-style; dynamic: p=0.001, 17.3% for US-style and

4.99% for European-style) in comparison to no-helmet baseline (Table 2). Particularly, the US-

style helmet exhibited a larger increase in neck flexion (static: 3.45% and dynamic: 2.76%) and a

greater reduction in neck extension (static: 8.23% and dynamic: 13.0%) than the European-style

helmet. Though the helmet use was not significant for neck lateral bending tasks (Table 2), the use

of US-style helmet led to a larger lateral bending angle (right: 2.93% and left: 4.73%) than the

European-style helmet, particularly to the right side (2.50%) than the left side.

197   *** Insert Table 2 ***

Neck ROM Data

The ANOVA results exhibited that the helmet use significantly reduced the neck flexion-extension

ROM (p=0.0395), especially the US-style helmet (~6.67%) followed by the European-style helmet

(~1%) (Table 3). While no significant effect of helmets was observed during lateral bending tasks

(p=0.0693), the US-style helmet increased the lateral bending ROM by 3.13% whereas the

European-style helmet decreased the lateral bending ROM by 2.76%. While compared with the

experimentally measured data from the literature, our baseline, no-helmet condition data showed

notably lower ROM values for both flexion-extension (14.1%~47.1%) and lateral bending

(11.6%~54.8%) neck movements (Table 3).

209   *** Insert Table 3 ***

Peak Cervical Intervertebral Kinematic Data

The significant effects (p<0.010) of the helmet use were observed for the majority of the

intervertebral joints' peak flexion, extension, and left and right lateral bending angles, except five

scenarios – C2-C3 left and right lateral bending during static task, C2-C3 right bending during

dynamic task, C0-C1 and C1-C2 extension (Figure 3). The C0-C1 joint contributed the most

towards the total neck peak angles during both static (21% and 26% for neck flexion and extension,

respectively) and dynamic (22% and 29% for neck flexion and extension, respectively) tasks,

followed by C4-C5, C5-C6, and C6-C7 joints. Interestingly, the C0-C1 joint exhibited trivial

contributions (lower than 10%) during both lateral bending motions (Figure 3).

221   *** Insert Figure 3 ***

Cervical Intervertebral ROM Data

The ANOVA tests displayed a significant effect of helmet use on both flexion-extension and lateral

bending ROM for six cervical joints (C2-C3 to C7-T1), except C0-C1 and C1-C2 joints. Compared

to the literature data, we also found noticeable discrepancies for both C0-C1 and C1-C2 joint ROM

(Table 3). This discrepancy can be attributed to how the OpenSim model distributed the angle

across the cervical intervertebral joints. To explore it further, we calculated the distribution ratio

between the dependent joint coordinates (movement) with respect to their coupled independent

joint coordinate (movement) (Table 4). We observed that motions of the lower and mid cervical

joints (C2 to C7) were somewhat evenly distributed (max ratio=12.6), while the motion of the

upper cervical joints was mainly carried by C0-C1 joint (max ratio=31.9). The independent joint

coordinates of C1-C2 and C7-T1 remain same irrespective of intersubject variations and

movement types.

236   *** Insert Table 4 ***

Cervical Intervertebral Movement Patterns

The flexion and extension movement patterns (Figure 4) showed that subjects went into the peak

flexion and extension positions, respectively, by about 2% and 5% faster (averaged across all

joints) with the US-style helmet than the no-helmet condition. In contrast, the European-style

helmet exhibited about 1% faster flexion and 3% slower extension movements across all joints

than the no-helmet baseline. Similarly, lateral bending movements (Figure 5) of the neck and all

joints (except C2-C3 joint) showed that subjects went into peak left and right bending positions,

respectively, by 5% and 9% faster with the US-style helmet, followed by 4% and 7% faster with

the European-style helmet, compared to the no-helmet baseline.

Sex Effect

The statistical tests for the sex effect did not show any statistical significance across all ROM and

peak angle data of the neck and individual cervical intervertebral joints. However, females broadly

exhibited greater peak flexion, peak lateral bending, flexion-extension ROM, and lateral bending

ROM than their male counterparts, irrespective of the helmet use (Table 2).

253   *** Insert Figure 4 ***

256   *** Insert Figure 5 ***

Discussion

The present study investigated the effects of firefighter helmet on cervical intervertebral

kinematics during static and dynamic neck flexion, extension, right, and left bending tasks. Results

demonstrated that the helmet COM had more pronounced effects on the cervical intervertebral

kinematics than the helmet mass, particularly during full flexion and extension positions. In full

flexion position, despite being lighter (12.4%; 250 g), US-style helmet exhibited more

hyperflexion and quicker attainment of peak flexion angles than European-style helmet.

Particularly, the longer moment arm of the US-style helmet in the superior direction (38.2% and

5.8 cm more superior) induced a larger rotational torques at each cervical joint and caused more

accelerated dynamic neck movements than the European-style helmet. Likewise, despite having a

lesser anterior COM location than the European-style helmet, the US-style helmet reached peak

extension angle more rapidly. This can be attributed to its superior COM that yielded about 10%

higher MOI at C0-C1 joint than those observed with European-style helmet. Similarly, though the

COM of the US-style helmet was less offset in the left lateral direction than the European-style

helmet, it increased the peak left bending angle by 4.51% (1.3º) because its superior COM caused

about 17.4% (0.016 kg.m^2) higher MOI in the superior direction. Thus, our findings highlighted

the importance of a low-profile (i.e., less superior COM) helmet in order to yield a greater neck

range of motion to the users. Finally, we observed some sex-specific insignificant differences in

neck peak angles which aligns well with a previous study (Pan et al., 2018).

Interestingly, our results revealed a greater contribution from C0-C1 joint and a trivial contribution

from C1-C2 joint during both flexion-extension and lateral bending movements. However,

previous studies (Anderst et al., 2015b; Ishii et al., 2006; Zhou et al., 2020) showed an equal

contribution (~11º) from both C0-C1 and C1-C2 joints during neck flexion-extension movements.

This discrepancy was owing to the fact that the MASI model divided the cervical spine into two

independent segments: 1) upper cervical spine (C0-C2) spine with C1-C2 as an independent

rotational DoF and 2) mid and lower cervical spine (C2-T1) with C7-T1 as an independent

rotational DoF (Cazzola et al., 2017; Vasavada et al., 1998). The other cervical joints in each of

these two segments have dependent rotational DoFs and their kinematics are estimated as a

percentage of the total motion of their corresponding independent rotational DoFs. Consequently,

this led to a greater contribution from C0-C1 joint and trivial movement in C1-C2 in the upper

cervical spine, in addition to a very slight movement in C7-T1 joint in the mid-lower cervical

spine.

Furthermore, the variations between OpenSim-derived ROM data and experimentally-measured

literature data can be attributed to several factors. The experimental studies by Anderst et al.

(2015b); Ishii et al. (2006); Zhou et al. (2020) considered both translational and rotational

movements (six DoFs) of the cervical intervertebral joints and the intervertebral joint angles were

directly measured between the adjacent vertebra's anatomical planes. In contrast, existing

OpenSim neck models employ three rotational DoFs and calculate the cervical intervertebral joint

kinematics on a fixed axis of rotation (Amevo et al., 1991). Previous studies reported that the neck

ROM in both flexion-extension and lateral bending decreases with age and males having

significantly lower ROM than females after their 30s (Pan et al., 2018). Thus, our findings of

reduced neck and cervical intervertebral mobility can be associated to the fact that our study

subjects were comparatively older and bulkier (high BMI) than reported experimental studies.

This study has several limitations. First, the effects of helmet inertial properties on neck rotation

were not evaluated. Second, we recruited and analyzed a limited number of subjects and two

different versions of firefighter helmets. Third, a certain extent of variations in estimating the neck

and cervical intervertebral angles can be associated to the OpenSim optimization routines of

scaling and IK processes; these variations would be different if we used a different modeling

platform. Fourth, as existing OpenSim neck models do not include translational DoFs and measure

intervertebral rotational kinematics by employing a fixed proportion, our data on cervical

kinematics are an estimated representation of the actual cervical intervertebral movement. In

summary, the present study is a first-of-its-kind investigation on the influence of helmet inertial

properties on the cervical intervertebral kinematics during both static and dynamic neck exertions.

Our findings established the critical role played by the helmet COM in adversely affecting the

cervical spinal mobility and acknowledged the placement of helmet COM near to C0-C1 joint (i.e.,

designing a low-profile helmet) in order to reduce potential neck injuries during prolonged wear.

Conflicts of Interest

315 None of the authors have conflicts of interest to declare.

Acknowledgements

317 This work was partly supported by the U.S. Department of Homeland Security

318 (70RSAT21CB0000023). We would like to acknowledge Mr. Felipe S. Zambrini, Mr. Leonardo

319 Wei, Mr. Hossein Bahreinizad, and Ms. Kathryn Bell for their assistance in data collection and

320 data preprocessing.

References

Amevo, B., Worth, D., Bogduk, N., 1991. Instantaneous axes of rotation of the typical cervical

motion segments: a study in normal volunteers. Clinical Biomechanics 6, 111-117.

Anderst, W.J., Donaldson III, W.F., Lee, J.Y., Kang, J.D., 2015a. Cervical motion segment

contributions to head motion during flexion\extension, lateral bending, and axial rotation. The

Spine Journal 15, 2538-2543.

Anderst, W.J., Donaldson III, W.F., Lee, J.Y., Kang, J.D., 2015b. Three-dimensional intervertebral

kinematics in the healthy young adult cervical spine during dynamic functional loading. Journal of

biomechanics 48, 1286-1293.

Ariens, G.A., Van Mechelen, W., Bongers, P.M., Bouter, L.M., Van Der Wal, G., 2000. Physical

risk factors for neck pain. Scandinavian journal of work, environment & health, 7-19.

Barrett, J.M., Healey, L.A., Fischer, S.L., Callaghan, J.P., 2022a. Cervical spine motion

requirements from night vision goggles may play a greater role in chronic neck pain than helmet

mass properties. Human factors, 00187208221090689.

Barrett, J.M., Healey, L.A., McKinnon, C.D., Laing, A.C., Dickerson, C.R., Fischer, S.L.,

Callaghan, J.P., 2023. Head supported mass, moment of inertia, neck loads and stability: A

simulation study. Journal of Biomechanics 146, 111416.

Barrett, J.M., McKinnon, C.D., Dickerson, C.R., Laing, A.C., Callaghan, J.P., 2022b. Posture and

helmet configuration effects on joint reaction loads in the middle cervical spine. Aerospace

medicine and human performance 93, 458-466.

Boschman, J.S., Frings-Dresen, M.H., Van Der Molen, H.F., 2015. Use of ergonomic measures

related to musculoskeletal complaints among construction workers: a 2-year follow-up study.

Safety and health at work 6, 90-96.

Campbell, R., Molis, J.L., 2022. Firefighter Injuries on the Fireground. National Fire Protection

Association (NFPA).

Cazzola, D., Holsgrove, T.P., Preatoni, E., Gill, H.S., Trewartha, G., 2017. Cervical spine injuries:

a whole-body musculoskeletal model for the analysis of spinal loading. PloS one 12, e0169329.

Christensen, S.W.M., Palsson, T.S., Krebs, H.J., Graven-Nielsen, T., Hirata, R.P., 2023. Prolonged

slumped sitting causes neck pain and increased axioscapular muscle activity during a computer

task in healthy participants–A randomized crossover study. Applied Ergonomics 110, 104020.

Diyana, M.A., Karmegam, K., Shamsul, B., Irniza, R., Vivien, H., Sivasankar, S., Syahira, M.P.A.,

Kulanthayan, K., 2019. Risk factors analysis: Work-related musculoskeletal disorders among

male traffic policemen using high-powered motorcycles. International Journal of Industrial

Ergonomics 74, 102863.

Echarri, J.J., Forriol, F., 2005. Influence of the type of load on the cervical spine: a study on

Congolese bearers. The Spine Journal 5, 291-296.

GBD, 2019. Global Burden of Disease Study 2019 (GBD 2019) Results., in: Seattle,

U.S.I.f.H.M.a.E.I., 2020. (Ed.).

Guidotti, T., 1992. Occupational repetitive strain injury. American Family Physician 45, 585-592.

Hanks, M.M., Sefton, J.M., Oliver, G.D., 2018. Neck kinematics and electromyography while

wearing head supported mass during running. Aerospace medicine and human performance 89,

9-13.

Hino, H., Abumi, K., Kanayama, M., Kaneda, K., 1999. Dynamic Motion Analysis of Normal and

Unstable Cervical Spines Using Cineradiography: An: In Vivo: Study. Spine 24, 163-168.

Hirsch, C., Schajowicz, F., Galante, J., 1967. Structural changes in the cervical spine: a study on

autopsy specimens in different age groups. Acta Orthopaedica Scandinavica 38, 1-77.

Ishii, T., Mukai, Y., Hosono, N., Sakaura, H., Fujii, R., Nakajima, Y., Tamura, S., Iwasaki, M.,

Yoshikawa, H., Sugamoto, K., 2006. Kinematics of the Cervical Spine in Lateral Bending: In Vivo:

Three-Dimensional Analysis. Spine 31, 155-160.

Kent, R., Forman, J., Bailey, A.M., Funk, J., Sherwood, C., Crandall, J., Arbogast, K.B., Myers,

B.S., 2020. The biomechanics of concussive helmet-to-ground impacts in the National Football

League. Journal of biomechanics 99, 109551.

Kim, M.G., Kim, K.-S., Ryoo, J.-H., Yoo, S.-W., 2013. Relationship between occupational stress

and work-related musculoskeletal disorders in Korean male firefighters. Annals of occupational

and environmental medicine 25, 1-7.

Mathys, R., Ferguson, S., 2012. Simulation of the effects of different pilot helmets on neck loading

during air combat. Journal of biomechanics 45, 2362-2367.

Mokhtarzadeh, H., Bagheri, S., 2023. Streamlining C3D File Processing and Visualization: A User-

Friendly Approach Using Google Colab and Open-Source Python Packages.

Mortensen, J.D., Vasavada, A.N., Merryweather, A.S., 2018. The inclusion of hyoid muscles

improve moment generating capacity and dynamic simulations in musculoskeletal models of the

head and neck. PloS one 13, e0199912.

Newman, P., Riches, A., Mara, J., Spratford, W., 2022. The effect of helmet mass and aircraft

acceleration on cervical spine loads during typical fast jet aircraft pilot head motions. Journal of

science and medicine in sport 25, 855-860.

Nimbarte, A.D., Sivak-Callcott, J.A., Zreiqat, M., Chapman, M., 2013. Neck postures and cervical

spine loading among microsurgeons operating with loupes and headlamp. IIE Transactions on

Occupational Ergonomics and Human Factors 1, 215-223.

Pan, F., Arshad, R., Zander, T., Reitmaier, S., Schroll, A., Schmidt, H., 2018. The effect of age and

sex on the cervical range of motion–A systematic review and meta-analysis. Journal of

biomechanics 75, 13-27.

Panjabi, M.M., Crisco, J.J., Vasavada, A., Oda, T., Cholewicki, J., Nibu, K., Shin, E., 2001.

Mechanical properties of the human cervical spine as shown by three-dimensional load–

displacement curves. Spine 26, 2692-2700.

Park, H., Park, J., Lin, S.-H., Boorady, L.M., 2014. Assessment of Firefighters' needs for personal

protective equipment. Fashion and Textiles 1, 1-13.

Peterson, G., Pihlström, N., 2021. Factors associated with neck and shoulder pain: a cross-

sectional study among 16,000 adults in five county councils in Sweden. BMC Musculoskeletal

Disorders 22, 1-9.

Stemper, B.D., Yoganandan, N., Pintar, F.A., Maiman, D.J., Meyer, M.A., DeRosia, J., Shender,

B.S., Paskoff, G., 2008. Anatomical gender differences in cervical vertebrae of size-matched

volunteers. Spine 33, E44-E49.

Torma-Krajewski, J., Steiner, L.J., Lewis, P., Gust, P., Johnson, K., 2006. Ergonomics and mining;

charting a path to a safer workplace.

Valente, G., Crimi, G., Vanella, N., Schileo, E., Taddei, F., 2017. nmsBuilder: Freeware to create

subject-specific musculoskeletal models for OpenSim. Computer methods and programs in

biomedicine 152, 85-92.

Van Dijke, G.H., Snijders, C., Roosch, E., Burgers, P., 1993. Analysis of biomechanical and

ergonomic aspects of the cervical spine in F-16 flight situations. Journal of biomechanics 26,

1017-1025.

Vasavada, A.N., Danaraj, J., Siegmund, G.P., 2008. Head and neck anthropometry, vertebral

geometry and neck strength in height-matched men and women. Journal of biomechanics 41,

114-121.

Vasavada, A.N., Li, S., Delp, S.L., 1998. Influence of muscle morphometry and moment arms on

the moment-generating capacity of human neck muscles. Spine 23, 412-422.

Vicon, 2023. Plug-in Gait Reference Guide. Vicon Motion Systems.

418 Wang, S., Park, J., Wang, Y., 2021. Cross-cultural comparison of firefighters' perception of mobility

419 and occupational injury risks associated with personal protective equipment. International journal

420 of occupational safety and ergonomics 27, 664-672.

421 Zhou, C., Wang, H., Wang, C., Tsai, T.-Y., Yu, Y., Ostergaard, P., Li, G., Cha, T., 2020.

422 Intervertebral range of motion characteristics of normal cervical spinal segments (C0-T1) during

423 in vivo neck motions. Journal of biomechanics 98, 109418.

Figure 1: A schematic presentation of (a) Task 1 wherein subjects performing static flexion, extension, left, and right bending tasks and (b) Task 2, in which they performed dynamic flexion-extension and dynamic lateral bending tasks. Both tasks were performed for three different conditions: 1) baseline, no-helmet (left), 2) US-style helmet (middle), and 3) European-style helmet (right) in a random order.

Figure 2: OpenSim inverse-solution workflow displaying the development of three modified MASI models: 1) no-helmet, 2) US-style helmet, and 3) European-style helmet conditions and their inverse simulation pipelines to calculate task-specific neck and cervical kinematics using experimental data.

Figure 3: The peak angles of individual intervertebral joints (C0-C1, C1-C2, C2-C3, C3-C4, C5-C6, and C7-T1) in extreme flexion, extension, and left and right lateral bending positions for all

456   helmet conditions: no-helmet, US-style helmet, and European-style helmet. If the helmet condition

457   was statistically significant for a joint, it is indicated with asterisks (*: p-value < 0.05; **: p-value

458   < 0.01) symbol.

Figure 4: Flexion and extension movements of cervical spine joints for different helmet conditions. The C1-C2 and C7-T1 joints were not included as their movements were insignificant.

476   The time-to-peak flexion and extension angles are indicated with arrow signs: red, blue, and black

477   refer to corresponding time-to-peak angles for US-style helmet, European-style helmet, and no-

478   helmet conditions, respectively. (Anderst et al., 2015a)

Figure 5: Left and right bending movements of cervical spine joints for different helmet

conditions. The C1-C2 and C7-T1 joints were not included as their contributions in total neck

movements were trivial. The time-to-peak flexion and extension angles are indicated with arrow

signs: red, blue, and black refer to corresponding time-to-peak angle for US-style helmet,

European-style helmet, and no-helmet conditions, respectively. (Anderst et al., 2015a)

Table 1: Inertial properties (mass, center of mass, and moment of inertial) of US-style and European-style

helmets. X, Y, and Z respectively indicate anterior-posterior, inferior-superior, and medio-lateral directions.

A positive value refers to anterior, right lateral, and superior directions. The center of mass was calculated

with respect to the C0-C1 joint.

	Mass (kg)	Center of Mass (m)			Moment of Inertia (kg.m2)			Moment of Inertia combined with the head (kg.m2)		
		X	Y	Z	Ixx	Iyy	Izz	Ixx	Iyy	Izz
US-style helmet	1.77	0.002	0.152	-0.006	0.017	0.028	0.022	0.092	0.088	0.10
European-style helmet	2.02	0.019	0.094	-0.008	0.023	0.03	0.031	0.076	0.068	0.090

498   Table 2: Peak flexion, extension, right bending, and left bending neck angles while holding

499   static neck postures and performing dynamic neck movements.

		Static neck posture		Dynamic neck movement	
Peak Flexion (°)	No Helmet	Male: 33.1 ± 5.22 Female: 38.0 ± 2.22	35.6 ± 1.01	Male: 36.3 ± 4.48 Female: 37.7 ± 4.05	35.62 ±1.02
	US-style Helmet	Male: 38.7 ± 1.32 Female: 39.3 ± 0.18	39.0 ± 0.21	Male: 37.8 ± 3.08 Female: 38.2 ± 1.71	38.04 ± 0.53
	European-style Helmet	Male: 37.3 ± 3.03 Female: 38.0 ± 3.92	37.7 ± 0.75	Male: 36.3 ± 4.48 Female: 37.7 ± 4.05	37.02 ± 0.92
Peak Extension (°)	No Helmet	Male: 45.6 ± 8.45 Female: 51.7 ± 6.60	48.7 ± 1.75	Male: 43.3 ± 10.8 Female: 47.3 ± 10.9	45.32 ± 2.34
	US-style Helmet	Male: 41.0 ± 11.2 Female: 46.0 ± 6.58	43.5 ± 2.02	Male: 39.2 ± 13.6 Female: 35.8 ± 8.98	37.47 ± 2.48
	European-style Helmet	Male: 44.8 ± 11.1 Female: 50.0 ± 6.44	47.4 ± 2.00	Male: 41.6 ± 11.4 Female: 44.6 ± 7.66	43.06 ± 2.08
Peak Right Bending (°)	No Helmet	Male: 24.6 ± 4.25 Female: 28.2 ± 3.74	26.4 ± 0.94	Male: 27.2 ± 4.02 Female: 29.3 ± 3.32	28.26 ± 0.82
	US-style Helmet	Male: 27.3 ± 2.30 Female: 29.0 ± 2.88	28.1 ± 0.58	Male: 27.7 ± 3.30 Female: 27.4 ± 3.19	27.58 ± 0.69
	European-style Helmet	Male: 26.8 ± 3.69 Female: 27.8 ± 3.07	27.3 ± 0.73	Male: 26.0 ± 3.33 Female: 27.0 ± 3.50	26.5 ± 0.74
Peak Left Bending (°)	No Helmet	Male: 24.8 ± 2.87 Female: 28.2 ± 3.41	26.5 ± 0.77	Male: 24.3 ± 7.49 Female: 28.2 ± 3.49	26.27 ± 1.31
	US-style Helmet	Male: 27.4 ± 2.85 Female: 30.2 ± 2.28	28.8 ± 0.63	Male: 27.4 ± 4.21 Female: 29.2 ± 2.84	28.28 ± 0.79
	European-style Helmet	Male: 27.2 ± 3.36 Female: 27.9 ± 3.52	27.5 ± 0.73	Male: 24.9 ± 6.10 Female: 27.6 ± 2.50	26.24 ± 1.04

Table 3: Flexion-extension and lateral bending full range of motion for each cervical intervertebral joint and the total neck (C0-T1). The total neck angle in Anderst et al. (2015) is defined as the angle between the head and the torso of the subjects.

| | | Cervical Intervertebral Joint | | | | | | | | |
		C0-C1	C1-C2	C2-C3	C3-C4	C4-C5	C5-C6	C6-C7	C7-T1	Neck Angle
Flexion-Extension	Anderst et al. (2015)	--	15.6 ± 5.8	12.7 ± 2.6	17.1 ± 3.3	19.5 ± 3.4	19.7 ± 3.7	15.8 ± 4.8	8.3 ± 3.5	119.0 ± 13.8
	Zhou et al. (2020)	6.3 ± 1.6º	13.7 ± 4.2º	9.5 ± 2.4º	14.9 ± 4.0º	19.4 ± 2.9º	17.1 ± 4.2º	12.3 ± 4.2º	4.1 ± 2.7º	94.5 ± 13.8º
	Cazzola et al. (2017)	--	--	8.21	12.4	16.6	16.6	12.4	7.34	--
	Nevins et al. (2014)	--	--	--	--	--	--	--	--	92.3 ± 14.9º
	No helmet	19.8± 1.9º	0.62 ± 0.06º	7.28 ± 1.32º	10.9 ± 1.98º	14.6 ± 2.64º	14.6 ± 2.64º	12.4 ± 2.25º	1.16 ± 0.21º	80.9 ± 11.4º
	US-Style helmet	20.5 ± 2.9º	0.64 ± 0.09º	6.62 ± 1.37º	9.93 ± 2.06º	13.2 ± 2.75º	13.2 ± 2.75º	11.2 ± 2.33º	1.05 ± 0.21º	75.5 ± 11.3º
	European-helmet style	20.3 ± 1.9º	0.64 ± 0.06º	7.19 ± 1.21º	10.8 ± 1.81º	14.3 ± 2.41º	14.3 ± 2.41º	12.2 ± 2.05º	1.14 ± 0.19º	80.1 ± 10.2º
Lateral Bending	Anderst et al. (2015)	--	--	--	14.3 ± 2.8	13.1 ± 3.2	12.3 ± 3.2	14.5 ± 3.9	5.6 ± 2.4	83.9 ± 14.5
	Zhou et al. (2020)	1.9 ± 1.5º	7.6 ± 2.7º	11.3 ± 4.5º	12.4 ± 3.1º	9.8 ± 2.4º	10.0 ± 2.3º	10.6 ± 3.3º	5.0 ± 2.8º	60.5 ± 14.4º
	Cazzola et al. (2017)	--	--	6.25	10.9	12.4	17.1	17.1	6.25	--
	Ishii et al. (2006)	1.9 ± 0.9º	1.6 ± 1.3º	3.7 ± 2.0º	3.5 ± 1.4º	3.3 ± 1.0º	4.3 ± 1.4º	5.7 ± 1.9º	4.1 ± 2.7º	--
	No helmet	5.26 ± 0.45º	0.18 ± 0.02º	5.67 ± 2.38º	13.2 ± 1.54º	13.2 ± 1.54º	9.56 ± 1.12º	8.36 ± 0.98º	1.06 ± 0.12º	54.2 ± 6.91º
	US-Style helmet	5.49 ± 0.35º	0.18 ± 0.02º	5.67 ± 2.38º	13.2 ± 1.54º	13.2 ± 1.54º	10.0 ± 0.49º	8.74 ± 0.43º	1.11 ± 0.05º	55.9 ± 4.68º
	European-helmet style	4.92 ± 0.55º	0.17 ± 0.02º	4.77 ± 2.73º	13.2 ± 1.14º	13.2 ± 1.14º	9.60 ± 0.83º	8.38 ± 0.72º	1.07 ± 0.09º	52.7 ± 5.68º

513   Table 4: Ratio between dependent and independent cervical intervertebral joint. The joint mobility of C6-

514   C7 to C2-C3 joints is dependent on the C7-T1 joint, while C0-C1 is dependent on C1-C2 joint.

| Degree of freedom (DoF) | Cervical Intervertebral Joints Ratio | | | | | |
| | C7-T1 | | | | | C1-C2 |
	C6-C7	C5-C6	C4-C5	C3-C4	C2-C3	C0-C1
Flexion-Extension	10.7	12.6	12.6	9.45	6.30	31.9
Lateral Bending	7.85	9.00	12.4	12.4	11.2	28.6