NeuroVelo: interpretable learning of temporal cellular dynamics from single-cell data

Idris Kouadri Boudjelthia[1,2], Salvatore Milite[3], Nour El Kazwini[1], Yuanhua Huang[4,5], Andrea Sottoriva[3], Guido Sanguinetti[1,6*]

[1*]Data Science, SISSA, Trieste, Italy.
[2]Abdus Salam International Centre for Theoretical Physics, Trieste, Italy.
[3]Computational Biology Research Centre, Human Technopole, Milan, Italy.
[4]School of Biomedical Sciences, University of Hong Kong, Hong Kong, China.
[5]Department of Statistics and Actuarial Science, University of Hong Kong, Hong Kong, China.
[6]School of Informatics, University of Edinburgh, Edinburgh, UK.

*Corresponding author(s). E-mail(s): gsanguin@sissa.it;
Contributing authors: ikouadri@sissa.it; salvatore.milite@fht.org;
nelkazwi@sissa.it; yuanhua@hku.hk; andrea.sottoriva@fht.org;

Abstract

Reconstructing temporal cellular dynamics from static single-cell transcriptomics remains a major challenge. Methods based on RNA velocity are useful, but interpreting their results to learn new biology remains difficult, and their predictive power is limited. Here we propose NeuroVelo, a method that couples learning of an optimal linear projection with non-linear Neural Ordinary Differential Equations. Unlike current methods, it uses dynamical systems theory to model biological processes over time, hence NeuroVelo can identify what genes and mechanisms drive the temporal cellular dynamics. We benchmark NeuroVelo against several state-of-the-art methods using single-cell datasets, demonstrating that NeuroVelo has high predictive power but is superior to competing methods in identifying the mechanisms that drive cellular dynamics over time. We also show how we can use this method to infer gene regulatory networks that drive cell fate directly from the data.

Keywords: single-cell transcriptomics, RNA velocity, neural networks, dynamical systems

1 Introduction

Single-cell transcriptomic (scRNA-seq) technologies have transformed our understanding of cellular diversity and heterogeneity[1], yet the destructive nature of the measurement process poses fundamental limits to their ability to capture temporal biological dynamics. Inferring dynamic information from static snapshots of scRNA-seq has been a major focus of computational research in the last decade. While most early efforts used advanced machine learning techniques to order cells along a pseudo-time trajectory [2–5], more recently the concept of RNA-velocity [6] offered a more mechanistic, biophysically grounded approach to solve the problem.

RNA-velocity leverages the surprisingly abundant pre-mRNA reads present in many scRNA-seq data sets to parametrise a simple first order kinetic model of RNA production and splicing. The relative abundance of spliced and unspliced reads in a given cell can then be used to deduce whether a gene is being transcriptionally activated or repressed. This idea enables researchers to capture a shadow of cellular dynamics even in static data sets. Recent years have witnessed a flourishing of RNA velocity approaches [7–12], permitting a simultaneous inference of pseudo-time and RNA velocity, and coupling the velocity equations with non-linear transformations that can better capture the complexity of the data. Nevertheless, both the biochemical foundations and the biological interpretation of RNA-velocity have been questioned [13, 14]. In particular, while RNA velocity enables an intuitive grasp of cellular dynamics at the level of individual cells, much less can be said at the level of the gene regulatory events which underpin such dynamics.

Here we propose NeuroVelo, a new approach which bridges the cellular and gene scales, simultaneously inferring temporal cellular dynamics and major gene interactions that drive such dynamics from scRNA-seq data. NeuroVelo is an approach grounded in dynamic system theory that combines ideas from Neural Ordinary Differential Equations (ODE) [15, 16] and RNA velocity in a physics-informed neural network architecture. We test extensively NeuroVelo on five scRNA-seq data sets and compare its performance against six recently published methods. On all data sets NeuroVelo achieved state of the art performance under a variety of metrics. Uniquely to our approach, we demonstrate how the interpretation of NeuroVelo results recovers regulatory networks and biological processes underpinning the dynamics in a natural and mathematically consistent way.

2 Results

2.1 The NeuroVelo model

Figure 1(a) illustrates the basic concept of NeuroVelo. scRNA-seq data consisting of both spliced and unspliced reads are encoded to a low dimensional space through two dimensionality reduction channels: one is a non-linear 1D encoder learning a pseudo-time coordinate associated with each cell, while the second is a linear projection to an *effective phase space* for the system. Cellular dynamics are defined through an autonomous system of differential equations parametrised by a neural network (a neural ODE). The resulting dynamics can be extremely rich. To further constrain it,

we impose the RNA velocity principle as a further penalty in the loss function in the spirit of physics-informed neural networks. Notice that this constraint is applied locally to each cell, thus removing limiting assumptions on global transcriptional dynamics which are often a major problem for RNA velocity approaches. Because the effective phase space is defined via a linear projection, the RNA velocity constraint can be applied *exactly* in the reduced dimensional space.

The choice of defining the effective phase space as a linear subspace of gene space, while it may limit the expressivity of the model, brings additional significant advantages: it avoids confounding the non-linear dynamics in the effective phase space with the effects of a non-linear projection, leading to more robust results (see Supp. Fig. 5). Most importantly, a major benefit of the linearity of the phase space is that standard techniques for the analysis of low-dimensional non-linear dynamical systems can be applied to the trained model. The resulting insights, thanks to the linearity of the encoder/ decoder model, can readily be translated in terms of genes. In practice, one may examine the Jacobian matrix of the neural ODE at any cell to identify the leading genes involved in the dynamics (by considering the leading eigenvectors of the Jacobian), and to define interaction networks

2.2 Datasets used, competing methods and evaluation metrics

To test NeuroVelo, we utilize a total of five recent scRNA-seq data sets:

- a data set of erythroid cells differentiation [17] during mouse gastrulation, comprising of 9815 cells quantifying a median of 2791 non-zero expressed genes per cell;
- a human bone marrow hematopoiesis data set [5], widely used in RNA-velocity studies, which quantifies a median of 1190 non-zero expressed genes in 5780 individual cells;
- a pancreatic endocrinogenesis [18] data set measuring a median of 2447 non-zero expressed genes in 3696 cells;
- two smaller CRISPR-based lineage barcoded mouse cancer data sets [19], measuring gene expression in 754 and 1082 cells at a higher depth (3490 and 2352 median non-zero expressed genes respectively.

To contextualise the performance of NeuroVelo, we analysed each data set with a number of recently proposed methods to reconstruct cellular dynamics. Perhaps the most widely used RNA-velocity method is scVelo [7], which remains the main benchmark. Very recently, multiple methods extended the RNA-velocity framework in several directions: we choose here UniTVelo [9], which focusses on improving the pseudotime estimation, and latentVelo [20] and deepVelo [8], which couples RNA-velocity with non-linear dimensionality reduction. We also use scTour [16], which does not use RNA-velocity but directly fits a neural ODE to the data, as a splicing-independent comparison. On the lineage barcoded data, we use PhyloVelo [19], a specialised method which exploits barcode information to obtain robust estimates of pseudotime. As performance metrics, we use the cross-boundary direction and the in-cluster coherence, two widely used metrics which summarise the consistency of the inferred dynamics with known biological dynamics (in data sets where cell-type annotation is present).

Fig. 1 (a) Schematic representation of the neuroVelo model: two autoencoders, a linear one to define the phase space, and a non-linear 1-D one to define pseudotime, are coupled in latent space through a non-linear neural ODE. RNA-velocity constraints are added as an additional penalty in the loss function. (b) Velocity field in the latent space and in the gene space on the mouse gastrulation dataset projected to thez UMAP-based embedding. (c) Histogram of Inferred pseudotime. (d) Comparison on the cross boundary direction. (e) Comparison on the inter-cluster coherence. (f) Gene network infered by NeuroVelo (left) and gene network structured using string-db (right)

For all methods, we report the best performance across several random restarts, when a default initialisation is not provided.

2.3 Reconstructing dynamical mechanisms from scRNA-seq data

On all three standard scRNA-seq data sets, most methods perform very well in terms of the cross-boundary direction and in-cluster coherence metrics, with generally neuroVelo, UniTVelo and latentVelo performing better than the other methods (see Table 1 for a comprehensive assessment of all methods on all data sets). Unlike other methods, however, neuroVelo provides additional insights in terms of potential network interactions underpinning the dynamics.

An analysis of the erythroid lineage in mouse gastrulation is shown in Figure 1 (b-f). NeuroVelo effectively captures the single-branched nature of the process, providing a good visualisation of the dynamics both in latent space and in gene space (Figure 1b), and a very good sequential ordering of the different cell types (Figure 1c). The quality of the inferred dynamics is further supported by Figure 1(d-e), which plots histograms of the evaluation metrics for each cell type, clearly showing neuroVelo to provide state-of-the art performance on every cell type. Figure 1f instead shows a network representation of the main interactions inferred by the model (left) and a literature-derived network obtained from the STRING database [21]. NeuroVelo recovered in a completely unsupervised way many of the most relevant genes in the erythroid lineage, and successfully predicts the densely connected network module involving the Hb genes.

A similar picture emerges from the analysis of the human bone marrow data set in Figure 2. NeuroVelo provides a good visualisation and a correct pseudotemporal ordering (Figure 2(a,c)), mirrored in state-of-the-art performance under both metrics (Figure 2 d-e). An enrichment analysis returns several highly enriched pathways related to immune cell proliferation and differentiation (Figure 2b). The predicted interactions between the most important genes are shown in Figure 2f, and once again shhow a very strong similarity with the STRINGDB network in Figure 2g. Interestingly, in this well annotated data set we can also linearise about different points in latent space, producing cell-type specific networks which highlight the varying temporal dynamics in the process (see Supplementary Movie 1).

As a third example of neuroVelo analyses on standard scRNA-seq, we examined the pancreatic endocrinogenesis data set. Results are shown in Figure 3; once again, neuroVelo provides an excellent visualisation (Figure 3a), and performs best or among the best for all cell types under the metrics considered (Figure 3c-d). An enrichment analysis (Figure 3 b,e) highlights highly relevant pathways connected with pancreas function with very high normalised enrichment score. An analysis of the interactions predicted again highlights some interactions already detailed in the literature (Figure 3 f-g), however it is noticeable that in this less well studied scenario fewer interactions can be derived from the literature, underscoring the potential for data-driven approaches like neuroVelo to uncover novel biological hypotheses.

Taken together, these results demonstrate that neuroVelo achieves state of the art or is competitive with the best RNA-velocity methods on a variety of data sets.

Fig. 2 (a) UMAP of NeuroVelo velocity field on the human bone marrow dataset, as well as (c) NeuroVelo pseudotime. (b) Gene set enrichment analysis of the gene influencing the dynamics. (d) Comparison on the cross boundary direction. (e) Comparison on the inter-cluster coherence. (f) and (g) Gene network infered by NeuroVelo (top) and gene network structured using string-db (bottom)

Additionally, neuroVelo is able to predict (possibly time-varying) interaction mechanisms which can explain the observed transcriptome dynamics, and which frequently recapitulate experimentally observed interactions in well characterised systems.

2.4 Inference of fitness in lineage barcoded data

As a second set of benchmark data, we consider two lineage barcoded data sets which were recently published by [22]. This technology combines scRNA-seq with barcoding to determine simultaneously the fitness of a cell population and its transcriptomic profile. [19] developed also a specialised "velocity" method called PhyloVelo, which does not use splicing information but relies on the barcoding to infer cellular dynamics.

Fig. 3 (a) UMAP of NeuroVelo velocity field on pancreatic endocrinogenesis dataset.(b) Gene set enrichment analysis of the ranked genes from NeuroVelo. (c) Comparison on the in-cluster coherence. (d) Comparison on the cross boundary direction. (e) Gene set enrichment analysis of insulin secretion pathway.

Results of the analyses on these two data sets are shown in Figure 4, which again show a very good visualisation on both data sets (panels a-b and d-e). To evaluate quantitatively the results, we focus on correlating the inferred pseudotime with the fitness signature provided by the barcoding experiments. Panel c shows the scatter-plot of fitness values versus inferred pseudotime for one of the data sets, while panel f shows a comparison of all methods (including PhyloVelo) in terms of Spearman correlation with fitness. This shows that most methods perform extremely well (in fact, comparably to PhyloVelo, which explicitly uses the barcoding information), with the exception of scVelo and DeepVelo, this latter method only on one of the data sets.

This analysis demonstrates that utilising splicing information can provide an effective way to reconstruct cellular ordering which validates against barcoding information. Once again, neuroVelo emerges as one of the strongest performers also on this task.

3 Discussion

NeuroVelo innovates over other RNA-velocity methods by bringing a new dimension of functional interpretability: while standard methods focus on defining a cell-level velocity field, depicting the evolution of individual cells, neuroVelo provides a data-driven mechanistic model which can be interpreted in terms of (time-varying) regulatory networks. Results on all data set demonstrated not only that neuroVelo is among the best

Fig. 4 (a) UMAP of NeuroVelo infered pseudotime and (b) NeuroVelo velocity field on the sample **3726_NT_T1** of the mouse cancer data set, as well as (c) scatterplot of the neuroVelo pseudotime against the fitness signature (inferred from barcoding information). (d) UMAP of NeuroVelo infered pseudotime and (e) NeuroVelo velocity field on the sample **3435_NT_T1** of the mouse cancer data set. (f) Comparison on pseudotime and fitness signature spearman correlation for 2 different samples.

performing tools in terms of standard RNA-velocity metrics, but also that the mechanisms it captures are biologically meaningful and extend known interactions from the literature.

Methodologically, neuroVelo attempts to strike a balance between complexity and interpretability. It does so by limiting its non-linearity to the dynamical system in the latent space, which enables both a very direct interpretation in terms of genes and the imposition of the RNA-velocity constraint as physics-informed loss term. An additional benefit of the relative simplicity of neuroVelo is its robustness.

Defining a semi-mechanistic model for single-cell dynamics opens a number of exciting opportunities to expand the scope of neuroVelo. First of all, principled ways to incorporate known mechanisms might be devised using ideas from Bayesian statistics. Secondly, other data modalities, such as chromatin accessibility, could be incorporated when available, thus providing a mechanistic extension to current methods for multi-omics analysis [23]-[24]. Finally, different types of underlying dynamics might be considered, for example to accomodate mutational events which might lead to non-smooth dynamics, of to incorporate spatial correlation in spatial transcriptomic data.

References

[1] Regev, A., Teichmann, S.A., Lander, E.S., Amit, I., Benoist, C., Birney, E., Bodenmiller, B., Campbell, P., Carninci, P., Clatworthy, M., *et al.*: The human cell atlas. elife **6**, 27041 (2017)

[2] Trapnell, C., Cacchiarelli, D., Grimsby, J., Pokharel, P., Li, S., Morse, M., Lennon, N.J., Livak, K.J., Mikkelsen, T.S., Rinn, J.L.: The dynamics and regulators of cell fate decisions are revealed by pseudotemporal ordering of single cells. Nature biotechnology **32**(4), 381–386 (2014)

[3] Haghverdi, L., Büttner, M., Wolf, F.A., Buettner, F., Theis, F.J.: Diffusion pseu- dotime robustly reconstructs lineage branching. Nature methods **13**(10), 845–848 (2016)

[4] Campbell, K.R., Yau, C.: Uncovering pseudotemporal trajectories with covariates from single cell and bulk expression data. Nature communications **9**(1), 2442 (2018)

[5] Setty, M., Kiseliovas, V., Levine, J., Gayoso, A., Mazutis, L., Pe'Er, D.: Char- acterization of cell fate probabilities in single-cell data with palantir. Nature biotechnology **37**(4), 451–460 (2019)

[6] La Manno, G., Soldatov, R., Zeisel, A., Braun, E., Hochgerner, H., Petukhov, V., Lidschreiber, K., Kastriti, M.E., Lönnerberg, P., Furlan, A., *et al.*: Rna velocity of single cells. Nature **560**(7719), 494–498 (2018)

[7] Bergen, V., Lange, M., Peidli, S., Wolf, F.A., Theis, F.J.: Generalizing rna velocity to transient cell states through dynamical modeling. Nature biotechnology **38**(12), 1408–1414 (2020)

[8] Chen, Z., King, W.C., Hwang, A., Gerstein, M., Zhang, J.: Deepvelo: Single- cell transcriptomic deep velocity field learning with neural ordinary differential equations. Science Advances **8**(48), 3745 (2022)

[9] Gao, M., Qiao, C., Huang, Y.: Unitvelo: temporally unified rna velocity reinforces single-cell trajectory inference. Nature Communications **13**(1), 6586 (2022)

[10] Gayoso, A., Weiler, P., Lotfollahi, M., Klein, D., Hong, J., Streets, A., Theis, F.J., Yosef, N.: Deep generative modeling of transcriptional dynamics for rna velocity analysis in single cells. Nature Methods, 1–10 (2023)

[11] Li, S., Zhang, P., Chen, W., Ye, L., Brannan, K.W., Le, N.-T., Abe, J.-i., Cooke, J.P., Wang, G.: A relay velocity model infers cell-dependent rna velocity. Nature biotechnology, 1–10 (2023)

[12] Qiao, C., Huang, Y.: Representation learning of rna velocity reveals robust

cell transitions. Proceedings of the National Academy of Sciences **118**(49), 2105859118 (2021)

[13] Barile, M., Imaz-Rosshandler, I., Inzani, I., Ghazanfar, S., Nichols, J., Marioni, J.C., Guibentif, C., Göttgens, B.: Coordinated changes in gene expression kinetics underlie both mouse and human erythroid maturation. Genome biology **22**(1), 1–22 (2021)

[14] Gorin, G., Fang, M., Chari, T., Pachter, L.: Rna velocity unraveled. PLOS Computational Biology **18**(9), 1010492 (2022)

[15] Chen, R.T., Rubanova, Y., Bettencourt, J., Duvenaud, D.K.: Neural ordinary differential equations. Advances in neural information processing systems **31** (2018)

[16] Li, Q.: sctour: a deep learning architecture for robust inference and accurate prediction of cellular dynamics. Genome Biology **24**(1), 1–33 (2023)

[17] Pijuan-Sala, B., Griffiths, J.A., Guibentif, C., Hiscock, T.W., Jawaid, W., Calero-Nieto, F.J., Mulas, C., Ibarra-Soria, X., Tyser, R.C.V., Ho, D.L.L., Reik, W., Srinivas, S., Simons, B.D., Nichols, J., Marioni, J.C., Göttgens, B.: A single-cell molecular map of mouse gastrulation and early organogenesis. Nature **566**(7745), 490–495 (2019) https://doi.org/10.1038/s41586-019-0933-9

[18] Bastidas-Ponce, A., Tritschler, S., Dony, L., Scheibner, K., Tarquis-Medina, M., Salinno, C., Schirge, S., Burtscher, I., Böttcher, A., Theis, F.J., Lickert, H., Bakhti, M.: Comprehensive single cell mrna profiling reveals a detailed roadmap for pancreatic endocrinogenesis. Development **146**(12) (2019) https://doi.org/10. 1242/dev.173849

[19] Wang, K., Hou, L., Wang, X., Zhai, X., Lu, Z., Zi, Z., Zhai, W., He, X., Curtis, C., Zhou, D., et al.: Phylovelo enhances transcriptomic velocity field mapping using monotonically expressed genes. Nature Biotechnology, 1–12 (2023)

[20] Farrell, S., Mani, M., Goyal, S.: Inferring single-cell transcriptomic dynamics with structured latent gene expression dynamics. Cell Reports Methods **3**(9), 100581 (2023) https://doi.org/10.1016/j.crmeth.2023.100581

[21] Szklarczyk, D., Gable, A.L., Nastou, K.C., Lyon, D., Kirsch, R., Pyysalo, S., Doncheva, N.T., Legeay, M., Fang, T., Bork, P., Jensen, L.J., Mering, C.: The string database in 2021: customizable protein–protein networks, and functional characterization of user-uploaded gene/measurement sets. Nucleic Acids Research **49**(D1), 605–612 (2020) https://doi.org/10.1093/nar/gkaa1074

[22] Yang, D., Jones, M.G., Naranjo, S., Rideout, W.M., Min, K.H.J., Ho, R., Wu, W., Replogle, J.M., Page, J.L., Quinn, J.J., et al.: Lineage tracing reveals the phylodynamics, plasticity, and paths of tumor evolution. Cell **185**(11), 1905–1923

(2022)

[23] Li, C., Virgilio, M.C., Collins, K.L., Welch, J.D.: Multi-omic single-cell velocity models epigenome–transcriptome interactions and improves cell fate prediction. Nature Biotechnology **41**(3), 387–398 (2022) https://doi.org/10.1038/s41587-022-01476-y

[24] Kazwini, N.E., Sanguinetti, G.: Share-topic: Bayesian interpretable modeling of single-cell multi-omic data. Genome Biology **25**(1) (2024) https://doi.org/10.1186/s13059-024-03180-3

Methods

Model architecture

NeuroVelo is a neural network architecture that consists of a linear auto-encoder and neural ODEs architecture in the latent representation of the data. The main idea of NeuroVelo is to construct cell dynamics from scRNA-seq data in the latent space.

We used spliced and unspliced reads of scRNA-seq data with g number of genes, and embedded them using the same encoder function $E : \mathbb{R}^g \rightarrow \mathbb{R}^l$, into a latent space $z = (z_s, z_u)$ of dimension l. This step is mainly for dimensionality reduction and feature extraction of the highly dimensional gene space to a much smaller latent space (50 by default).

Part of the encoder is also used to estimate the pseudotime of the cells. Both pseudotime and latent representation of the cell are used to train nonlinear neural ODEs.

Once we project the cells into a lower-dimensional space, we use a set of neural ODEs to describe the cellular dynamics in this latent space

$$\frac{dz_s^{(d)}(t)}{dt} = f^{(d)}(z_s^{(d)}(t), t), \tag{1}$$

where $f^{(d)} : \mathbb{R}^l \rightarrow \mathbb{R}^l$ is a two layers neural network with nonlinear activation function, this neural ODE describes the dynamics of cells from particular sample d. Using the nonlinear ODEs in the latent space helps to capture the essential and complex dynamics of cells in this space.

Notice that, since we are learning both the pseudotime and the generator function of the dynamics (the f function), one could reverse simultaneously the pseudotime and the sign of f without altering the trajectories. This ambiguity may be resolved either by prior knowledge or by inverting both signs *a posteriori*.

The encoder latent representation is decoded with a linear decoder network $D : \mathbb{R}^l \rightarrow \mathbb{R}^g$ to create a reconstruction of the original spliced and unspliced inputs ($\hat{X}_s$, $\hat{X}_u$), learning another function that maps from latent space to gene space.

Model training

The tasks learnt by neural networks are based on what loss function the network is optimizing. To ensure that the cellular dynamics learned by the network have biological meaning, we propose a loss function that puts biophysical constraints on the data and does not require any parameter fine-tuning.

The first part of the loss is the usual mean squared error (MSE) of autoencoders network, we want our spliced and unspliced inputs to match their reconstructed counterparts from the decoder and so the first loss part is a sum of MSE of spliced and unspliced reads.

The second part of the loss is what puts a biophysical constraint on the neural ODEs in the same fashion of physics-informed neural networks. The idea is to make the derivative of latent spliced reads $\dot{z}_s^d(t)$ align with the splicing dynamics from the RNA velocity but in latent representation ($e^\beta z_u - e^\gamma z_s$), There is an exponential of β

(and γ) because they are analogy of splicing and degradation rate and they must be positive.

The final loss is written as follows:

$$
\begin{aligned}
L =& \text{MSE}(X_s, \hat{X}_s) + \text{MSE}(X_u, \hat{X}_u) + \sum_{d=1}^{D} \\
& \text{MSE}\left(f^{(d)}(\boldsymbol{z}_s^{(d)}(t), t), e^{\beta} \boldsymbol{z}_u^{(d)} - e^{\gamma} \boldsymbol{z}_s^{(d)}\right) + \text{MSE}\left(z_s(t), z_s\right)
\end{aligned}
\tag{2}
$$

Where the sum over d is the sum over specific group of cells or treatments. $\dot{z}(t)_s^d$ is the function that describes the splicing dynamics of a sample d in the latent space. z_s^d and z_u^d are the projected spliced and unspliced reads of the sample d. Notice that the third term in the loss enforces the RNA-velocity constraint, so that the role of the transcription rate is modelled flexibly and learnt directly from the data. The last term in the loss aim to align the latent dynamics with the latent representation, due to the linearity of the model, this is equivalent to MSE $\left(\hat{X}_s(t), X_s\right)$ where $\hat{X}_s(t)$ is the decoded latent dynamics $z_s(t)$.

In this way, we are able to investigate complex and specific cellular dynamics by learning splicing dynamics constrained nonlinear ODEs in a reduced space and without the need to fine tune parameters on the level of the loss function as well.

Interpretation

Genes ranking

Any dynamical process is generally governed by a nonlinear ODE, we can understand the behavior of a system by linearizing the ODE around a given point which is in this case an average cell or group of cells, the linearized system is:

$$
\dot{\boldsymbol{z}}_s(t) = \mathbf{J}\boldsymbol{z}_s(t), \quad \mathbf{J} = \begin{bmatrix} \frac{\partial f_1}{\partial z_1} & \cdots & \frac{\partial f_1}{\partial z_l} \\ \vdots & \ddots & \vdots \\ \frac{\partial f_l}{\partial z_1} & \cdots & \frac{\partial f_l}{\partial z_l} \end{bmatrix}
\tag{3}
$$

We perform *eigenanalysis* on the Jacobian matrix. The eigenvalues give the important directions of the correspondent eigenvectors in the latent space, then we use the decoder function to map these important directions in the latent space to the gene space. The output of this decoder is a list of ranked genes based on their importance in a particular direction.

The main issues related to using neural networks are interpretability and robustness, the former is not a problem because NeuroVelo uses both linear embedding and projection, thus the interpretation of the latent space into the gene space is straightforward. The robustness part is more of a concern because a different initialization leads to a different local minima which makes biological interpretation uncertain. Here we propose a geometrical and statistical approach that gives a solid gene list by using many trained models.

The first step is to find the set of eigenvectors from other models that align the most with an eigenvector of a current model $\vec{v}_i^{(m)}$, the alignment is based on the absolute value of the cosine similarity. This set of the most aligned eigenvectors is given by the following equation:

$$U\left(\vec{v}_i^{(m)}\right) = \left\{ \max_j \left| S_c\left(\vec{v}_i^{(m)}, \vec{v}_j^{(m')}\right)\right|, \text{for } m' \neq m \right\}$$

where S_c is the cosine similarity function and m' is the index of the trained model.

We take the ranked genes of the aligned eigenvectors, and we average the ranks gene-wise. The output is a list of genes ranked based on the average rank across the aligned eigenvectors from different trained models. This indicates that the genes that are at the top of the list hold significant importance for the dynamics learned by various models and vice versa. A set of different analyses can be performed on these average-ranked genes for validation.

Genes network

As shown previously, The non-linear latent dynamics are approximated by the linearized system $\dot{\boldsymbol{z}}_s(t) = \mathbf{J}\boldsymbol{z}_s(t)$. By mapping the latent representation to the gene space, we can show that this system can be written as:

$$\dot{\boldsymbol{X}}_s(t) = \hat{\mathbf{J}}\boldsymbol{X}_s(t) + \mathbf{C}$$

where $\mathbf{C}$ is a bias term that does not depend on X. We call $\hat{\mathbf{J}} = \mathbf{W_d}\mathbf{J}\mathbf{W_e}$ the decoded Jacobian, $\mathbf{W_d}$ and $\mathbf{W_e}$ are the weight of the decoder and encoder networks respectively.

$\hat{\mathbf{J}}$ Tell us which genes influence the expression of other genes and it is used to build the genes network.

Parameters selection

RNA velocity estimation can be very sensitive to the processing done such as constructing kNN graph as shown in [14] to use "moments" instead of raw reads. In addition, using neural network to estimate RNA velocity increases the number of parameter combinations, such as learning rate, optimizer, batch size and network size (dimensions). Moreover, for the same set of parameters, different initializations can be stuck in different local minima, leading to convergence in any case, but to different velocity estimates.

In address this issue, we propose a metric, *Velocity Alignment* which uses the same cosine similarity measure as *ICCoh* but is applied to velocities estimated using models trained with different random seeds.

$$\text{VA}^{(n,m)} = \frac{1}{N}\mathbf{diag}\left(S_c(\mathbf{V}^{(n)}, \mathbf{V}^{(m)})\right)$$

$V^{(n)}$ and $V^{(m)}$ are RNA velocity estimated from different trained model (n) and (m) and N is the total number of cells. The **diag** takes the diagonal elements of the

cosine similarity measure, meaning that we are measuring how the same cell velocity from 2 different models is aligned.

The idea is to select the set of parameters with the highest cosine similarity. This approach ensures that even if the model converges to a local minimum, the velocity estimated from different seeds is aligned.

It is important to point that this metric should be computed for models with different random initializations but for the same set of other parameters.

Implementation

NeuroVelo is implemented in Python machine learning framework `PyTorch 2.0` and using `torchdiffeq` package for ODE solvers in PyTorch.
Velocity field visualizations are done with `scvelo`
except for the mouse lung cancer dataset it was done using `PhyloVelo` package. Gene networks visualizations are done with `networkx`
Gene set enrichment analysis is done with "*GSEApy: Gene Set Enrichment Analysis in Python*" `gseapy`. Passing a dataframe of genes and their average rank as a ranking metric to `prerank` function. The enrichment analysis plots are all generated by the same package.
The metrics *ICCoh* and *CBDir* are borrowed from [12]

Datasets

Mouse erythroid

The human bone marrow dataset is downloaded from ScVelo package `scv.datasets.gastrulation_erythroid()`. The dataset is already processed and contains spliced and unspliced counts. We picked the top 2000 highly variables gene and we used counts training.

Mouse lung cancer

This dataset is CRISPR/Cas9-based lineage tracing dataset from a genetically-engineered mouse model (GEMM) of lung adenocarcinoma. We used it to compare NeuroVelo to PhyloVelo, mainly using two tumors (3726_NT_T1 and 3435_NT_T1).

We requested the spliced/unspliced reads from [19]. We picked the top 2000 highly variables gene and we used moments instead of counts for training.

Human bone marrow hematopoiesis

The human bone marrow dataset is downloaded from ScVelo package `scv.datasets.bonemarrow()`. The bone marrow is the primary site of new blood cell production or haematopoiesis. It is composed of hematopoietic cells, marrow adipose tissue, and supportive stromal cells. The dataset is already processed and contains spliced and unspliced counts. We picked the top 2000 highly variables gene and we used moments instead of counts for training.

	Erythroid Mouse		3435_NT_T1	3726_NT_T1
	Mean CBDir	Mean ICCoh	Spearman correlation	Spearman correlation
NeuroVelo	0.8304	0.9999	0.88	0.86
UniTVelo	0.832575	0.98776	0.88	0.77
ScTour	0.801175	0.38038	0.90	0.84
LatentVelo	0.84415	0.97412	0.92	0.88
DeepVelo	0.41515	0.92614	0.45	0.85
ScVelo	-0.3519	0.83798	0.12	-0.043
PhyloVelo	-	-	0.83	0.86

	Human Bone Marrow		Pancreatic endocrinogenesis	
	Mean CBDir	Mean ICCoh	Mean CBDir	Mean ICCoh
NeuroVelo	0.81943	0.996017	0.603533	0.9997
UniTVelo	0.804933	0.97743	0.614	0.9866
ScTour	0.786033	0.47849	0.5898	0.67406
LatentVelo	0.7664	0.98141	0.5854	0.9763
DeepVelo	-0.804933	0.93207	0.5674	0.8854
ScVelo	-0.839467	0.91819	0.6131	0.8698
PhyloVelo	-	-	-	-

Table 1 Metrics table for different methods and datasets. For method that allows different random seeds (NeuroVelo, ScTour and LatentVelo) the table shpws the best performance of running 10 seeds. More on stability of velocity is shown in figure 5

Pancreatic endocrinogenesis

Pancreatic endocrinogenesis dataset is downloaded from ScVelo package `scv.datasets.pancreas()`. Endocrine cells originate from endocrine progenitors found within the pancreatic epithelium. These progenitors differentiate into four primary cell types: α-cells that produce glucagon, β-cells that produce insulin, δ-cells that produce somatostatin, and ε-cells that produce ghrelin. The dataset is already processed and contains spliced and unspliced counts. We picked the top 2000 highly variables gene and we used counts training.

Fig. 5 Comparison on velocity alignment, each point is the velocity alignment of a pair of trained models.