GEfetch2R: fetching single-cell/bulk RNA-seq data from public repositories to R and benchmarking the subsequent format conversion tools

Yabing Song[1], Jianbin Wang[2,*], Jiaxin Gao[1,*]

[1]State Key Laboratory of Microbial Diversity and Innovative Utilization, Institute of
Microbiology, Chinese Academy of Sciences, Beijing, China

[2]School of Life Sciences, Tsinghua University, Beijing, China.

*Address correspondence to Jianbin Wang, jianbinwang@tsinghua.edu.cn and Jiaxin
Gao, gaojx@im.ac.cn

Key words: single-cell/bulk RNA-seq, data download, format conversion, tool
benchmark, software

Abstract

Background

Downloading and reanalyzing the existing single-cell RNA sequencing (scRNA-seq) data provides an efficient choice to gain clues and new insights. However, no tool can fetch the diverse scRNA-seq data types (raw data, count matrix, and processed object) distributed in various repositories, process and load the downloaded data to R, convert formats between scRNA-seq objects, and benchmark the format conversion tools.

Findings

Here, we present *GEfetch2R*, an R package with Docker image to (i) download diverse scRNA-seq data types, including raw data (SRA and ENA), count matrices (GEO, UCSC Cell Browser, and PanglaoDB), and processed objects (Zenodo, CELLxGENE, and HCA); (ii) process the downloaded data, load output/downloaded count matrices and annotations to R (*SeuratObject*/*DESeqDataSet*), filter the *SeuratObject* based on cell metadata and genes, and merge multiple *SeuratObjects* if applicable; (iii) convert formats between the widely used scRNA-seq objects, including *SeuratObject*, *AnnData*, *SingleCellExperiment*, *CellDataSet*/*cell_data_set*, and *loom*, and benchmark format conversion tools in terms of information kept, usability, running time, and scalability to guide the tool selection. Furthermore, *GEfetch2R* can also download, process, and load bulk RNA-seq raw data (SRA and ENA) and count matrices (GEO) to R (*DESeqDataSet*).

Conclusions

GEfetch2R is an R package dedicated to facilitating researchers to access and explore the existing gene expression data from various public repositories. It can function as a data downloader (supports all three scRNA-seq and two bulk RNA-seq data types), a data processor (processes and loads the output/downloaded count matrices and annotations to R), and an object format converter (between the widely used scRNA-seq objects).

Introduction

In recent years, single-cell RNA sequencing (scRNA-seq) has emerged as a powerful tool to reveal cellular heterogeneity and fundamental characteristics of gene expression [1]. As a result, thousands of scRNA-seq datasets have been generated and uploaded to public repositories. Downloading and reanalyzing the existing scRNA-seq data provides an efficient choice to gain clues and new insights. For example, rare cell type identification [2] and pan-cancer scRNA-seq analysis [3] usually require a huge number of samples and cells, which is extremely expensive and time-consuming if not integrating the available scRNA-seq datasets. As well, exploring existing relevant scRNA-seq data can accelerate the progress of one's own research.

The existing scRNA-seq data are in three types: raw data (*sra*/*fastq*/*bam*), count matrix, and processed object (e.g. *rds* and *h5ad*), which are stored in different repositories. The raw data are mainly stored in Sequence Read Archive (SRA) [4] and European Nucleotide Archive (ENA) [5], the count matrices can be found in Gene Expression Omnibus (GEO) [6] and some scRNA-seq databases (e.g. UCSC Cell Browser [7] and PanglaoDB [8]), and a majority of processed objects are provided by Zenodo [9], Human Cell Atlas (HCA) [10], and CELLxGENE [11]. The diversity of data types and their distribution in specialized repositories make scRNA-seq data download difficult. Secondly, as many scRNA-seq protocols and preprocessing tools have been developed, the data they generated and stored differ. Representatively, there are differences between 10x Genomics (10x) [12] and Smart-seq2 [13] in terms of

sequencing reads and output count matrix form. How to process and load these

different types of downloaded files into a unified object that can be analyzed matter.

Thirdly, the formats and programming languages of downloaded processed objects are

varied due to the prosperity in scRNA-seq analysis tools, such as *SeuratObject*

(*Seurat*, R) [14], *AnnData* (*Scanpy*, Python) [15], *CellDataSet*/*cell_data_set*

(*Monocle2/3*, R) [16, 17], and *SingleCellExperiment* (*scater*, R) [18]. Diverse object

formats and programming languages hinder the integration of scRNA-seq data and the

interoperability between different analysis tools, thus the object format conversion is

vital.

Currently available tools mainly focus on downloading raw data (SRA and ENA) and

count matrices (GEO) (Table 1). *ffq* [19] is designed to fetch sample metadata

including the download links, therefore third-party tools are needed to perform

downloading. *GEOfastq* [20], *SRA-Toolkit* [21], *enaBrowserTools* [22], *fastq-dl* [23],

pysradb [24], and *GEOfetch* [25] supports downloading raw data from SRA and/or

ENA. Among them, *GEOfastq*, *fastq-dl*, and *GEOfetch* can only download *fastq*,

sra/*fastq*, and *sra* files respectively, and *GEOfetch* supports splitting *sra* into

fastq/*bam* files. *GEOfastq*, *enaBrowserTools*, *fastq-dl* (version <1.2.0), and *pysradb*

support downloading data via Aspera, while *fastq-dl* and *pysradb* parallelize the

download process. *pysradb*, *GEOfetch*, and *GEOquery* [26] are able to download the

supplementary files from GEO, and *GEOquery* can extract the count matrix from

ExpressionSet. *rPanglaoDB* [27] can be used to download scRNA-seq count matrices

and annotations from PanglaoDB, which only contains datasets originating from

human and mouse, has relatively small sample numbers, and is no longer maintained.

The above generalized tools, except *rPanglaoDB*, support downloading raw data

and/or count matrices from limited databases. And this download is regardless of

whether the data are from scRNA-seq or bulk RNA-seq, thus lacking support for

unique characteristics of scRNA-seq data (such as 10x-style *fastq* files and *bam* files

with custom tags). *rPanglaoDB* specializes in downloading scRNA-seq count

matrices and annotations, but the support is quite insufficient. As for format

conversion, many tools have been developed for the same conversion stream. From

SeuratObject to *AnnData* (Seu2AD), available tools are *SeuratDisk*, *sceasy*, and

scDIOR, while the above tools and *schard* are suitable for the reverse stream

(AD2Seu). From *SingleCellExperiment* to *AnnData* (SCE2AD), available tools are

sceasy, *scDIOR*, and *zellkonverter*, while *scDIOR*, *zellkonverter*, and *schard* are

suitable for the reverse stream (AD2SCE). Multiple available tools for the same

stream confused the format conversion process, and currently lacking a benchmark of

format conversion tools to guide the tool selection. Besides, no tool can cover all the

conversion streams between the widely used scRNA-seq objects.

To address the above issues, we present *GEfetch2R*, an R package to (i) fetch

scRNA-seq/bulk RNA-seq raw data, count matrices, and processed objects from

diverse public repositories; (ii) process the downloaded data, load the count matrices

and annotations to R (*SeuratObject*/*DESeqDataSet*), filter the *SeuratObject* based on

cell metadata and genes, and merge multiple *SeuratObjects* if applicable; (iii) convert

formats between the widely used scRNA-seq objects, and benchmark format

conversion tools to guide the tool selection.

Materials and Methods

Download, process and load raw data

With GEO accessions as input, *GEfetch2R* can download raw data (*sra*/*fastq*/*bam*)

from SRA and ENA (Supplementary Fig. S1). Firstly, *GEfetch2R* extracts all sample

metadata under given GEO accessions, users can skip this step and provide a data

frame containing interested samples. The output sample metadata is used as input for

subsequent raw data download. For *sra* files, *GEfetch2R* uses *prefetch* command to

download them from SRA, and uses *ascp* and *download.file* command in parallel to

download them from ENA.

For *fastq* files in SRA, *GEfetch2R* uses *parallel-fastq-dump* (parallel), *fasterq-dump*

(parallel), and *fastq-dump* commands to split the downloaded *sra* files into *fastq* files.

If the data are from 10x, the *--split-files* parameter is added and at least two *fastq* files

are generated. *GEfetch2R* automatically distinguishes read1 and read2 based on read

length, and renames them according to the *CellRanger* required format. As for data

from other scRNA-seq protocols or bulk RNA-seq, the *--split-3* parameter is used. For

fastq files in ENA, *GEfetch2R* supports splitting the downloaded *sra* files as above,

alternatively, if there are *fastq* files in ENA, *GEfetch2R* uses *ascp* and *download.file*

command in parallel to download them directly.

For *bam* files in SRA, if they are from 10x, *GEfetch2R* uses *prefetch* command with

--type TenX parameter to download the original uploaded *bam* files directly to keep

the custom tags required to reconstruct the original *fastq* files. As for *bam* files from

other scRNA-seq protocols or bulk RNA-seq, *GEfetch2R* uses *sam-dump* commands

to split the downloaded *sra* files into *bam* files. For *bam* files in ENA, *GEfetch2R*

uses *ascp* and *download.file* command in parallel to download them directly. If *fastq*

files are needed, *GEfetch2R* uses *bamtofastq* command developed by 10x to convert

the downloaded 10x-generated *bam* files to *fastq* files, and uses *samtools* [28]

command to convert the downloaded *bam* files generated by other scRNA-seq

protocols or bulk RNA-seq to *fastq* files.

With prepared *fastq* files, if they are from 10x, *GEfetch2R* uses *CellRanger* to

perform read alignment and counting with default parameters. Users can pass custom

parameters to *st.paras* parameter in *Fastq2R* function. The output count matrix is then

loaded to R using *Seurat*. If multiple count matrices are available, *GEfetch2R* merges

multiple *SeuratObjects* if applicable. As for *fastq* files from Smart-seq2 or bulk

RNA-seq, *GEfetch2R* uses *STAR* to perform read alignment and counting with

--quantMode GeneCounts parameter. Users can also pass custom parameters to

st.paras parameter in *Fastq2R* function. The output count matrix is then loaded to R

using *DESeq2*.

Download, process and load count matrices and annotations

As in Supplementary Fig. S1, *GEfetch2R* first extracts detailed dataset metadata, such

as description, source/tissue, organism, protocol, and related publication. Users can

filter datasets based on these attributes, and the filtered metadata is used as

subsequent input. When fetching count matrices from GEO, *GEfetch2R* tries to

extract the count matrix from *ExpressionSet* first. If the extracted count matrix is

empty or contains non-integer values, *GEfetch2R* generates the count matrix from

supplementary files. For supplementary files in *CellRanger* output format, *GEfetch2R*

automatically categorizes the downloaded files based on sample names. For

supplementary files composed of the count matrix of every single cell/bulk sample,

GEfetch2R creates a count matrix containing all cells/samples. Users can also add

down.supp = TRUE parameter in *ParseGEO* function to generate the count matrix

directly from supplementary files. For UCSC Cell Browser, *GEfetch2R* accesses

count matrices online instead of downloading them to save time and disk usage. In

addition to count matrices, UCSC Cell Browser contains diverse annotations, such as

cell type annotation, cell type composition, and dimensionality reduction coordinates,

GEfetch2R supports extracting all these annotations. For PanglaoDB, similar to

UCSC Cell Browser, it also contains various annotations (e.g. cell type annotation and

cell type composition), *GEfetch2R* uses *rPanglaoDB* to extract count matrices and

corresponding annotations.

With available scRNA-seq count matrices and various annotations, *GEfetch2R* loads

the count matrices to R using *Seurat*, adds available annotations to the *SeuratObjects*

(UCSC Cell Browser and PanglaoDB), filters the *SeuratObjects* based on cell

metadata and genes (UCSC Cell Browser and PanglaoDB), and merges *SeuratObjects*

if applicable. For the bulk RNA-seq count matrix containing all samples, *GEfetch2R*

loads it to R using *DESeq2* (GEO).

Download and load processed objects

Similar to downloading count matrices, *GEfetch2R* first extracts detailed dataset

metadata (dataset description in Zenodo) (Supplementary Fig. S1). Users can select

the dataset of interest based on the dataset information and use it as input for

subsequent processed object download. For processed objects in Zenodo, with

provided DOIs or selected dataset description table, and the file extensions (e.g. *rds*,

rdata, *loom*, and *h5ad*), *GEfetch2R* downloads the corresponding processed objects.

For processed objects in CELLxGENE, *GEfetch2R* provides two methods to

download them. *GEfetch2R* uses *cellxgene-census* [29] developed by the

CELLxGENE team to efficiently access the cloud-hosted Census single-cell data and

filter the data based on cell metadata and genes. However, some newly uploaded data

that can be explored on the web page may be missing due to the delay of cloud

hosting (e.g. the stable Census release is 2025-01-30 when the current date is

2025-02-26). To overcome this, *GEfetch2R* takes advantage of CZ CELLxGENE

Discover API to get the download links of processed objects (*rds* and *h5ad* files)

directly, the same as clicking the download button on the web page. For processed

objects in HCA, with filtered metadata and provided file extensions (e.g. *rdata*, *rds*,

h5, *h5ad*, *loom*, and *tsv*), *GEfetch2R* downloads the corresponding processed objects.

With processed objects in *rds* format, *GEfetch2R* loads them (*SeuratObjects*) to R,

filters the *SeuratObjects* based on cell metadata and genes (CELLxGENE), and

merges *SeuratObjects* if applicable.

Benchmark format conversion tools

To inspect the information kept after format conversion, we used the pbmc3k dataset

analyzed by the standard *Seurat* and *Scanpy* workflow. The *SingleCellExperiment*

used to inspect the information kept from *SingleCellExperiment* to *AnnData* was

generated by *zellkonverter* (convert *AnnData* to *SingleCellExperiment*). The detailed

code and output used to evaluate the retained information are provided in

Supplementary Note.

To examine the running time and scalability of format conversion tools, we used

GEfetch2R to select and download five processed objects (both *rds* and *h5ad* files)

with more than one million cells from CELLxGENE (Supplementary Table S1), then

subsampled them to varied cell numbers: 1.2 million (1.2M, two objects), 1 million

(1M), 800,000 (800K), 600,000 (600K), 500,000 (500K), 300,000 (300K), 200,000

(200K), 100,000 (100K), 80,000 (80K), 60,000 (60K), 50,000 (50K), 30,000 (30K),

20,000 (20K), 10,000 (10K). Each format conversion tool was executed on all the five

object sets (64 objects in total). For the same object set, we ensured consistency in the

type of count matrices converted between different tools to avoid potential bias. All

format conversion tools were executed on a server with one Intel(R) Xeon(R) Gold

5220R CPU, 512GB RAM, and CentOS 7.5.1804 operating system. The running time

(elapsed time) was recorded using *system.time* command in R. To ensure the

independence of each run, all commands are run in linear order on the Linux shell as

R scripts.

Format conversion between scRNA-seq objects

GEfetch2R uses *Seurat* to convert formats between *SeuratObject* and

SingleCellExperiment, uses *Seurat* and *SeuratDisk* to convert formats between

SeuratObject and *loom*, uses *Seurat* and *SeuratWrappers* to convert formats between

SeuratObject and *CellDataSet*/*cell_data_set*, and uses *LoomExperiment* to convert

formats between *SingleCellExperiment* and *loom*. For format conversion between

AnnData and *SeuratObject*/*SingleCellExperiment*, all the tools used for benchmarking

are available in *GEfetch2R*.

Results

Overview of *GEfetch2R*

GEfetch2R supports downloading all the three types of scRNA-seq data: raw data,

count matrix, and processed object (Fig. 1). The databases corresponding to each data

type, number of datasets/species/cells available, downloaded and returned data, and

other key features are summarized in Table 2. For fetching raw data, *GEfetch2R*

accepts GEO accessions as input, and downloads *sra*, *fastq*, and *bam* files from SRA

and ENA. In particular, the parameters for downloading 10x-related *fastq* and *bam*

files have been optimized, such as downloading and formatting the *fastq* files to

CellRanger required format, and downloading *bam* files with original tags. With

downloaded files, *GEfetch2R* processes them and loads the output to R (*SeuratObject*

for 10x-generated data, *DESeqDataSet* for Smart-seq2 or bulk RNA-seq data). For

fetching count matrices, with GEO accessions (GEO) and key words/filter criteria

(UCSC Cell Browser and PanglaoDB) as input, *GEfetch2R* accesses count matrices

and various annotations, loads them to R, and extracts subset based on cell metadata

and genes (UCSC Cell Browser and PanglaoDB). For fetching processed objects, with

DOI (Zenodo) and key words/filter criteria (CELLxGENE and HCA) as input,

GEfetch2R downloads processed objects in given file extensions, loads *rds* files

(SeuratObjects) to R, and extracts subset based on cell metadata and genes

(CELLxGENE). The processed objects in other formats can be loaded to R/Python

through format conversion.

To enable the interoperability between scRNA-seq analysis tools and the integration

of processed objects in diverse formats, *GEfetch2R* supports converting formats (i)

between   *SeuratObject*   and   *AnnData*,   *SingleCellExperiment*,

CellDataSet/*cell_data_set*, *loom*; (ii) between *SingleCellExperiment* and *loom*; (iii)

between *SingleCellExperiment* and *AnnData*. Moreover, as several tools have been

developed   for   the   same   conversion   stream   between   *AnnData*   and

SeuratObject/SingleCellExperiment, we benchmarked their performance in terms of

information kept, usability, running time, and scalability.

Figure 1: Overview of *GEfetch2R*. (A) Fetching and loading various data from public

repositories to R. The download of raw data, count matrix, and processed object are

indicated by ochre borders (horizontal). The input, supported databases, and final

output are indicated by orange borders (vertical). The boxes in purple indicate R

objects, in light pink indicate downloaded file formats. (B) Format conversions

supported by *GEfetch2R*. The boxes indicate scRNA-seq objects, the directional

arrows between boxes indicate conversion stream between objects, the texts above

arrows represent the tool used for the conversion, the red directional arrows without

texts indicate conversion streams that are benchmarked.

Application of *GEfetch2R* in COVID-19 scRNA-seq altas exploration

Coronavirus disease 2019 (COVID-19) is a highly contagious disease caused by

severe acute respiratory syndrome coronavirus 2, with symptoms ranging from mild

to severe [30]. Depicting the dynamic immune responses across symptom severities at

the single-cell level is an effective method to understand COVID-19 progression. To

demonstrate the utility of *GEfetch2R*, we applied it to download and explore all T

cells of a COVID-19 scRNA-seq altas [30] from UCSC Cell Browser. As shown in

Fig. 2A, there are twelve T cell subtypes, including six subtypes of $CD4^+$ T cells,

three subtypes of $CD8^+$ T cells, and three subtypes of natural killer T (NKT) cells. The

cell type composition analysis across four conditions (healthy donor (HD), moderate,

severe, and convalescent (conv)) revealed that compared with HDs, the proportions of

four $CD4^+$ T subtypes ($CD4^+$ naive, $CD4^+$ memory, $CD4^+$ effector memory, and

regulatory T (Treg)) and $CD8^+$ naive subtype were significantly decreased in

COVID-19 patients, and the proportion of $CD4^+$ naive subtype was still significantly

reduced in COVID-19 conv samples (Fig. 2B-C). Meanwhile, the proportions of

$CD4^+$ effector-GNLY, $CD8^+$ effector-GNLY, NKT CD56, and NKT CD160 subtypes

were significantly increased in COVID-19 patients, and the $CD4^+$ effector-GNLY

subtype was nearly absent in HDs but highly enriched in moderate, severe and conv

samples (Fig. 2B-C). The apoptosis scoring results showed that T cells in COVID-19

patients generally had significantly increased apoptosis scores (Fig. 2D).

Figure 2: Application of *GEfetch2R* in COVID-19 scRNA-seq altas exploration.

(A) UMAP embedding of all T cells. Clusters in different colors represent T cell

subtypes. (B) The proportion of each cell type across HD, moderate, severe, and conv

samples. (C) Differential cell type composition analysis. All differences with

$P < 0.05$ are labeled; two-sided unpaired Mann–Whitney U-test was used for

analysis. (D) The apoptosis scoring results. All differences with Bonferroni adjusted

$P < 0.01$ are indicated. $**P < 0.01$; $***P < 0.001$; $****P < 0.0001$; using

two-sided unpaired Dunn's test. NKT: natural killer T; Treg: regulatory T.

Benchmark of format conversion tools

Information kept

We evaluated and ranked the information kept of format conversion tools in terms of

count matrix and annotation. Figure 3A and Supplementary Note show our rank

reasoning and the overall information kept rank of each tool. In Seu2AD, *scDIOR* can

preserve all the three count matrices and more annotations, thus ranking first.

SeuratDisk can keep two of the three count matrices and more annotations, thus

ranking second. While *sceasy* keeps only one count matrix and the least annotations,

thus ranking last. In SCE2AD, *zellkonverter* and *scDIOR* both keep all the three count

matrices, while *zellkonverter* preserves the most comprehensive annotations, thus

zellkonverter ranks first. *sceasy* keeps only one count matrix and less comprehensive

annotations, resulting in the lowest information kept rank. In AD2Seu, *scDIOR*,

sceasy, and *SeuratDisk* can keep two of the three count matrices, which is more than

schard. And, *scDIOR* preserves the most comprehensive annotations, thus ranking

first. Both *schard* and *sceasy* retain the least annotations, thus *schard* ranks last. In

AD2SCE, *zellkonverter* can preserve two of the three count matrices and the most

comprehensive annotations, thus ranking first. While both *schard* and *scDIOR* keep

only one count matrix, and *schard* retains the least annotations, thus *schard* ranks last.

Table A — Conversion, Tool, Count matrix, Annotation, Notes, Information rank

Conversion	Tool	Count matrix	Annotation	Notes	Information rank
Seu2AD	SeuratDisk	data, counts/scale.data(conditional)	obs (meta.data), var (meta.features), uns, obsm (reductions), obsp (graphs), layers (assays)	the obsp only contains distances, not connectivities	2
	sceasy	counts/data/scale.data	obs (meta.data), var (meta.features), obsm (reductions)		3
	scDIOR	counts, data, scale.data(conditional)	obs (meta.data), var (meta.features), obsm (reductions), layers (assays), obsp (graphs)		1
SCE2AD	sceasy	counts/data/scale.data	obs (colData), var and varm (rowData), obsm (reducedDim)		3
	scDIOR	counts, data, scale.data	obs (colData), var (rowData), obsm (reducedDim), layers (assays)		2
	zellkonverter	counts, data, scale.data	obs (colData), var and varm(rowData), obsm (reducedDim), layers (assays), uns (metadata), obsp (colPairs)		1
AD2Seu	SeuratDisk	scale.data, counts/data(conditional)	meta.data (obs), meta.features (var), reductions (obsm, varm), misc (uns)	the misc is incomplete, only includes pca and umap	2
	sceasy	scale.data, counts/data(conditional)	meta.data (obs), meta.features (var), reductions (obsm)	the meta.features is incomplete	3
	scDIOR	scale.data, counts/data(conditional)	meta.data (obs), meta.features (var), reductions (obsm), assays (layers), graphs (obsp)	the meta.features is incomplete	1
	schard	counts/data/scale.data	meta.data (obs), meta.features (var), reductions (obsm)		4
AD2SCE	scDIOR	counts/data/scale.data	colData (obs), rowData (var), reducedDim (obsm), assays (layers)		2
	zellkonverter	scale.data, counts/data(conditional)	colData (obs), rowData (var, varm), reducedDim (obsm), assays (layers), metadata (uns), colPairs (obsp)		1
	schard	counts/data/scale.data	colData (obs), rowData (var), reducedDim (obsm)		3

Table B — Conversion, Tool, Programming language, Dependency, Availability, Documanetation, Support, Compatibility, Others, Usability rank

Conversion	Tool	Programming language	Dependency	Availability	Documanetation	Support	Compatibility	Others	Usability rank
Seu2AD	SeuratDisk	R		GitHub, Conda	README, webpage	no Q&A	excellent	two steps, generate intermediate file	2
	sceasy	R	python env	GitHub, Conda	README	no Q&A	excellent		3
	scDIOR	R, Python		GitHub	README	no Q&A	excellent	generate h5 instead of h5ad file	1
SCE2AD	sceasy	R	python env	GitHub, Conda	README	no Q&A	excellent		3
	scDIOR	R, Python		GitHub	README	no Q&A	excellent	generate h5 instead of h5ad file	1
	zellkonverter	R	python env	GitHub, Conda, Bioconductor	webpage	active Q&A	excellent		2
AD2Seu	SeuratDisk	R		GitHub, Conda	README, webpage	no Q&A	fail (failure on test and converted datasets)	two steps, generate intermediate file	3
	sceasy	R	python env	GitHub, Conda	README	no Q&A	good (failure on test datasets, but success on zellkonverter converted datasets)		2
	scDIOR	R, Python	python env	GitHub	README	no Q&A	fail (failure on test and converted datasets)		4
	schard	R		GitHub	README	active Q&A	excellent		1
AD2SCE	scDIOR	R, Python	python env	GitHub	README	no Q&A	excellent		3
	zellkonverter	R	python env	GitHub, Conda, Bioconductor	webpage	active Q&A	excellent		2
	schard	R		GitHub	README	active Q&A	excellent		1

Figure 3: The information kept and usability of format conversion tools. (A) The information kept of format conversion tools in terms of count matrix and annotation. In 'Count maatrix' column, 'counts' represents raw count matrix, 'data' represents normalized data matrix, 'scale.data' represents scaled data matrix. In 'Annotation' column, the text outside/inside parentheses represents the data slot of the source/target object. (B) The usability of format conversion tools in terms of programming language, dependency, availability, documentation, support, and compatibility. Q&A: question and answer. The tool with the highest rank is marked in green.

Usability

We evaluated and ranked the usability of format conversion tools in terms of programming language, dependency, availability, documentation, support, and compatibility. Fig. 3B shows our rank reasoning and the overall usability rank of each tool. In Seu2AD, *sceasy* requires an additional Python environment, resulting in the lowest usability rank. *SeuratDisk* and *scDIOR* have comparable usability, but *scDIOR* can be used in both R and Python platforms, thus having a higher usability rank. In SCE2AD, *scDIOR* is the only tool that doesn't require an additional Python environment and can be used in both R and Python platforms, resulting in the highest usability rank. *zellkonverter* is hosted on Bioconductor and has active questions and answers (Q&As), thus ranking second. In AD2Seu, *schard* doesn't require an additional Python environment, has active Q&As, and is the only tool that runs successfully on all test data. Among the remaining three tools, *sceasy* runs successfully on *zellkonverter* converted *AnnData*, while the other tools still fail. Based on the above results, *schard* ranks first and *sceasy* ranks second in usability, and the subsequent running time is recorded on *zellkonverter* converted *AnnData*. In AD2SCE, *schard* has active Q&As and is the only tool that doesn't require an additional Python environment, resulting in the highest usability rank. *zellkonverter* and *scDIOR* have comparable usability, but the former is slightly better. In detail, *zellkonverter* is hosted on Bioconductor and has active Q&As, while *scDIOR* can be used in both R and Python platforms.

Running time and scalability

In Supplementary Table S2, we summarized the running time of the format

conversion   tools   for   converting   between   *AnnData*   and

SeuratObject/*SingleCellExperiment* on five object sets (64 objects in total). Figure 4

shows that in AD2SCE, *schard* is always the fastest tool across all the five object sets,

while *zellkonverter* is the slowest tool in two of the five object sets. In AD2Seu, when

the cell number is smaller than 200K, *schard* is faster than *sceasy* or has comparable

speed, but *sceasy* is significantly faster than *schard* when the cell number exceeds

200K. This alternation means that *sceasy* has better scalability than *schard*. In

SCE2AD, *zellkonverter* is always the fastest tool across all the five object sets, while

sceasy and *scDIOR* are the slowest tools in two of the five object sets. In Seu2AD,

across all the five object sets, *sceasy* is always the fastest tool, while *SeuratDisk* is

always the slowest tool.

Figure 4: The running time of format conversion tools. There are twenty subplots,

distributed in four rows and five columns. Each row represents the format conversion

tools are executed on the same object set. Each column represents the same

conversion stream. *x*-axis means the cell number (K: thousand, M: million), *y*-axis

means the running time.

Comparison of *GEfetch2R* with other similar tools

Table 1 shows a feature comparison of *GEfetch2R* with other tools that are capable of

downloading data from public repositories. *GEfetch2R* distinguishes itself in the

following aspects. Firstly, *GEfetch2R* supports downloading the most diverse data

types (raw data, count matrix, and processed objects), and each data type can be

downloaded from multiple public repositories. This benefits users in collecting data

more comprehensively and choosing appropriate download data types according to

different needs. For quick data exploration, downloading processed objects is a good

choice, whereas for fine data integration to draw conclusions, downloading raw data

or count matrices can help reduce the bias. Secondly, *GEfetch2R* adopts multiple

methods to speed up downloading, including Aspera support, parallel downloading

fastq files, and parallel splitting *sra* files into *fastq* files. Thirdly, *GEfetch2R* supports

downloading data of both scRNA-seq and bulk RNA-seq, and considers the

characteristics of data generated by different protocols. For 10x-generated data,

GEfetch2R downloads and formats the *fastq* files to *CellRanger* required format,

downloads *bam* files with original tags, converts *bam* files to *fastq* files using

bamtofastq, and aligns *fastq* files to the reference genome using *CellRanger*. For

Smart-seq2 and bulk RNA-seq data, *GEfetch2R* converts *bam* files to *fastq* files using

samtools, and aligns *fastq* files to the reference genome using *STAR*. This expands the

scope of use of *GEfetch2R* and makes the data it downloads easier to use. Fourthly,

besides data download, *GEfetch2R* can process the downloaded data, load

output/downloaded   count   matrices   and   annotations   to   R

(*SeuratObject*/*DESeqDataSet*), extract a subset of the *SeuratObject* based on cell

metadata and genes, and merge multiple *SeuratObjects* if applicable. This greatly

distinguishes *GEfetch2R* from other tools, which are pure data downloaders. Lastly,

GEfetch2R provides the most comprehensive object format conversions, and

benchmarks the format conversion tools for converting between *AnnData* and

SeuratObject/*SingleCellExperiment*. This enables users to integrate multiple objects

in diverse formats, bridges the widely used scRNA-seq analysis tools, and guides the

selection of format conversion tools.

Conclusions and Discussions

GEfetch2R is an R package dedicated to facilitating researchers to access and explore

the existing gene expression data from various public repositories. As a data

downloader, *GEfetch2R* supports downloading the most diverse scRNA-seq data

types, including raw data (SRA and ENA), count matrices (GEO, UCSC Cell Browser,

and PanglaoDB), and processed objects (Zenodo, CELLxGENE, and HCA). Besides

the data download ability, *GEfetch2R* can process the downloaded data, load

output/downloaded count matrices and annotations to R

(*SeuratObject*/*DESeqDataSet*), extract a subset of the *SeuratObject* based on cell

metadata and genes, and merge multiple *SeuratObjects* if applicable. Furthermore, to

enable the integration of scRNA-seq data and the interoperability between different

analysis tools, *GEfetch2R* provides the most comprehensive format conversions

between different scRNA-seq objects, including *SeuratObject*, *AnnData*,

SingleCellExperiment, *CellDataSet*/*cell_data_set*, and *loom*. In particular, *GEfetch2R*

benchmarks the format conversion tools for converting between

SeuratObject/*SingleCellExperiment* and *AnnData*. In Seu2AD, *scDIOR* has the best

performance in terms of information kept and usability, and *sceasy* is always the

fastest tool. In SCE2AD, *zellkonverter* has the highest information kept rank, *scDIOR* is the best in usability, and *zellkonverter* is consistently the fastest tool. In AD2Seu, *scDIOR* has the best performance in terms of information kept, *schard* is the best in usability, and *sceasy* has better scalability than *schard*. In AD2SCE, *zellkonverter* has the highest information kept rank, *schard* is the best in terms of usability and speed.

In addition to fetching scRNA-seq data, *GEfetch2R* can also be used to download raw data (SRA and ENA) and count matrices (GEO) of bulk RNA-seq, process the downloaded data, and load output/downloaded count matrices to R (*DESeqDataSet*).

Currently, there are still several aspects of *GEfetch2R* that can be improved. Firstly, *GEfetch2R* only supports processing the Smart-seq2 and 10x-generated raw data, users can download the raw data generated by other scRNA-seq protocols using *GEfetch2R*, but the subsequent process is not available. Secondly, many widely used scRNA-seq databases are not supported by *GEfetch2R*, such as Single Cell Portal [31]. We will actively develop to support more scRNA-seq protocols and databases. Besides, since the APIs of supported databases may change, we will update *GEfetch2R* on time to ensure usage.

Availability and Requirements

- Project name: *GEfetch2R*
- Project homepage: https://github.com/showteeth/GEfetch2R
- Software documentation: https://showteeth.github.io/GEfetch2R
- Docker image: https://hub.docker.com/r/soyabean/gefetch2r

• Operating system(s): Platform independent

• Programming language: R

• Other requirements: R 2.10 or higher, Python 3.7.3 or higher (format

conversion)

• License: GPL-3.0

• RRID: SCR_026714

Additional Files

Supplementary Note. Step-by-step code and output showing information kept of

format conversion tools.

Supplementary Fig. S1. The detailed workflow of *GEfetch2R*.

Supplementary Table S1. The datasets used for benchmarking format conversion

tools.

Supplementary Table S2. The running time of the format conversion tools on five

object sets.

Abbreviations

scRNA-seq: single-cell RNA sequencing; SRA: Sequence Read Archive; ENA:

European Nucleotide Archive; GEO: Gene Expression Omnibus; HCA: Human Cell

Atlas; 10x: 10x Genomics; Seu2AD: from SeuratObject to AnnData; AD2Seu: from

AnnData to SeuratObject; SCE2AD: from SingleCellExperiment to AnnData;

AD2SCE: from AnnData to SingleCellExperiment; K: thousand; M: million;

COVID-19: Coronavirus disease 2019; NKT: natural killer T; HD: healthy donor;

conv: convalescent; Treg: regulatory T; Q&As: questions and answers.

Acknowledgements

446 We thank SRA, ENA, GEO, PanglanDB, UCSC Cell Browser, Zenodo,

447 CELLxGENE, and HCA for generously hosting the single-cell/bulk RNA-seq data

448 and providing websites/APIs for users to access these data, and gratefully

449 acknowledge all the data contributors. These are the cornerstones for the development

450 of *GEfetch2R*.

Funding

452 This work was supported by the National Natural Science Foundation of China (No.

453 22050004); and the start-up funds from Institute of Microbiology of Chinese

454 Academy of Sciences.

Author Contributions

456 Y.S., J.W., and J.G. contributed to the conception and design of *GEfetch2R*. Y.S.

457 implemented and benchmarked *GEfetch2R*. J.W. and J.G. provided supervision and

458 secured funding. All authors prepared and approved the manuscript.

Data Availability

460 The datasets used in this study are freely available from SRA, CELLxGENE, and

461 *SeuratData* [32]. All scripts used for the COVID-19 scRNA-seq altas exploration and

462 benchmark of format conversion tools, including downloading, processing,

463   subsampling, running, and visualizing, are available in the GitHub repository [33].

464   Snapshots of the code and data are available in Software Heritage [34].

Competing Interests

466   The authors declare that they have no competing interests.

References

1.   Haque A, Engel J, Teichmann SA, et al. A practical guide to single-cell RNA-sequencing for biomedical research and clinical applications. Genome Med. 2017;9(1):1-12. 10.1186/s13073-017-0467-4.

2.   Cheng Y, Fan X, Zhang J, et al. A scalable sparse neural network framework for rare cell type annotation of single-cell transcriptome data. Commun Biol. 2023;6(1):545. 10.1038/s42003-023-04928-6.

3.   Zheng L, Qin S, Si W, et al. Pan-cancer single-cell landscape of tumor-infiltrating T cells. Science. 2021;374(6574):abe6474. 10.1126/science.abe6474.

4.   Katz K, Shutov O, Lapoint R, et al. The sequence read archive: a decade more of explosive growth. Nucleic Acids Res. 2022;50(D1):D387-D90. 10.1093/nar/gkab1053.

5.   Burgin J, Ahamed A, Cummins C, et al. The European Nucleotide Archive in 2022. Nucleic Acids Res. 2022;51(D1):D121-D5. 10.1093/nar/gkac1051.

6.   Barrett T, Wilhite SE, Ledoux P, et al. NCBI GEO: archive for functional genomics data sets—update. Nucleic Acids Res. 2012;41(D1):D991-D5. 10.1093/nar/gks1193.

7.   Speir ML, Bhaduri A, Markov NS, et al. UCSC cell browser: visualize your single-cell data. Bioinformatics. 2021;37(23):4578-80. 10.1093/bioinformatics/btab503.

8.   Franzén O, Gan L-M , Björkegren JL. PanglaoDB: a web server for exploration of mouse and human single-cell RNA sequencing data. Database. 2019;2019:baz046. 10.1093/database/baz046.

9.   Zenodo. CERN, Genève. 2013. https://www.zenodo.org/. Accessed 14 December 2024.

10.   Regev A, Teichmann SA, Lander ES, et al. The human cell atlas. elife. 2017;6:e27041. 10.7554/eLife.27041.

11.   Megill C, Martin B, Weaver C, et al. cellxgene: a performant, scalable exploration platform for high dimensional sparse matrices. bioRxiv. 2021:2021.04.05.438318. 10.1101/2021.04.05.438318.

12.   Zheng GX, Terry JM, Belgrader P, et al. Massively parallel digital transcriptional profiling of single cells. Nat Commun. 2017;8(1):14049. 10.1038/ncomms14049.

13.   Picelli S, Faridani OR, Björklund ÅK, et al. Full-length RNA-seq from single cells using Smart-seq2. Nat Protoc. 2014;9(1):171-81. 10.1038/nprot.2014.006.

14.   Satija R, Farrell JA, Gennert D, et al. Spatial reconstruction of single-cell gene expression data. Nat Biotechnol. 2015;33(5):495-502. 10.1038/nbt.3192.

15.   Wolf FA, Angerer P , Theis FJ. SCANPY: large-scale single-cell gene expression data analysis. Genome Biol. 2018;19:1-5. 10.1186/s13059-017-1382-0.

16.   Qiu X, Mao Q, Tang Y, et al. Reversed graph embedding resolves complex single-cell
trajectories. Nat Methods. 2017;14(10):979-82. 10.1038/nmeth.4402.

17.   Cao J, Spielmann M, Qiu X, et al. The single-cell transcriptional landscape of mammalian
organogenesis. Nature. 2019;566(7745):496-502. 10.1038/s41586-019-0969-x.

18.   McCarthy DJ, Campbell KR, Lun ATL, et al. Scater: pre-processing, quality control,
normalization and visualization of single-cell RNA-seq data in R. Bioinformatics.
2017;33(8):1179-86. 10.1093/bioinformatics/btw777.

19.   Gálvez-Merchán Á, Min KH, Pachter L, et al. Metadata retrieval from sequence databases
with ffq. Bioinformatics. 2023;39(1) 10.1093/bioinformatics/btac667.

20.   Pickering A. GEOfastq. https://github.com/alexvpickering/GEOfastq. Accessed 2 March 2025.

21.   NCBI. SRA-Toolkit. https://github.com/ncbi/sra-tools. Accessed 2 March 2025.

22.   ENA. enaBrowserTools. https://github.com/enasequence/enaBrowserTools. Accessed 2 March
2025.

23.   Petit R. fastq-dl. https://github.com/rpetit3/fastq-dl. Accessed 2 March 2025.

24.   Choudhary S. pysradb: A Python package to query next-generation sequencing metadata and
data from NCBI Sequence Read Archive. F1000Research. 2019;8:532.
10.12688/f1000research.18676.1.

25.   Khoroshevskyi O, LeRoy N, Reuter VP, et al. GEOfetch: a command-line tool for
downloading data and standardized metadata from GEO and SRA. Bioinformatics.
2023;39(3):btad069. 10.1093/bioinformatics/btad069.

26.   Davis S , Meltzer PS. GEOquery: a bridge between the Gene Expression Omnibus (GEO) and
BioConductor. Bioinformatics. 2007;23(14):1846-7. 10.1093/bioinformatics/btm254.

27.   Osorio D, Kuijjer ML , Cai JJ. rPanglaoDB: an R package to download and merge labeled
single-cell RNA-seq data from the PanglaoDB database. Bioinformatics. 2022;38(2):580-2.
10.1093/bioinformatics/btab549.

28.   Li H, Handsaker B, Wysoker A, et al. The sequence alignment/map format and SAMtools.
Bioinformatics. 2009;25(16):2078-9. 10.1093/bioinformatics/btp352.

29.   Program CCS, Abdulla S, Aevermann B, et al. CZ CELLxGENE Discover: a single-cell data
platform for scalable exploration, analysis and modeling of aggregated data. Nucleic Acids
Res. 2024;53(D1):D886-D900. 10.1093/nar/gkae1142.

30.   Zhang J-Y, Wang X-M, Xing X, et al. Single-cell landscape of immunological responses in
patients with COVID-19. Nat Immunol. 2020;21(9):1107-18. 10.1038/s41590-020-0762-x.

31.   Tarhan L, Bistline J, Chang J, et al. Single Cell Portal: an interactive home for single-cell
genomics data. bioRxiv. 2023:2023.07.13.548886. 10.1101/2023.07.13.548886.

32.   satijalab. SeuratData. https://github.com/satijalab/seurat-data. Accessed 2 March 2025.

33.   Song Y. Code and data used for exploration and benchmark.
https://github.com/showteeth/GEfetch2R/tree/main/man/benchmark. Accessed 7 April 2025.

34.   Song Y. An archival copy of GEfetch2R.
https://archive.softwareheritage.org/browse/origin/directory/?origin_url=https://github.com/sh
owteeth/GEfetch2R. Accessed 7 April 2025.