1   **The quest for improved biohydrogen formation: are heat shocks the solution?**

2   Maximilian Barth [1], Magdalena Werner [1], Pascal Otto [1], Benjamin Richwien [2], Samira

3   Bahramsari [2], Maximilian Krause [3], Benjamin Schwan [1], Christian Abendroth[*, 4]

6   *Corresponding author (E-Mail: christian.abendroth@b-tu.de)

[1] TUD Dresden University of Technology, Institute for Circular Economy, Pirna,

Germany

[2] Robert Boyle Institute e.V., Jena, Germany

[3] Dresden-concept Genome Center, CMCB Center for Molecular and Cellular

Bioengineering, TUD Dresden University of Technology, Dresden, Germany

[4] Department of Circular Economy, Brandenburg University of Technology Cottbus-

Senftenberg, Cottbus, Germany

Keywords: dark fermentation, hydrogen production, sewage sludge, microwave heat

shocks, 16S-rRNA sequencing

Highlights

- The entire reactor content of 3.5 litre was heat shocked.

- Heat shocks economically boosted dark fermentation hydrogen yield.

- Heat pumps with COP of 4.3 would allow energetic net gain due to heat shocks.

- Oven and microwave-based heat shocks are not significantly different.

- Microwaves heat sludge 6.4 times faster than ovens.

- Heat shocks inhibited methane production completely.

- Heat shocks increased particularly *Clostridium sensu stricto* 1 and 11.

- Hydrogen could be enriched from sucrose, but not from lipids or proteins.

Abstract

Heat shocks are a favoured method used to trigger hydrogen production in dark fermentation. However, these treatments are often restricted to a very small volume, which is then inoculated into synthetic medium. Moreover, heat shocks are usually applied with an oven. This study explored the feasibility of applying heat shocks to the entire seed sludge using a microwave, a method not previously investigated. The experiments were conducted on a technical scale with 5 litre tank reactors. The highest productivity was achieved with an oven (0.95 mol H_2/mol hexose), but the microwave was not significantly different and had the advantage of heating the sludge 6.4 times faster. The study also emphasized the repeatability of heat shocks, with microwave-assisted experiments showing low variation coefficients averaging 29%. The approach is already economically sustainable with high-temperature heat pumps with a COP of 4.3, enhancing its practical relevance.

1 Introduction

Anaerobic digestion is a technology, which allows the production of methane from multiple organic resources and residues, as for example straw and corn stover (Croce et al., 2016), chicken dung (Bayrakdar et al., 2017), food waste (Xu et al., 2018) and other. The possibility to produce methane from biodegradable remnants is intriguing, although it is hard to compete to existing technologies, which are based on fossil fuels. In Germany, the monetary shortcoming is counterbalanced based on the German Renewable Energy Sources Act. Therefore, to make anaerobic digestion a self-sustained technology, technological and conceptual advancements are needed. A possibility to achieve this is to intertwine anaerobic digestion with existing bio-based industries creating synergetic effects. To give some examples: Chen et al. (2018) suggested to integrate anaerobic digestion and microalgae cultivation. A review article from Sawatdeenarunat et al. in 2016 discusses additionally the possibility to produce valuable side products from extracted solids from the digestate or from the biogas itself, as for example syngas, methanol, butanol and other. A particular promising approach to produce valuable side products is the application of two stage digesters with a separated acidification stage. Acidic anaerobic digestion allows the accumulation of short chain fatty acids (C2 – C5), which are important platform chemicals for the chemical industry (Uludag-Demirer et al., 2019). Under specific conditions even a chain elongation can be achieved during the digestion process, yielding medium chain carboxylic acids (Groof et al., 2019). Another promising metabolite formed during anaerobic digestion is hydrogen (Khan et al., 2018). Particularly, a two-stage digestion process is well suited for microbial hydrogen production (Cooney et al., 2007). Using acidic pretreatment stages of anaerobic digesters for hydrogen production is a process, which is very similar to dark fermentation. Dark

fermentation approaches are extensively described in the literature and already in late 80s,

mixed culture fermentation was applied for microbial hydrogen production

(Roychowdhury et al., 1988). However, particularly when applying hydrogen production

with mixed cultures and in combination with a methane yielding digester, several

problems can occur. Anaerobic digestion involves around 300 operational taxonomic

units, which covered 80 percent of all reads from 16S rRNA gen amplicon high

throughput sequencing of samples belonging to 32 full-scale digester plants (Kirkegaard

et al., 2017). Such a high diversity makes it difficult to achieve a stable microbiome that

yields a predictable outcome of hydrogen. A study by Alibardi et al. (2012) is noteworthy

in the context of high microbial diversity. This research emphasized that heat-shock

applications could enhance hydrogen yield, thereby increasing its predictability. Another

problem that occurs when coupling a dark fermentation stage with a methanogenic reactor

is the immigration of methanogens. Although high organic loading rates (OLR) and,

therefore, low pH levels tend to supress methanogenesis (Bertucci et al., 2019; Senturk

et al., 2014), the formation of methane during dark fermentation has been described

before (Słupek et al., 2019). Interestingly, heat-shocks can help to optimize this problem

too. Although methanogenesis becomes not fully supressed, it has been indicated recently

that heat-shocks can reduce the amount of methane, which is produced in separated

acidification stages (Abendroth et al., 2018). The fact that heat-shocks can simultaneously

supress methanogenesis and contribute to an enrichment of hydrogen forming bacteria

makes them particularly interesting. Although multiple research articles already address

the application of heat-shocks to improve hydrogen formation, the authors of the present

work have barely detected works, where the complete seed sludge was heat shocked. An

enrichment culture is unlikely to prevail in a complex anaerobic sludge. In respect to an

industrial application, therefore, the treatment of the complete seed sludge would be more practical. The presented work tries to close this gap by investigating the industrial suitability of heat-shocks for separated acidification stages heating up the entire seed sludge. For the first time, the application of microwaves was assessed in parallel to oven-based heat-shocks. Further, the impact of heat-shocks on the underlying microbiome was explored.

2   Material and Methods

2.1   Inoculum and Substrate

Dark fermentation experiments were performed, using customary sucrose as substrate and sewage sludge as seed sludge. The sewage sludge was retrieved from a digester of a municipal wastewater treatment plant in Saxony, Germany. At mesophilic temperatures $(30-35°C)$, the average solids retention time (SRT) was kept at 16.5 days with an average pH of 7.6. The amount of total solids (TS) was at 2.78 g/l with a median ammonium content (NH_4-N) of 1109 mg/l. The sludge contained 57.52 g/l total organic solids. During the experiments, the solubilized chemical oxygen demand of the seed sludge was 1220 mg/l and the median of the VFAs was 34.71 mg/l. The dissolved organic carbon (DOC) was 329.85 mg/l. The seed sludge contained further 118.45 mg/l calcium, 33.71 mg/l magnesium, 178.35 mg/l potassium and 16.46 mg/l sodium. Gelatine, mixed rye bread, coconut oil and sucrose were tested as substrates and based on that sucrose was chosen as the carbon source for the ongoing experiments.

2.2   Experimental set-up

For dark fermentation, customized tank reactors (CTRs) from the company Lehmann-UMT GmbH (Germany) were applied (Figure 1A). These CTRs had a volume of 5 litre

with a working volume of 3,3 litre maximum. Each fermentation lasted for 7 days. Before

transferring the seed sludge into the respective reactors, 50, 75 or 100 g/l of sucrose were

added. The process temperature during fermentation was 38 ± 1 °C.

During the experiments, the impact of heat shocks on hydrogen formation was

investigated. Heat shocks were applied before the feeding substrate was added. Different

methods of heating were tested. For the heat shock, the slurry was heated by means of

both oven and microwave. By oven, the sludge was incubated at 130°C in 1 litre Schott

flasks. By microwave, the sludge was heated in 5 litre measuring cups at 1000 watts. Both

methods were used to heat the sludge to 80-90°C, to eliminate hydrogen consuming

microorganisms. Incubation times varied from 25 minutes to 3 hours (Figure 1B)

depending on the used method. After the heat shock, the sludge was cooled down to 40°C.

Zhu and Béland (2006) reported that heat shocks are often performed in the range of 80

to 104°C and with exposure times of up to 120 min. Here, the exposure times are much

shorter and the temperature of the heat shock is only up to 80°C ± 1°C. For the microwave

these were 5-10 minutes and in the oven 10-20 minutes. These lower conditions were

chosen following the experiments of Wong et al. (2014) which showed that effective heat

shock pretreatment of anaerobic sludge can be achieved at lower temperatures (65-85 °C)

and durations of 45-60 min. Taking into account that the entire seed sludge was heat

treated in the present work, lower temperatures and shorter incubation times were

preferred to be more energy efficient.

For each condition tested, fermentation experiments were repeated minimum 6 times

which resulted in a total amount of 69 reactions, that were evaluated. Control experiments

accounted for 29, oven heat pretreatment for 20, and microwave heat shock pretreatment

for 20 tests.

*Figure 1: **(A)** Experimental set up: double-walled reactors (1) with a volume of 5L each.*

Each reactor was filled through an input port (2) and acidified hydrolysate was removed

through a port at the bottom (3). For heating, a water pipe was connected to the input (9)

and output (10) ports of the double-wall clearance. Water was heated using a thermostat

(6). Produced gas was measured by a MilliGascounter (5), connected with a tube (4),

and stored in a gas bag (7). The time resolved gas production was recorded with an

*Arduino (8) connected to the gas counter. **(B)** Average incubation time for heat shocking*

up to a minimum of 80°C for pre-treatment with oven (set to 130°C) and microwave (set

*to 1000 Watt). **(C)** Preliminary tests: Comparison of hydrogen production with sucrose,*

mixed rye bread, gelatine and coconut oil as feeding substrates and sewage sludge as

inoculum. Both control and heat shock (oven and microwave) scenarios were tested.

 2.3 Sampling and chemical analysis

During the fermentation, produced biogas was collected in gas bags (Tesseraux, Germany) and quantified using a RITTER MilliGascounter (Bochum, Germany). Based on the guideline VDI 4630 from the Association of German Engineers (2016), the gas volume was normalized to standard temperature (273 K) and standard pressure (1013 hPa).

The solubilized COD was measured in the liquid phase after centrifugation at 1.200 g and subsequent vacuum filtration through a 0.2 μm cellulose-acetate filter (Sartorius AG, Göttingen, Germany). The COD was determined using the Spectroquant COD kit (VWR, Germany) according to the manufacturer's guidelines. The spectrum of VFAs (lactic acid, formic acid, acetic acid, propionic acid, iso-butyric acid, butyric acid and valeric acid) was determined by ion chromatography. For this, a cation exchange column (Metrosep Organic Acids 250/7.8 column; Model: 882 Compact IC plus, Metrohm AG, Herisau, Switzerland) was applied. The mobile phase had a concentration of 0.6 mmol/l of perchloric acid and 10 mmol/l of lithium chloride. The detection limit was 0.25 mg/l. The inoculation sludge had no lactic and valeric acid and only very small amounts of propionic and butyric acid (1.54 and 2.75 mg/l). Formic acid and acetic acid were present in the initial substrate at 7.17 mg/l and 13.42 mg/l, respectively. Total volatile fatty acids (TVFAs) were analysed as the sum of all detected VFAs. Initially, heavy metals were measured by microwave digestion and ICP (PerkinElmer Optical-Emission Spectrometer Optima 8000/ S10 Autosampler). Nitrogen content (TKN and NH_4-N) was determined according to ISO 5663.

For microbiome analysis with 16S-rRNA gene amplicon high-throughput sequencing, an aliquot of 3 ml of each sample stored in ethanol was centrifuged and washed with sterile

phosphate-buffered saline (PBS) until the supernatant was clear. DNA was extracted from

the resulting pellets using a Qiagen DNeasy PowerSoil Kit. DNA was quantified using

the Qubit 1x dsDNA Kit from ThermoFisher. The extracted metagenomic DNA was used

to amplify the hypervariable region V3-V4 of the 16S ribosomal RNA gene. The

conserved regions V3 and V4 (470 bp) of the 16S rRNA gene were amplified using PCR

cycling: initial denaturation at 95 °C for 3 min; 25 amplification cycles (20 s at 98 °C, 15

s at 60 °C, 30 s at 72 °C); and 5 min extension at 72 °C. The following primers were used:

- 341F (5' ACACTCTTCCCTACACGACGCTCTTCCGATCT NNNNN

CCTAYGGGRBGCASCAG 3') and

- 806R (5' GTGACTGGAGTTCAGACGTGTGCTCTTCCGATCT

GGACTACNNGGGTATCTAAT 3').

Amplification was performed using the Thermo Scientific Phusion High-Fidelity DNA

polymerase kit. The purification of the amplicons was carried out after each PCR with

the 1x v/v AmPure XP beads from Beckmann Coulter. The purified 16S amplicons were

indexed with a second PCR containing TruSeq Illumina Indexing Primers (cycling

conditions 98C 30sec denaturation, 98C 15sec, 65C 75sec, 10 cycles, final elongation

5min 65C, 4C overnight). Final libraries were again purified with 1x v/v AmPure XP

beads and quality-assessed on an Agilent FragmentAnalyzer (1-6000bp NGS Kit).

Libraries are then equimolarly pooled and sequenced. Sequencing was performed using

2X250pb or 2 × 300pb paired-end cycle runs on an Illumina MiSeq instrument. The

Illumina raw sequences were loaded into Qiime2 (v. 2021.2.0) (Bolyen et al., 2019) . The

quality of the sequences was checked with the Demux plugin and the DA-DA2 pipeline

integrated in Qiime2 was used to trim and join the sequences, remove chimaeras and

detect amplicon sequence variants (ASVs) (> 99.9 % similarity). The taxonomy of each

sequence variant was determined using SILVA (Quast et al., 2013) as the reference

database for taxonomic assignment.

2.4   Analysis of hydrogen content

Produced gas was collected in gas bags (Tesseraux, Germany). The gas volume was

determined and normalised after measuring temperature and air humidity. Carbon dioxide

(CO_2), oxygen (O_2), methane (CH_4) and hydrogen sulphide (H_2S) were detected with a

X-AM 8000 gas detector by Dräger (Lübeck). Nitrogen and hydrogen cannot be detected

directly by the analyser. At the beginning the reactor was filled with 3.3 litre of sewage

sludge and 1.7 litre air, consisting of nitrogen by 79 %. The nitrogen content of the initial

gas phase was deducted of the gas production. The amount of hydrogen was estimated as

the remaining part after subtracting the percentages of nitrogen, oxygen, carbon dioxide

and methane. The amount of hydrogen sulphide was very low (usually a few ppm), and

therefore, it was neglected. The gas contained in the headspace was also considered. The

formula to estimate the yield of hydrogen considers the density and the molar mass of

hydrogen, the input mass and molar mass of the substrate (sucrose) and the number of

hexose molecule per molecule sucrose. The formula assumes that the substrate is

consumed completely.

$$y = \frac{V(H_2) \times \rho(H_2) \times M(Suc)}{(M(H_2) \times m(Suc) \times N(Suc)}$$

y… yield [mol H₂/mol Hexose]

V(H₂)… generated volume of hydrogen [Nl]

ρ(H₂)… density of hydrogen [g H₂/Nl]; (0,0899 g H₂/Nl)

M(Suc) … molar mass of sucrose [g Suc/mol Suc]; (342,3 g Suc/mol Suc)

M(H₂)… molar mass of hydrogen [gH₂/molH₂]; (2,01588 g H₂/mol H₂)

m(Suc) … mass of sucrose [g Suc/l Input]

N(Suc)… number of hexose molecules per sucrose molecule; (1.9)

2.5   Statistical Analysis

For the basic statistical evaluation of the test series, each with at least 6 measured values,

the median was selected in order to better represent the tendency of the individual test

results. To test the experimental groups for statistically significant group differences, the

Levene test was first used as a test procedure for homogeneity of variance. Unlike the

Bartlett test, this test is significantly more robust when populations are not normally

distributed (Eid et al., 2017). For experimental groups that did not have homogeneity of

variance, a WELCH ANOVA was performed (Sadooghi-Alvandi et al., 2012; Eid et al.,

2017). Groups with homogeneity of variance were compared using classic ANOVA.

Pairwise experimental group differences were determined using post-hoc tests. For this

purpose, the Tukey-Kramer test (Ruxton and Beauchamp, 2008; Shingala and Rajyaguru,

2015) and, for groups without homogeneity of variance, the Games Howell test was used

(Lee and Lee, 2018). For all tests, the significance level was set at $\alpha = 0.05$.

3   Results and Discussion

3.1   *Dark mixed culture fermentation with different substrates*

The main substrate in the present work is sucrose. Usually, dark fermentation experiments are published with carbohydrates as substrates. Originally, it was planned to work also with substrates rich in proteins and fat to assess the suitability of substrates other than carbohydrates. Therefore, in preliminary tests, various feeding substrates (namely sucrose, mixed rye bread, gelatine and coconut oil) were evaluated regarding to their hydrogen formation efficiency. These substrates were mixed with sewage sludge. The room loadings were between 30 g/l for gelatine and 50 g/l for bread, coconut oil and sucrose, and an additional 100 g/l for sugar. Each mixture was filled into 1 litre SIMAX glass bottles, which were prefilled with digested sewage sludge. To trigger H_2 formation, heat shocks were performed using an oven and a microwave as described in material and methods. In every experiment, a reaction with untreated sludge was used as control. The highest amount of hydrogen was obtained in the experiments, where sludge was heat shocked using an oven and with a loading rate of 50 g/l of sucrose (Figure 1C). This resulted in a yield of 9 litre hydrogen per litre sludge. High amounts of hydrogen were also obtained with 100 g/l sucrose in both oven and microwave heat shocks. Mixed 50 g/l rye bread performed well compared to 30 g/l gelatine and 50 g/l coconut oil, but it could not match the hydrogen production achieved with sucrose (Figure 1C). These results align with findings from other studies on dark fermentation, where substrates high in carbohydrates yielded significantly better gas rates (Lay et al., 2003; Kannaiah Goud et al., 2014; Luo et al., 2010). As depicted in Figure 1C, as twice as much biogas was produced in the heat-treated trials compared to the untreated control.

3.2 Dark mixed culture fermentation of sucrose

As shown in Figure 1C, fat and proteins are hardly suited for dark mixed culture

fermentation. Therefore, subsequent experiments were focused on sucrose as substrate.

Acidification of sucrose was performed in 5 litre CTRs, using digested sewage sludge

from a local wastewater treatment plant in Saxony as inoculum. Different loading rates

(50, 75 and 100 g/l) were compared in terms of hydrogen production, to determine the

optimal substrate concentration (Figure 2). Assuming an idealized uniform consumption

of the substrate, these would correspond to loading rates of 7, 11 and 14 g COD/l*d. The

highest average hydrogen yield in mol H_2 per mol hexose was achieved in experiments

with 50 g/l sucrose (Figure 2C). Control and pretreated sludges with the microwave or

the oven showed hydrogen formation efficiencies of 0.14, 0.51 and 0.95 mol H_2/mol

hexose respectively. These values correspond to the median. With untreated substrate,

the lowest median hydrogen formation was observed at 100 g/l sucrose, where only 0.69

litre H_2 per litre of working volume was formed. This corresponds to a formation

efficiency of just 0.06 mol H_2/mol hexose.

In the heat-treated experiments, the lowest median hydrogen yield was produced with 100

g/l sucrose, respectively 0.39 and 0.33 mol H_2/mol hexose for microwave and oven

pretreatment. The reduced yield per gram of substrate indicates overfeeding. As depicted

in Figures 3A and B, an increase in feeding rates led to a rise in both the total volume and

the absolute quantity of hydrogen, but only in the experiments that underwent microwave

pretreatment. Conversely, in the oven-treated experiments, the volumes decreased,

leading to an inverse effect. Consequently, the efficiency of hydrogen formation in the

oven experiments dropped significantly by approximately two-thirds from 50 g/l to 100

g/l. However, the decrease in hydrogen yield with microwave pretreatment was only 28%.

In the control experiments that were untreated, there was only a slight change in gas

volumes.

3.3   Application of heat shocks for optimization of hydrogen production

After the initial characterization of sucrose, it was now tried to optimize the hydrogen

production due to thermal pretreatment. Processes involving heterogeneous microflora

are deemed more suitable than homogeneous pure cultures due to their simpler process

control and efficient substrate conversion, provided that the medium undergoes

pretreatment (Rafieenia et al., 2018). As per Saady (2013), inhibiting H_2-consuming

microorganisms such as hydrogenotrophic methanogens, homoacetogens, lactic acid

bacteria, propionate-producing bacteria, and sulphate reducers is a crucial step in H_2

production by dark fermentation in mixed microbial communities. In the here presented

experiments, heat shocks were employed as a pretreatment to the seed sludge prior to the

addition of the respective substrate to enhance hydrogen yield. Many studies use heat

shocks to generate small volume of enriched hydrogen, which is than inoculated in a

medium. To increase industrial relevance, digested sewage sludge was used as seed

sludge and the entire seed sludge was pretreated. This strategy allows for the selection of

spore-forming hydrogen-producing microorganisms and the inhibition of non-spore-

forming hydrogen consumers. Different incubation times were necessitated by the

varying heat shock methods. The microwave pretreatment took approximately 35 minutes

for the slurry temperature to reach at least 80°C, while in the oven, it took nearly 3 hours

for the slurry to attain the desired temperature (Figure 1B). Once the temperature was

achieved, the sludge was immediately removed and allowed to cool down to 40°C. Figure

2A illustrates that compared to the untreated control experiments, the heat shocks

significantly augmented both the total gas volume and absolute hydrogen production

(Figure 2B), as improved hydrogen formation efficiency (Figure 2C). In the heat shock

trials (both oven and microwave), methane production was successfully eliminated

(Figure 2D). For instance, Hasyim et al. (2011) conducted a shock at 105°C for 20 min

in an autoclave, while Wang et al. (2019) performed a 70°C heat shock for 60 min with

free ammonia assistance to fully inhibit methane production using glucose as a substrate.

The recent experiments have demonstrated that even shorter and less energy-intensive

heat shocks can completely eliminate methane production and facilitate more efficient

biological hydrogen production from sewage sludge. However, it needs to be considered

that the experiments were batch-wise. In a continuous reactor or with sludge recirculation

in a two-stage process, it would still be conceivable that methanogens could gradually

adapt to the temperature shocks.

As a result of the heat treatments, the relative standard deviation of the hydrogenation

efficiency increased by 49% on average in the microwave pretreatment and by 70% in

the oven pretreatment. The standard deviation of the oven tests was on average 32%

higher than in the microwave tests. Hydrogen yield could potentially be increased further

by pH controlling, since pH values of 4.0 to 4.5 have a negative effect on hydrogen

production (O-Thong et al., 2009). The pretreatment with the oven was overall related to

higher gas production compared to the microwave. However, the boxplots of the

pretreated series of experiments show that the microwave shocks reduced the scatter of

the results, an effect that was not observed in the experiments with oven treatment.

Distinct observations were made at a loading rate of 50 g/l sucrose. Here, the oven

demonstrated a significant increase in absolute hydrogen production and consequently in

hydrogen formation efficiency (Figure 2B and 2C). A median of 5.92 l H_2/l sludge was

produced, corresponding to a hydrogen yield of 0.95 mol H_2/mol hexose. The maximum

hydrogen yields of 1.09 and 1.05 mol H_2/mol hexose are comparable to the experimental

results of O-Thong et al. in 2009 (1.16 mol H_2/mol hexose) and Baghchehsaraee et al. in

2008 (1.32 to 2.12 mol H_2/mol hexose). The high HBut/HAc molar ratios for the heat

shocked experiments (Figure 4B) indicating that hydrogen was produced via the butyrate

pathway (Pineda-Muñoz et al., 2020). Without heat pretreatment, the HBut/HAc ratio

shows that hydrogen was accordingly formed via the acetate pathway. For both heat

shock methods, the median hydrogen formation efficiency shows a decreasing trend as

the loading rate increases. This pattern is reflected in the total volume and hydrogen

volume for the oven-based heat shock experiments. In contrast, specific hydrogen

production increases with increasing feeding rate in the microwave pretreatment

experiments (Figure 2C). Concomitantly, the microwave assisted hydrogen production

efficiency remains more constant, decreasing by only 22% from 50 g/l to 100 g/l (65%

decrease for oven pretreatment). The distribution of gas volume indicates that in all

experiments involving heat shock pretreatment, the total hydrogen content in the gas

increased to approximately 40% for microwave and 41% for oven pretreated. This is a

significant increase when compared to the median of the control at 18% H_2 (Figure 2D).

Fang and Liu (2002) investigated the effect of pH on hydrogen formation as well as the

composition of the digestate and showed that within a short time 90% of the glucose was

metabolized. They managed to increase the hydrogen content in the biogas to 64% with

a pH value, which was optimally adjusted to 5.5. While in microwave-treated approaches

the relative hydrogen fraction increases slightly from 38% to 42%, it remained constant

at 40% to 42% in the oven-treated experiments. In both heat shock pretreated methods,

the highest relative hydrogen content was obtained in the experiments with 100 g/l

sucrose. Methane was not produced in any of the heat-treated trials. The residual portion

of the gas mixture consisted entirely of carbon dioxide.

In general, thermal pretreatment increased the hydrogen production capacity of anaerobic

sludge in dark fermentation experiments by at least a factor of 3.6 for microwave and a

factor of 5.3 for oven compared to untreated experiments. The maximum increase of 6.8

times was obtained in oven-treated trials at 75 g/l loading rate and in microwave assisted

trials by 6.5 times at 100 g/l loading rate (microwave: 50 g/l - 3.6 times, 75 g/l - 5.4 times;

oven: 50 g/l - 6.6 times, 100 g/l - 5.3 times). Hence, these findings align with those

reported by Baghchehsaraee et al. (2008) and O-Thong et al. (2009), who reported

enhancement rates of 5.1 (80°C for 30 min) and 7.9-fold (100°C for 1 h) as a result of

thermal pretreatments. The greatest increase of 1.9-fold in the oven-treated trials over

those with microwave treatment was achieved at a loading rate of 50 g/l. However, this

did not result in statistically significant differences between microwave and oven

pretreatment in terms of overall hydrogen production (Figure 4A). Only at 100 g/l, no

significant group differences for biogas volume and hydrogen content could be

determined between control and oven. In both the 50 g/l and 75 g/l loading rate

experiments, there were statistically significant differences between oven/microwave and

control for the hydrogen volume, hydrogen fraction, efficiency, and biogas volume. In a

few cases, hydrogen yields similar to those achieved by Tao et al. in 2007 (2.64 and 3.20

mol H_2/mol sucrose) were obtained. They carried out experiments with cattle dung and

longer and hotter heat shocks (112° for 4.5 h). Pineda-Muñoz et al. (2020) also succeeded

in producing high hydrogen yields by combining heat shock and ultrasonic treatment but

failed to completely suppress methane production despite nearly identical heat shock

conditions.

Figure 2: Application of heat shocks to optimize hydrogen productivity: Different concentrations of substrate (sucrose) and different pretreatments (oven and microwave) were compared. (A) Maximal biogas productivity and (B) the highest hydrogen production were reached with substrate concentration of 50 g L^{-1} and pretreated with oven heat shock. All fermentations were performed at least 5 times. (C) The highest hydrogen efficiency was achieved with 50 g/l sucrose both in microwave and oven experiments. (D) shows the gas composition depending on the feeding amount and pretreatment. To better indicate the impact of different loading rates, median values have been connected with a trend line.

 3.4   Taxonomic shifts due to heat shocks

Using 16S rRNA gene amplicon high-throughput sequencing, the effect of microwave

heat shock on the taxonomic profile and diversity of the microbiome at 25 g/l sucrose was

determined to reflect the stressor of overfeeding less strongly. Microwave treatment

effectively eliminated non-spore formers and homogenized the microbiome towards

Clostridia. In more severely overfed experiments, a similar effect was observed, but with

lower abundances of *Clostridia*. With a loading rate 25 g/l sucrose *Clostridia*

predominantly colonized the microwave-treated substrates (average abundance of 79%).

As depicted in Figure 3A, the microbial growth community in the microwave-treated

reactions was composed of 60% to 69% *Clostridium sensu stricto 1*. In contrast,

Streptococcus dominated the control experiments, making up 46% to 56% of the total

microbiome. *Paeniclostridium* was only present in the heat-treated experiments,

suggesting that it either benefited from the heat shock or was activated, as it must have

already been present in the inoculum. The heat shock was successful in completely

suppressing *Lactobacillus*, a lactic acid producer. Heat shock pretreatment resulted in a

reduction of species diversity by an average of 7% compared to the control, as shown in

Figure 3B. While the Shannon index showed no difference in diversity, the Simpson

index indicated a reduction in species diversity in the microwave-treated trials. Both

scenarios exhibited low evenness, pointing to a highly uneven distribution of species. The

strong shift towards *Clostridium sensu stricto 1* and the decrease in absolute species

number in the heat-treated experiments led to a more uneven distribution of species. This

generally low equal distribution is also mirrored in the taxonomic profile, which shows

that 20% to 28% of the microbiome consists of smaller groups of microorganisms with

less than 5% relative abundance.

Figure 3: (A) Microbial community as relative abundances differentiated according to

pretreatment. Only the most abundant microorganisms with abundance >5% are

presented. Others with abundances below 5% are summarized as "others < 5.0%". (B)

Alpha Diversity of the microbiome for genus level data of microwave and control

samples, loading rate 25 g/l of sucrose.

3.5 Production of volatile fatty acids

In general, the TVFA production was approximately 30 to 40 g/l for heat shocked experiments and between 35 and 55 g/l for non-pretreated ones. The thermal pretreated experiments demonstrated a significant shift of the acid balance towards butyric acid. In heat shocked experiments, the molar ratio of HBut/HAc was in a range from 1.13 to 2.05 (Figure 4B). Without thermal pretreatment, the HBut/HAc ratio was between 0.34 and 0.59. With the loading rate of 50 g/L and due to microwave assisted pretreatment, butyric acid concentration increased 2.77-fold up to 7.55 g/l. In contrast, the concentration of formic acid decreased to 24.02 g/l (0.75-fold). With the oven assisted pretreatment, butyric and formic acid reached similar concentrations with values of 10.80 g/l and 28.08 g/l respectively. Of the seven VFA analysed, formic, acetic and butyric acid were the most abundant ones (in sum >95%). Lactic and propionic acid showed rather low concentration, which is similar to results of Fang and Liu (2002). 2.73 g/l butyric acid and 31.97 g/l formic acid were formed in the untreated control reactions, with the same loading rate of 50 g/l. In none of the experiments were larger amounts of propionic or lactic acid present, although their formation is typical for processes with high loading rates (Oh et al., 2004). It can therefore be assumed that only a few propionic acid formers were already present in the seed sludge. Notable concentrations of iso-butyric acid (0.019 g/l) and valeric acid (0.007 g/l) could not be determined in any of the tests either. The formation of acetic acid was hardly influenced by the pretreatment, neither by the oven or the microwave. After an experimental period of seven days, pH values of 3.98 on average were measured in all experiments. At the start of the experiments, the pH value was generally 7.56. Based on Pineda-Muñoz et al. (2020), it can be assumed that acetic acid and as well the formic acid were increasingly formed with decreasing pH. Therefore,

it can be assumed that the ratio of butyric acid would be even higher if the pH would be

regulated.

*Figure 4: **(A)** Graphical representation of statistical significance (significant for p<0.05)*

of group comparisons for hydrogen and biogas volumes, hydrogen formation efficiency

and hydrogen fraction. Marker in grey area means a significant difference between the

*respective comparison groups. **(B)** Production of volatile fatty acids (median)*

differentiated by treatment method and feeding amount. Volatile fatty acids were

*analysed in triplicates in all cases. **(C)** Exemplary course of gas production over 7 days*

*and **(D)** first 24 hours for untreated (control) and heat shock treated (oven and*

microwave). Performed with sewage sludge and 75 g/l sucrose as feeding substrate.

3.6   The kinetics of hydrogen production after heat-shock application

In the untreated experiments, gas production commences immediately upon the

introduction of the feeding substrate, albeit at a slow pace for the initial 9 hours (Figure

4C and 4D, with 50 g/l sucrose as substrate). This was succeeded by a swift escalation

over the subsequent 7 hours. After approximately 16 hours of experimentation, there is a

noticeable plateau in gas production, which nearly halts entirely after about 96 hours. In

contrast, in the heat shock experiments, biogas production does not initiate until 6 hours

post-feeding but then ascends steeply and continuously until the 36th hour. The

subsequent rise is considerably less steep compared to the control experiment and nearly

ceases entirely after 108 hours. This pattern was observed with both pretreatment, oven

and microwave. The rate of gas formation in the heat-treated trials was less steep

compared to the untreated control (Figure 4C), yet the robust biogas formation remained

active for almost twice as long (30 hours) compared to the control trials (16 hours). The

experiments demonstrated that heat shock pretreatment results in a more uniform and

prolonged biogas production, significantly augmenting the total volume of biogas, albeit

with a delay in gas production for the initial six hours.

To better highlight, whether differences between the different treatments are significant,

statistical significance was assessed based on an ANOVA (Figure 4A). For example, at a

loading rate of 100 g/L of sucrose, there is no significant difference between microwave

and oven assisted pretreatment regarding hydrogen volume, biogas volume, efficiency

and hydrogen percentage.

3.7   Industrial relevance

The research conducted in this study indicates that one litre of heat-treated sludge can

yield an average of 5.92 m^3 of hydrogen per m^3 sludge at a loading rate of 50 g/L.

Subtracting the average values for the control from this, the heat treatment results in an

additional gain of 5.02 m^3 hydrogen per m^3 of sludge. The thermal energy required to

heat the seed sludge from 38°C to 80°C is 49.04 kWh/m^3, considering that it takes 4.2 kJ

to increase the temperature of 1l sludge by 1°C. The additional energy produced in form

of hydrogen due to the heat shocks corresponds to 54.18 kJ/l sludge, which corresponds

to 15.06 kWh/m^3 sludge. Based on the 49.04 kWh/m^3 for the heat shock, the energy loss

for the heat shock process is 33.98 kWh/m^3. This amount of energy must at least be

recovered using a heat pump, to make this concept energetically attractive.

Approved high-temperature heat pumps, which are currently available on the market, can

achieve a coefficient of performance (COP) of 4.3 when heating to 80°C from a starting

temperature of 20°C (as per data from ENGIE Refrigeration GmbH in 2018).   This

implies that 1 kWh of electrical energy can produce up to 4.3 kWh of thermal energy. To

generate 49.04 kWh of thermal energy, a heat shock requiring 11.4 kWh electrically

would be needed, assuming a coefficient of performance (COP) of 4.3. By this COP an

additional energy output of 3.66 kWh/m3 sludge compared to the calorific energy of the

extra hydrogen is produced by the heat shock. The process would also be energetically

profitable due to further energy losses during the heat exchange process with the sludge,

which are not considered here. Future technological improvements that raise the COP

could make enhanced hydrogen production through heat shocks even more sustainable.

Considering the varying costs of hydrogen and electric energy, the economic appeal of

the concept could remain intact even if the hydrogen equivalent of one kilowatt-hour is

priced higher than electricity itself. Based on Machhammer et al. (2015) and Bukold

(2020), a good benchmark for costs of hydrogen production is the average price for steam

reforming of 1.70€/kg H_2. The energy cost for a heat shock using a high temperature heat

pump with a COP of 4.3 would be 0.4€/m^3 of sludge, (based on an average industrial

electricity price of 35€/MWh. Selling the produced hydrogen at the same price of

1.70€/kg, would generate an average revenue of 0.91€ from the amount of hydrogen from

one cubic meter of heat shocked sludge. This translates to a profit of 0.51€/m^3 of sludge.

Despite a net energy loss, the production of hydrogen through heat shocks proves to be

more cost-effective compared to other alternative methods of hydrogen production. The

current hydrogen costs of hydrogen production without steam reforming range from

5.20€/kg, as reported by Gerloff in 2023, to 7.60€/kg, according to Machhammer et al. in

2015. Lowering the heat shock temperature could significantly decrease the energy

requirement and thus the essential costs, while potentially yielding similar or even higher

hydrogen yields (Baghchehsaraee et al., 2008). These calculations are based on ideal

assumptions and the successful scaling of trials in an industrial setting, with a particular

focus on electricity costs.

4   Conclusions

The presented experiments indicate that thermal shock pretreatment of the entire seed

sludge can trigger biohydrogen production from digested sewage sludge. Microwave heat

shocks, which were statistically equivalent to oven heat shocks in terms of hydrogen

production via dark fermentation, led to a less diverse microbiome and a strong increased

Clostridia growth. By using already available high-temperature heat pumps and

successful upscaling, heat shocks are energetically sustainable and economically

competitive with electrolysis for hydrogen production. A significant byproduct of

microwave heat shocks was the production of substantial amounts of butyric and formic

acid as potential future green platform chemicals.

Acknowledgements

We are grateful for funding of the work by the German Ministry of Economic Affairs

and Climate Action (grant numbers 49MF190057, 16KN070128, 16KN070126 and

16KN070163).

Data availability

The genome data will be published in the gene bank database of the National Center for

Biotechnology Information after acceptance of the paper.

References

Baghchehsaraee B, Nakhla G, Karamanev D, Margaritis A, Reid G. The effect of heat pretreatment
temperature on fermentative hydrogen production using mixed cultures. International Journal of
Hydrogen Energy 2008; 33(15): 4064–73.

Bolyen E, Rideout JR, Dillon MR, Bokulich NA, Abnet CC, Al-Ghalith GA, et al. Reproducible,
interactive, scalable and extensible microbiome data science using QIIME 2. Nat Biotechnol 2019;
37(8): 852–7.

Bukold S. Kurzstudie: Blauer Wasserstoff. Perspektiven und Grenzen eines neuen Technologiepfades.
Greenpeace Energy, https://green-planet-energy.de/fileadmin/docs/publikationen/Studien/blauer-
wasserstoff-studie-2020.pdf; 2020 [accessed November 3, 2023].

Cooney M, Maynard N, Cannizzaro C, Benemann J. Two-phase anaerobic digestion for production of
hydrogen-methane mixtures. Bioresource technology 2007; 98(14): 2641–51.

Eid M, Gollwitzer M, Schmitt M. Statistik und Forschungsmethoden. 5th ed. Weinheim: Beltz, 2017.
1088 p.

ENGIE Refrigeration GmbH. CO2-Kältemaschinen und CO2-Hochtemperaturwärmepumpen,
https://www.engie-refrigeration.de/sites/engie-refrigeration.de/files/2021-
08/DE_Folder_thermeco_Waermepumpen_web.pdf; 2018 [accessed November 3, 2023].

Fang HHP, Liu H. Effect of pH on hydrogen production from glucose by a mixed culture. Bioresource
technology 2002; 82(1): 87–93.

Gerloff N. Economic analysis of hydrogen production in Germany with a focus on green hydrogen,
considering all three major water electrolysis technologies. Sustainable Energy Fuels 2023; 7(8):
1893–907.

Hasyim R, Imai T, Reungsang A, O-Thong S. Extreme-thermophilic biohydrogen production by an
anaerobic heat treated digested sewage sludge culture. International Journal of Hydrogen Energy
2011; 36(14): 8727–34.

Kannaiah Goud R, Sarkar O, Venkata Mohan S. Regulation of biohydrogen production by heat-shock
pretreatment facilitates selective enrichment of Clostridium sp. International Journal of Hydrogen
Energy 2014; 39(14): 7572–86.

Lay J-J, Fan K-S, Chang J-1, Ku C-H. Influence of chemical nature of organic wastes on their conversion
to hydrogen by heat-shock digested sludge. International Journal of Hydrogen Energy 2003; 28(12):
1361–7.

Lee S, Lee DK. What is the proper way to apply the multiple comparison test? Korean Journal of
Anesthesiology 2018; 71(5): 353–60.

Luo G, Xie L, Zou Z, Wang W, Zhou Q. Evaluation of pretreatment methods on mixed inoculum for both
batch and continuous thermophilic biohydrogen production from cassava stillage. Bioresource
technology 2010; 101(3): 959–64.

Machhammer O, Bode A, Hormuth W. Ökonomisch/ökologische Betrachtung zur Herstellung von
Wasserstoff in Großanlagen. Chemie Ingenieur Technik 2015; 87(4): 409–18.

Oh S-E, Iyer P, Bruns MA, Logan BE. Biological hydrogen production using a membrane bioreactor.
Biotechnology and Bioengineering 2004; 87(1): 119–27.

O-Thong S, Prasertsan P, Birkeland N-K. Evaluation of methods for preparing hydrogen-producing seed
inocula under thermophilic condition by process performance and microbial community analysis.
Bioresource technology 2009; 100(2): 909–18.

Pineda-Muñoz CF, Conde-Baez L, Lucho-Constantino C, Medina-Moreno SA, Jiménez-González A.
Ultrasonic Energy Effect on Dark Fermentation by Ultrasound Application Alone and in Combination
with Heat Shock. Bioenerg. Res. 2020; 13(1): 334–48.

Quast C, Pruesse E, Yilmaz P, Gerken J, Schweer T, Yarza P, et al. The SILVA ribosomal RNA gene
database project: improved data processing and web-based tools. Nucleic Acids Res 2013;
41(Database issue): D590-6.

Rafieenia R, Lavagnolo MC, Pivato A. Pre-treatment technologies for dark fermentative hydrogen
production: Current advances and future directions. Waste Manag 2018; 71: 734–48.

Ruxton GD, Beauchamp G. Time for some a priori thinking about post hoc testing. Behavioral Ecology
2008; 19(3): 690–3.

Saady NMC. Homoacetogenesis during hydrogen production by mixed cultures dark fermentation:
Unresolved challenge. International Journal of Hydrogen Energy 2013; 38(30): 13172–91.

Sadooghi-Alvandi SM, Jafari AA, Mardani-Fard HA. One-way ANOVA with unequal variances.
Communications in Statistics - Theory and Methods 2012; 41(22): 4200–21.

Shingala MC, Rajyaguru A. Comparison of post hoc tests for unequal variance. International Journal of
New Technologies in Science and Engineering 2015; 2(5): 22–33.

Tao Y, Chen Y, Wu Y, He Y, Zhou Z. High hydrogen yield from a two-step process of dark- and photo-
fermentation of sucrose. International Journal of Hydrogen Energy 2007; 32(2): 200–6.

Wang D, Wang Y, Liu X, Xu Q, Yang Q, Li X, et al. Heat pretreatment assists free ammonia to enhance
hydrogen production from waste activated sludge. Bioresource technology 2019; 283: 316–25.

Wong YM, Wu TY, Juan JC. A review of sustainable hydrogen production using seed sludge via dark
fermentation. Renewable and Sustainable Energy Reviews 2014; 34: 471–82.

Zhu H, Béland M. Evaluation of alternative methods of preparing hydrogen producing seeds from
digested wastewater sludge. International Journal of Hydrogen Energy 2006; 31(14): 1980–8.

626 **Appendices**

Figure S1: Microbial community as relative abundances differentiated according to

pretreatment (loading rate 25 g/l). Only the microorganisms with abundance < 5% are

presented. Others with abundances below 0.5% are summarized as "others < 0.5%".

*Figure S2: Microbial community as relative abundances differentiated according to pretreatment. Loading rate was at 100 g/l sucrose. **(A)** Only the most abundant microorganisms with abundance > 5% are presented. Others with abundances below 5% are summarized as "others < 5.0%. **(B)** Breakdown of minor microorganisms below 5% abundance. Organisms with abundances below 0.5% are summarized as "others<0.5%".*