Title Page

1. Manuscript Title

Practical Bayesian Inference in Neuroscience: Or How I Learned To Stop Worrying and Embrace the Distribution

2. Abbreviated Title

Practical Bayesian Inference in Neuroscience

3. List all Author Names and Affiliations in order as they would appear in the published article

Brandon S Coventry[1] , Edward L Bartlett[2]

[1]Department of Neurological Surgery and the Wisconsin Institute for Translational Neuroengineering, University of Wisconsin-Madison, Madison, WI USA 53705
[2]Weldon School of Biomedical Engineering, Department of Biological Sciences, and the Institute for Integrative Neuroscience, Purdue University, West Lafayette, IN USA 47907

4. Author Contributions:

BSC and ELB designed research, analyzed data, and wrote the manuscript. BSC performed research and provided analytic tools.

5. Correspondence should be addressed to

Edward L Bartlett

email: ebartle@purdue.edu

6. Number of Figures: 7
7. Number of Tables: 2
8. Number of Multimedia: 0
9. Number of Words in Abstract: 197
10. Number of Words for Significance Statement: 97
11. Number of Words for Introduction: 662
12. Number of Words for Discussion: 719
13. Acknowledgements:

The authors would like to thank the anonymous reviewers for their helpful and constructive feedback on this article. Funding for experiments which generated young and aged responses to SAM stimuli was provided by the National Institutes of Health (NIDCD R01DC011580, PI: ELB). Funding for experiments generating INS dose-response data was provided by the Purdue Institute for Integrative Neuroscience collaborative training grant (PI: BSC).

14: Conflict of Interest

BSC and ELB hold a provisional patent (USPTO: 18/083,490) related to INS study data used in this article.

15: Funding sources

ELB: NIDCD R01DC011580

BSC: Purdue Institute for Integrative Neuroscience Collaborative Training Grant.

16. Code and Data Repository

https://github.com/bscoventry/BayesianNeuralAnalysis

ABSTRACT

Typical statistical practices in the biological sciences have been increasingly called into question due to

difficulties in replication of an increasing number of studies, many of which are confounded by the

relative difficulty of null significance hypothesis testing designs and interpretation of p-values. Bayesian

inference, representing a fundamentally different approach to hypothesis testing, is receiving renewed

interest as a potential alternative or complement to traditional null significance hypothesis testing due

to its ease of interpretation and explicit declarations of prior assumptions. Bayesian models are more

mathematically complex than equivalent frequentist approaches, which have historically limited

applications to simplified analysis cases. However, the advent of probability distribution sampling tools

with exponential increases in computational power now allows for quick and robust inference under any

distribution of data. Here we present a practical tutorial on the use of Bayesian inference in the context

of neuroscientific studies. We first start with an intuitive discussion of Bayes' rule and inference

followed by the formulation of Bayesian-based regression and ANOVA models using data from a

variety of neuroscientific studies. We show how Bayesian inference leads to easily interpretable

analysis of data while providing an open-source toolbox to facilitate the use of Bayesian tools.

Significance Statement

Bayesian inference has received renewed interest as an alternative to null-significance hypothesis

testing for its interpretability, ability to incorporate prior knowledge into current inference, and robust

model comparison paradigms. Despite this renewed interest, discussions of Bayesian inference are

often obfuscated by undue mathematical complexity and misunderstandings underlying the Bayesian

inference process. In this article, we aim to empower neuroscientists to adopt Bayesian statistical

inference by providing a practical methodological walkthrough using single and multi-unit recordings

from the rodent auditory circuit accompanied by a well-documented and user-friendly toolkit containing

regression and ANOVA statistical models commonly encountered in neuroscience.

Keywords: Bayesian Inference, Neural Data Analysis, Statistical Inference

Introduction

The scientific process generates new experiments and updates models based on quantitative

differences among experimental variables, evaluated by statistical inference. Inference tools are

foundational to these studies, providing the necessary machinery to make decisions and conclusions

from data. Frequentist-based null significance hypothesis testing (NHST) has been the gold standard of

inference in neuroscience and science at large in part due to the computational simplicity of frequentist

models compared to permutation sampling or Bayesian-based methods. A significant problem present

in the current practice of NHST, however, arises in the adoption of the p-value as the *de facto* metric of

experimental "success", notorious for its difficulty in interpretation and correct usage (Krueger and Heck,

2019). The confluence of exponential increases in computational power with the wider discussion of

problems with NHST usage has created renewed interest in Bayesian inference as an alternative to

frequentist NHST while offering interpretability benefits over the p-value and NHST overall.

The use of p-values thresholds as a ubiquitous decision rule in frequentist methods is fraught with

problems due to fundamental misunderstandings of its use, interpretability, and most pathologically, its

susceptibility to intentional and unintentional p-hacking(Nuzzo, 2014). Contrary to the initial intent of

Ronald Fisher(Fisher, 1992), the p-value has often become the gatekeeper of significance in studies. In

this role, it limits deeper observations into data, and it is often used without proper experimental design

to ensure proper use and control. Statistical inference methods require first defining a statistical model

with the power to adequately describe the data-generating process. Inference is then performed to

estimate the population distribution from limited samples of observed data. Once estimates of

population distributions are made, the determination of whether or not these distributions represent a

significant effect is determined. NHST is somewhat a victim of its own success, where common

practice has distilled the practice of NHST to chase the somewhat arbitrary $p < 0.05$ measure of

significance devoid of model or data considerations(Krueger and Heck, 2019). Furthermore, even in the best of experimental designs, the p-value is a surrogate for arguably what a researcher is most interested in: how likely is it that observed data has some effect different from null(Kruschke, 2011; Gelman and Shalizi, 2013).

Bayesian methods offer a solution to the problem of pathological p-value use and interpretation, providing a direct measure of the probability that observations have some effect(Kruschke, 2011; Gelman and Shalizi, 2013). This is done by reallocation of probability of possibilities as parameters in a mathematical model of the data-generating process, leading to probabilistic estimates desired by but not attainable with p-value analyses. Bayesian methods are inherently data-driven; models are built with prior knowledge directly incorporated from parameters estimated directly from observed data.

Bayesian inference, though chronologically younger than frequentist approaches, was not adopted as the primary inference paradigm due to the computational demands necessary to solve inference problems outside of certain canonical forms(Bishop, 2006) and the adoption of frequentist interpretation of probability(Fienberg, 2006). Inference on arbitrary distributions required a deeper mathematical knowledge and computation of integrals which were potentially intractable without modern numerical integration techniques. Frequentist paradigms however were more easily adapted to computationally simple algorithms, allowing researchers to "do statistics" without extensive formal training. However, exponential increases in computational power with the development of powerful Markov chain Monte Carlo (MCMC) sampling methods now allow researchers to perform meaningful Bayesian inference on arbitrary distributions underlying observed data(Gilks et al., 1996). While Bayesian approaches have received some attention for inference in electrophysiology(Wood et al., 2004; Wu et al., 2006; Vogelstein et al., 2009; Cronin et al., 2010; Gerwinn et al., 2010; Park and Pillow, 2011), the advantageous interpretability of inference and data driven nature found in Bayesian

statistics have of as yet been widely used in neuroscientific studies. This is in part a pedagogical problem, in that most neuroscientists do not encounter Bayesian statistics during formal training combined with the perception that a high level of mathematical acuity is necessary to perform Bayesian inference.

The goal of this tutorial is to remedy the opacity that often accompanies discussions of Bayesian inference by providing simple, step-by-step walkthroughs of Bayesian inference with four common inference paradigms utilizing tools that facilitate Bayesian computation for users at all levels of mathematical skill. We also aim to demonstrate the explanatory power of Bayesian inference in the context of neuroscience data. While the aim of this article is focused on application, this tutorial will begin with a brief introduction to Bayes' rule and its constituent components necessary for inference. For more theoretical and mathematical considerations of Bayesian inference, see the following books and articles(Gerwinn et al., 2010; Colombo and Seriès, 2012; Bielza and Larranaga, 2014; Kruschke, 2014; Kruschke and Vanpaemel, 2015; Ma, 2019; Gelman et al., 2021; Van De Schoot et al., 2021; Cinotti and Humphries, 2022).

Outline of Bayesian Methods

To best facilitate practical application of Bayesian inference methods in neuroscience, a variety of datasets were acquired and analyzed. Data acquisition paradigms are described in materials and methods below. Bayesian inference is introduced in the context of regression to infer changes in inferior colliculus single-unit firing from changing auditory stimuli. T-test-like group comparisons are demonstrated using computational models of basal ganglia thalamocortical local field potentials. Bayesian implementations of repeated measures and random effects models are demonstrated using chronic, multi-channel single-unit recordings from auditory cortex. Finally, Bayesian ANOVAs and ANCOVAs are utilized in assessing age-related changes in inferior colliculus single unit firing. All model

100 implementations are available in our Bayesian inference for neuroscience toolbox at

101 https://github.com/bscoventry/Practical-Bayesian-Inference-in-Neuroscience-Or-How-I-Learned-To-

102 Stop-Worrying-and-Embrace-the-Dist.

An Introduction to Bayesian Inference

105 Bayes' rule forms the basis for all Bayesian inference as the machinery to reallocate probability from

106 prior distributions and observed data to the posterior. While a full mathematical and computational

107 treatment of Bayes' rule is out of scope for this article, we begin by outlining the components of Baye's

108 rule, how inference is performed, and present a hypothetical experiment to show how priors might be

109 formed.

Bayes' Rule

Foundational to Bayesian approaches is a complementary, but epistemically differing view of

probability from that of frequentist approaches. While the frequentist perspective treats probability as

the relative frequency of the occurrence of some event, the Bayesian perspective instead treats

probability as the expectation of an event occurring which can be used to not only quantify the state of

knowledge of an event, but also the uncertainty involved in measuring an event(Bishop, 2006;

Kruschke, 2011, 2014; Van De Schoot et al., 2021). Traditionally, the Bayesian perspective has been

called 'belief'(Kruschke, 2010), a perhaps unfortunate name which belies the fact that the Bayesian

perspective of uncertainty of an event is fundamentally quantifiable. Perhaps a better description of

Bayesian belief is instead quantification of the state of knowledge by accounting for uncertainty. The

cornerstone of Bayesian inference is Bayes rule, defined as:

122
$$P(H|E) = \frac{P(E|H)P(H)}{P(E)}$$

123   where H is the quantification of the state of a hypothesis, and E is the quantification of observed

124   evidence. In the context of inference, it is helpful to explicitly state the role of the model in Bayesian

125   formulations:

126
$$P(\theta|E,M) = \frac{P(E|\theta,M)P(\theta|M)}{P(E|M)}$$

where M is the model of the data generating process and θ are the model parameters. The individual

components of Bayes' rule are given names corresponding to the purpose they serve, with $P(\theta|E,M)$

called the posterior distribution, $P(E|\theta,M)$ the likelihood function, $P(\theta|M)$ the prior distribution, and

$P(E|M)$ the evidence or marginal likelihood function. Taken together, Bayes' equation represents the

quantification of observed data accounting for prior knowledge(Fig 1A). Each component plays a key

role in Bayesian inference and each will be discussed briefly below.

The Model Evidence

The denominator term $P(E|M)$, called the model evidence (or just the evidence or marginal likelihood in

Bayesian parlance) is the quantification of the probability of observing the data under a chosen model

of the data generating function. At first glance, the calculation of the total evidence appears to be an

insurmountable task. In reality this term is the weighted average of parameter values in a given model

weighted by the relative probability of a given parameter value(Kruschke, 2014) and thus acts as a

normalization term to ensure the numerator is a proper probability distribution. The structure of $P(E|M)$

will change based on whether the distributions represent probability mass functions (discrete case) or

probability density functions (continuous case). In the discrete case, the evidence is

143
$$P(E|M) = \sum_{\theta} p(E|\theta,M)\,p(\theta|M)$$

144   and in the continuous case:

145
$$P(E|M) = \int p(E|\theta,M)p(\theta|M)d\theta$$

The evidence function thus represents an average of the likelihood function across all parameter

values conditioned on the prior distribution. The marginal likelihood can also be utilized to assess the

plausibility of two competing models(Johnson et al., 2023). The evidence, especially in the continuous

case, is historically what made Bayesian inference difficult due to the need to evaluate a complex

integral numerically. However, the advent of Markov-chain Monte Carlo (MCMC) methods with

improvements in personal computer processing power has allowed for computationally efficient

integration without the need for supercomputing hardware. MCMC methods will be discussed in a

subsequent section.

The Prior

The prior, $P(\theta|M)$, is often the major stumbling block for those entering into Bayesian inference, but

this hurdle is less about the prior, and more about what the prior is perceived as. The prior, $P(\theta|M)$

describes the investigators prior beliefs on the state of knowledge of the study. While normally

distributed priors are common, the prior can take the form of any proper probability distribution. Critics

of Bayesian inference have described the prior as purely subjective, but we, and many

others(Kruschke, 2010; Box and Tiao, 2011; Gelman and Shalizi, 2013), argue that the prior represents

an explicit declaration of the investigators knowledge, assumptions, and the general state of a field

which is implicit and often is present but not stated in frequentist approaches. Moreover, one is

encouraged to perform prior predictive checks to compare the sensitivity of competing priors in a

Bayesian inference model, as we will show subsequently. The practice of the design of experiments

and their resulting publications are rife with implicit priors which are often not acknowledged or realized

when reporting results. As an example, consider study of cortical extracellular single unit

recordings(Paninski et al., 2004; Bartlett and Wang, 2007; De La Rocha et al., 2007; Coventry et al.,

2024 as illustrative examples). The investigator could be leading a project with vast knowledge

accumulated over years of study. Or the investigator is a trainee of a career researcher who draws a

view of cortical physiology from their experienced mentor mixed with reading current literature. When
designing an experiment, the investigator will have some intuition regarding likely and biologically
feasible resting state and stimulus-evoked firing rates, cognitively assigning relatively low likelihood of
seeing extremes of firing rates with higher likelihood assigned to moderate firing rates previously
observed in literature or seen in experiments, and likely will discard or treat as outliers firing rates on
the extremes or thought to be non-biological noise. The power of the prior distribution in Bayesian
approaches is in part the need to explicitly quantify and report these prior beliefs, which can be
analyzed and scrutinized as part of the peer review or post-publication process. Prior distributions also
require investigators to consider their biases and relative expectation on the importance of previously
recorded and read data, promoting a deeper understanding of not only the data obtained within their
lab, but also of the general state of the specific neuroscience field. As the name implies, prior beliefs
are quantified as probability distributions by the investigators.

This begs the question as to what a prior might look like in newer avenues of study where a paucity of
data exists. Or in situations where researchers and data analysts want the data to "speak for itself"
outside any influence of the prior. In these cases, priors can be designed to be "non-informative" or
"weakly-informative", assigning broad, non-committal distributions to the prior. One might assign a
uniform distribution on the prior, effectively treating each parameter outcome as equally likely.
Uniformly distributed priors do require some caution, however, as any parameter value outside of the
bounds of the uniform distribution is automatically assigned probability 0 in the posterior, even if that
value has been observed(Fig 1B Left). In many cases, it's better to allow small, but nonzero
probabilities to extreme values, such as the tails of a normal distribution, such that evidence for
unexpected events is represented in the posterior given strong data(Fig 1B Right). Conversely, priors
can be made to be highly informative in situations where physiological bounds are well known and well-
studied, where extreme values are known to be biophysically irrelevant or impossible or known to be

due to instrument noise(e.g. large 50/60 Hz noise peak in power spectrum indicative of wall power

noise).

The Likelihood

The likelihood function, $P(E|\theta, M)$ describes the probability that data is observed given parameter

values θ in a data generating model M. In the context of inference, the likelihood function updates

information given in a prior distribution to the posterior distribution given the observed data(Etz, 2018).

The likelihood function is generally not a proper distribution, in that it is conditioned on yet unknown

parameters and may not integrate to 1, but the evidence and prior terms ensures that resultant

posterior distributions are true probability densities. The idea of likelihood functions are present in both

Bayesian and frequentist models, but have vastly different interpretations. The model parameters in a

frequentist viewpoint converge upon singular values learned, usually though maximum likelihood

estimation, from merging competing hypotheses of data. Bayesian approaches treat model parameters

as ranges arising from distributions after observing the data at-hand.

The Posterior

The prior, likelihood, and evidence then form the posterior $P(\theta|E, M)$, the reallocation or mapping of

probability from likelihood function, prior, and model evidence to an all-encompassing distribution. The

posterior thus is the evidence for parameters θ conditioned on observed data and a model of the data

generating function. The posterior forms the basis for inference, with all relevant information encoded

in its distribution. Inference on the posterior distribution is covered in a section below.

Estimation of the Posterior

Despite Bayes' rule being formulated before Fisher's description of frequentist methods, a major

reason that Bayesian inference was not been widely adopted was fundamentally a computational one,

in that evaluation of Bayes' rule often requires solving non-trivial integrals. A subset of computationally

tractable prior distributions and likelihood functions formed canonical posteriors in which the posterior is

easily inferred. However, these cases are not generalizable to experimental data which can be noisy

and not well behaved. Modern Markov-chain Monte-Carlo (MCMC) tools have been developed to

quickly and easily estimate arbitrary distributions. MCMC involves the generation of random samples

which converge to a target probability distribution, the details of which can be learned from the

following reviews(Hoffman and Gelman, 2011; Betancourt, 2017).

Making Decisions on the Posterior

We define inference broadly as the process by which reasoning and decisions about a phenomena are

made from a sample of observations of the phenomena. Incorporation of prior knowledge in Bayesian

inference allows for optimal decision making on observed data(Blackwell and Ramamoorthi, 1982). The

posterior contains all necessary information to make inferences on experimental data incorporating

prior knowledge. However, it is best to consider the specific goals of inference before performing

statistics. Possible goals of inference are as follows(Kutner et al., 2005; Kruschke, 2014):

•   Infer the parameters of a model.

•   Reject or confirm a hypothesis, null or otherwise

•   Compare two or more competing models

In the case of neuroscientific studies of unit electrophysiology, inferring model parameters occurs when

an experiment aims to establish how neural firing rates change with changes in applied stimuli. Or one

may want to confirm or reject a null hypothesis that a treatment has the desired effect or that there are

differences between neural populations. Importantly, because the Bayesian inference operates solely

on the posterior distribution, one can confirm or reject competing hypotheses and not simply reject the

null as in frequentist NHST.

Regardless of the goal, inference always involves analyzing the posterior, which provides a complete

representation of the distribution of a given parameter given the experimental data. Therefore,

decisions about the data, the effect of model parameters, and/or which hypothesis has more evidence

is performed with calculations on the posterior. There are multiple decision rules that can be used to

assess the posterior. The most common, and in our opinion, the most intuitive is that of the Bayesian

credible interval. The confidence interval calculates the probability that a population parameter lies in a

certain interval. As credible intervals are not strictly unique, Bayesian inference convention is to fix the

interval to the smallest interval which contains 95% of the posterior distribution density mass called the

highest density interval (HDI). Observations of posterior HDIs can then be used to assess the relative

effect of a parameter. Regions of practical equivalence (ROPE) may be included in the posterior

distribution that explicitly define a range of values that are effectively equivalent to a null value, with

parameters considered significant if 95% of the posterior distribution (95% HDI) does not contain 0 or

any values in the ROPE (Kruschke, 2018). Along with posterior HDIs, calculations of maximum *a*

posteriori (MAP, distribution mode) estimates from the posterior are performed to quantify a most likely

parameter value. While decision rules are important to assess the relative effect of statistical model

parameters, we reiterate that simply passing a decision rule should not conclude the inference step.

Inference should be made in context of the evidence presented in model quality checks, observed data

posterior distributions, and decision metrics.

A Simple Example of Bayesian Applications in Neuroscience

As a simple, motivating example of how priors and likelihoods can be derived in neuroscientific studies,

consider a hypothetical *in vitro* whole-cell patch clamp experiment recording a cortical neuron (Fig 1E).

The experimental details are less important than the formulation of Bayesian models, but are given in

some detail to help visualize the hypothetical study. Consider a study to assess the effect of a novel

drug on firing rates of a specific class of cortical neuron. The goal of the study is to assess the change

in the firing frequency versus injection current before and after drug application during current-clamp

recording. Before the beginning of the experiment, the graduate student surveys the knowledge (i.e. a

literature search) surrounding these neurons and assigns a broad, normally distributed prior centered

around the average firing rates of these cortical neurons across all studies surveyed. The logic to this

prior is that while firing rate distribution to this novel drug is not known, the totality of observed firing

rates reasonably approximates the range of possible firing states of that neuron. The graduate student

runs the study, plots the distribution of observed results and finds that drug application produces small

increases in mean firing rates that are very consistent between trials and cells, as evidenced by

relatively tight distributions of data (Fig 1E left, observed data distributions). However, the overlap of

naive and drug conditions means that quantification of the uncertainty of measurement of the drug

effect must be performed in the form of the MAP and credible intervals in each condition. The

distributions of evoked firing rates as a function of injected currents are the data encoded in the

likelihood function. After completion of the experiment, the advisor of the graduate student noticed that

both *in vitro* and *in vivo* data were included in the prior, even though firing rates differ dramatically

between those preparations in previous work. Re-running the analysis with the highly informed prior

based on in vitro data produces a similar result, but with a slight reduction in the uncertainty in the

difference of group means as measured by group mean difference MAP estimates and credible

intervals. In this case, comparing weakly and strongly informed models also shows that relatively

drastic changes in the prior make minor changes in posterior estimates, suggesting that observed data

is the primary driver of inference and is not unduly influenced by the prior. Taken together, both broad,

minimally informative and highly informative priors often lead to similar decisions on the data and are

useful for cases where prior knowledge is sparse. However, when prior knowledge is available,

incorporating more information in the form of an informative prior backed by data provides reduction in

uncertainty in estimation of study effects.

This simple example shows one way in which priors and likelihoods are defined in neuroscience

studies in a manner that most researchers unknowingly do by running experiments and reading the

literature. The prior serves to take intrinsic prior knowledge and quantify it to provide more transparent

reporting of experimental results. Furthermore, data forms the likelihood function, facilitating inference

that makes decisions on the data at hand while accounting for prior knowledge of the state of a

particular field. It also introduces the idea of using model comparison to assess prior influence on

inference, which will be rigorously explored below.

Inference Using Null Significance Hypothesis Testing

While theoretical comparisons of Bayesian inference vs NHST are out of scope for this article, a brief

description of decision-making using NHST is warranted to orient Bayesian inference. For detailed

descriptions and discussions of NHST, see the following reference texts and articles(Kutner et al., 2005;

Nieuwenhuis et al., 2011; Maris, 2012; Kruschke, 2014; Bzdok and Ioannidis, 2019). Proper NHST

experimental design is performed before data acquisition with sample size, statistical tests, and

significance levels set to achieve a desired level of statistical power. However, proper NHST

experimental design is largely not followed, in part due to lack of proper statistical training and external

career pressure(Munafò et al., 2017) as well as the relative difficulty in data acquisition(Button et al.,

2013). We believe that Bayesian approaches provide a way to do statistics more in line with current

neuroscientific practice, in which beliefs about data are updated as data is acquired, informed by the

current state of the field. Statistical power relies on estimates of population variances and differences in

group means. We note that this is somewhat analogous to the declaration of prior distributions in

Bayesian inference. After data is acquired using the predefined stopping rule, NHST inference is then

performed. Similar to Bayesian inference, NHST utilizes a parameterized likelihood function(Fig 1C)

that describes the data-generating process. The null hypothesis is the likelihood function descriptive of

a nonexistent effect. Statistical significance is most commonly assessed through the p-value metric, a

measure quantifying the probability of obtaining a value of a given test statistic at least as extreme as

the test statistic observed under the assumption of a null hypothesis. Another common metric for

statistical significance and parameter estimation is the confidence interval, which utilizes sample

distributions to estimate parameters of the population distribution. Importantly, unlike data-driven

Bayesian approaches, both p-values and confidence intervals draw inference using in part data that is

not observed, owing from calculations over hypothetical replications of an experiment(Wagenmakers,

2007; Kruschke, 2014). Comparisons between Bayesian methods and NHST are summarized in Table

1.

Error Quantification and Model Comparison

Critical to any statistical model and inference therein is its fit to observed data. While it is entirely

possible to perform linear regression on data distributions which are highly nonlinear, predictions and

inference made by the model will likely be inaccurate. Both Bayesian and frequentist inference offer

robust model error quantification. Bayesian approaches, however, can utilize the posterior distribution

to not only quantify and bound the distribution of model errors, but also include *post hoc* posterior

predictive sampling as part of the inference paradigm. Posterior predictive sampling involves making

random draws from the posterior and building a sampling distribution. This distribution is then

compared to the observed data distribution to quantify the model's disparity from observed data. Along

with posterior predictive checks, prior predictive checks act as a sensitivity measure of the influence of

the prior distribution on the posterior distribution. Taken together, Bayesian inference thus allows for

robust statistical inference on observed experimental data which appropriately includes prior

knowledge of the state of the field.

Formulation of Models and Applied Bayesian Inference

There are a multiplicity of programs and programming languages that facilitate Bayesian analysis, such

as standalone programs of Jasp(Love et al., 2019) and probabilistic programming language packages

such as BUGS(Brooks, 2003) and STAN(Carpenter et al., 2017), we chose to use PyMC(Salvatier et

al., 2016) for its ease in explicitly declaring probability distributions and its implementation in Python

which is in common use in neuroscientific data analysis. Model formation is often conserved between

frequentist and Bayesian approaches; it is only the mode of inference that differs. However, for clarity,

we will discuss both model formation and performing inference in the subsequent sections.

Materials and Methods

Bayesian inference was performed on a range of data typical to neuroscience experiments. Regression

models, ANOVA models, and group comparisons are performed on single-unit activity recorded from

inferior colliculus (IC) neurons in response to auditory stimuli in young and aged rats(Palombi et al.,

2001; Simon et al., 2004; Rabang et al., 2012; Herrmann et al., 2017). Random-effects regression

models are performed on single units recorded in the auditory cortex (A1) using high-density recording

arrays in response to infrared neural stimulation(Izzo et al., 2007; Cayce et al., 2011, 2014; Coventry et

al., 2024) of the medial geniculate body (MGB). All surgical procedures used in this study were

approved by the Institutional Animal Care and Use Committee (PACUC) of Purdue University (West

Lafayette, IN, #120400631) and in accordance with the guidelines of the American Association for

Laboratory Animal Science(AALAS) and the National Institutes of Health guidelines for animal research

Computational Hardware

To underscore that meaningful Bayesian inference does not require cluster computing or extensive

computational resources, all computations were performed on a Windows MSI GS-66 laptop with an

Intel i7 processor with an Nvidia RTX2070 GPU. Our inference programs are CPU-bound, not requiring

any GPU resources. Computations can be performed on most modern CPUs, but are accelerated with

more CPU threads and cores and parallelization on GPUs.

Bayesian Linear Regression and Analysis of Covariance Assessment of the Disruption

of Temporal Processing in the Inferior Colliculus Due to Aging

The inferior colliculus (IC) is the major integrative center of the auditory pathway, receiving excitatory

inputs from ventral and dorsal cochlear nuclei, excitatory and inhibitory inputs from the lateral and

medial superior olivary complex(Kelly and Caspary, 2005) and inhibitory inputs from superior

paraolivary nucleus and the dorsal and ventral nuclei of the lateral lemniscus(Cant and Benson, 2006;

Loftus et al., 2010). The IC encodes auditory information through hierarchical processing of input

synaptics with local IC circuitry(Caspary et al., 2002; Rabang et al., 2012; Grimsley et al., 2013). Age-

related changes in auditory processing primarily arise as deficits in temporal processing(Frisina and

Frisina, 1997; Parthasarathy et al., 2010; Parthasarathy and Bartlett, 2012; Herrmann et al., 2017).

This dataset is composed of single unit responses recorded from young (Age$\leq$ 6 months) and aged

(age $\geq$ 22 months) Fisher 344 rats. Auditory brainstem responses were recorded from animal subjects

a few days prior to surgery to ensure hearing thresholds were typical of the rodent's age. Single unit

recordings were performed in a 9'x9' double-walled, electrically isolated anechoic chamber (Industrial

Acoustics Corporation). Animals were initially anesthetized via a bolus injection of ketamine (VetaKet,

60-80 mg/kg) and medetomidine (0.1-0.2 mg/kg) mixture via intramuscular injection. Oxygen was

maintained via a manifold and pulse rate and blood oxygenation monitored through pulse oximetry.

Supplemental doses of ketamine/medetomidine (20 mg/kg ketamine, 0.05 mg/kg medetomidine) were

administered intramuscularly as required to maintain surgical plane of anesthesia. An incision was

made down midline and the skull exposed. Periosteum was resected and a stainless steel headpost

was secured anterior to bregma via 3 stainless steel bone screws. A craniectomy was made above

inferior colliculus (-8.5 anterior/posterior, 1 mm medial/lateral from bregma). A single tungsten

electrode was advanced dorsally towards the central nucleus of the inferior colliculus (ICC) during

which bandpass noise (200 ms, center frequencies 1-36kHz in five steps per octave, 0.5 octave

bandwidth) was delivered. ICC was identified based on short-latency driven responses to bandpass

noise search stimuli with ascending tonotopy and narrowly tuned responses to pure tones of varying

frequencies. Once neurons were identified, responses from 5-10 repetitions of sinusoidal amplitude-

modulated tones (750 ms tone length, modulation depth between -30 to 0 dB) were recorded using a

preamplifying headstage (RA4PA, Tucker-Davis Technologies) and discretized at a sampling rate of

24.41 kHz (RZ-5, TDT). Sinusoidal amplitude-modulated tones were defined as:

$$s(t) = A[1 + m * cos(2\pi f_m t + \varphi)] * n(t)$$

403 where m is modulation depth ranging between $0.032 - 1 \, (-30 - 0 \, dB)$, f_m the modulation frequency, φ

404 the reference phase of the modulator, A is the scaling factor for stimulus sound level, and $n(t)$ the

405 broadband noise stimulus. SAM stimuli are schematized in Fig 2C. Single units were filtered between

406 0.3 and 5 kHz. Offline spike sorting was performed using OpenExplorer (TDT).

Bayesian Multilinear Regression Assessment of Thalamocortical Recruitment From Infrared Neural Stimulation

Infrared neural stimulation (INS) is an optical technique using coherent infrared light to stimulate nerves

and neurons without the need for genetic modification of the target or direct contact with tissue that

offers spatially constrained activation above electrical stimulation(Wells et al., 2005, 2005; Izzo et al.,

2007; Cayce et al., 2011, 2014; Coventry et al., 2020, 2024). In this study, rats were chronically

implanted in A1 with 16 channel planar Utah-style arrays (TDT, Alacua FL) and stimulating optrodes in

the medial geniculate body of auditory thalamus (Thor Labs, Newton NJ). Rodents were initially

anesthetized with a bolus injection of a ketamine (80 mg/kg) and medetomidine (0.2 mg/kg) cocktail.

Oxygen was maintained via a manifold and pulse rate and blood oxygenation monitored through pulse

oximetry. Supplemental doses of ketamine/medetomidine (20 mg/kg ketamine, 0.05 mg/kg

medetomidine) were administered intramuscularly as required to maintain surgical plane of anesthesia.

An incision was made down midline and the skull exposed. The periosteum was removed via blunt

dissection and 3 stainless steel bone screws were placed in skull for headcap stability. An additional

titanium bones crew was placed in skull to serve as a chronic ground and reference point for recording

electrodes. Craniectomies were made above medial geniculate body (-6 anterior/posterior, -3.5

medial/lateral from bregma) and auditory cortex (-6 anterior/posterior, -5 medial/lateral from bregma).

Fiber optic stimulating optrodes were placed in the midpoint of MGB (-6 dorsal/ventral from dura) and

affixed to the skull using UV-curable dental acrylic (MidWest Dental). A 16 recording channel planar

array was putatively placed in layers 3/4 of auditory cortex, with placement confirmed by short-latency

high amplitude multiunit activity elicited from band pass noise (200 ms, center frequencies 1-36kHz in

five steps per octave, 0.5 octave bandwidth) test stimuli. Recording electrodes were sealed onto the

headcap. Animals were allowed to recover for 72 hours prior to the beginning of the recording regime.

All recordings were performed in a 9'x9' electrically isolated anechoic chamber. During recording

periods, animals received a intramuscular injection of medetomidine(0.2 mg/kg) for sedation. Optical

stimuli were delivered from a 1907 nm diode laser (INSight open source optical stimulation system)

coupled to the optrode with a 200 μm, 0.22 NA fiber (Thor Labs FG200LCC). Laser stimuli were

controlled via a RX-7 stimulator (TDT) and consisted of train stimuli with pulse widths between 0.2-10

ms, interstimulus intervals between 0.2-100 ms and energy per pulse between 0-4 mJ. Applied laser

energies were randomized to limit effects from neural adaptation with 30-60 repetitions per pulse

width/interstimulus interval combinations. Signals from recording electrodes were amplified via a

Medusa 32 channel preamplifier and discretized and sampled at 24.414 kHz with a RZ-2 biosignal

processor and visualized using Open-Ex software (TDT). Action potentials were extracted from raw

waveforms via real-time digital band-pass filtering with cutoff frequencies of 300-5000 Hz. Single units were extracted offline via superparamagnetic clustering in WaveClus (Quiroga et al., 2004). Studies were performed to assess the dose-response profiles of optically-based deep brain stimulation over the span of several months. As each electrode recorded diverse populations of neurons which are potentially subject to change due to electrode healing in, age of the device, and adaptation to the stimulus, a within subjects, repeated measures regression model was warranted. Bayesian hierarchical regressions can easily deal with complex models such as these. This data was part of a previous study(Coventry et al., 2024).

Bayesian T-Test Assessment of Computational Models of Basal Ganglia Thalamocortical Function in Parkinson's Disease

Parkinson's disease is a chronic and progressive neurological disorder resulting from a loss of dopaminergic neurons in the substantia nigra of the basal ganglia circuit(Dickson, 2018; Bove and Travagli, 2019). Computational models of basal ganglia thalamocortical function provide insight into alterations of circuit dynamics as well as potential therapeutic targets. In prior work, a modified mean-field basal ganglia thalamocortical (BGTC) model (Grado et al., 2018; Coventry and Bartlett, 2023) was implemented to study network deep brain stimulation encoding mechanisms in dopamine depleted states. In the case of BGTC circuits, mean-field modeling consists of the average extracellular electric field response of collections of neurons with cellular properties modeled after each stage of the BGTC circuit in both healthy and dopamine depleted states(Van Albada and Robinson, 2009). In each model trial, local field potentials (LFP) were recorded from the globus pallidus internus in resting state and stimulation conditions. Stimulation trials consisted of subthreshold (0.01 mA, 100μs pulse width, 130 Hz) or suprathreshold (1.8 mA, 240μs pulse width, 130 Hz) deep brain stimulation of the subthalamic nucleus. LFP activity in the β band (13-30 Hz) is a known biomarker for Parkinson's

465 symptomology(Little et al., 2013; Guidetti et al., 2021), so LFP power spectral density estimates of β

466 band activity were calculated. Total LFP power in the β band was calculated as follows:

$$P_{Tot} = 2 \sum_{f=13}^{30} P_{xx}(f)\Delta f$$

468 where P_{xx} is the power spectral density at frequency f, Δf reflecting model sampling rate, and the factor

469 2 accounting for frequency folding from Fourier decomposition.

Results

Estimation of Spike Rates from Auditory Stimuli: A Motivating Example

To facilitate the discussion of Bayesian inference in neuroscience, consider an example found

prominently in auditory neuroscience(Fig 2). In our first experiment, single unit recordings were made

from the inferior colliculus (IC) in response to applied sinusoidal amplitude-modulated tones (SAM, see

Methods). The goal of this analysis is to create a linear model of SAM temporal auditory processing by

quantifying increases in evoked single-unit firing rates in response to decreased SAM modulation depth.

The linear regression model seeks to estimate a linear relationship between one (simple linear) or more

(multilinear) predictor and measured variables. In this model, both the measured result and predictors

are metric, as opposed to categorical, variables which map to a continuum of possible values. The

simple linear regression model takes the form of:

482
$$y = \alpha + \beta x + \epsilon$$

where y is the measured (predicted) group, x is the predictor, β is the "slope" parameter dictating the

relative increase or decrease in y per unit change in x, α is the intercept term which, in models of firing

rate represents non-evoked, spontaneous firing rates, and ϵ is an error term which quantifies the

difference between the expected value of y at a given x given a linear model versus the observed

value of y at x. It should be noted that ϵ is not present in all regression models, but the authors suggest

inclusion to quantify deviations from linear fit.

Linear regression thus forms a model in which SAM depth predicts evoked firing rates in which the

model parameters are estimated and used to draw conclusions about the relative dependency of y on

x. To begin, an observation of the relative distribution of the measured data, in this case firing rates

elicited from IC, will allow for robust inference model design. Data distributions are most often

visualized through construction of data histograms. Probability density functions (pdf) can then be

estimated through kernel density estimation (KDE), a process in which data points are convolved with

gaussian kernels to create a smooth estimation of underlying continuous data pdfs(Rosenblatt, 1956;

Parzen, 1962). Inspection of the distribution of firing rates (Fig 2B) suggests that a log transform would

allow for the data to be normally distributed, making model computations easier through use of

canonical normal distributions.

Performing Bayesian Inference on the Linear Regression Model

Turning back to the example of IC single unit firing rates in response to SAM depth stimuli, the first step

in inference is to place a prior distribution on the data. Previous studies and data can be used to inform

the prior, but for this example we chose to demonstrate regression with moderately informative priors

on $\alpha, \beta,$ and ϵ so as to let observed data drive posterior inference. Given that the observed data is

roughly normal, a good first pass is to place a normal distribution on the prior with mean equal to the

mean of the observed data and a variance that is wide enough to capture all observed data. After

inference is made, sensitivity analyses can be performed to assess the relative importance of the prior

parameter values on posterior estimates. Larger prior variances allow for small, but non-zero

probabilities on extreme values. This tends to be a more robust approach than setting a value of 0 on

extreme events, as observed data with strong evidence for an extreme value can be adequately

represented in the posterior. After observation of the underlying distribution of the observed data and

decision on a prior distribution, a linear regression inference model can be easily described in code as

follows:

Code Example 1: PyMC initialization of a simple linear regression model

```python
with pm.Model() as regression:        #Define a model that we call regression
    a = pm.Normal('a', mu=prMean, sigma = 5) #Normally distributed prior on a
    B = pm.Normal('B', mu=prMean, sigma = 5) #Normally distributed prior on B
    eps = pm.HalfCauchy("eps", 5)            #Model error prior
# Now we define our likelihood function, which for regression is our regression
function
    reg = pm.Deterministic('reg', a + (B*modDepth))
    likelihood = pm.Normal('Y',mu = reg, sigma = eps, observed = fir-
ingRate)
#Deterministic is for non probabilistic data. This is a modification to help sam-
pling, inference is still probabilistic.
```

518 The likelihood variable then translates our model to one of Bayesian inference by casting the model as

519 a probability distribution, in this case

520
$$y \sim N(\alpha + \beta x + \epsilon)$$

Importantly, Bayesian inference does not require any extra preprocessing of the data outside of what is

dictated by the experimental design. In this case, we are interested in estimating assessing the

interplay of varying modulation depth on maximum firing rates. Our raw data then is estimated mean

firing rates calculated from PSTHs, which are incorporated into the regression model in the "observed"

variable in the likelihood function. To generate the posterior, all that needs to be done is to initialize and

run MCMC as follows:

Code Example 2: Running the MCMC sampler

```
with regression:                    #Access our defined model
    trace = pm.sample(numSamples, tune=numBurnIn, target_accept=0.90,chains = 4)
    #4 parallel, independent MCMC chains.
```

This routine calculates the regression model, generating a trace variable containing the posterior

distributions of all model parameters after sampling numSamples with numBurnIn samples to initialize

chains. We also ran 4 chains in parallel with a target_accept probability of 90%. Acceptance probability

is somewhat based on the statistics of observed data and model, with more difficult posteriors

benefiting from higher accept probability values(Gilks et al., 1996). Improper acceptance probabilities

can give rise to insufficient number of draws and malformation of posterior distributions. PyMC provides

a helpful readout for when posterior draws are malignant and indicative of higher acceptance

probabilities. In summary, in a few lines of code the researcher has observed distributions of the data

and explicitly defined a model of the data generator and likely now has a better intuition of the data and

how it is distributed. All that's left to observe the posteriors with HDIs to infer significance from the

model.

Plotting the 95% HDI estimation of the regression line (Fig 3A) of modulation depth vs natural log-

transformed firing rates suggest a small but significant increase in firing rates with increases in

modulation depth as evidenced by a 95% HDI credible region (0.015-0.022) that does not include zero

from the β posterior distribution (Fig. 3B). A MAP value of 0.018 represents the most probable slope

value from the regression. Posterior distributions of model parameters (Fig. 3B) also show that there is

an estimated basal firing rate above 0 (α MAP = 3.1) with model error terms considered small for being

significantly smaller than intercept term ($\in$ MAP = 0.74). The spread of the 95% HDI on inferred

parameters is used as a measure of uncertainty of the parameter, with narrow HDIs representing more

certainty in MAP estimated parameter. In our model, the α parameter has a spread between 3.02 to

3.13, with a difference of 0.11 containing 95% of its posterior distribution, suggesting strong certainty in

552 the MAP estimate of 3.1. Similar narrow spread is see in the β parameter, with a difference of 0.007

553 containing 95% of the posterior. The model error term shows that observed data deviation from the

554 model is constrained between 0.71 and 0.76 suggesting relative certainty in the magnitude of deviation

555 of the data from the model. In the context of regression, these posterior results can be interpreted as a

556 mean firing rate increase by a factor of 1.02 (2%, $e^{0.018}$) per percentage change in SAM depth that

557 follows a most probable model of

558
$$ln(mean\ Firing\ Rate) = 3.1 + 0.018 * modDepth + 0.74$$

560 The $\propto$ term in the context of this study represents the natural log firing rate for 0% modulation,

561 corresponding to a pure tone stimulus. Statistical conclusions should not end after making inferences

562 on model parameters however. Critical to the validity of statistical inference is the quality of the model

563 fit to observed data. This goodness of fit in Bayesian approaches can be analyzed by posterior

564 predictive checks, in which sample draws are made from the posterior distribution, simulating

565 observations of data generated from the experiment from which the statistical model was fit, and

566 comparing sampled to observed data to assess deviation of model predictions from observed data

567 distributions. In PyMC, posterior predictive checks can be easily performed using the following code:

569 *Code Example 3: Performing posterior predictive checks*

```
"""
Now let's do some posterior predictive checks. PyMC has some nice functions
that make this quite easy. We will also sample the posterior distribution for the
standard 16,000 samples, which for this posterior should be more than enough.
    """
    with regression:
        ppcRegression = pm.sample_posterior_predictive(trace, random_seed=Random-
        seed)
        #The above code envokes the regression mode, then uses the posterior from
        the trace, pulling synthetic samples to compare to observed. Random seed
        is set so that each run can be perfectly replicated
    az.plot_bpv(ppcRegression, hdi_prob=0.95,kind='p_value')
        #Bayes p-values, similar to frequentist,can be used to assess if posterior
        predictive is sufficiently close to observed density. Should be centered
        around 0.50.
    az.plot_ppc(ppcRegression)
    az.plot_trace(trace,var_names=['a', 'B','eps'])
    plt.show()
```

To illustrate how posterior predictive checks can be used, a competing model was made which

performs Bayesian linear regression to the same data and priors except without log transformation of

the data. In each case, random draws were made from each log transformed and non-log transformed

posteriors to create empirical data distributions. Comparison of empirical distributions qualitatively

show that log-transformed models present a better fit to observed data than non-log transformed

models. The relative disparity between posterior predictive model fits and observed data can be

quantified by use of Bayesian p-values(Fig 3C), a distance measure between two distributions(for

details of Bayesian p-values, see Kruschke, 2014). The closer the Bayesian p-value is to 0.5, the better

data sampled from the posterior overlaps with the distribution of observed data. Plotting the resulting

distributions and the Bayesian p-values indeed show the log-transformed model fits better to observed

data than the non-transformed model. Similar analyses can be performed around model free

parameters, such as prior variables, to form a sensitivity analysis of our of prior distributions on

resulting posterior inferences.

A secondary and quick check of posterior sampling can be performed by qualitative evaluation of the

MCMC sampling chains, often called traces. Traces represent the long term run of a Markov chain

which represent the distribution of interest. As such, good traces show evidence of effective sampling

and convergence to target probability distributions. PyMC offers easy ways to visualize posterior

MCMC traces using the *plot_trace* function. Figure 4 shows traces obtained from our Bayesian

regression example. Kernel density estimates of traces corresponding to the posterior distributions of

regression parameters show good convergence of MCMC traces to a target distribution (Fig 4A). As

MCMC chains are time series samples which form a distribution, evaluation of traces through sampling

time can also be used as a diagnostic of sampling convergence. Traces should have a "fuzzy

caterpillar" like appearance (Fig 4B) without any stark jump discontinuities from sample to sample.

Quantitative trace evaluations are also available, with the Gelman-Rubin statistic ($\hat{r}$) being the most

prominent. The Gelman-Rubin statistic measures the variance between MCMC chains to the within

chain variance, effectively measuring chain stationarity and convergence(Gelman and Rubin, 1992).

Heuristically, $\hat{r} < 1.05$ is considered good convergence of MCMC chains. This value can be calculated

post hoc after sampling and PyMC will automatically flag if $\hat{r} \geq 1.05$ is detected.

Inference Reporting Guidelines

Proper presentation of statistical methods and processes is critical to the interpretation of conclusions

drawn from inference. While there are many reporting guidelines for Bayesian inference, we follow the

Bayesian Analysis Reporting Guidelines as given by Kruscke(Kruschke, 2021) and provide an

example reporting document including posterior predictive checks, Bayesian model comparisons, and

sensitivity analysis in our Github code repository.

T-Tests and Comparison of Groups

Comparison of differences between two or more groups is one of the most fundamental inference

paradigms, ubiquitous to all fields of neuroscience. Frequentist implementations of group comparisons,

such as the t-test and χ^2-tests, suffer from similar ailments as frequentist regressions: strict

assumptions about distributions of observed data, lack of interpretability of group differences, and the

inability to confirm a null hypothesis. Added to these is that of the multiple comparisons problem, with

increasing number of comparisons leading to increasing type-I errors. Bayesian implementations of

group comparisons provide complete descriptions of group differences in means, variances, and effect

sizes, the ability to confirm and not simply reject null hypotheses, and complete posterior distributions,

which remove the need for multiple comparisons corrections(Gelman et al., 2009; Kruschke, 2011,

2013). One implementation of Bayesian group comparisons is Bayesian estimation Supersedes the t-

Test (BEST)(Kruschke, 2013), consisting of a hierarchical model with data described by t distributions

and minimally informative priors on group means and standard deviations.

Comparison of β-Band Dynamics in a DBS Model Using BEST

To illustrate the use of BEST in group comparisons, a computational model of the dopamine-depleted

basal ganglia thalamocortical circuit was utilized (Fig 5A). Simulations consisted of measurements of

oscillatory activity in local field potential (LFP) β-band (13-30Hz), elevation of which is a known

biomarker for Parkinsonian symptomology across the basal ganglia circuit(Singh, 2018). "No

stimulation", in no stimulation, subthreshold "sham" stimulation, and effective DBS stimulation groups

were tested. LFPs were recorded from globus pallidus internus and stimulation in subthalamic nucleus

with 2000 repetitions of each group performed. Figure 5B shows example LFP power spectrums for no

stimulation, subthreshold stimulation, and DBS conditions respectively, with reductions in β-band

activity shown in DBS conditions compared to no stimulation and subthreshold stimulation respectively.

Posterior distributions allow for estimates of group means and standard deviations of LFP β power (Fig

5C) with qualitative observations of non-overlapping credible regions of means (DBS: 0.46-0.47, No

stimulation: 0.86-0.88) and standard deviations (DBS: 0.036-0.041, No stimulation: 0.068-0.078)

suggesting that DBS produces strong reductions in β power. Unlike frequentist methods, direct

measurements of differences in group means are easily quantified from subtraction of group posterior

distributions. We reiterate that unlike frequentist methods, this inference is formed directly from

observed data, and not conditioned on hypothetical population distributions. Differences in group

means show strong reductions in β-band power in DBS conditions (MAP estimate $\mu_{DBS} - \mu_{nostim} =$

-0.4) with MAP estimates of effect size showing strong, discernible evidence of DBS effect in

reducing β oscillatory activity (MAP = -6.9). Differences in group means and effect size are

considered significant because 95% HDIs do not contain 0.

Estimation of group differences further shows the explanatory power of Bayesian inference in its ability

to provide direct, probabilistic estimates of group summary statistics, group differences, and effect

sizes. Bayesian approaches with appropriate priors are also more robust to sample size, particularly

lower sample sizes that are typical of many neuroscience experiments(Smid et al., 2020). To illustrate

this, we utilized frequentist t-test and BEST inference, comparing no stimulation and subthreshold

stimulation groups. BEST and t-test estimates on these groups should confirm a null hypothesis/ fail to

reject the null hypothesis respectively given no effect of subthreshold stimulation on LFP β-band

activity. In this study, random study stopping points were simulated by performing BEST and t-test

estimates on increasing sample sizes (2-1000, steps of 5). Data points were pulled from random

permutation of no stimulation and subthreshold stimulation groups. BEST estimation showed rapid

convergence to estimated group differences of 0 at low sample sizes, while frequentist p-values

showed strong fluctuations regardless of sample size (Fig 5D). P-value oscillations showed several

instances of falling below $p < 0.05$ decision criteria, even at sample sizes larger than the majority of

neuroscientific experiments. While p-value dynamics are contextual, based on data type and

underlying data distributions, this data shows the potential of NHST to draw drastically different

experimental conclusions from sampled data distributions with very similar sample sizes.

Multilinear Regressions, Repeated Measures, and Hierarchical Models

In many experiments, inference across multiple possible data generating parameters must be analyzed

and accounted for. These models, called multilinear regressions, are extensions of standard linear

regression as follows:

$$y = X^T\beta + \epsilon \rightarrow y = \beta_0 + \beta_1 x_1 + \beta_2 x_2 \ldots + \beta_n x_n + \epsilon$$

where n is the total number predictors.

To illustrate the use of multilinear regressions, consider the case of thalamocortical infrared neural

stimulation (INS)(Fig 6A). Auditory thalamic neurons in the medial geniculate body were excited by

pulse trains of optical stimuli varying in pulse energy and time between pulses. The resulting auditory

cortex single unit responses are recorded using a planar, Utah style array in layer 3/4. An important

and understudied aspect of INS is the effect of laser energy and interstimulus interval changes on

evoked firing rate responses; a so-called dose-response curve. We begin by specifying predicted and

predictor values. Dose-response relationships were measured by predicting maximum firing rates in

response to applied INS energy (E) and inter-pulse intervals (ISI). As we suspect an interaction

between E and ISI, an interaction term of E*ISI was incorporated. Therefore, the model was defined as:

$$\max(FR) = \alpha + \beta_1 E + \beta_2 ISI + \beta_3 (E * ISI) + \epsilon$$

An important aspect of this study was that rats underwent chronic recordings through the duration of

the lifetime of the implant. It almost a certainty that stimulation and recording quality will change over

the lifetime of the devices due to neural adaptation to stimulation(Falowski et al., 2011) and glial

response and encapsulation of the devices(Van Kuyck et al., 2007; Woolley et al., 2013). This

experimental paradigm is thus complicated by potentially meaningful repeated measures within subject

variability. Furthermore, slight differences in electrode and optrode placement between rodents could

create a heterogeneity in the receptive fields of recorded neurons(Vasquez-Lopez et al., 2017),

representing a potentially meaningful between-subject variance.

Hierarchical Structures Capture Latent Variables

Models in both Bayesian and frequentist paradigms capture these within and between subject

variances by adding hierarchical structure to the model. From the Bayesian perspective, hierarchical

models are defined by allocating hyperparameters on the prior which encode within and between group

variances in the model, with each hyperparameter containing hyperprior distributions. Graphically, this

is organized in Fig 6B. Bayesian and frequentist hierarchical models share similar roots, with particular

hyperprior distributions in Bayesian paradigms becoming proportional to frequentist random effects

models.

While this appears to be a herculean task in data modeling, PyMC allows for declarations of

hierarchical models, as shown in Code Snippet 4:

Code Example 4: Creating a hierarchical regression model

```python
animal_code_idx = data.animal_code.values        #Encodes within and between
subject variances as parameter indices
    with pm.Model() as Heirarchical_Regression:
        # Hyperpriors for group nodes
        mu_a = pm.Normal("mu_a", mu=0.0, sigma=1)
        sigma_a = pm.HalfNormal("sigma_a", 5)
        mu_b = pm.Normal("mu_b", mu=0.0, sigma=1)
        sigma_b = pm.HalfNormal("sigma_b", 5)
        mu_b2 = pm.Normal("mu_b2",mu=0.0, sigma=1)
        sigma_b2 = pm.HalfNormal("sigma_b2",5)
        mu_b3 = pm.Normal("mu_b3", 1)
        sigma_b3 = pm.HalfNormal("sigma_b3",5)

        sigma_nu = pm.Exponential("sigma_nu",5.0)
        #Base layer
        nu = pm.HalfCauchy('nu', sigma_nu)          #Nu for robust regression
        a_offset = pm.Normal('a_offset', mu=0, sigma=1, shape=(n_channels))
        a = pm.Deterministic("a", mu_a + a_offset * sigma_a)
        # Declare Regression parameters under a normal distribution
        b1_offset = pm.Normal('b1_offset', mu=0, sigma=1, shape=(n_channels))
        b1 = pm.Deterministic("b1", mu_b + b1_offset * sigma_b)

        b2_offset = pm.Normal("b2_offset",mu=0, sigma=1, shape=(n_channels))
        b2 = pm.Deterministic("b2", mu_b2 + b2_offset*sigma_b2)

        b3_offset = pm.Normal("b3_offset",mu=0, sigma=1, shape=(n_channels))
        b3 = pm.Deterministic("b3", mu_b3 + b3_offset*sigma_b3)
        #Add in the error term
        eps = pm.HalfCauchy("eps", 5,shape=(n_channels))
        #Declare regression model
        regression = a[animal_code_idx] + (b1[animal_code_idx] *
    XenergyPerPulse) + (b2[animal_code_idx] * XDist)
    +(b3[animal_code_idx]*XenergyPerPulse*XDist)
      #Encode model into likelihood function
        likelihood =
    pm.StudentT("MaxZ_like",nu=nu,mu=regression,sigma=eps[animal_code_idx],
    observed= MaxZ)
```

Owing to the scarcity of thalamocortical INS data, we assigned noninformative, wide spread normal

distributions on the priors and hyperpriors so as to let the data speak for itself. We also utilized a

student-T distribution as the likelihood function to accommodate outliers in a modification known as

"robust regression"(Kruschke, 2014). Student-T distributions have tails which are not bounded by the

exponential function, meaning that extreme values have less impact or skew on the posterior

distribution. Half-Cauchy distributions are placed on the error term and Student-T normality parameter

v. Half-Cauchy distributions are advantageous in learning scale parameters from the data in

hierarchical models (Gelman, 2006; Polson and Scott, 2012).

It is important to validate that our model and data generating functions indeed represent the observed

data. Sensitivity analyses and posterior predictive checks thus can be performed to ensure the model

chosen is the one that best describes the observed data. Sensitivity analyses were performed by

varying prior variance and comparing models which were nominal or natural log transformed with

normal and student-T likelihood functions. Model comparisons can be performed in many ways, but a

common paradigm is the leave-one-out cross validation (LOO)(Gelman et al., 2014). LOO consists of

partitioning data into training and test sets and iteratively fitting the model under test with training data

and testing out of sample fits with test data. Models are then ranked using the expected log pointwise

predictive density (ELPD) measure:

718
$$ELPD = \sum_{i=1}^{k} \int dy_i p_t \bar{y_i} \log\left(p(\bar{y_i}|y)\right)$$

where p_t, y_i are unknown distributions representing the true data generating function for estimates of

true posterior predictive function $(\bar{y}|y)$ from observed data y(Vehtari et al., 2017). In general, larger

values of ELPD represent better out of sample fits indicative of a better model conditioned on observed

data. We can then use standard errors between the model with the best ELPD (dse) and all competing

models to rank all models to observed data. Importantly, these metrics should be understood only in

the context of a model relative to other models, and not a global predictor of model validity.

Observations of posterior fits to the data using posterior predictive fits and Bayesian p-values should

be utilized on the final model to determine model fit. This seemingly complex model comparison can be

quickly and easily done in PyMC with the following commands:

Code Example 5: Model Comparisons

```
Var5_loo = az.loo(trace_Var5)
Var100_loo = az.loo(trace_Var100)
df_comp_loo = az.compare({"Var5": trace_Var5, "Var100": trace_100})
```

Model comparison results are given in Table 2~~1~~. Similar to the simple regression above, the log

transformed model provided much better fits to observed data than non-log transformed models.

Interestingly and instructively, moderately informative priors (variance 5) outperformed noninformative

priors (variance 100), suggesting that constraining prior variance can have predictive power in

inference. Posterior predictive checks on the winning model show good fits to observed data with a

Bayesian p-value near 0.5.

We can now perform inference on our multi-regression model. It was found (Fig 6C) that α was

significantly above 0 (MAP = 2.2, 95% HDI does not cross 0) suggesting that basal firing rates of

recorded neurons were typically above 0 as expected. It was also seen that maximal firing rates were

significantly dependent on applied INS energy (β_1 MAP = 0.58, HDI does not cross 0) with increases in

INS energy leading to larger evoked maximal firing rates. The relative spread of the 95% HDI on β_1 of

0.27-0.88 suggests a heterogeneity in neuron dose-response characteristics that can be explored more.

Somewhat surprisingly, there was no significant effect of ISI on maximum firing rates (β_2 MAP = -

0.055). The relative spread across 0 of -0.45 to 0.3 suggests that extreme values of ISI might

potentially have an effect, with smaller ISIs causing neural integration of singular INS pulses into a

singular, large pulse. However, that cannot be determined given the INS parameters used in this study.

Also surprisingly, there was no significant effect of Energy-ISI interactions (β_3 MAP = 0.028),

suggesting that INS energy is the primary mediator of evoked firing rates.

Bayesian ANOVAs

Comparison of differences between groups is another routine statistical procedure used when predictor

variables are nominal or categorical in nature or a mixture of metric and categorical predictors. The

frequentist treatment of these experimental designs largely uses analysis of variances methods,

namely ANOVA for categorical predictors and, more generally, ANCOVAs for categorical predictors

with metric covariates. ANOVAs are models that take the form of:

756
$$y = \alpha + \sum_i \beta_i x_i$$

where β_i, x_i are the parameters corresponding to nominal predictor class i, α is the offset or bias

parameter, and y is the metric dependent variable. ANOVA parameters and class values β_i, x_i are

treated differently than the regression case, as x_i are categorical as opposed to continuous, metric

values. As such x categories are recast into "one-hot" encoded vectors $\vec{x} = [x_0, x_1, ..., x_i]$ in which only a

singular value in an array can have a value of 1 and all other elements are cast to 0, allowing for binary

indication of a given class among a group of classes. If an individual value falls into group j, for

example, $\vec{x}_{i \neq j} = 0, \vec{x}_{i=j} = 1$. The coefficients β_i then encodes the change in dependent variable y from

inclusion of datapoint x in category i. Importantly, deflections from baseline are constrained such that

$\sum_i \beta_i = 0$. Both Bayesian and frequentist ANOVA models treat β_i parameters as group deflections

about the baseline level of the dependent variable.

ANCOVA is a modification to the ANOVA model to include a metric covariance term:

$$y = \alpha + \sum_i \beta_i x_i + \beta_{co}, x_{co}$$

where β_{co}, x_{co} are the parameters corresponding to metric predictors. Metric predictors terms are

valuable in accounting for within group variance which is attributable to some other metric measurable

variable, such as decreased firing rates in response to an applied stimulus found in a class of aged

animals.

Bayesian analogues of ANOVA and ANCOVA can be easily defined in PyMC and are termed BANOVA

and BANCOVA (Fig 7A) respectively to distinguish models from their frequentist counterparts.

Traditional ANOVAs make two key assumptions; that underlying data is normally distributed and a

homogeneity of variance among groups. To account for these assumptions, normal distributions are

placed on prior parameter and observed data distributions and a uniform distribution prior is placed on

observed data variance σ_y. Importantly, observed data distributions should be assessed to assure

distributions are normally distributed. While not strictly an ANOVA-like structure, an advantage of

Bayesian approaches is the ability to create models which handle arbitrary distributions. While

traditional ANOVAs also assume independent group variances, the relative shared influence between

groups can be learned from the data by imposing a hyperprior on group variance σ_β (Gelman, 2006). As

with any prior distributions, selection of σ_β should be informed by prior inspection of the data. A Half-

Cauchy distribution is once again chosen as it weakly informative and allows for extreme values if data

dictates(Gelman, 2006; Polson and Scott, 2012). Setting σ_β to a large constant replicates a traditional

ANOVA.

As a guiding example, consider a similar experiment to that done in simple linear regression. In this

experiment, we aim to understand age-related changes in IC auditory processing of sinusoidal

amplitude modulated sounds. This experiment consisted of two groups of young (animals < 6 months

in age) and aged (animals > 22 months in age). SAM stimuli at increasing modulation depths were

played to the animals with evoked single unit responses recorded from IC. As seen in the previous

simple linear regression experiment (Fig 3), there is a significant increase in evoked firing rate with

increased modulation depth in young animals. As such, it should be included in comparison between

the two groups. Taken together, this suggests BANCOVA will serve as an appropriate model.

BANCOVAs are inherently hierarchical(Gelman, 2005; Kruschke, 2014) (Fig 7A) to allow for between

subject variances to be represented in the prior if these variances mutually inform one another. Setting

this hyperprior to a constant creates a model analogous to a frequentist ANCOVA(Kruschke, 2014).

The formation of the BANCOVA is again relatively straightforward:

Code Example 6: Creating a Bayesian ANCOVA

```python
with pm.Model() as BANCOVA:
        #Define hyperprior on sigma
        bSigma = pm.HalfCauchy('bSigma',2.0) #Recommended by Gelman, this
parameter doesn't overemphasize 0 on sigma.
        #Define Prior, likelihood distributions. Relatively noninformative
        a = pm.Normal('a',yMean,sigma = np.sqrt(yStDv))
        B = pm.Normal('B',0,sigma=bSigma,shape=numCategories)
        Bcov = pm.Normal('Bcov',yMean,sigma = np.sqrt(yStDv))
        sigmaLikelihood = pm.Uniform('sigmaLikelihood',yStDv/100,yStDv*10)
        BancovaModel = a + B[ClassAge] + (Bcov*(modDepth - modDepthMean))
        y = pm.Normal('y',mu=BancovaModel,sigma = yStDv,observed=firingRate)
        #Now, make sure model coefficients sum to 0 to create an ANOVA-like
structure
        aScaled = pm.Deterministic('aScaled',a+aesara.tensor.mean(B) + Bcov*(-
modDepthMean))
        bScaled = pm.Deterministic('bScaled',B - aesara.tensor.mean(B))
```

with inference made in the exact same way as the previous models.

After model sampling, posterior sampling checks were performed to ensure posterior distributions

adhere well to observed data. Posterior predictive distributions show good qualitative fit to observed

firing rate data with Bayesian p-values centered around 0.51, suggesting good model fits to observed

data (Fig 7B). Comparisons between groups is simple once posterior distributions are obtained. Similar

to Bayesian group comparisons (BEST, Fig 5), all that needs to be done is to measure differences

between aged and young group mean parameter posteriors (Fig 7C), encoding influence of young and

age groups on firing rates. Aged and young contrasts show significantly elevated firing rates in young

rats across all SAM stimuli (Young-aged difference MAP = 0.25, 95% HDI excludes 0). Another

advantage of Bayesian inference is the ability to observe the distribution, and thus the most likely value

and spread of effect size. In this analysis, the effect of age in SAM stimulus processing is significant but

small (effect size MAP =0.058, 95% HDI excludes 0) but with a wide spread of effect (95% HDI

between 0.025-0.64) suggesting variable temporal acuity between rodent subjects. Finally, firing rates

vs SAM amplitude depth for each class are plotted with $y = \alpha + \beta_{young/age} x_{young/age} + \beta_{cov} x_{cov}$

superimposed.

Multiple Comparisons in Bayesian Inference

In traditional frequentist analyses, corrections for multiple comparisons are necessary in order to

ensure that maximum Type I errors (false positives) are constrained to a maximum of 5% ($\alpha = 0.05$).

With Bayesian inference, a posterior distribution across all parameters is obtained which remains

unchanged no matter how many comparisons are made(Kruschke, 2014). Furthermore, frequentist

type I errors are classically defined in the context of rejection of a null hypothesis. Bayesian inference is

not strictly concerned with rejection of a null hypothesis, instead weighing competing hypotheses given

observed data. Bayesian models are not immune to making false conclusions about data. These errors,

called type M for errors in magnitude and type S for errors in sign occur when outliers in data exert too

much influence on inference. These errors can be controlled by proper choice of priors or by building

hierarchical models (Fig 6A, Fig 7A) which can account for outliers by pulling parameters towards

group means when evidence is small and allowing parameters with good evidence to remain in a

phenomenon called partial pooling implicit to hierarchical structures(Gelman et al., 2009).

Discussion

Bayesian inference approaches present a powerful statistical tool which encourages deep and

meaningful exploration of data and allows for presentation of data in intuitive and transparent ways. In

this tutorial, we demonstrate the ease by which Bayesian inference can be performed across a wide

variety of experimental designs and provide source code which can be modified to accommodate

neuroscientific experiments using all free and open source tools. We intentionally used the base PyMC

toolchain in order to explicitly show Bayesian model creation. However, there are PyMC plugin tools

such as Bambi (Capretto et al., 2022) which can facilitate creation of Bayesian models in single lines of

code. An example of Bambi-enabled model creation is provided in our Bayesian inference toolbox.

Applications of Bayesian Inference

In this tutorial, our inference examples largely focused on data commonly found in electrophysiology

and computational neuroscience studies. However, Bayesian inference is agnostic to the form and type

of data used in inference. The described statistical models are easily adapted to

electroencephalography, neuroanatomical measures, behavioral measures, and calcium events,

among others. Bayesian inference is of particular interest to neuroscience experiments involving very

large datasets, such as spatial transcriptomics (Gregory et al., 2022; Song et al., 2022).

We also focused primarily on canonical statistical model structures of t-test group comparisons, simple

regression, ANOVAs, and mixed-effect models. Bayesian models can further be defined for other

statistical models such as logistic, Poisson, and ridge regressions, mixture of Gaussians, and time-

series analysis.

Tempering Expectations of Bayesian Inference

Despite the enthusiasm of some Bayesian advocates, Bayesian inference is not a panacea. It is

subject to similar problems as frequentist NHST, in that models can be used which do not adequately

fit underlying data statistics or priors can be chosen which dominate model performance and

deemphasize observed data. However, Bayesian approaches support and encourage model

transparency, requiring researchers to declare model priors and posteriors while encouraging

continued discussion of inference on data as opposed to stopping if a p-value is below an arbitrary

threshold. A second caveat is that running MCMCs can be slower than frequentist approaches, with run

times sometimes in minutes as opposed to seconds. However, time increases are not astronomical and

can be further reduced to levels similar to frequentist approaches by using GPU computing or using

programs such as JASP(Love et al., 2019) which utilize a C backend to speed up computation.

The Controversy of the Prior

The prior is arguably the most contentious aspect of Bayesian inference, with arguments that the prior

unduly influences decisions on data. It is absolutely possible to have priors that distort posterior

distributions into poor inference. Similar arguments can be levied at Frequentist approaches which

perform similar distortions on decision metrics, such as applying ANOVA tests when underlying data is

not normal. Often times, these mistakes are not done out of malevolence, but due to the modern

framework of how statistics is performed. We argue that having to consider what prior to use, and thus

what one's assumptions are, what distributions are physiologically relevant, and the distributions of

observed data will help to prevent errors in statistical modeling while creating greater transparency in

how conclusions on data are drawn.

Decisions with Bayes Factors

Some studies which utilize Bayesian inference use a decision metric called a Bayes' factor, which is a

measurement of the ratio of marginal likelihoods of two competing models providing log likelihood of

evidence for one model over another(Johnson et al., 2023). We intentionally chose not to utilize Bayes'

factor metrics because, in the authors' opinions, they reduce inference to evaluation of a single metric

over an arbitrary threshold, as opposed to analysis over posterior distributions of observed data.

Furthermore, certain prior declarations yield undefined Bayes' factors(Gelman and Rubin, 1995)

potentially encouraging using suboptimum models in order to provide arbitrary decision metrics.

Bayesian and Frequentist Approaches: A Holistic Approach to Inference

Following in the steps of Bayarri and Berger(Bayarri and Berger, 2004), data analysis should not

consist solely of Bayesian or frequentist approaches devoid of the other. There are certainly cases

where frequentist approaches should be used, such as clinical trials where preregistration and proper

protocol design can provide bounds on false-positive and false negative rates necessary for translation

of medical therapeutics. Hybrid frequentist and Bayesian approaches can also provide richer insight

into analyses where posterior distributions are unidentifiable or difficult to sample(Raue et al., 2013) or

in identifying when improper models have been chosen(Berger et al., 1997). Bayesian ideas of

posterior predictive checks and model comparisons can also be applied to frequentist NHST, many of

which would help address problems of replication and data transparency. As frequentist approaches

are often baked into the pedagogy of neuroscience and neural engineering, we aim for this tutorial to

be a thorough introduction into the application of Bayesian statistics to help develop a toolkit which can

be used for robust data analysis or in conjunction with previously established frequentist approaches.

These models are also easily extendable into Bayesian analogs of logistic or multinomial regressions,

gaussian mixture models, Bayesian time series analyses, among many more.

Code and Data Availability

The code/software and data described in this paper is freely available online at
https://github.com/bscoventry/Practical-Bayesian-Inference-in-Neuroscience-Or-How-I-Learned-To-
Stop-Worrying-and-Embrace-the-Dist. The code is available as Extended Data.

References

908 Bartlett EL, Wang X (2007) Neural Representations of Temporally Modulated Signals in the Auditory
909    Thalamus of Awake Primates. J Neurophysiol 97:1005–1017.

910 Bayarri MJ, Berger JO (2004) The Interplay of Bayesian and Frequentist Analysis. Stat Sci 19 Available
911    at: https://projecteuclid.org/journals/statistical-science/volume-19/issue-1/The-Interplay-of-
912    Bayesian-and-Frequentist-Analysis/10.1214/088342304000000116.full [Accessed August 5,
913    2023].

914 Berger JO, Boukai B, Wang Y (1997) Unified frequentist and Bayesian testing of a precise hypothesis.
915    Stat Sci 12 Available at: https://projecteuclid.org/journals/statistical-science/volume-12/issue-
916    3/Unified-frequentist-and-Bayesian-testing-of-a-precise-hypothesis/10.1214/ss/1030037904.full
917    [Accessed August 8, 2023].

918 Betancourt M (2017) A Conceptual Introduction to Hamiltonian Monte Carlo. Available at:
919    https://arxiv.org/abs/1701.02434 [Accessed July 26, 2023].

920 Bielza C, Larranaga P (2014) Bayesian networks in neuroscience: a survey. Front Comput Neurosci 8
921    Available at: http://journal.frontiersin.org/article/10.3389/fncom.2014.00131/abstract [Accessed
922    November 2, 2023].

923 Bishop C (2006) Pattern Recognition and Machine Learning, 1st ed. New York, NY: Springer.

924 Blackwell DL, Ramamoorthi RV (1982) A Bayes but Not Classically Sufficient Statistic. Ann Stat
925    10:1025–1026.

926 Bove C, Travagli RA (2019) Neurophysiology of the brain stem in Parkinson's disease. J Neurophysiol
927    121:1856–1864.

928 Box GEP, Tiao GC (2011) Bayesian Inference in Statistical Analysis, 1st ed. Germany: Wiley.

929 Brooks SP (2003) Bayesian Computation: A Statistical Revolution. Philos Trans Math Phys Eng Sci
930    361:2681–2697.

931 Button KS, Ioannidis JPA, Mokrysz C, Nosek BA, Flint J, Robinson ESJ, Munafò MR (2013) Power
932    failure: why small sample size undermines the reliability of neuroscience. Nat Rev Neurosci
933    14:365–376.

934 Bzdok D, Ioannidis JPA (2019) Exploration, Inference, and Prediction in Neuroscience and
935    Biomedicine. Trends Neurosci 42:251–262.

Cant NB, Benson CG (2006) Organization of the inferior colliculus of the gerbil (Meriones
unguiculatus): Differences in distribution of projections from the cochlear nuclei and the
superior olivary complex. J Comp Neurol 495:511–528.

Capretto T, Piho C, Kumar R, Westfall J, Yarkoni T, Martin OA (2022) **Bambi** : A Simple Interface for
Fitting Bayesian Linear Models in *Python*. J Stat Softw 103 Available at:
https://www.jstatsoft.org/v103/i15/ [Accessed August 29, 2023].

Carpenter B, Gelman A, Hoffman MD, Lee D, Goodrich B, Betancourt M, Brubaker M, Guo J, Li P,
Riddell A (2017) *Stan* : A Probabilistic Programming Language. J Stat Softw 76 Available at:
http://www.jstatsoft.org/v76/i01/ [Accessed August 5, 2023].

Caspary DM, Palombi PS, Hughes LF (2002) GABAergic inputs shape responses to amplitude
modulated stimuli in the inferior colliculus. Hear Res 168:163–173.

Cayce JM, Friedman RM, Chen G, Jansen ED, Mahadevan-Jansen A, Roe AW (2014) Infrared neural
stimulation of primary visual cortex in non-human primates. NeuroImage 84:181–190.

Cayce JM, Friedman RM, Jansen ED, Mahavaden-Jansen A, Roe AW (2011) Pulsed infrared light alters
neural activity in rat somatosensory cortex in vivo. NeuroImage 57:155–166.

Cinotti F, Humphries MD (2022) Bayesian Mapping of the Striatal Microcircuit Reveals Robust
Asymmetries in the Probabilities and Distances of Connections. J Neurosci 42:1417–1435.

Colombo M, Seriès P (2012) Bayes in the Brain—On Bayesian Modelling in Neuroscience. Br J Philos
Sci 63:697–723.

Coventry BS, Bartlett EL (2023) Closed-Loop Reinforcement Learning Based Deep Brain Stimulation
Using SpikerNet: A Computational Model. In: 11th International IEEE EMBS Conference on
Neural Engineering, pp 1–4. Baltimore, Maryland USA.

Coventry BS, Lawlor GL, Bagnati CB, Krogmeier C, Bartlett EL (2024) Characterization and closed-
loop control of infrared thalamocortical stimulation produces spatially constrained single-unit
responses. PNAS 3(2) Nexus:pgae082.

Coventry BS, Sick JT, Talavage TM, Stantz KM, Bartlett EL (2020) Short-wave Infrared Neural
Stimulation Drives Graded Sciatic Nerve Activation Across A Continuum of Wavelengths. In:
2020 42nd Annual International Conference of the IEEE Engineering in Medicine & Biology
Society (EMBC). IEEE.

Cronin B, Stevenson IH, Sur M, Körding KP (2010) Hierarchical Bayesian Modeling and Markov
Chain Monte Carlo Sampling for Tuning-Curve Analysis. J Neurophysiol 103:591–602.

De La Rocha J, Doiron B, Shea-Brown E, Josić K, Reyes A (2007) Correlation between neural spike
trains increases with firing rate. Nature 448:802–806.

Dickson DW (2018) Neuropathology of Parkinson disease. Parkinsonism Relat Disord 46:S30–S33.

Etz A (2018) Introduction to the Concept of Likelihood and Its Applications. Adv Methods Pract
Psychol Sci 1:60–69.

Falowski SM, Sharan A, Reyes BAS, Sikkema C, Szot P, Van Bockstaele EJ (2011) An Evaluation of
Neuroplasticity and Behavior After Deep Brain Stimulation of the Nucleus Accumbens in an
Animal Model of Depression. Neurosurgery 69:1281–1290.

Fienberg SE (2006) When did Bayesian inference become "Bayesian"? Bayesian Anal 1 Available at:
https://projecteuclid.org/journals/bayesian-analysis/volume-1/issue-1/When-did-Bayesian-
inference-become-Bayesian/10.1214/06-BA101.full [Accessed October 23, 2023].

Fisher RA (1992) Statistical Methods for Research Workers. In: Breakthroughs in Statistics (Kotz S,
Johnson NL, eds), pp 66–70 Springer Series in Statistics. New York, NY: Springer New York.
Available at: http://link.springer.com/10.1007/978-1-4612-4380-9_6 [Accessed August 5, 2023].

Frisina DR, Frisina RD (1997) Speech recognition in noise and presbycusis: relations to possible neural
mechanisms. Hear Res 106:95–104.

Gelman A (2005) Analysis of variance—why it is more important than ever. Ann Stat 33 Available at:
https://projecteuclid.org/journals/annals-of-statistics/volume-33/issue-1/Analysis-of-
variancewhy-it-is-more-important-than-ever/10.1214/009053604000001048.full   [Accessed
August 6, 2023].

Gelman A (2006) Prior distributions for variance parameters in hierarchical models (comment on article
by   Browne   and   Draper).   Bayesian   Anal   1   Available   at:
https://projecteuclid.org/journals/bayesian-analysis/volume-1/issue-3/Prior-distributions-for-
variance-parameters-in-hierarchical-models-comment-on/10.1214/06-BA117A.full.

Gelman A, Carlin J, Stern H, Dunson D, Vehtari A, Rubin D (2021) Bayesian Data Analysis, 3rd ed.
Boca Raton: Chapman and Hall/CRC.

Gelman A, Hill J, Yajima M (2009) Why we (usually) don't have to worry about multiple comparisons.
Available at: https://arxiv.org/abs/0907.2478 [Accessed August 29, 2023].

Gelman A, Hwang J, Vehtari A (2014) Understanding predictive information criteria for Bayesian
models. Stat Comput 24:997–1016.

Gelman A, Rubin DB (1992) Inference from Iterative Simulation Using Multiple Sequences. Stat Sci
7:457–472.

Gelman A, Rubin DB (1995) Avoiding Model Selection in Bayesian Social Research. Sociol Methodol
25:165.

Gelman A, Shalizi CR (2013) Philosophy and the practice of Bayesian statistics: *Philosophy and the*
practice of Bayesian statistics. Br J Math Stat Psychol 66:8–38.

Gerwinn S, Macke JH, Bethge M (2010) Bayesian inference for generalized linear models for spiking
neurons.   Front   Comput   Neurosci   4   Available   at:

http://journal.frontiersin.org/article/10.3389/fncom.2010.00012/abstract [Accessed November 2,
2023].

Gilks WR, Richardson S, Spiegelhalter DJ (1996) Markov Chain Monte Carlo in Practice. Boca Raton:
Chapman and Hall/CRC.

Grado LL, Johnson MD, Netoff TI (2018) Bayesian adaptive dual control of deep brain stimulation in a
computational model of Parkinson's disease Santaniello S, ed. PLOS Comput Biol 14:e1006606.

Gregory BA, Thompson CH, Salatino JW, Railing MJ, Zimmerman AF, Gupta B, Williams K, Beatty
JA, Cox CL, Purcell EK (2022) Structural and functional changes of pyramidal neurons at the
site of an implanted microelectrode array in rat primary motor cortex. Available at:
http://biorxiv.org/lookup/doi/10.1101/2022.09.15.507997 [Accessed March 31, 2023].

Grimsley CA, Sanchez JT, Sivaramakrishnan S (2013) Midbrain local circuits shape sound intensity
codes. Front Neural Circuits 7 Available at:
http://journal.frontiersin.org/article/10.3389/fncir.2013.00174/abstract [Accessed August 27,
2023].

Guidetti M, Marceglia S, Loh A, Harmsen IE, Meoni S, Foffani G, Lozano AM, Moro E, Volkmann J,
Priori A (2021) Clinical perspectives of adaptive deep brain stimulation. Brain Stimulat
14:1238–1247.

Herrmann B, Parthasarathy A, Bartlett EL (2017) Ageing affects dual encoding of periodicity and
envelope shape in rat inferior colliculus neurons Foxe J, ed. Eur J Neurosci 45:299–311.

Hoffman MD, Gelman A (2011) The No-U-Turn Sampler: Adaptively Setting Path Lengths in
Hamiltonian Monte Carlo. Available at: https://arxiv.org/abs/1111.4246 [Accessed July 26,
2023].

Izzo AD, Suh E, Pathria J, Walsh JT, Whitlon DS, Richter C-P (2007) Selectivity of neural stimulation
in the auditory system: a comparison of optic and electric stimuli. J Biomed Opt 12:021008.

Johnson VE, Pramanik S, Shudde R (2023) Bayes factor functions for reporting outcomes of hypothesis
tests. Proc Natl Acad Sci 120:e2217331120.

Kelly JB, Caspary DM (2005) Pharmacology of the inferior colliculus. In: The inferior colliculus., 1st
ed. New York, NY: Springer.

Krueger JI, Heck PR (2019) Putting the *P* -Value in its Place. Am Stat 73:122–128.

Kruschke JK (2010) What to believe: Bayesian methods for data analysis. Trends Cogn Sci 14:293–300.

Kruschke JK (2011) Bayesian Assessment of Null Values Via Parameter Estimation and Model
Comparison. Perspect Psychol Sci 6:299–312.

Kruschke JK (2013) Bayesian estimation supersedes the t test. J Exp Psychol Gen 142:573–603.

Kruschke JK (2014) Doing Bayesian Data Analysis: A tutorial with R, JAGS, and stan, 2nd ed.
Academic Press. Available at: http://www.indiana.edu/~kruschke/DoingBayesianDataAnalysis/.

Kruschke JK (2018) Rejecting or Accepting Parameter Values in Bayesian Estimation. Adv Methods
Pract Psychol Sci 1:270–280.

Kruschke JK (2021) Bayesian Analysis Reporting Guidelines. Nat Hum Behav 5:1282–1291.

Kruschke JK, Vanpaemel W (2015) Bayesian Estimation in Hierarchical Models. In: The Oxford
Handbook of Computational and Mathematical Psychology, pp 279–299. Oxford University
Press.

Kutner MH, Nachtsheim CJ, Neter J, Li W (2005) Applied Linear Statistical Models, 5th ed. Boston,
MA: McGraw-Hill Irwin.

Little S, Pogosyan A, Neal S, Zavala B, Zrinzo L, Hariz M, Foltynie T, Limousin P, Ashkan K,
FitzGerald J, Green AL, Aziz TZ, Brown P (2013) Adaptive deep brain stimulation in advanced
Parkinson disease. Ann Neurol 74:449–457.

Loftus WC, Bishop DC, Oliver DL (2010) Differential Patterns of Inputs Create Functional Zones in
Central Nucleus of Inferior Colliculus. J Neurosci 30:13396–13408.

Love J, Selker R, Marsman M, Jamil T, Dropmann D, Verhagen J, Ly A, Gronau QF, Smíra M,
Epskamp S, Matzke D, Wild A, Knight P, Rouder JN, Morey RD, Wagenmakers E-J (2019)
JASP: Graphical Statistical Software for Common Statistical Designs. J Stat Softw 88
Available at: http://www.jstatsoft.org/v88/i02/ [Accessed August 5, 2023].

Ma WJ (2019) Bayesian Decision Models: A Primer. Neuron 104:164–175.

Maris E (2012) Statistical testing in electrophysiological studies. Psychophysiology 49:549–565.

Munafò MR, Nosek BA, Bishop DVM, Button KS, Chambers CD, Percie Du Sert N, Simonsohn U,
Wagenmakers E-J, Ware JJ, Ioannidis JPA (2017) A manifesto for reproducible science. Nat
Hum Behav 1:0021.

Nieuwenhuis S, Forstmann BU, Wagenmakers E-J (2011) Erroneous analyses of interactions in
neuroscience: a problem of significance. Nat Neurosci 14:1105–1107.

Nuzzo R (2014) Scientific method: Statistical errors. Nature 506:150–152.

Palombi PS, Backoff PM, Caspary DM (2001) Responses of young and aged rat inferior colliculus
neurons to sinusoidally amplitude modulated stimuli. Hear Res 153:174–180.

Paninski L, Fellows MR, Hatsopoulos NG, Donoghue JP (2004) Spatiotemporal Tuning of Motor
Cortical Neurons for Hand Position and Velocity. J Neurophysiol 91:515–532.

Park M, Pillow JW (2011) Receptive Field Inference with Localized Priors Sporns O, ed. PLoS Comput
Biol 7:e1002219.

Parthasarathy A, Bartlett E (2012) Two-channel recording of auditory-evoked potentials to detect age-
related deficits in temporal processing. Hear Res 289:52–62.

Parthasarathy A, Cunningham PA, Bartlett EL (2010) Age-Related Differences in Auditory Processing
as Assessed by Amplitude-Modulation Following Responses in Quiet and in Noise. Front Aging
Neurosci 2 Available at: http://journal.frontiersin.org/article/10.3389/fnagi.2010.00152/abstract
[Accessed March 13, 2023].

Parzen E (1962) On Estimation of a Probability Density Function and Mode. Ann Math Stat 33:1065–
1076.

Polson NG, Scott JG (2012) On the Half-Cauchy Prior for a Global Scale Parameter. Bayesian Anal 7
Available at: https://projecteuclid.org/journals/bayesian-analysis/volume-7/issue-4/On-the-Half-
Cauchy-Prior-for-a-Global-Scale-Parameter/10.1214/12-BA730.full [Accessed August 29, 2023].

Quiroga RQ, Nadasdy Z, Ben-Shaul Y (2004) Unsupervised spike detection and sorting with wavelets
and superparamagnetic clustering. Neural Comput 16:1661–1687.

Rabang CF, Parthasarathy A, Venkataraman Y, Fisher ZL, Gardner SM, Bartlett EL (2012) A
computational model of inferior colliculus responses to amplitude modulated sounds in young
and aged rats. Front Neural Circuits 6:77.

Raue A, Kreutz C, Theis FJ, Timmer J (2013) Joining forces of Bayesian and frequentist methodology:
a study for inference in the presence of non-identifiability. Philos Trans R Soc Math Phys Eng
Sci 371:20110544.

Rosenblatt M (1956) Remarks on Some Nonparametric Estimates of a Density Function. Ann Math Stat
27:832–837.

Salvatier J, Wiecki TV, Fonnesbeck C (2016) Probabilistic programming in Python using PyMC3. PeerJ
Comput Sci 2:e55.

Simon H, Frisina RD, Walton JP (2004) Age reduces response latency of mouse inferior colliculus
neurons to AM sounds. J Acoust Soc Am 116:469–477.

Singh A (2018) Oscillatory activity in the cortico-basal ganglia-thalamic neural circuits in Parkinson's
disease. Eur J Neurosci 48:2869–2878.

Smid SC, McNeish D, Miočević M, Van De Schoot R (2020) Bayesian Versus Frequentist Estimation
for Structural Equation Models in Small Sample Contexts: A Systematic Review. Struct Equ
Model Multidiscip J 27:131–161.

Song S, Regan B, Ereifej ES, Chan ER, Capadona JR (2022) Neuroinflammatory Gene Expression
Analysis Reveals Pathways of Interest as Potential Targets to Improve the Recording
Performance of Intracortical Microelectrodes. Cells 11:2348.

Van Albada SJ, Robinson PA (2009) Mean-field modeling of the basal ganglia-thalamocortical system.
I. J Theor Biol 257:642–663.

Van De Schoot R, Depaoli S, King R, Kramer B, Märtens K, Tadesse MG, Vannucci M, Gelman A,
Veen D, Willemsen J, Yau C (2021) Bayesian statistics and modelling. Nat Rev Methods Primer
1:1.

Van Kuyck K, Welkenhuysen M, Arckens L, Sciot R, Nuttin B (2007) Histological Alterations Induced
by Electrode Implantation and Electrical Stimulation in the Human Brain: A Review.
Neuromodulation Technol Neural Interface 10:244–261.

Vasquez-Lopez SA, Weissenberger Y, Lohse M, Keating P, King AJ, Dahmen JC (2017) Thalamic
input to auditory cortex is locally heterogeneous but globally tonotopic. eLife 6:e25141.

Vehtari A, Gelman A, Gabry J (2017) Practical Bayesian model evaluation using leave-one-out cross-
validation and WAIC. Stat Comput 27:1413–1432.

Vogelstein JT, Watson BO, Packer AM, Yuste R, Jedynak B, Paninski L (2009) Spike Inference from
Calcium Imaging Using Sequential Monte Carlo Methods. Biophys J 97:636–655.

Wagenmakers E-J (2007) A practical solution to the pervasive problems of p values. Psychon Bull Rev
14:779–804.

Wells J, Kao C, Jansen ED, Konrad P, Mahadevan-Jansen A (2005) Application of infrared light for in
vivo neural stimulation. J Biomed Opt 10:064003.

Wood E, Fellows M, Donoghue JR, Black MJ (2004) Automatic spike sorting for neural decoding. In:
The 26th Annual International Conference of the IEEE Engineering in Medicine and Biology
Society,   pp   4009–4012.   San   Francisco,   CA,   USA: IEEE.   Available   at:
http://ieeexplore.ieee.org/document/1404120/ [Accessed January 31, 2024].

Woolley AJ, Desai HA, Otto KJ (2013) Chronic intracortical microelectrode arrays induce non-uniform,
depth-related tissue responses. J Neural Eng 10:026007.

Wu W, Gao Y, Bienenstock E, Donoghue JP, Black MJ (2006) Bayesian Population Decoding of Motor
Cortical Activity Using a Kalman Filter. Neural Comput 18:80–118.

1130

1131

1132

1133

1134

Legends

Figure 1: Graphical description of Bayes rule and the interaction between prior distributions and likelihood functions leading to the final posterior distribution. A. Bayes rule can be thought of as a reallocation of probability to the posterior after accounting for prior distributions and observed evidence. B. An example of posterior generated from an inverse-Gamma distributed likelihood and a uniformly distributed prior. Uniform priors reflect the likelihood function, and thus the observed data with no redistribution probability, making uniform distributions uninformative priors. However, care must be taken in using uniform distributions as observed data outside of prior bounds is mapped to 0 probability. A second example of a posterior generated from an inverse-gamma distributed likelihood and a gaussian distributed prior shows how a prior can be considered informative (right). In this posterior, the prior "shapes" the posterior to a greater extent than a uniform prior. Well designed priors in neuroscientific data can thus shape posteriors away from responses which are not physiological and can be vetted in the statistical decision, data review, and post-publication review stages. Prior distributions with longer tails can handle extremes of observed data by mapping extreme events to low, but non-zero representation in the posterior. Example B represents extremes of prior choices, with minimally informative priors often chosen to let the data "speak for itself" with little change to posterior from prior influence. C. Comparison of Bayesian and Frequentist statistics. NHST utilizes a parameterized likelihood function that describes the data generating process. D. Decisions in NHST are generally made based on quantification of the probability of observing test results as extreme as observed data assuming that the null hypothesis is true. E. An illustrative example of how Bayesian inference might be used in an electrophysiological experiment. Prior distributions can be iteratively formulated by previous experiments drawn from both internal and published data.

Figure 2: Example of Bayesian simple linear regression on population estimates of firing rate vs

amplitude modulation depth stimuli. This model was applied to population single unit firing rates

elicited from inferior colliculus with sinusoidal amplitude modulated (SAM) tones. The goal of this

model was to predict evoked firing rates from increases in SAM modulation depths. A. Density plot of

observed firing rates vs SAM modulation depth and fitted regression estimates. B. Histogram and

kernel density estimation (KDE) of the distribution of SAM-evoked inferior colliculus firing rates. C.

Schematic of amplitude modulated stimuli.

1165

Figure 3: Completed Bayesian inference quantifying linear relationships in evoked firing rate from

increases in modulation depth. A. Scatterplot of observed firing rates vs SAM depth stimuli with fitted

regression line estimates superimposed. 95% HDI estimates of regression slopes are shown in orange,

with the spread of lines encoding the 95^{th} percentile of most likely slope values. B. Estimates of

Bayesian linear regression parameters. Intercept term α was significantly above 0 (MAP = 3.1, 95%HDI

does not overlap 0) which indicates basal firing rates above 0. Regression slope was small but

significantly above 0 (MAP = 0.018, 95% HDI does not overlap 0) suggesting an increase in evoked

firing rates with increased modulation depth. Error term ϵ was significantly above 0 (MAP = 0.74, 95%

HDI does not overlap 0) suggesting some model deviation from observed data. However, error terms

were considered small as ϵ MAP $< \alpha$ basal firing rate MAPs. C. Posterior predictive checks of linear

(left) and log linear (right) regression models show that log transformed firing rate models produce

posterior predictions most inline with observed data. Disparity of empirical posterior predictive

distributions from observed data as quantified through Bayesian P-values also suggest log transformed

firing rates creates a superior model fit.

1180

Figure 4: Evaluation of Markov-chain Monte Carlo (MCMC) chains can help diagnose ill-fitting

distributions. A. Kernel density estimates of the marginal posteriors corresponding to each of the

regression parameters of each MCMC trace. Qualitatively, chain distributions should appear similar to

each other, suggesting good convergence to target distributions. B. Time series plot of trace value vs

sample number of marginal posteriors corresponding to each regression parameter. Qualitatively good

traces should have a "fuzzy caterpillar" like shape, evident in all parameters of this model, indicative of

good integration over the joint posterior distribution and effective sampling of the posterior.

1188

Figure 5: Bayesian implementations of t-tests provide descriptive quantification of differences in group

means and standard deviations and effect sizes drawn directly from observed data. A. Schematic of the

basal-ganglia thalamocortical computational model. Modeled DBS stimulation was performed in

subthalamic nucleus with local field potential (LFP) recordings made from globus pallidus internus. All

simulations were performed assuming dopamine-depleted conditions. B. Example LFP power spectral

densities from no stimulation condition (green), subthreshold DBS stimulation (0.01 mA, 100 μs pulse

widths, 130 Hz, orange), and effective DBS stimulation (1.8 mA, 240 μs pulse widths, 130 Hz, blue). C.

Total β-band power in no stimulation and DBS stimulation was calculated (n=2000 repitions). Group

comparison by Bayesian estimation supersedes the T-test (BEST) shows significant reduction in mean

β-band power as evidenced by group mean difference 95% HDIs not including 0 (MAP $\mu_{DBS} -$

$\mu_{nostim} = -0.4$). Estimated effect size distributions further give evidence of a strong DBS effect of

lowering β-band power in dopamine-depleted conditions (MAP $_{effectsize} = 6.9, 95\%$ HDI does not

contain 0). D. Frequentist t-tests show strong dependance on sample size. Comparisons of β-band power

were made between no stimulation and subthreshold stimulation groups. Subthreshold stimulation will

have no effect on β-band power with only differences formed by model noise simulating intrinsic neural

noise. Increasing numbers of shuffled samples were included in t-test and BEST tests. BEST differences

in group means show rapid convergence to null differences. P-values from frequentist t-tests however

show drastic fluctuations some of which cross $p < 0.05$ significance threshold even at large sample

sizes.

1208

Figure 6: Example of Bayesian multilinear regression incorporating a hierarchical structure. A. In this

experiment, rodents were implanted with fiber optic arrays into auditory thalamus and planar recording

arrays into auditory cortex. Single unit responses were recorded from INS stimuli with applied energy

and interstimulus intervals varied to derive dose-response curves. Figure was drawn using BioRender

under publication license (www.biorender.com). B. Hierarchical schematic of Bayesian multilinear

regression. Hierarchical structures are advantageous in accounting for within and between subject

variability or for repeated measures designs. C. Resulting parameter distributions from dose-response

models. Energy was a significant contributor to maximum firing rate, with increasing laser energy

resulting in increased maximum firing rate, as determined by 95% HDI of the laser energy term β_1

excluding 0 (MAP = 0.58). Laser pulse interstimulus interval did not significantly contribute to changes

in max firing rate as indicated by ISI parameter β_2 overlapping 0 in its 95% HDI with a MAP value near

0 (MAP = 0.028). The relatively wide spread about zero does suggest that there may be a subset of ISIs

which contribute more strongly to firing rates and warrants further study. Laser energy-ISI interactions

also did not significantly contribute to max firing rate as evidenced by interaction parameter β_3

including 0 in its 95% HDI. The intercept term α, correspondint to basal firing rates, were significantly

above 0 (MAP = 2.2, 95% HDI excludes 0).

1225

Figure 7: An example of Bayesian inference using ANOVA-like models. A. General schematic of

BANOVA/BANCOVA models. Traditional ANOVAs have two key assumptions; normality of group

data and homogeneity of variance. Normality of group data is imposed in BANOVA-like models as

normal distributions around group parameters with homogeneity of variance encoded as a uniform

distribution around posterior variance term σ_y. Traditional ANOVAs assume a fixed variance on group

parameter values σ_β, imposing the constraint that each group is estimated independently from each other

group. A uniquely Bayesian approach is to instead learn σ_β values from the data itself by placing a

distribution on σ_β. B. Posterior predictive checks suggest posterior distributions show good fit in mean

and variance to observed data. C. Once posterior distributions are calculated, group comparisons can be

easily done by subtracting young and aged posteriors to yield a contrast distribution. It is found that

firing rates across all modulation depths are significantly higher in aged vs young rodents (contrast

MAP = 0.25, 95% HDI does not overlap 0). Another unique feature of Bayesian approaches is the

ability to assess distributions on effect size. In this BANCOVA, while group differences are significant,

their relative effective size is small but significant (effect size MAP = 0.057, 95% HDI does not cross 0)

suggesting marginal impact of age on firing rates elicited from SAM stimuli. Finally, metric covariates

of firing rate in response to varying SAM depth in young and aged groups can be plotted as regressions

superimposed on raw data.

1243

1244

1245

 Figures

1248   **Figure 1:**

1249

Figure 2:

1250

1251

1252

1253

1254

1255 **Figure 3**

1256

Figure 4:

1257

1258

1259

1260

1261

1262

1263

1264

1265

1266 **Figure 5:**

1267

1268

1269

1270

Figure 6:

1271

1272

1273

1274

1275

1276

1277

Figure 7:

1278

1279

1280

1281

1282

1283

1284

1285

1286

1287

1288   **Tables**

1289   *Table 1: Brief Comparison of Bayesian and frequentist inference paradigms*

	Bayesian	Frequentist
Philosophy of probability	*Quantification of uncertainty*	*Frequency of events*
Data inference	*P(hypothesis|data) "data driven"*	*P(data|hypothesis)*
Decision rules	*HDI, credible interval, ROPE, distribution of observed data Distributions, Bayes factors*	*p-value, confidence interval, Type I/II error control*
Model parameters are	*Distributions formed around uncertainty in observed data*	*Fixed but unknown values inferred from estimators (maximum likelihood/least squares)*
Data Distributions	*Any distribution*	*Parametric models require data to follow normal distributions. Non-parametric methods are limited.*
Requires explicit declaration of prior distribution	*Yes*	*No*
Computational complexity	*Higher*	*Lower*
Advantages	*Inference backed by evidence from observed data, complete probabilistic description of experimental data, inference less dependent on sample size.*	*Robust error control with proper experimental design, quick and easy to implement*
Disadvantages	*More computationally complex, prior choice can require extensive expert knowledge*	*Strong dependance on sample size, decision rules are binary abstracted from data*

1290

1291

1292

1293

1294

1295

1296

1297

 Table 2: LOO Model comparisons and sensitivity analyses

Model	R	ELPD	DSE
St Log Var 5	1	-5337.48	0.00
ST Log Var 100	2	-5337.62	0.420867
ST Log Var 0.5	3	-5337.76	0.409773
St Log Var 25	4	-5338.15	0.492297
ST Log Var 10	5	-5338.18	0.300197
ST Log Var 1	6	-5338.26	0.331152
N Log Var 10	7	-5340.60	3.308668
N Log var 1	8	-5341.09	3.293779
N log var 5	9	-5341.16	3.296273
N log var 0.5	10	-5342.46	3.300550
ST Semilog Var 1	11	-5466.76	15.845916
St Semilog var 5	12	-5467.12	15.856552
ST semilog var 10	13	-5467.15	15.895646
ST semilog var 0.5	14	-5467.18	15.866405
ST Var 1	15	-15336.31	79.406629
ST var 0.5	16	-15355.67	80.415787
St var 5	17	-15355.67	80.415787
N var 10	18	-16119.11	82.384329
N var 1	19	-16132.23	83.549811

1299	*N var 0.5*	20	-16154.55	84.262219
1300				
1301				
1302				
1303				
1304				
1305				
1306				
1307				
1308				
1309				
1310				
1311				
1312				
1313				
1314				
1315				
1316				

Extended Data

All data and source code can be found in our GitHub toolbox: https://github.com/bscoventry/Practical-Bayesian-Inference-in-Neuroscience-Or-How-I-Learned-To-Stop-Worrying-and-Embrace-the-Dist.

Installation and Running of the Bayesian Inference Toolbox

```
 1. OS recommendations
 2.
 3. This code works for Windows and Linux distributions. We believe this should work for MacOS, but is
untested.
 4. Setting up a PyMC environment
 5.
 6. To use these scripts, we strongly recommend setting up an Anaconda environment dedicated to PyMC.
Anaconda can be freely downloaded directly from https://www.anaconda.com/. To setup a PyMC environment,
open an anaconda prompt and run:
 7.
 8. conda create -n PyMC python=3.8
 9.
10. which creates a conda environment named PyMC using Python version 3.8. We recommend at least this
version of Python, but have tested down to Python 3.6.8 as working. Anaconda environments create self
constrained python libraries such that Python dependencies from one environment are not altered by changed
in other project environments.
11.
12. To activate an environment, in anaconda, run
13.
14. conda activate PyMC
15.
16. Installing PyMC and required packages
17.
18. To install PyMC, first activate a PyMC environment. Then run:
19.
20. conda install -c conda-forge "pymc>=5"
21. conda install -c conda-forge numpyro
22. pip install arviz
23. pip install aesara
24. pip install numpy
25. pip install pandas
26. pip install scipy
27. pip install seaborn
28. pip install matplotlib
29.
30. This installs PyMC and all required packages individually. Alternatively, pip installations can be
groups as "pip install scipy,numpy,..."
31.
32. To run DBS LFP models, install the following packages:
33.
34. pip install tabulate
35. pip install docopt
36. pip install nutpie
37.
38. Running sample programs
39.
40. We recommend creating a new directory on your machine to download all programs and data to. To run
programs, activate the PyMC environment and navigate to the code/data directory as:
41.
42. cd 'path to your directory'
```

```
43.
44. An example of 'path to your directory might be 'C:\CodeRepos\PyMC'.
45.
46. Programs are then run by simplying typing
47.
48. python BayesRegression.py
49.
50. Programs will run and give diagnostics in the anaconda terminal and show plots found in the paper.
51. Where do I find the data?
52.
53. Data for Bayesian linear regressions, comparisons of models, and BANOVA/BANCOVAs are found at the
following open science framework link: Data for Bayesian Multilinear regressions can be found at its papers
open science framework repository: [Redacted for double blind peer review].
54.
```

BayesRegression.py

```python
1.  1.  #----------------------------------------------------------------------------------------
    --------------------------------------
2.  #
3.  # Date: 08-17-2022
4.  # Purpose: This calculates a simple linear regression (Bayesian Formulation) on auditory evoked data
    with modulation of amplitude
5.  #          modulated depth. Use this as a tutorial for simple linear regression for neural data
6.  # Revision History: See Github for Rollback
7.  # Notes: PDB is added in to debug code at your leasure. Add pdb.set_trace() anywhere in line to create
    a break point to explore
8.  # variables. We highly recommend doing this to explore the code to get a good feel for it.
9.  #----------------------------------------------------------------------------------------
    --------------------------------
10. """
11. To begin, let's import all of our dependencies, including our data and python packages
12. """
13. import numpy as np                  #Numpy for numerical 'ala Matlab' computations
14. import pymc as pm                    #pymc will be doing most of our heavy lifting for Bayesian
    calculations
15. import matplotlib.pyplot as plt      #This works as our plotting tool
16. import arviz as az                   # arviz is a visualization package for plotting probabilistic
    variables, such as prior or posterior distributions
17. import aesara                        #Aesara is out tool for calculations involving tensors. PyMC will
    mostly work with this for us.
18. import pandas as pd                  #Using pandas to read in CSV data files
19. import pickle                        #Pickle for saving data after completion of our model
20. import seaborn as sns                #We will use some of seaborn's distribution plotting tools
21. import pdb
22. # Let's load some data!
23. if __name__ == '__main__':          #This statement is to allow for parallel sampling in windows. Linux
    distributions don't require this. Doesn't hurt Linux to have this either.
24.     print(f"Running on PyMC v{pm.__version__}")      #Tells us which version of PyMC we are running
25.     AMDepthData = pd.read_csv("depthData.csv")      #Read in our data. Note this address may change
    based on where program files are downloaded.
26.     data1 = AMDepthData.loc[AMDepthData['Age'] == 2]              #Let's consider young responses
    first.
27.     data1.reset_index(drop=True, inplace = True)
28.     AMDepthData = data1
29.     """
30.     Now let's setup some meta data for our model analyses. We will set the number of burn in samples,
    which "primes" the markov chain Monte Carlo (MCMC) algorithm, and number of
31.     samples to draw from the posterior. In general, less "well behaved" data will require more samples
    to get MCMC to converge to steady state.
32.     """
33.     numBurnIn = 2000
34.     numSamples = 4000
```

```
35.    #These next two lines of code setup the color scheme used for plotting. Does not affect model at
all
36.    color = '#87ceeb'
37.    az.style.use("arviz-darkgrid")
38.    Randomseed = 7
39.    """
40.    Now let's grab out relevant data. For AM Depth studies, our data file contains a tot_mean
variable, which codes the mean firing rate elicited from a stimulus at a given
41.    modulation depth. Modulation depth is metric data which exists across a continuum of values,
meaning that a regression is a good choice. So the goal is to build a model
42.    of the form:
43.    firingRate = a + B*modDepth + modelError
44.    where a can be largely thought of as spontaneous, non evoked firing rates, B is slope describing
the relative change of firing rate as a function of modulation depth, and
45.    modelError being the error term of the model describing misses of our fitting process. Because
this is a Bayesian approach, a, B, and modelError are themselves distributions
46.    that we will make inference on.
47.    """
48.    # data3 = AMDepthData.loc[(AMDepthData['Age'])==1]
49.    # data3.reset_index(drop=True, inplace = True)
50.    # AMDepthData = data3
51.    modDepth = AMDepthData.ModDepth                    #This is our modulation depth vector
52.    firingRate = AMDepthData['TotMean']                #This is our mean firing rate. Note, data can
be accessed in a pandas array using dot notation (data.subsetData) or
53.
54.    firingRate = np.log(firingRate+0.01)
55.                                                       #Index like data['subsetData']
56.    firingRate = firingRate.astype(aesara.config.floatX) #Make sure response variable is in a tensor
like structure for computaiton. This is the only time we need to directly invoke aesara
57.    modDepth = np.asarray(modDepth)                    #Make sure Xs are not panda series, aesara is
not a fan of those sometimes.
58.    """
59.    Let's do some data visualization first. Always good to look at the data first. We will plot the
scatter plot of the response variable and predictor variable
60.    """
61.    plt.figure(1)
62.    plt.scatter(modDepth,firingRate)
63.    plt.show()
64.    #Plot the distribution of response variable, firing rate
65.    sns.displot(firingRate, kde=True)
66.    plt.show()
67.    #Create a distribution plot of the data.
68.    sns.violinplot(x=modDepth, y=firingRate, split=True)
69.    plt.show()
70.    """
71.    Okay great, the distribution looks somewhat normally distributed. Let's carry on
72.    """
73.    """
74.    Let's define our model. This is where the power of Bayesian responses really shows. We can easily
define our own models to explicitly fit data. To do so, let's define a prior and
75.    a likelihood function. For regresison, our likelihood function takes the form of Y = a
+B*predictor + modelError. Our prior can come from previous knowledge, or relatively uninformative,
76.    mostly letting data speak for itself. We will use a Normally distributed prior, which is preferred
to a uniform prior. This is because if data falls outside of a uniform prior, the probability incorporated
77.    into the model is 0, effectively ignoring more extreme values. Intuitively, we want to incorporate
more extreme data, but at a reduced level. Normal distributions do this for us.
78.    """
79.    prMean = np.mean(firingRate)
80.    with pm.Model() as regression:                     #Define a model that we call regression
81.        a = pm.Normal('a', mu=prMean, sigma = 5)            #Normally distributed prior on a
82.        B = pm.Normal('B', mu=prMean, sigma = 5)            #Normally distributed prior on B
83.        eps = pm.HalfCauchy("eps", 5)                       #Model error prior, half Cauchy distributed with
variance 5
84.        # Now we define our likelihood function, which for regression is our regression function
```

```
1496    85.            reg = pm.Deterministic('reg', a + (B*modDepth))      #Deterministic is for non probabilistic
1497  data. This is a modification to help sampling, inference is still probabilistic
1498    86.            likelihood = pm.Normal('Y',mu = reg, sigma = eps, observed = firingRate)
1499    87.            """
1500    88.            And that's it! We've quickly, explicitly, and easily defined our model. We set prior
1501  distributions on a, B, and modelError, and defined a likelihood function of a normal linear regression
1502    89.            with our observed data being our firingRate, which is the variable we are trying to predict.
1503  Easy eh?
1504    90.            """
1505    91.      """
1506    92.      Our last step is to run inference to get our posterior distribution which we do by MCMC sampling.
1507  In PyMC this is also easy.
1508    93.      """
1509    94.      with regression:                  #Access our defined model
1510    95.          trace = pm.sample(numSamples, tune=numBurnIn, target_accept=0.90,chains = 4)       #4
1511  parallel, independent MCMC chains.
1512    96.      """
1513    97.      Now we're sampling! We initialize the chain with numBurnIn samples, and then run for numSamples.
1514  Target_accept determines MCMC step size in order to get to a sampling acceptance rate. Generally,
1515    98.      higher probability of target_accept helps with difficult to sample posteriors. For now, 0.9 is
1516  fine.
1517    99.
1518    100.     You will see the sampling run in the command prompt. Once complete, we have our posterior and can
1519  now make inference!
1520    101.     """
1521    102.
1522    103.     intercept = trace.posterior["a"]                  #Grab the posterior distribution of a
1523    104.     Slope = trace.posterior["B"]                      #Grab the posterior distribution of B
1524    105.     err = trace.posterior["eps"]                      #Grab the posterior distribution of model error
1525    106.
1526    107.     """
1527    108.     Let's plot our posteriors!
1528    109.     """
1529    110.     #az.plot_trace(trace, compact=True)
1530    111.     az.plot_posterior(trace, var_names=['a', 'B','eps'], point_estimate='mode',hdi_prob=0.95)
1531    112.     plt.show()
1532    113.     fig = plt.figure(figsize=(9, 6))
1533    114.     ax = fig.add_subplot(
1534    115.     111,
1535    116.     xlabel=r"Modulation Depth",
1536    117.     ylabel=r"Firing Rate",
1537    118.     title="Posterior predictive regression lines",
1538    119.     )
1539    120.     #sc = ax.scatter(modDepth, firingRate)
1540    121.     sc = sns.violinplot(x=modDepth, y=firingRate, split=True)
1541    122.     #Plot posterior HDIs
1542    123.     az.plot_hdi(
1543    124.         modDepth,
1544    125.         trace.posterior.reg,
1545    126.         color="k",
1546    127.         hdi_prob=0.95,
1547    128.         ax=ax,
1548    129.         fill_kwargs={"alpha": 0.25},
1549    130.         smooth=False,
1550    131.     )
1551    132.     az.plot_energy(trace)
1552    133.     az.plot_trace(trace)
1553    134.     plt.show()
1554    135.     #pdb.set_trace()
1555    136.     """
1556    137.     Now let's do some posterior predictive checks. PyMC has some nice functions that make this quite
1557  easy. We will also sample the posterior distribution for the
1558    138.     standard 16,000 samples, which for this posterior should be more than enough.
1559    139.     """
```

```
140.        with regression:
141.            ppcRegression = pm.sample_posterior_predictive(trace, random_seed=Randomseed)
142.
143.    #The above code envokes the regression mode, then uses the posterior from the trace, pulling
synthetic samples to compare to observed. Random seed is set so that each run can be perfectly replicated
144.        az.plot_bpv(ppcRegression, hdi_prob=0.95,kind='p_value')
145.    #Bayes p-values, similar to frequentist,can be used to assess if posterior predictive is
sufficiently close to observed density. Should be centered around 0.50.
146.        az.plot_ppc(ppcRegression)
147.        az.plot_trace(trace,var_names=['a', 'B','eps'])
148.        plt.show()
149.
```

BayesRegression_WithBambi.py

```
1.  1.  #-----------------------------------------------------------------------------------------
------------------------
 2. # Author:
 3. # Purpose: Simple Bayesian Regression with PyMC and BAMBI. Need to install Bambi for this to work.
 4. # Note: We recommend going through the modeling process first with PyMC before this model. Bambi is
very good but abstracts
 5. #        much of the model building context away. Use ony if comfortable with Bayesian Models.
 6. #-----------------------------------------------------------------------------------------
--------------------
 7. """
 8. To begin, let's import all of our dependencies, including our data and python packages
 9. """
10. import numpy as np                    #Numpy for numerical 'ala Matlab' computations
11. import pymc as pm                      #pymc will be doing most of our heavy lifting for Bayesian
calculations
12. import matplotlib.pyplot as plt  #This works as our plotting tool
13. import arviz as az                    # arviz is a visualization package for plotting probabilistic
variables, such as prior or posterior distributions
14. import bambi as bmb                   #Model abstraction tool
15. import pandas as pd                   #Database tool
16. import pdb
17. # Let's load some data!
18. if __name__ == '__main__':        #This statement is to allow for parallel sampling in windows. Linux
distributions don't require this. Doesn't hurt Linux to have this either.
19.     print(f"Running on PyMC v{pm.__version__}")      #Tells us which version of PyMC we are running
20.     AMDepthData = pd.read_csv("depthData.csv")      #Read in our data. Note this address may change
based on where program files are downloaded.
21.     data1 = AMDepthData.loc[AMDepthData['Age'] == 1]                    #Let's consider young responses
first.
22.     data1.reset_index(drop=True, inplace = True)
23.     AMDepthData = data1
24.     AMDepthData['TotMean'] = np.log(AMDepthData['TotMean']+0.01)
25.     #Define the model
26.     studT = bmb.Model("TotMean ~ ModDepth",AMDepthData,family="t")            #Defaults to Gauss, use
t for student t likelihood
27.     #Run the MCMC
28.     Robust_Reg  = studT.fit(draws=5000, idata_kwargs={"log_likelihood": True})
29.     studT.predict(Robust_Reg, kind="pps")
30.
31.     #Now do some plotting
32.     plt.figure(figsize=(7, 5))
33.     # Plot Data
34.     plt.plot(AMDepthData['ModDepth'], AMDepthData['TotMean'], "x", label="data")
35.     # Plot recovered linear regression
36.     x_range = np.linspace(AMDepthData['ModDepth'], AMDepthData['ModDepth'], 2000)
37.     y_pred = Robust_Reg.posterior.ModDepth.mean().item() * x_range +
Robust_Reg.posterior.Intercept.mean().item()
38.     plt.show(block=False)
```

```
39.
40.     #So as we can see, quick and easy model running at the cost of interpretability. For example,
priors aren't exactly the most transparent.
41.
```

Banova_Bancova.py

```python
1.  import numpy as np                  #Numpy for numerical 'ala Matlab' computations
2.  import pymc as pm                    #pymc will be doing most of our heavy lifting for Bayesian
calculations
3.  import matplotlib.pyplot as plt  #This works as our plotting tool
4.  import arviz as az                   # arviz is a visualization package for plotting probabilistic
variables, such as prior or posterior distributions
5.  import aesara                        #Aesara is out tool for calculations involving tensors. PyMC will
mostly work with this for us.
6.  import pandas as pd                  #Using pandas to read in CSV data files
7.  import pdb
8.  import seaborn as sns
9.  plt.style.use('seaborn-white')    #Set plot styles here
10. color = '#87ceeb'
11. if __name__ == '__main__':         #This statement is to allow for parallel sampling in windows. Linux
distributions don't require this.
12.     print(f"Running on PyMC v{pm.__version__}")      #Tells us which version of PyMC we are running
13.     AMDepthData = pd.read_csv("depthData.csv")       #Read in our data. Note this address may change
based on where program files are downloaded.
14.     """
15.     Now let's setup some meta data for our model analyses. We will set the number of burn in samples,
which "primes" the markov chain Monte Carlo (MCMC) algorithm, and number of
16.     samples to draw from the posterior. In general, less "well behaved" data will require more samples
to get MCMC to converge to steady state.
17.     """
18.     numBurnIn = 2000
19.     numSamples = 5000
20.     #These next two lines of code setup the color scheme used for plotting. Does not affect model at
all
21.     color = '#87ceeb'
22.     az.style.use("arviz-darkgrid")
23.     Randomseed = 7
24.     """
25.     Now let's grab out relevant data. For AM Depth studies, our data file contains a tot_mean
variable, which codes the mean firing rate elicited from a stimulus at a given
26.     modulation depth. Modulation depth is metric data which exists across a continuum of values,
meaning that a regression is a good choice. So the goal is to build a model
27.     of the form:
28.     firingRate = a + B*modDepth + modelError
29.     where a can be largely thought of as spontaneous, non evoked firing rates, B is slope describing
the relative change of firing rate as a function of modulation depth, and
30.     modelError being the error term of the model describing misses of our fitting process. Because
this is a Bayesian approach, a, B, and modelError are themselves distributions
31.     that we will make inference on.
32.     """
33.
34.     modDepth = AMDepthData.ModDepth.values                     #This is our modulation depth vector
35.
36.     firingRate = AMDepthData['TotMean']              #This is our mean firing rate. Note, data can be
accessed in a pandas array using dot notation (data.subsetData) or
37.     firingRate = np.log(firingRate+0.01)              #Posterior predictive checks dictate that a log
transformation on firing rates best fits a BANCOVA model
```

```python
38.      AMDepthData['TotMean']  = firingRate            #Add firing rate back into pandas array for ease
of data access. In certain cases, may want to keep these seperate
39.      #Get y variable (firing rates) mean and sd across groups for setting minimally informative prior
parameters
40.      yMean = np.mean(firingRate)
41.      yStDv = np.std(firingRate)
42.      modDepthMean = np.mean(modDepth)
43.      #Grab age class. In this data set, Age is already cast to encoded integers. 1 is aged, 2 is young.
44.      ageNum = AMDepthData['Age'].astype(aesara.config.floatX)
45.
46.      age = ageNum - 1           #0 and 1s instead of 1 and 2 for categories. Because computer
science and we like computer science. 0 Aged, 1 Young
47.      numCategories = 2
48.      #The following two lines adds a category option of age to the dataframe. This is because we've
built this to use Categories, and I want to demonstrate how to easily cast objects to this type
49.      #If the data being used already isn't in this form.
50.      AMDepthData['AgeClass'] = age
51.      AMDepthData.AgeClass = AMDepthData.AgeClass.astype('category')
52.      ClassAge = AMDepthData.AgeClass.cat.codes.values
53.      AMDepthData['LogModDepth'] = modDepth
54.
55.      def plot_cred_lines(b0, bj, bcov, x, ax):
56.          #This function plots the covariance variable at the MAP beta values. Used later for plotting
57.          B = pd.DataFrame(np.c_[np.transpose(b0.values), np.transpose(bj.values),
np.transpose(bcov.values)], columns=['beta0', 'betaj', 'betacov'])
58.
59.          # Credible posterior prediction lines
60.          hpd_interval = az.hdi(B.values, hdi_prob=0.95)
61.          B_hpd = B[B.beta0.between(*hpd_interval[0,:]) &
62.                    B.betaj.between(*hpd_interval[1,:]) &
63.                    B.betacov.between(*hpd_interval[2,:])]
64.          xrange = np.linspace(x.min(), x.max())
65.
66.          for i in np.random.randint(0, len(B_hpd), 10):
67.              ax.plot(xrange, B_hpd.iloc[i,0]+B_hpd.iloc[i,1]+B_hpd.iloc[i,2]*xrange, c=color, alpha=.6,
zorder=0)
68.      """
69.      Define the ANCOVA Model
70.      """
71.
72.      with pm.Model() as BANCOVA:
73.          #Define hyperprior on sigma
74.          bSigma = pm.HalfCauchy('bSigma',2.0)                #Recommended by Gelman, this parameter
doesn't overemphasize 0 on sigma.
75.          #Define Prior, likelihood distributions. Relatively noninformative
76.          a = pm.Normal('a',yMean,sigma = np.sqrt(yStDv))
77.          B = pm.Normal('B',0,sigma=bSigma,shape=numCategories)
78.          #Define covariate, in our case this is mod depth, but we initially set mean and variance to
that of observed firing rates. Will learn with data.
79.          Bcov = pm.Normal('Bcov',yMean,sigma = np.sqrt(yStDv))
80.          #variance on likelihood function is set to uniform to satisfy homogeneity of variance
assumption of ANOVA like structures.
81.          sigmaLikelihood = pm.Uniform('sigmaLikelihood',yStDv/100,yStDv*10)
82.          #Set the BANCOVA model. Note that [ClassAge] effectively sets seperate Beta parameters per
each class, which is what we want.
83.          BancovaModel = a + B[ClassAge] + (Bcov*(modDepth - modDepthMean))
84.          #Set likelihood on BANCOVA model
85.          y = pm.Normal('y',mu=BancovaModel,sigma = yStDv,observed=firingRate)
86.          #Now, make sure model coefficients sum to 0 to create an ANOVA-like structure
87.          aScaled = pm.Deterministic('aScaled',a+aesara.tensor.mean(B) + Bcov*(-modDepthMean))
88.          bScaled = pm.Deterministic('bScaled',B - aesara.tensor.mean(B))
89.      pm.model_to_graphviz(BANCOVA)                         #This creates a visualizer of our model.
90.      plt.show()                                           #Go ahead and plot our model.
91.
```

```
92.     """
93.     Our last step is to run inference to get our posterior distribution which we do by MCMC sampling.
In PyMC this is also easy.
94.     """
95.     with BANCOVA:                    #Access our defined model
96.         trace = pm.sample(numSamples, tune=numBurnIn, target_accept=0.90,chains = 1)
97.
98.     #Now that we have our trace, time to plot raw data for analysis.
99.     fg = sns.FacetGrid(AMDepthData, col='AgeClass', despine=False)
100.    fg.map(plt.scatter, 'LogModDepth', 'TotMean', facecolor='none', edgecolor='b')
101.    #Grab our Beta posteriors for young and age classes respectively.
102.    bScaledAge = trace.posterior['bScaled'][:,:,1]
103.    bScaledYoung = trace.posterior['bScaled'][:,:,0]
104.    #np.shape(trace)                         #Uncomment this line if you want to see the overall
structure of the trace. Good for diagnostics
105.    aTrace = trace.posterior['aScaled']
106.
107.
108.    cTrace = trace.posterior['Bcov']
109.    scale = trace.posterior['sigmaLikelihood']
110.
111.    #We perform inference over the contrasts between groups. In this case lets look at differences
between aged and young classes.
112.    yVa = bScaledYoung - bScaledAge              #Difference calculation
113.    effectSize = yVa/scale       #Get the effect size
114.
115.    #Plot differences
116.    fig, axes = plt.subplots(2,1)
117.    az.plot_posterior(yVa, hdi_prob=0.95, ref_val=0, ax=axes[0],point_estimate='mode')
118.    az.plot_posterior(effectSize, hdi_prob=0.95, ref_val=0, ax=axes[1],point_estimate='mode')
119.
120.
121.    dataY = AMDepthData.loc[AMDepthData['AgeClass'] == 'Young']                   #Get Young and Aged
data
122.    dataY.reset_index(drop=True, inplace = True)
123.    dataA = AMDepthData.loc[AMDepthData['AgeClass'] == 'Aged']
124.    dataA.reset_index(drop=True, inplace = True)
125.
126.
127.    fg = sns.FacetGrid(AMDepthData, col='AgeClass', despine=False)
128.    fg.map(plt.scatter, 'LogModDepth', 'TotMean', facecolor='none', edgecolor='b')
129.    #Plot cred lines of 95% HDI of Beta class and Beta cov parameters
130.    for ck, ax in enumerate(fg.axes.flatten()):
131.        if ck == 0:
132.            plot_cred_lines(aTrace,
133.                            bScaledAge,
134.                            cTrace,
135.                            AMDepthData.ModDepth, ax)
136.        if ck == 1:
137.            plot_cred_lines(aTrace,
138.                            bScaledYoung,
139.                            cTrace,
140.                            AMDepthData.ModDepth, ax)
141.    ax.set_xticks(np.arange(.6, 1.1, .1))
142.    #Look at the data!
143.    plt.show(block=False)
144.    """
145.    Here we perform posterior predictive checks and get Bayesian P-Values.
146.    """
147.    with BANCOVA:
148.        ppcBANCOVA = pm.sample_posterior_predictive(trace, random_seed=Randomseed)
149.    #The above code envokes the regression mode, then uses the posterior from the trace, pulling
synthetic samples to compare to observed. Random seed is set so that each run can be perfectly replicated
150.    az.plot_bpv(ppcBANCOVA, hdi_prob=0.95,kind='p_value')
```

```
151.    #Bayes p-values, similar to frequentist,can be used to assess if posterior predictive is
sufficiently close to observed density. Should be centered around 0.50.
152.    az.plot_ppc(ppcBANCOVA)
153.    plt.show(block=False)
154.    #Pause the program in case we want to do inline exploration of data. type exit() in terminal to
end program.
155.    pdb.set_trace()
156.
```

HeirarchicalLinearRegression_Bayesian.py

```python
1. #-------------------------------------------------------------------------------------------
------------------
2. #
3. # Date: 08/23/2022
4. # Purpose: This program is a modified port of my previous heirarchical linear regression programs,
updated for pymc (v4)
5. # Revision History: Based on Code I used for my dissertation. This is the release version. See github
for rollback
6. # Dependencies: PyMC as well as all PyMC dependencies.
7. # References: Gelman et al, 2021: http://www.stat.columbia.edu/~gelman/book/BDA3.pdf
8. #              Kruske Doing Bayesian Data Analysis Text
9. #               Betancourt & Girolami (2013) https://arxiv.org/pdf/1312.0906.pdf
10. #-------------------------------------------------------------------------------------------
------------------
11. """
12. To begin, let's import all of our dependencies, including our data and python packages
13. """
14. import arviz as az
15. import matplotlib.pyplot as plt
16. import numpy as np
17. import pandas as pd
18. import pymc as pm
19. import aesara
20. import matplotlib.pyplot as plt
21. import pdb
22. from mpl_toolkits.mplot3d import Axes3D
23. import json
24. import pickle # python3
25. import seaborn as sns
26. if __name__ == '__main__':                              #This statement is to allow for
parallel sampling in windows. Linux distributions don't require this.
27.     print(f"Running on PyMC3 v{pm.__version__}")
28.     color = '#87ceeb'
29.     az.style.use("arviz-darkgrid")
30.
31.     """
32.     Here we will load data in, and do necessary extraction. For the moment, we are interested in
purely excitatory responses on pulse trains
33.     """
34.     data = pd.read_csv("C:\CodeRepos\Statistics\INS_statTable_MKIV.csv")        #Use pandas to read
in data
35.
36.     data1 = data.loc[data['Is_Responsive'] == 1]             #Responses driven by INS
37.     data1.reset_index(drop=True, inplace = True)
38.     data2 = data1.loc[data1['Number_of_Pulses']>1]           #Pulse trains
39.     data2.reset_index(drop=True, inplace = True)
40.     data3 = data2.loc[np.isnan(data2['Max_BARS_Z'])==0]      #Take care of any nans
41.     data3.reset_index(drop=True, inplace = True)
42.     data4 = data3.loc[data1['Max_BARS_Z']>0]                 #Purely excitatory, which is the
vast majority of responses
43.     data4.reset_index(drop=True, inplace = True)
44.
```

```
45.        data = data4                                                    #Don't need full dataframe
46.        """
47.        Convert power to energy based on laser power levels and pulse widths, then save this into the
dataframe
48.        """
49.        Xenergy = data.Energy.values
50.        lenData = len(Xenergy)
51.        XenergyPerPulse = np.zeros((lenData,))
52.        XPW = data.Pulse_Width.values
53.        for ck in range(lenData):
54.
55.            XenergyPerPulse[ck] = Xenergy[ck]/XPW[ck]
56.            if XenergyPerPulse[ck] < 0:
57.                XenergyPerPulse[ck] = 0
58.        data['XenergyPerPulse'] = XenergyPerPulse
59.
60.        XenergyPerPulse = data.XenergyPerPulse
61.        #Grab response variable
62.        MaxZ = data["Max_BARS_Z"].astype(aesara.config.floatX)            #Convert to tensor
63.        MaxZ = np.log(MaxZ+0.1)
64.        #Plot distribution of data (log scale)
65.        sns.distplot(MaxZ, kde=True)
66.
67.
68.        """
69.        Now let's setup some meta data for our model analyses. We will set the number of burn in samples,
which "primes" the markov chain Monte Carlo (MCMC) algorithm, and number of
70.        samples to draw from the posterior. In general, less "well behaved" data will require more samples
to get MCMC to converge to steady state.
71.        """
72.        numBurnIn = 4000
73.        numSamples = 5000
74.        RANDOM_SEED = 7
75.        """
76.        Since we are doing a within-subjects repeated measures design, we need to create a mapping between
subjects and data. Each animal had a 16 channel recording array in A1 that
77.        is recording from different groups of neurons. So we sort by animal and electrode
78.        """
79.        animal_codes = np.unique(data.animal_code)
80.        animal_codes_map = np.arange(0,len(animal_codes))
81.        newCodes = np.zeros((len(data.animal_code)),dtype=int)
82.        for ck in range(len(data.animal_code)):
83.            curCode = data.animal_code[ck]
84.            newCode = np.where(curCode == animal_codes)
85.            newCode = newCode[0][0]
86.            newCodes[ck] = int(newCode)
87.        data['animal_code'] = newCodes
88.        animal_code_idx = data.animal_code.values
89.        n_channels = len(data.animal_code.unique())
90.        """
91.        Finally get our independent variables, ISI and energy per pulse
92.        """
93.        XDist = data.ISI.values
94.        XDist = np.log(XDist+0.1)
95.
96.        XenergyPerPulse = data['XenergyPerPulse']#np.log(data['XenergyPerPulse']+0.1)
97.        XenergyPerPulse = np.asarray(np.log(XenergyPerPulse+0.1))
98.        # Plot data vs predictors
99.        fig = plt.figure()
100.        ax = fig.add_subplot(projection='3d')
101.        ax.scatter(XenergyPerPulse,XDist,data['Max_Z_Score'])
102.        plt.xlabel('Energy')
103.        plt.ylabel('ISI')
104.
```

```
105.        """
106.        Now define the model
107.        """
108.        pdb.set_trace()
109.        with pm.Model() as Heirarchical_Regression:
110.            # Hyperpriors for group nodes
111.            mu_a = pm.Normal("mu_a", mu=0.0, sigma=1)
112.            sigma_a = pm.HalfNormal("sigma_a", 5)
113.            mu_b = pm.Normal("mu_b", mu=0.0, sigma=1)
114.            sigma_b = pm.HalfNormal("sigma_b", 5)
115.            mu_b2 = pm.Normal("mu_b2",mu=0.0, sigma=1)
116.            sigma_b2 = pm.HalfNormal("sigma_b2",5)
117.            mu_b3 = pm.Normal("mu_b3", 1)
118.            sigma_b3 = pm.HalfNormal("sigma_b3",5)
119.
120.            sigma_nu = pm.Exponential("sigma_nu",5.0)
121.            #Base layer
122.            nu = pm.HalfCauchy('nu', sigma_nu)          #Nu for robust regression
123.            a_offset = pm.Normal('a_offset', mu=0, sigma=1, shape=(n_channels))
124.            a = pm.Deterministic("a", mu_a + a_offset * sigma_a)
125.
126.            b1_offset = pm.Normal('b1_offset', mu=0, sigma=1, shape=(n_channels))
127.            b1 = pm.Deterministic("b1", mu_b + b1_offset * sigma_b)
128.
129.            b2_offset = pm.Normal("b2_offset",mu=0, sigma=1, shape=(n_channels))
130.            b2 = pm.Deterministic("b2", mu_b2 + b2_offset*sigma_b2)
131.
132.            b3_offset = pm.Normal("b3_offset",mu=0, sigma=1, shape=(n_channels))
133.            b3 = pm.Deterministic("b3", mu_b3 + b3_offset*sigma_b3)
134.
135.            eps = pm.HalfCauchy("eps", 5,shape=(n_channels))
136.
137.            regression = a[animal_code_idx] + (b1[animal_code_idx] * XenergyPerPulse) +
     (b2[animal_code_idx] * XDist) +(b3[animal_code_idx]*XenergyPerPulse*XDist)
138.
139.            likelihood = pm.StudentT("MaxZ_like",nu=nu,mu=regression,sigma=eps[animal_code_idx], observed=
     MaxZ)
140.
141.        """
142.        Now we run the model!
143.        """
144.        with Heirarchical_Regression:
145.            if __name__ == '__main__':
146.                step = pm.NUTS()
147.                rTrace = pm.sample(numSamples, tune=numBurnIn, target_accept=0.95,chains = 4)
148.                #rTrace = pm.sampling_jax.sample_numpyro_nuts(numSamples, tune=numBurnIn,
     target_accept=0.95,chains = 4)
149.
150.        """
151.        Now do model analytics
152.        """
153.        intercept = rTrace.posterior["a"]                     #Grab the posterior distribution of a
154.        EnergySlope = rTrace.posterior["b1"]                     #Grab the posterior distribution of b1
155.        ISISlope = rTrace.posterior["b2"]                    #Grab the posterior distribution of B
156.        InteractionSlope = rTrace.posterior["b3"]                     #Grab the posterior distribution of B
157.        err = rTrace.posterior["eps"]                    #Grab the posterior distribution of model error
158.        f_dict = {'size':16}
159.
160.        fig, ([ax1, ax2, ax3], [ax4, ax5, ax6]) = plt.subplots(2,3, figsize=(12,6))
161.        for ax, estimate, title, xlabel in zip(fig.axes,
162.                                [intercept, EnergySlope, ISISlope,InteractionSlope, err],
163.                                ['Intercept', 'Energy Slope','ISI Slope','Interaction Slope','Error
     Parameter'],
164.                                [r'$a$', r'$\beta1$', r'$\beta 2$', r'$\beta 3$' , r'$err$']):
```

```python
165.            pm.plot_posterior(estimate, point_estimate='mode', ax=ax, color=color,hdi_prob=0.95)
166.            ax.set_title(title, fontdict=f_dict)
167.            ax.set_xlabel(xlabel, fontdict=f_dict)
168.
169.    """
170.    Let's check out model with posterior predictive checks
171.    """
172.    with Heirarchical_Regression:
173.        if __name__ == '__main__':
174.            ppc = pm.sample_posterior_predictive(rTrace, random_seed=RANDOM_SEED)
175.
176.    az.plot_bpv(ppc, hdi_prob=0.95,kind='p_value')
177.    az.plot_ppc(ppc)
178.
179.    """
180.    Now let's plot our trace diagnostics
181.    """
182.
183.    #pm.model_to_graphviz(Heirarchical_Regression)
184.
185.    az.plot_trace(rTrace, var_names=["mu_a", "mu_b", "mu_b2", "mu_b3", "sigma_a",
"sigma_b","sigma_b2","sigma_b3", "eps"])
186.
187.    az.plot_trace(rTrace, var_names=["a"])
188.
189.    az.plot_trace(rTrace, var_names=["b1"])
190.
191.    az.plot_trace(rTrace, var_names=["b2"])
192.
193.    az.plot_trace(rTrace, var_names=["b3"])
194.
195.    az.plot_trace(rTrace, var_names=["nu"])
196.    plt.show()
197.    pdb.set_trace()
198.    az.to_netcdf(rTrace,filename='HierModel_Var5_StudentT_PerPulseScaled_SemilogT.netcdf')
199.    az.to_netcdf(ppc,filename='HierModel_Var5_StudentT_PerPulseScaled_Semilog_ppc.netcdf')
200.
```

DBS_LFP_GenData.py

```python
1. #----------------------------------------------------------------------------------------
----
2. #
3. # Date: 12/16/2023
4. # Purpose: Generate data to address asymptotics of Bayesian vs Frequentist inference on a DBS-LFP model
5. #----------------------------------------------------------------------------------------
----
6. from mfm import MFM          #This is the mean-field model of DBS-LFP. See mfm for details
7. import numpy as np
8. import matplotlib.pyplot as plt   #Helpful for plotting
9. import pdb
10. #Keywards to set up models
11. kwargsDBS = {                      #Dopamine depleted, continuous DBS, 100us pulsewidth
12.        'cDBS': True,
13.        'cDBS_amp': 0.01,   #1.8 if doing driven responses
14.        'cDBS_f': 130,
15.        'cDBS_width': 100,  #240 if doing driven responses
16.        'DD' : True,
17.        'verbose' : False,
```

```
18.          'tstop'    : 15
19.      }
20. kwargsStimless = {                        #Dopamine depleted, no stim
21.          'cDBS': False,
22.          'DD' : True,
23.          'verbose' : False,
24.          'tstop'    : 15
25.      }
26. # Let's set up the model!
27. DBS_LFP = MFM(**kwargsDBS)                    #Model that contains subthreshold DBS, ie should be
    identical in a PD model to no stim
28. Stimless_LFP = MFM(**kwargsStimless)          #Model that recieves no stimulation whatsoever
29. # Let's setup some data generating parameters
30. numtrials = 2000                    #Number of trials to run the model.
31. BetaPower_NoStim = np.zeros((numtrials,))
32. BetaPower_Stim = np.zeros((numtrials,))
33. #Some helpful defs here to calculate beta band power
34. def calcBetaPower(PXX):
35.      betaband = [27,62]
36.      beta = PXX[betaband[0]:betaband[1]]
37.      deltabeta = 0.48828125
38.      linBeta = np.power(10,beta/10)
39.      betapower = 2*np.sum(linBeta*deltabeta)
40.      return betapower
41. #Get our data!
42. for ck in range(numtrials):
43.      DBS_LFP.run()
44.      newPXXStim = DBS_LFP.getPXX()
45.      BetaPower_Stim[ck] = calcBetaPower(newPXXStim)
46.      Stimless_LFP.run()
47.      newPXXStimless = Stimless_LFP.getPXX()
48.      BetaPower_NoStim[ck] = calcBetaPower(newPXXStimless)
49.      #Need to clear model vars
50.      DBS_LFP = MFM(**kwargsDBS)
51.      Stimless_LFP = MFM(**kwargsStimless)
52. pdb.set_trace()
53. import pickle as pl
54. pl.dump(BetaPower_Stim, open( "BetaPowerStim.p", "wb" ) )
55. pl.dump(BetaPower_NoStim, open( "BetaPowerNoStim.p", "wb" ) )
56.
```

BEST_Comparison.py

```
1. #------------------------------------------------------------------
2. #
3. # Date: 12/23/23
4. # Purpose: This is to demonstrate Bayesian Estimation Supercedes the T-Test in PyMC
5. # For group comparisons. See the original Kruscke paper:
   https://jkkweb.sitehost.iu.edu/articles/Kruschke2013JEPG.pdf
6. # Data: BGTC circuit Dopamine depleted DBS vs no DBS.
7. # Note: Code adapted from Kruscke's original paper and the PyMC BEST tutorial
8. #------------------------------------------------------------------
9. import numpy as np
10. from scipy.stats import ttest_ind
11. import matplotlib.pyplot as plt
12. import pymc as pm
13. import pandas as pd
14. import arviz as az
15. import pdb
```

```
16. import pickle as pl
17. from scipy.stats import mode
18.
19. #Let's define the Bayesian Estimates Supersedes the T-Test (BEST) model.
20. if __name__ == '__main__':
21.     #To begin BEST estimation of mean difference between two groups, begin by getting total sample
statistics
22.     with open('BetaPowerStimComparison.p','rb') as f:
23.         DBS = pl.load(f)
24.     with open('BetaPowerNoStimComparison.p','rb') as f:
25.         NoStim = pl.load(f)
26.     totalData = pd.DataFrame(
27.         dict(value=np.r_[DBS, NoStim], group=np.r_[["DBS"] * len(DBS), ["NoStim"] * len(NoStim)]))
28.
29.     group_mu = totalData.value.mean()
30.     group_sigma = totalData.value.std() * 2
31.     #Okay, let's define our model
32.     with pm.Model() as best:
33.         group1_mean = pm.Normal("group1_mean",mu=group_mu,sigma=group_sigma)
34.         group2_mean = pm.Normal("group2_mean",mu=group_mu,sigma=group_sigma)
35.         #This particular model does use uniform distributions on sigma, so need to be careful here. We
know from the data that this encompases
36.         #All sigmas of interest, so we are not truncating data. Care should be taken when using one's
own data. Or just use a normal distribution instead
37.         sig_low = 0.00001
38.         sig_high = 10
39.         group1_std = pm.Uniform("group1_std", lower=sig_low, upper=sig_high)
40.         group2_std = pm.Uniform("group2_std", lower=sig_low, upper=sig_high)
41.         #Following Kruscke's lead here
42.         nu_minus_one = pm.Exponential("nu_minus_one", 1 / 29.0)
43.         nu = pm.Deterministic("nu", nu_minus_one + 1)
44.         lambda1 = group1_std ** -2
45.         lambda2 = group2_std ** -2
46.
47.         group1 = pm.StudentT("group1", nu=nu, mu=group1_mean, lam=lambda1, observed=DBS)
48.         group2 = pm.StudentT("group2", nu=nu, mu=group2_mean, lam=lambda2, observed=NoStim)
49.         #Get group statistics distributions of mean,stand dev, and effect size
50.         diff_of_means = pm.Deterministic("difference of means", group1_mean - group2_mean)
51.         diff_of_stds = pm.Deterministic("difference of stds", group1_std - group2_std)
52.         effect_size = pm.Deterministic("effect size", diff_of_means / np.sqrt((group1_std ** 2 +
group2_std ** 2) / 2))
53.
54.     #Now that we have our model, let's start the sampling!
55.     with best:
56.         trace = pm.sample(2000, tune=500, target_accept=0.90,chains = 4)
57.     #Alright! Let's plot posteriors
58.     az.plot_posterior(trace,var_names=["group1_mean", "group2_mean", "group1_std",
"group2_std"],hdi_prob=0.95,point_estimate = 'mode')
59.     az.plot_posterior(trace,var_names=["difference of means", "difference of stds", "effect
size"],hdi_prob=0.95,point_estimate = 'mode')
60.     plt.show()
61.
62.
```

T-TestTutorial.py

```
1. #------------------------------------------------------------------------------
2. #Author: Redacted for Double Blind Peer Review
3. #Date: 12/18/23
4. #Purpose: Demonstrate the role of sample size on two comparison t-tests and Bayes t-tests
5. #Requires: Data from DBS_LFP_GenData.py
6. #------------------------------------------------------------------------------
7. import numpy as np
```

```
8.  from scipy.stats import ttest_ind
9.  import matplotlib.pyplot as plt
10. import pymc as pm
11. import pandas as pd
12. import arviz as az
13. import pdb
14. import pickle as pl
15. from scipy.stats import mode
16. import nutpie
17. #Let's define the Bayesian Estimates Supersedes the T-Test (BEST) model.
18. if __name__ == '__main__':
19.     def BEST(group_1,group_2):
20.         totalData = pd.DataFrame(
21.         dict(value=np.r_[group_1, group_2], group=np.r_[["group1"] * len(group_1), ["group2"] *
len(group_2)]))
22.         #totalData = np.concatenate(group1,group2)
23.         group_mu = totalData.value.mean()
24.         group_sigma = totalData.value.std() * 2
25.         with pm.Model() as best:
26.             group1_mean = pm.Normal("group1_mean",mu=group_mu,sigma=group_sigma)
27.             group2_mean = pm.Normal("group2_mean",mu=group_mu,sigma=group_sigma)
28.             #This particular model does use uniform distributions on sigma, so need to be careful
here. We know from the data that this encompases
29.             #All sigmas of interest, so we are not truncating data. Care should be taken when using
one's own data. Or just use a normal distribution instead
30.             sig_low = 0.00001
31.             sig_high = 10
32.             group1_std = pm.Uniform("group1_std", lower=sig_low, upper=sig_high)
33.             group2_std = pm.Uniform("group2_std", lower=sig_low, upper=sig_high)
34.             #Following Kruscke's lead here
35.             nu_minus_one = pm.Exponential("nu_minus_one", 1 / 29.0)
36.             nu = pm.Deterministic("nu", nu_minus_one + 1)
37.             lambda1 = group1_std ** -2
38.             lambda2 = group2_std ** -2
39.
40.             group1 = pm.StudentT("group1", nu=nu, mu=group1_mean, lam=lambda1, observed=group_1)
41.             group2 = pm.StudentT("group2", nu=nu, mu=group2_mean, lam=lambda2, observed=group_2)
42.             #Get group statistics distributions of mean,stand dev, and effect size
43.             diff_of_means = pm.Deterministic("difference of means", group1_mean - group2_mean)
44.             diff_of_stds = pm.Deterministic("difference of stds", group1_std - group2_std)
45.             effect_size = pm.Deterministic("effect size", diff_of_means / np.sqrt((group1_std ** 2 +
group2_std ** 2) / 2))
46.         #compiled_model = nutpie.compile_pymc_model(best)
47.         #trace = nutpie.sample(compiled_model,tune=2000,draws=2000,chains=4,target_accept=0.90)
48.         with best:
49.             trace = pm.sample(2000, nuts_sampler="numpyro", tune=500, target_accept=0.90,chains = 4)
50.
51.         diff_of_means_hdi =  az.hdi(trace.posterior, var_names=["difference of means"],hdi_prob=0.95)
52.         diff_of_means_hdi  =  diff_of_means_hdi['difference of means'].data
53.         dataSummary = az.summary(trace.posterior,var_names=["difference of means"],hdi_prob=0.95)
54.         gatherChains = np.squeeze(np.reshape(trace.posterior['difference of means'].data,(1,2000*4)))
55.
56.         MAPest = mode(gatherChains)[0]#[0]
57.
58.         if diff_of_means_hdi[0] < 0 <= diff_of_means_hdi[1]:
59.             acceptNull = True
60.         else:
61.             acceptNull = False
62.         effect_size_hdi =  az.hdi(trace.posterior, var_names=["effect size"],hdi_prob=0.95)
63.         return acceptNull,MAPest
64.     #Okay, lets load in our data
65.     with open('BetaPowerStim.p','rb') as f:
66.         BetaStim = pl.load(f)
67.     with open('BetaPowerNoStim.p','rb') as f:
```

```
68.         BetaNoStim = pl.load(f)
69.     #diffmeans = BEST(BetaStim,BetaNoStim)
70.     numComparisons = len(BetaStim)            #Equal group sizes, just want to shuffle number of n's
71.     bestMap = []
72.     bestResult = []
73.     pvalResult = []
74.     ttestcounter = 0
75.     BestCounter = 0
76.     ttestTotal = []
77.     BestTotal = []
78.     for ck in range(2,numComparisons,5):
79.         BetaStim = np.random.permutation(BetaStim)
80.         betaStimCur = BetaStim[0:ck]
81.         BetaNoStim = np.random.permutation(BetaNoStim)
82.         betaNoStimCur = BetaNoStim[0:ck]
83.         Result,MAPest = BEST(betaStimCur,betaNoStimCur)
84.         bestMap.append(MAPest)
85.         if Result == False:
86.             BestCounter = BestCounter + 1
87.         bestResult.append(Result)
88.         BestTotal.append(BestCounter)
89.         t_test = ttest_ind(betaStimCur,betaNoStimCur)
90.         pval = t_test[1]
91.         pvalResult.append(pval)
92.         if pval < 0.05:
93.             correct = True
94.         else:
95.             ttestcounter = ttestcounter+1
96.         ttestTotal.append(ttestcounter)
97.         print(ck)
98.     pdb.set_trace()
99.     Ns = range(2,numComparisons,5)
100.    plt.plot(Ns,BestTotal)
101.    plt.plot(Ns,ttestTotal)
102.    plt.show()
103.    plt.plot(Ns,pvalResult)
104.    plt.plot(Ns,bestMap)
105.    plt.show()
106.
```