Binary Discriminator Facilitates GPT-based Protein Design

Zishuo Zeng[1,4*], Rufang Xu[1], Jin Guo[1], Xiaozhou Luo[1,2,3,4*]

1. Synceres Biosciences Co. Ltd., Shenzhen 518100, China
2. Shenzhen Key Laboratory for the Intelligent Microbial Manufacturing of Medicines, Shenzhen Institute of Advanced Technology, Chinese Academy of Sciences, Shenzhen, 518055, CN
3. CAS Key Laboratory of Quantitative Engineering Biology, Shenzhen Institute of Synthetic Biology, Shenzhen Institute of Advanced Technology, Chinese Academy of Sciences, Shenzhen, 518055, CN
4. Center for Synthetic Biochemistry, Shenzhen Institute of Synthetic Biology, Shenzhen Institutes of Advanced Technology, Chinese Academy of Sciences, Shenzhen 518055, CN
* Corresponding authors
Emails: zs.zeng@siat.ac.cn, xurufang@synceres.com, guojin@synceres.com, xz.luo@siat.ac.cn

Abstract

Generative pre-trained transformers (GPT) models provide powerful tools for de novo protein design (DNPD). GPT-based DNPD involves three procedures: a) finetuning the model with proteins of interest; b) generating sequence candidates with the finetuned model; and c) prioritizing the sequence candidates. Existing prioritization strategies heavily rely on sequence identity, undermining the diversity. Here, we coupled a protein GPT model with a custom discriminator, which enables selecting candidates of low identity to natural sequences while highly likely with desired functions. We applied this framework to creating novel antimicrobial peptides (AMPs) and malate dehydrogenases (MDHs). Experimental verification pinpointed four broad-spectrum AMPs from 24 candidates. Comprehensive computational analyses on the prioritized MDHs candidates provide compelling evidence for the anticipated function. During experimental validation, 4/10 and 3/10 natural MDHs and generated-prioritized novel candidates, respectively, were expressed and soluble. All the soluble candidates (3/3) are functional in vitro. This framework is time- and data-efficient and may therefore considerably expedite the DNPD process.

Key words: GPT, transformers, protein *de novo* design, deep learning, transfer learning, antimicrobial peptide, malate dehydrogenase

Abbreviations used: generative pre-trained transformers (GPT), natural language processing (NLP), generative adversarial network (GAN), language model (LM), recurrent neural networks (RNN), antimicrobial peptide (AMP), malate dehydrogenase (MDH), enzyme commission (EC), minimum inhibitory concentration (MIC).

Introduction

de novo protein design (DNPD), i.e., generating artificial proteins with desired functions, has proven to be a powerful tool in overcoming bottlenecks across various fields, including drug discovery [1-3], biosensor engineering [4-6], and synthetic biology [7-9]. DNPD is being accelerated by recent advancements in generative large language models (LLMs, including GPT) [10], for examples, ProtGPT2 [11] and ProGen [12]. Similar to the LLMs for natural language processing (NLP) [13], these protein generative models were trained on large amount of "text corpus" (proteomes) and can generate "sentences" (protein sequences) that captures the "language semantics" (physicochemical and thermodynamic properties similar to natural proteins). Besides, just like LLMs for NLP can be finetuned to adapt to a specific task (such as automatic dialogues [14], summarizing text [15], and poetry writing [16]), protein generative models can be finetuned [17] to generate artificial proteins bearing a specific function of interest. Therefore, protein LLM holds great promise in DNPD.

However, evaluating the quality of the generated sequences remains a challenge, as protein sequences are not human-understandable like natural languages. In the work of ProGen [12], evaluating the generated sequences was mainly done by per-token log-likelihood scoring, which computes the per-residue conditional probabilities along the sequence, conceptually akin to perplexity, which measures the model's confidence in the generated sequence. However, limitations of perplexity in the NLP field have been noticed, such as sensitivity to text length and repeated content [18], inability to reflect semantic coherence [19], and disagreements with human judgements [20]. Another common approach for sequence evaluation is through its identity to known natural proteins of interest, which was used in a generative adversarial network (GAN)-based framework, ProteinGAN [21]. In this approach, the generated sequences are prioritized based on their similarity to the known homologs. Both per-token log-likelihood and sequence identity may overlook the promising (likely to possess the desired protein function) but novel (very different from known natural proteins) sequences – the dark matters in the potential proteome universe.

In addition to per-token log-likelihood and sequence identity, a variety of existing protein predictors may be used to prioritizing the generated protein candidates from different perspectives,

such as protein structure [22] and enzyme commission (EC) number [23]. Johnson et al. also

incorporated multiple sequence-based and structure-based tools (e.g., Rosetta [24], ESM-v1 [25],

CARP-640M [26], ProteinMPNN [22], MIF-ST [27], and ESM-IF [28]) for predicting whether the generated

enzymes possess *in vitro* activity [29]. However, using these existing predictors suffer from multiple

limitations. First, none of these predictors directly reports the likelihood of the desired functions.

Second, it requires non-trivial efforts in benchmarking and programming environment setup. Third,

these predictors may not be applicable to different types of proteins (e.g., EC number prediction

only applies to enzymes).

To address the limitations of current prioritization strategies, here we coupled ProtGPT2 with a

convolutional neural network (CNN)-based protein discriminator. Positive protein data are used to

finetune the protein generator, ProtGPT2; while both positive and negative data are used to train the

discriminator, which will be used to prioritize the generated sequence candidates, allowing a one-

stop solution to DNPD for different types of proteins without the dependencies on external tools. A

pre-trained LLM, ProtTrans, was used for protein feature extraction for the discriminator. Such LLM-

based contextualized embedding technique has been proven to outperform traditional protein

features such as one-hot encoding [30-32]. The efficacy of the framework was then demonstrated by

two distinct types of sequences: AMPs as representatives of short sequences lacking homology,

and malate dehydrogenases (MDHs) as representatives of longer sequences with inferable

homology. In addition, the prompts length and size of finetuning set have been investigated to fully

elucidate the potential of this framework. Altogether, our results position this framework as a

powerful and efficient tool to advance DNPD.

85   **Materials and Methods**

Data preparation

We   downloaded   3,011   antibacterial   peptides   from   SATPdb   database   [33]

(http://crdd.osdd.net/raghava/satpdb/, accessed on 8/24/2022) as positive set. We filtered this

peptide set to only include those composed of canonical amino acids and that were less than or

equal to 50 residues in length, resulting in 2,879 peptides, which we refer to as the AMP set. For the

negative set, we downloaded 13,225 short (less than or equal to 50-residue-long) protein

sequences/peptides from UniProt [34] (https://www.uniprot.org/, accessed on 8/16/2022). We

removed sequences containing certain keywords ("antimic*", "antibac*", "*toxic*", "defensive") from

the UniProt description. This negative set curation is consistent with other relevant methods [35]. To

create a balanced negative set and to avoid bias in sequence length distribution, we randomly

sampled from this UniProt pool strictly following the AMP set's length distribution. For example, if

there were 179 AMPs that are 21-residue-long, then we sampled exactly 179 sequences that are

21-residue-long. In total, we collected 2,879 non-AMPs as negative set.

We gathered a positive set of 16,706 MDH sequences from the training set of Repecka et al.'s

study [21]. For negative set, we searched "enzyme" on UniProt (https://www.uniprot.org/) and

downloaded all reviewed sequences (n=568,002, accessed on 8/16/2022). To later evaluate how

well our model discriminates MDH from functionally close enzymes, we used the validation set

(n=213) from Repecka et al. as positive set; we also identified 5,766 EC1.1.1.X sequences (first

three enzyme commission [EC] [36] levels are 1.1.1 and the last level is not 37) and 543 EC1.1.X.X

sequences (first three EC levels are 1.1 and the third level is not 1) as negative set. We then

narrowed these sequences to those a) whose EC numbers are not 1.1.1.37 (the EC number of

MDH); b) whose sequence lengths are within the range of the positive set's (64-505); and c) that are

not functionally close (EC1.1.1.X or EC1.1.X.X), resulting in 206,596 non-MDH sequences as

negative set.

To compile a balanced negative set without bias in sequence length distribution, we

enumerated the number of sequences by an interval of 50 and sampled that amount of non-MDH

sequences for that interval. For example, if there were 39 MDH sequences that are 110-160

residues long, then we sampled 39 non-MDH sequences of that length range. As a result, we

collected 16,706 non-MDH sequences as negative set.

Since the 16,706 MDH sequences may vary a lot (with a length range of [64-505]), to ensure

consistency during the finetuning process, we clustered the MDH sequences into multiple clusters

using cd-hit [37]. To reduce the number of resulting clusters, we used the lowest allowed sequence

identity threshold (0.4) and word length (2) for clustering. A total of 82 clusters were generated and

the majority of these clusters are singletons or very small. The four largest clusters constituted

97.3% (n=16,258) of all MDH sequences. We termed these four clusters as *cluster765*, *cluster2029*,

cluster5987, and *cluster7477*, with the number inside the name indicating the number of sequences

in that cluster (e.g., *cluster765* contain 765 sequences).

Generator finetuning and sample generation

For the AMP generation task, we finetuned ProtGPT2 [11] (https://huggingface.co/nferruz/ProtGPT2)

with default parameters on the AMP set. We then generated 3,000 sequences using text generation

pipelines from Python (v. 3.8.15) transformers package (v. 4.26.0.dev0) [38]

(https://huggingface.co/docs/transformers/index) with maximum lengths being 20. Note that the

generated sequences may exceed this maximum length. As negative control for the finetuning

process, we also generated 3,000 sequences using the non-finetuned ProtGPT2 model.

For the MDH generation task, we finetuned the ProtGPT2 model using four separate datasets:

cluster765, *cluster2029*, *cluster5987*, and *cluster7477*, resulting in four finetuned models. To

generate new sequences, we supplied each finetuned model with a starter sequence of varying

length, ranging from 0-100 residues, taken from the representative sequence of the corresponding

finetuning set. The maximal length for generation is set to be 400. The results of this sample

generation are summarized in Table 1 below. *All finetuning tasks were conducted on* NVIDIA A100

(80G) graphical processing unit (GPU).

Table 1. Summary of the MDH sequence generation.

Group name	Group meaning	Template	Starter seq. length	No. generated seq.
random	randomly generated according to	representative seq. of	0	1000

	the amino acid occurrence distribution of all MDH	*cluster7477*	10	1000
			50	1000
			100	1000
noft	generated by non-finetuned ProtGPT2	representative seq. of *cluster7477*	0	1000
			10	1000
			50	1000
			100	1000
cluster765	finetuned by *cluster765*	representative seq. of *cluster765*	0	1000
			10	1000
			50	1000
			100	1000
cluster2029	finetuned by *cluster2029*	representative seq. of *cluster2029*	0	1000
			10	1000
			50	1000
			100	1000
cluster5987	finetuned by *cluster5987*	representative seq. of *cluster5987*	0	1000
			10	1000
			50	1000
			100	1000
cluster7477	finetuned by *cluster7477*	representative seq. of *cluster7477*	0	1000
			10	1000
			50	1000
			100	1000

Discriminator training

For the AMP discriminator, we split the balanced AMP/non-AMP set (n=2,879+2,879) into training,

validation, and testing set in 8:1:1 ratio. From the MDH/non-MDH balanced set (n=16,706+16,706),

we randomly sampled 4,500 sequences for training (13.47%) and 500 sequences for validation

(1.50%), and the remaining 28,412 sequences were used for testing (85.03%). We performed

discriminator training, hyperparameter tuning, and performance evaluation on training set, validation

set, and testing set, respectively.

To extract features from the protein sequences, we utilized the ProtT5-XL-UniRef50 model,

which was pretrained and publicly available in the ProtTrans project [39]. We chose ProtT5-XL-

UniRef50 among others in ProtTrans because it achieved the best performance most often in

different predictive tasks [39]. We used the transformers package (v. 4.26.0.dev0) in Python (v.

3.8.15) to implement the embedding, with maximum lengths of 50 for the AMP task and 505 for the

MDH task.

For the discriminator architecture, we used Keras package (v. 2.10.0) [40] to implement a

convolutional neural network (CNN) followed by a fully connected neural network (FCNN) (Figure 1).

Each convolution layer was coupled with a maximum-pooling layer, and the last maximum-pooling

layer was flattened, which was fed to the FCNN. Recticfied linear unit [41] was used as activation

function for all layers except for the output layer, where the activation function was sigmoid function

[42] instead. We then used Adam [43] as the optimizer, binary cross-entropy (Eqn. 1) as the loss

function, and accuracy (Eqn. 2) as the evaluation metric. We set maximum number of training

epochs to be 100 with early stopping (patience=5). We adopted the following hyperparameter setup

after tuning: three 3×3 convolution filter, each followed by 2×2 max-pooling layer; a flatten layer;

three fully connected layers (with 1024, 512, 256 nodes, respectively) and one output layer. Tunable

hyperparameters include number of filters in CNN, kernel size in CNN, maximum-pooling size,

number of dense layers in FCNN, number of nodes in each FCNN layer, batch size, and learning

rate of optimizer. Embedding and training were carried out on a NVIDIA A100 (80G) graphical

processing unit.

$$\text{binary cross\_enthropy} = -\frac{1}{N}\sum_{i=1}^{N}(y_i \cdot \log(\hat{y}_i) + (1 - y_i) \cdot \log(1 - \hat{y}_i)) \quad （\text{Eqn. 1}）$$

where N is the number of samples, y_i and $\hat{y}_i$ are the *i*-th actual and predicted label, respectively.

$$\text{accuracy} = \frac{TP + TN}{TP + TN + FP + FN} \quad （\text{Eqn. 2}）$$

where *TP*, *TN*, *FP*, and *FN* are true positive, true negative, false positive, and false negative,
respectively.

Bioinformatics analysis

We performed Pfam domain [44] scanning on all generated MDH sequences using HMMER package

[45] (v. 3.3.2). Pfam profiles were built using hmmerbuild command with Pfam seed alignment flatfile

and   and   Pfam   profile   flatfile   (downloaded   from

http://ftp.ebi.ac.uk/pub/databases/Pfam/current_release/Pfam-A.seed.gz   and

http://ftp.ebi.ac.uk/pub/databases/Pfam/current_release/Pfam-A.hmm.gz , respectively. accessed on

11/10/2022). The E-value threshold for Pfam domain scanning was set as 0.001.and we considered

a sequence to have MDH's signature domain if at least one "lactate/malate dehydrogenase" or

"Malate/L-lactate dehydrogenase" was identified.

We evaluated the sequence redundancy within *cluster765*, *cluster2029*, *cluster5987*,

cluster7477, as well as the generated MDH sequences using cd-hit (parameters set as default). We

defined "ratio of non-redundant sequences" as the number of non-redundant sequences determined

by cd-hit divided by the number of input sequences.

For every generated MDH sequence, we performed pairwise alignment using BLAST

standalone package [46] (v. 2.13.0+) against all known MDH sequences (n=16,706) and identified the

"best hit" (highest bit score) sequence. We recorded the identity between query (generated)

sequences and their corresponding best hit sequence. Based on these best hit sequences' identity

and ungapped alignment length, we utilized HFSP curve (homology-derived functional similarity of

proteins [47], HFSP=0) to visualize whether a generated sequence share the same function as its best

hit known MDH.

Sequence space visualization using t-SNE

We randomly selected 100 known MDHs from *cluster2029*, 100 MDH candidates generated by

cluster2029-finetuned ProtGPT2 that are prioritized (non-redudant and discriminator

prediction>0.95), 100 EC1.1.1.X and 100 EC1.1.X.X for visualization of sequence spatial distribution

with t-distributed stochastic neighbor embedding (t-SNE) algorithm [48]. Each of the selected

sequences were embedded by the ProtT5-XL-UniRef50 model [39] as an $L\times1024$ matrix (where L is

the length of the protein), which was then flattened into a $L\times1024$-long vector as protein-level

features. The t-SNE transformation from the embedded features to two-dimensional space was

conducted using Python scikit-learn package (v1.1.2) [49].

Mapping conservation to enzyme functionally important sites

Finetuned-generated MDH candidates that are a) non-redundant and b) with discriminator

prediction>0.95 were selected. We used a known MDH sequence (UniProt ID: P11708) with

determined protein structure (protein data bank [PDB] [50] ID: 4MDH) as the reference sequence and

was BLASTed against the selected MDH candidates. From the selected MDH candidates with

significant hit, 499 were randomly sampled and then subjected to multiple sequence alignment

(MSA) along with P11708 using MAFFT [51] program. The MSA-derived entropy scores were

computed using the msa package [52] in R. The conservation scores were calculated as the maximal

entropy minus the actual entropy at a given position, so that higher score indicates higher

conservation. Annotation of functionally important sites (substrate binding, NAD binding, and sulfate

binding) of 4MDH were obtained from PDB. Conservation scores were mapped to residue positions

in 4MDH. Visualization of 4MDH was performed using PyMOL [53].

Statistical analysis and visualization

214 Statistical analysis and visualization were conducted in R (v. 4.2.2) with ggplot2 package (v. 3.4.0).

215 Calculation for area under the receiver operating characteristic curve (ROC-AUC) was done with

216 pROC package [54] (v. 1.18.0).

Experimental validation of AMP candidates

Solid-phase peptide synthesis was used to synthesize crude peptides (which contained 40-70% of

the target peptide) by GenScript Biotech in Nanjing, China. Mass spectrometry was used to

determine their precise molecular weights. The peptides used for the minimum inhibitory

concentration (MIC) were further purified to a 90% degree of purity, as determined by high-

performance liquid chromatography.

We used six strains of bacteria in our experiment: four Gram-positive strains (*Staphylococcus*

aureus GDMCC 1.221, *Bacillus pumilus* GDMCC 1.225, *Bacillus subtilis* GDMCC 1.222, and

Kocuria rhizophila GMDCC 1.226) and two Gram-negative strains (*Escherichia coli* GDMCC 1.335

and *E. coli* DH5α). All strains were obtained from Guangdong Microbial Culture Collection Center in

Guangzhou, China, except for *E. coli* DH5α, which was maintained in our lab. Each bacterial strain

was streaked on Luriae-Bertani (LB) agar medium and incubated overnight at the optimum growth

temperature according to the provider's instructions. Individual colonies were picked and inoculated

into LB culture medium, which was then shaken at 200 rpm at the optimum growth temperature

overnight. The bacterial suspension was diluted 1:100 using fresh LB culture medium and then

cultured for 4-5 hours to reach the logarithmic phase (OD600 of 0.4-0.6). The suspension was

adjusted to OD600=0.1 by LB solution and then diluted 1,000 times. A volume of 100 μL cell

suspension was transferred into 96-well plates for the next test.

For the bacterial inhibition experiment, we used crude peptides with a target peptide content

of approximately 50% for ease of calculation. Freeze-dried peptide powders were dissolved in

dimethylsulfoxide (DMSO) to a concentration of 3 mM target peptide. For the antibacterial activity

test, peptides (or an equal volume of DMSO solution as a negative control) were added to 96-well

plates (each well containing 100 μL cell suspension). The peptide solution and fresh LB solution

were adjusted to reach a concentration of 60 μM. Blank controls were set up using LB solution

without peptide/DMSO. OD600 values were measured after shaking at 500 rpm at the optimum

growth temperature for 12 hours using a high-speed oscillating incubator (ZQZY-88BHS, Shanghai

Zhichu Instrument Co., Ltd., China). The blank control OD600 value was used for data

normalization. Dunnett's test was used to compare experimental groups with the control group (two-

sided) using OriginPro software (version 9.2, 64 bit). All experiments were performed with three

independent replicates.

The peptides used for the MIC determination were more than 90% pure. We prepared a series

of peptide concentrations ranging from 0.94 µM to 120 µM. The same culture steps were conducted

as described above, except that the final incubation step lasted for 16-18 hours. MICs were

determined as the minimum concentration of AMPs where bacteria showed no detectable growth.

All experiments were performed with three independent replicates.

Experimental validation of the MDH candidates

To evaluate the performance of our framework in generating functional enzymes, we randomly

selected 10 MDH candidates from a pool of candidates that are of high discriminator prediction

(>0.9) and low identity (<50%) to any natural MDHs included in ProteinGAN [21]. As positive controls,

we also randomly selected 10 natural MDHs from the training set of ProteinGAN [21].

Sequences were synthesized by Tsingke with codon optimization for expression in *E. coli*

BL21 (DE3), and subcloned into a pET-21a(+) plasmid with a His-tag at the 3' end. The integrity of

the obtained constructs was confirmed via DNA sequencing. Plasmids encoding the investigated

MDHs were transformed into chemically competent *E. coli* BL21 (DE3) cells. A single colony from a

transformant agar plate was picked and incubated in Luria Broth (LB) medium with 100 µg/mL

ampicilin, grown overnight at 37℃. For expression, 500 µL of this overnight culture was inoculated

into terrific broth (TB) medium (50 mL, containing 100 µg/mL ampicilin) and incubated at 37℃ and

180 rpm in a flask until the optical density at 600 nm (OD600) reached 0.6~0.8. Protein expression

was induced by the adding 1 mM Isopropyl β-d-1-thiogalactopyranoside (IPTG) and incubating at 16℃

with shaking at 180 rpm overnight.

The culture was centrifuged at 4,000 rpm for 10 min at 4℃ to pellet the cells. The supernatant

was discarded, and the pellet was resuspended in Tris-HCL buffer (100 mM, pH 7.5) supplemented

with 1 mg/mL lysozyme (Takara Bio). The mixture was incubated at 30℃ for 30 min and then cooled

to 0℃ on ice. Cells were disrupted by ultrasonication using Ultrasonic Homogenizer JY92-IIN

(Scientz) at 100 W with a cycle of 3-second pulse and 5-second pause) for 20 min. The cell debris

was removed by centrifugation at 16,000 rpm for 20 min at 4℃. The supernatant was collected for

protein purification.

The soluble recombinant MDHs were purified using Ni-NTA Agarose (Qiagen). The

supernatant was loaded onto the column and washed with a wash buffer (100 mM Tris-HCL buffer,

pH 7.5, 300 mM NaCl, 25 mM imidazole, 5% glycerol). Proteins were eluted with an elution buffer

(100 mM Tris-HCL buffer, pH 7.5, 300 mM NaCl, 333 mM imidazole, 5% glycerol). The eluent was

desalted using BeyoDesalt™ G-25 Midi Desalting Column (Beyotime Biotechnology) and 100 mM

Tris-HCL buffer. The concentration of the desalted protein solution was determined using a

NanoDrop 2000 system (Thermo Fisher Scientific).

To test for MDH activity, a reaction mixture (50 µL) in 100 mM Tris-HCL buffer containing 1

mM oxaloacetic acid and 1 mM NADH was prepared in a UV-transparent 96-well with a clear flat

bottom (Beyotime Biotechnology). The reaction was initiated by adding 50 µL of purified protein to

the mixture. The reaction was carried out at room temperature, and NADH oxidation to NAD+ was

monitored by measuring absorbance at 340 nm ($\varepsilon = 6.22$ mM^{-1} cm^{-1}) every 30 seconds for 30

minutes using an Infinite® 200 PRO plate reader (Tecan). All reactions were performed in triplicates,

and a mixture without purified protein served as the negative control.

For the biotransformation assay, the reaction mixture was scaled up to 250 µL and

incubated at 25℃ overnight. All the reactions were performed in triplicates, and the mixture without

purified protein served as the negative control. The biotransformation was quenched by adding

equal volume of acetonitrile, followed by thorough vortexing and centrifugation at 12,000 rpm for 1

min at room temperature. The supernatant was filtered through a 0.22 µm ultrafitration membrane

(Millipore), and malic acid was analyzed by HPLC-ESI-MS/MS on a 6475 Triple Quadrupole LC/MS

System (Aglient). Chromatographic separation was achieved on an Acquity UPLC HSS T3 Column

(1.8 µm, 2.1 × 150 mm; Waters) using a 1290 Infinity II ultra performance liquid chromatography

(UPLC) system (Agilent). The separation was performed at 30℃ with an isocratic elution of 90%

water (with 0.1% formic acid) and 10% methanol at a flow rate of 0.15 mL/min. The mass

spectrometer was operated in negative ion mode with multiple reaction monitoring (MRM), using

133 *m/z* and 115.1 *m/z* as precursor and product ions, respectively. Fragmentation voltage was set

to 60 V, collision energy to 5 V, gas temperature to 300°C, gas flow to 5 L/min, sheath gas pressure

to 11 L/min, capillary voltage to 3500 V, and nozzle voltage to 1000 V. Data acquisition and analysis

were performed using Agilent MassHunter Qualitative Analysis 10.0 (Agilent).

304   **Results**

Overview of the DNPD framework

We developed a convenient one-stop solution (Figure 1) for general-purpose protein design by

integrating a state-of-the-art protein generative model, ProtGPT2 [11] with a custom-built protein

discriminator. The ProtGPT2 model, a large-scale language model with 738 million parameters,

serves as the foundation for generating new protein sequences. The protein discriminator,

consisting of a convolutional neural network followed by a fully connected neural network (Figure

1A), is used to assess and prioritize the generated sequences. Protein sequence features are

extracted using ProtT5-XL-UniRef50, a model-based embedding framework in ProtTrans collection,

which comprises of 3 billion parameters [39]. The generative model is finetuned with a positive set of

protein sequences, while the discriminator is trained on a balanced dataset containing both positive

and negative protein sequences. As proof of concepts, we applied this framework to the design of

two distinct protein classes: antibacterial peptides (AMP) and malate dehydrogenases (MDH;

EC1.1.1.37).

Discriminators accurately classifies AMP/non-AMP and MDH/non-MDH sequences

For the AMP/non-AMP discriminator, the AMP and non-AMP sequences were obtained from

SATPdb database [33] and UniProt [34], respectively. Short peptides from UniProt that are shorter than

50 residues and without certain antimicrobial-relevant keywords were selected as non-AMPs [35].

Similarly, for the MDH/non-MDH discriminator, we acquired MDH sequences from Repecka et al. [21]

and non-MDH sequences randomly sampled from UniProt [34]. To ensure unbiased results, all

training, validation, and test sets were carefully balanced by randomly sampling negative sets to

mirror the sequence length distribution in positive sets. The discriminators achieved high accuracies

and converged rapidly (<100 epochs), demonstrating the effectiveness of transfer learning-based

embedding techniques. Specifically, the AMP/non-AMP discriminator achieved an accuracy of 0.81

on a balanced testing set of 576 samples (Figure 2A), while the MDH/non-MDH discriminator

attained an accuracy of 0.99 on a larger balanced test set of 28,412 samples (Figure 2A). It is

important to note that numerous AMP/non-AMP discriminators have been developed by other

researchers [55]. However, our framework is meant for de novo design for peptides/proteins in

general, instead of building a discriminator for a specific task such as classifying AMP.

To further evaluate the discriminators' capability to differentiate between functionally close

enzymes, we assembled additional datasets comprising EC1.1.1.X enzymes (n=5,766, excluding

EC1.1.1.37) and EC1.1.X.X enzymes (n=543, excluding EC1.1.1.X), as well as an additional

reserved set of 213 MDHs for further examination. All of these sequences were unseen during

training. The MDH/non-MDH discriminator achieved a 0.99 ROC-AUC for both EC1.1.1.X vs. MDHs

and EC1.1.X.X vs. MDHs (Figure 2B), highlighting its exceptional ability in differentiating between

functionally similar enzymes. Overall, the results demonstrated the effectiveness of the

discriminators in accurately distinguishing protein sequences of interest.

Finetuning increases the likelihood of the generated sequences being AMP or MDH

Finetuning essentially involves adapting a pre-trained LM to a custom input dataset, enabling the

updated LM's to generate content more closely aligned with the input's style [56]. We finetuned

ProtGPT2 with 2,879 known AMPs and subsequently generated 3,000 AMP candidates using the

finetuned model. During generation, the "maximal length" was set to 20 and no starter sequence

was provided, however, it was to be noted that the actual generated sequences may exceed the set

"maximal length". For comparison, we created an equal amount of a) random sequences, i.e.,

randomly constructed sequences following the length distribution as natural AMPs; b) "AA-imitating",

i.e., following natural AMPs' amino acid and length distribution; c) ProtGPT2-random sequences,

i.e., sequences generated by the non-finetuned ProtGPT2. As expected, the finetuned-generated

sequences are more likely to be actual AMPs than "AA-mimicking" and "ProtGPT2-random"

(prediction median 0.87 vs. 0.37 and 0.01, Wilcoxon signed rank test p-value<2.2e-16; Figure 3A).

Surprisingly, we noticed that the "AA-mimicking" group also reached moderately high prediction

(median=0.37; Figure 3A). This can be attributed to two reasons—a) there lacks gold standard

negative set and our positive set is relatively small (excluding anti-yeast, anti-viral, etc.); and b)

cationic charge and hydrophobicity are the dominant determinants of antimicrobial effects [57-59].

Since these "AA-mimicking" peptides closely mimics the amino acid profile of natural AMPs, they

inherit the cationic charge and hydrophobicity and are thus more likely to possess antimicrobial

effects.

To explore the impact of data size and sequence redundancy on finetuning results for MDHs,

we clustered the 16,706 known MDHs and selected the four largest clusters (termed *cluster765*,

cluster2029, *cluster5987*, and *cluster7477*) as finetuning sets, comprising 765, 2029, 5987, and

7477 sequences, respectively. As controls, we generated two sets of sequences: a) random

sequences that followed the amino acid and length distribution of the known MDHs; and b)

sequences generated by the non-finetuned model. Discriminator predictions revealed that

sequences generated by the finetuned models were significantly more likely to be MDHs than

random and non-finetuned model-generated sequences (prediction median 0.91 vs. 0.003 and 0.91

vs. 0.033, respectively; Wilcoxon signed rank test p-value<2.2e-16 for both comparison; Figure 3B).

Notably, we found that even a relatively small number of sequences (~700, in the case of

cluster765) were sufficient to fine-tune ProtGPT2 for generating high-quality MDH sequences.

Importantly, the discriminator's predicted scores do not correlate with ProtGPT2's perplexity during

generation (Pearson correlation= -0.01). Considering the aforementioned limitations of perplexity,

we further demonstrated the superiority of our discriminator in candidate prioritization.

Note that users can choose to provide a leading sequence to prompt ProtGPT2 during

sequence generation, which we refer to as "starter sequence". To investigate whether such a starter

sequence would guide the generation towards our desired functions, we incorporated starter

sequences of variable lengths. We supplied the first 0 (i.e., none), 10, 50, or 100 residues of a

representative sequence (the representative sequence in the corresponding cluster; see Materials

and Methods) as a starter sequence during the generation process. As a result, providing a starter

sequence did not necessarily improve the quality of the generated sequences, as candidates

generated without starter sequences generally had higher discriminator predicted scores (Figure

3B). Notably, in *cluster5987 and cluster7477, employing a starter sequence adversely impacted*

prediction accuracy. This suggests that, for a diverse training set, the inclusion of a starter sequence

might impose unnecessary constraints on sequence generation.

We observed that most of the generated sequences were non-redundant identified by cd-hit

[37], except for those generated by the *cluster2029*-finetuned model (ratio of non-redundant

sequences =0.31 vs. 0.67-0.95 in other generated groups), likely due to the low non-redundancy

within the cluster itself (ratio of non-redundant sequences =0.08 vs. 0.28-0.33 in other clusters;

Figure 4A). The effect of supplying a starter sequence on the redundancy of generated sequences

was not conclusive (Figure S1).

Prioritized generated AMP candidates are endowed with antibacterial activity

With the generated AMP candidates and their corresponding discriminator predictions available, we

randomly selected 24 AMP candidates with predicted scores greater than 0.95; meanwhile, 10

random peptides were generated as control (Table S1). The amino acid and peptide length

distributions of the random peptides are the same as the natural AMPs'. These peptides were

tested against six different bacterial strains, including four Gram-positive strains (*S. aureus*, *K.*

rhizophila, *B. pumilus*, and *B. subtilis*) and two Gram-negative strains (*E. coli* GDMCC 1.335 and

DH5α). Out of the 24 generated AMP candidates, six completely inhibited the growth of at least one

bacterial strain (Figure S2). Notably, five of these candidates displayed broad-spectrum activity

against all six bacterial strains. In comparison, only one of the randomly selected peptides exhibited

activity against some bacterial strains, highlighting the presence of many unknown AMPs in nature,

as reported in previous studies [60,61]. To accurately assess the potency of these candidates, five

broad-spectrum AMPs were purified to 90% purity and their minimum inhibition concentrations

(MICs) were determined by a growth-based assay. Four of these candidates displayed remarkably

low MICs (with the lowest at 1.875 µM, Table 2), highlighting their potential for therapeutic and

industrial applications.

Most finetuned-generated MDH candidates harbor MDH domains

A domain is a structural unit that carries a certain protein function. The function of MDHs is

characterized by a "lactate/malate dehydrogenase" or a "Malate/L-lactate dehydrogenase" domain

(here we denote as "MDH domain") catalogued in Pfam database [62]. Thus, bearing such signature

domain serves as a good indicator of generation quality in addition to our discriminator. We found

that not a single random or non-finetuned-generated sequence has the MDH domain (Figure S3),

suggesting that this domain is extremely unlikely to occur by chance. In contrast, the vast majority

(94.54%) of finetuned-generated sequences have MDH domains, increasing the confidence in their

potential to possess the desired MDH function. Besides, the discriminator's predictions on

sequences with MDH domains are significantly higher than those without MDH domains (prediction

median 0.95 vs. 0.02, Wilcoxon signed rank test p-value<2.2e-16; Figure 4B), assuring that the

discriminator can well capture the sequence-function relationship.

Homology inference suggests MDH function in most finetuned-generated MDH candidates

The MDH candidates generated through fine-tuning exhibit high sequence identity

(median=83.65%) with their best hit known MDH (Figure 4C). Meanwhile, we believe that some high

identity candidates may not actually be MDH (Figure 4D, bottom right corner) according to our

discriminator. In contrast, some candidates with relatively low best hit identities (50-60%) exhibit

high predicted scores, enabling researchers to select MDH candidates with a relatively high degree

of novelty. Next, to further validate the utility of the discriminator in light of homology, we selected a

set of generated candidates highly likely to be MDH, i.e., prediction>0.95, defined as *prioritized*

candidates. We applied HFSP (homology-derived functional similarity of proteins) [47] to the *prioritized*

candidates. HFSP assesses whether a pair of proteins share the same function based on ungapped

alignment length and alignment identity. Although resolution of HFSP may not be able to reach the

fourth level of EC number [47], it is still a useful baseline for homology reference. Notably, HFSP

predicted that all prioritized generated candidates have the same function as their corresponding

best hit sequence (Figure 4F), i.e., a known MDH. These results reinforced our confidence in the

quality and functionality of the MDH sequences generated through fine-tuning, as supported by

homology analysis.

Prioritized MDH candidates are close to known MDHs in sequence space

To visualize spatial relationships between sequence-derived features of the known MDHs and the

discriminator-prioritized MDH candidates, we first embedded the protein sequences into L×1024-

dimensional vectors (where L is the length of a protein) using ProtTrans ProtT5-XL-UniRef50, we

than used t-SNE algorithm [48] to transform the vectors into a two-dimensional space. Here, we

randomly selected 100 known MDHs and 100 *prioritized candidates* to be visualized. To avoid bias

caused by redundant sequences, we further limited the *prioritized candidates* to be non-redundant

with each other determined by cd-hit [37] during the random selection. Functionally similar enzymes

(EC1.1.1.X and EC1.1.X.X) were also added into the comparison as reference. The resulting

visualization (Figure S4) showed that known MDHs and the *prioritized candidates* tend to cluster

together, while functionally similar enzymes barely locate in the space between the known MDHs

and the prioritized MDH candidates. This observation suggests that, in terms of sequence context,

the *prioritized candidates* are in line with the known MDHs and are distinct from functionally similar

enzymes.

Prioritized MDH candidates are conserved at important functional sites

We randomly selected 499 *prioritized candidates* to perform multiple sequence alignment (MSA)

with a known MDH with structural information (UniProt ID: P11708; PDB ID: 4MDH). From the MSA,

we derived position-specific conservation scores and mapped them to 4MDH's structural

annotations. We found that the conservation scores at substrate binding sites, NAD binding sites,

and sulfate binding sites were significantly higher than those at other sites (11 vs. 7, t-test p-

value<0.00025 for all three comparisons; Figure 4E). These results suggest that our framework has

successfully learned the sequence patterns required for MDH function and that the resulting MDH

candidates are likely to perform this function.

Prioritized MDH candidates are functional in vitro

We randomly selected 10 prioritized (predicted score > 0.9) and novel MDH (< 50% identity to any

natural MDH) candidates generated from our framework for experimental validation. As positive

controls, we randomly selected 10 natural MDHs from the training set (n=16,705) of ProteinGAN [21].

Information of these sequences is summarized in Table S2. We expressed these proteins in *E. coli*

BL21 (DE3) system (Figure S5). We observed that only 3/10 MDH candidates and 4/10 positive

controls were soluble (Figure 5 A). Activity assays showed that all the soluble MDH candidates and

the positive controls are functional in vitro (Figure 5 B-C), showcasing the utility of our framework in

designing functional and novel enzymes.

<div align="center">**Discussion**</div>

AMPs offer hopes in addressing the global antibiotic-resistance crisis [63] due to their advantages

over small molecule antibiotics, e.g., modulation of immune response, broad-spectrum activity,

multiple mechanisms of action, and diverse source organisms from all domains of life [64]. Numerous

attempts have been made to predict and *de novo* design novel AMPs [65-67]. Recently, there are four

deep generative language model-based methods for AMP design with experimental validation [61,68-

70]. The first three methods involved an RNN-based generator and a predictor, both trained on known

AMPs. In addition to the predictor, a variety of physicochemical properties were also employed to

facilitate candidate filtering. The fourth method [70] is more complex—an autoencoder generator was

trained on all known short peptide sequences to better reflect peptide properties and enable high

diversity. Meanwhile, multiple attribute classifiers (such as antimicrobial activity, toxicity, sequence

similarity, and physicochemical properties) were trained on the latent space of the autoencoder, and

the generation process was guided by these attribute classifiers altogether for desired peptide

properties, and the attribute classifiers and a series of external predictors were used for candidate

screening. All of these language model-based methods, as well as GAN-based methods [71], have

successfully identified experimentally valid novel AMPs, some of which are broad-spectrum.

However, performance comparison across these methods is difficult due to variations in data size,

time consumption for training, threshold of "inhibitory effect", definition of "broad-spectrum", bacterial

strains tested, peptide purity, and sequence novelty. From a usage convenience standpoint, our

framework has two major advantages over other language model-based methods. First, it does not

need to train a generator from scratch, as the existing generator (ProtGPT2) assumably performs

better due to the tremendously larger training protein dataset. Second, the candidate prioritization is

straightforward as it relies on only one discriminator, instead of multiple classifiers or additional

calculation of physicochemical properties.

Enzyme engineering has become an essential aspect of metabolic engineering and synthetic

biology [72,73]. When incorporating a heterogenous enzyme into an engineering chassis, it is often

necessary to adjust the enzyme properties to better fit the working condition. Generating artificial

protein sequences offers more options for selecting the ideal enzyme version. For example, a

variety of tools can be applied to screen for more suitable solubility [74,75], catalytic capacity [76,77], and

protein-protein interaction [78,79]. Many attempts have been made for enzyme DNPD [80,81]. One of the

most successful non-LLM frameworks is ProteinGAN [21], a GAN-based generator. As a showcase,

ProteinGAN was trained on 16,706 MDHs and produced 55 candidates for testing, of which 13

candidates experimentally displayed MDH catalytic activity. Notably, GAN is suitable for continuous

data (such as images), but not for discrete data (such as text), because GAN relies on gradient-

based optimization and there is no smooth gradient between distinct tokens [82]. When applied in text

(such as protein) generation tasks, GAN also suffers from training instability [83], ignorance on

sequential dependencies [84], mode collapse [85], and result evaluation [86].

Compared to ProteinGAN, our framework has several advantages. First, our discriminator was

trained on much less protein sequences than ProteinGAN (n=2,029 vs. n=16,706) without

compromising the accuracy (0.99 accuracy on a much larger testing set: n=28,412). Second, it can

distinguish MDHs from functionally similar enzymes at a high resolution, surpassing the limitations

of traditional homology-based methods [47]. The candidate screening process is therefore remarkably

simplified and improved, eliminating the need for additional predictors and replacing sequence

identity-based criteria with a straightforward sequence-function scoring scheme. With that said, it

allows us to select both conservative (high sequence identity) and novel (low sequence identity)

candidates while maintaining high functional fidelity (high discriminator scoring). Last but not least,

our framework is time-efficient. The time consumption for the MDH task (in the case of the

cluster2029 for example) is dissected as follows: ~10 min generator finetuning (n=2,029), ~1 h

embedding the training/validation sets (n=4,500 + 500), 2 min discriminator training/validation

(n=4,500 + 500), ~4 h generation (1,000 sequences), ~20 min embedding the generated sequences

(n=1,000) , and ~1 min prediction. The MDH task can be completed in 6 hours (without parallel

computing), which is a small fraction of the time it took for ProteinGAN (9 days). Designing novel

MDHs was also attempted in Madani et al.'s work on ProGen [12]. In their work, the aforementioned

per-token log-likelihood scoring, as well as ProteinGAN's discriminator were used for the

prioritization on the generated MDH candidates, achieving 0.94 and 0.87 ROC-AUC, respectively,

on 56 samples obtained from the ProteinGAN paper [21]. In comparison, our discriminator achieved

higher ROC-AUC (0.99) on a much larger test set (n=28,412), demonstrating the accuracy of our

discriminator.

A major limitation of our framework is that finetuning ProtGPT2 requires a large GPU memory:

among the NVIDIA GPU hardware we have tried (A100, A10, V100, T4, P4, P100), only NVIDIA

A100 (80G) was able to handle the workload. A minor disadvantage is that, unlike GAN requires

only positive set, a negative set is also needed to train our discriminator. However, obtaining a

negative set from protein sequence databases such as UniProt [34] is straightforward.

In summary, we developed a framework that can be quickly tailored to various peptide or

protein tasks without the need to re-learn the protein grammar. Compared to other de novo

peptide/protein design methods [21,70,87], our framework is time- and data-efficient, and is more

convenient to use without the need to incorporating multiple filters or classifiers for screening

purposes. Therefore, this framework may have the potential to significantly accelerate AI-based

DNPD.

Data and code availability

Codes for the framework and result analysis, as well as the data to replicate this work, were

deposited in GitHub repository (https://github.com/zishuozeng/GPT_protein_design).

Acknowledgements

We would like to thank Yu Han (SIAT) for the constructive discussion and all researchers who made

the data and tools relevant to this study available.

Author contributions

Z.Z. and X.L. conceived the ideas; Z.Z. performed the modeling, data analysis, and result

visualization; R.X. performed the AMP and MDH experimental validation and wrote the methods for

it; Z.Z. wrote all other parts of the manuscript; J.G. performed preliminary finetuning experiments;

X.L. revised the manuscript.

Funding

The Project Supported by National Key R&D Program of China (2019YFA0904100), National

Natural Science Foundation of China (32001079), Shenzhen Science and Technology Program

Competing interests

Figure 1. **Discriminator (A) and generator (B) architecture.** In panel A, positive and negative sequences are embedded using ProtTrans (each residue is converted to a 1,024-value long vector). The embedded inputs are fed to a neural network with three convolution layers and three max-pooling layers, followed by a fully connected neural network. Meanwhile, in panel B, the positive sequences are used to finetune ProtGPT2, which is then used to generate positive candidate sequences. In the end, the discriminator is used to screen the most likely positive sequence candidates.

Figure 2. Accuracies (A) and resolutions (B) of the discriminators. In panel A, numbers denoted inside the bars are size of testing set (both balanced). Panel B shows MDH/non-MDH discriminator's predictions on MDHs and functionally close enzymes: "EC1.1.1.X" are enzymes with the first three EC digits being 1.1.1. (excluding EC1.1.1.37); likewise, "EC1.1.X.X" are enzymes with the first two EC digits being 1.1. (excluding EC1.1.1.X). Numbers above the boxes are data size, and all data are not included in training set. AUCs for EC1.1.X.X vs. MDH and EC1.1.1.X VS. MDH are both 0.99.

Figure 3. Effects of generator finetuning on AMP (A) and MDH (B) likelihood of the generated sequences. Panel A shows the discriminator's predictions on four groups of peptide sequences. Group "random" means randomly constructed peptides; group "AA-mimicking" means peptides constructed following the amino acid and length distribution of the actual AMPs; group "ProtGPT2-random" means peptides generated by ProtGPT2 without any finetuning; group "ProtGPT2-finetuned" means peptides generated by ProtGPT2 that was finetuned with actual AMPs. In panel B, group "random" means random sequences following amino acid distributions MDHs; group "noft" in panel B means candidates generated by non-finetuned ProtGPT2. Other groups in panel B (*cluster765*, *cluster2029*, *cluster5987* and cluster7377) indicates sequences generated by ProtGPT2 finetuned by the respective sequence cluster (the numbers indicate corresponding cluster size).

Figure 4. Computational analysis and evidence for the functionality of the prioritized MDH candidates. Panel **A** shows the ratios of non-redundancy within each cluster (*cluster765*, *cluster2029*, *cluster5987* and cluster7377) and among the generated sequences finetuned by the corresponding cluster. Panel **B** shows discriminator predictions on generated MDH candidates with and without MDH domains. Panel **C** shows the histogram of best hit identity of the generated MDH candidates. Panel **D** shows discriminator's prediction vs. best hit identity (presented as data point density, grey grids contain <10 data points) for the finetuned-generated MDH candidates. Panel **E** shows the conservation along the MDH candidates with respect to functionally important sites. Position-specific conservation scores were derived from multiple sequence alignment (MSA) among 500 sequences (a known MDH sequence [UniProt ID: P11708] and 499 randomly sampled finetuned-generated MDH candidates with discriminator prediction>0.95). The determined protein structure (PDB ID: 4MDH) of P11708 was added to the MSA to map the protein positions to functionally important sites. The structure image depicts the structure of 4MDH with ligands sulfate

(yellow spheres) and NAD (purple licorie) highlighted. Resides highlighted in pink, green, and
orange indicate substrate binding, NAD binding, and sulfate binding sites, respectively. The boxplot
summarizes the conservation scores at different sites. Panel **F** shows the best hit's identities and
ungapped alignment lengths of generated sequences (blue dots) with high predicted scores (>0.95).
Red curve in panel E indicates HFSP curve: sequence pairs above and below the curve are
predicted by HFSP as having the same and different enzyme functions, respectively.

Figure 5. Experimental validation on the generated and prioritized MDH candidates. Ten
prioritized (prediction > 0.9) and novel (<50% sequence identity to any natural MDHs) were
randomly selected. Ten natural MDHs were also randomly selected as positive control. Samples
without recombinant enzymes served as negative control. Results showed that 3/10 generated
candidates and 4/10 positive controls were expressed and soluble (no significant difference;
proportion test p-value=1), as displayed in panel A. Panel B shows the malic acid concentration
transformed from oxaloacetic acid. Panel C shows the consumption of NADH over time. Prefix letter
A and N indicates the artificially generated group and the natural group (positive control) group,
respectively. For example, "A_MDH4" indicates the fourth generated MDH candidate and
"N_MDH1" indicates the first positive control.

Table 2. MIC of the identified broad-spectrum AMPs.

Peptides ID	sequence	length	prediction	mass	MIC (μM)					
					S. aureus GMDCC1.221	*B. pumilus* GMDCC1.225	*B. subtilis* GDMCC1.222	*K. rhizophila* GDMCC1.226	*E. Coli* GDMCC1.355	*E. Coli* DH5
AMP3	GLFKIFKKSVKHACKKLK	18	0.97	2103.7	15	3.75	3.75	15	7.5	3.75
AMP6	KYLRRKGGRKWVKNAFR NLM	20	0.97	2522.1	60	15	60	120	120	120
AMP13	YRGIRGKGWWKAAKAA LKAVSAAAKH	26	0.99	2796.3	1.875	1.875	1.875	3.75	15	7.5
AMP23	KIKEKLRQKLGNIMEKHL HKLAHRILLKK	29	0.98	3545.4	3.75	15	7.5	60	30	15

References

Linsky, T. W. *et al.* De novo design of potent and resilient hACE2 decoys to neutralize SARS-CoV-2. *Science* **370**, 1208-1214 (2020).

Sesterhenn, F. *et al.* De novo protein design enables the precise induction of RSV-neutralizing antibodies. *Science* **368**, eaay5051 (2020).

Pan, X. & Kortemme, T. Recent advances in de novo protein design: Principles, methods, and applications. *Journal of Biological Chemistry* **296** (2021).

Quijano-Rubio, A. *et al.* De novo design of modular and tunable protein biosensors. *Nature* **591**, 482-487 (2021).

Liu, K. *et al.* De novo design of a transcription factor for a progesterone biosensor. *Biosensors and Bioelectronics* **203**, 113897 (2022).

Jackson, C., Anderson, A. & Alexandrov, K. The present and the future of protein biosensor engineering. *Current Opinion in Structural Biology* **75**, 102424 (2022).

Madhavan, A. *et al.* Design of novel enzyme biocatalysts for industrial bioprocess: Harnessing the power of protein engineering, high throughput screening and synthetic biology. *Bioresource Technology* **325**, 124617 (2021).

Ennist, N. M. *et al.* De novo protein design of photochemical reaction centers. *Nature Communications* **13**, 4937 (2022).

Currin, A., Swainston, N., Day, P. J. & Kell, D. B. Synthetic biology for the directed evolution of protein biocatalysts: navigating sequence space intelligently. *Chemical Society Reviews* **44**, 1172-1239 (2015).

Ferruz, N. & Höcker, B. Controllable protein design with language models. *Nature Machine Intelligence* **4**, 521-532 (2022).

Ferruz, N. *et al.* From sequence to function through structure: deep learning for protein design. *Computational and Structural Biotechnology Journal* (2022).

Madani, A. *et al.* Large language models generate functional protein sequences across diverse families. *Nature Biotechnology*, 1-8 (2023).

Min, B. *et al.* Recent advances in natural language processing via large pre-trained language models: A survey. *ACM Computing Surveys* (2021).

Budzianowski, P. & Vulić, I. Hello, it's GPT-2--how can I help you? towards the use of pretrained language models for task-oriented dialogue systems. *arXiv preprint arXiv:1907.05774* (2019).

15 Alexandr, N., Irina, O., Tatyana, K., Inessa, K. & Arina, P. in *Data Science and*
Intelligent Systems: Proceedings of 5th Computational Methods in Systems and
Software 2021, Vol. 2. 748-757 (Springer).

16 Liao, Y., Wang, Y., Liu, Q. & Jiang, X. Gpt-based generation for classical chinese
poetry. *arXiv preprint arXiv:1907.00151* (2019).

17 Strokach, A. & Kim, P. M. Deep generative modeling for protein design. *Current*
opinion in structural biology **72**, 226-236 (2022).

18 Wang, Y., Deng, J., Sun, A. & Meng, X. Perplexity from PLM Is Unreliable for
Evaluating Text Quality. *arXiv preprint arXiv:2210.05892* (2022).

19 Newman, D., Noh, Y., Talley, E., Karimi, S. & Baldwin, T. in *Proceedings of the 10th*
annual joint conference on Digital libraries. 215-224.

20 Chang, J., Gerrish, S., Wang, C., Boyd-Graber, J. & Blei, D. Reading tea leaves:
How humans interpret topic models. *Advances in neural information processing*
systems **22** (2009).

21 Repecka, D. *et al.* Expanding functional protein sequence spaces using generative
adversarial networks. *Nature Machine Intelligence* **3**, 324-333 (2021).

22 Dauparas, J. *et al.* Robust deep learning–based protein sequence design using
ProteinMPNN. *Science* **378**, 49-56 (2022).

23 Yu, T. *et al.* Enzyme function prediction using contrastive learning. *Science* **379**,
1358-1363 (2023).

24 Nivón, L. G., Moretti, R. & Baker, D. A Pareto-optimal refinement method for protein
design scaffolds. *PloS one* **8**, e59004 (2013).

25 Meier, J. *et al.* Language models enable zero-shot prediction of the effects of
mutations on protein function. *Advances in Neural Information Processing Systems*
34, 29287-29303 (2021).

26 Yang, K. K., Fusi, N. & Lu, A. X. Convolutions are competitive with transformers for
protein sequence pretraining. *bioRxiv*, 2022.2005. 2019.492714 (2022).

27 Yang, K. K., Zanichelli, N. & Yeh, H. Masked inverse folding with sequence transfer
for protein representation learning. *bioRxiv*, 2022.2005. 2025.493516 (2022).

28 Hsu, C. *et al.* in *International Conference on Machine Learning.* 8946-8970 (PMLR).

29 Johnson, S. R. *et al.* Computational Scoring and Experimental Evaluation of
Enzymes Generated by Neural Networks. *bioRxiv*, 2023.2003. 2004.531015 (2023).

30 Villegas-Morcillo, A. *et al.* Unsupervised protein embeddings outperform hand-
crafted sequence and structure features at predicting molecular function.
Bioinformatics **37**, 162-170 (2021).

31 Heinzinger, M. *et al.* Modeling aspects of the language of life through transfer-
learning protein sequences. *BMC bioinformatics* **20**, 1-17 (2019).

32 Jha, K., Saha, S. & Singh, H. Prediction of protein–protein interaction using graph
neural networks. *Scientific Reports* **12**, 8360 (2022).

33 Singh, S. *et al.* SATPdb: a database of structurally annotated therapeutic peptides.
Nucleic acids research **44**, D1119-D1126 (2016).

34 Consortium, T. U. UniProt: the universal protein knowledgebase in 2021. *Nucleic
acids research* **49**, D480-D489 (2021).

35 Sidorczuk, K. *et al.* Benchmarks in antimicrobial peptide prediction are biased due to
the selection of negative data. *Briefings in Bioinformatics* **23**, bbac343 (2022).

36 McDonald, A. G. & Tipton, K. F. Enzyme nomenclature and classification: The state
of the art. *The FEBS Journal* (2021).

37 Li, W. & Godzik, A. Cd-hit: a fast program for clustering and comparing large sets of
protein or nucleotide sequences. *Bioinformatics* **22**, 1658-1659 (2006).

38 Wolf, T. *et al.* Huggingface's transformers: State-of-the-art natural language
processing. *arXiv preprint arXiv:1910.03771* (2019).

39 Elnaggar, A. *et al.* ProtTrans: towards cracking the language of Life's code through
self-supervised deep learning and high performance computing. *arXiv preprint
arXiv:2007.06225* (2020).

40 Chollet, F. Keras: Deep learning library for theano and tensorflow. *URL:
https://keras. io/k* **7**, T1 (2015).

41 Agarap, A. F. Deep learning using rectified linear units (relu). *arXiv preprint
arXiv:1803.08375* (2018).

42 Rasamoelina, A. D., Adjailia, F. & Sinčák, P. in *2020 IEEE 18th World Symposium
on Applied Machine Intelligence and Informatics (SAMI).* 281-286 (IEEE).

43 Kingma, D. P. & Ba, J. Adam: A method for stochastic optimization. *arXiv preprint
arXiv:1412.6980* (2014).

44 Bateman, A. *et al.* The Pfam protein families database. *Nucleic acids research* **32**,
D138-D141 (2004).

45 Eddy, S. R. Accelerated profile HMM searches. *PLoS computational biology* **7**,
e1002195 (2011).

46 Camacho, C. *et al.* BLAST+: architecture and applications. *BMC bioinformatics* **10**,
1-9 (2009).

47 Mahlich, Y., Steinegger, M., Rost, B. & Bromberg, Y. HFSP: high speed homology-
driven function annotation of proteins. *Bioinformatics* **34**, i304-i312 (2018).

48   Hinton, G. E. & Roweis, S. Stochastic neighbor embedding. *Advances in neural*
information processing systems **15** (2002).

49   Pedregosa, F. *et al.* Scikit-learn: Machine learning in Python. *the Journal of machine*
Learning research **12**, 2825-2830 (2011).

50   Berman, H. M. *et al.* The protein data bank. *Nucleic acids research* **28**, 235-242
(2000).

51   Katoh, K., Rozewicki, J. & Yamada, K. D. MAFFT online service: multiple sequence
alignment, interactive sequence choice and visualization. *Briefings in bioinformatics*
20, 1160-1166 (2019).

52   Bodenhofer, U., Bonatesta, E., Horejš-Kainrath, C. & Hochreiter, S. msa: an R
package for multiple sequence alignment. *Bioinformatics* **31**, 3997-3999 (2015).

53   DeLano, W. L. Pymol: An open-source molecular graphics tool. *CCP4 Newsl. Protein*
Crystallogr **40**, 82-92 (2002).

54   Robin, X. *et al.* pROC: an open-source package for R and S+ to analyze and
compare ROC curves. *BMC bioinformatics* **12**, 1-8 (2011).

55   Xu, J. *et al.* Comprehensive assessment of machine learning-based methods for
predicting antimicrobial peptides. *Briefings in Bioinformatics* **22**, bbab083 (2021).

56   Devlin, J., Chang, M.-W., Lee, K. & Toutanova, K. Bert: Pre-training of deep
bidirectional transformers for language understanding. *arXiv preprint*
arXiv:1810.04805 (2018).

57   Palermo, E. F. & Kuroda, K. Structural determinants of antimicrobial activity in
polymers which mimic host defense peptides. *Applied microbiology and*
biotechnology **87**, 1605-1615 (2010).

58   Shagaghi, N., Palombo, E. A., Clayton, A. H. & Bhave, M. Antimicrobial peptides:
biochemical determinants of activity and biophysical techniques of elucidating their
functionality. *World Journal of Microbiology and Biotechnology* **34**, 1-13 (2018).

59   Kumar, P., Kizhakkedathu, J. N. & Straus, S. K. Antimicrobial peptides: diversity,
mechanism of action and strategies to improve the activity and biocompatibility in
vivo. *Biomolecules* **8**, 4 (2018).

60   Ma, Y. *et al.* Identification of antimicrobial peptides from the human gut microbiome
using deep learning. *Nature Biotechnology* **40**, 921-931 (2022).

61   Nagarajan, D. *et al.* Computational antimicrobial peptide design and evaluation
against multidrug-resistant clinical isolates of bacteria. *Journal of Biological*
Chemistry **293**, 3492-3509 (2018).

62   Finn, R. D. *et al.* The Pfam protein families database: towards a more sustainable
future. *Nucleic acids research* **44**, D279-D285 (2015).

63 Roope, L. S. *et al.* The challenge of antimicrobial resistance: what economics can
contribute. *Science* **364**, eaau4679 (2019).

64 Bahar, A. A. & Ren, D. Antimicrobial peptides. *Pharmaceuticals* **6**, 1543-1575
(2013).

65 Chen, X. *et al.* Sequence-based peptide identification, generation, and property
prediction with deep learning: A review. *Molecular Systems Design & Engineering* **6**,
406-428 (2021).

66 Yan, J. *et al.* Recent Progress in the Discovery and Design of Antimicrobial Peptides
Using Traditional Machine Learning and Deep Learning. *Antibiotics* **11**, 1451 (2022).

67 Ramazi, S., Mohammadi, N., Allahverdi, A., Khalili, E. & Abdolmaleki, P. A review on
antimicrobial peptides databases and the computational tools. *Database* **2022**
(2022).

68 Capecchi, A. *et al.* Machine learning designs non-hemolytic antimicrobial peptides.
Chemical science **12**, 9221-9232 (2021).

69 Dean, S. N., Alvarez, J. A. E., Zabetakis, D., Walper, S. A. & Malanoski, A. P.
PepVAE: variational autoencoder framework for antimicrobial peptide generation and
activity prediction. *Frontiers in Microbiology* **12**, 725727 (2021).

70 Das, P. *et al.* Accelerated antimicrobial discovery via deep generative models and
molecular dynamics simulations. *Nature Biomedical Engineering* **5**, 613-623 (2021).

71 Tucs, A. *et al.* Generating ampicillin-level antimicrobial peptides with activity-aware
generative adversarial networks. *ACS omega* **5**, 22847-22851 (2020).

72 Jang, W. D., Kim, G. B., Kim, Y. & Lee, S. Y. Applications of artificial intelligence to
enzyme and pathway design for metabolic engineering. *Current Opinion in*
Biotechnology **73**, 101-107 (2022).

73 Pleiss, J. Protein design in metabolic engineering and synthetic biology. *Current*
opinion in biotechnology **22**, 611-617 (2011).

74 Khurana, S. *et al.* DeepSol: a deep learning framework for sequence-based protein
solubility prediction. *Bioinformatics* **34**, 2605-2613 (2018).

75 Han, X., Wang, X. & Zhou, K. Develop machine learning-based regression predictive
models for engineering protein solubility. *Bioinformatics* **35**, 4640-4646 (2019).

76 Li, F. *et al.* Deep learning-based k cat prediction enables improved enzyme-
constrained model reconstruction. *Nature Catalysis* **5**, 662-672 (2022).

77 Yu, H. & Luo, X. Pretrained language models and weight redistribution achieve
precise kcat prediction. *bioRxiv*, 2022.2011. 2023.517595 (2022).

78 Hu, X., Feng, C., Ling, T. & Chen, M. Deep learning frameworks for protein-protein
interaction prediction. *Computational and Structural Biotechnology Journal* (2022).

79 Casadio, R., Martelli, P. L. & Savojardo, C. Machine learning solutions for predicting
protein–protein interactions. *Wiley Interdisciplinary Reviews: Computational*
Molecular Science **12**, e1618 (2022).

80 Jiang, L. *et al.* De novo computational design of retro-aldol enzymes. *science* **319**,
1387-1391 (2008).

81 Siegel, J. B. *et al.* Computational design of an enzyme catalyst for a stereoselective
bimolecular Diels-Alder reaction. *Science* **329**, 309-313 (2010).

82 Yu, L., Zhang, W., Wang, J. & Yu, Y. in *Proceedings of the AAAI conference on*
artificial intelligence.

83 Arjovsky, M. & Bottou, L. Towards principled methods for training generative
adversarial networks. *arXiv preprint arXiv:1701.04862* (2017).

84 Caccia, M. *et al.* Language gans falling short. *arXiv preprint arXiv:1811.02549*
(2018).

85 Thanh-Tung, H. & Tran, T. in *2020 international joint conference on neural networks*
(ijcnn). 1-10 (IEEE).

86 Shmelkov, K., Schmid, C. & Alahari, K. in *Proceedings of the European conference*
on computer vision (ECCV). 213-229.

87 Szymczak, P. *et al.* Discovering highly potent antimicrobial peptides with deep
generative model HydrAMP. *nature communications* **14**, 1453 (2023).

831