Bioconversion of Glucose-Rich Lignocellulosic Wood Hydrolysates to 3-Hydroxypropionic

Acid and Succinic Acid using Engineered *Saccharomyces cerevisiae*

Scott Bottoms [1*], Christina Mürk[2], Rodrigo Ledesma-Amaro [3,4], Mart Loog [1]

1. Institute of Technology, University of Tartu, Nooruse 1, Tartu, 50411 Estonia

2. Institute of Chemistry, University of Tartu, Ravila 14A, Tartu, 50411 Estonia

3. Imperial College Centre for Synthetic Biology, Imperial College London, London, SW7 2AZ, UK

4. Department of Bioengineering, Imperial College London, London, SW7 2AZ, UK

* Corresponding author. E-mail address: scott.bottoms@ut.ee (S. Bottoms)

Abstract

Background: 3-hydroxypropionic acid (3-HP) and succinic acid (SA) were announced as two of

the top twelve value-added platform chemicals from biomass out of a group of over 300 potential

compounds that could be made from biomass in a government report in 2004 (Werpy and

Petersen, 2004) and in an updated report in 2010 (Bozell and Petersen, 2010). The screening

criteria used in the report classified 3-HP and SA as direct petroleum replacement building block

chemicals. 3-HP is a precursor to several high-value compounds, such as acrylic acid, 1,3-

propanediol, acrylamide, and methyl acrylates, that ultimately end up in products such as fibers,

contact lenses, diapers, fabric coatings, and other super absorbent polymers (SAPs). SA is a high-

value platform chemical used in polyester production and a precursor for nylon and other

bioplastics. Additionally, these reports identified pathways to building block compounds from

sugars. Yeast fermentations were identified in these reports as a preferred potential pathway to

3-HP and SA production from sugars because of yeasts' natural low pH tolerance.

Results: The laboratory strain *Saccharomyces cerevisiae* BY4741 was engineered to produce

either 3-HP or SA. These yeasts can convert fermentable sugars from glucose-rich lignocellulosic

hardwood feedstocks into organic acid products such as 3-HP and SA under low pH conditions

using exponential fed-batch cultivation strategies. Glucose-rich wood sugars provided a better

growth environment for the engineered yeast strains, increasing production titers by 6.1 and 6.5

times for SA and 3-HP, respectively.

Conclusions: This study shows the potential of locally produced glucose-rich wood sugars to

increase the production of platform chemicals necessary in the production of biobased polymers

by engineered yeast cell factories.

Keywords: 3-hydroxypropionic acid, succinic acid, *Saccharomyces cerevisiae*, yeast cell

factories, lignocellulosic feedstock, wood sugars, β-alanine pathway, fed-batch cultivation,

platform chemicals

Introduction:

3-hydroxypropionic acid (3-HP) and succinic acid (SA) were announced as two of the top twelve

value-added platform chemicals from biomass out of a group of over 300 potential compounds

that could be made from biomass in a government report in 2004 (Werpy and Petersen, 2004)

and in an updated report in 2010 (Bozell and Petersen, 2010). The screening criteria used in the

report classified 3-HP and SA as direct petroleum replacement building block chemicals. 3-HP is

a precursor to several high-value compounds, such as acrylic acid, 1,3-propanediol, acrylamide,

and methyl acrylates, that ultimately end up in products such as fibers, contact lenses, diapers,

fabric coatings, and other super absorbent polymers (SAPs). SA is a high-value platform chemical

used in polyesters and a precursor for nylon and other bioplastics. Additionally, these reports

identified pathways to building block compounds from sugars. Yeast fermentations were

identified in these reports as a preferred potential pathway to valuable organic acids from sugars

because of yeasts' natural low pH tolerance. Conveniently, 3-HP has a pKa of 4.87 and SA a $pKa_{1/2}$

of 4.2 and 5.6; thus, utilizing a fermentation process at low pH improves the overall production

economics compared to neutral or high pH production microbes.

Saccharomyces cerevisiae BY4741-3HP was engineered to produce 3-HP through the β-alanine

biosynthetic pathway (Sun et al., 2023) as it was identified as the most economically attractive

according to a biosynthetic metabolic model (Borodina et al., 2015) as β-alanine (3-

aminopropionic acid) is the only occurring β-type amino acid and is an abundant microbial

metabolite as it is a precursor of pantothenic acid which is an intermediate metabolite in

coenzyme A and acyl carrier protein (Wang et al., 2021).

Methods:

<u>Strains and Chemicals</u>

S. cerevisiae BY4741 (*MATa his3Δ1 leu2Δ0 met15Δ0 ura3Δ0*) was utilized in all experiments,

as described by Shaw et al. (2022). The yeast strains were made prototrophic using single-copy

plasmids for auxotrophic coverage, as outlined by Mülleder et al. (2016). The 3-HP standard

was obtained from Tokyo Chemical Industry Company (TCI), the SA standard from Acros

Organics (Belgium), D-Glucose anhydrate from Research Products International (DPI, Prospect,

IL, USA), and C6-rich wood sugars from Fibenol OÜ (Imavere, Estonia).

<u>Yeast Growth</u>

Yeast cells were cultured from glycerol stocks in standard complex medium (YPD) at 30 °C, with

solid medium containing 10 g/L tryptone, 5 g/L yeast extract, 10 g/L agar, and 20 g/L D-

glucose. Liquid cultures without agar were shaken at 250 RPM under the same conditions.

<u>Growth Medium</u>

Synthetic Mineral Medium (SMM) comprised 7.5 g/L $(NH_4)_2SO_4$, 14.4 g/L KH_2PO_4, 0.9 g/L

$MgSO_4 \cdot 7H_2O$, with trace elements and vitamin solutions. The trace elements solution contains

(per L) 9 g $CaCl_2.2H_2O$, 9 g $ZnSO_4.7H_2O$, 6 g $FeSO_4.7H_2O$, 2 g H_3BO_3, 2 g $MnCl_2.4H_2O$, 0.8 g

$Na_2MoO_4.2H_2O$, 0.6 g $CoCl_2.6H_2O$, 0.2 g $CuSO_4.5H_2O$, 0.2 g KI, and 30 g EDTA. The vitamin

solution contains (per L) 50 mg biotin, 200 mg *p*-aminobenzoic acid, 1 g nicotinic acid, 1 g

calcium pantothenate, 1 g pyridoxine HCl, 1 g thiamine HCl, and 25 g myo-inositol. SMD and

SMW denoted medium combined with either glucose or wood sugars, respectively.

<u>Cultivation Conditions</u>

Growth morphologies were visualized in 96-well microtiter plates and 250 mL flasks with

working volumes of 200 μL and 50 mL of SMD(2%) and SMW(2%), agitated at 1200 RPM or

250 RPM, respectively. Optical density values of microtiter plates were measured at 600 nm

(BioTek Synergy MX), and culture flasks were measured using a spectrophotometer (Thermo

Genesys 50) in standard polystyrene 1 mL cuvettes.

<u>Seed Preparation for Bioreactors</u>

Freshly grown colonies from a YPD plate were used to inoculate SMD(2%), shaken at 250 RPM

at 30 °C overnight. This culture was split into two flasks with fresh SMD(2%) the following

morning and continued shaking for approximately two doubling times. The two flasks were

combined and centrifuged, and the pellet was resuspended in fresh SMD(2%) for bioreactor

seeding.

<u>Fed-batch Cultivations</u>

Cultivations were carried out in 1-L bioreactors (Applikon Biotechnology, Delft, Netherlands)

with an initial batch volume of 300 mL at pH 5.0 and 30 °C. Dissolved oxygen was maintained at

25% or higher using 1-vvm aeration and agitation speeds between 500 to 950 RPM. All

experiments were seeded at OD600 of 0.5. The composition of the cultivation off-gas (CO_2/O_2)

was measured using an inline gas analyzer (BlueSens gas sensor GmbH, Herten, Germany).

Data was recorded and curated with BioXpert v2.95 (Applikon Biotechnology, Delft,

Netherlands). Batch growth medium included 20 g/L D-glucose (SMD(2%)), while fed-batch

medium had higher growth salts concentrations, comprising 148 g/L $(NH_4)_2SO_4$, 19.7 g/L

KH$_2$PO$_4$, and 7.8 g/L MgSO$_4$ · 7H$_2$0, 8 mL trace elements solution, and 5 mL vitamin solution at

pH 5.0 with 0.005% antifoam 204 (Sigma) added in the feed medium only. Either 300 g/L of D-

glucose or 300 g/L of glucose-rich wood sugars were added to the concentrated growth salts.

The wood sugars were centrifuged at 15,000 x g for 10 minutes before being added to the

concentrated growth salts to remove unsuspended solids. Unsuspended solids would clog the

feed tubing in the current configuration. In the case of SA fed-batch production, 1000 ng/μL of

tetracycline A was added to the batch and feed medium as previously (Shaw et al., 2022). Initial

carbon-limited feeding rates were started at 0.15 1/h. Periodic culture samples were taken and

measured for optical densities and LC analysis. LC samples were filtered through a 0.45-micron

syringe filter and stored at -20 °C until analysis.

HPLC Analysis

For monosaccharide detection, 20 μL of the sample was injected into a Shimadzu LC-2050C 3D

Plus system equipped with a Shimadzu RID-20A refractive index detector and an Aminex HPX-

87P LC column (300 X 7.8 mm) at 85 °C using a mobile phase of MilliQ H2O at a flow rate of 0.6

mL/min for 40 minutes. Organic acid detection analyses were performed using the same system

equipped with an Aminex HPX-87H LC column (300 X 7.8 mm) at 60 °C with an H$^+$ precolumn.

The mobile phase for organic acid detection was 1 mM H2SO4 at a flow rate of 0.6 mL/min for

45 minutes. Note that an H$^+$/CO^{3-} deashing precolumn is attached inline during monosaccharide

detection runs but not stored in the column oven as the maximum operating temperature is

60 °C.

Results:

Engineered *S. cerevisiae* BY4741 can convert fermentable sugars from glucose-rich

lignocellulosic hardwood biomass feedstocks into platform chemical products such as 3-HP and

SA under low pH conditions (Table 1). The tested yeast strains were able to produce 14.63 ± 0.29

g/L of SA by feeding wood sugars (*n=3*) and 2.39 ± 0.093 g/L of SA by feeding D-glucose (*n=3*)

which is 6.1 times improvement in SA titers (Fig. 2). Concurrently, engineered yeasts produced

9.71 ± 0.168 g/L of 3-HP by feeding wood sugars (*n=2*) and 1.52 ± 0.006 g/L of 3-HP with D-

glucose (*n=3*), a 6.4 times improvement in 3-HP titers (Fig. 1).

Discussion:

In this study, utilizing exponential fed-batch cultivation strategies with glucose-rich wood sugars

proved crucial for achieving substantially higher yields of 3-HP or SA than pure glucose feed. The

maximum specific growth rates during the batch phase were 0.28 1/h (3-HP strain) and 0.295

1/h (SA strain). Towards the end of the batch phase, a detectable amount of ethanol, reaching up

to 9 g/L, was observed, accompanied by increased respiration. This observation suggested the

occurrence of the Crabtree effect, where carbon was being directed towards ethanol production,

resulting in low biomass.

Upon lowering the maximum specific growth rate (μmax) to 0.15 1/h during carbon-limited

feeding (Fig. 3), concentrations of organic acids (3-HP, SA, and some acetic acid, not shown)

increased over time. This led to the initiation of uncoupling respiration from fermentation,

aligning with findings from studies by Postma et al. (1989) and Verduyn et al. (1984). Maintaining

the growth rate as low as possible under these conditions was crucial, facilitating CO_2 production

rates to match O_2 uptake, thereby maximizing biomass yield.

Since 3-HP is a non-metabolizable organic acid for *S. cerevisiae* and SA production accumulates

rapidly, the increasing levels of organic acids in the culture broth lowers the growth rate threshold

at which ethanol formation occurs (Hagman et al., 2014). This underscores the importance of

carefully managing growth conditions to optimize the production of target compounds in the

fermentation process.

Numerous challenges arise in recovering 3-hydroxypropionic acid (3-HP) in high concentrations

and purity. When microbial cell factories produce 3-HP, it completely solubilizes in culture

medium at relatively low concentrations. Complicating matters, 3-HP is a carboxylic acid with a

low molecular weight, enhancing its solubility in aqueous media. Traditional distillation

techniques prove ineffective due to 3-HP's decomposition at high temperatures and its tendency

to polymerize at higher concentrations. The subsequent processing steps necessary for the

recovery of purified 3-HP can represent a considerable portion of the total production costs

(Chemarin et al., 2019). Specifically, this percentage can vary for carboxylic acids but remains

substantial, explaining why 3-HP is commercially available as a 30% aqueous solution at a

premium price from several chemical producers.

Conclusions:

This work shows that the wood-derived glucose-rich hydrolysate feeding composition produces

the highest 3-HP and SA titers compared to glucose feeding of the same concentrations with

engineered *S. cerevisiae* in this study. It is unclear why the wood sugars provide a better

environment for 3-HP and SA production in yeasts, but similar results have been obtained in a

recent study (Ingham *et al.*, 2023), making the combination of high concentration of growth salts,

wood sugars, yeast cell factories, low pH, and a slow feeding rate for 3-HP or SA production worth

a more in-depth study.

Declarations

Ethics approval and consent to participate

Consent for publication

Availability of data and material

Competing interests

Funding

Authors' contributions

Authors' information

Acknowledgments

References:

Borodina, I. *et al.* Establishing a synthetic pathway for high-level production of 3-

hydroxypropionic acid in Saccharomyces cerevisiae via β-alanine. *Metab. Eng.* **27**, 57–64

(2015).

Chemarin, F., M. Moussa, F. Allais, I.C. Trelea, V. Athès, Recovery of 3-hydroxypropionic acid

from organic phases after reactive extraction with amines in an alcohol-type solvent. Separation

and Purification Technology. **219**, 260-267 (2019).

Hagman A, Säll T, Piškur J. Analysis of the yeast short-term Crabtree effect and its origin. FEBS

J. 2014 Nov;281(21):4805-14. doi: 10.1111/febs.13019. Epub 2014 Sep 26. PMID: 25161062;

PMCID: PMC4240471.

Mülleder M, Campbell K, Matsarskaia O et al. Saccharomyces cerevisiae single-copy plasmids

for auxotrophy compensation, multiple marker selection, and for designing metabolically

cooperating communities [version 1; peer review: 2 approved]. F1000Research 2016, 5:2351.

Postma E, Verduyn C, Scheffers WA, Van Dijken JP. Enzymic analysis of the crabtree effect in

glucose-limited chemostat cultures of Saccharomyces cerevisiae. Appl Environ Microbiol. 1989

Feb;55(2):468-77. doi: 10.1128/aem.55.2.468-477.1989. PMID: 2566299; PMCID:

PMC184133.

Shaw, W.M., Studená, L., Roy, K. *et al.* Inducible expression of large gRNA arrays for

multiplexed CRISPRai applications. *Nat Commun* **13**, 4984 (2022).

Sun, Li, Quanwei Zhang, Xiao Kong, Yanfeng Liu, Jianghua Li, Guocheng Du, Xueqin Lv,

Rodrigo Ledesma-Amaro, Jian Chen, and Long Liu. "Highly efficient neutralizer-free l-malic

acid production using engineered Saccharomyces cerevisiae." Bioresource Technology 370

(2023): 128580.

Verduyn, C., Zomerdijk, T.P.L., van Dijken, J.P. et al. Continuous measurement of ethanol

production by aerobic yeast suspensions with an enzyme electrode. Appl Microbiol Biotechnol

19, 181−185 (1984).

Wang, L., Mao, Y., Wang, Z., Ma, H. & Chen, T. Advances in biotechnological production of β-

alanine. *World J. Microbiol. Biotechnol.* **37**, (2021).

Werpy, T. & Petersen, G. Top Value Added Chemicals from Biomass Volume I. *Us Nrel* Medium:

ED; Size: 76 pp. pages (2004) doi:10.2172/15008859.

232   **Figures and Table:**

233   Table 1. Organic acid titers for *S. cerevisiae* BY4741 using different carbon sources in fed-batch

	D-glucose Feed		**Wood Sugar Feed**	
Strain	**3-HP (g/L)**	**SA (g/L)**	**3-HP (g/L)**	**SA (g/L)**
BY4741 parental	0.00 ± 0.00	0.09 ± 0.03	0.14 ± 0.04	0.07 ± 0.07
BY4741-3HP (SHP413)	1.52 ± 0.01	0.00 ± 0.00	9.71 ± 0.17	0.24 ± 0.12
BR4741-SA (YLS108-2)	0.09 ± 0.08	2.39 ± 0.09	0.00 ± 0.00	14.68 ± 0.29

Figure 1. 3-hydroxypropionic acid-producing yeast strain. Fed-batch over 36 hours with 300 g/L

of either Glucose or Glucose-rich wood sugars. Error bars represent standard deviation. Each

cultivation was carried out in either duplicates or triplicates.

Figure 2. Succinic acid-producing yeast strain. Fed-batch over 36 hours with 300 g/L of either

Glucose or Glucose-rich wood sugars. Error bars represent standard deviation. Each cultivation

was carried out in either duplicates or triplicates.

Figure 3. During the carbon-limited fed-batch phase, the target max specific growth rate was

0.15 1/h. A) For the 3-HP production strain, μ of 0.154 and 0.14 1/h were achieved for wood

sugars and glucose growth, respectively. B) Similar results were attained with the succinic acid

production strain.