Identifying images in the biology literature that are problematic for people with a color-vision deficiency

Harlan P. Stevens[1], Carly V. Winegar[1], Arwen F. Oakley[1], Stephen R. Piccolo[1,*]

1 - Department of Biology, Brigham Young University, Provo, UT, USA

* - Please address correspondence to S.R.P. at stephen_piccolo@byu.edu.

Abstract

To help maximize the impact of scientific journal articles, authors must ensure that article figures are accessible to people with color-vision deficiencies. Up to 8% of males and 0.5% of females experience a color-vision deficiency. For deuteranopia, the most common color-vision deficiency, we evaluated images published in biology-oriented research articles between 2012 and 2022. Out of 66,253 images, 56,816 (85.6%) included at least one color contrast that could be problematic for people with moderate-to-severe deuteranopia ("deuteranopes"). However, after informal evaluations, we concluded that spatial distances and within-image labels frequently mitigated potential problems. We systematically reviewed 4,964 images, comparing each against a simulated version that approximates how it appears to deuteranopes. We identified 636 (12.8%) images that would be difficult for deuteranopes to interpret. Although still prevalent, the frequency of this problem has decreased over time. Articles from cell-oriented biology subdisciplines were most likely to be problematic. We used machine-learning algorithms to automate the identification of problematic images. For a hold-out test set of 879 additional images, a convolutional neural network classified images with an area under the receiver operating characteristic curve of 0.89. To enable others to apply this model, we created a Web application where users can upload images, view

deuteranopia-simulated versions, and obtain predictions about whether the images are problematic. Such efforts are critical to ensuring the biology literature is interpretable to diverse audiences.

Keywords: accessibility, color vision deficiency, deuteranopia, protanopia, scientific publishing

Introduction

Most humans have trichromatic vision: they perceive blue, green, and red colors using three types of retinal photoreceptor cells that are sensitive to short, medium, or long wavelengths of light, respectively. Color-vision deficiency (CVD) affects between 2% and 8% of males (depending on ancestry) and approximately 0.5% of females[1]. Congenital CVD is commonly caused by mutations in the genes (or nearby promoter regions) that code for red or green cone photopigments; these genes are proximal to each other on the X chromosome[2].

CVD is divided into categories, the most common being *deutan CVD*, affecting approximately 6% of males of European descent, and *protan CVD*, affecting 2% of males of European descent[1]. Both categories are commonly known as red-green colorblindness. Within each category, CVD is subclassified according to whether individuals are *dichromats*—able to see two primary colors—or *anomalous trichromats*—able to see three primary colors but differently from *normal trichromats*. Anomalous trichromats differ in the degree of severity with which they can distinguish color patterns. Individuals with deuteranopia ("deuteranopes") or protanopia do not have corresponding green or red cones, respectively[3]. Individuals with deuteranomaly do not have properly functioning green cones, and those with protanomaly do not have properly functioning red cones. People with any of these conditions often see green and red as brown or beige colors. Thus, when images contain shades of green and red—or when either is paired with brown—parts of the image may be indistinguishable. Furthermore, it can be problematic when some pinks or oranges are paired with greens. These issues can lead to incorrect interpretations of figures in scientific journal articles for individuals with CVD.

Efforts have been made to ensure that scientific figures are accessible to people with CVD. For example, researchers have developed algorithms that attempt to recolor images so that people with CVD can more easily interpret them[4–6]. However, these tools are not in wide use, and more work is needed to verify their efficacy in practice. In the meantime, as researchers prepare scientific figures, they can take measures to improve accessibility for people with CVD. For example, they can avoid rainbow color maps that show colors in a gradient; they can use color schemes or color intensities that are CVD friendly[7]; additionally, they can provide labels that complement information implied by color differences. However, for the millions of images that have already been published in scientific articles, little is known about the frequency with which these images are CVD friendly. The presence or absence of particular color pairings—and distances between them—can be quantified computationally to estimate this frequency. However, a subjective evaluation of individual images is necessary to identify whether color pairings and distances are likely to affect scientific interpretation.

In this paper, we focus on deuteranopia and its subtypes. To estimate the extent to which the biological literature contains images that may be problematic to deuteranopes, we manually reviewed a "training set" of 4,964 images and a "test set" of 1,000 images. These images were published in biology-oriented articles in the *eLife* journal between 2012 and 2022. After identifying images that we deemed most likely to be problematic or not, we used machine-learning algorithms to identify patterns that could discriminate between these two categories of images and thus might be useful for automating the identification of problematic images. If successful, such an algorithm could be used to alert authors, presenters, and publishers that scientific images could be modified to improve visual accessibility and thus make biology more inclusive.

Methods

Image acquisition and summarization

We evaluated images in articles from *eLife*, an open-access journal that publishes research in "all areas of the life sciences and medicine"[8]. Article content from this journal is released under a Creative Commons Attribution license. On June 1, 2022, we downloaded all available images from an Amazon Web Services storage bucket provided by journal staff. We also cloned a GitHub repository that *eLife* provides (https://github.com/elifesciences/elife-article-xml); this repository contains text and metadata from all articles published in the journal since its inception. For each article, we parsed the article identifier, digital object identifier, article type, article subject, and publication date; we stored this information in a tab-delimited file. We excluded any article that was not published with the "Research article" type.

For each available image, we identified whether the image was either grayscale or contained colors. For each color image, we calculated a series of metrics to summarize the colors, contrasts, and distances between potentially problematic colors. These metrics have similarities to those used to assess recoloring algorithms, including global luminance error[9], local contrast error[10], and global chromatic diversity[11,12]. Before calculating the metrics, we sought to make the images more comparable to each other and to reduce the computational demands of analyzing the images. We scaled each image to a height of 300 pixels and generated a quantized version with a maximum of 256 colors. For each image, we then created a second version that simulated how a deuteranope would see the image. To facilitate these simulations, we used the *colorspace* package[13] and specified a "severity" value of 0.8. Severity values range between 0 and 1 (with 1 being the most severe). We chose this threshold under the assumption that a mild severity level might not be stringent enough to identify a lack of contrast in the images. However, because many people with deuteranomaly do not have complete deuteranopia, this threshold reflects more moderate cases.

Our approach and rationale for these metrics are described below. In these descriptions, we refer to the quantized, resized images as "original" images and their simulated counterparts as "simulated" images.

- *Mean, pixel-wise color distance between the original and simulated image*. Our rationale was that the most problematic images would show relatively large overall differences between the original and simulated versions. When calculating these differences, we used version 2000 of Hunt's distance[14], which quantifies red/green/blue (RGB) color differences in a three-dimensional space. This metric is symmetric, so the results are unaffected by the order in which the colors were specified; we used the absolute value of these distances.

- *Color-distance ratio between the original and simulated images for the color pair with the largest distance in the original image*. First, we excluded black, white, and gray colors. Second, we calculated the color distance (Hunt's method) between each unique pair of colors in the original image. Third, we calculated the color distance between the colors at the same locations in the simulated image. Fourth, we calculated the ratio between the original distance and the simulated distance. Our rationale was that problematic color pairs would have relatively high contrast (large distances) in the original images and relatively low contrast (small distances) in the simulated images. This approach is similar to that described by Gregor Aisch[15].

- *Number of color pairs that exhibited a high color-distance ratio between the original and simulated images*. This metric is similar to the previous one. However, instead of using the maximum ratio, we counted the number of color pairs with a ratio higher than five; this threshold was used by Gregor Aisch[15]. Our rationale was that even if one color pair did not have an extremely high ratio, the presence of many high-ratio pairs would indicate a potential problem.

- *Proportion of pixels in the original image that used a color from one of the high-ratio color pairs*. Again, using a threshold of five, we identified unique colors among the color-distance pairs and counted the number of pixels in the original image that used any of these colors. Our rationale was that a relatively large number of pixels with potentially problematic colors may

make an image as difficult for a deuteranope to interpret as an image with a few extremely low-

contrast pixels.

• *Mean Euclidean distance between pixels for high-ratio color pairs*. First, we identified color pairs

with a ratio higher than five. For each color pair, we identified pixels in the original image that

used the two colors and calculated the Euclidean distance between those pixels in the image's

two-dimensional layout. Then, we calculated the mean of these distances. Our rationale was that

potentially problematic color pairs close together in an image would be more likely to cause

problems than color pairs that are distant within the image.

After calculating these metrics for each available image, we calculated a ranked-based score. First, we

assigned a rank to each image based on each of the metrics separately. For the "Mean Euclidean distance

between pixels for high-ratio color pairs," relatively large values were given relatively high ranks

(indicating that they were less problematic). For the other metrics, relatively small values were given

relatively high ranks. Finally, we averaged the ranks to calculate a combined score for each image.

When analyzing images, calculating metrics, and creating figures and tables, we used the R statistical

software (version 4.2.1)[16] and the following packages:

• colorspace (version 2.0-3)[13]

• doParallel (1.0.17)[17]

• knitr (1.44)[18]

• magick (2.7.3)[19] - interfaces with the ImageMagick software (6.9.10.23)[20]

• pROC (1.17.0.1)[21]

• spacesXYZ (1.2-1)[22]

• tidyverse (2.0.0)[23]

• xml2 (1.3.3)[24]

Qualitative image evaluation

We manually reviewed images to assess qualitatively whether visual characteristics were likely to be problematic for deuteranopes. Our intent was to establish a reference standard for evaluating the quantitative metrics we had calculated. Initially, we randomly sampled 1,000 images from among those we had downloaded. Two authors of this paper (HPS and AFO) reviewed each of the original (non-quantized, non-resized) images and the corresponding image that was simulated to reflect deuteranopia (severity = 0.8). Neither of these authors has been diagnosed with deuteranopia. This ensured the reviewers could compare the images with and without deuteranopia simulation. To avoid confirmation bias, neither author played a role in defining the quantitative metrics described above. Both authors reviewed the images and recorded observations based on four criteria:

1. Did an image contain shades of red, green, and/or orange that might be problematic for deuteranopes?

2. When an image contained potentially problematic color shades, did the color contrasts negate the potential problem? (The reviewers examined the images in their original and simulated forms when evaluating the contrasts.)

3. When an image contained potentially problematic color shades, did within-image labels mitigate the potential problem?

4. When an image contained potentially problematic color shades, were the colors sufficiently spatially distant from each other so that the colors were unlikely to be problematic?

After discussing a given image, the reviewers recorded a joint conclusion about whether the image was "Definitely problematic," "Probably problematic," "Probably okay," or "Definitely okay." For images that had no visually detectable color, the reviewers recorded "Gray-scale."

After this preliminary phase, we randomly selected an additional 4,000 images and completed the same process. During the review process, we identified 36 cases where multiple versions of the same image had

been sampled. We reviewed these versions manually and found that subsequent versions either had

imperceptible differences or slight differences in the ways that sub-figures were laid out. None of these

changes affected the colors used. Thus, we excluded the duplicate images and retained the earliest version

of each image. The resulting 4,964 images constituted a "training set," which we used to evaluate our

calculated metrics and to train classification models (see below). Later, we randomly selected an

additional 1,000 images, which we used as a "hold-out test set." Again, we excluded duplicate images and

those for which different versions were present in the training set and hold-out test set. The same authors

(HPS and AFO) performed the manual review process for these images.

Classification analyses

We used classification algorithms to discriminate between images that we had manually labeled as either

"Definitely problematic" or "Definitely okay." Although it reduced our sample size, we excluded the

"Probably problematic" and "Probably okay" images with the expectation that a smaller but more

definitive set of examples would produce a more accurate model. Removing these images reduced our

training set to 4,501 images.

First, we evaluated our ability to classify images as "Definitely problematic" or "Definitely okay" based

on the five metrics we devised. For this task, we used the following classification algorithms, which are

designed for one-dimensional data: Random Forests[25], k-nearest neighbors[26], and logistic regression[27]. We

used implementations of these algorithms in scikit-learn (version 1.1.3)[28] with default hyperparameters,

other than two exceptions; we used the "liblinear" solver for logistic regression, and we set the

"class_weight" hyperparameter to "balanced" for Random Forests and Logistic Regression. For

evaluation, we used three iterations of five-fold cross validation. For the test samples in each fold, we

calculated the area under the receiver operating characteristic curve (AUROC)[29,30] using the *yardstick*

package (version 1.2.0)[31]. We calculated the median AUROC across the folds and then averaged them

across the three iterations.

Second, we evaluated our ability to classify the images as "Definitely problematic" or "Definitely okay"

based on the images themselves. We used a convolutional neural network (CNN) because they are

capable of handling two-dimensional inputs and to account for spatial patterns and colors within images.

To generate the CNN model, we used the Tensorflow (2.10.0) and Keras (2.10.0) frameworks[32,33]. To

support transfer learning (described below), we scaled both dimensions of each image to 224. To perform

hyperparameter optimization, we again used three iterations of five-fold cross validation (with the same

assignments as the earlier classification analysis). Each hyperparameter combination extended a baseline

model that had eight, two-dimensional, convolutional layers; each layer used batch normalization and the

relu activation function. Subsequent layers increased in size, starting with 32 nodes and increasing to 64,

128, 256, 512, and 728. We trained for 30 epochs with an Adam optimization set, a learning rate of 1e-3,

and the binary cross-entropy loss function. The output layer used a sigmoid activation function.

In addition to the baseline model, we tested 22 hyperparameter combinations based on the following

techniques:

• *Class weighting* - To address class imbalance (most images were "Definitely okay" in the training

set), we increased the weight of the minority class ("Definitely problematic") proportionally to its

frequency in the training set.

• *Early stopping* - During model training, classification performance on the (internal) validation set

is monitored to identify an epoch when the performance is no longer improving or has begun to

degrade; the goal of this technique is to find a balance between underfitting and overfitting.

• *Random flipping and rotation* - In an attempt to prevent overfitting, we enabled random,

horizontal flipping of training images and data augmentation via differing amounts of random

image rotation[34]. We evaluated rotation thresholds of 0.2 and 0.3.

• *Dropout* - Again to prevent overfitting, we asked the model to temporarily remove a subset of

neurons from the network. We evaluated dropout rates of 0.2 and 0.5.

• *Transfer learning* - This technique uses a corpus of ancillary images such that model building is

informed by patterns observed previously. We evaluated two corpuses: MobileNetV2[35,36] and

ResNet50[37]. MobileNetV2 is a 53-layer convolutional neural network trained on more than a

million images from the ImageNet database to classify images with objects into 1,000 categories.

ResNet50 is a 50-layer convolutional neural network, similarly trained. MobileNetV2 is designed

for use on mobile devices, so it is optimized to be lightweight. As such, MobileNetV2 uses 3.4

million parameters, while ResNet50 uses over 25 million trainable parameters. When we applied

transfer learning from either ResNet50 or MobileNetV2, we did not use the base model design

referred to above. Instead, we added a global pooling function into a dense layer. Because our

training dataset was relatively small, adding fewer layers may reduce the risk of overfitting.

• *Fine tuning* - When transfer learning was used, we sometimes performed fine tuning. With this

approach, we allowed an initial model to be trained for 30 epochs (unless early stopping was

specified). We then fine-tuned the model by unfreezing the ResNet50 (or MobileNetV2) layers

and retraining the initial model with a lower learning rate of 1e-5.

To guide (internal) evaluation of the models, we specified the following metrics: true positives, false

positives, true negatives, false negatives, accuracy, precision, recall, AUROC, and precision-recall curve.

After identifying the best hyperparameter combination via cross validation, we created a hold-out test set,

randomly selecting an additional 1,000 images from eLife articles published during the same timeframe

as the training set. We did *not* use these images when developing the model or selecting hyperparameters.

Web application

We created a Web application using the *Node.js* framework[38]. The application enables researchers to

evaluate uploaded images. First, users upload an image in PNG or JPEG format. The application displays

the image alongside a deuteranopia-simulated version of the image. For simulation, we implemented the

Machado et al.[39] matrix for deuteranopia in Javascript with a "severity" value of 0.8, the same parameter

used in training. If the user requests it, the application uses our CNN model to predict whether the image

is likely to be problematic for a deuteranope; the prediction includes a probabilistic score so that users can

assess the model's confidence level. To facilitate execution of the CNN within the Web application, we

used Tensorflow.js (version 4.0.0)[40].

Code and data availability

The images we used for evaluation and the trained TensorFlow model are stored in an Open Science

Framework repository (https://osf.io/8yrkb). The code for processing and analyzing the images is

available at https://github.com/srp33/bio_image_colorblindness. That repository also includes the

calculated metrics, cross-validation assignments, results of image curation, and outputs of the

classification algorithms. The Web application code is available at

https://github.com/srp33/colorblind_image_tester.

Results

We downloaded images from research articles published in the eLife journal between 2012 and 2022. Not

counting duplicate versions of the same image, we obtained 66,253 images. Of these images, 1,744

(2.6%) were grayscale (no color). Of these images, 56,816 (85.6%) included at least one color pair for

which the amount of contrast might be problematic to people with moderate-to-severe deuteranopia

("deuteranopes"). To characterize potentially problematic aspects of each color-based image, we

calculated five metrics based on color contrasts and distances; we also compared the color profiles against

what deuteranopes might see (see Methods). The distributions of these metrics are depicted in Figures S1-

S5.

A brief evaluation suggested that many images with the highest scores (or lowest, as would be the case

for the "Mean Euclidean distance between pixels for high-ration color pairs" metric) for these metrics

were likely to be problematic for deuteranopes. However, we noted that certain color pairs were more

problematic than others, and the use of effective labels and/or spacing between colors often mitigated

potential problems. Thus, to better estimate the extent to which images in the biological literature are

problematic for deuteranopes, we manually reviewed a sample of 4,964 images and judged whether it

would be likely for deuteranopes to recognize the scientific message behind each image. Additional Data

File S1 contains a record of these evaluations, along with comments that indicate either problematic

aspects of the images or factors that mitigated potential problems. We concluded that 636 (12.8%) of the

images were "Definitely problematic," whereas 3,865 of the images (77.9%) were "Definitely okay." The

remaining images were grayscale (n = 179), or we were unable to reach a confident conclusion (n = 284).

For the images that were "Definitely okay," we visually detected shades of green and red or orange in

2,348 (60.8%) images; however, in nearly all (99.3%) of these cases, we deemed that the contrasts

between the shades were sufficient that a deuteranope could interpret the images. Furthermore, distance

between the colors and/or labels within the images mitigated potential problems in 54.2% and 48.4% of

cases, respectively.

For the images that were either "Definitely okay" or "Definitely problematic," we calculated the

percentage of "Definitely problematic" images in a given year or associated with a given biology

subdiscipline. The percentage of problematic images declined steadily between 2012 and 2021, with a

modest increase in 2022 (Figure 1). The subdisciplines with the highest percentages of problematic

images were *Stem Cells and Regenerative Medicine*, *Developmental Biology*, and *Cell Biology* (Figure 2).

Despite the benefits of manual review, this process is infeasible on a large scale. Therefore, we evaluate

techniques for automating classification. Firstly, we used the five metrics we calculated to classify the

training images. We also combined these metrics into a single, ranked-based score for each image.

Figures 3, S6-S10 illustrate differences for these metrics between the two classes. To quantify their

predictive performance, we calculated the area under the receiver operating characteristic curve

(AUROC)[29]. Values closer to 1.0 indicate relatively high predictive performance. A value of 0.5 indicates

that predictions are no better than random guessing. The best-performing metric on the training set was

the number of color pairs that exhibited a high color-distance ratio between the original and simulated

images (AUROC: 0.75); the mean, pixel-wise color distance between the original and simulated image

performed worse than random guessing (Table S1). Secondly, as an alternative to the combined rank

score, we used classification algorithms to make predictions with the five metrics as inputs. In cross

validation on the training set, the best-performing algorithm was Logistic Regression, attaining an

AUROC of 0.82 (Table S2). Thirdly, we created a convolutional neural network (CNN) to make

predictions according to visual and spatial patterns in the images. CNNs are highly configurable and often

sensitive to model parameters. Accordingly, we performed multiple iterations of cross validation on the

training set and identified a hyperparameter combination that attained an AUROC of 0.93, slightly

outperforming other combinations (Table S3).

We manually reviewed a hold-out test set with an additional 1,000 images (Additional Data File S2).

After removing images from the hold-out test set that were not "Definitely okay" or "Definitely

problematic," we were left with 879 images to test the classification algorithms. For the Logistic

Regression algorithm and CNN, we trained models using the full training set and classified each hold-out

image as "Definitely okay" or "Definitely problematic." Logistic Regression classified the images with an

AUROC of 0.82; the CNN classified the images with an AUROC of 0.89 (Figures 4-5). Upon reviewing

the 92 misclassified images and comparing them against our manual annotations, we determined that in

13 cases, the reviewers had missed subtle patterns and that it would be justified to change the labels

(Additional Data File S3). For 31 of the misclassified images, we visually identified patterns that might

have confused the CNN; however, upon reevaluation, we maintain that the original labels were valid. For

the remaining 48 misclassified images, we were unable to identify patterns that seemed likely to have

confused the model.

Discussion

Significant prior work has been done to address and improve accessibility for individuals with CVD[41]. This work can be generally categorized into three types of studies: simulation methods, recolorization methods, and estimating the frequency of accessible images. Simulation methods have been developed to better understand how images appear to individuals with CVD. Brettel et al. first simulated CVDs using the long, medium, and short (LMS) colorspace[42]. For dichromacy, the colors in the LMS space are projected onto an axis that corresponds to the non-functional cone cell. Viénot et al. expanded on this work by applying a 3x3 transformation matrix to simulate images in the same LMS space[43]. Machado et al. created matrices to simulate CVDs based on the shift theory of cone cell sensitivity[39,44]. These algorithms allow individuals without CVD to qualitatively test how their images would appear to people with CVD. The simulation algorithms and matrices are freely available and accessible via websites and software packages[45–48].

CVD simulations have facilitated the creation of colorblind-friendly palettes[49], and they have led to algorithms that recolor images to become more accessible to people with CVD. Recolorization methods focus on enhancing color contrasts and preserving image naturalness[41]. Many algorithms have been developed to compensate for dichromacy[50–61]. These algorithms apply a variety of techniques including hue rotation, customized difference addition, node mapping, and generative adversarial networks[41,57]. Many of these methods have been tested for efficacy, both qualitatively and quantitatively[41]. Recoloring algorithms have been applied to PC displays, websites, and smart glasses[62]. Despite the prevalence of these algorithms, current techniques have not been systematically compared and may sacrifice image naturalness to increase contrast. Additionally, recoloring may not improve the accessibility of some scientific figures because papers often reference colors in figure descriptions. Recoloring the image could interfere with matching colors between the text and images.

An increase in available resources for making figures accessible to individuals with CVD has prompted some researchers to investigate whether these resources have been impactful in decreasing the frequency of published scientific figures with problematic color pairings. Frane examined the prevalence of images in psychology journals that could be confusing to people with CVD[63]. A group of panelists with CVD qualitatively evaluated 246 images and found that 13.8% of color figures caused difficulty for at least one panelist; this percentage is similar to our findings. They also found that in instructions to authors, journals rarely mentioned the importance of designing figures for CVD accessibility. Angerbauer et al. recruited crowdworkers to analyze a sample of 1,710 published images and to identify issues with the use of color[64]. On average, 60% of the sampled images were given a rating of "accessible" across CVD types. From 2000 to 2019, they observed a slight increase in CVD accessibility for published figures.

Our study focuses on the biology literature and uses simulations to estimate the prevalence of problematic figures. Our work suggests that approximately 13% of figures in the *eLife* journal are challenging for scientists with moderate-to-severe deuteranopia to interpret. Although this journal may not represent biology-related journals more broadly, *eLife* does publish articles across diverse biology subdisciplines, and its content-licensing scheme made it possible to perform this study in a transparent manner. We hope that providing examples of figures that may cause issues for individuals with CVD will raise awareness of this problem and encourage authors and publishers to be more proactive about publishing CVD-friendly figures.

By summarizing color patterns in more than 66,000 images and manually reviewing 6,000 images, we have created an open data resource that other researchers can use to develop their own methods. Furthermore, we have created an automated process for assigning predictions to other scientific figures. We have made this model accessible to other scientists by deploying it in a Web application (https://bioapps.byu.edu/colorblind_image_tester); we anticipate that scientists and journal editors will find this tool useful when preparing or evaluating figures for publication. However, it is infeasible to

perfectly automate the process of determining whether an image is CVD friendly, so we encourage

biologists to use this tool as a starting point only.

Our analysis has limitations. Firstly, it relied on deuteranopia simulations rather than the experiences of

deuteranopes. However, by using simulations, the reviewers were capable of seeing two versions of each

image: the original and a simulated version. Secondly, because we used a single, relatively high severity

threshold, our simulations do not represent the full spectrum of experiences that scientists with

deuteranopia have. Furthermore, recent evidence suggests that commonly used mathematical

representations of color differences are unlikely to reflect human perceptions perfectly[65]. As methods

evolve for more accurately simulating color perception, we will be more capable of estimating the extent

to which scientific figures are problematic for deuteranopes. Thirdly, our evaluations focused on

deuteranopia, the most common form of CVD. It will be important to address other forms of CVD, such

as protanopia, in future work. Finally, our CNN model was trained using biology-oriented images and

thus might be less effective for other image types. Future studies could expand on this work, using images

from other disciplines and/or non-science sources.

Diverse resources are available to researchers looking to make their figures suitable for people with CVD.

For example, the *seaborn* Python package includes a "colorblind" palette[66]. The *colorBlindness* package

for R provides simulation tools and CVD-friendly palettes[67]. When designing figures, researchers may

find it useful to first design them so that key elements are distinguishable in grayscale. Then, color can be

added—if necessary—to enhance the image. Color should not be used for the sole purpose of making the

image aesthetically pleasing. Using minimal color avoids problems that arise from color pairing issues.

Rainbow color maps, in particular, should be avoided. If a researcher finds it necessary to include

problematic color pairings in figures, they can vary the saturation and intensity of the colors so they are

more distinguishable to people with CVD. Many of the problematic figures that we identified in this study

originated from fluorescence microscopy experiments, where red and green dyes are commonly used.

Accordingly, cell biology might be a biology subdiscipline that is disproportionately inaccessible to

deuteranopes. Choosing alternative color dyes could reduce this problem and improve the interpretability

of microscopy images for people in all fields.

376 Declarations

Ethics approval and consent to participate

Not applicable.

Consent for publication

Not applicable.

Competing interests

The authors declare no competing interests.

Financial disclosure

The authors received no specific funding for this work.

Author contributions

The following contributions are described using the CRediT Taxonomy[68].

HPS: Conceptualization, Data Curation, Formal Analysis, Investigation, Methodology, Software,

Validation, Writing – Original Draft, Writing – Review and Editing

CVW: Conceptualization, Investigation, Methodology, Software, Writing – Original Draft, Writing –

Review and Editing

AFO: Data Curation, Formal Analysis, Writing – Review & Editing

SRP: Conceptualization, Formal Analysis, Investigation, Methodology, Project Administration,

Resources, Software, Supervision, Visualization, Writing – Original Draft, Writing – Review & Editing

Figures

Figure 1: Longitudinal trends. For the 4,964 images in the training set, we identified images that were "Definitely okay" or "Definitely problematic". This graph shows the percentage of these images that were "Definitely problematic" in a given year, over time. We used linear regression to calculate the P-value.

Figure 2: Trends by biology subdiscipline. For the 4,964 images in the training set, we identified

images that were "Definitely okay" or "Definitely problematic". This graph shows the percentage of these

images that were "Definitely problematic" for a given subdiscipline, as indicated in the article metadata.

In many cases, a single image was associated with multiple subdisciplines; these images are counted

separately for each subdiscipline. We used a chi-squared goodness-of-fit test to calculate the P-value.

Figure 3: Rank-based metric score for images categorized as "Definitely okay" or "Definitely problematic".

Figure 4: Convolutional Neural Network predictions for the hold-out test set. Each point represents

the prediction for an image from the hold-out test set. Relatively high confidence scores indicate that the

model had more confidence that a given image was "Definitely problematic" for a person with

deuteranopia.

Figure 5: Receiver operating characteristic curve for Convolutional Neural Network predictions on

the hold-out test set. This curve illustrates tradeoffs between sensitivity and specificity for the

Convolutional Neural Network on the hold-out test set. The area under the curve is 0.89.

References

1.   Delpero, W. T., O'Neill, H., Casson, E. & Hovis, J. Aviation-relevent epidemiology of color

vision deficiency. *Aviat. Space Environ. Med.* **76**, 127–133 (2005).

2.   Nathans, J., Thomas, D. & Hogness, D. S. Molecular genetics of human color vision: The genes

encoding blue, green, and red pigments. *Science* **232**, 193–202 (1986).

3.   Simunovic, M. P. Colour vision deficiency. *Eye* **24**, 747–755 (2010).

4.   Flatla, D. R. Accessibility for individuals with color vision deficiency. in *Proc. 24th Annu. ACM*

Symp. Adjun. User Interface Softw. Technol. 31–34 (Association for Computing Machinery, 2011).

doi:10.1145/2046396.2046412.

5.   Lin, H.-Y., Chen, L.-Q. & Wang, M.-L. Improving Discrimination in Color Vision Deficiency by

Image Re-Coloring. *Sensors* **19**, 2250 (2019).

6.   Tsekouras, G. E. *et al.* A Novel Approach to Image Recoloring for Color Vision Deficiency.

Sensors **21**, 2740 (2021).

7.   Crameri, F., Shephard, G. E. & Heron, P. J. The misuse of colour in science communication. *Nat*

Commun **11**, 5444 (2020).

8.   About · eLife.

9.   Kuhn, G. R., Oliveira, M. M. & Fernandes, L. A. F. An improved contrast enhancing approach

for color-to-grayscale mappings. *Visual Comput* **24**, 505–514 (2008).

10.   Zhu, Z. *et al.* Naturalness-and information-preserving image recoloring for redgreen dichromats.

Signal Process. Image Commun. **76**, 68–80 (2019).

11.   Chen, W., Chen, W. & Bao, H. An Efficient Direct Volume Rendering Approach for Dichromats.

IEEE Trans. Vis. Comput. Graph. **17**, 2144–2152 (2011).

12.   Ma, Y., Gu, X. & Wang, Y. Color discrimination enhancement for dichromats using self-

organizing color transformation. *Inf. Sci.* **179**, 830–843 (2009).

13.   Stauffer, R., Mayr, G. J., Dabernig, M. & Zeileis, A. Somewhere over the rainbow: How to make

effective use of colors in meteorological visualizations. *Bull. Am. Meteorol. Soc.* **96**, 203–216 (2009).

14.   Hunt, R. W. G. *The reproduction of colour*. (John Wiley & Sons, 2005).

15.   Aisch, G. I wrote some code that automatically checks visualizations for non-colorblind safe

colors. Here's how it works. *vis4.net* (2018).

16.   R Core Team. *R: A language and environment for statistical computing*. (R Foundation for

Statistical Computing, 2022).

17.   Corporation, M. & Weston, S. *doParallel: Foreach parallel adaptor for the 'parallel' package.* (2022).

18.   Xie, Y. Knitr: A comprehensive tool for reproducible research in R. in *Implementing reproducible computational research* (eds. Stodden, V., Leisch, F. & Peng, R. D.) (Chapman and Hall/CRC, 2014).

19.   Ooms, J. *Magick: Advanced graphics and image-processing in R.* (2021).

20.   Still, M. *The Definitive Guide to ImageMagick.* (Apress, 2006).

21.   Robin, X. *et al.* pROC: An open-source package for R and S+ to analyze and compare ROC curves. *BMC bioinformatics* **12**, 77 (2011).

22.   Davis, G. *spacesXYZ: CIE XYZ and some of its derived color spaces.* (2022).

23.   Wickham, H. *et al.* Welcome to the tidyverse. *J. Open Source Softw.* **4**, 1686 (2019).

24.   Wickham, H., Hester, J. & Ooms, J. *Xml2: Parse XML.* (2021).

25.   Breiman, L. Random forests. *Mach. Learn.* **45**, 5–32 (2001).

26.   Fix, E. & Hodges, J. L. Discriminatory analysis. Nonparametric discrimination: Consistency properties. *Int. Stat. Rev. Int. Stat.* **57**, 238–247 (1989).

27.   Nelder, J. A. & Wedderburn, R. W. Generalized linear models. *J. R. Stat. Soc. Ser. A Stat. Soc.* **135**, 370–384 (1972).

28.   Pedregosa, F. *et al.* Scikit-learn: Machine learning in Python. *J. Mach. Learn. Res.* **12**, 2825–2830 (2011).

29.   Tanner Jr, W. P. & Swets, J. A. A decision-making theory of visual detection. *Psychol. Rev.* **61**, 401 (1954).

30.   Swets, J. A. Measuring the accuracy of diagnostic systems. *Science* **240**, 1285–1293 (1988).

31.   Kuhn, M., Vaughan, D. & Hvitfeldt, E. *Yardstick: Tidy characterizations of model performance.* (2023).

32.   Abadi, M. *et al.* {}TensorFlow{}: A system for {large-scale} machine learning. in *12th USENIX Symp. Oper. Syst. Des. Implement. OSDI 16* 265–283 (2016).

33.   Géron, A. *Hands-on machine learning with scikit-learn, keras, and TensorFlow*. (" O'Reilly

Media, Inc.", 2022).

34.   Wong, S. C., Gatt, A., Stamatescu, V. & McDonnell, M. D. Understanding Data Augmentation

for Classification: When to Warp? in *2016 Int. Conf. Digit. Image Comput. Tech. Appl. DICTA* 1–6

(2016). doi:10.1109/DICTA.2016.7797091.

35.   Sandler, M., Howard, A., Zhu, M., Zhmoginov, A. & Chen, L.-C. MobileNetV2: Inverted

Residuals and Linear Bottlenecks. (2019) doi:10.48550/arXiv.1801.04381.

36.   Krizhevsky, A., Sutskever, I. & Hinton, G. E. Imagenet classification with deep convolutional

neural networks. *Adv. Neural Inf. Process. Syst.* **25**, (2012).

37.   He, K., Zhang, X., Ren, S. & Sun, J. Deep residual learning for image recognition. in *Proc. IEEE

Conf. Comput. Vis. Pattern Recognit.* 770–778 (2016).

38.   Node.js. *Node.js*.

39.   Machado, G. M., Oliveira, M. M. & Fernandes, L. A. F. A physiologically-based model for

simulation of color vision deficiency. *IEEE Trans Vis Comput Graph* **15**, 1291–1298 (2009).

40.   TensorFlow.js | Machine Learning for JavaScript Developers. *TensorFlow*.

41.   Zhu, Z. & Mao, X. Image recoloring for color vision deficiency compensation: A survey. *Vis

Comput* **37**, 2999–3018 (2021).

42.   Brettel, H., Viénot, F. & Mollon, J. D. Computerized simulation of color appearance for

dichromats. *J. Opt. Soc. Am. A, JOSAA* **14**, 2647–2655 (1997).

43.   Viénot, F., Brettel, H. & Mollon, J. D. Digital video colourmaps for checking the legibility of

displays by dichromats. *Color Res. Appl.* **24**, 243–252 (1999).

44.   Stockman, A. & Sharpe, L. T. The spectral sensitivities of the middle- and long-wavelength-

sensitive cones derived from measurements in observers of known genotype. *Vision Research* **40**, 1711–

1737 (2000).

45.   Coblis Color Blindness Simulator Colblindor.

46.   Color blind safe colors on color wheel | Adobe Color.

47.   DaltonLens-Python. (2023).

48.   Wilke, C. Colorblindr. (2023).

49.   Olson, J. M. & Brewer, C. A. An Evaluation of Color Selections to Accommodate Map Users with Color-Vision Impairments. *Ann. Assoc. Am. Geogr.* **87**, 103–134 (1997).

50.   Jefferson, L. & Harvey, R. An interface to support color blind computer users. in *Proc. SIGCHI Conf. Hum. Factors Comput. Syst.* 1535–1538 (Association for Computing Machinery, 2007). doi:10.1145/1240624.1240855.

51.   Huang, J.-B., Tseng, Y.-C., Wu, S.-I. & Wang, S.-J. Information Preserving Color Transformation for Protanopia and Deuteranopia. *IEEE Signal Process. Lett.* **14**, 711–714 (2007).

52.   Rumiński, J. *et al.* Color transformation methods for dichromats. in *3rd Int. Conf. Hum. Syst. Interact.* 634–641 (2010). doi:10.1109/HSI.2010.5514503.

53.   Rasche, K., Geist, R. & Westall, J. Re-coloring Images for Gamuts of Lower Dimension. *Comput. Graph. Forum* **24**, 423–432 (2005).

54.   Machado, G. M. & Oliveira, M. M. Real-Time Temporal-Coherent Color Contrast Enhancement for Dichromats. *Comput. Graph. Forum* **29**, 933–942 (2010).

55.   Ching, S.-L. & Sabudin, M. Website image colour transformation for the colour blind. in *2010 2nd Int. Conf. Comput. Technol. Dev.* 255–259 (2010). doi:10.1109/ICCTD.2010.5645874.

56.   Ribeiro, M. & Gomes, A. J. P. Recoloring Algorithms for Colorblind People: A Survey. *ACM Comput. Surv.* **52**, 72:1–72:37 (2019).

57.   Li, H. *et al.* Color vision deficiency datasets & recoloring evaluation using GANs. *Multimed Tools Appl* **79**, 27583–27614 (2020).

58.   Wang, X. *et al.* Fast contrast and naturalness preserving image recolouring for dichromats. *Computers & Graphics* **98**, 19–28 (2021).

59.   Nakauchi, S. & Onouchi, T. Detection and modification of confusing color combinations for red-green dichromats to achieve a color universal design. *Color Res. Appl.* **33**, 203–211 (2008).

60. Zhu, Z. *et al.* Processing images for redgreen dichromats compensation via naturalness and information-preservation considered recoloring. *Vis Comput* **35**, 1053–1066 (2019).

61. Ma, Y., Gu, X. & Wang, Y. Color discrimination enhancement for dichromats using self-organizing color transformation. *Information Sciences* **179**, 830–843 (2009).

62. Tanuwidjaja, E. *et al.* Chroma: A wearable augmented-reality solution for color blindness. in *Proc. 2014 ACM Int. Jt. Conf. Pervasive Ubiquitous Comput.* 799–810 (Association for Computing Machinery, 2014). doi:10.1145/2632048.2632091.

63. Frane, A. A Call for Considering Color Vision Deficiency When Creating Graphics for Psychology Reports. *J. Gen. Psychol.* **142**, 194–211 (2015).

64. Angerbauer, K. *et al.* Accessibility for Color Vision Deficiencies: Challenges and Findings of a Large Scale Study on Paper Figures. in *Proc. 2022 CHI Conf. Hum. Factors Comput. Syst.* 1–23 (Association for Computing Machinery, 2022). doi:10.1145/3491102.3502133.

65. Bujack, R., Teti, E., Miller, J., Caffrey, E. & Turton, T. L. The non-Riemannian nature of perceptual color space. *Proc. Natl. Acad. Sci. U.S.A.* **119**, e2119753119 (2022).

66. Waskom, M. L. Seaborn: Statistical data visualization. *J. Open Source Softw.* **6**, 3021 (2021).

67. Ou, J. *colorBlindness: Safe color set for color blindness.* (2021).

68. Brand, A., Allen, L., Altman, M., Hlava, M. & Scott, J. Beyond authorship: Attribution, contribution, collaboration, and credit. *Learn. Publ.* **28**, 151–155 (2015).