Semantical and Geometrical Protein Encoding Toward Enhanced Bioactivity and Thermostability

Yang Tan[1,2,5†] **, Bingxin Zhou**[1,3,*,†] **, Lirong Zheng**[1] **, Guisheng Fan**[2] **, Liang Hong**[1,3,4,5,*]

*For correspondence:
bingxin.zhou@sjtu.edu.cn (Bingxin Zhou); hongl3liang@sjtu.edu.cn (Liang Hong)

[†]These authors contributed equally to this work

[1]Institute of Natural Sciences, Shanghai Jiao Tong University, Shanghai 200240, China.;
[2]School of Information Science and Engineering, East China University of Science and Technology, Shanghai, 200237, China; [3]Shanghai National Center for Applied Mathematics (SJTU center), Shanghai Jiao Tong University, Shanghai, 200240, China; [4]Zhangjiang Institute for Advanced Study, Shanghai Jiao Tong University, Shanghai, 201203, China; [5]Shanghai Artificial Intelligence Laboratory, Shanghai, 200232, China

---

Abstract   Protein engineering is a pivotal aspect of synthetic biology, involving the modification of amino acids within existing protein sequences to achieve novel or enhanced functionalities and physical properties. Accurate prediction of protein variant effects requires a thorough understanding of protein sequence, structure, and function. Deep learning methods have demonstrated remarkable performance in guiding protein modification for improved functionality. However, existing approaches predominantly rely on protein sequences, which face challenges in efficiently encoding the geometric aspects of amino acids' local environment and often fall short in capturing crucial details related to protein folding stability, internal molecular interactions, and bio-functions. Furthermore, there lacks a fundamental evaluation for developed methods in predicting protein thermostability, although it is a key physical property that is frequently investigated in practice. To address these challenges, this paper introduces a novel pre-training framework that integrates sequential and geometric encoders for protein primary and tertiary structures. This framework guides mutation directions toward desired traits by simulating natural selection on wild-type proteins and evaluates variant effects based on their fitness to perform specific functions. We assess the proposed approach using three benchmarks comprising over 300 deep mutational scanning assays. The prediction results showcase exceptional performance across extensive experiments when compared to other zero-shot learning methods, all while maintaining a minimal cost in terms of trainable parameters. This study not only proposes an effective framework for more accurate and comprehensive predictions to facilitate efficient protein engineering, but also enhances the *in silico* assessment system for future deep learning models to better align with empirical requirements. The PyTorch implementation are available at https://github.com/tyang816/ProtSSN.

Introduction

The diverse roles proteins play in nature necessitate their involvement in varied bio-functions, such as catalysis, binding, scaffolding, and transport (*Frauenfelder and McMahon, 1998*). Advances in science and technology have positioned proteins, particularly those with desired catalytic and binding properties, to pivotal positions in medicine, biology, and scientific research. While wild-type proteins exhibit optimal bio-functionality in their native environments, industrial applications of-

Figure 1. An illustration of ProtSSN that extracts the semantical and geometrical characteristics of a protein from its sequentially-ordered global construction and spatially-gathered local contacts with protein language models and equivariant graph neural networks. The encoded hidden representation can be used for downstream tasks such as variants effect prediction that recognizes the impact of mutating a few sites of a protein on its functionality.

ten demand adaptation to conditions such as high temperature, high pressure, strong acidity, and strong alkalinity. The constrained efficacy of proteins in meeting the stringent requirements of industrial functioning environments hinders their widespread applications (*Woodley, 2013*; *Ismail et al., 2021*; *Zheng et al., 2022*; *Jiang et al., 2023*). Consequently, there arises a need to engineer these natural proteins to enhance their functionalities, aligning them with the demands of both industrial and scientific applications.

Analyzing the relationship between protein sequence and function yields valuable insights for engineering proteins with new or enhanced functions in synthetic biology. The intrinsic goal of protein engineering is to unveil highly functional sequences by navigating the intricate, high-dimensional surface of the fitness landscape (*Yang et al., 2019*), which delineates the relationship between amino acid (AA) sequences and the desired functional state. Predicting the effects of AA substitutions, insertions, and deletions (*Riesselman et al., 2018*; *Gray et al., 2018*; *Notin et al., 2022*) in proteins, *i.e.*, mutation, thus allows researchers to dissect how changes in the AA sequence can impact the protein's catalytic efficiency, stability, and binding affinity (*Shin et al., 2021*). However, the extensive, non-contiguous search space of AA combinations poses challenges for conventional methods, such as rational design (*Aprile et al., 2020*) or directed evolution (*Wang et al., 2021*), in efficiently and effectively identifying protein variants with desired properties. In response, deep learning has emerged as a promising solution that proposes favorable protein variants with high fitness.

Deep learning approaches have been instrumental in advancing scientific insights into proteins, predominantly categorized into sequence-based and structure-based methods. Autoregressive protein language models (*Notin et al., 2022*; *Madani et al., 2023*) interpret AA sequences as raw text to generate with self-attention mechanisms (*Vaswani et al., 2017*). Alternatively, masked language modeling objectives develop attention patterns that correspond to the residue-residue contact map of the protein (*Meier et al., 2021*; *Rao et al., 2021a*; *Rives et al., 2021*; *Vig et al., 2021*; *Brandes et al., 2022*; *Lin et al., 2023*). Other methods start from a multiple sequence alignment, summarizing the evolutionary patterns in target proteins (*Riesselman et al., 2018*; *Frazer et al., 2021*; *Rao et al., 2021b*). These methods result in a strong capacity for discovering the hidden protein space. However, the many-to-one relationship of both sequence-to-structure and structure-to-function projections requires excessive training input or substantial learning resources, which raises concerns regarding the efficiency of these pathways when navigating the complexities of the vast sequence space associated with a target function. Moreover, the overlooked local environment of proteins hinders the model's ability to capture structure-sensitive properties that impact protein's thermostability, interaction with substrates, and catalytic process (*Zhao et al., 2022*; *Koehler Leman et al., 2023*). Alternatively, structure-based modeling methods serve as an effective enhancement to complement sequence-oriented inferences for proteins with their local environment (*Torng and*

77 *Altman, 2019*; *Jones et al., 2021*; *Zhou et al., 2023b*; *Yi et al., 2023*). Given that core mutations of-
78 ten induce functional defects through subtle disruptions to structure or dynamics (*Roscoe et al.,*
79 *2013*), incorporating protein geometry into the learning process can offer valuable insights into sta-
80 bilizing protein functioning. Recent efforts have been made to encode geometric information of
81 proteins for topology-sensitive tasks such as molecule binding (*Jin et al., 2021*; *Myung et al., 2022*;
82 *Kong et al., 2023*) and protein properties prediction (*Zhang et al., 2022*). Nevertheless, structure
83 encoders fall short in capturing non-local connections for AAs beyond their contact region and
84 overlook correlations that do not conform to the 'structure-function determination' heuristic.

85 There is a pressing need to develop a novel framework that overcomes limitations inherent
86 in individual implementations of sequence or structure-based investigations. To this end, we in-
87 troduce ProtSSN to assimilate the semantics and topology of **Prot**eins from their **S**equence and
88 **S**tructure with deep neural **N**etworks. ProtSSN incorporates the intermediate state of protein struc-
89 tures and facilitates the discovery of an efficient and effective trajectory for mapping protein se-
90 quences to functionalities. The developed model extends the generalization and robustness of
91 self-supervised protein language models while maintaining low computational costs, thereby facil-
92 itating self-supervised training and task-specific customization. A funnel-shaped learning pipeline,
93 as depicted in Fig. 1, is designed due to the limited availability of protein crystal structures com-
94 pared to observed protein sequences. Initially, the linguistic embedding establishes the semantic
95 and grammatical rules in AA chains by inspecting millions of protein sequences. The topological
96 embedding then enhances the interactions among locally connected AAs. Since a geometry can
97 be placed or observed by different angles and positions in space, we represent proteins' topol-
98 ogy by graphs and enhance the model's robustness and efficiency with a rotation and translation
99 equivariant graph representation learning scheme.

100 The pre-trained ProtSSN demonstrates its feasibility across a broad range of mutation effect
101 prediction benchmarks covering catalysis, interaction, and thermostability. Mutation effects pre-
102 diction serves as a common *in silico* assessment for evaluating the capability of an established
103 deep learning framework in identifying favorable protein variants. With the continuous evolution of
104 deep mutation scanning techniques and other high-throughput technologies, benchmark datasets
105 have been curated to document fitness changes in mutants across diverse proteins with varying de-
106 grees of combinatorial and random modifications (*Moal and Fernández-Recio, 2012*; *Nikam et al.,*
107 *2021*; *Veleckỳ et al., 2022*). **ProteinGym v1** (*Notin et al., 2023*) comprehends fitness scoring of mu-
108 tants to catalytic activity and binding affinity across over 200 well-studied proteins of varying deep
109 mutational scanning (DMS) assays and taxa. Each protein includes tens of thousands of mutants
110 documented from high-throughput screening techniques. While **ProteinGym v1** initiates the most
111 comprehensive benchmark dataset for mutants toward different properties enhancement, these
112 fitness scores are normalized and simplified into several classes without further specifications. For
113 instance, a good portion of protein assays is scored by their stability, which, in practice, is further
114 categorized into thermostability, photostability, pH-stability, *etc*. Moreover, these stability prop-
115 erties should be discussed under certain environmental conditions, such as pH and temperature.
116 Unfortunately, these detailed attributes are excluded in **ProteinGym v1**. Since a trade-off rela-
117 tionship emerges between activity and thermostability (*Zheng et al., 2022*), protein engineering in
118 practice extends beyond enhancing catalytic activities to maintaining or increasing thermostabil-
119 ity for prolonged functional lifetimes and applications under elevated temperatures and chemical
120 conditions (*Liu et al., 2019*). Consequently, there is a need to enrich mutation effect prediction
121 benchmarks that evaluate the model's efficacy in capturing variant effects concerning thermosta-
122 bility under distinct experimental conditions. In this study, we address the mutation effect predic-
123 tion tasks on thermostability with **DTm** and **DDG**, two new single-site mutation benchmarks that
124 measure thermostability using ΔTm and $\Delta\Delta$G values, respectively. Both benchmarks group exper-
125 imental assays based on the protein-condition combinations. These two datasets supplement the
126 publicly available DMS assay benchmarks and facilitate ready-to-use assessment for future deep
127 learning methods toward protein thermostability enhancement.

Figure 2. An example source record of the mutation assay. The record is derived from DDG for the A chain of protein 1A7V, experimented at pH=6.5 and degree at 25°C.

Table 1. Statistical summary of **DTm** and **DDG**.

pH Range	DTm			DDG		
	# Assays	avg. # mut	avg. AA	# Assays	avg. # mut	avg.AA
Acid (pH < 7)	29	29.1	272.8	21	22.6	125.3
Neutral (pH = 7)	14	37.4	221.2	10	23.1	78.3
Alkaline (pH > 7)	23	50.1	233.3	5	24.6	101.4
sum	66	38.2	221.2	36	23.0	108.8

This work fulfills practical necessities in the development of deep learning methods for protein engineering from three distinct perspectives. Firstly, the developed ProtSSN employs self-supervised learning during training to obviate the necessity for additional supervision in downstream tasks. This zero-shot scenario is desirable due to the scarcity of experimental results, as well as the 'cold-start' situation common in many wet lab experiments. Secondly, the trained model furnishes robust and meaningful approximations to the joint distribution of the entire amino acid chain, thereby augmenting the *epistatic effect* (*Sarkisyan et al., 2016*; *Khersonsky et al., 2018*) in deep mutations. This augmentation stems from the model's consideration of the nonlinear combinatorial effects of amino acid sites. Additionally, we complement the existing dataset of DMS assay with additional benchmark assays related to protein-environment interactions, specifically focusing on thermostability–an integral objective in numerous protein engineering projects.

Materials and Methods

This section starts by introducing the three mutational scanning benchmark datasets used in this study, including an open benchmark dataset **ProteinGym v1** and two new datasets on protein thermostability, *i.e.*, **DTm** and **DDG**. Section establishes the proposed ProtSSN for protein sequences and structures encoding. The overall pipeline of model training and inference is presented in Section . The experimental setup for model evaluation is provided in Section .

Dataset

To evaluate model performance in predicting mutation effects, we compare ProtSSN with SOTA baselines on **ProteinGym-v1**, the largest open benchmark for DMS assays. We also introduce two novel benchmarks, **DTm** and **DDG**, for assessing protein thermostability under consistent control environments. Details of the new datasets are provided in Table 1. Considering the significant influence of experimental conditions on protein temperature, we explicitly note the pH environment in each assay. Refer to the following paragraphs for more details.

Table 2. Details of Baseline Models.

Model	Type seq	Type struct	Description	Source Code
RITA (*Hesslow et al., 2022*)	✓		a generative protein language model with billion-level parameters	github.com/lightonai/RITA
ProGen2 (*Nijkamp et al., 2023*)	✓		a generative protein language model with billion-level parameters	github.com/salesforce/progen
ProtTrans (*Elnaggar et al., 2021*)	✓		Transformer-based models trained on large protein sequence corpus	github.com/agemagician/ProtTrans
Tranception (*Notin et al., 2022*)	✓		an autoregressive model for variant effect prediction with retrieve machine	github.com/OATML-Markslab/Tranception
CARP (*Yang et al., 2022*)	✓		pretrained CNN protein sequence masked language models of various sizes	github.com/microsoft/protein-sequence-models
ESM-1b (*Rives et al., 2021*) ESM-1v (*Meier et al., 2021*) ESM2 (*Lin et al., 2023*)	✓ ✓ ✓		a masked language model-based pre-train method with various pre-training dataset and positional embedding strategies	github.com/facebookresearch/esm
ESM-if1 (*Hsu et al., 2022*)		✓	an inverse folding method with mask language modeling and geometric vector perception (*Jing et al., 2020*).	
MIF-ST (*Yang et al., 2023*)	✓	✓	pretrained masked inverse folding models with sequence pretraining transfer	github.com/microsoft/protein-sequence-models

ProteinGym

The assessment of ProtSSN for deep mutation effects prediction is conducted on **ProteinGym v1** (*Notin et al., 2023*). It is the most extensive protein substitution benchmark comprising 217 assays and more than $2.5M$ mutants. These DMS assays cover a broad spectrum of functional properties (*e.g.*, ligand binding, aggregation, viral replication, and drug resistance) and span various protein families (*e.g.*, kinases, ion channel proteins, transcription factors, and tumor suppressors) across different taxa (*e.g.*, humans, other eukaryotes, prokaryotes, and viruses).

DTm

The assays in the first novel thermostability benchmark are sourced from single-site mutations in **ProThermDB** (*Nikam et al., 2021*). Each assay is named in the format '*UniProt_ID-pH*'. For instance, '*O00095-8.0*' signifies mutations conducted and evaluated under pH 8.0 for protein $O00095$. The attributes include 'mutant', 'score', and 'UniProt_ID', with at least 10 mutants to ensure a meaningful evaluation. To concentrate on single-site mutations compared to wild-type proteins, we exclude records with continuous mutations. To avoid dealing with partial or misaligned protein structures resulting from incomplete wet experimental procedures, we employ UniProt ID to pair protein sequences with folded structures predicted by AlphaFold2 (*Jumper et al., 2021*) from https://alphafold.ebi.ac.uk. In total, **DTm** consists of 66 such protein-environment pairs and $2,520$ mutations.

DDG

The second novel thermostability benchmark is sourced from **DDMut** (*Zhou et al., 2023c*), where mutants are paired with their PDB documents. We thus employ crystal structures for proteins in **DDG** and conduct additional preprocessing steps for environmental consistency. In particular, we group mutants of the same protein under identical experimental conditions and examine the alignment between mutation sites and sequences extracted from crystal structures. We discard mutant records that cannot be aligned with the sequence loaded from the associated PDB document. After removing data points with fewer than 10 mutations, **DDG** comprises 36 data points and 829 mutations. As before, assays are named in the format '*PDB_ID-pH-temperature*' to indicate the chemical condition (pH) and temperature (in Celsius) of the experiment on the protein. An example assay content is provided in Fig. 2.

Proposed Method

Labeled data are usually scarce in biomolecule research, which demands designing a general self-supervised model for predicting variant effects on unknown proteins and protein functions. We propose ProtSSN with a pre-training scheme that recovers AA types from a given protein backbone structure with noisy local environment observations.

Multi-level Protein Representation

Protein Primary Structure (Noisy)

Denote a given observation with AA type $\tilde{v}$. We assume this arbitrary observation is undergoing random mutation toward a stable state. The training objective is to learn a revised state v that is less likely to be eliminated by natural selection due to unfavorable properties such as instability or inability to fold. The perturbed observation is defined by a multinomial distribution.

$$\pi(\tilde{v} \mid v) = p\Theta(\pi_1, \pi_2, \ldots, \pi_{20}) + (1 - p)\delta(\tilde{v} - v), \tag{1}$$

where an AA in a protein chain has a chance of p to mutate to one of 20 AAs (including itself) following a *replacement distribution* $\Theta(\cdot)$ and $(1 - p)$ of remaining unchanged. We consider p as a tunable parameter and define $\Theta(\cdot)$ by the frequency of AA types observed in wild-type proteins.

Protein Tertiary Structure

The geometry of a protein is described by $\mathcal{G} = (\mathcal{V}, \mathcal{E}, \boldsymbol{W}_V, \boldsymbol{W}_E, \boldsymbol{X}_V)$, which is a residue graph based on the k-nearest neighbor (kNN). Each node $v_i \in \mathcal{V}$ represents an AA in the protein connected to up to k closest nodes within 30Å (*Zhou et al., 2023a*). Node attributes $\boldsymbol{W}_V$ are hidden semantic embeddings of AA types extracted by the semantic encoder (see Section), and edge attributes $\boldsymbol{W}_E \in \mathbb{R}^{93}$ feature relationships of connected nodes based on inter-atomic distances, local N-C positions, and sequential position encoding. Additionally, $\boldsymbol{X}_V$ records 3D coordinates of AAs in the Euclidean space, which plays a crucial role in the subsequent geometric embedding stage to preserve roto-translation equivariance.

Semantic Encoding of Global AA Contacts

Although it is generally believed by the community that a protein's sequence determines its biological function via the folded structure, following strictly to this singular pathway risks overlooking other unobserved yet potentially influential inter-atomic communications impacting protein fitness. Our proposed ProtSSN thus includes pairwise relationships for residues through an analysis of proteins' primary structure from $\tilde{V}$ and embeds them into hidden representations $\boldsymbol{W}_V$ for residues. At each update, information and representations of the noisy AA sequence are encoded from the noisy input via an *Evolutionary Scale Modeling* method, ESM-2 (*Lin et al., 2023*), which employs a BERT-style masked language modeling objective. This objective predicts the identity of randomly selected AAs in a protein sequence by observing their context within the remainder of the sequence. Alternative semantic encoding strategies are discussed in Section .

Geometrical Encoding of Local AA Contacts

Proteins are structured in 3D space, which requires the geometric encoder to possess roto-translation equivariance to node positions as well as permutation invariant to node attributes. This design is vital to avoid the implementation of costly data augmentation strategies. We practice *Equivariant Graph Neural Networks* (EGNN) (*Satorras et al., 2021*) to acquire the hidden node representation $\boldsymbol{W}_V^{l+1} = \left\{ \boldsymbol{w}_{v_1}^{l+1}, \ldots, \boldsymbol{w}_{v_n}^{l+1} \right\}$ and node coordinates $\boldsymbol{X}_{\text{pos}}^{l+1} = \left\{ \boldsymbol{x}_{v_1}^{l+1}, \ldots, \boldsymbol{x}_{v_n}^{l+1} \right\}$ at the $l + 1$th layer

$$
\begin{aligned}
\boldsymbol{m}_{ij} &= \phi_e \left(\boldsymbol{w}_{v_i}^l, \boldsymbol{w}_{v_j}^l, \left\| \boldsymbol{x}_{v_i}^l - \boldsymbol{x}_{v_j}^l \right\|^2, \boldsymbol{w}_{e_{ij}} \right), \\
\boldsymbol{x}_{v_i}^{l+1} &= \boldsymbol{x}_{v_i}^l + \frac{1}{n} \sum_{j \neq i} \left(\boldsymbol{x}_{v_i}^l - \boldsymbol{x}_{v_j}^l \right) \phi_x \left(\boldsymbol{m}_{ij} \right), \\
\boldsymbol{w}_{v_i}^{l+1} &= \phi_v \big(\boldsymbol{w}_i^l, \sum_{j \neq i} \boldsymbol{m}_{ij} \big).
\end{aligned}
\tag{2}
$$

In these equations, $\boldsymbol{w}_{e_{ij}}$ represents the input edge attribute on $\mathcal{V}_{ij}$, which is not updated by the network. The propagation rules ϕ_e, ϕ_x and ϕ_v are defined by differentiable functions, *e.g.* multi-layer perceptrons (MLPs). The final hidden representation on nodes $\boldsymbol{W}_V^L$ embeds the microenvironment and local topology of AAs, and it will be carried on by readout layers for label predictions.

Model Pipeline

ProtSSN is designed for protein engineering with a self-supervised learning scheme. The model is capable of conducting zero-shot variant effect prediction on an unknown protein, and it can generate the joint distribution for the type of all AAs along the protein sequence of interest. This process accounts for the epistatic effect and concurrently returns all AA sites in a sequence. Below, we detail the workflow for training the zero-shot model and scoring the effect of a specific mutant.

Training

The fundamental model architecture cascades a frozen sequence encoding module and a trainable tertiary structure encoder. The protein is represented by its sequence and structure characteristics, where the former is treated as plain text and the latter is formalized as a kNN graph with model-encoded node attributes, handcrafted edge attributes, and 3D positions of the corresponding AAs. The node attributes are encoded by a protein language model, which analyses pairwise hidden relationships among AAs from the input protein sequence and produces a vector representation $\boldsymbol{w}_{v_i} \in \boldsymbol{W}_V$ for each AA, *i.e.*,

$$\boldsymbol{W}_V = \mathrm{LM}_{\mathrm{frozen}}(\tilde{\boldsymbol{V}}) \tag{3}$$

with $\tilde{\boldsymbol{V}}$ be the perturbed initial AA-type encoding. The language model $\mathrm{LM}_{\mathrm{frozen}}(\cdot)$, ESM-2 (*Lin et al., 2023*) for instance, has been pre-trained on a massive protein sequence database (*e.g.*, **UniRef50** (*Suzek et al., 2015*)) to understand the semantic and grammatical rules of wild-type proteins with high-dimensional AA-level long-short-range interactions. The independent perturbation on AA types follows 1 operates in every epoch, which requires constant updates on the sequence embedding. To further enhance the interaction of locally connected AAs in the node representation, a stack of L EGNN layers is implemented on the input graph $\mathcal{G}$ to yield

$$\boldsymbol{W}_V^L = \mathrm{EGNN}(\mathcal{G}). \tag{4}$$

During the pre-training phase for protein sequence recovery, the output layer $\phi(\cdot)$ provides the probability of AAs in one of 20 types, *i.e.*,

$$\boldsymbol{Y} = \phi(\boldsymbol{W}_V^L) \in \mathbb{R}^{n \times 20} \tag{5}$$

for n AAs of the input protein. The model's learnable parameters are refined by minimizing the cross-entropy of the recovered AAs with respect to the ground-truth AAs in wild-type proteins.

Inferencing

For a given mutant, its fitness score is derived from the joint distribution of the altered AA types on associated nodes that provides a preliminary assessment based on natural observations. We consider the AA type in the wild-type protein as a reference state and compare it with the predicted probability of AAs at the mutated site. Formally, for a mutant with mutated sites $\mathcal{T}$ ($|\mathcal{T}| \geq 1$), we define its fitness score using the corresponding *log-odds-ratio*, *i.e.*,

$$\sum_{t \in \mathcal{T}} \log p(\boldsymbol{y}_t) - \log p(\boldsymbol{v}_t), \tag{6}$$

where $\boldsymbol{y}_t$ and $\boldsymbol{v}_t$ denote the mutated and wild-type type of the tth AA.

Experimental Protocol

We validate the efficacy of ProtSSN on zero-shot mutation effect prediction tasks. The performance is compared with other SOTA models of varying numbers of trainable parameters. The implementations are programmed with `PyTorch-Geometric` (ver 2.2.0) and `PyTorch` (ver 1.12.1) and executed on an NVIDIA® Tesla A100 GPU with $6,912$ CUDA cores and 80GB HBM2 installed on an HPC cluster.

Table 3. Spearman's ρ correlation of variant effect prediction on **DTm**, **DDG**, and **ProteinGym v1**.

Model	Version	# Params (million)	DTm	DDG	ProteinGym v1					
					Activity	Binding	Expression	Organismal	Stability	Overall Fitness
Sequence Encoder										
RITA	small	30	0.122	0.143	0.294	0.275	0.337	0.327	0.289	0.304
	medium	300	0.131	0.188	0.352	0.274	0.406	0.371	0.348	0.350
	large	680	0.213	0.236	0.359	0.291	0.422	0.374	0.383	0.366
	xlarge	1,200	0.221	0.264	0.402	0.302	0.423	0.387	0.445	0.373
ProGen2	small	151	0.135	0.194	0.333	0.275	0.384	0.337	0.349	0.336
	medium	764	0.226	0.214	0.393	0.296	0.436	0.381	0.396	0.380
	base	764	0.197	0.253	0.396	0.294	**0.444**	0.379	0.383	0.379
	large	2,700	0.181	0.226	0.406	0.294	0.429	0.379	0.396	0.381
	xlarge	6,400	0.232	0.270	0.402	0.302	0.423	0.387	0.445	0.392
PortTrans	bert	420	0.268	0.313	-	-	-	-	-	-
	bert_bfd	420	0.217	0.293	-	-	-	-	-	-
	t5_xl_uniref50	3,000	0.310	0.365	-	-	-	-	-	-
	t5_xl_bfd	3,000	0.239	0.334	-	-	-	-	-	-
Tranception	small	85	0.119	0.169	0.287	0.349	0.319	0.270	0.258	0.288
	medium	300	0.189	0.256	0.349	0.285	0.409	0.362	0.342	0.349
	large	700	0.197	0.284	0.401	0.289	0.415	**0.389**	0.381	0.375
ESM-1v	-	650	0.279	0.266	0.390	0.268	0.431	0.362	0.476	0.385
ESM-1b	-	650	0.271	0.343	0.428	0.289	0.427	0.351	0.500	0.399
ESM-2	t12	35	0.214	0.216	0.314	0.292	0.364	0.218	0.439	0.325
	t30	150	0.288	0.317	0.391	0.328	0.425	0.305	0.510	0.392
	t33	650	0.330	0.392	0.391	0.328	0.425	0.305	0.510	0.419
	t36	3,000	0.327	0.351	0.417	0.322	0.425	0.379	0.509	0.410
	t48	15,000	0.311	0.252	0.405	0.318	0.425	0.388	0.488	0.405
CARP	-	640	0.288	0.333	0.395	0.274	0.419	0.364	0.414	0.373
Structure Encoder										
ESM-if1	-	142	0.395	**0.409**	0.368	**0.392**	0.403	0.324	**0.624**	0.422
Sequence + Structure Encoder										
MIF-ST	-	643	**0.400**	0.406	0.390	0.323	0.432	0.373	0.486	0.401
ProtSSN (ours)	k20_h512	148	0.419	0.442	0.458	0.371	0.436	0.387	0.566	0.444
	ensemble	1,467	0.425	0.452	0.466	0.371	0.451	0.398	0.568	0.451

† The top three are highlighted by First, Second, **Third**.

Training Setup

ProtSSN is pre-trained on a non-redundant subset of **CATH v4.3.0** (*Orengo et al., 1997*) domains, which contains $30,948$ experimental protein structures with less than 40% sequence identity. We remove proteins that exceed $2,000$ AAs in length for efficiency. For each kNN protein graph, node features are extracted and updated by a frozen ESM2-t33 prefix model (*Lin et al., 2023*). Protein topology is inferred by a 6-layer EGNN (*Satorras et al., 2021*) with the hidden dimension tuned from $\{512, 768, 1280\}$. Adam (*Kingma and Ba, 2015*) is used for backpropagation with the learning rate set to 0.0001. To avoid training instability or CUDA out-of-memory, we limit the maximum input to $8,192$ AA tokens per batch, constituting approximately 32 graphs.

Baseline Methods

We undertake an extensive comparison with baseline methods of self-supervised sequence or structure-based models on the fitness of mutation effects prediction (Table 2). Sequence models employ position embedding strategies such as autoregression (RITA (*Hesslow et al., 2022*), Tranception (*Notin et al., 2022*), and ProGen2 (*Nijkamp et al., 2023*)), masked language modeling (ESM-1b (*Rives et al., 2021*), ESM-1v (*Meier et al., 2021*), and ESM2 (*Lin et al., 2023*)), a combination of the both (ProtTrans (*Elnaggar et al., 2021*)), and convolutional modeling (CARP (*Yang et al., 2022*)). Ad-

₂₇₈ ditionally, we also compare with ESM-if1 (*Hsu et al., 2022*) which incorporates masked language
₂₇₉ modeling objectives with GVP (*Jing et al., 2020*), as well as MIF-ST (*Yang et al., 2023*) with both
₂₈₀ sequence and structure encoding.

Benchmark Datasets

₂₈₂ We conduct a comprehensive comparison of deep learning predictions on hundreds of DMS assays
₂₈₃ concerning different protein types and biochemical assays. We prioritize experimentally measured
₂₈₄ properties that possess a monotonic relationship with protein fitness, such as catalytic activity,
₂₈₅ binding affinity, expression, and thermostability. In particular, **ProteinGym v1** (*Notin et al., 2023*)
₂₈₆ groups 5 sets of protein properties from 217 assays. Two new datasets named **DTm** and **DDG** ex-
₂₈₇ amine 102 environment-specific assays with thermostability scores. In total, 319 assays with around
₂₈₈ 2.5 million mutants are scored. To better understand the novelty of the proposed ProtSSN, we de-
₂₈₉ signed additional investigations on **ProteinGym v0** (*Notin et al., 2022*), an early-release version of
₂₉₀ **ProteinGym** with $1.5M$ missense variants across 86 assays (excluding one assay that failed to be
₂₉₁ folded by both AlphaFold2 and ESMFold, *i.e.*, `A0A140D2T1_ZIKV_Sourisseau_growth_2019`).

Evaluation Metric

₂₉₃ We evaluate the performance of pre-trained models on a diverse set of proteins and protein func-
₂₉₄ tions using Spearman's ρ correlation that measures the strength and direction of the monotonic
₂₉₅ relationship between two ranked sequences, *i.e.*, experimentally evaluated mutants and model-
₂₉₆ inferred mutants (*Meier et al., 2021*; *Notin et al., 2022*; *Frazer et al., 2021*; *Zhou et al., 2023a*). This
₂₉₇ non-parametric rank measure is robust to outliers and asymmetry in mutation scores, and it does
₂₉₈ not assume any specific distribution of mutation fitness scores. The scale of ρ ranges from -1 to 1,
₂₉₉ indicating the negative or positive correlation of the predicted sequence to the ground truth. The
₃₀₀ prediction is preferred if its ρ to the experimentally examined ground truth is close to 1.

Results

Variant Effect Prediction

₃₀₃ We commence our investigation by assessing the predictive performance of ProtSSN on four bench-
₃₀₄ mark datasets using state-of-the-art (SOTA) protein learning models. We deploy different versions
₃₀₅ of ProtSSN that learns kNN graphs with $k \in \{10, 20, 30\}$ and $h \in \{512, 768, 1,280\}$ hidden neurons in
₃₀₆ each of the 6 EGNN layers. For all baselines, their performance on **DTm** and **DDG** are reproduced
₃₀₇ with the official implementation listed in Table 2, and the scores on **ProteinGym v1** are retrieved
₃₀₈ from https://proteingym.org/benchmarks by *Notin et al.* (*2023*). As visualized in Fig. 3 and reported
₃₀₉ in Table 3, ProtSSN demonstrated exceptional predictive performance with a significantly smaller
₃₁₀ number of trainable parameters when predicting the function and thermostability of mutants.

₃₁₁ Compared to protein language models (Fig. 3, colored circles), ProtSSN benefits from abundant
₃₁₂ structure information to more accurately capture the overall protein characteristics, resulting in
₃₁₃ enhanced thermostability and thus achieving higher correlation scores on **DTm** and **DDG**. This is
₃₁₄ attributed to the compactness of the overall architecture as well as the presence of stable local
₃₁₅ structures such as alpha helices and beta sheets, both of which are crucial to protein thermosta-
₃₁₆ bility by providing a framework that resists unfolding at elevated temperatures (*Robinson-Rechavi*
₃₁₇ *et al., 2006*). Consequently, the other two structures-involved models, *i.e.*, ESM-if1 and MIF-ST, also
₃₁₈ exhibit higher performance on the two thermostability benchmarks.

₃₁₉ While sequence-based analysis cannot entirely replace the role of structure-based analysis,
₃₂₀ compared to a fully structure-based deep learning method, a protein language model is more likely
₃₂₁ to capture sufficient information from sequences by increasing the model scale, *i.e.*, the number of
₃₂₂ trainable parameters. This observation aligns with the mechanism of protein functionality, where
₃₂₃ local structures (such as binding pockets and catalytic pockets) and the overall structure (such as
₃₂₄ conformational changes and allosteric effect) are both crucial for binding and catalysis (*Sheng et al.,*

Figure 3. Number of trainable parameters and Spearman's ρ correlation on **DTm**, **DDG**, and **ProteinGym v1**, with the medium value located by the dashed lines. Dot, cross, and diamond markers represent sequence-based, structure-based, and sequence-structure models, respectively.

Figure 4. Ablation Study on **ProteinGym v0** with different modular settings of ProtSSN. Each record represents the average Spearman's correlation of all assays.

2014). Unlike the thermostability benchmarks, the discrepancies between structure-involved models and protein language models are mitigated in **ProteinGym v1** by increasing the model scale. Overall, structure-based and sequence-based methods are suitable for different types of assays, but a comprehensive framework, such as ProtSSN, exhibits the best performance.

Ablation Study

The effectiveness of ProtSSN with different modular designs is examined by its performance on the early released version **ProteinGym v0** (*Notin et al., 2022*) with 86 DMS assays. The complete comparison of baseline comparison on **ProteinGym v0** is detailed in Table S1 in SI. For the ablation study, the results are summarized in Fig. 4(a)-(d) and detailed in Table S2, where each record is subject to a combination of key arguments under investigation. For instance, in the top orange box of Fig. 4(a), we report all ablation results that utilize 6 EGNN layers for graph convolution, regardless of the different scales of ESM-2 or the definitions of node attributes. For all modules investigated in this section, we separately discuss their influence on predicting mutation effects when modifying a single site or an arbitrary number of sites. The two cases are marked on the y-axis by single' and 'all', respectively.

Inclusion of Roto-Translation Equivariance

We assess the effect of incorporating rotation and translation equivariance for protein geometric and topological encoding. Three types of graph convolutions are compared, including GCN (*Kipf and Welling, 2017*), GAT (*Veličković et al., 2018*), and EGNN (*Satorras et al., 2021*). The first two are classic non-equivariant graph convolutional methods, and the last one, which we apply in the main algorithm, preserves roto-translation equivariance. We fix the number of EGNN layers to 6 and examine the performance of the other two methods with either 4 or 6 layers. We find that integrating equivariance when embedding protein geometry significantly.

Sequence Encoding

We next investigate the benefits of defining data-driven node attributes for protein representation learning. We compare the performance of models trained on two sets of graph inputs: the first set defines its AA node attributes through trained ESM2 (*Lin et al., 2023*), while the second set uses one-hot encoded AA types for each node. A clear advantage of using hidden representations by prefix models over hardcoded attributes is evident from the results presented in Fig. 4(b).

Table 4. Influence of folding strategies (AlphaFold2 and ESMFold) on prediction performance for structure-involved models.

	DTm			DDG			ProteinGym-interaction			ProteinGym-catalysis		
	AlphaFold2	ESMFold	diff ↓	AlphaFold2	ESMFold	diff ↓	AlphaFold2	ESMFold	diff ↓	AlphaFold2	ESMFold	diff ↓
avg. pLDDT	90.86	83.22	-	95.19	86.03	-	82.86	65.69	-	85.80	73.45	-
ESM-if1	0.395	0.371	0.024	0.457	0.488	-0.031	0.351	0.259	0.092	0.386	0.368	0.018
MIF-ST	0.400	0.378	0.022	0.438	0.423	-0.015	0.390	0.327	0.063	0.408	0.388	0.020
k30_h1280	0.384	0.370	0.014	0.396	0.390	**0.006**	0.398	0.373	**0.025**	0.443	0.439	**0.004**
k30_h768	0.359	0.356	**0.003**	0.378	0.366	0.012	0.400	0.374	**0.026**	0.442	0.436	**0.006**
k30_h512	0.413	0.399	0.014	0.408	0.394	0.014	0.400	0.372	**0.028**	0.447	0.442	**0.005**
k20_h1280	0.415	0.391	0.024	0.429	0.410	0.019	0.399	0.365	0.034	0.446	0.441	**0.005**
k20_h768	0.415	0.403	**0.012**	0.419	0.397	0.022	0.401	0.370	0.031	0.449	0.442	0.007
k20_h512	0.419	0.395	0.024	0.441	0.432	**0.009**	0.406	0.371	0.035	0.449	0.439	0.010
k10_h1280	0.406	0.391	0.015	0.426	0.411	0.015	0.396	0.365	0.031	0.440	0.434	**0.006**
k10_h768	0.400	0.391	**0.009**	0.414	0.400	0.014	0.379	0.349	0.030	0.431	0.421	0.010
k10_h512	0.383	0.364	0.019	0.424	0.414	**0.010**	0.389	0.364	**0.025**	0.440	0.432	0.008

† The top three are highlighted by **First**, **Second**, **Third**.

Depth of EGNN

Although graph neural networks can extract topological information from geometric inputs, it is vital to select an appropriate number of layers for the module to deliver the most expressive node representation without encountering the oversmoothing problem. We investigate a wide range of choices for the number of EGNN layers among $\{6, 12, 18\}$. As reported in Fig. 4(c), embedding graph topology with deeper networks does not lead to performance improvements. A moderate choice of 6 EGNN layers is sufficient for our learning task.

Scale of ESM

We also evaluate ProtSSN on different choices of language embedding dimensions to study the trade-off between computational cost and input richness. Various scales of prefix models, including $\{8, 150, 650, 3000\}$ millions of parameters, have been applied to produce different sequential embeddings with $\{320, 640, 1280, 2560\}$ dimensions, respectively. Fig. 4(d) reveals a clear preference for ESM2-t33, which employs 650 million parameters to achieve optimal model performance with the best stability. Notably, a higher dimension and richer semantic expression do not always yield better performance. A performance degradation is observed at ESM2 with 3 billion parameters.

AA Perturbation Strategies

ProtSSN utilizes noise sampling at each epoch on the node attributes to emulate random mutations in nature. This introduction of noise directly affects the node attribute input to the graphs. Alongside the 'mutate-then-recode' method we implemented in the main algorithm, we examined four additional strategies to perturb the input data during training. The construction of these additional strategies is detailed below, and their corresponding Spearman's ρ on **ProteinGym v0** is in Fig. 4(e).

Global Average

Suppose the encoded sequential representation of a node is predominantly determined by its AA type. In essence, the protein sequence encoder will return similar embeddings for nodes of the same AA type, albeit at different positions within a protein. With this premise, the first strategy replaces the node embedding for perturbed nodes with the average representations of the same AA types. For example, a random node v_i in a protein is Glycine. If it is altered in the current epoch, $\tilde{v}_i$ is designated as the average sequential embedding of all other Glycines.

Sliding Window

The presumption in the previous method neither aligns with the algorithmic design nor biological heuristics. Self-attention discerns the interaction of the central token with its neighbors across

Table 5. Variant Effect Prediction on **ProteinGym v0** with both MSA and non-MSA methods. Results are retrieved from (*Notin et al., 2022*).

Model	Type	# Params (million)	ρ (by mutation depth) ↑			ρ (by MSA depth) ↑			ρ (by taxon) ↑			
			Single	Double	All	Low	Medium	High	Prokaryote	Human	Eukaryote	Virus
MSA-based methods												
SiteIndep	single	-	0.378	0.322	0.378	**0.431**	0.375	0.342	0.343	0.375	0.401	0.406
EVmutation	single	-	0.423	0.401	0.423	0.406	0.403	0.484	0.499	0.396	0.429	0.381
Wavenet	single	-	0.399	0.344	0.400	0.286	0.404	0.489	0.492	0.373	0.442	0.321
DeepSequence	single	-	0.411	0.358	0.416	0.386	0.391	0.505	0.497	0.396	0.461	0.332
	ensemble	-	0.433	0.394	0.435	0.386	0.394	**0.534**	0.522	0.405	0.480	0.361
EVE	single	-	**0.451**	**0.406**	**0.452**	0.417	**0.434**	0.525	0.518	0.411	0.469	**0.436**
	ensemble	-	**0.459**	**0.409**	**0.459**	0.424	**0.441**	0.532	**0.526**	0.419	**0.481**	**0.437**
MSA-Transfomer	single	100	0.405	0.358	0.426	0.372	0.415	0.500	0.506	0.387	0.468	0.379
	ensemble	500	0.440	0.374	0.440	0.387	0.428	0.513	0.517	0.398	0.467	0.406
Tranception-R	single	700	**0.450**	**0.427**	**0.453**	**0.442**	**0.438**	0.500	0.495	0.424	**0.485**	**0.434**
non-MSA-based methods												
RITA	ensemble	2,210	0.393	0.236	0.399	0.350	0.414	0.407	0.391	0.391	0.405	0.417
ESM-1v	ensemble	3,250	0.416	0.309	0.417	0.390	0.378	**0.536**	0.521	**0.439**	0.423	0.268
ProGen2	ensemble	10,779	0.421	0.312	0.423	0.384	0.421	0.467	0.497	0.412	0.459	0.373
ProtTrans	ensemble	6,840	0.417	0.360	0.413	0.372	0.395	0.492	0.498	0.419	0.400	0.322
ESM2	ensemble	18,843	0.415	0.316	0.413	0.391	0.381	0.509	0.508	**0.456**	0.461	0.213
ProtSSN	ensemble	1,476	0.433	0.381	0.433	0.406	0.402	**0.532**	**0.530**	0.436	**0.491**	0.290

† The top three are highlighted by **First**, **Second**, **Third**.

---

the entire document (protein). The representation of an AA is influenced by both its neighbors' types and locations. Thus, averaging embeddings of AAs from varying positions is likely to forfeit positional information of the modified AA. For this purpose, we consider a sliding window of size 3 along the protein sequence.

Gaussian Noise

The third option regards node embeddings of AA as hidden vectors and imposes white noise on the vector values. We define the mean= 0 and variance= 0.5 on the noise, making the revised node representation $\tilde{v} = v + \mathcal{N}(0, 0.5)$.

Mask

Finally, we employ the masking technique prevalent in masked language modeling and substitute the perturbed AA token with a special `<mask>` token. The prefix language model will interpret it as a novel token and employ self-attention mechanisms to assign a new representation to it. We utilize the same hyperparameter settings as that of BERT (*Devlin et al., 2018*) and choose 15% of tokens per iteration as potentially influenced subjects. Specifically, 80% of these subjects are replaced with `<mask>`, 10% of them are replaced randomly (to other AA types), and the remaining 10% stay unchanged.

Folding Methods

The analysis of protein structure through topological embeddings poses challenges due to the inherent difficulty in obtaining accurate structural observations through experimental techniques such as NMR (*Wüthrich, 1990*) and Cryo-EM (*Elmlund et al., 2017*). As a substitution, we use *in silico* folding models such as AlphaFold2 (*Jumper et al., 2021*) and ESMFold (*Lin et al., 2023*). Although these folding methods may introduce additional errors due to the inherent uncertainty or inaccuracy in structural predictions, we investigate the robustness of our model in the face of potential inaccuracies introduced by these folding strategies.

Table 4 examines the impact of different folding strategies on the performance of DMS predictions for ESM-if1, MIF-ST, and ProtSSN. Although the performance based on ESMFold-derived protein structures generally lags behind structures folded by AlphaFold2, the minimal difference

Table 6. Spearman's ρ correlation of variant effect prediction on **DTm** and **DDG** for non-MSA methods with model ensemble.

Model	# Params (million)	DTm	DDG
RITA	2,210	0.195	0.255
ESM-1v	3,250	0.300	0.310
Tranception	1,085	0.202	0.277
ProGen2	10,779	0.293	0.282
ProTrans	6,840	0.323	0.389
ESM2	18,843	0.346	0.383
ProtSSN	1,476	**0.425**	**0.440**

between the two strategies across all four benchmarks validates the robustness of our ProtSSN in response to variations in input protein structures. We deliberately divide the assays in **ProteinGym v0** (*Notin et al., 2022*) into two groups of interaction (*e.g.*, binding and stability) and catalysis (*e.g.*, activity), as the former is believed more sensitive to the structure of the protein (*Robertson and Murphy, 1997*).

ProtSSN emerges as the most robust method, maintaining consistent performance across different folding strategies, which underscores the importance of our model's resilience to variations in input protein structures. The reported performance difference for both ESM-if1 and MIF-ST is $3-5$ times higher than that of ProtSSN. The inconsistency between the optimal results for **DDG** and the scores reported in Table 3 comes from the utilization of crystal structures in the main results. Another noteworthy observation pertains to the performance of ESM-if1 and MIF-ST on **DDG**. In this case, predictions based on ESMFold surpass those based on AlphaFold2, even outperforming predictions derived from crystal structures. However, the superior performance of these methods with ESMFold hinges on inaccurate protein structures, rendering them less reliable.

Performance Enhancement with MSA and Ensemble

We extend the evaluation on **ProteinGym v0** to include a comparison of our zero-shot ProtSSN with few-shot learning methods that leverage MSA information of proteins (*Meier et al., 2021*). The details are reported in Table 5, where the performance of baseline methods are retrieved from https://github.com/OATML-Markslab/ProteinGym. For ProtSSN, we employ an ensemble of nine models with varying sizes of kNN graphs ($k \in \{10, 20, 30\}$) and EGNN hidden neurons ($\{512, 768, 1280\}$), as discussed previously. The MSA depth reflects the number of MSA sequences that can be found for the protein, which influences the quality of MSA-based methods.

ProtSSN demonstrates superior performance among non-MSA zero-shot methods in predicting both single-site and multi-site mutants, underscoring its pivotal role in guiding protein engineering towards deep mutation. Furthermore, ProtSSN outperforms MSA-based methods across taxa, except for viruses, where precise identification of conserved sites is crucial for positive mutations, especially in spike proteins (*Katoh and Standley, 2021*; *Mercurio et al., 2021*). In essence, ProtSSN provides an efficient and effective solution for variant effects prediction when compared to both non-MSA and MSA-based methods. Note that although MSA-based methods generally consume fewer trainable parameters than non-MSA methods, they incur significantly higher costs in terms of search time and memory usage. Moreover, the inference performance of MSA-based methods relies heavily on the quality of the input MSA, where the additionally involved variance makes impacts the stability of the model performance.

Discussion and Conclusion

The development of modern computational methodologies for protein engineering is a crucial facet of *in silico* protein design. Effectively assessing the fitness of protein mutants not only sup-

ports cost-efficient experimental validations but also guides the modification of proteins toward enhanced or novel functions. Recent deep learning solutions employ a common strategy that involves establishing a hidden protein representation and masking potential mutation sites to recommend plausible amino acids. Previous research has primarily focused on extracting protein representations from either their sequential or structural modalities, with many treating the prediction of mutational effects merely as a secondary task following inverse folding or *de novo* protein design. These approaches often overlook the importance of comprehensive investigation on both global and local perspectives of amino acid interaction that are critical for featuring protein functions. Furthermore, these methods hardly tailored model designs for suggesting mutations, despite the significance of this type of tasks. In this work, we introduce ProtSSN, a denoising framework that effectively cascades protein sequence and structure embedding for predicting mutational effects. Both the protein language model and equivariant graph neural network are employed to encode the global interaction of amino acids with geometry-aware local enhancements. We have extensively validated the efficacy of ProtSSN across various protein function assays and taxa, including two thermostability datasets prepared by ourselves. Our approach consistently demonstrates substantial promise for protein engineering applications, such as facilitating the design of mutation sequences with enhanced interaction and enzymatic activity.

References

Aprile FA, Sormanni P, Podpolny M, Chhangur S, Needham LM, Ruggeri FS, Perni M, Limbocker R, Heller GT, Sneideris T, et al. Rational design of a conformation-specific antibody for the quantification of Aβ oligomers. Proceedings of the National Academy of Sciences. 2020; 117(24):13509–13518.

Brandes N, Ofer D, Peleg Y, Rappoport N, Linial M. ProteinBERT: A universal deep-learning model of protein sequence and function. Bioinformatics. 2022; 38(8):2102–2110.

Devlin J, Chang MW, Lee K, Toutanova K. BERT: Pre-training of deep bidirectional transformers for language understanding. arXiv:181004805. 2018; .

Elmlund D, Le SN, Elmlund H. High-resolution Cryo-EM: the nuts and bolts. Current Opinion in Structural Biology. 2017; 46:1–6.

Elnaggar A, Heinzinger M, Dallago C, Rehawi G, Yu W, Jones L, Gibbs T, Feher T, Angerer C, Steinegger M, Bhowmik D, Rost B. ProtTrans: Towards Cracking the Language of Lifes Code Through Self-Supervised Deep Learning and High Performance Computing. IEEE Transactions on Pattern Analysis and Machine Intelligence. 2021; .

Frauenfelder H, McMahon B. Dynamics and function of proteins: the search for general concepts. Proceedings of the National Academy of Sciences. 1998; 95(9):4795–4797.

Frazer J, Notin P, Dias M, Gomez A, Min JK, Brock K, Gal Y, Marks DS. Disease variant prediction with deep generative models of evolutionary data. Nature. 2021; 599(7883):91–95.

Gray VE, Hause RJ, Luebeck J, Shendure J, Fowler DM. Quantitative missense variant effect prediction using large-scale mutagenesis data. Cell Systems. 2018; 6(1):116–124.

Hesslow D, Zanichelli N, Notin P, Poli I, Marks D. RITA: a study on scaling up generative protein sequence models. In: *ICML Workshop on Computational Biology*; 2022. .

Hsu C, Verkuil R, Liu J, Lin Z, Hie B, Sercu T, Lerer A, Rives A. Learning inverse folding from millions of predicted structures. In: *ICML* PMLR; 2022. p. 8946–8970.

Ismail AR, Kashtoh H, Baek KH. Temperature-resistant and solvent-tolerant lipases as industrial biocatalysts: Biotechnological approaches and applications. International Journal of Biological Macromolecules. 2021; 187:127–142.

Jiang F, Bian J, Liu H, Li S, Bai X, Zheng L, Jin S, Liu Z, Yang GY, Hong L. Creatinase: Using Increased Entropy to Improve the Activity and Thermostability. The Journal of Physical Chemistry B. 2023; 127(12):2671–2682.

Jin W, Wohlwend J, Barzilay R, Jaakkola TS. Iterative Refinement Graph Neural Network for Antibody Sequence-Structure Co-design. In: *ICLR*; 2021. .

Jing B, Eismann S, Suriana P, Townshend RJL, Dror R. Learning from Protein Structure with Geometric Vector Perceptrons. In: *ICLR*; 2020. .

Jones D, Kim H, Zhang X, Zemla A, Stevenson G, Bennett WD, Kirshner D, Wong SE, Lightstone FC, Allen JE. Improved protein–ligand binding affinity prediction with structure-based deep fusion inference. Journal of Chemical Information and Modeling. 2021; 61(4):1583–1592.

Jumper J, Evans R, Pritzel A, Green T, Figurnov M, Ronneberger O, Tunyasuvunakool K, Bates R, Žídek A, Potapenko A, et al. Highly accurate protein structure prediction with AlphaFold. Nature. 2021; 596(7873):583–589.

Katoh K, Standley DM. Emerging SARS-CoV-2 variants follow a historical pattern recorded in outgroups infecting non-human hosts. Communications Biology. 2021; 4(1):1134.

Khersonsky O, Lipsh R, Avizemer Z, Ashani Y, Goldsmith M, Leader H, Dym O, Rogotner S, Trudeau DL, Prilusky J, et al. Automated design of efficient and functionally diverse enzyme repertoires. Molecular Cell. 2018; 72(1):178–186.

Kingma DP, Ba J. ADAM: A method for stochastic optimization. In: *International Conference on Learning Representation*; 2015. .

Kipf TN, Welling M. Semi-supervised classification with graph convolutional networks. In: *ICLR*; 2017. .

Koehler Leman J, Szczerbiak P, Renfrew PD, Gligorijevic V, Berenberg D, Vatanen T, Taylor BC, Chandler C, Janssen S, Pataki A, et al. Sequence-structure-function relationships in the microbial protein universe. Nature Communications. 2023; 14(1):2351.

Kong X, Huang W, Liu Y. Conditional Antibody Design as 3D Equivariant Graph Translation. In: *ICLR*; 2023. https://openreview.net/forum?id=LFHFQbjxIiP.

Lin Z, Akin H, Rao R, Hie B, Zhu Z, Lu W, Smetanin N, Verkuil R, Kabeli O, Shmueli Y, et al. Evolutionary-scale prediction of atomic-level protein structure with a language model. Science. 2023; 379(6637):1123–1130.

Liu Q, Xun G, Feng Y. The state-of-the-art strategies of protein engineering for enzyme stabilization. Biotechnology Advances. 2019; 37(4):530–537.

Madani A, Krause B, Greene ER, Subramanian S, Mohr BP, Holton JM, Olmos Jr JL, Xiong C, Sun ZZ, Socher R, et al. Large language models generate functional protein sequences across diverse families. Nature Biotechnology. 2023; .

Meier J, Rao R, Verkuil R, Liu J, Sercu T, Rives A. Language models enable zero-shot prediction of the effects of mutations on protein function. In: *NeurIPS*, vol. 34; 2021. p. 29287–29303.

Mercurio I, Tragni V, Busto F, De Grassi A, Pierri CL. Protein structure analysis of the interactions between SARS-CoV-2 spike protein and the human ACE2 receptor: from conformational changes to novel neutralizing antibodies. Cellular and Molecular Life Sciences. 2021; 78:1501–1522.

Moal IH, Fernández-Recio J. SKEMPI: A structural kinetic and energetic database of mutant protein interactions and its use in empirical models. Bioinformatics. 2012; 28(20):2600–2607.

Myung Y, Pires DE, Ascher DB. CSM-AB: graph-based antibody–antigen binding affinity prediction and docking scoring function. Bioinformatics. 2022; 38(4):1141–1143.

Nijkamp E, Ruffolo JA, Weinstein EN, Naik N, Madani A. ProGen2: exploring the boundaries of protein language models. Cell Systems. 2023; 14(11):968–978.

Nikam R, Kulandaisamy A, Harini K, Sharma D, Gromiha MM. ProThermDB: thermodynamic database for proteins and mutants revisited after 15 years. Nucleic Acids Research. 2021; 49(D1):D420–D424.

Notin P, Dias M, Frazer J, Hurtado JM, Gomez AN, Marks D, Gal Y. Tranception: protein fitness prediction with autoregressive transformers and inference-time retrieval. In: *ICML*; 2022. p. 16990–17017.

Notin P, Kollasch AW, Ritter D, Van Niekerk L, Paul S, Spinner H, Rollins NJ, Shaw A, Weitzman R, Frazer J, et al. ProteinGym: Large-scale benchmarks for protein fitness prediction and design. In: *NeurIPS*; 2023. .

Orengo C, Michie A, Jones S, Jones D, Swindells M, Thornton J. CATH – a hierarchic classification of protein domain structures. Structure. 1997; 5(8):1093–1109. doi: https://doi.org/10.1016/S0969-2126(97)00260-8.

544 **Rao R**, Meier J, Sercu T, Ovchinnikov S, Rives A. Transformer protein language models are unsupervised struc-
545 ture learners. In: *ICLR*; 2021. .

546 **Rao RM**, Liu J, Verkuil R, Meier J, Canny J, Abbeel P, Sercu T, Rives A. MSA transformer. In: *ICML*; 2021. p.
547 8844–8856.

548 **Riesselman AJ**, Ingraham JB, Marks DS. Deep generative models of genetic variation capture the effects of
549 mutations. Nature Methods. 2018; 15(10):816–822.

550 **Rives A**, Meier J, Sercu T, Goyal S, Lin Z, Liu J, Guo D, Ott M, Zitnick CL, Ma J, et al. Biological structure and
551 function emerge from scaling unsupervised learning to 250 million protein sequences. Proceedings of the
552 National Academy of Sciences. 2021; 118(15):e2016239118.

553 **Robertson AD**, Murphy KP. Protein structure and the energetics of protein stability. Chemical Reviews. 1997;
554 97(5):1251–1268.

555 **Robinson-Rechavi M**, Alibés A, Godzik A. Contribution of electrostatic interactions, compactness and quater-
556 nary structure to protein thermostability: lessons from structural genomics of Thermotoga maritima. Journal
557 of Molecular Biology. 2006; 356(2):547–557.

558 **Roscoe BP**, Thayer KM, Zeldovich KB, Fushman D, Bolon DN. Analyses of the effects of all ubiquitin point
559 mutants on yeast growth rate. Journal of Molecular Biology. 2013; 425(8):1363–1377.

560 **Sarkisyan KS**, Bolotin DA, Meer MV, Usmanova DR, Mishin AS, Sharonov GV, Ivankov DN, Bozhanova NG,
561 Baranov MS, Soylemez O, et al. Local fitness landscape of the green fluorescent protein. Nature. 2016;
562 533(7603):397–401.

563 **Satorras VG**, Hoogeboom E, Welling M. E(n) equivariant graph neural networks. In: *ICML*; 2021. p. 9323–9332.

564 **Sheng G**, Zhao H, Wang J, Rao Y, Tian W, Swarts DC, van der Oost J, Patel DJ, Wang Y. Structure-based cleavage
565 mechanism of Thermus thermophilus Argonaute DNA guide strand-mediated DNA target cleavage. Proceed-
566 ings of the National Academy of Sciences. 2014; 111(2):652–657.

567 **Shin JE**, Riesselman AJ, Kollasch AW, McMahon C, Simon E, Sander C, Manglik A, Kruse AC, Marks DS. Pro-
568 tein design and variant prediction using autoregressive generative models. Nature Communications. 2021;
569 12(1):2403.

570 **Suzek BE**, Wang Y, Huang H, McGarvey PB, Wu CH, Consortium U. UniRef clusters: a comprehensive and
571 scalable alternative for improving sequence similarity searches. Bioinformatics. 2015; 31(6):926–932.

572 **Torng W**, Altman RB. High precision protein functional site detection using 3D convolutional neural networks.
573 Bioinformatics. 2019; 35(9):1503–1512.

574 **Vaswani A**, Shazeer N, Parmar N, Uszkoreit J, Jones L, Gomez AN, Kaiser L, Polosukhin I. Attention Is All You
575 Need. In: *NeurIPS*; 2017. .

576 **Veleckỳ J**, Hamsikova M, Stourac J, Musil M, Damborsky J, Bednar D, Mazurenko S. SoluProtMutDB: A manually
577 curated database of protein solubility changes upon mutations. Computational and Structural Biotechnology
578 Journal. 2022; 20:6339–6347.

579 **Veličković P**, Cucurull G, Casanova A, Romero A, Lio P, Bengio Y. Graph attention networks. In: *ICLR*; 2018. .

580 **Vig J**, Madani A, Varshney LR, Xiong C, Rajani N, et al. BERTology Meets Biology: Interpreting Attention in Protein
581 Language Models. In: *ICLR*; 2021. .

582 **Wang Y**, Xue P, Cao M, Yu T, Lane ST, Zhao H. Directed evolution: methodologies and applications. Chemical
583 Reviews. 2021; 121(20):12384–12444.

584 **Woodley JM**. Protein engineering of enzymes for process applications. Current Opinion in Chemical Biology.
585 2013; 17(2):310–316.

586 **Wüthrich K**. Protein structure determination in solution by NMR spectroscopy. Journal of Biological Chemistry.
587 1990; 265(36):22059–22062.

588 **Yang KK**, Lu AX, Fusi N. Convolutions are competitive with transformers for protein sequence pretraining. In:
589 *ICLR Machine Learning for Drug Discovery*; 2022. .

590 **Yang KK**, Wu Z, Arnold FH. Machine-learning-guided directed evolution for protein engineering. Nature Meth-
591 ods. 2019; 16(8):687–694.

592 **Yang KK**, Zanichelli N, Yeh H. Masked inverse folding with sequence transfer for protein representation learning.
593 Protein Engineering, Design and Selection. 2023; 36.

594 **Yi K**, Zhou B, Shen Y, Liò P, Wang YG. Graph denoising diffusion for inverse protein folding. In: *NeurIPS*; 2023. .

595 **Zhang N**, Bi Z, Liang X, Cheng S, Hong H, Deng S, Lian J, Zhang Q, Chen H. Ontoprotein: Protein pretraining with
596 gene ontology embedding. arXiv:220111147. 2022; .

597 **Zhao W**, Zhong B, Zheng L, Tan P, Wang Y, Leng H, de Souza N, Liu Z, Hong L, Xiao X. Proteome-wide 3D
598 structure prediction provides insights into the ancestral metabolism of ancient archaea and bacteria. Nature
599 Communications. 2022; 13(1):7861.

600 **Zheng L**, Lu H, Zan B, Li S, Liu H, Liu Z, Huang J, Liu Y, Jiang F, Liu Q, et al. Loosely-packed dynamical structures
601 with partially-melted surface being the key for thermophilic argonaute proteins achieving high DNA-cleavage
602 activity. Nucleic Acids Research. 2022; 50(13):7529–7544.

603 **Zhou B**, Zheng L, Wu B, Tan Y, Lv O, Yi K, Fan G, Hong L. Protein Engineering with Lightweight Graph Denoising
604 Neural Networks. bioRxiv. 2023; doi: 10.1101/2023.11.05.565665.

605 **Zhou B**, Zheng L, Wu B, Yi K, Zhong B, Lio P, Hong L. Conditional Protein Denoising Diffusion Generates Pro-
606 grammable Endonucleases. bioRxiv. 2023; p. 2023–08.

607 **Zhou Y**, Pan Q, Pires DE, Rodrigues CH, Ascher DB. DDMut: predicting effects of mutations on protein stability
608 using deep learning. Nucleic Acids Research. 2023; p. gkad472.