Isolation and electrochemical analysis of a facultative anaerobic electrogenic

strain *Klebsiella* sp. SQ-1

Lei Zhou[1], Tuoxian Tang[2], Dandan Deng[1], Yayue Wang[1], Dongli Pei[1]*

1 Henan Provincial Engineering Research Center for Development and Application of

Characteristic Microorganism Resources, College of Biology and Food, Shangqiu

Normal University, Shangqiu, Henan 476000, PR China

2 Department of Biological Sciences, Virginia Tech, Blacksburg, VA 24060, USA

*Corresponding author, Dr. Dongli Pei; Email: peidongli007@sqnu.edu.cn

Abstract

Electricigens decompose organic matter and convert stored chemical energy into electrical energy through extracellular electron transfer. They serve as significant biocatalysts for microbial fuel cells which have practical applications in green energy generation, effluent treatment, and bioremediation. A facultative anaerobic electrogenic strain SQ-1 is isolated from sludge in a biotechnology factory. The strain SQ-1 is a close relative of *Klebsiella variicola*. Multilayered biofilms form on the surface of a carbon electrode after the isolated bacteria are inoculated into a microbial fuel cell device. This strain produces high current densities of 625 μA cm^{-2} by using acetate as the carbon source in a three-electrode configuration. The electricity generation performance is also analyzed in a dual-chamber microbial fuel cell. It reaches a maximum power density of 560 mW m^{-2} when the corresponding output voltage is 0.59 V. The facultative strain SQ-1 utilizes hydrous ferric oxide as an electron acceptor to perform extracellular electricigenic respiration in anaerobic conditions. Since facultative strains possess better properties than anaerobic strains, *Klebsiella* sp. SQ-1 may be a promising exoelectrogenic strain for applications in microbial electrochemistry.

Keywords: microbial fuel cell, *Klebsiella* sp., electrochemical analysis, extracellular respiration, facultative electricigens

Introduction

Microbial fuel cell (MFC) is a bio-electrochemical system that converts chemical energy to electricity by using electricigens as biocatalysts, which has practical values in biomass degradation, sewage disposal, and clean energy generation (Elmaadawy et al., 2022; Ren et al., 2022; Thapa et al., 2022). Electricigens function as biocatalysts in MFC, which play vital roles in substrate oxidation and electron (or hydrogen) transfer. The electricity generation process consists of several steps: anodic oxidation, electron transport in an external circuit, proton migration, and cathodic reduction. Generally, two types of inocula are utilized in MFC: mixed culture and pure culture. In mixed culture, microbial interactions offer good adaptability to the environment because the microflora can degrade a wide variety of substrates and facilitate concurrent power generation. Additionally, some microbes secrete specific electron transfer mediators (ETMs) which may also contribute to the performance boost in the MFC (Islam et al., 2018; Kiely et al., 2011). However, this synergy effect in microflora doesn't always happen. Antagonistic interactions and metabolic conflicts between different microbes give rise to a performance decrease in MFC.

In contrast, using simple substrates as carbon sources such as acetate, formate, citrate, and pyruvate (Yousaf, 2017; Zhao et al., 2017; Zhou et al., 2016), pure culture achieved better performance than mixed culture. Different types of electricigens like *Geobacter* sp., *Shewanella* sp., *Pseudomonas* sp., *Citrobacter* sp., *Klebsiella* sp., *Escherichia* sp., *Bacillus* sp., and *Saccharomyces cerevisiae* have been employed as

biocatalysts in MFC (Bond et al., 2003; Cao et al., 2019; Ieropoulos et al., 2005; Jimenez Pacheco et al., 2023; Kim et al., 2005; Rabaey et al., 2005). Studies on these isolated bacteria helped scientists better understand the specific mechanisms of extracellular respiration (Bishir et al., 2023; Meylani et al., 2023). More importantly, it is easier to manipulate these electricigens and optimize their power generation performance in MFC. Among the studied electricigens, *Geobacter* sp. and *Shewanella* sp. are the most representative anaerobic and facultative anaerobic strains, respectively. *Geobacter* sp. can use ambient ferric iron or solid electrodes as electron acceptors for extracellular electron transfer, but it is not able to secret ETMs. As for *Shewanella* sp., the "nanowires" extended from the outer membrane give it an advantage in extracellular electron transfer, by which the ferric reduction is accelerated. However, it showed much lower power generation in MFC or other bio-electrochemical systems than strictly anaerobic *Geobacter* sp. under the same conditions (Marsili et al., 2008; Pirbadian et al., 2014).

To date, several facultative anaerobic electricigens such as *Shewanella*sp., *Pseudomonas* sp., *Citrobacter* sp., and *Klebsiella* sp. were isolated and able to achieve the metabolic pathway shift between electricigenic respiration and anaerobic fermentation in MFC, which showed prospective applications in bioremediation, wastewater treatment, heavy metal leaching, and the global carbon cycle (Chaudhuri et al., 2003; Deng et al., 2010; Rabaey et al., 2004). For instance, the wild-type *Klebsiella variicola* generates electricity by utilizing the palm oil mill effluent as a substrate, achieving the maximum power density of 4,426 mW m^{-3} and a high

coulombic efficiency of 63% in MFC (Islam et al., 2018). Another facultative anaerobic electricigen named *Shewanellaoneidensis* MR-1 is a model dissimilatory iron-reducing bacterium, which uses iron oxides as electron acceptors and adsorbs phosphate anions and metal ions during the bioreduction process (Ge et al., 2022; Long et al., 2021; Yu et al., 2022).

Previous electrochemical studies have demonstrated that the low power output by electricigens is a big hurdle to the industrial applications of MFC (Bello et al., 2017). Therefore, it is a long-term challenge to screen superior exoelectrogenic strains with high efficiency and strong environmental adaptability. In this study, a facultative anaerobic strain SQ-1 was isolated from sludge in a biotechnology factory. The electricity generation capacity and ferric reduction of this strain were investigated by using dual-chamber MFCs and an electrochemical workstation.

Experimental

Materials and methods

Growth medium, inoculation, and culture

The activated sludge was collected from an anaerobic waste water tank in New Yangshao Biological Technology Factory, Henan, China. The sample was inoculated in 100 mL of growth medium containing 0.6 g KCl, 1.5 g NH_4Cl, 0.3 g KH_2PO_4, 0.1 g $MgCl_2$, 0.1 g $CaCl_2$, 10 mL of trace element solution, and 10 mL of vitamin solution as previously described (Liu et al., 2014; Zhou et al., 2016). Meanwhile, 20 mM acetate sodium and 40 mM fumarate were supplemented as electron donors and acceptors, respectively. The initial pH of the medium was adjusted to 7.2 and

autoclaved at 121 °C for 15 min. The mixed microflora (or pure bacteria) was

incubated at 30 °C under aerobic or anaerobic static conditions. Anaerobic conditions

were created in serum vials by purging with high-purity nitrogen for 20 min and the

vial was sealed with a rubber plug. The model electricigen *G. sulfurreducens* PCA

was purchased from Deutsche Sammlung von Mikroorganismen und Zellkulturen

GmbH and cultured in the growth medium.

Isolation and identification of the electricigenic strain

The enrichment of facultative anaerobes was achieved by injecting 10% of the sludge

sample into 200 mL of growth medium in a 500 mL flask. The microbes were

cultured at 30 °C, 180 rpm for 7 days. Five percent of the selective inoculation was

transferred into the growth medium under anaerobic conditions and cultured at 30 °C

for 7 days to further deplete aerobic bacteria. The finally as-obtained mixed bacteria

were utilized as inoculum for screening facultative anaerobic electricigens using a

dual-chamber MFC.

After the electrochemically active biofilm was enriched on the anode, the whole

electrode was immersed in the phosphate-buffered saline (PBS) solution and the

biofilm was detached by shaking strongly to prepare a bacterial suspension for

utilization. The well-dispersed samples were serially diluted from 10^{-1} to 10^{-6} and

plated on agar plates in an anaerobic incubator. After one week of culture at 30 °C,

different colonies were inoculated into the liquid growth medium. An MFC device

was used to test voltage-producing capabilities. The whole isolation procedure was

repeated until single colonies of facultative anaerobic electricigens were isolated and

they exhibited similar output power density.

Discrete colonies were used as templates for PCR. The following universal primers were used to amplify the 16S rDNA: 27F (5'-AGA GTTTGA TCC TGG CTC AG-3') and 1492R (5'-GGT TAC CTT GTT ACGACT T-3'). The 16S rDNA gene sequences were compared in the National Centre for Biotechnology Information (NCBI) databank, and the related neighbor-joining phylogenetic tree was constructed by using the Molecular Evolutionary Genetics Analysis (MEGA, version 6.0) package. A bootstrap analysis was based on 1,000 resamplings.

MFC construction and operation

A dual-chamber MFC having a total volume of 150 mL and an effective volume of 100 mL in each section (anode or cathode) was used to test the electrogenic ability of the isolated electricigen SQ-1 or *G. sulfurreducens* PCA, respectively. The anode and cathode compartments were separated by a proton exchange membrane (PEM, Nafion 117, Dupont Co., USA) with an effective area of 4π cm^2. In the anode chamber, a carbon rod with a working area of 9.6 cm^2 was used as an anode. The growth medium containing 20 mM sodium acetate was used as anolyte and 10% inoculum of the isolated strain or *G. sulfurreducens* PCA was added to the chamber. A small carbon brush (2.5 cm in diameter and 2.5 cm long) connected by a titanium wire served as an electrode in the cathodic chamber, which contained 50 mM potassium ferricyanide and 0.1 M PBS solution. The MFC was purged strictly with high-purity nitrogen for at least 20 min before running experiments. A 1,000 ohms resistance was connected in an external circuit except when plotting the polarization curve. Besides, the output

voltages were simultaneously monitored by a Keithley instrument (Model 2400) at an

interval of 24 h. The recorded voltage was converted to output power.

All the electrodes were cleaned with 5.0 M NaOH and 75% ethanol several times to

remove impurities and stored in deionized water before the next use. All

measurements were performed at 30 °C. The experiments were conducted in triplicate

under the same operating conditions.

Half-cell experiments

Half-cell electrochemical experiments were performed by a 50 mL quartz bioreactor

in a three-electrode system, consisting of working and counter electrodes as well as a

saturated calomel reference electrode (SCE, Hg/Hg_2Cl_2 saturated KCl, +0.244 V vs.

hydrogen standard electrode (SHE)). The polished graphite with a geometric surface

area of 2.6 cm^2 served as the working and counter electrode, respectively. The

anaerobic bioreactor was sealed with a rubber plug and purged with high-purity

nitrogen for 20 min before running experiments. The growth of biofilm was

monitored by an 8-channel potentiostat (CHI 1040C, CH Instruments, USA) at a

constant potential of 0.30 V with stirring at 30 °C. Meanwhile, the cyclic

voltammogram (CV) was tested at a scan rate of 5 mV s^{-1} between the potential

ranges of +0.3 V (E_i) to -0.6 V (E_f). All potentials in this study are versus SCE unless

otherwise stated.

Electrochemical impedance spectroscopy

Electrochemical impedance spectroscopy (EIS) analysis was performed in a

three-electrode system to evaluate the contribution of internal resistances in biofilms

and this system was connected to an electrochemical station (CHI 760E, CH Instruments, USA) (Islam et al., 2017). The EIS was acquired at OCV by applying AC potential in the frequency range of 100,000-5,000,000 Hz at 10 mV amplitude to prevent biofilm detachment and maintain systematic stability. The EIS data was plotted in a Nyquist curve. The charge transfer resistance (R_{ct}) and ohmic resistance (R_{Ω}) were calculated by fitting the measured impedance data to an equivalent circuit (EC): R(Q[RW]) using Z view software.

Morphological analysis

The morphological characteristics of biofilm on carbon electrodes were analyzed with a scanning electron microscope (Hitachi S-3400N, Tokyo, Japan) at 15 kV as mentioned before (Zhou et al., 2016).

Analysis of ferric reduction

Ferric citrate was used as an electron acceptor to verify the capability of ferric reduction under aerobic and anaerobic conditions. The microbial growth was estimated by measuring the optical density (OD) of the cell culture at a wavelength of 600 nm (OD_{600}). The *o*-phenanthroline (1,10-phenanthroline) method was used to measure the total Fe(II) concentration (Georgi et al., 2017; Islas et al., 2018). Aliquots were taken from the medium and the same volume of 0.5 M HCl was added. The mixture was vigorously shaken and incubated in an anaerobic incubator for 24 hours to extract the adsorbed Fe(II). After centrifugation at 10,000 g for 5 min, the supernatants were used for Fe(II) measurements. Experiments were performed in triplicate.

Results and discussion

Enrichment, isolation, and identification of the strain SQ-1

Various organic compounds were utilized in the MFC for power generation, such as glucose, sodium citrate, sodium lactate, and glutamic acid (Qiu et al., 2022; Sarmin et al., 2021; Yyya et al., 2022). The output voltage of the MFC using mixed microflora as an inoculum and sodium acetate as a carbon source was measured. It showed a maximum output voltage of 0.55 V after 35 hours of running. When there was enough sodium acetate in the culture, a voltage of 0.50 V or above was maintained for at least 50 hours in three fed-batch MFCs (Fig. 1A). Moreover, the polarization curve was plotted when the MFC stably ran in the second batch (Fig. 1B). The maximum power density was 260 mW m^{-2} when the output voltage was 0.48 V. This MFC system showed average electricity generation performance. It may be due to the antagonism between certain microbial populations or the lack of substrate metabolite-based synergy, which inhibited the biofilm enrichment on the anode or the electron transfer between microbes and electrode surface (Judith et al., 2017; Min-Chi et al., 2015).

In an MFC system catalyzed by mixed microflora, it is believed that both the biofilms enriched on the anode and free microorganisms in the solution contributed to electricity generation. Once electrochemically active biofilm was enriched from activated sludge in the MFC, the anode was used to isolate facultative anaerobic electricigens by using the spread plate technique. A single colony was picked from the agar plate and passaged five times. The isolated electricigen, named SQ-1 was identified through 16S rDNA sequencing, which was found to be 99.23% homologous

to *Klebsiella variicola* SB5531[T] (Fig. 1C). Additionally, the isolated strain SQ-1 and

the strictly anaerobic electricigen *G. sulfurreducens* PCA were cultured in the same

growth medium under anaerobic conditions for 3 days. Their bacterial solutions

showed a different color. (Fig. 1D).

Electricity generation performance of *Klebsiella* sp. SQ-1 in MFC

In this study, the electrochemical activity of the isolated strain SQ-1 was evaluated in

MFC. The output voltage was recorded using the isolated *Klebsiella* sp. SQ-1 and *G.*

sulfurreducens PCA as inoculums, respectively. The strain SQ-1 showed a rapid

increase of output voltage from 110 to 180 h, which reached approximately 0.53 V

(Fig. 2A). The output voltage of *G. sulfurreducens* PCA showed an identical pattern in

fed-batch MFCs under similar conditions (Fig. 2B). The maximum output voltage

(0.57 V) of the strain SQ-1 was higher than that of *G. sulfurreducens* PCA (0.52 V).

More importantly, the strain SQ-1 was able to maintain a high output voltage for a

longer time than that of *G. sulfurreducens* PCA in each fed-batch MFC, which

suggested that the facultative strain SQ-1 had better electricity generation

performance than either the strictly anaerobic *G. sulfurreducens* PCA or the mixed

bacteria (Fig. 1A).

The maximum power density of SQ-1 reached 560 mW m^{-2} when the corresponding

output voltage was 0.59 V in MFC (Fig. 2C). The *G. sulfurreducens* PCA showed a

maximum power density of 460 mW m^{-2} when the output voltage was 0.47 V (Fig.

2D). The electrical generation performance of some reported electricigens was

summarized in Table 1. Facultative electricigens showed many advantages over

anaerobic electricigens, for example, less stringent growth conditions and faster

microbial growth. However, low power generation in a bio-electrochemical system

impeded their applications in the MFC (Sunarno et al., 2019; Vikromvarasiri et al.,

2016). The facultative anaerobic electricigen *Klebsiella* sp. SQ-1 with high power

generation capacity might be one of the potential candidates in the engineering of

biological catalysts for MFC.

Electrochemical performance of *Klebsiella* sp. SQ-1 in half-cell experiments

The chronoamperometric curve of SQ-1 showed that the current density increased

from 7 μA cm^{-2} and drastically reached the maximum value of approximately 625 μA

cm^{-2} after operating for 43 hours by utilizing sodium acetate as the sole carbon source

(Fig. 3A). The power generation capacity of the strain SQ-1 was similar with that of

G. sulfurreducens PCA as previously reported (Zhou et al., 2016).

The current density gradually decreased after it reached the plateau due to the

depletion of substrate and accumulation of metabolites. The cyclic voltammogram

(CV) method was performed to analyze its electrochemical characteristics, and a

typical sigmoidal CV curve was obtained when the biofilm formed on a carbon sheet

electrode with a maximum current density of 625 μA cm^{-2} (Table 1). The strong

catalytic activity indicated the biofilms and dissociated microbes effectively transfer

electrons to the electrode surface under the turnover status. Meanwhile, two pairs of

redox peaks under the non-turnover status were shown (Fig. 3A inset). Their midpoint

potentials were located at -0.35 V (E_1) and -0.43 V (E_2), respectively (Fig. 3A).

The morphological characteristics of the strain SQ-1 were studied using a scanning

electron microscope (Fig. 3B(1)). Multilayered biofilms were found on the carbon

electrode surface, which might show that it has enough capability to generate a highly

stable current. Besides, the strain SQ-1 was inoculated into the growth medium

containing Fe(III) oxide as electron acceptor and acetate sodium as electron donor,

and the color of the Fe(III)oxide medium changed from brown to black after 5 days of

incubation (Fig. 3B (2), (3)). The black suspension was magnetically attracted to the

side of a magnet bar, indicating the strain SQ-1 has a strong ferric reduction ability.

To investigate the electron transfer kinetics of the strain SQ-1, CVs were recorded at

scan rates of 1, 2, 5, 10, 20, and 50 mV s^{-1} under the non-turnover condition (Fig. 3C).

A linear relationship between cathodic peak values and scan rates (v) or the square

root of scan rates ($v^{1/2}$) was obtained at approximately -0.37 V when the basic medium

(without electron donor or acceptor) was used. Their good linear relationship

(R_1^2=98.7 and R_2^2=96.3) suggested that the biofilms of SQ-1 showed

surface-controlled and diffusion-controlled kinetics (Fig. 3C inset). A similar pattern

of kinetics was found in *G. sulfurreducens*, *C. freundii*, or mixed culture biofilms

which were formed on carbon electrodes, ITO (Indium Tin Oxide) electrodes, or gold

surfaces under non-turnover conditions (Liu et al., 2015; Liu et al., 2010; Zhou et al.,

2017).

Moreover, the Nyquist plot for the strain SQ-1 biofilms attached on working

electrodes in a half-cell system was shown in Fig. 3D. The equivalent circuit EC:

R(Q[RW]) was used to fit the impedance spectra of biofilms where Rs is the solution

resistance; Rct is the charge transfer resistance at the interface of electrodes; Qct

refers to the constant phase element, which represents the double layer capacitance; $R_{biofilm}$ is the biofilm resistance; $Q_{biofilm}$ represents the double layer capacitance caused by biofilms on the surface of electrodes. The equivalent circuit fitted well with the model and a high R_{ct} (148 ohms) was achieved when the effective electrochemical biofilms formed on the surface of electrodes.

Ferric reduction of *Klebsiella* sp. SQ-1

The strain SQ-1 showed a typical microbial growth curve in both aerobic and anaerobic conditions when the hydrous ferric oxide (HFO) was absent (Fig. 4A). The OD_{600} value measured after 30 hours of growth in aerobic condition (OD_{600}=3.46) was much higher than that in anaerobic conditions (OD_{600}=0.47), which suggested that aerobic respiration plays a dominant role in the growth of strain SQ-1. To further explore the effect of HFO on the growth of *Klebsiella* sp. SQ-1, batch cultures were supplemented with different amounts of ferric citrate and incubated under aerobic or anaerobic conditions. An approximate OD_{600} value of 3.51 was measured after five days of culture in aerobic conditions without the presence of hydrous ferric oxide (Fig. 4B). A lower OD_{600} value (OD_{600}=2.24) was obtained when the medium was supplemented with 5 mM HFO, indicating the growth of strain SQ-1 was affected by the extracellular HFO. However, the bacterial growth maintained at a high and similar level even if the medium was supplemented with higher concentrations of ferric citrate (10-70 mM). Therefore, it was speculated that metabolic pathways were modified in these facultative bacteria when both oxygen and HFO were present in their living environment. Aerobic respiration was the principal pathway that the strain

SQ-1 utilized to grow and proliferate but a part of the energy flow was diverted to the extracellular electricigenic respiration which resulted in less biomass production. By contrast, a much lower OD_{600} value ranging from 0.1 to 0.56 was measured in anaerobic conditions (Fig. 4B) when the growth medium was supplemented with 5 mM to 70 mM ferric citrate, which suggested that the HFO served as an extracellular electron acceptor and sustained the growth of *Klebsiella* sp. SQ-1.

To estimate the Fe(III)-reduction efficiency of the strain SQ-1, the amount of reduced Fe(II) in the medium was measured by the method of *o*-phenanthroline. The amount of Fe(II) at the stationary phase gradually increased when the concentration of Fe(III) increased from 5 mM to 40mM under anaerobic conditions (Fig. 4C). The concentration of reduced Fe(II) increased from 1.25 mM to 6.00 mM (Fig. 4D). The amount of Fe(II) at the stationary phase started to fall when the concentration of Fe(III) was higher than 40 mM, which suggested that high concentration of Fe(III) might inhibit extracellular electricigenic respiration of the strain SQ-1. The highest reduction ratio of ~25% was calculated when 5 mM Fe(III) was supplied (Fig. 4D). Notably, the bacterial biomass was at a low level (OD_{600}=0.1, Fig. 4B) under this condition, which suggested that the strain SQ-1 has a strong ferric reduction ability. However, the reduction ratio decreased to approximately 15% when the concentration of Fe(III) increased to 40 mM and dropped to 4% when the concentration of Fe(III) was 70 mM (Fig. 4D).

Conclusion

A facultative anaerobic electricigen was isolated from a wastewater tank in a

biotechnology factory after a series of aerobic and anaerobic enrichment procedures. The strain SQ-1 was identified as a relative of *Klebsiella variicola* based on its 16S rDNA gene sequences. Using sodium citrate as a substrate, the maximum power density of 560 mW m^{-2} was achieved in a dual-chamber MFC, which was higher than that of *G. sulfurreducens* PCA under similar conditions. Moreover, the strain SQ-1 showed high ferric reduction activity and achieved 15% ferric reduction in the presence of 40 mM HFO under anaerobic conditions. Aerobic respiration was the optimal energy-generating way for *Klebsiella* sp. SQ-1 to grow and proliferate when cultured in aerobic conditions. When the medium was supplemented with HFO and the bacteria were cultured in anaerobic conditions, extracellular electricigenic respiration and anaerobic fermentation were employed to sustain its growth. Considering its high power generation and ferric reduction capacity, the facultative anaerobic strain *Klebsiella* sp. SQ-1 might be a promising biocatalyst in microbial electrochemistry.

Acknowledgments

This research project was supported by grants from the Henan Province Programs for Science and Technology Development (222102110003) and the Natural Science Foundation of Henan Province (222300420259). The funding was awarded to Dongli Pei and Yayue Wang, respectively.

Author Contributions

Lei Zhou: Data collection, Data analysis, Writing-original draft; Tuoxian Tang: Data analysis, Writing-review & editing; Dandan Deng, Writing-review; Yayue Wang,

Dongli Pei, Resources, Funding acquisition, Writing-review & editing. All authors

read and approved the final version of this manuscript.

Conflict of interest

The authors declare that they have no known competing financial interests or personal

relationships that could have appeared to influence the work reported in this paper.

Literature

Bello M M, Raman A. Trend and current practices of palm oil mill effluent polishing: Application of advanced oxidation processes and their future perspectives. J Environ Manage. 2017 Apr;198(1):170-182. https://doi.org/10.1016/j.jenvman.2017.04.050

Bishir M, Correa C R, Olszewski M P, Ado S A, Tariq M, Kruse A. The technology of microbial fuel cells: a promising approach towards simultaneous and sustainable wastewater treatment and bioelectricity generation. Int J Biomass and Renewables. 2023 Apr;12(1):1-8. https://myjms.mohe.gov.my/index.php/ijbr/article/view/22205

Bond, Daniel, R., Lovley, Derek, R. Electricity Production by *Geobacter sulfurreducens* attached to electrodes. Appl Environ Microbiol. 2003 Mar;69(3):1548-1555. https://doi.org/10.1128/AEM.69.3.1548-1555.2003

Cao Y, Mu H, Liu W, Zhang R, Guo J, Xian M, Liu H. Electricigens in the anode of microbial fuel cells: pure cultures versus mixed communities. Microb Cell Fact. 2019 Feb;18(1):39. https://doi.org/10.1186/s12934-019-1087-z

Chaudhuri S K, Lovley D R. Electricity generation by direct oxidation of glucose in

mediatorless microbial fuel cells. Nat Biotechnol. 2003 Sep;21(10):1229-1232. https://doi.org/10.1038/nbt867

Deng D, Zhang Y, Liu Y. A Geobacter strain isolated from rice paddy soil with higher bioelectricity generation capability in comparison to *Geobacter sulfurreducens* PCA. Rsc Adv. 2015 Apr;5(55):43978-43989. https://doi.org/10.1039/C5RA06211J

Deng L F, Fangbai L I, Zhou S G, Huang D Y, Jinren N I. A study of electron-shuttle mechanism in *Klebsiella pneumoniae* based-microbial fuel cells. Sci Bull (Beijing). 2010 Jan;(01):99-104. https://doi.org/10.1007/s11434-009-0563-y

Elmaadawy K, Liu B, Hassan G K, Wang X, Wang Q, Hu J, Hou H, Yang J, Wu X. Microalgae-assisted fixed-film activated sludge MFC for landfill leachate treatment and energy recovery. Process Saf Environ Prot. 2022 Feb;160:221-231. http://dx.doi.org/10.1016/j.psep.2022.02.021

Ge C, Huang D, Wang D, Zhang E, Li M, Zhu F, Zhu C, Chen N, Wu S, Zhou D. Biotic Process Dominated the Uptake and Transformation of Ag^+ by *Shewanella oneidensis* MR-1. Environ Sci Technol. 2022 Feb;4:2366–2377. https://doi.org/10.1021/acs.est.1c06369.

Georgi N, Landman E B, Klein T J, van Blitterswijk C A, Karperien M. O-Phenanthroline as modulator of the hypoxic and catabolic response in cartilage tissue-engineering models. J Tissue Eng Regen Med. 2017 Nov;11(3):724-732. http://dx.doi.org/10.1002/term.1969

Guo Y, Wang G, Zhang H, Wen H, Li W. Effects of biofilm transfer and electron

mediators transfer on *Klebsiella quasipneumoniae* sp. 203 electricity generation performance in MFCs. Biotechnol Biofuels. 2020 Sep;13:1-11. http://dx.doi.org/10.21203/rs.3.rs-17738/v2

Huang J, Zhu N, Cao Y, Peng Y, Wu P, Dong W. Exoelectrogenic bacterium phylogenetically related to *Citrobacter freundii*, isolated from anodic biofilm of a microbial fuel cell. Appl Biochem Biotech. 2015 Nov;175:1879-1891. http://dx.doi.org/10.1007/s12010-014-1418-9

Ieropoulos I, Greenman J, Melhuish C, Hart J. Energy accumulation and improved performance in microbial fuel cells. J Power Sources. 2005 Nov;145(2):253-256. http://dx.doi.org/10.1016/j.jpowsour.2004.11.070

Islam M A, Ethiraj B, Cheng C K, Yousuf A, Khan M. An insight of synergy between *Pseudomonas aeruginosa* and *Klebsiella variicola* in microbial fuel cell. ACS Sustainable Chem Eng. 2018 Jan;6(3): 4130-4137. https://doi.org/10.1021/acssuschemeng.7b04556

Islam M A, Woon C W, Ethiraj B, Cheng C K, Yousuf A, Khan M M R. Correlation of power generation with time-course biofilm architecture using *Klebsiella variicola* in dual chamber microbial fuel cell. Int J Hydrogen Energy. 2017 Sep;42(41):25933-25941. http://dx.doi.org/10.1016/j.ijhydene.2017.08.193

Islas M S, Martinez Medina J J, Piro O E, Echeverria G A, Ferrer E G, Williams P A M. Comparisons of the spectroscopic and microbiological activities among coumarin-3-carboxylate, o-phenanthroline and zinc(II) complexes. Spectrochim Acta A. 2018 Jun;198:212-221.

http://dx.doi.org/10.1016/j.saa.2018.03.003

Jimenez Pacheco H G, Portocarrero Banda A A, Vilca Cayllahua E I, Miranda Ramos L M, Alvarez Tohalino V L, Del Carpio Beltran H J, Delgado Sarmiento P K. New Electrogenic Microorganism *Citrobacter* sp. Isolated from Microbial Fuel Cell and Bacterial Characteristics Determination. Energies. 2023 Mar;16(7):3047. https://doi.org/10.3390/en16073047

Judith F, Deng L, Christian G. Antagonistic Microbial Interactions: Contributions and Potential Applications for Controlling Pathogens in the Aquatic Systems. Front Microbiol. 2017 Nov;8: 1-14. https://doi.org/10.3389/fmicb.2017.02192

Kiely P D, Regan J M, Logan B E. The electric picnic: synergistic requirements for exoelectrogenic microbial communities. Curr Opin Biotechnol. 2011 Mar;22(3):378-385. https://doi.org/10.1016/j.copbio.2011.03.003

Kim J R, Min B, Logan B E. Evaluation of procedures to acclimate a microbial fuel cell for electricity production. Appl Microbiol Biot. 2005 Jan;68(1):23-30. https://doi.org/ 10.1007/s00253-004-1845-6

Liu Y, Deng D, Lan X. A highly efficient mixed-culture biofilm as anodic catalyst and insights into its enhancement through electrochemistry by comparison with *G. sulfurreducens*. Electrochim Acta. 2015 Aug;155:327-334. http://dx.doi.org/10.1016/j.electacta.2014.12.152

Liu Y, Kim H, Franklin R, Bond D R. Gold line array electrodes increase substrate affinity and current density of electricity-producing *G. sulfurreducens* biofilms. Energ Environ Sci. 2010 Sep;3(11):1782.

http://dx.doi.org/10.1039/c0ee00242a

Liu Y, Tang T X, Pei X Q, Zhang C, Wu Z L. Identification of ketone reductase ChKRED20 from the genome of *Chryseobacterium* sp. CA49 for highly efficient anti-Prelog reduction of 3,5-bis(trifluoromethyl)acetophenone. J Mol Catal B-Enzym. 2014 Apr;102:1-8. https://doi.org/10.1016/j.molcatb.2014.01.009

Liu Z, Du Z, Lian J, Zhu X, Li S, Li H. Improving energy accumulation of microbial fuel cells by metabolism regulation using Rhodoferax ferrireducens as biocatalyst. Lett Appl Microbiol. 2007 Apr;44(4):393-398. http://dx.doi.org/10.1111/j.1472-765X.2006.02088.x

Long X, Okamoto A. Outer membrane compositions enhance the rate of extracellular electron transport via cell-surface MtrC protein in *Shewanella oneidensis* MR-1. Bioresour Technol. 2021 Oct;(320): 124290. https://doi.org/10.1016/j.biortech.2020.124290

Marsili E, Baron D B, Shikhare I D, Dan C, Gralnick J A, Bond D R. *Shewanella* secretes flavins that mediate extracellular electron transfer. Proc Natl Acad Sci. 2008 Mar;(10):3968-3973. https://doi.org/10.1073/pnas.0710525105

Meylani V, Surahman E, Fudholi A, Almalki W H, Ilyas N, Sayyed R. Biodiversity in microbial fuel cells: Review of a promising technology for wastewater treatment. J Environ Chem Eng. 2023 May;(11):109503. https://doi.org/10.1016/j.jece.2023.109503

Min C H, Cheng C Y, Liu M H, Ying C C. Effects of operating parameters on

measurements of biochemical oxygen demand using a mediatorless microbial fuel cell biosensor. Sensors. 2015 Nov;16(1):35. https://doi.org/10.3390/s16010035

Pirbadian S, Barchinger S E, Leung K M, Byun H S, Jangir Y, Bouhenni R A, Reed S B, Romine M F, Saffarini D A, Shi L. *Shewanella oneidensis* MR-1 nanowires are outer membrane and periplasmic extensions of the extracellular electron transport components. Proc Natl Acad Sci. 2014 Aug;111(35):12883-12888. http://dx.doi.org/10.1073/pnas.1410551111

Qiao Y, Li C M, Lu Z, Ling H, Kang A, Chang M W. A time-course transcriptome analysis of Escherichia coli with direct electrochemistry behavior in microbial fuel cells. Chem Commun. 2009 Sep;(41):6183-6185. http://dx.doi.org/10.1039/b912003c

Qiu S, Wang L, Zhang Y, Yu Y. Microbial Fuel Cell-Based Biosensor for Simultaneous Test of Sodium Acetate and Glucose in a Mixed Solution. Int J Environ Res Public Health. 2022 Sep;19(19). http://dx.doi.org/10.3390/ijerph191912297

Rabaey K, Boon N, Siciliano S D, Verhaege M, Verstraete W. Biofuel Cells Select for Microbial Consortia That Self-Mediate Electron Transfer. Appl Environ Microb. 2004 Sep;70(9):5373-5382. http://dx.doi.org/10.1128/aem.70.9.5373-5382.2004

Rabaey K, Verstraete W. Microbial fuel cells: novel biotechnology for energy generation. Trends Biotechnol. 2005 Jul;23(6):291-298.

http://dx.doi.org/10.1016/J.TIBTECH.2005.04.008

Ren Z, Ji G, Liu H, Yang M, Xu S, Ye M, Lichtfouse E. Accelerated start-up and improved performance of wastewater microbial fuel cells in four circuit modes: Role of anodic potential. J Power Sources. 2022 May;535:231403. http://dx.doi.org/10.1016/j.jpowsour.2022.231403

Sarmin S, Tarek M, Roopan S M, Cheng C K, Rahman Khan M M. Significant improvement of power generation through effective substrate-inoculum interaction mechanism in microbial fuel cell. J Power Sources. 2021 Dec;484:229285. http://dx.doi.org/10.1016/j.jpowsour.2020.229285

Sunarno J N, Prasertsan P, Duangsuwan W, Cheirsilp B, Sangkharak K. Biodiesel derived crude glycerol and tuna condensate as an alternative low-cost fermentation medium for ethanol production by *Enterobacter aerogenes*. Ind Crops and Prod. 2019 Jul;138:111451. http://dx.doi.org/10.1016/j.indcrop.2019.06.014

Thapa B S, Pandit S, Patwardhan S B, Tripathi S, Mathuriya A S, Gupta P K, Lal R B, Tusher T R. Application of microbial fuel cell (MFC) for pharmaceutical wastewater treatment: an overview and future perspectives. Sustain Sci. 2022 Jul;14(14):8379. http://dx.doi.org/10.3390/su14148379

Vikromvarasiri N, Haosagul S, Boonyawanich S, Pisutpaisal N. Microbial dynamics in ethanol fermentation from glycerol. Int J Hydrogen Energy. 2016 Jun;41(35):15667-15673. http://dx.doi.org/10.1016/j.ijhydene.2016.04.188

Watson V J, Logan B E. Power production in MFCs inoculated with *Shewanella*

oneidensis MR-1 or mixed cultures. Biotechnol Bioeng. 2010 Sep;105(3):489-498. http://dx.doi.org/10.1002/bit.22556

Yong X Y, Yan Z Y, Shen H B, Zhou J, Wu X Y, Zhang L J, Zheng T, Jiang M, Wei P, Jia H H. An integrated aerobic-anaerobic strategy for performance enhancement of *Pseudomonas aeruginosa*-inoculated microbial fuel cell. Bioresource Technol. 2017 Jun;241:1191-1196. http://dx.doi.org/10.1016/j.biortech.2017.06.050

Yousaf S. Characterization of the Electric Current Generation Potential of the *Pseudomonas aeruginosa* Using Glucose, Fructose, and Sucrose in Double Chamber Microbial Fuel Cell. Iran J Biotechnol. 2017 Dec;15(4):216. http://dx.doi.org/10.15171/ijb.1608

Yu W, Wang R, Linghu R, Liang J, Hu Q, Yao Y. The influence of *Shewanella oneidensis* MR-1 on the transformation of iron oxides and phosphorus in a red soil. Soil Water Res. 2022 Jan;(1)17: 59-68. http://dx.doi.org/10.17221/60/2021-SWR

Yang Y Y, Sheng H Z, Shao L C, Jun J W, Liang C, Shan W L, Xiang X, Xiang T Z. Electrochemistry of newly isolated Gram-positive bacteria *Paenibacillus lautus* with starch as sole carbon source. Electrochim Acta. 2022 Apr;411:140068. https://doi.org/10.1016/j.electacta.2022.140068

Zhao Y G, Zhang Y, She Z, Shi Y, Wang M, Gao M, Guo L. Effect of Substrate Conversion on Performance of Microbial Fuel Cells and Anodic Microbial Communities. Environ Eng Sci. 2017 Sep;34(9):666-674.

https://doi.org/10.1089/ees.2016.0604

Zhou L, Deng D, Zhang D, Chen Q, Kang J, Fan N, Liu Y. Microbial electricity

generation and isolation of exoelectrogenic bacteria based on petroleum

hydrocarbon-contaminated soil. Electroanal. 2016 Feb;28(7):1510-1516.

https://doi.org/10.1002/elan.201501052

Zhou L, Deng D, Zhang Y, Zhou W, Jiang Y, Liu Y. Isolation of a facultative

anaerobic exoelectrogenic strain LZ-1 and probing electron transfer

mechanism in situ by linking UV/Vis spectroscopy and electrochemistry.

Biosens   Bioelectron.   2017   Apr;90:264-268.

http://dx.doi.org/10.1016/j.bios.2016.11.059

Figure legends

Figure 1. Enrichment, isolation, and identification of the strain SQ-1

(A) The output voltage performance of mixed microflora in a dual-chamber MFC

using sodium acetate as a carbon source. Arrows show the supply of sodium acetate.

(B) The output voltage (circle) and power density (square) curves for mixed

microflora.

(C) Phylogenetic analysis of the strain SQ-1 based on 16S rDNA gene sequences.

(D) The appearance of the strain SQ-1 and *G. sulfurreducens* PCA in liquid growth

medium after 3 days of growth.

Figure 2. Output voltage and power density of *Klebsiella* sp. SQ-1 in MFC

(A) The output voltage performance of the strain SQ-1 in a dual-chamber MFC using

sodium acetate as a carbon source. Arrows show the supply of sodium acetate.

(B) The output voltage performance of a model electricigen *G. sulfurreducens* PCA in

a dual-chamber MFC using sodium acetate as a carbon source. Arrows show the

supply of sodium acetate.

(C) The output voltage (circle) and power density (square) curve for the strain SQ-1.

(D) The output voltage (circle) and power density (square) curves for *G.*

sulfurreducens PCA.

Figure 3. Electrochemical performance of *Klebsiella* sp. SQ-1 in a three-electrode

system

(A) Chronoamperometric curves for the strain SQ-1 in a three-electrode system using

sodium acetate as electron acceptors. Inset, cyclic voltammograms of the enriched

strain SQ-1 biofilm on electrodes in different stages. (a) before the formation of

biofilm; (b) after the formation of biofilm with a current density below 2 $\mu A\,cm^{-2}$.

(B) (B1), The morphology of the strain SQ-1 biofilms under the scanning electron

microscope (5,000×). Biofilms were attached to the graphite surface. (B2) The

appearance of bacterial culture after 5 days of incubation when the growth medium is

supplemented with Fe(III) oxide. A magnet is placed outside the tube. The arrow

shows the magnet attracts the black suspension. (B3) The initial appearance of

bacterial culture.

(C) Voltammograms of the strain SQ-1 biofilm. Scan rates: 1, 2, 5, 10, 20, 50 mV s^{-1}.

Inset, the linear dependence of the cathodic peak current density at -0.37 V versus

scan rates or square roots of scan rates.

(D) The Nyquist plot for biofilms attached to working electrodes.

Figure 4. Ferric reduction of *Klebsiella* sp. SQ-1

(A) The growth curve of strain SQ-1 measured under aerobic and anaerobic

conditions.

(B) The growth curve of strain SQ-1 when the growth medium was supplemented

with different amounts of ferric citrate.

(C) Measurement of reduced Fe^{2+}.

(D) Analysis of Fe^{3+} reduction ratio. The concentration of Fe^{2+} was measured after 30

hours of incubation.

Figure 1

Figure 2

Figure 3

3 **Table 1. Electrical generation performance of reported electricigens**

Strains	Substrates	Voltage (V)	Power density (mW m^{-2})	Current density (μA cm^{-2})	References
SQ-1	Sodium acetate	0.59	560	625	This work
G. sulfurreducens PCA	Sodium acetate	0.47	460	605	(Deng et al., 2015)
Pseudomonas aeruginosa	Glucose	/	/	52.1	(Yong et al., 2017)
Klebsiella pneumonia	Glucose	0.621	40.26	/	(Guo et al., 2020)
Shewanella oneidensis	Lactate	/	41	/	(Watson et al., 2010)
Citrobacter freundii	Citrate	/	204.5	/	(Huang et al., 2015)
Escherichia coli	Glucose	/	/	34	(Qiao et al., 2009)
Rhodoferax ferrireducens	Glucose	/	/	14.6	(Liu et al., 2007)