Improving generalizability for MHC-I binding peptide predictions through structure-based geometric deep learning

Dario F. Marzella[†1], Giulia Crocioni[†2], Tadija Radusinović[3], Daniil Lepikhov[1], Heleen Severin[1], Dani L. Bodor[2], Daniel T. Rademaker[1], ChiaYu Lin[2], Sonja Georgievska[2], Nicolas Renaud[2], Amy L. Kessler[4], Pablo Lopez-Tarifa[2], Sonja Buschow[4], Erik Bekkers[3], Li C. Xue[1]*

[†] these authors contributed equally

*corresponding author

[1] *Medical BioSciences department, Radboudumc, Radboud University Medical Center, 6525 GA Nijmegen, The Netherlands*

[2] *Netherlands eScience Center, Amsterdam, The Netherlands*

[3] *University of Amsterdam, Amsterdam, The Netherlands*

[4] *Department of Gastroenterology and Hepatology, Erasmus MC, University Medical Center Rotterdam, 3015 GD Rotterdam, The Netherlands.*

Abstract

Understanding MHC peptide presentation is crucial for pathogen recognition, autoimmune disease treatment, and cancer immunotherapy development. *In silico* prediction of MHC-bound peptides is essential for cost-effective therapy design. However, state-of-the-art sequence-based (SeqB) methods encounter challenges in sensitivity to data biases and limited generalizability, particularly for less-studied MHC alleles. We hypothesize that structure-based (StrB) methods can enhance generalization by leveraging encoded physics and geometric rules. Introducing three supervised StrB geometric deep learning (GDL) approaches, we demonstrate their superior generalization outperforming two SeqB methods by 5 to 11% in AUC. To enhance data efficiency, we present a self-supervised learning approach, 3D-SSL, surpassing SeqB methods without using binding affinity data. We demonstrated StrB method resilience to biases in binding data using a case study on HBV vaccine design. These findings emphasize the capacity of structure-based methods to enhance generalizability and efficiently use limited data, bearing implications for data-intensive fields like T-cell receptor specificity predictions.

Introduction

T cell discrimination between self and non-self relies on T cell receptor (TCR) recognition of peptides presented by Major Histocompatibility Complex (MHC) molecules. Accurate identification of peptides presented by MHC on the cell surface is pivotal for understanding autoimmune diseases[3], transplant rejection[4], and formulating effective strategies for cancer immunotherapy[5–7]. With over 14,000 human MHC-I proteins[8] encoded by HLA-A, HLA-B, and HLA-C genes, the theoretical 20^9 9-residue peptides (called 9-mers) create impractical *in vitro* testing scenarios. This calls for the development of in silico peptide-MHC (pMHC) binding prediction methods.

Much effort has been devoted to design predictors for pMHC binding[9]. Most state-of-the-art (SOTA) predictors are sequence-based machine learning methods[10–12] trained on a large amount of experimental binding data for pMHC (~600K for MHC-I[11] and >480K for MHC-II[10]). Sequence-based (SeqB) methods take amino acid sequences as input to predict binding affinity (BA) or eluted ligand rank. In addition to this, NetMHCpan uses a structure-derived concept like the MHC pseudosequence[13], which consists of using only the MHC residues observed to interact with the peptide in X-ray structures instead of the whole MHC sequence. MHCflurry 2.0 adds to the MHC-I binding prediction an antigen processing model, integrating both scores in its final MHC presentation

predictor. These methods are reported to perform well on most of 214 well-studied alleles with hundreds of thousands of mass spectrometry data.

While these approaches have shown considerable advancement and contributed to numerous clinical trials[14,15], they are not without limitations. A notable constraint stems from their reliance on extensive data, posing challenges for the thousands of less-explored HLA alleles with limited available binding information. Moreover, redundancy reduction strategies, such as the removal of identical peptides or using independent test sets[11,12,16], are not designed to ensure that the test data do not resemble the training data, thereby possibly leading to an overly optimistic performance. Finally, these methods typically train and test on a small subset of MHC alleles, which is minimal considering the broad spectrum of human alleles. Consequently, predictions for underrepresented alleles in these sets may exhibit lower accuracy, akin to an out-of-distribution (OOD) issue in machine learning, where real-case scenarios differ significantly from training data, posing challenges in generalization[17–19].

While SeqB methods have become the standard for pMHC BA prediction, structure-based (StrB) methods have the potential to provide more reliable predictions with better generalizability[20]. A StrB has several compelling advantages as it can 1) integrate the huge amount of experimental pMHC binding affinity data with physico-chemical properties of 3D interfaces, 2) reflect minor changes of mutations in 3D space and energy landscape, 3) naturally handle variable peptide lengths in 3D space. The booming advances of geometric deep learning (GDL)[21–24], a specialized branch tailored for 3D objects, underscores the timely opportunity for enhancing pMHC binding affinity predictions by the development of StrB methods. Importantly, the highly conserved MHC structures observed across various species, together with the constrained peptide binding within the MHC binding groove, establish a foundation for constructing accurate pMHC 3D models[25,26]. These models, in turn, serve as reliable input data for GDL algorithms.

Much efforts have been devoted to design StrB methods for predicting MHC-binding peptides with different degrees of success in the past decades[20]. Typically, energy terms, statistical potentials and structural descriptors (e.g., the number of polar-polar interactions) are used as input of machine learning algorithms (see review[20]). These methods were limited by the number of experimental pMHC structures in the PDB databank[27]. Recently, much advances in pMHC 3D modelling have been achieved[25,26,28]. Notably, our PANDORA software enables reliably modelling of pMHC within a few minutes minutes per CPU core, with an accuracy of 0.82 and 1.11 Å in backbone RMSD (root mean squared deviation) for pMHC-I and -II, respectively[25,29]. A recent StrB approach for pMHC binding prediction which exploited a similar modelling approach is 3pHLA[30]. Based on 77,000 3D models generated with APE-Gen[26], the authors used Rosetta[31] to extrapolate energy scores at each of the peptide's positions and provided these scores as vectors to train a random-forest predictor. However, condensing all structural features into a singular energy score is likely to result in the loss of crucial structural signals, such as local favorable interactions, clashes, and long-distance interactions. This promotes us to develop end-to-end GDL methods that directly work on structural features at atom or residue level to predict the binding between peptide and MHC. Moreover, recently Wilson et al.[32] have developed a StrB binding motif prediction method, for which they trained inception convolutional neural networks (CNN) on electrostatic potentials of MHC structures on experimental binding motifs, demonstrating high prediction speed and precision. MHCfold predicts pMHC 3D structures and the interactions at the same time and achieved impressive results in both tasks[33].

In this study, we designed and evaluated three different StrB approaches, characterized by different data resolution, features and algorithm designs. We implemented three different GDL algorithms: 3D

Convolutional Neural Networks (3D-CNN), graph networks (GNN), equivariant grant networks (EGNN). When dealing with 3D structures, it is imperative for a GDL algorithm to exhibit rotation-translation (RT) invariance, ensuring that the network's predictions remain constant irrespective of the orientation and origin of the input structure. 3D-CNNs analyze structural features that are mapped on a 3D grid, capturing local geometric relationships effectively. While they maintain translation equivariance, they're sensitive to input rotation, which can cause issues when the inputs do not share a common orientation. Despite this, by augmenting data with random rotations, 3D-CNNs perform well on different structure-based tasks[21,34]. GNNs treat structures as connected nodes (representing atoms and/or residues) on a graph, updating the features of a node iteratively through passing information of its neighboring nodes[35]. Such message passing GNNs can leverage geometric information, to make them structure-aware, by conditioning messages[36] on pairwise geometric attributes[24]. When conditioned on pairwise distances, the network is guaranteed to be RT-invariant, i.e., the output of the network will be constant even if the input rotates and translates. The Equivariant GNNs (EGNNs) as proposed by Satorras et al.[22] falls in this class of GNNs[24], but further enhances its networks by enabling position updates of the atoms by an equivariant mechanism, where equivariant means that if the input graph rotates, the output and all of its features consistently rotate as well. EGNN's simplicity and effectiveness in RT-equivariant applications make it widely used for predicting molecule properties and generating realistic small molecules[22,24].

Here, we evaluate whether our GDL-based StrB methods can have a more robust generalization than SeqB methods for pMHC binding predictions. For this, we boosted 100K binding affinity data with pMHC 3D models. We compared three different GDL StrB networks with two SeqB networks on an allele-clustered scenario, minimizing the similarity between the test data and the training data. By comparing these performances with those on a shuffled data set, we evaluated the accuracy drop when generalizing to unseen cases. In addition, being inspired by the success of the self-supervised learning (SSL) in natural language processing[37,38], we also designed a novel self-supervised GDL method, 3D-SSL, trained on ~1200 X-ray structures without exposure to any binding affinity data, which demonstrated superior potential of data efficiency. Finally, we demonstrate the robustness of StrB methods to biases in the binding data on a study-case on HBV vaccine.

Results

Data separations using allele clustering

We set out to test the generalization power of StrB over SeqB approaches to unseen data through two different data splitting configurations of the same binding affinity dataset[11]: a randomly shuffled one, resembling SOTA-used datasets, and an allele-clustered one. The allele-clustered data configuration was designed to test the applicability of the neural networks to a test set composed of unseen data, the distribution of which might deviate significantly from the training data (e.g. patients with rare alleles).

In the shuffled configuration, we randomly split the data in training, validation and test sets, using target stratification to ensure similar target distribution in all data sets (**Fig. 1A**). This configuration is similar to what is usually done in the existing literature, where the test set is either randomly extracted from the starting dataset or is an independent dataset with similar alleles and peptides distributions[11,16]. In the second experiment (allele-clustered), we clustered the data based on the MHC pseudosequence[13] using a PAM30-based[39] hierarchical clustering for each gene, i.e., HLA-A, -B and -C, respectively (**Fig. 1B-D**, see also Methods). Then from a total of ~100K binding affinity data (see details in Methods), for each gene we selected the most distant clusters based on the MHC pseudosequence's dendrogram so that about 10% of each gene's data (10% for HLA-A, 11% for -B

and 12% for -C, respectively) was selected as a test set. We shuffled and split the remaining data into training and validation sets in a target-stratified manner. This design allows the networks to sample a large number of cases from each HLA gene, while strategically incorporating distant clusters of alleles into the test data. This configuration aims at simulating real-case scenarios in which the network has to provide a prediction on alleles it has never seen or seen infrequently. We build 3D models for all these binding affinity data using PANDORA[29], which served as input of our GDL approaches (**Figure 1E**).

Figure 1. Data overview. A) Shuffled data distribution representation between HLA-A, -B and -C for the training and test sets. B-D) show the hierarchical clustering of HLA-A, -B, -C pseudosequences, respectively, with training data in black and test data in red. In all panels, the mustard/teal bar by each gene label represents the binders/non-binders (positive/negative) ratio for the gene. E) Data enrichment through 3D modeling. We used PANDORA[29] to generate 20 3D models of each of the 100 178 pMHC datapoints, thus enriching the sequence information with physics-derived informations, such as geometry and physico-chemical features.

StrB predictors demonstrate greater generalizability than SeqB on distant alleles

For StrB predictors we used architectures with various E(3)-equivariance properties and with various types of physico-chemical features (**Fig. 2A**). We developed an atom-level 3D-CNN and a residue-level GNN using different structural and energy-related features (**Tables 1** and **2**), and a residue-level EGNN using as input features only the residues identities and their XYZ coordinates (**Table 3**). Since many SOTA SeqB predictors are not available to be re-trained for a fair comparison, we developed a Multi-Layer Perceptron (MLP) to represent a baseline sequence-based approach. We also re-trained MHCflurry2.0, being a SOTA architecture available for re-training (see Methods).

Figure 2. Our supervised StrB methods overview and performances. A) Overview of the pipeline employed for processing pMHC complexes and running the supervised structure-based networks. The process involves: 1) Identifying interface atoms and residues from the pMHC 3D models, 2) converting each pMHC interface into volumetric grids and graphs enriched with geometric and physico-chemical information (**Tables 1-3**), 3) Run the networks on these representations: volumetric grids for the CNN and graphs for GNN and EGNN. GNN and EGNN use similar graph topology, differing on features and message passing framework (see details in Methods). B-C) The performance of StrB and SeqB methods on the shuffled test dataset and on the allele-clustered test dataset, respectively. D) AUC per allele on the allele-clustered test set. Allele name and number of test cases are reported on the x-axis, and the alleles are sorted by sequence distance with the training set. The black dashed line marks the random predictor AUC value of 0.5.

As expected, in the shuffled data configuration, all methods perform well (**Fig. 2B**), with the MLP and our EGNN showing a slight edge, with Area under the ROC Curve (AUC) of 0.91 and 0.87 (see AUCPR details in **Suppl. Fig. 1**), respectively. The shuffled data configuration resembles the commonly used scenario in the existing literature, where the test set features distributions do not necessarily deviate from the training set ones. In these scenarios, SeqB methods learn that the features distribution can provide good predictions, as suggested from their higher performance shown in **Fig. 2B**. StrB methods' high performance suggests their potential in reaching performance comparable to the current SeqB literature.

In the allele-clustered configuration (**Fig. 2C**), all predictors consistently show a decline in performance, while StrB consistently outperforms SeqB by 5-11% in terms of AUC. The substantial performance drop of SeqB methods underscores their susceptibility to the out-of-distribution issue, highlighting the importance of rigorous evaluation for obtaining real-life estimations of predictive methods. EGNN, our simplest GDL method and the top-performing StrB, achieves a significantly better AUC and AUCPR compared to SeqB methods by 8-11% in AUC. Specifically, EGNN achieves an AUC of 0.73 and an AUCPR of 0.64, surpassing the best performing SeqB method MHCFlurry's performance of 0.65 AUC and 0.56 AUCPR. MHCFlurry is an ensemble predictor using multiple neural networks, demonstrating better generalization than a basic MLP. **Fig. 2D** shows the performances on each test allele ordered with increasing distance to the training alleles. StrB approaches demonstrated more robust performance than SeqB methods on distant alleles.

Regarding the computational costs of our three StrB approaches, the GNN architecture demonstrated results comparable to CNN in terms of performance metrics, but has clear computational efficiency advantages: performance maintained with a coarser-grained resolution (residue-level graphs vs. atomic-level grids), faster featurization and data mapping, and lower storage requirements. Notably, the EGNN showed the best predictive power, and with even faster data mapping and featurization and lower storage requirement (**Table 4**).

Table 4. Computational costs of our StrB supervised methods. Our EGNN showed the best prediction performance, with fastest data mapping and featurization and lowest storage requirement.

	featurization and data mapping on one CPU core/pMHC model	hard-drive storage/pMHC model
3D-CNN	3.2$\pm$0.1s	744$\pm$17 KB
GNN	6.2$\pm$0.1s	5.6$\pm$0.2 MB
EGNN	0.07$\pm$0.02 s	3.9$\pm$0.1 KB

Self-supervised learning demonstrates superior data efficiency

Self-supervised learning is a game-changing technique for natural language processing[37,38]. Many well-known architects, including BERT[37], GPT-X[38], MAEs (Masked Autoencoders)[40] are SSL at their core. Unlike supervised binding affinity prediction, where a network is trained to directly predict a target value (a binding label, in our case), in SSL we mask or noise part of the data, and task the network with unmasking/denoising the input. Because of this self-prediction nature, SSL is potentially data efficient. Here we extend SSL to 3D and evaluate its performance on pMHC binding predictions.

Training. Our 3D-SSL method is trained on a masked residue prediction (MRP) task (**Suppl. Fig. 2**). At training time, 20% of the residues in the pMHC complex is masked, i.e. set to a dedicated 'unknown' token. An EGNN is trained to predict the residue types of the masked nodes. In essence, the MRP pushes the network to learn which residues are likely to be found in a given environment, effectively learning a multi-body statistical potential[41–43]. For proof-of-concept, our 3D-SSL is currently trained only on 1,245 X-ray structures from TCRpMHC complexes (**Fig. 3C,** Methods).

Inference. Once the network has been trained on X-ray structures, we use it to predict the peptide binding of our test allele-clustered dataset. The trained network takes a pMHC 3D model as input, masks each peptide residue and predicts the probability of the 20 amino acid types at the masked position. We convert the probabilities into energy using Boltzmann distributions. The 3D-SSL score is a sum of individual peptide residue contributions to the binding (**Fig. 3A,** Methods). We used this final score as a label for the binding affinity.

Figure 3. Self-Supervised learning approach (3D-SSL) overview and performances. A) the inference stage of 3D-SSL. 3D-SSL is an EGNN network. It takes the microenvironment of a masked peptide residue as input, predicts the probability of amino acid identities of the masked residue, then converts the probability into statistical potential using Boltzmann distribution as the energy contribution of this microenvironment. For the training stage of 3D-SSL, see **Suppl. Fig. 2**. B) Comparison of 3D-SSL (i.e., unsupervised EGNN) with the same EGNN network trained in a supervised manner and with

3D-SSL, not being exposed to the binding affinity values, on the allele-clustered dataset already already outperformed the SeqB supervised methods trained on 90,160 binding affinity data, with AUC of 0.67 vs. 0.62-0.65 (**Fig. 3B**). This result shows the superior data efficiency potential of SSL networks in this field. As a comparison, the same EGNN architecture trained in a supervised way achieves an AUC of 0.73, confirming the commonly observed results that SSL learning networks tend to perform less well than supervised learning trained on specific tasks in natural language processing (NLP).

Interestingly, we noticed that including peptide-TCR structures in the training set of 3D-SSL improved the prediction for pMHC binding affinity. We have tested two different training sets for 3D-SSL: one including only pMHC structures and one including also peptide-TCR (T-Cell Receptor) structures, extracted from full TCR-peptide-MHC X-ray complexes. We found out that the larger dataset including peptide-TCR structures provided higher binding affinity prediction performance, from AUC of 0.64 to 0.67 (**Fig. 3C**). The improved results with peptide-TCR data might indicate that adding competing binding environments contributes to the prediction of the binding affinity between peptide and MHC.

A case study: Vaccine for chronic Hepatitis B virus (HBV) infections

We finally compared one of our StrB methods, GNN, to two SOTA softwares on a real-case scenario: an HBV vaccine design study[44]. In this study, HLA-A*02:01 matched dendritic cells (DCs) from healthy donors were exposed to synthetic long peptides containing HBV sequences in order to test which peptides would be presented, therefore possible effective vaccine candidates (**Fig. 4A**). Notably, two closely related peptides (HLYSHPIIL, denoted as HL, and HLYSHPIIL**G**, denoted as HG, differing only in an additional C-terminal glycine in HG) are experimentally confirmed as binders through mass spectrometry and in vitro binding assays[44]. However, only HL is predicted as a binder by NetMHCpan4.1b web server and the BA predictor of MHCflurry 2.0's official release (**Fig. 4B**). The HL peptide has been reported numerous times in literature as an HLA-A02 binder[45–47], thus it is likely in the training set of NetMHCpan4.1 and MHCflurry 2.0. We went on to check whether our StrB methods can identify the HG peptide as a binder. We first generated 3D models of the pMHC complex between the HG peptide and HLA-A*0201, then use our trained GNN network to make predictions. Our GNN is able to predict both peptides as binders with high confidence scores (**Fig. 4B**).

The HG/HL case in fact is a relatively easy case for structure-based approaches after we inspect their 3D models. As apparent from the 3D models, the C-terminal glycine is overhanging without causing major unfavorable interactions nor clash (**Fig. 4C**, see also **Suppl. Video 1**). The HL peptide can form a weak salt bridge with MHC LYS146 using its C-terminal carboxyl group. Adding the glycine causes a bigger entropic effect (i.e. the glycine has to reduce its entropy to fit in the pocket), which can be balanced by the interactions of the glycine's carboxyl group, taking another weak salt bridge with LYS146 and an extra Hydrogen bond with THR80. Overall, this result indicates that structural modeling adds important biochemical environment to assist structure-based AI to generalize the unseen HG peptide.

It is critical to emphasize that the biases in SeqB networks might result from training data with potential bias. In fact, the proteasome has a low probability of cleaving the C-terminal bond of a glycine[48]. As a result, C-terminal glycines are poorly represented in their training set, likely causing the poor performance of SeqB methods on peptides with C-terminal glycines. MHCflurry 2.0 addresses similar challenges with its antigen preprocessing (AP) module[11], which filters out peptides not supposed to be processed by non-APC cells, such as peptides containing C-terminal glycines. However, this does not justify the inaccuracies in their BA predictor, which should be able to predict these peptides as binders when presented with them. Overall, the robustness of the StrB GNN might prove effective against other issues caused by the biases that SeqB networks inherit from the data, such as the low accuracy in predicting MHC binding of cysteine-containing peptides, caused by underrepresentation of cysteines in the MS-derived immunopeptidomes used for training.

Figure 4. Case study on two peptides in HBV vaccine research. A) HBV case study experiment. Sequences isolated from HBV have been used to synthesize SLPs. The SLPs were then added to DCs cultures from 8 healthy donors. Samples were then analyzed through LC-MS/MS, leading to the identification of peptides presented on the surface of DCs. The peptides were then fed into NetMHCpan4.1b, MHCflurry2.0 BA and our StrB GNN. Only our GNN successfully identified both peptides as binders. B) Outputs and cutoffs from predictors tested. The GNN here is trained on the whole ~100K binding affinity data. C-D) Structural models for HLYSHPIILG (green) and HLYSHPIIL (cyan). Expected polar interactions and hydrogen bonds are shown as yellow dashed lines. Structural models are generated by PANDORA[29]. Visualizations are done in PYMOL[49].

Discussion

Generalizability is an important topic in a broad range of studies[50–52]. In this proof-of-concept study, we investigated the generalizability of various StrB approaches in predicting pMHC interactions, a pivotal aspect of immune surveillance and a major bottleneck in the design of cancer vaccines[5–7] and TCR therapies[53,54]. We showed that our StrB networks, especially EGNN, have greater generalization power compared to conventionally used SeqB networks when evaluated on unseen MHC alleles. Importantly, our self-supervised approach, 3D-SSL already outperforms sequence-based approaches

trained on ~90 times more data, demonstrating the potential data efficiency of 3D-SSL. The presented HBV test case, although not representing an extensive comparison of SeqB and StrB neural networks biases, exemplifies how StrB methods better capture the biochemical environment of the pMHC complex, potentially minimizing non-biochemical biases in the data.

We demonstrate the efficiency and feasibility of boosting experimental BA data with physics-derived pMHC 3D models to achieve better predictions of MHC-bound peptides. The inherent conservation of MHC structures makes physics modeling feasible. These models offer essential complementary information to biochemical binding assays, aiding in training highly generalizable algorithms for the identification of MHC-bound peptides. We anticipate that the fusion of 3D modeling with the expanding capabilities of geometric deep learning will soon provide robust and valuable tools for prioritizing targets in cancer immunotherapies, thereby accelerating development timelines and significantly reducing associated costs.

The extensive diversity of MHC-bound peptides, along with the continuously expanding wealth of experimental binding data, and the availability of our 3D models, are expected to draw the interest of AI researchers, particularly those in the geometric deep learning field. This convergence can inspire the development of innovative algorithms, offering fresh solutions and insights to both the AI and immunology communities. For example, we are actively employing generative AI to generate pMHC 3D models, replacing our physics modeling step (which typically takes around 5 minutes per pMHC), accomplishing the task within a fraction of a second (manuscript under preparation).

While our study is on pMHC-I, our StrB methods are directly applicable to pMHC-II complexes, which play a pivotal role in cancer immunotherapy responses[55,56] but their BA is challenging to predict. StrB methods can naturally handle peptide length variability in 3D space while SeqB methods are inherently limited as they take fixed length input. All together, our StrB approaches, especially, our 3D-SSL approach, may provide a data efficiency solution for data hungry fields, for example, the long-standing challenge of TCR specificity predictions. Expanding the 3D-SSL information source to the Protein Data Bank[27] structures and AlphaFold2[23,57] models and integrating supervised methods with our 3D-SSL are potential next steps.

Methods

Binding affinity data collection

BA data was collected from O'Donnel *et al.*[11] through MHCflurry 2.0 ```download-fetch``` command, which yielded a total of 598,450 pMHC binding affinity measurements. We selected only qualitative essays on human alleles and filtered out data points considered non-exact values (i.e. samples assigned to have a value lower or higher than a certain threshold, with no exact value associated). The final dataset consists of 100,178 data points each containing a peptide sequence, an MHC allele name and their measured BA, using a threshold of 500 nM to separate binders from non-binders, resulting in 44,102 binders and 56,076 non-binders from 110 HLA alleles (see **Fig. 1** and Data & Code Availability).

3D modeling with PANDORA

The BA dataset was processed with PANDORA (v2.0beta2) software[29] to generate 3D models of the pMHC complexes for these binding affinity data. For every case, PANDORA uses NetMHCpan4.1[10] to predict the binding core, thus assigning the anchor residues to restraint. The 3D models were

generated with PANDORA's default mode (i.e., 20 3D models per case, no restraints flexibility added), with the exception that only the G-domain of the MHC is modeled, while the rest of the chain and the beta-2 microglobulin are ignored. The top molpdf[58] scored model was selected as best model and used as the training, validation and test data.

Data clusterings

In the shuffled data configuration, we split the data into training (90%) and test (10%) sets after random shuffling, stratifying them on the binary target to make sure the positive and negative cases are equally represented in the different sets. During the training phase, 15% of the training set was used as a validation set.

For the allele clustering, allele pseudosequences were collected from O'Donnel et al.[11]. As explained in Hoof et al.[13], these pseudosequences only contain the residues at the MHC positions that have been shown in X-ray structures to interact with the peptide, which makes it so every pseudosequence has the same length and no alignment is needed, as every position correspond to the same physical position on the MHC structure. The pseudosequence were separated per gene and scored against each other using a BLOSUM62 scoring matrix, and the so-obtained evolutionary distances were used to build a hierarchical clustering using the cluster.hierarchy module from scipy[59] for each HLA gene. From these three clusterings (one per gene), we selected the most distant clusters until reaching the closest possible value to 10% of the data (10% for HLA-A, 11% for HLA-B and 12% for HLA-C) to form the test set. All the other data points were left as a train/validation set.

Training data for 3D-SSL

We extracted 1245 entries by overlapping PDB IDs containing MHCI from ProtCID with the protein-peptide database Propedia[60]. These Propedia entries are composed of 517 pMHC and 731 TCRα-peptide or TCRβ-peptide structures, separated out from the original PDB structures. We consider two SSL datasets from these entries. First, a reduced dataset of 517 only pMHC structures, and all the extracted entries for the second one. This corresponds to two SSL training scenarios, one where the network sees only pMHC structures, and another where it also sees TCR$\alpha/\square$-peptide structures (**Fig. 3C**).

3D-CNN

3D-CNNs are translation invariant but not rotation equivariant. For this reason, we decided to align all the pMHC 3D models to prevent any rotation issue and avoid resorting to data augmentation. In order to generate consistent 3D grids for each 3D model, all the selected 3D models were aligned using GradPose[61]. The principal component analysis (PCA) of the peptides coordinates was then calculated and the X, Y and Z axis of each PDB file were translated to match with the three principal components, to make sure the axis of the grid would sit along the axis of biggest variation in the peptides' backbone.

For the grids featurization, the PDB files of the aligned pMHC 3D models were then processed with DeepRank software[62] to generate 3D grids as described in Renaud et al.[21]. Each grid was set to have a shape of 35x30x30 Å and a resolution of 1 Å. Only residues of each chain within 8.5Å from the other chain are considered "interface" residues and kept for feature calculation. Features were then generated for each atom position and mapped to the grid points with a Gaussian mapping as described in Renaud et al.[21]. In addition to DeepRank's default features, we added an Energy of Desolvation feature calculated as in Domungiez et al.[1], as the difference in the solvation energy between the bound and unbound complex. We have also replaced DeepRank's default PSSM feature used for sequence

embedding with the lighter skip-gram residue embedding taken from Phloyphisut *et al.*[63]. All the features used are summarized in **Table 1**. The network architecture is described in detail in the **Supplementary Note 2**.

Table 1. Input features to the CNN architecture. Full features details on built-in deeprank features can be found on https://deeprank.readthedocs.io/en/latest/deeprank.features.html.

Feature & Shape & Type	Description
SkipGram [6, 1], float	Skip-Gram embedding for residue type
Edesolv [1], float	Desolvation energy, calculated as in Dominguez *et al.*[1]
Anchor [1], bool	Label to indicate if the residue is an anchor residue (peptide side) or a pocket residue (MHC side)
RCD_apolar-apolar [1], float	Residue Contact Density for apolar-apolar interactions calculated as in Vangone and Bonvin[2]
RCD_apolar-charged [1], float	Residue Contact Density for apolar-charged interactions calculated as in Vangone and Bonvin[2]
RCD_charged-charged [1], float	Residue Contact Density for charged-charged interactions calculated as in Vangone and Bonvin[2]
RCD_polar-apolar [1], float	Residue Contact Density forpolar-apolar interactions calculated as in Vangone and Bonvin[2]
RCD_polar-charged [1], float	Residue Contact Density for polar-charged interactions calculated as in Vangone and Bonvin[2]
RCD_polar-polar [1], float	Residue Contact Density for polar-polar interactions calculated as in Vangone and Bonvin[2]
RCD_total [1], float	Residue Contact Density for total interactions calculated as in Vangone and Bonvin[2]
bsa [1], float	Buried Surface Area
charge [1], float	Charge based on the OPLS force field implemented in HADDOCK[1]
coulomb [1], float	Electrostatics based on the OPLS force field implemented in HADDOCK[1]
vdwaals [1], float	Van Der Waals energy based on the OPLS force field implemented in HADDOCK[1]

GNN

The PDB files were converted into protein-protein interfaces (PPI) in the form of residue-level graphs using DeepRank2 package[64,65]. The latter is a Python package inherited from our previous package DeepRank[62] and that offers a complete framework to learn PPI interface patterns in an end-to-end fashion using GNNs. For a given PDB file representing a pMHC complex, we defined the interface graph as all the residues involved in intermolecular contacts, i.e. the residues of a given chain having a heavy atom within an 15 Å distance cutoff of any heavy atom from the other chain. These contact residues formed the nodes of the graph. Edges were defined between two contact residues from distinct chains presenting a minimal atomic distance smaller than 15 Å. Node and edge residue-level features used are summarized in **Table 2**. The network architecture is described in detail in the **Supplementary Note 2**.

Table 2. Input features to the GNN architecture. Full features details can be found on https://deeprank2.readthedocs.io/en/latest/features.html.

Feature & Shape & Type	Description
NODE FEATURES	
res_type [21, 1], bool	One-hot representation of the node's residue (20 amino acids + unknown).
res_size [1], int	The number of non-hydrogen atoms in the side chain.
res_mass [1], float	The average residue mass in Da.
res_charge [1], int	The charge of the residue in fully protonated state in Coulomb.
res_pI [1], float	The isoelectric point, i.e., the pH at which the molecule has no net electric charge.
polarity [4, 1], bool	One-hot representation of the polarity of the amino acid: NONPOLAR, POLAR, NEGATIVE, POSITIVE.
hb_donors [1], int	The number of hydrogen bond donor atoms in the residue.
hb_acceptors [1], int	The number of hydrogen bond acceptor atoms in the residue.
res_depth [1], float	The average distance in Å of the residue to the closest molecule of bulk water, computed via BioPython.
hse [3, 1], float	Half sphere exposure, which indicates how buried an amino acid residue is in the biomolecule, computed via BioPython.

sasa [1], float	Solvent-accessible surface area, in Å^2, computed via FreeSASA.
bsa [1], float	Buried surface area, which represents the area of the complex interface, in Å^2, computed via FreeSASA.
irc_total [1], int	The number of residues on the other chain that are within a cutoff distance of 5.5 Å.
irc_negative_negative irc_negative_positive, irc_nonpolar_negative, irc_nonpolar_nonpolar, irc_nonpolar_polar, irc_nonpolar_positive, irc_polar_negative, irc_polar_polar, irc_polar_positive, irc_positive_positive [1], int	As above, but for specific residue polarity pairings.

EDGE FEATURES

same_chain [1], bool	Boolean indicating whether the edge connects nodes belonging to the same chain (1) or separate chains (0).
covalent [1], bool	Boolean indicating whether nodes are covalently bound (1) or not (0). Covalency is not directly assessed, but any edge with a maximum distance of 2.1 Å is considered covalent.
electrostatic [1], float	Electrostatic potential (also known as Coulomb potential) between two nodes, calculated using interatomic distances and charges of each atom.
vanderwaals [1], float	Van der Waals potential (also known as Lennard-Jones potential) between two nodes, calculated using interatomic distances and a list of atoms with Van der Waals parameters.
distance [1], float	Interatomic distance between atoms in Å, computed from the xyz atomic coordinates taken from the PDB file.

EGNN

The PDB files were converted into protein-protein interfaces (PPI) in the form of residue-level graphs. For a given PDB file representing a pMHC complex, we defined the interface graph as all the residues which carbon α atoms fall within a 10 Å radius of any peptide's residue carbon α. The only features that were used for residues are the residue type, coordinates, and a binary label representing whether the residue comes from the peptide or the MHC. Edges were defined using a k-nearest neighbors (KNN) procedure, where a node is connected to 10 of its closest neighbors. A binary edge attribute distinguishes between cross-chain edges and inter-chain edges. Node and edge features used are summarized in **Table 3**. The EGNN network is trained in a supervised manner and a self-supervised manner (i.e., 3D-SSL). The details are described in **Supplementary Note 2**.

Table 3. Input features to the EGNN architecture.

Feature & Shape & Type	Description
NODE FEATURES	
res_type [1], int	Index of node residue type.
pos [3], float	The xyz coordinates of the residue C-alpha.
entity [1], bool	Boolean indicating whether the node is the peptide (1) or the protein (0). Used for pooling.
EDGE FEATURES	
same_chain [1], bool	Boolean indicating whether the edge connects nodes belonging to the same chain (1) or separate chains (0).

Sequence-based methods

The original script from the MHCFlurry 2.0 work[11] was used to build a combined ensemble made of several neural networks. For each data configuration, the only parameters modified from the MHCflurry 2.0 script were the data input and output paths. The original script is available on https://github.com/openvax/mhcflurry/blob/master/downloads-generation/models_class1_pan/GENERATE.sh. For further details see **Supplementary Note 3**.

The MLP we used consists of a simple architecture built using PyTorch 2.13 and it is described in detail in **Supplementary Note 3**.

HBV case study

Immunopeptidomic data was obtained by LC-MS/MS as described in Kessler *et al.*[44]. In short, monocyte-derived dendritic cells (moDCs) from 8 healthy donors were pulsed with 12 prototype hepatitis B virus (HBV) synthetic long peptides (SLPs) in combination with a maturation stimulus for 22 hours. HLA-I-peptide complexes were immunoprecipitated and subjected to data-dependent acquisition LC-MS/MS analysis. Data was analyzed in PEAKS, FDR5. Obtained spectra from cross-presented, SLP-derived peptides were manually validated by two MS experts. For the values reported in **Fig. 4B**, NetMHCpan 4.1b from the web server[10] and MHCflurry2.0 locally installed[11] where used to predict the peptides' binding to HLA-A*02:01 with default options.

Data & Code Availability

Datasets and the trained networks are available in zenodo upon acceptance. The code for data generation, featurization and training is available at https://github.com/DeepRank/3D-Vac.

Authors Contribution

(Dario F. Marzella[†], Giulia Crocioni[†], Tadija Radusinović, Daniil Lepikhov, Heleen Severin, Dani L. Bodor, Daniel T. Rademaker, ChiaYu Lin, Sonja Georgievska, Nicolas Renaud, Amy L. Kessler, Pablo Lopez-Tarifa, Sonja Buschow, Erik Bekkers, Li C. Xue)

Conceived the study: LX, DFM. Prepared the data: DFM, DL, HS. 3D-CNN: DFM, HS. GNN: GC, CL. EGNN: TR. 3D-SSL: TR. MHCFlurry and MLP: DL, DFM. HBV data collection: ALK, SB. Project supervision and coordination: LX, EB. Manuscript writing and editing: DFM, GC, LX, SG, PL, DB, DL, ALK, SB, EB. Figures: DFM, GC, NR.

All authors read and contributed to the manuscript. Giulia and Dario agree that the order of their respective names may be changed for personal pursuits to best suit their own interests.

Acknowledgments

LX and DM are supported by the Hypatia Fellowship from Radboudumc (Rv819.52706), Hanarth Fond and the Kika grant (grant number 454). GC and SG are supported by the Netherlands eScience Center under grant number NLESC.OEC.2021.008. This work was also supported by the NVIDIA Academic Hardware Grant Program. We thank SurfSara for their generous GPU and CPU supercomputing grants (EINF-2380 and EINF-4578). We sincerely thank the funding through the AI-For-Health program at Radboudumc for H. Severin and D. Lepikov. We thank the Erasmus fellowship to D. Lepikov. We also thank Farzaneh Meimandi Parizi and Coos Baakman, the main developers of the preprocessing part of the DeepRank2 package, and Sven van der Burg, who helped with the refactoring and the maintenance of the package in the first phase of the project.

References

1. Dominguez, C., Boelens, R. & Bonvin, A. M. J. J. HADDOCK: A Protein–Protein Docking Approach Based on Biochemical or Biophysical Information. *J. Am. Chem. Soc.* **125**, 1731–1737 (2003).

2. Vangone, A. & Bonvin, A. M. Contacts-based prediction of binding affinity in protein–protein complexes. *eLife* **4**, e07454 (2015).

3. Sollid, L. M., Pos, W. & Wucherpfennig, K. W. Molecular mechanisms for contribution of MHC molecules to autoimmune diseases. *Curr. Opin. Immunol.* **31**, 24–30 (2014).

4. Benichou, G., Takizawa, P. A., Olson, C. A., McMillan, M. & Sercarz, E. E. Donor major histocompatibility complex (MHC) peptides are presented by recipient MHC molecules during graft rejection. *J. Exp. Med.* **175**, 305–308 (1992).

5. Kreiter, S., Castle, J. C., Türeci, Ö. & Sahin, U. Targeting the tumor mutanome for personalized vaccination therapy. *OncoImmunology* **1**, 768–769 (2012).

6. Castle, J. C. *et al.* Exploiting the Mutanome for Tumor Vaccination. *Cancer Res.* **72**, 1081–1091 (2012).

7. Carreno, B. M. *et al.* A dendritic cell vaccine increases the breadth and diversity of melanoma neoantigen-specific T cells. *Science* **348**, 803–808 (2015).

8. Robinson, J. *et al.* IPD-IMGT/HLA Database. *Nucleic Acids Res.* **48**, D948–D955 (2020).

9. Peters, B. *et al.* A Community Resource Benchmarking Predictions of Peptide Binding to MHC-I Molecules. *PLOS Comput. Biol.* **2**, e65 (2006).

10. Reynisson, B., Alvarez, B., Paul, S., Peters, B. & Nielsen, M. NetMHCpan-4.1 and NetMHCIIpan-4.0: improved predictions of MHC antigen presentation by concurrent motif deconvolution and integration of MS MHC eluted ligand data. *Nucleic Acids Res.* **48**, W449–W454 (2020).

11. O'Donnell, T. J., Rubinsteyn, A. & Laserson, U. MHCflurry 2.0: Improved Pan-Allele Prediction of MHC Class I-Presented Peptides by Incorporating Antigen Processing. *Cell Syst.* **11**, 42-48.e7 (2020).

12. Gfeller, D. *et al.* Improved predictions of antigen presentation and TCR recognition with MixMHCpred2.2 and PRIME2.0 reveal potent SARS-CoV-2 CD8+ T-cell epitopes. *Cell Syst.* **14**, 72-83.e5 (2023).

13. Hoof, I. *et al.* NetMHCpan, a method for MHC class I binding prediction beyond humans. *Immunogenetics* **61**, 1–13 (2009).

14. Ott, P. A. *et al.* An immunogenic personal neoantigen vaccine for patients with melanoma. *Nature* **547**, 217–221 (2017).

15. Sahin, U. *et al.* Personalized RNA mutanome vaccines mobilize poly-specific therapeutic immunity against cancer. *Nature* **547**, 222–226 (2017).

16. Jurtz, V. *et al.* NetMHCpan-4.0: Improved Peptide–MHC Class I Interaction Predictions Integrating Eluted Ligand and Peptide Binding Affinity Data. *J. Immunol.* **199**, 3360–3368 (2017).

17. *Dataset Shift in Machine Learning*. (MIT Press, Cambridge, Mass, 2009).

18. Yao, H. *et al.* Improving Out-of-Distribution Robustness via Selective Augmentation.

in *Proceedings of the 39th International Conference on Machine Learning* 25407–25437 (PMLR, 2022).

19.   Krueger, D. *et al.* Out-of-Distribution Generalization via Risk Extrapolation (REx). in *Proceedings of the 38th International Conference on Machine Learning* 5815–5826 (PMLR, 2021).

20.   Antunes, D. A., Abella, J. R., Devaurs, D., Rigo, M. M. & Kavraki, L. E. Structure-based Methods for Binding Mode and Binding Affinity Prediction for Peptide-MHC Complexes. *Curr. Top. Med. Chem.* **18**, 2239–2255 (2019).

21.   Renaud, N. *et al.* DeepRank: a deep learning framework for data mining 3D protein-protein interfaces. *Nat. Commun.* **12**, 7068 (2021).

22.   Satorras, V. G., Hoogeboom, E. & Welling, M. E(n) Equivariant Graph Neural Networks. Preprint at https://doi.org/10.48550/arXiv.2102.09844 (2022).

23.   Jumper, J. *et al.* Highly accurate protein structure prediction with AlphaFold. *Nature* **596**, 583–589 (2021).

24.   Bekkers, E. J., Vadgama, S., Hesselink, R. D., van der Linden, P. A. & Romero, D. W. Fast, Expressive SE(n) Equivariant Networks through Weight-Sharing in Position-Orientation Space. Preprint at https://doi.org/10.48550/arXiv.2310.02970 (2023).

25.   Marzella, D. F. *et al.* PANDORA: A Fast, Anchor-Restrained Modelling Protocol for Peptide: MHC Complexes. *Front. Immunol.* **13**, 878762 (2022).

26.   Abella, J., Antunes, D., Clementi, C. & Kavraki, L. APE-Gen: A Fast Method for Generating Ensembles of Bound Peptide-MHC Conformations. *Molecules* **24**, 881 (2019).

27.   Berman, H. M. The Protein Data Bank. *Nucleic Acids Res.* **28**, 235–242 (2000).

28.   Mikhaylov, V. & Levine, A. J. Accurate modeling of peptide-MHC structures with AlphaFold. *bioRxiv* 2023.03.06.531396 (2023) doi:10.1101/2023.03.06.531396.

29.   Parizi, F. M. *et al.* PANDORA v2.0: Benchmarking peptide-MHC II models and software improvements. *Front. Immunol.* **14**, (2023).

30.   Conev, A., Devaurs, D., Rigo, M. M., Antunes, D. A. & Kavraki, L. E. 3pHLA-score improves structure-based peptide-HLA binding affinity prediction. *Sci. Rep.* **12**, 10749

(2022).

31. Alford, R. F. *et al.* The Rosetta All-Atom Energy Function for Macromolecular Modeling and Design. *J. Chem. Theory Comput.* **13**, 3031–3048 (2017).

32. Wilson, E., Cava, J. K., Chowell, D., Anderson, K. S. & Singharoy, A. The Electrostatic Landscape of MHC-Peptide Binding Revealed Using Inception Networks. SSRN Scholarly Paper at https://doi.org/10.2139/ssrn.4436851 (2023).

33. Aronson, A., Hochner, T., Cohen, T. & Schneidman-Duhovny, D. *Structure Modeling and Specificity of Peptide-MHC Class I Interactions Using Geometric Deep Learning*. http://biorxiv.org/lookup/doi/10.1101/2022.12.15.520566 (2022) doi:10.1101/2022.12.15.520566.

34. Rezaei, M. A., Li, Y., Wu, D., Li, X. & Li, C. Deep Learning in Drug Design: Protein-Ligand Binding Affinity Prediction. *IEEE/ACM Trans. Comput. Biol. Bioinform.* **19**, 407–417 (2022).

35. Gilmer, J., Schoenholz, S. S., Riley, P. F., Vinyals, O. & Dahl, G. E. Neural Message Passing for Quantum Chemistry. Preprint at https://doi.org/10.48550/arXiv.1704.01212 (2017).

36. Koishekenov, Y. & Bekkers, E. J. An Exploration of Conditioning Methods in Graph Neural Networks. Preprint at https://doi.org/10.48550/arXiv.2305.01933 (2023).

37. Devlin, J., Chang, M.-W., Lee, K. & Toutanova, K. BERT: Pre-training of Deep Bidirectional Transformers for Language Understanding. Preprint at https://doi.org/10.48550/arXiv.1810.04805 (2019).

38. Brown, T. B. *et al.* Language Models are Few-Shot Learners. Preprint at https://doi.org/10.48550/arXiv.2005.14165 (2020).

39. Dayhoff, M. O., Schwartz, R. M. & Orcutt, B. C. A Model of Evolutionary Change in Proteins. in *Atlas of protein sequence and structure* (1978).

40. He, K. *et al.* Masked Autoencoders Are Scalable Vision Learners. Preprint at https://doi.org/10.48550/arXiv.2111.06377 (2021).

41. Miyazawa, S. & Jernigan, R. L. Estimation of effective interresidue contact energies

from protein crystal structures: quasi-chemical approximation. *Macromolecules* **18**, 534–552 (1985).

42.   Lazaridis, T. Effective energy functions for protein structure prediction. *Curr. Opin. Struct. Biol.* **10**, 139–145 (2000).

43.   Kozakov, D., Brenke, R., Comeau, S. R. & Vajda, S. PIPER: An FFT-based protein docking program with pairwise potentials. *Proteins Struct. Funct. Bioinforma.* **65**, 392–406 (2006).

44.   Kessler, A. L. & Buschow, S. Manuscript in preparation. (2023).

45.   Sette, A. *et al.* The relationship between class I binding affinity and immunogenicity of potential cytotoxic T cell epitopes. *J. Immunol. Baltim. Md 1950* **153**, 5586–5592 (1994).

46.   Ishizuka, J. *et al.* Quantitating T Cell Cross-Reactivity for Unrelated Peptide Antigens. *J. Immunol.* **183**, 4337–4345 (2009).

47.   Zheng, J. *et al.* Identification of novel hepatitis B virus therapeutic vaccine candidates derived from polymerase protein. *Aging* **13**, 14372–14384 (2021).

48.   Winter, M. B. *et al.* Immunoproteasome functions explained by divergence in cleavage specificity and regulation. *eLife* **6**, e27364.

49.   Schrödinger, LLC. The PyMOL Molecular Graphics System, Version 1.8. (2015).

50.   Zhang, C., Bengio, S., Hardt, M., Recht, B. & Vinyals, O. Understanding deep learning requires rethinking generalization. Preprint at https://doi.org/10.48550/arXiv.1611.03530 (2017).

51.   Chatterjee, A. *et al.* Improving the generalizability of protein-ligand binding predictions with AI-Bind. *Nat. Commun.* **14**, 1989 (2023).

52.   Arora, S., Ge, R., Liang, Y., Ma, T. & Zhang, Y. Generalization and Equilibrium in Generative Adversarial Nets (GANs). Preprint at https://doi.org/10.48550/arXiv.1703.00573 (2017).

53.   Campillo-Davo, D., Flumens, D. & Lion, E. The Quest for the Best: How TCR Affinity, Avidity, and Functional Avidity Affect TCR-Engineered T-Cell Antitumor Responses. *Cells*

9, 1720 (2020).

54.   Zhong, S. *et al.* T-cell receptor affinity and avidity defines antitumor response and autoimmunity in T-cell immunotherapy. *Proc. Natl. Acad. Sci. U. S. A.* **110**, 6973–6978 (2013).

55.   Alspach, E. *et al.* MHC-II neoantigens shape tumour immunity and response to immunotherapy. *Nature* **574**, 696–701 (2019).

56.   Kreiter, S. *et al.* Mutant MHC class II epitopes drive therapeutic immune responses to cancer. *Nature* **520**, 692–696 (2015).

57.   Varadi, M. *et al.* AlphaFold Protein Structure Database: massively expanding the structural coverage of protein-sequence space with high-accuracy models. *Nucleic Acids Res.* **50**, D439–D444 (2022).

58.   Shen, M. & Sali, A. Statistical potential for assessment and prediction of protein structures. *Protein Sci.* **15**, 2507–2524 (2006).

59.   Virtanen, P. *et al.* SciPy 1.0: fundamental algorithms for scientific computing in Python. *Nat. Methods* **17**, 261–272 (2020).

60.   Martins, P. M. *et al.* Propedia: a database for protein–peptide identification based on a hybrid clustering algorithm. *BMC Bioinformatics* **22**, 1 (2021).

61.   Rademaker, D. T., van Geemen, K. J. & Xue, L. C. GradPose: a very fast and memory-efficient gradient descent-based tool for superimposing millions of protein structures from computational simulations. *Bioinformatics* **39**, btad444 (2023).

62.   Renaud, N. *et al.* DeepRank/deeprank: 0.2.1. Zenodo https://doi.org/10.5281/ZENODO.5957173 (2022).

63.   Phloyphisut, P., Pornputtapong, N., Sriswasdi, S. & Chuangsuwanich, E. MHCSeqNet: a deep neural network model for universal MHC binding prediction. *BMC Bioinformatics* **20**, 270 (2019).

64.   Crocioni *et al.* Deeprank2. Zenodo https://doi.org/10.5281/ZENODO.8305000 (2023).

65.   Crocioni, G. *et al.* Deeprank GNN (tbd). Zenodo https://doi.org/10.5281/ZENODO.6772110 (2022).