scELMo: **E**mbeddings from **L**anguage **Mo**dels are Good Learners for **S**ingle-**c**ell Data Analysis

Tianyu Liu[1,2], Tianqi Chen[2†], Wangjie Zheng[2†], Xiao Luo[3], Hongyu Zhao[1,2*]

[1]Interdepartmental Program in Computational Biology & Bioinformatics, Yale University, New Haven, 06511, CT, USA.
[2]Department of Biostatistics, Yale University, New Haven, 06511, CT, USA.
[3]Department of Computer Science, University of California, Los Angeles, Los Angeles, 90095, CA, USA.

*Corresponding author(s). E-mail(s): hongyu.zhao@yale.edu;
Contributing authors: tianyu.liu@yale.edu; tianqi.chen.tc732@yale.edu;
wangjie.zheng@yale.edu; xiaoluo@cs.ucla.edu;
†These authors contributed equally to this work.

Abstract

Various Foundation Models (FMs) have been built based on the pre-training and fine-tuning framework to analyze single-cell data with different degrees of success. In this manuscript, we propose a method named scELMo (Single-cell Embedding from Language Models), to analyze single-cell data that utilizes Large Language Models (LLMs) as a generator for both the description of metadata information and the embeddings for such descriptions. We combine the embeddings from LLMs with the raw data under the zero-shot learning framework to further extend its function by using the fine-tuning framework to handle different tasks. We demonstrate that scELMo is capable of cell clustering, batch effect correction, and cell-type annotation without training a new model. Moreover, the fine-tuning framework of scELMo can help with more challenging tasks including in-silico treatment analysis or modeling perturbation. scELMo has a lighter structure and lower requirements for resources. Our method also outperforms recent large-scale FMs (such as scGPT [1], Geneformer [2]) and other LLM-based single-cell data analysis pipelines (such as GenePT [3] and GPTCelltype [4]) based on our evaluations, suggesting a promising path for developing domain-specific FMs.

Keywords: Single-Cell Data Analysis, Foundation Model, Large Language Model, In-silico Treatment Analysis, Perturbation Analysis.

1 Introduction

Developing foundation models (FMs) has become critical for broad areas including but not restricted to engineering and sciences [5–7], and large language models (LLMs) are examples of successful FMs. In biology, FMs have been developed to analyze DNA sequences [8, 9], represent cells and genes [1, 2, 10, 11], and perform other tasks. It has been shown that FMs can facilitate various downstream biological analyses. Here we focus on a specific type of biomedical tabular data, known as single-cell sequencing data [12, 13], for its intersection with FMs. Single-cell sequencing data can describe biological activity and information at the cell level. The units are individual cells, and the features can be gene expression levels [13], protein expression levels [14, 15], methylation levels [16], and others.

Several pre-training-based FMs have been developed to analyze single-cell data based on large-scale sequencing datasets collected from different studies. However, the developers of GenePT [3] discussed the limitation of only using the sequence information for biological analysis, and conjecture that we can either use the information from the National Center for Biotechnology Information (NCBI) [17] as prompts to get the embeddings of such prompts from LLMs to describe the genes (GenePT-w), or transfer cells to sentences by gene ranking and use the ranking results as a prompt to extract the cell embeddings from LLMs (GenePT-s). The results from GenePT can be further explored by incorporating pre-existing knowledge or literature of the features in single-cell datasets. However, GenePT has limited generation ability by relying on external knowledge from NCBI. Moreover, the NCBI database may not be informative enough to summarize the gene functions in a well-structured manner. On the other hand, using GenePT-s to generate cell embeddings is not very practical because of the high sparsity of single-cell data, so the genes with zero expression are hard to rank. GenePT-s is also not capable of handling large-scale datasets because of the usage and time limitation from OpenAI API [18]. GenePT also discussed the zero-shot learning ability of such embeddings. Recently, the access of LLMs including GPT 3.5 [19], GPT 4 [20], and LLaMa [21] offers us opportunities to explore the information of these features with the help of LLMs. These LLMs have been widely used to summarize knowledge [22], design network searching/models [23], and perform other tasks to enhance scientific research [24, 25].

In this manuscript, motivated by GenePT, we explore the ability of using LLMs in a different manner. We generate meaningful text descriptions of cell-level or feature-level metadata as well as embeddings of such descriptions based on LLMs. We assume that the embeddings from LLMs carry biological properties and can be utilized in various downstream applications. Here we introduce scELMo as a pipeline for analyzing single-cell multi-omic data based on the text description and embeddings directly from LLMs [26]. Using gene as one example, we use LLMs to summarize the functional information of a given gene with a suitable prompt and also use the same LLM to extract the

embeddings of such description. We then either incorporate the embeddings directly into the single-cell data by matrix operation or combine the embeddings with other models with fine-tuning targets for various challenging tasks. We demonstrate that scELMo is a simple but effective tool for single-cell data analysis under both the zero-shot learning framework and the fine-tuning framework based on comprehensive benchmarking analyses.

2 Results

Overview of scELMo. The embeddings from LLMs are powerful in preserving the context and information similarity of the original inputs [27–29], and thus they are good priors as a start for incorporating the biological knowledge from enriched text to analyze a specific dataset. Therefore, the high-level idea of scELMo is to transfer the information of each cell from the sequencing data space to the embedding space from LLM. We complete this transformation by incorporating information from the feature space (for example, genes and proteins.) or the cell space (for example, cell types or cell states). To transfer the feature information into the LLM embedded space, we can either use prior knowledge from a known database such as NCBI or the summary given by LLMs as a prompt, and then generate the embeddings for the prompt based on LLMs' embedding layers. Here we choose GPT 3.5 to summarize the functions of features and to generate embeddings based on our evaluation in the Results section.

After having embeddings for features or cells, we can use them based on the zero-shot learning framework for clustering or batch effect correction. Such framework requires us to consider the contribution of each biological feature in generating the cell embeddings. As several methods demonstrate the improvement of considering biological knowledge in modeling single-cell data [1, 30, 31], we can also combine the embeddings with task-specific models to improve their performance for various downstream tasks. Such framework provides a more flexible approach for utilizing gene embeddings as information-enriched biological priors to enhance task-specific methods in downstream applications. Figure 1 shows the flowchart of scELMo under two different frameworks. The details of scELMo under different frameworks are given in the Methods section.

Evaluation of Hallucinations in LLMs. The first step of our work is to define a suitable LLM for generating text descriptions and embeddings. A suitable LLM should not suffer from Hallucinations [32], that is, generating fake or incorrect information about our given feature information or cell information. Here we consider GPT 2 [33], GPT 3.5, GPT 4, Llama-2 (70B), Mistral [34], bioGPT [35], Claude 2 [36], and Bard (PaLM 2) [37] as candidates to generate text description. Considering the diversity of tokens as well as the access to embedding layers, we chose GPT 3.5 to generate embeddings. We randomly sampled 20 proteins and 20 genes from known proteins (∼200 proteins from [38]) and genes (∼30,000 genes from NCBI), and used these LLMs we mentioned above to generate the text description of these features. We evaluated the correctness of the outputs by comparing them with known databases (GeneCards [39] and NCBI) based on both Bilingual Evaluation Understudy (BLEU) [40] score and Human-Eval [41] score. The results of genes and proteins are shown in Figure 2

Fig. 1 Workflow of scELMo. (a) Zero-shot learning (denoted as ice) framework of scELMo. We extract the text description of metadata by using either databases or LLMs. The prompts are adjustable. We use GPT 3.5 to generate the embeddings of the text description as the embeddings of features or cell states. We then aggregate these embeddings with single-cell profiles to generate cell embeddings. (b) Fine-tuning (denoted as fire) framework of scELMo. We combine embeddings of metadata and single-cell profiles with task-specific adaptors and train the adaptors to address downstream applications.

(a), together with the time usage for one query for each LLM, shown in Figure 2 (b). We also include the results of cell types in Extended Data Figure 1 (a).

Based on our results, GPT 3.5 and GPT 4 gave us the most accurate text description. However, comparing with GPT 3.5, GPT 4 required longer query time and some of the outputs from GPT 4 did not follow our required format mentioned in the prompt. Meanwhile, we also considered analyzing the effects of different prompts as prompt engineering for querying gene information. We show the results based on MetaPrompt [42] and Chain-of-Thought (COT) [43] based on Extended Data Figure 1 (b). According to this figure, using these methods does not improve BLEU scores

significantly while their Human-Eval scores are lower than the results based on the original prompts. By considering the trade-off between query time and quality of generated descriptions, we selected GPT 3.5 as our tool to generate text descriptions of features based on our default prompts. Moreover, we also evaluated the stability of the embeddings of LLM's outputs based on the same prompt for the same gene, as well as the similarity of embeddings from different genes. Our results are summarized in Extended Data Figures 2 (a) and (b). According to Extended Data Figure 2 (a), the correlation between the embeddings from different LLM outputs of the same gene was higher than 0.9, suggesting that the embeddings from GPT 3.5 have high stability and may capture the intrinsic functions for each gene. Based on Extended Data Figure 2 (b), the embeddings from different genes had lower correlation ([0.74, 0.84]) comparing with the embeddings from the same gene ([0.88, 0.99]). Therefore, the embeddings from GPT 3.5 may also capture the functional heterogeneity of different genes. Moreover, we analyze the effects of gene embeddings from different random seeds on downstream applications in the Discussion section. Furthermore, we loaded the gene functional annotation provided by Geneformer [2] to predict the functional information for the other genes based on a k-nearest-neighbor (kNN) classifier. Extended Data Figures 3 (a) and (b) display the functional clustering for these genes, where genes with similar functions were embedded into a joint cluster. To evaluate the correctness of functional clustering, we performed Gene Ontology Enrichment Analysis (GOEA) [44–46] and Ingenuity Pathway Analysis (IPA) [47] based on the top 10 clusters of protein-encoding genes. This setting can demonstrate the robustness of gene embeddings analysis based on different databases. We visualize the top pathways ranked by $-log$(adjusted p-value) (the p-value adjusted by Bonferroni correction) of each cluster in Extended Data Figures 4 and 8. We found that all the clusters contain pathways related to important biological activities, including metabolism, transport, and genetics, etc. We also analyzed text descriptions from NCBI and LLMs in Appendix A. The outputs of different LLMs are summarized in Supplementary File 1. We could also utilize embeddings from LLMs to analyze single-cell data and spatial transcriptomic data from Mouse and other species, thus offering potentials in cross-species analysis. These are summarized in Appendix B.

scELMo for clustering and batch effect correction. In this section, we investigated the contribution of feature embeddings from scELMo for cell-level tasks including clustering and batch effect correction.

Clustering is effective in checking whether feature embeddings carry biological information. We incorporated gene embeddings or protein embeddings into the single-cell sequencing data and evaluated the performance of clustering based on cell embeddings. The metrics we chose include NMI, ARI, and ASW [49], which are widely used in the evaluation of clustering for single-cell data. In the following analysis, if not otherwise specified, GenePT means GenePT-w. Since we generated gene embeddings for gene names from both NCBI and Ensemble [50], we had more genes that those from GenePT. Moreover, when incorporating the feature embeddings, GenePT utilized a naive arithmetic average (aa) method, where it computed the embeddings for one cell by directly multiplying the gene expression vector from this cell and the matrix of gene embeddings from GPT 3.5. The aa mode ignored the scales of log-normalized

Fig. 2 Evaluations of the outputs of LLMs and the clustering performance. *: This sign represents that the selected method has zero Human-Eval score. (a) Metrics for evaluating meaningful outputs of biological features across different LLMs. The left panel represents the BLEU score and Human-Eval score of genes, while the right panel represents the BLEU score and Human-Eval score of proteins. (b) Average query time for each LLM. The left panel represents the query time of genes, and the right panel represents the query time of proteins. (c) Evaluations of the clustering performance based on major methods. Different panels represent the results of different datasets.

gene expression levels across different cells. However, the level of gene expression is a key factor affecting cellular function [51, 52]. Different from GenePT, we treated the gene expression levels as weights and computed the weighted average (*wa*) value for each cell as an alternative averaging approach. We implemented these approaches for generating cell embeddings and details are included in the Methods section.

Figure 2 (c) shows that using the *wa* mode was better than using the *aa* mode for clustering. Meanwhile, the *wa* mode has better performances in three out of four datasets comparing with task-specific methods SC3 [53] and scVI [54]. Moreover, using embeddings from scELMo also improved the clustering performance compared with

Fig. 3 Results of batch effect correction for single-cell proteomic data. (a) UMAPs [48] for the cell-type information (left) and batch information (right) of cite-seq-based datasets. The upper panel represents the raw data. The bottom panel represents the cell embeddings from GPT 3.5 *wa* mode. (b) Evaluations of the batch effect correction for cite-seq-based datasets across different methods. (c) UMAPs for the cell-type information (left) and batch information (right) of cite-seq-based dataset and CyTOF-based dataset. The upper panel represents the raw data. The bottom panel represents the cell embeddings from GPT 3.5 *wa* mode. (d) Evaluations of the batch effect correction for cite-seq-based dataset and CyTOF-based dataset across different methods.

the embeddings from GenePT, advocating LLMs as a tool for summarizing scientific concepts. However, various approaches of combining the embeddings from GenePT and GPT 3.5 (e.g. GPT 3.5 + GenePT *wa* means sum by genes, and GPT 3.5 || GenePT *wa* means concatenation by genes.) did not improve the scores compared with the individual setting. The average ranks of all methods across different datasets are summarized in Extended Data Figure 5 (a), with the GPT 3.5 *wa* mode having the lowest rank. Finally, if we combined cell embeddings with the embeddings of cell-type information from GPT 3.5, we could get scores close to one, suggesting that the cell-type embeddings contained meaningful cell-type information. Appendix C summarizes factors that could affect clustering performance.

For the batch effect correction task, because GenePT already evaluated the performance of such embeddings for small-scale single-cell RNA sequencing (scRNA-seq) data, we first focused on single-cell proteomic data, such as those collected from CITE-seq [15] and CyTOF [14]. To ensure the fairness of benchmarking, our batch effect correction relies on projecting the datasets from different batches into a joint space without active training. Here we considered two scenarios. We tried to use the embeddings from scELMo and GenePT to reduce the batch effect for datasets from the same

or different protocols. To evaluate the performance of batch effect correction, we used metrics from scIB [49] and considered the contribution of our embeddings for reducing batch effect (known as S_{batch}) and for preserving the biological variation (known as S_{bio}) separately. Details of our metrics are included in the Method section. We also included task-specific methods including MARIO [55], Harmony [56], and MNN [57] for comparisons. Figures 3 (a) and (b) display the results for batch effect correction from two CITE-seq datasets and Figures 3 (c) and (d) display the results for batch effect correction for one CITE-seq dataset and one CyTOF dataset. These four figures show that using the aa approach did not improve the performance of scELMo for both cases. This observation also applied to task-specific methods. MARIO performed well in integrating the CITE-seq dataset and the CyTOF dataset, but it did not show superiority in integrating two CITE-seq datasets. MNN performed worse than either aa or wa approaches in these two datasets. Moreover, the aa approach could reduce S_{batch} and S_{bio} simultaneously compared with these two scores from the raw dataset under the Cytof+CITE-seq case, thus led to a larger batch effect. On the other hand, the wa approach led to the reduction of the batch effect as shown by the improvement of these two scores. Moreover, incorporating the cell-type embeddings with the aa mode also did not improve S_{batch} and S_{bio} jointly. However, combining the cell-type embeddings with the cell embeddings under the wa mode also improved the S_{bio} score for both cases. Therefore, finding a good base embedding space is important for utilizing cell-state embeddings. We also evaluated the performances of scELMo in integrating atlas-level scRNA-seq data [58–60], shown in Extended Data Figure 6. We demonstrated that scELMo outperformed GenePT in integrating large-scale transcriptomic data. As an extension, we summarize our analysis of multi-omic data integration [61] in Appendix D.

scELMo for cell-type annotation. Cell-type annotation is a critical component of single-cell analysis [62]. Here we investigated the ability of scELMo to annotate cells under both the zero-shot learning framework and the fine-tuning framework. For the zero-shot learning framework, we incorporated the gene embeddings into both the training and testing datasets to access cell embeddings and used a kNN classifier implemented by GenePT to annotate cells in the testing dataset. However, this approach failed when the training datasets were from multiple resources or had large batch effects (shown in the PBMC section of Table 1). Therefore, we constructed a simple classifier based on neural networks [63] and contrastive learning [64], shown in Extended Data Figure 7. We then trained the model based on gene embeddings and expression profiles. Such model is also known as an adaptor in Natural Language Processing (NLP) tasks [26]. We tested the ability of cell embeddings from this model for annotating cell types. Here we considered three different datasets from different tissues for evaluation. The hPancreas dataset and the PBMC dataset contain one batch for testing and the rest of batches for training. The Aorta dataset is split into training and testing datasets from one study with a ratio of 0.8/0.2, by following the default setting of [3].

Table 1 shows that the zero-shot learning ability of embeddings from GPT 3.5 is impressive for annotating cells for the hPancreas dataset and the PBMC dataset. scELMo also outperforms the method GPTCelltype [4], which is based on the markers

Table 1 Scores of cell-type annotation task under different settings. Parts of the results are directly extracted from GenePT. Here PCA represents principal component analysis, and *scELMo+random emb* represents fine-tuning scELMo with random numbers as meaningless gene embeddings. Average ranks of all methods across datasets are summarized in Extended Data Figure 5 (b). We boldfaced the highest score of each metric for each dataset.

	zero-shot settings	Accuracy	Precision	Recall	F1
	GPT 2 query	0.000	0.000	0.000	0.000
	GPT 4 query	0.000	0.000	0.000	0.000
	scGPT (z)	0.770	0.610	0.560	0.550
	Geneformer (z)	0.500	0.250	0.340	0.270
	GenePT-w	0.940	0.720	0.630	0.650
	GenePT-s	0.890	0.650	0.530	0.560
	GPTCelltype	0.501	0.386	0.415	0.366
	PCA	0.633	0.369	0.382	0.357
hPancreas [65–68]	GPT3.5 aa	0.933	0.702	0.614	0.629
	GPT3.5 wa	0.933	0.702	0.613	0.629
	fine-tuning settings				
	scGPT	**0.970**	0.742	**0.758**	**0.741**
	Geneformer	0.321	0.105	0.094	0.086
	scELMo+GenePT	0.963	**0.790**	0.662	0.680
	scELMo+random emb	0.968	0.683	0.693	0.680
	scELMo+GPT 3.5	**0.970**	0.769	0.674	0.687
	zero-shot settings	Accuracy	Precision	Recall	F1
	GPT 2 query	0.000	0.000	0.000	0.000
	GPT 4 query	0.000	0.000	0.000	0.000
	scGPT (z)	0.938	0.921	0.894	0.901
	Geneformer (z)	0.860	0.700	0.600	0.620
	GenePT-w	0.870	0.910	0.680	0.720
	GenePT-s	0.860	0.700	0.600	0.620
	GPTCelltype	0.340	0.254	0.261	0.228
	PCA	0.929	0.923	0.911	0.910
Aorta [69]	GPT3.5 aa	0.877	0.867	0.678	0.719
	GPT3.5 wa	0.877	0.867	0.677	0.718
	fine-tuning settings				
	scGPT	**0.962**	0.938	0.939	0.937
	Geneformer	0.340	0.087	0.092	0.080
	scELMo+GenePT	0.958	**0.952**	**0.940**	**0.946**
	scELMo+random emb	0.951	0.913	0.874	0.882
	scELMo+GPT 3.5	0.957	0.950	0.936	0.942
	zero-shot settings	Accuracy	Precision	Recall	F1
	GPT 2 query	0.000	0.000	0.000	0.000
	GPT 4 query	0.000	0.000	0.000	0.000
	scGPT (z)	0.915	0.781	0.803	0.789
	Geneformer (z)	0.126	0.128	0.130	0.095
	GenePT-w	0.286	0.607	0.270	0.315
	GenePT-s	-	-	-	-
	GPTCelltype	0.501	0.387	0.415	0.366
	PCA	0.436	0.392	0.278	0.285
PBMC [70–73]	GPT3.5 aa	0.190	0.564	0.181	0.230
	GPT3.5 wa	0.190	0.562	0.181	0.231
	fine-tuning settings				
	scGPT	0.933	0.798	0.822	0.807
	Geneformer	0.235	0.146	0.147	0.131
	scELMo+GenePT	0.919	0.785	0.823	0.801
	scELMo+random emb	0.903	0.854	0.826	0.835
	scELMo+GPT 3.5	**0.955**	**0.940**	**0.929**	**0.934**

extracted from LLMs for cell-type annotation. Moreover, representing cells by using the gene rank and the representation for GPT 2 or GPT 4 did not perform well. Therefore, zero-shot learning based on gene embeddings is capable of cell-type annotation for datasets with minimal batch effect. However, for the PBMC dataset, which consisted of datasets from different sources, there was a clear gap between zero-shot learning results and fine-tuning results. Moreover, the fine-tuning results by combining the gene embeddings from GPT 3.5 or GenePT and our adaptor are comparable with FMs like scGPT [1] and Geneformer [2]. However, scGPT and Geneformer need more

Fig. 4 Results of in-silico treatment analysis. A gene is treated as a potential therapeutic target if the change of cosine similarity (CS) by removing the gene is larger than 1e-4. The reason for setting such threshold was discussed in the Methods section. We chose the top 10 DEGs as candidates. (a) The change of CS by removing different genes in the expression space for hypertrophic (HCM) or dilated cardiomyopathy (DCM) states. (b) The change of CS by removing different genes in the expression space for ascending aortic aneurysm (Ascending only, Ascending to descending, and Ascending w/ root). (c) The accuracy of disease-state annotation under different settings of scELMo. We highlighted the genes detected by both GenePT and scELMo using stars (*) and marked the genes that were discovered by previous research as therapeutic targets using **bold** type.

resources including NVIDIA A100 GPU and longer running time for fine-tuning [74], further shown in Extended Data Figures 9 (a) and (b). For all the datasets we tested, scELMo with a fine-tuning framework performed better than the same settings with the exception of the zero-short learning framework. Moreover, scELMo could improve the annotation score for embeddings from different sources. Our results show that cell-type annotation based on fine-tuning the adaptor with gene embeddings from LLMs is accurate and easy to implement.

scELMo for in-silico treatment analysis. Using computational methods to discover novel target therapies and drugs has attracted much attention [75–77]. In this

section, we study the ability of scELMo to use the adaptor for cell-type annotation and the gene embeddings we extracted from GPT 3.5 or NCBI to model human diseases and reveal potential therapeutic targets. This is a new task and has not been discussed in GenePT. Inspired by Geneformer [2], we finetuned our adaptor based on the classification task of cell conditions and used the cell embeddings from the adaptor for therapeutic target discovery. We utilized the training-validating framework to choose the adaptor with best performance and tested the change of embeddings by removing the differenetially expressed genes (DEGs) in the expression levels across different conditions. We discussed the importance of fine-tuning a model in Appendix E. Meanwhile ,in Figure 4 (c), we found that using gene embeddings from GPT 3.5 can give us the most accurate result. If we remove a suitable candidate for targeted therapies, the cell embeddings under disease will be more similar to those under control. The metric we used to evaluate similarity is the cosine similarity between the embeddings under the diseased case and the average cell embedding under the control case. We evaluated the discovered targets through GOEA and literature review as summarized in Supplementary File 2.

We first considered hypertrophic or dilated cardiomyopathy states [78] using the scRNA-seq Heart dataset [79]. We identified genes whose in-silico deletion in the disease conditions could significantly shift the cell embeddings from the disease conditions to the non-failing (NF) or control condition. The change of cosine similarity before and after the deletion for cardiomyopathy states is summarized in Figure 4 (a). Based on this figure, our adaptor identified two novel potential therapeutic targets for cells under the DCM case and four novel targets for cells under the HCM case, and using gene embeddings from GPT 3.5 or NCBI gives us consistent result. The silence of genes identified by scELMo may help the shift from cells under the disease conditions to cells under the control condition. There is literature to support our discovery of ANKRD1 [80], EXT1 [81], NPPB [82] and TTTY10 [83]. Moreover, there is supporting evidence of GSN [2] by CRISPR-based technology [84] as a therapeutic target. We show the results of GOEA based on selected genes in Extended Data Figures 10 (a) and (b) with at least 10 pathways ranked by $-log$(adjusted p-value) and the results of IPA in Extended Data Figure 11 (a). According to the pathway information, the selected genes play an important role in cardiac activities, corresponding to the target tissue. Meanwhile, the select genes can also capture the interaction of these important pathways. These findings suggest the potential usefulness of genes selected by scELMo.

Then we considered ascending aortic aneurysm [85], which has three different disease states. The scRNA-seq dataset we used is the scRNA-seq Aorta dataset. We used the similar approach discussed above and summarize the change of cosine similarity before and after deletion in Figure 4 (b). scELMo identified six novel genes as potential therapeutic targets for cells under the Ascending only state, two novel genes as potential therapeutic targets for cells under the Ascending to descending state, and three genes as potential therapeutic targets for cells under the Ascending w/ root state. Interestingly, MT-ATP6 gene was selected by scELMo as a potential target, which implied that cells under different states might have different speeds for cell death [86] or neurodegeneration [87]. We also show the results of GOEA based on selected genes in Extended Data Figure 10 (c)-(e) and the results of IPA in Extended Data Figure 11

Fig. 5 Results of perturbation analysis. (a) Scores of casual factor analysis for ChangYe2021 dataset [88, 89] based on CINEMA-OT across different input data. We considered four different types of extension. We still use S_{batch} to represent the levels of perturbation effect removal because we used the metrics for benchmarking batch integration. (b) Scores of causal factor analysis for perturbed PBMC dataset [90] based on CINEMA-OT across different input data. (c) Scores of gene expression prediction under different perturbation cases based on CPA. We considered four different methods and two datasets. (d) Scores of gene expression prediction using perturb-seq datasets based on GEARS. We considered three different methods and three datasets. The arrows represent the direction of metrics comparison.

(b). our selected genes are important for immune responses according to these pathways. These results suggest the potential benefit of exploring the correlation between cellular function and clinical manifestations of this disease.

scELMo for perturbation analysis. Analyzing the perturbation effect on cell state using single-cell data is also an important task. Here we focus on three tasks across different perturbation types, for example, cell-level perturbation [91] or gene-level perturbation [92]. Our idea is to use the cell embeddings or gene embeddings generated based on the zero-shot learning framework of scELMo to replace or combine with the original input of different models to enhance their performance on the tasks including causal factor analysis, gene expression prediction with cell-level perturbation and gene expression prediction with gene-level perturbation. We evaluated the contribution of scELMo for the causal factor analysis task based on CINEMA-OT [90], the gene expression prediction task for cell-level perturbation data based on CPA [93], and the gene expression prediction task for gene-level perturbation data based on GEARS [94]. All of the metrics we considered in these three tasks are from these models.

CINEMA-OT is a tool based on a causal learning framework and optimal transport to distinguish between perturbation effects and intrinsic cell-state effects for scRNA-seq datasets. We replaced the input of CINEMA-OT with cell embeddings from scELMo and investigated the contribution of our cell embeddings by evaluating the reduction of batch effect in the space of intrinsic cell-state effects (also known as the confounder space). By removing the perturbation effect, the perturbation case in

the intrinsic cell-state space became the batch label and we should not observe the difference of the embeddings from the same cell types in this space. Based on Figure 5 (a), using cell embeddings rather than the default PCA results as input improved the performance of CINEMA-OT for cells from the same cell type. Moreover, the embeddings from GenePT were a better choice compared with the embeddings from GPT 3.5. Moreover, based on Figure 5 (a), only incorporating gene embeddings may not contribute to the casual factor analysis for cells from different cell types. However, if we consider incorporating the cell-type embeddings with the cell embeddings and use the updated embeddings as new input, we can improve the performance of CINEMA-OT for separating the perturbation effect and intrinsic cell states across different perturbation cases significantly, supported by performing the Wilcoxon Rank-Sum test between default mode (GenePT mode) and scELMo based on the scores from two datasets (p-value=0.031 for both cases). Moreover, Extended Data Figures 12 (a) and (b) show that the visualization could also be improved by using the updated embeddings as model input. Extended Data Figures 12 (c) and (d) show that incorporating the cell embeddings into CINEMA-OT did not affect the analysis of gene synergy effect, and the difference between synergy of Monocyte and synergy of other cell types was also obvious. For the causal factor analysis task, using the wa mode did not improve the score. One possible reason is that CINEMA-OT can learn the best representation of cell embeddings with a good start for optimization, so the aa mode is adequate. Therefore, scELMo can improve the performance of CINEMA-OT on the causal factor analysis task by offering a new candidate of input data.

CPA is a tool based on Conditional Variational Auto-encoder (CVAE) to predict the gene expression levels for the out-of-distribution (OOD) samples of scRNA-seq data under certain perturbations. Here we combined the gene embeddings from scELMo with the original input dataset and learned a new latent space for gene expression prediction. We investigated the contribution of gene embeddings by comparing the R2 score between these two different settings. We computed the R2 score based on the predicted gene expression levels and the observed gene expression levels. Figure 5 (c) shows the performance of CPA under different methods for two datasets. For the CPA example dataset shown in the left panel, using the cell embeddings from GenePT and the GPT 3.5 in the training process slightly improved the average R2 score, while its median value was still lower than the default mode. For the Openproblems dataset [95] shown in the right panel, using cell embeddings from both scGPT, GPT 3.5 and GenePT improved the performance of CPA. Moreover, the R2 score based on combining cell embeddings with CPA had a higher average value and lower variance compared with the default mode. We further performed Wilcoxon Rank-sum tests for the R2 scores between different conditions and set the significant threshold for p-value as 0.05. Based on our computation, the pairs of settings with significant differences include GPT 3.5 aa vs. Default (p-value=0.003), GPT 3.5 aa vs. GenePT (p-value=0.002) based on the CPA example dataset, and GPT 3.5 aa vs. Default (p-value=7e-11), GPT 3.5 wa vs. Default (p-value=6e-12) based on the Openproblems dataset. Therefore, scELMo could improve the performance of CPA on the prediction task by introducing the cell embeddings into the training process.

GEARS is a tool based on Graph Neural Networks (GNN) [96] to predict the gene expression levels for perturb-seq-based datasets. Here we combined the gene embeddings from scELMo with the original gene embeddings of GEARS to learn the predicted value of target genes. We studied the contribution of gene embeddings by comparing the Pearson Correlation Coefficient (PCC) and Mean Squared Errors (MSE) between the default settings and updated settings when all genes were considered and when only DEGs were considered. The results are summarized in Figure 5 (d) and Extended Data Figure 13 (a). For both Replogle [97] and Dixit [92] datasets, scELMo based on gene embeddings from GPT 3.5 outperformed the default settings as well as scELMo based on gene embeddings from GenePT and scGPT, supported by the comparisons based on all the metrics. For the Dixit dataset, using gene embeddings from GPT 3.5 improved the gene expression prediction made by GEARS for both the all genes case and the DEGs case obviously. By considering the four datasets (Dixit, Norman [98], Adamson [99], and Replogle [97]) together, we performed Wilcoxon Rank-sum test between the PCC and PCC_DEG of scELMo and the default mode, and the improvement of scELMo is significant (p-value=0.027). Furthermore, we also simulated datasets with different numbers of cells based on the Dixit dataset to test the robustness and consistency of our improvement, inspired by [100]. Extended Data Figure 13 (b) shows that scELMo has an overall better performance as well as a lower variance compared with the default mode. Therefore, we believe that the introduction of gene embeddings from LLMs can also contribute to perturbation effect prediction by incorporating more knowledge about perturbed genes.

3 Discussion

Developing methods to model genetic and cellular functionalities is an important task in computational biology. Although a common practice is to propose a biological question and design relevant experiments to answer this question, recent years have seen the development of a foundation model that may be informative to address many known and unknown biological questions. In the single-cell data analysis area, many researchers have proposed to pre-train a large-scale model and declare it as a foundation model by showing their comparable performance with different task-specific models in specific downstream tasks. However, it is hard to find tasks that could only be resolved through such pre-training and fine-tuning framework [74], which questioned the contribution of consuming large-scale resources to develop such models. Therefore, inspired by GenePT, we explored another approach to generalizing a foundation model in the single-cell research area, that is, utilizing the contribution of LLMs to generate meaningful feature embeddings and cell embeddings. We could either directly utilize these embeddings for clustering or reducing batch effect, or combine these embeddings with task-specific models to improve their performance. These two approaches are integrated in scELMo. Our gene embeddings are also robust to randomness, shown in Extended Data Figure 14 for different downstream tasks with low variance. Accessing the outputs of known LLMs like GPT 3.5 did not require many resources, and our results did show the superiority of scELMo in answering multiple biological questions.

For scELMo under the zero-shot learning framework, we could utilize cell embeddings to perform clustering and batch effect correction. These contributions are based on the fact that embeddings from the text description of features in single-cell datasets are good for representing biological concepts or functions. We also discussed the factors that could affect the performance of generating meaningful cell embeddings, including the approach to computing the average embeddings, the number of cells in one dataset, the number of features we need, and other factors. We showed that such embeddings could be used for multi-omic data analysis, which illustrates the power of using LLMs as tools for incorporating prior information to enhance task-specific analysis.

Considering the limitation of the zero-shot learning framework, we also proposed a fine-tuning framework for scELMo. By combining the feature embeddings from GPT 3.5 with a light-structured neural network, we could use the embeddings to annotate cell types with performance similar to those of FMs that require much more resources for pre-training and fine-tuning. Moreover, scELMo can also be used for detecting novel therapeutic targets by examining the change of embeddings corresponding to the removal of certain genes, supported by related biological experiments. We could also directly incorporate the cell embeddings or feature embeddings with task-specific models for better performance in modeling the data with perturbation. In-silico treatment analysis and perturbation analysis are two challenging and important tasks with cell-level knowledge, which further supported the potential of scELMo and related work.

Here we suggest a guideline for users interested in scELMo. The *wa* mode works better for clustering and batch effect correction, while the *aa* mode works better for perturbation analysis. We explain the rationale of such setting in the Method section. Both types of embeddings can help in performing cell-type annotation and in-silico treatment analysis. We recommend users consider the embeddings of meta-data information based on their specific tasks and requirements. We also encourage users to actively explore the boundaries of scELMo's capabilities to discover more interesting applications towards biology.

However, both GenePT and scELMo have the following limitations. Firstly, the rapid developments of LLMs likely lead to embeddings better than GPT 3.5. With a more powerful LLM, we will have a better representation of features and cells. Secondly, LLMs could not generate meaningful information for genes that were recently discovered or analyzed. Although GPT 3.5 does not makeup concepts for genes, the lack of knowledge still presents a question for the applications of scELMo. Thirdly, without enough resources, fine-tuning LLMs to generate better domain-specific embeddings is hard to deploy. Moreover, the training datasets for fine-tuning domain-specific LLMs are also hard to collect. Finally, extracting features from other biomedical data like GWAS [101] or scATAC-seq [102] data will be difficult since the number of features for these data is quite large.

Therefore, in the future, we plan to generate a database containing the text description as well as the embeddings of such descriptions of features from different LLMs. Models like CPA can utilize these embeddings to perform prediction under the OOD cases. Considering the limitation of our embeddings to enhance the perturbation prediction task, we may incorporate the perturbation information of target

genes' descriptions or consider better metrics for evaluating tasks related to perturbations. Moreover, we will keep on figuring out a more practical approach to offer a gene-specific LLM. In addition, since the idea from scELMo is capable of modeling arbitrary biomedical data with tabular format, we believe that extending the usage of scELMo to other tasks or areas is also very promising.

4 Methods

Problem definition. For a typical single-cell dataset $X^{n \times m}$ after normalization [103] with n cells and m features, our target is to utilize the text description from a mapping function $\mathcal{M}()$ for feature-level metadata information $f^{m \times 1}$ and cell-level metadata information $c^{n \times 1}$ to learn the embeddings of cells. If we define the embedding generation layer of $\mathcal{M}()$ as $\mathcal{M}_{\mathrm{e}}()$, our cell embeddings can be represented as:

$$e_f = \mathcal{M}_{\mathrm{e}}(\mathcal{M}(Prompt(f))),$$
$$e_c = \mathcal{M}_{\mathrm{e}}(\mathcal{M}(Prompt(c))),$$
$$e_{cells} = AVG(X)e_f + e_c,$$

where $Prompt$ is a mapping function that can transfer the name of input data to the prompt space. The prompts can be used as the input of language models. The function $AVG()$ represents the method we used to average the embeddings of all genes for each cell. If the mode is aa, we divide X by m. If the mode is wa, we divide each row of X by the sum of this row. Considering the cell with index i, we can define these two processes as:

$$AVG_{aa}(X_i) = \frac{X_i}{m},$$
$$AVG_{wa}(X_i) = \frac{X_i}{sum(X_i)}.$$

Then we use matrix multiplication to combine the feature embeddings and the expression profile. Our default setting of the mapping function is a LLM. GenePT can be treated as a special case of scELMo, that is, replacing the LLM with a known database and using aa mode. Incorporating the embeddings of cell-level metadata is an optional choice. We intend to investigate if the cell embeddings can offer a better representation than the raw data.

Moreover, with the embeddings of feature-level metadata information and cell-level metadata information, we also consider if incorporating our embeddings with task-specific model $\mathcal{T}$ can improve the performance of $\mathcal{T}$, that is:

$$Score(\mathcal{T}(X)) < Score(\mathcal{T}(X, e_f, e_c)),$$

where $Score()$ is a metric to evaluate the output of the given model, where higher value represents better output. We also may not need to have e_f and e_c for every model.

Method explanation. Our consideration of AVG is inspired by [3] as well as the noise level of scRNA-seq dataset [104]. By compressing the gene expression profiles into a lower dimension, we can jointly model both the magnitude of gene expression

levels and the functional information of genes. Moreover, we assume and demonstrate that such new cell embeddings can represent cells in a better approach contributed by the external information of gene functions and cell-type-specific information generated by LLMs. The raw data, on the other hand, are no longer required for further analysis. Furthermore, a systematical evaluation of LLM embeddings for medical machine learning usage [105] also supports our assumption. We found that *wa* mode worked better in handling the tasks of clustering and batch effect correction. As a possible reason, we believe that we need to consider the contributions of individual genes as well as their grouped effect for generating the cell embeddings under the zero-shot learning framework. For the fine-tuning framework, different task-specific methods have their favorable designs to incorporate LLM embeddings as prior knowledge, and thus we have a more flexible design.

scELMo under the zero-shot learning framework. To evaluate the performance of e_{cells} under the zero-shot learning framework, we consider three tasks: clustering, batch effect correction, and cell-type annotation based on a kNN classifier. In this section, $\mathcal{T}$ is defined as a kNN classifier.

For clustering and batch effect correction, we directly use e_{cells} as a new representation for X and evaluate e_{cells} for these two tasks. For cell-type annotation based on a kNN classifier, we consider training dataset X_{train} and testing dataset X_{test}, and their corresponding cell embeddings e_{cells}^{train} and e_{cells}^{test}. We use e_{cells}^{train} with its cell types to train a kNN classifier and perform cell-type annotation based on e_{cells}^{test}. Since kNN is based on similarity searching, we treat this method as an ability of zero-shot learning. We follow the settings from GenePT for this classifier and set k=10.

scELMo under the fine-tuning framework. To evaluate the performance of e_f and e_c under the fine-tuning framework, we considered three tasks: cell-type annotation with an adaptor, in-silico treatment analysis with an adaptor, and perturbation analysis with task-specific models as adaptors.

For the cell-type annotation and in-silico treatment analysis tasks, we propose a light-structured neural network with a contrastive learning [64, 106] design. Here $\mathcal{T}$ is a neural network with ReLU [107] as the activation function. Our intuition comes from the requirement for a good representation of cells with different labels and conditions. Therefore, we formalize the loss function of our model as:

$$\mathcal{L}_{total} = \mathcal{L}_{classifier} + \lambda \mathcal{L}_{contrastive},$$

where $\mathcal{L}_{classifier}$ represents the classification loss of the model output as we use cell-type labels for model training, and $\mathcal{L}_{contrastive}$ represents the contrastive learning loss we use to distinguish the representations of cells under different conditions in the latent space. λ is a hyper-parameter, where we set $\lambda = 100$ in this manuscript to assign a larger weight for label-aware clustering. We utilize the embeddings after fine-tuning as the training and testing datasets and use a kNN classifier to annotate the cell types to evaluate the representation we learn based on scELMo.

To analyze the target of in-silico treatment, we first compute the cosine similarity (CS_{old}) between the average cell embeddings based on the diseased case and control case. Then we delete the target gene by setting its expression profile as zero and compute the new embeddings and cosine similarity (CS_{new}). We define the score of

our targeted gene g as:

$$Score(g) = CS_{new} - CS_{old}.$$

If such a score is larger than 1e-4, we treat the gene we analyze as a candidate for therapeutic targets. This threshold is based on the upper bound of the tiny quantities determined by Numpy [108] for scientific notation representation and the smallest non-zero scale of the y-axis in Figures 4 (a) and (b). We utilize the selected genes to run gene pathway analysis based on Gene Ontology Enrichment Analysis (GOEA) [44–46] and Ingenuity Pathway Analysis (IPA) [47].

For the perturbation analysis task, we consider three different models for the three tasks. Here $\mathcal{T}$ represents different models corresponding to different perturbation analysis tasks. For the causal factor analysis task and CINEMA-OT, we replace the original input of CINEMA-OT with e_{cells}. We follow the default settings of CINEMA-OT for processing related datasets. For the gene expression prediction task and CPA, we add a new neural network component to make e_{cells} learnable and combine the output of this component with the latent space from the original CPA. We do not modify the training process of CPA. We follow the default settings of CPA for processing related datasets. For the gene expression prediction task based on perturb-seq-based datasets and GEARS, we add the e_f to the original gene embeddings of GEARS. We do not modify the training process of GEARS. We follow the default settings of GEARS for processing Dixit, Norman, Adamson, and Replogle datasets.

Data pre-processing. We follow the data pre-processing steps from Scanpy [103] for scRNA-seq datasets. For single-cell proteomic datasets, we follow the pre-processing steps from TotalVI [109] and MARIO [55] and do not change the distribution of the original data because of its density.

Metrics. To evaluate the hallucinations of LLM outputs, we consider two metrics including BiLingual Evaluation Understudy (BLEU) [40] score and Human-Eval score [41].

The BLEU score is used to evaluate the similarity between observed string $\hat{y}$ and ground truth string y based on $n - grams$ strategy. Considering we have a function $C(s, y)$ to generate the number of appearances of s as a substring of y and a set $G_n(\hat{y})$ as the $n - grams$ set, the BLEU score is defined as:

$$BLEU = \frac{\sum_{s \in G_n(\hat{y})} \min(C(s, \hat{y}), C(s, y))}{\sum_{s \in G_n(\hat{y})} C(s, \hat{y})}.$$

The score is in [0,1] and a higher value means better performance.

The Human-Eval score means we compare the truthfulness between the LLM outputs and references from NCBI and GeneCard databases to assign scores for the string pairs. We assign 1 if the outputs contain the correct information and 0 if the outputs do not contain the correct information. We have one human expert for evaluation. A higher value means better performance.

For the evaluations of clustering and batch effect correction, we utilize the metrics described and implemented by scIB [49]. We compute all the metrics we could compute in the evaluation process. All of the scores of the metrics in scIB are in [0,1] and a higher value means better performance.

For clustering, we use NMI, ARI, and ASW_{label} for evaluation. For batch effect correction, we compute ASW_{batch}, PCR, Graph Connectivity, kBET, and iLISI and average the scores from these metrics to generate S_{batch}. We compute ASW_{label}, NMI, ARI, and cLISI and average the scores from these metrics to generate S_{bio}. Details of these metrics, referred from [49, 74], are introduced below:

1. Normalized Mutual Information (NMI): NMI is a score to evaluate the performance of biological information conservation. We compute this score based on the mutual information between the optimal Leiden clusters and the known cell-type labels and then take the normalization. $\text{NMI} \in (0,1)$ and higher NMI means better performance.

2. Adjusted Rand Index (ARI): ARI is a score to evaluate the performance of biological information conservation. ARI is used to evaluate the agreement between optimal Louvain clusters and cell-type labels. $\text{ARI} \in (0,1)$ and higher ARI means better performance.

3. Average Silhouette Width (ASW): We have cell type ASW (ASW_{cell}) and batch ASW (ASW_{batch}) for this metric. For one cell, ASW calculates the ratio between the inner cluster distance and the intra cluster distance for this cell. Therefore, higher ASW_{cell} means better biological information conservation and lower ASW_{batch} means better batch effect correction. To make them consistent, for ASW_{cell}, we take the normalization, that is:

$$ASW_{cell} = \frac{ASW_{cell}^{raw} + 1}{2}.$$

Similarly, for ASW_{batch}, we take the inverse value of the normalized result, that is:

$$ASW_{batch} = 1 - \frac{ASW_{batch}^{raw} + 1}{2}.$$

Both of metrics are in (0,1), and a higher score means better model performance.

4. Local Inverse Simpson's Index (LISI): LISI is a metric to evaluate whether datasets are well-mixed under batch labels ($iLISI$) or can be discerned with different cell types $cLISI$. We first compute the k-nearest-neighbor list of one cell and count the the number of cells that can be extracted from the neighbors before one label is observed twice. Furthermore, we take the normalization for $iLISI$ with B batches, that is:

$$iLISI = \frac{iLISI^{raw} - 1}{B - 1}.$$

Similarly, for $cLISI$ with C cell types, we take the inverse value of the normalized result, that is:

$$cLISI = 1 - \frac{cLISI^{raw} - 1}{C - 1}.$$

Both of metrics are in (0,1), and a higher score means better model performance.

5. Graph Connectivity (GC): GC measures the connectivity of cells in different cell types. If the batch effect is substantially removed, the connectivity of cells of the same cell type from different batches will have a higher connectivity score based on the k-NN neighbor graph. Therefore, we can compute the GC score for each cell type and take the average. GC score is in (0,1) and higher means better batch effect correction performance.

6. Principal Component Regression (PCR): PCR is a metric to evaluate the performance of batch effect correction. We calculate the R^2 for a linear regression of the covariate of interest onto each principal component. The variance contribution of the batch effect for all the PCs is based on the sum of the product between the variance of each PC and the R^2 of each PC across all the PCs. Therefore, the score can be represented as:

$$PCR = \sum_{i=1}^{G} \text{Var}\left(C \mid \text{PC}_i\right) \times R^2\left(\text{PC}_i \mid B\right),$$

where G denotes the number of PCs and B denotes the batch information. PCR is in (0,1) and a higher score means better performance.

7. kBET: the kBET algorithm is used to determine if the label composition of the k-nearest-neighbors of a cell is similar to the expected label composition. For the batch label mixture of cells in the same cell types, the proportion of cells from different batches for the neighbors of one cell should match the global level distribution. The kBET score $\in (0, 1)$ and higher score means better batch effect correction performance.

For the evaluations of cell-type annotation, we use Scikit-learn [110] to calculate Accuracy, Precision, Recall, and F1 score by comparing the predicted cell-type labels and ground-truth cell-type labels. All of the metrics are in [0,1] and a higher value means better performance.

For the evaluations of in-silico treatment analysis, we use Scipy [111] to compute the cosine similarity between the mean cell embeddings from the control case and the mean cell embeddings from the diseased case. The definition of the score here is described in the Methods section.

For the evaluations of perturbation analysis, we have three different tasks with different metrics. For the causal factor analysis task, the metrics are the same as what we use in the batch effect correction task. For the gene expression prediction task based on CPA, we use the R2 score as a metric to evaluate the performance for regression. R2 score is defined as:

$$R2 = 1 - \frac{SS_{\text{res}}}{SS_{\text{tot}}} = 1 - \frac{\sum_i (y_i - f_i)^2}{\sum_i (y_i - \bar{y})^2},$$

where y_i represents the ground-truth gene expression level, f_i represents the predicted gene expression level, and $\bar{y}$ represents the average expression levels of the given gene. A higher averaged R2 score and a lower variance mean better performance.

For the evaluation of gene expression prediction tasks based on GEARS, we use PCC and MSE as metrics. We define PCC as:

$$PCC = \frac{1}{m} \sum_{i}^{m} \frac{cov(y_i, f_i)}{\sigma_{y_i} \sigma_{f_i}},$$

where m represents the number of used genes, cov represents the covariance, σ represents the standard deviation. ρ is in [0,1] and a higher value means better performance.

We can also define MSE as:

$$MSE = \frac{1}{mn} \sum_{i}^{m} \sum_{j}^{n} (y_{ij} - f_{ij})^2,$$

where y_{ij} represents the ground truth gene expression level of gene i in cell j, and f_{ij} represents the predicted gene expression level of gene i in cell j. Lower MSE score means better performance.

We consider computing these two metrics for both the all genes case and the top 20 DEGs case.

Explanations of baseline models. For tasks related to description generation, we consider MetaPrompt [42] and Chain-of-Thought (COT) [42] as baseline models for prompt engineering. MetaPrompt introduces a system prompt for LLMs and generates the outputs conditioned on the context in the system prompt. COT allows LLMs to obtain complex reasoning capabilities by allowing models to address the problem with intermediate steps.

For tasks related to clustering, we consider PCA (raw) [110], GenePT [3], SC3 [53], and scVI [54] as baseline models. PCA is widely used for dimension reduction of single-cell data. The principles of GenePT are summarized in the Introduction section. SC3 utilizes consensus clustering for analyzing scRNA-seq data, which is based on aggregating the k-means results after PCA transformation to generate the consensus and then performs the clustering based on consensus. scVI utilizes a generative model to learn the embeddings in the latent space of scRNA-seq data.

For tasks related to batch effect correction, we consider PCA (raw), GenePT, MARIO [55], Harmony [56] and MNN [57] as baseline models. MARIO considers both the shared features and distinct features for proteomic data and performs paired matching for cells from different batches to generate integrated results in the latent space. Harmony assigns labels for different cells with a soft-clustering method, computes the centroids for different clusters, and updates cell embeddings based on the soft cluster membership. MNN utilizes mutual nearest neighbors to learn the relationships for cells in different batches and updates the cell embeddings based on the relationships.

For tasks related to cell-type annotation, we consider GPT 2 [33], GPT 4 [20], scGPT [1], Geneformer [2], GPTCelltype [4], Multilayer Perception (MLP) and PCA for evaluation. To evaluate GPT 2 and GPT 4, we transfer the cell information into a sentence based on the rank of genes for each cell and treat this task as a Question-Answer task. scGPT is a pre-training-based FM for multiple tasks in single-cell research. The authors utilized multi-layer transformers to construct the model architecture and pre-trained scGPT based on large-scale scRNA-seq datasets. They finetuned scGPT to address problems in downstream applications like cell-type annotation. Geneformer is also a model based on pre-training. The authors utilized BERT [112] as a based model and pre-trained BERT from the sketch using scRNA-seq data transferred into sentences. They also finetuned Geneformer to address problems in downstream applications including cell-type annotation, in silico-treatment analysis,

etc. GPTCelltype utilizes GPT-4 to extract markers of cell types to annotate cell clusters. To evaluate this model, we unify the model outputs and ground truth cell-type labels. MLP means we fits a MLP based on gene expression profiles and cell types. We extract the embeddings from these two models and PCs based on both zero-shot learning framework and fine-tuning framework, and utilize kNN to perform classification based on the embeddings.

For tasks related to perturbation analysis, we consider CINEMA-OT [90], CPA [93], and GEARS [94] for modification and evaluation. We included gene embeddings from GPT 3.5, NCBI (GenePT), and scGPT as inputs. CINEMA-OT is a method for separating confounding signals or causal factors from perturbations at single-cell level. The first step is to initialize the expected matrix rank based on biwhitening [113]. The second step is to separate confounder signals and treatment-associated signals based on Independent Component Analysis (ICA) [110]. The last step is to match the cells based on entropy regularized optimal transport [114]. We analyze the confounder embeddings for CINEMA-OT and follow the benchmarking pipeline mentioned in the original paper. CPA is a method for modeling the gene expression levels of scRNA-seq data with perturbations. CPA treats perturbations of cells as covariates and encodes these covariates as embeddings into the training process of a CVAE. CPA can also be used to predict the gene expression levels of OOD samples. GEARS is a method for predicting gene expression levels of perturb-seq-based datasets. It models the perturbations of genes based on knowledge graph and gene embeddings, thus utilizing GNN and Multi-layer Perceptrons (MLPs) to predict the gene expression levels under gene-level perturbation.

Datasets information. We did not generate new sequencing datasets in this project. The download links and data statistics are summarized in the Supplementary File 3.

Reproductivities. To generate the text descriptions and embeddings, we rely on the API of OpenAI. To run scELMo, we rely on Yale High-performance Computing Center (YCRC) and utilize one NVIDIA A5000 GPU with up to 30 GB RAM for fine-tuning. We utilize the bigmem node with up to 1000 GB RAM for analysis, and the minimal RAM requirement to analyze ∼1,000,000 cells is 70 GB.

The codes of scELMo can be found in https://github.com/HelloWorldLTY/scELMo. The licence is MIT license.

5 Ethics and Inclusion.

Although scELMo is not biased to gender, races, and other factors, the users are solely responsible for the content they generate with models in scELMo, and there are no mechanisms in place for addressing harmful, unfaithful, biased, and toxic content disclosure. Any modifications of the models should be released under different version numbers to keep track of the original models related to this manuscript.

The target of current scELMo only serves for academic research. The users cannot use it for other purposes. Finally, we are not responsible for any effects of the use of the model.

Acknowledgements. We thank Gefei Wang and Chen Lin for the suggestions of datasets. We thank Yiqun Chen and Mingze Dong for helpful discussions.

Author contributions. T.L. designed this study. T.L. and X.L. designed the model. T.L., T.C. and W.Z. ran all the experiments. T.L. and H.Z. wrote the manuscript. H.Z. supervised this work.

Competing interests. The authors declare no competing interests.

References

[1] Cui, H., Wang, C., Maan, H., Pang, K., Luo, F., Duan, N., Wang, B.: scgpt: toward building a foundation model for single-cell multi-omics using generative ai. Nature Methods, 1–11 (2024)

[2] Theodoris, C.V., Xiao, L., Chopra, A., Chaffin, M.D., Al Sayed, Z.R., Hill, M.C., Mantineo, H., Brydon, E.M., Zeng, Z., Liu, X.S., et al.: Transfer learning enables predictions in network biology. Nature, 1–9 (2023)

[3] Chen, Y.T., Zou, J.: Genept: A simple but hard-to-beat foundation model for genes and cells built from chatgpt. bioRxiv, 2023–10 (2023)

[4] Hou, W., Ji, Z.: Assessing gpt-4 for cell type annotation in single-cell rna-seq analysis. Nature Methods, 1–4 (2024)

[5] Wu, J., Yang, S., Zhan, R., Yuan, Y., Wong, D.F., Chao, L.S.: A survey on llm-gernerated text detection: Necessity, methods, and future directions. arXiv preprint arXiv:2310.14724 (2023)

[6] Zhao, W.X., Zhou, K., Li, J., Tang, T., Wang, X., Hou, Y., Min, Y., Zhang, B., Zhang, J., Dong, Z., et al.: A survey of large language models. arXiv preprint arXiv:2303.18223 (2023)

[7] Zhou, C., Li, Q., Li, C., Yu, J., Liu, Y., Wang, G., Zhang, K., Ji, C., Yan, Q., He, L., et al.: A comprehensive survey on pretrained foundation models: A history from bert to chatgpt. arXiv preprint arXiv:2302.09419 (2023)

[8] Nguyen, E., Poli, M., Faizi, M., Thomas, A.W., Wornow, M., Birch-Sykes, C., Massaroli, S., Patel, A., Rabideau, C.M., Bengio, Y., Ermon, S., Re, C., Baccus, S.: HyenaDNA: Long-range genomic sequence modeling at single nucleotide resolution. In: Thirty-seventh Conference on Neural Information Processing Systems (2023). https://openreview.net/forum?id=ubzNoJjOKj

[9] Marin, F.I., Teufel, F., Horlacher, M., Madsen, D., Pultz, D., Winther, O., Boomsma, W.: BEND: Benchmarking DNA language models on biologically meaningful tasks. In: The Twelfth International Conference on Learning Representations (2024). https://openreview.net/forum?id=uKB4cFNQFg

[10] Fan, Y., Li, Y., Ding, J., Li, Y.: Gfetm: Genome foundation-based embedded

topic model for scatac-seq modeling. In: Ma, J. (ed.) Research in Computational Molecular Biology, pp. 314–319. Springer, Cham (2024)

[11] Yang, F., Wang, W., Wang, F., Fang, Y., Tang, D., Huang, J., Lu, H., Yao, J.: scbert as a large-scale pretrained deep language model for cell type annotation of single-cell rna-seq data. Nature Machine Intelligence **4**(10), 852–866 (2022)

[12] Han, X., Zhou, Z., Fei, L., Sun, H., Wang, R., Chen, Y., Chen, H., Wang, J., Tang, H., Ge, W., *et al.*: Construction of a human cell landscape at single-cell level. Nature **581**(7808), 303–309 (2020)

[13] Saliba, A.-E., Westermann, A.J., Gorski, S.A., Vogel, J.: Single-cell rna-seq: advances and future challenges. Nucleic acids research **42**(14), 8845–8860 (2014)

[14] Cheung, R.K., Utz, P.J.: Cytof—the next generation of cell detection. Nature Reviews Rheumatology **7**(9), 502–503 (2011)

[15] Stoeckius, M., Hafemeister, C., Stephenson, W., Houck-Loomis, B., Chattopadhyay, P.K., Swerdlow, H., Satija, R., Smibert, P.: Simultaneous epitope and transcriptome measurement in single cells. Nature methods **14**(9), 865–868 (2017)

[16] Karemaker, I.D., Vermeulen, M.: Single-cell dna methylation profiling: technologies and biological applications. Trends in biotechnology **36**(9), 952–965 (2018)

[17] Wheeler, D.L., Barrett, T., Benson, D.A., Bryant, S.H., Canese, K., Chetvernin, V., Church, D.M., DiCuccio, M., Edgar, R., Federhen, S., *et al.*: Database resources of the national center for biotechnology information. Nucleic acids research **35**(suppl_1), 5–12 (2007)

[18] Shevlane, T.: Structured Access: An Emerging Paradigm for Safe AI Deployment. In: The Oxford Handbook of AI Governance. Oxford University Press. https://doi.org/10.1093/oxfordhb/9780197579329.013.39 . https://doi.org/10.1093/oxfordhb/9780197579329.013.39

[19] Brown, T., Mann, B., Ryder, N., Subbiah, M., Kaplan, J.D., Dhariwal, P., Neelakantan, A., Shyam, P., Sastry, G., Askell, A., *et al.*: Language models are few-shot learners. Advances in neural information processing systems **33**, 1877–1901 (2020)

[20] OpenAI: GPT-4 Technical Report (2023)

[21] Touvron, H., Lavril, T., Izacard, G., Martinet, X., Lachaux, M.-A., Lacroix, T., Rozière, B., Goyal, N., Hambro, E., Azhar, F., et al.: Llama: Open and efficient foundation language models. arXiv preprint arXiv:2302.13971 (2023)

[22] Xiao, L., Chen, X.: Enhancing llm with evolutionary fine tuning for news summary generation. arXiv preprint arXiv:2307.02839 (2023)

[23] Jawahar, G., Abdul-Mageed, M., Lakshmanan, L., Ding, D.: LLM performance predictors are good initializers for architecture search. In: Ku, L.-W., Martins, A., Srikumar, V. (eds.) Findings of the Association for Computational Linguistics ACL 2024, pp. 10540–10560. Association for Computational Linguistics, Bangkok, Thailand and virtual meeting (2024). https://doi.org/10.18653/v1/2024.findings-acl.627 . https://aclanthology.org/2024.findings-acl.627

[24] Kumar, V., Gleyzer, L., Kahana, A., Shukla, K., Karniadakis, G.E.: Mycrunchgpt: A llm assisted framework for scientific machine learning. Journal of Machine Learning for Modeling and Computing **4**(4) (2023)

[25] Varghese, J., Chapiro, J.: Chatgpt: The transformative influence of generative ai on science and healthcare. Journal of Hepatology (2023)

[26] Peters, M.E., Neumann, M., Iyyer, M., Gardner, M., Clark, C., Lee, K., Zettlemoyer, L.: Deep contextualized word representations. In: Walker, M., Ji, H., Stent, A. (eds.) Proceedings of the 2018 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long Papers), pp. 2227–2237. Association for Computational Linguistics, New Orleans, Louisiana (2018). https://doi.org/10.18653/v1/N18-1202 . https://aclanthology.org/N18-1202

[27] Petukhova, A., Matos-Carvalho, J.P., Fachada, N.: Text clustering with llm embeddings. arXiv preprint arXiv:2403.15112 (2024)

[28] Keraghel, I., Morbieu, S., Nadif, M.: Beyond words: a comparative analysis of llm embeddings for effective clustering. In: International Symposium on Intelligent Data Analysis, pp. 205–216 (2024). Springer

[29] Asudani, D.S., Nagwani, N.K., Singh, P.: Impact of word embedding models on text analytics in deep learning environment: a review. Artificial intelligence review **56**(9), 10345–10425 (2023)

[30] Cao, Z.-J., Gao, G.: Multi-omics single-cell data integration and regulatory inference with graph-linked embedding. Nature Biotechnology **40**(10), 1458–1466 (2022)

[31] Huang, K., Lopez, R., Hütter, J.-C., Kudo, T., Rios, A., Regev, A.: Sequential optimal experimental design of perturbation screens guided by multi-modal priors. In: International Conference on Research in Computational Molecular Biology, pp. 17–37 (2024). Springer

[32] Zhang, Y., Li, Y., Cui, L., Cai, D., Liu, L., Fu, T., Huang, X., Zhao, E., Zhang, Y., Chen, Y., et al.: Siren's song in the ai ocean: A survey on hallucination in

large language models. arXiv preprint arXiv:2309.01219 (2023)

[33] Radford, A., Wu, J., Child, R., Luan, D., Amodei, D., Sutskever, I., *et al.*: Language models are unsupervised multitask learners. OpenAI blog **1**(8), 9 (2019)

[34] Jiang, A.Q., Sablayrolles, A., Mensch, A., Bamford, C., Chaplot, D.S., Casas, D., Bressand, F., Lengyel, G., Lample, G., Saulnier, L., Lavaud, L.R., Lachaux, M.-A., Stock, P., Scao, T.L., Lavril, T., Wang, T., Lacroix, T., Sayed, W.E.: Mistral 7B (2023)

[35] Luo, R., Sun, L., Xia, Y., Qin, T., Zhang, S., Poon, H., Liu, T.-Y.: Biogpt: generative pre-trained transformer for biomedical text generation and mining. Briefings in Bioinformatics **23**(6), 409 (2022)

[36] Models, C.: Model card and evaluations for claude models (2023). https://www-files.anthropic.com/production/images/Model-Card-Claude-2.pdf

[37] Anil, R., Dai, A.M., Firat, O., Johnson, M., Lepikhin, D., Passos, A., Shakeri, S., Taropa, E., Bailey, P., Chen, Z., Chu, E., Clark, J.H., Shafey, L.E., Huang, Y., Meier-Hellstern, K., Mishra, G., Moreira, E., Omernick, M., Robinson, K., Ruder, S., Tay, Y., Xiao, K., Xu, Y., Zhang, Y., Abrego, G.H., Ahn, J., Austin, J., Barham, P., Botha, J., Bradbury, J., Brahma, S., Brooks, K., Catasta, M., Cheng, Y., Cherry, C., Choquette-Choo, C.A., Chowdhery, A., Crepy, C., Dave, S., Dehghani, M., Dev, S., Devlin, J., Díaz, M., Du, N., Dyer, E., Feinberg, V., Feng, F., Fienber, V., Freitag, M., Garcia, X., Gehrmann, S., Gonzalez, L., Gur-Ari, G., Hand, S., Hashemi, H., Hou, L., Howland, J., Hu, A., Hui, J., Hurwitz, J., Isard, M., Ittycheriah, A., Jagielski, M., Jia, W., Kenealy, K., Krikun, M., Kudugunta, S., Lan, C., Lee, K., Lee, B., Li, E., Li, M., Li, W., Li, Y., Li, J., Lim, H., Lin, H., Liu, Z., Liu, F., Maggioni, M., Mahendru, A., Maynez, J., Misra, V., Moussalem, M., Nado, Z., Nham, J., Ni, E., Nystrom, A., Parrish, A., Pellat, M., Polacek, M., Polozov, A., Pope, R., Qiao, S., Reif, E., Richter, B., Riley, P., Ros, A.C., Roy, A., Saeta, B., Samuel, R., Shelby, R., Slone, A., Smilkov, D., So, D.R., Sohn, D., Tokumine, S., Valter, D., Vasudevan, V., Vodrahalli, K., Wang, X., Wang, P., Wang, Z., Wang, T., Wieting, J., Wu, Y., Xu, K., Xu, Y., Xue, L., Yin, P., Yu, J., Zhang, Q., Zheng, S., Zheng, C., Zhou, W., Zhou, D., Petrov, S., Wu, Y.: PaLM 2 Technical Report (2023)

[38] Hao, Y., Hao, S., Andersen-Nissen, E., Mauck, W.M., Zheng, S., Butler, A., Lee, M.J., Wilk, A.J., Darby, C., Zager, M., *et al.*: Integrated analysis of multimodal single-cell data. Cell **184**(13), 3573–3587 (2021)

[39] Safran, M., Dalah, I., Alexander, J., Rosen, N., Iny Stein, T., Shmoish, M., Nativ, N., Bahir, I., Doniger, T., Krug, H., et al.: Genecards version 3: the human gene integrator. Database **2010** (2010)

[40] Papineni, K., Roukos, S., Ward, T., Zhu, W.-J.: Bleu: a method for automatic

evaluation of machine translation. In: Proceedings of the 40th Annual Meeting of the Association for Computational Linguistics, pp. 311–318 (2002)

[41] Freitag, M., Foster, G., Grangier, D., Ratnakar, V., Tan, Q., Macherey, W.: Experts, errors, and context: A large-scale study of human evaluation for machine translation. Transactions of the Association for Computational Linguistics **9**, 1460–1474 (2021)

[42] Suzgun, M., Kalai, A.T.: Meta-prompting: Enhancing language models with task-agnostic scaffolding. arXiv preprint arXiv:2401.12954 (2024)

[43] Wei, J., Wang, X., Schuurmans, D., Bosma, M., Xia, F., Chi, E., Le, Q.V., Zhou, D., *et al.*: Chain-of-thought prompting elicits reasoning in large language models. Advances in neural information processing systems **35**, 24824–24837 (2022)

[44] Ashburner, M., Ball, C.A., Blake, J.A., Botstein, D., Butler, H., Cherry, J.M., Davis, A.P., Dolinski, K., Dwight, S.S., Eppig, J.T., *et al.*: Gene ontology: tool for the unification of biology. Nature genetics **25**(1), 25–29 (2000)

[45] Aleksander, S.A., Balhoff, J., Carbon, S., Cherry, J.M., Drabkin, H.J., Ebert, D., Feuermann, M., Gaudet, P., Harris, N.L., *et al.*: The gene ontology knowledgebase in 2023. Genetics **224**(1), 031 (2023)

[46] Fang, Z., Liu, X., Peltz, G.: Gseapy: a comprehensive package for performing gene set enrichment analysis in python. Bioinformatics **39**(1), 757 (2023)

[47] Krämer, A., Green, J., Pollard Jr, J., Tugendreich, S.: Causal analysis approaches in ingenuity pathway analysis. Bioinformatics **30**(4), 523–530 (2014)

[48] McInnes, L., Healy, J., Saul, N., Großberger, L.: Umap: Uniform manifold approximation and projection. Journal of Open Source Software **3**(29), 861 (2018) https://doi.org/10.21105/joss.00861

[49] Luecken, M.D., Büttner, M., Chaichoompu, K., Danese, A., Interlandi, M., Müller, M.F., Strobl, D.C., Zappia, L., Dugas, M., Colomé-Tatché, M., *et al.*: Benchmarking atlas-level data integration in single-cell genomics. Nature methods **19**(1), 41–50 (2022)

[50] Martin, F.J., Amode, M.R., Aneja, A., Austine-Orimoloye, O., Azov, A.G., Barnes, I., Becker, A., Bennett, R., Berry, A., Bhai, J., *et al.*: Ensembl 2023. Nucleic acids research **51**(D1), 933–941 (2023)

[51] Soneson, C., Robinson, M.D.: Bias, robustness and scalability in single-cell differential expression analysis. Nature methods **15**(4), 255–261 (2018)

[52] Armingol, E., Officer, A., Harismendy, O., Lewis, N.E.: Deciphering cell–cell interactions and communication from gene expression. Nature Reviews Genetics

22(2), 71–88 (2021)

[53] Kiselev, V.Y., Kirschner, K., Schaub, M.T., Andrews, T., Yiu, A., Chandra, T., Natarajan, K.N., Reik, W., Barahona, M., Green, A.R., *et al.*: Sc3: consensus clustering of single-cell rna-seq data. Nature methods **14**(5), 483–486 (2017)

[54] Lopez, R., Regier, J., Cole, M.B., Jordan, M.I., Yosef, N.: Deep generative modeling for single-cell transcriptomics. Nature methods **15**(12), 1053–1058 (2018)

[55] Zhu, B., Chen, S., Bai, Y., Chen, H., Liao, G., Mukherjee, N., Vazquez, G., McIlwain, D.R., Tzankov, A., Lee, I.T., *et al.*: Robust single-cell matching and multimodal analysis using shared and distinct features. Nature Methods **20**(2), 304–315 (2023)

[56] Korsunsky, I., Millard, N., Fan, J., Slowikowski, K., Zhang, F., Wei, K., Baglaenko, Y., Brenner, M., Loh, P.-r., Raychaudhuri, S.: Fast, sensitive and accurate integration of single-cell data with harmony. Nature methods **16**(12), 1289–1296 (2019)

[57] Haghverdi, L., Lun, A.T., Morgan, M.D., Marioni, J.C.: Batch effects in single-cell rna-sequencing data are corrected by matching mutual nearest neighbors. Nature biotechnology **36**(5), 421–427 (2018)

[58] Stephenson, E., Reynolds, G., Botting, R.A., Calero-Nieto, F.J., Morgan, M.D., Tuong, Z.K., Bach, K., Sungnak, W., Worlock, K.B., Yoshida, M., *et al.*: Single-cell multi-omics analysis of the immune response in covid-19. Nature medicine **27**(5), 904–916 (2021)

[59] Sikkema, L., Ramírez-Suástegui, C., Strobl, D.C., Gillett, T.E., Zappia, L., Madissoon, E., Markov, N.S., Zaragosi, L.-E., Ji, Y., Ansari, M., et al.: An integrated cell atlas of the lung in health and disease. Nature Medicine, 1–15 (2023)

[60] Litviňuková, M., Talavera-López, C., Maatz, H., Reichart, D., Worth, C.L., Lindberg, E.L., Kanda, M., Polanski, K., Heinig, M., Lee, M., *et al.*: Cells of the adult human heart. Nature **588**(7838), 466–472 (2020)

[61] Miao, Z., Humphreys, B.D., McMahon, A.P., Kim, J.: Multi-omics integration in the age of million single-cell data. Nature Reviews Nephrology **17**(11), 710–724 (2021)

[62] Zeng, H.: What is a cell type and how to define it? Cell **185**(15), 2739–2755 (2022)

[63] LeCun, Y., Bengio, Y., Hinton, G.: Deep learning. nature **521**(7553), 436–444 (2015)

[64] Chen, T., Kornblith, S., Norouzi, M., Hinton, G.: A simple framework for contrastive learning of visual representations. In: International Conference on Machine Learning, pp. 1597–1607 (2020). PMLR

[65] Baron, M., Veres, A., Wolock, S.L., Faust, A.L., Gaujoux, R., Vetere, A., Ryu, J.H., Wagner, B.K., Shen-Orr, S.S., Klein, A.M., *et al.*: A single-cell transcriptomic map of the human and mouse pancreas reveals inter-and intra-cell population structure. Cell systems **3**(4), 346–360 (2016)

[66] Muraro, M.J., Dharmadhikari, G., Grün, D., Groen, N., Dielen, T., Jansen, E., Van Gurp, L., Engelse, M.A., Carlotti, F., De Koning, E.J., *et al.*: A single-cell transcriptome atlas of the human pancreas. Cell systems **3**(4), 385–394 (2016)

[67] Xin, Y., Kim, J., Okamoto, H., Ni, M., Wei, Y., Adler, C., Murphy, A.J., Yancopoulos, G.D., Lin, C., Gromada, J.: Rna sequencing of single human islet cells reveals type 2 diabetes genes. Cell metabolism **24**(4), 608–615 (2016)

[68] Lawlor, N., George, J., Bolisetty, M., Kursawe, R., Sun, L., Sivakamasundari, V., Kycia, I., Robson, P., Stitzel, M.L.: Single-cell transcriptomes identify human islet cell signatures and reveal cell-type–specific expression changes in type 2 diabetes. Genome research **27**(2), 208–222 (2017)

[69] Li, Y., Ren, P., Dawson, A., Vasquez, H.G., Ageedi, W., Zhang, C., Luo, W., Chen, R., Li, Y., Kim, S., *et al.*: Single-cell transcriptome analysis reveals dynamic cell populations and differential gene expression patterns in control and aneurysmal human aortic tissue. Circulation **142**(14), 1374–1388 (2020)

[70] Wang, Y., Liu, T., Zhao, H.: Respan: a powerful batch correction model for scrna-seq data through residual adversarial networks. Bioinformatics **38**(16), 3942–3949 (2022)

[71] Pullin, J.M., McCarthy, D.J.: A comparison of marker gene selection methods for single-cell rna sequencing data. Genome Biology **25**(1), 56 (2024)

[72] Granja, J.M., Klemm, S., McGinnis, L.M., Kathiria, A.S., Mezger, A., Corces, M.R., Parks, B., Gars, E., Liedtke, M., Zheng, G.X., *et al.*: Single-cell multi-omic analysis identifies regulatory programs in mixed-phenotype acute leukemia. Nature biotechnology **37**(12), 1458–1465 (2019)

[73] Wilk, A.J., Lee, M.J., Wei, B., Parks, B., Pi, R., Martínez-Colón, G.J., Ranganath, T., Zhao, N.Q., Taylor, S., Becker, W., *et al.*: Multi-omic profiling reveals widespread dysregulation of innate immunity and hematopoiesis in covid-19. Journal of Experimental Medicine **218**(8), 20210582 (2021)

[74] Liu, T., Li, K., Wang, Y., Li, H., Zhao, H.: Evaluating the utilities of large language models in single-cell data analysis. bioRxiv, 2023–09 (2023)

[75] Li, Y.Y., An, J., Jones, S.J.: A computational approach to finding novel targets for existing drugs. PLoS computational biology **7**(9), 1002139 (2011)

[76] Kumar, R., Saha, P.: A review on artificial intelligence and machine learning to improve cancer management and drug discovery. International Journal for Research in Applied Sciences and Biotechnology **9**(3), 149–156 (2022)

[77] Abdelazim, M.A., Nasr, M.M., Ead, W.M.: A survey on classification analysis for cancer genomics: Limitations and novel opportunity in the era of cancer classification and target therapies. Annals of Tropical Medicine and Public Health **23**, 24 (2020)

[78] Spudich, J.A.: Hypertrophic and dilated cardiomyopathy: four decades of basic research on muscle lead to potential therapeutic approaches to these devastating genetic diseases. Biophysical journal **106**(6), 1236–1249 (2014)

[79] Chaffin, M., Papangeli, I., Simonson, B., Akkad, A.-D., Hill, M.C., Arduini, A., Fleming, S.J., Melanson, M., Hayat, S., Kost-Alimova, M., *et al.*: Single-nucleus profiling of human dilated and hypertrophic cardiomyopathy. Nature **608**(7921), 174–180 (2022)

[80] Pagiatakis, C., Di Mauro, V.: The emerging role of epigenetics in therapeutic targeting of cardiomyopathies. International Journal of Molecular Sciences **22**(16), 8721 (2021)

[81] Fang, C., Lv, Z., Yu, Z., Wang, K., Xu, C., Li, Y., Wang, Y.: Exploration of dilated cardiomyopathy for biomarkers and immune microenvironment: Evidence from rna-seq. BMC Cardiovascular Disorders **22**(1), 320 (2022)

[82] Feng, Y., Cai, L., Hong, W., Zhang, C., Tan, N., Wang, M., Wang, C., Liu, F., Wang, X., Ma, J., *et al.*: Rewiring of 3d chromatin topology orchestrates transcriptional reprogramming and the development of human dilated cardiomyopathy. Circulation **145**(22), 1663–1683 (2022)

[83] Balashanmugam, M.V., Shivanandappa, T.B., Nagarethinam, S., Vastrad, B., Vastrad, C.: Analysis of differentially expressed genes in coronary artery disease by integrated microarray analysis. Biomolecules **10**(1), 35 (2019)

[84] Barrangou, R., Doudna, J.A.: Applications of crispr technologies in research and beyond. Nature biotechnology **34**(9), 933–941 (2016)

[85] Davies, R.R., Kaple, R.K., Mandapati, D., Gallo, A., Botta Jr, D.M., Elefteriades, J.A., Coady, M.A.: Natural history of ascending aortic aneurysms in the setting of an unreplaced bicuspid aortic valve. The Annals of thoracic surgery **83**(4), 1338–1344 (2007)

[86] Moreno-Loshuertos, R., Movilla, N., Marco-Brualla, J., Soler-Agesta, R., Ferreira, P., Enríquez, J.A., Fernández-Silva, P.: A mutation in mouse mt-atp6 gene induces respiration defects and opposed effects on the cell tumorigenic phenotype. International Journal of Molecular Sciences **24**(2), 1300 (2023)

[87] Stendel, C., Neuhofer, C., Floride, E., Yuqing, S., Ganetzky, R.D., Park, J., Freisinger, P., Kornblum, C., Kleinle, S., Schöls, L., et al.: Delineating mt-atp6-associated disease: From isolated neuropathy to early onset neurodegeneration. Neurology Genetics **6**(1) (2020)

[88] Chang, M.T., Shanahan, F., Nguyen, T.T.T., Staben, S.T., Gazzard, L., Yamazoe, S., Wertz, I.E., Piskol, R., Yang, Y.A., Modrusan, Z., *et al.*: Identifying transcriptional programs underlying cancer drug response with trace-seq. Nature Biotechnology **40**(1), 86–93 (2022)

[89] Green, T.D., Peidli, S., Shen, C., Gross, T., Min, J., Garda, S., Taylor-King, J.P., Marks, D.S., Luna, A., Blüthgen, N., *et al.*: scperturb: Information resource for harmonized single-cell perturbation data. In: NeurIPS 2022 Workshop on Learning Meaningful Representations of Life (2022)

[90] Dong, M., Wang, B., Wei, J., O. Fonseca, A.H., Perry, C.J., Frey, A., Ouerghi, F., Foxman, E.F., Ishizuka, J.J., Dhodapkar, R.M., et al.: Causal identification of single-cell experimental perturbation effects with cinema-ot. Nature Methods, 1–11 (2023)

[91] Lotfollahi, M., Wolf, F.A., Theis, F.J.: scgen predicts single-cell perturbation responses. Nature methods **16**(8), 715–721 (2019)

[92] Dixit, A., Parnas, O., Li, B., Chen, J., Fulco, C.P., Jerby-Arnon, L., Marjanovic, N.D., Dionne, D., Burks, T., Raychowdhury, R., *et al.*: Perturb-seq: dissecting molecular circuits with scalable single-cell rna profiling of pooled genetic screens. cell **167**(7), 1853–1866 (2016)

[93] Lotfollahi, M., Klimovskaia Susmelj, A., De Donno, C., Hetzel, L., Ji, Y., Ibarra, I.L., Srivatsan, S.R., Naghipourfar, M., Daza, R.M., Martin, B., et al.: Predicting cellular responses to complex perturbations in high-throughput screens. Molecular Systems Biology, 11517 (2023)

[94] Roohani, Y., Huang, K., Leskovec, J.: Predicting transcriptional outcomes of novel multigene perturbations with gears. Nature Biotechnology, 1–9 (2023)

[95] Burkhardt, D., Benz, A., Lieberman, R., Gigante, S., Chow, A., Holbrook, R., Cannoodt, R., Luecken, M.: Open problems – single-cell perturbations. Kaggle, (2023)

[96] Kipf, T.N., Welling, M.: Semi-supervised classification with graph convolutional networks. In: International Conference on Learning Representations (2017).

https://openreview.net/forum?id=SJU4ayYgl

[97] Replogle, J.M., Saunders, R.A., Pogson, A.N., Hussmann, J.A., Lenail, A., Guna, A., Mascibroda, L., Wagner, E.J., Adelman, K., Lithwick-Yanai, G., *et al.*: Mapping information-rich genotype-phenotype landscapes with genome-scale perturb-seq. Cell **185**(14), 2559–2575 (2022)

[98] Norman, T.M., Horlbeck, M.A., Replogle, J.M., Ge, A.Y., Xu, A., Jost, M., Gilbert, L.A., Weissman, J.S.: Exploring genetic interaction manifolds constructed from rich single-cell phenotypes. Science **365**(6455), 786–793 (2019)

[99] Adamson, B., Norman, T.M., Jost, M., Cho, M.Y., Nuñez, J.K., Chen, Y., Villalta, J.E., Gilbert, L.A., Horlbeck, M.A., Hein, M.Y., *et al.*: A multiplexed single-cell crispr screening platform enables systematic dissection of the unfolded protein response. Cell **167**(7), 1867–1882 (2016)

[100] Wenteler, A., Occhetta, M., Branson, N., Huebner, M., Curean, V., Dee, W., Connell, W., Hawkins-Hooker, A., Chung, P., Ektefaie, Y., et al.: Perteval-scfm: Benchmarking single-cell foundation models for perturbation effect prediction. bioRxiv, 2024–10 (2024)

[101] Visscher, P.M., Brown, M.A., McCarthy, M.I., Yang, J.: Five years of gwas discovery. The American Journal of Human Genetics **90**(1), 7–24 (2012)

[102] Mimitou, E.P., Lareau, C.A., Chen, K.Y., Zorzetto-Fernandes, A.L., Hao, Y., Takeshima, Y., Luo, W., Huang, T.-S., Yeung, B.Z., Papalexi, E., *et al.*: Scalable, multimodal profiling of chromatin accessibility, gene expression and protein levels in single cells. Nature biotechnology **39**(10), 1246–1258 (2021)

[103] Wolf, F.A., Angerer, P., Theis, F.J.: Scanpy: large-scale single-cell gene expression data analysis. Genome biology **19**, 1–5 (2018)

[104] Chu, S.-K., Zhao, S., Shyr, Y., Liu, Q.: Comprehensive evaluation of noise reduction methods for single-cell rna sequencing data. Briefings in bioinformatics **23**(2), 565 (2022)

[105] Gao, Y., Myers, S., Chen, S., Dligach, D., Miller, T.A., Bitterman, D., Churpek, M., Afshar, M.: When raw data prevails: Are large language model embeddings effective in numerical data representation for medical machine learning applications? arXiv preprint arXiv:2408.11854 (2024)

[106] Musgrave, K., Belongie, S., Lim, S.-N.: Pytorch metric learning. arXiv preprint arXiv:2008.09164 (2020)

[107] Agarap, A.F.: Deep learning using rectified linear units (relu). arXiv preprint arXiv:1803.08375 (2018)

[108] Harris, C.R., Millman, K.J., Van Der Walt, S.J., Gommers, R., Virtanen, P., Cournapeau, D., Wieser, E., Taylor, J., Berg, S., Smith, N.J., *et al.*: Array programming with numpy. Nature **585**(7825), 357–362 (2020)

[109] Gayoso, A., Steier, Z., Lopez, R., Regier, J., Nazor, K.L., Streets, A., Yosef, N.: Joint probabilistic modeling of single-cell multi-omic data with totalvi. Nature methods **18**(3), 272–282 (2021)

[110] Pedregosa, F., Varoquaux, G., Gramfort, A., Michel, V., Thirion, B., Grisel, O., Blondel, M., Prettenhofer, P., Weiss, R., Dubourg, V., *et al.*: Scikit-learn: Machine learning in python. the Journal of machine Learning research **12**, 2825–2830 (2011)

[111] Virtanen, P., Gommers, R., Oliphant, T.E., Haberland, M., Reddy, T., Cournapeau, D., Burovski, E., Peterson, P., Weckesser, W., Bright, J., *et al.*: Scipy 1.0: fundamental algorithms for scientific computing in python. Nature methods **17**(3), 261–272 (2020)

[112] Devlin, J., Chang, M.-W., Lee, K., Toutanova, K.: BERT: Pre-training of deep bidirectional transformers for language understanding. In: Burstein, J., Doran, C., Solorio, T. (eds.) Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers), pp. 4171–4186. Association for Computational Linguistics, Minneapolis, Minnesota (2019). https://doi.org/10.18653/v1/N19-1423 . https://aclanthology.org/N19-1423

[113] Landa, B., Zhang, T.T., Kluger, Y.: Biwhitening reveals the rank of a count matrix. SIAM Journal on Mathematics of Data Science **4**(4), 1420–1446 (2022)

[114] Cuturi, M.: Sinkhorn distances: Lightspeed computation of optimal transport. Advances in neural information processing systems **26** (2013)

[115] Han, X., Wang, R., Zhou, Y., Fei, L., Sun, H., Lai, S., Saadatpour, A., Zhou, Z., Chen, H., Ye, F., *et al.*: Mapping the mouse cell atlas by microwell-seq. Cell **172**(5), 1091–1107 (2018)

[116] Stickels, R.R., Murray, E., Kumar, P., Li, J., Marshall, J.L., Di Bella, D.J., Arlotta, P., Macosko, E.Z., Chen, F.: Highly sensitive spatial transcriptomics at near-cellular resolution with slide-seqv2. Nature biotechnology **39**(3), 313–319 (2021)

[117] Cordero, P., Parikh, V.N., Chin, E.T., Erbilgin, A., Gloudemans, M.J., Shang, C., Huang, Y., Chang, A.C., Smith, K.S., Dewey, F., *et al.*: Pathologic gene network rewiring implicates ppp1r3a as a central regulator in pressure overload heart failure. Nature communications **10**(1), 2760 (2019)