PAPER

Improving dictionary-based named entity recognition with deep learning

Katerina Nastou,[1] Mikaela Koutrouli,[1] Sampo Pyysalo[2] and Lars Juhl Jensen[1]

[1]Novo Nordisk Foundation Center for Protein Research, University of Copenhagen, Blegdamsvej 3, 2200, Copenhagen, Denmark and
[2]TurkuNLP Group, Department of Computing, University of Turku, Turku, Finland
*Corresponding author. lars.juhl.jensen@cpr.ku.dk

Abstract

Dictionary-based named entity recognition (NER) allows terms to be detected in a corpus and normalized to biomedical databases and ontologies. However, adaptation to different entity types requires new high-quality dictionaries and associated lists of blocked names for each type. The latter are so far created by identifying cases that cause many false positives through manual inspection of individual names, a process that scales poorly.

In this work we aim to improve block lists by automatically identifying names to block, based on the context in which they appear. By comparing results of three well-established biomedical NER methods, we generated a dataset of over 12.5 million text spans where the methods agree on the boundaries and type of entity tagged. These were used to generate positive and negative examples of contexts for four entity types, namely genes, diseases, species and chemicals, which were then used to train a Transformer-based model (BioBERT) to perform entity type classification. Application of the best model (F1-score=96.7%) allowed us to generate a list of problematic names that should be blocked. Introducing this into our system doubled the size of the previous list of corpus-wide blocked names. Additionally, we generated a document-specific list that allows ambiguous names to be blocked in specific documents. These changes boosted text mining precision by ∼5.5% on average, and over 8% for chemical and gene names, positively affecting several biological databases utilizing this NER system to extract associations between biomedical entities, like the STRING database, with only a minor drop in recall (0.6%).

Key words: Named Entity Recognition, STRING database, Transformer-based models, Dictionary-based NER

Introduction

Named entity recognition (NER) is an important task in text mining that allows the identification of domain-specific terms or phrases – also known as named entities – in text and their classification into entity types [Nadeau and Sekine, 2007]. In the biomedical domain, named entities include genes, chemicals and diseases among others. NER is a prerequisite for the performance of other text mining tasks that allow the extraction of valuable information from text, such as relation extraction (RE) [Perera et al., 2020].

Dictionary-based methods, which leverage pre-defined dictionaries compiled from extensive collections of terms for each entity type, have been a prominent approach in NER [Leser and Hakenberg, 2005], as they simultaneously allow both the recognition and normalization of identified names in text. However, constructing dictionaries tailored for biomedical text mining demands significant time and expert knowledge, posing challenges in achieving optimal results [Wang et al., 2018].

We have in the past developed a robust, fast dictionary-based tagging engine, the JensenLab `tagger`, which serves as the core of an NER system that is applicable to many biomedical

problems [Jensen, 2016]. The software can process thousands of PubMed abstracts per second and this high speed makes it well-suited for both real-time text mining [Pafilis et al., 2016] and NER in massive text corpora [Westergaard et al., 2018]. Combining this tagger with other dictionaries forms the basis for extraction of associations among genes/proteins [Szklarczyk et al., 2023], small molecule compounds [Szklarczyk et al., 2016], cellular components [Binder et al., 2014], tissues [Palasca et al., 2018], and diseases [Grissa et al., 2022]. Text-mining results obtained from these applications are normalized to identifiers from suitable databases and ontologies [Jeske et al., 2019, Schriml et al., 2012, Ashburner et al., 2000, Wang et al., 2009, Maglott et al., 2000, Hubbard et al., 2002], and are used in several biological databases, which are freely available as a suite of web resources. These databases include the STRING database of protein interactions [Szklarczyk et al., 2023].

Despite its simplicity, dictionary based NER is a powerful method that can perform surprisingly well in the biomedical domain. While software obviously does matter, the most important part of any dictionary-based NER system is the dictionary itself. Adaptation of the NER system to a different

domain requires the construction of a new high-quality dictionary and an associated block list of names. The manual creation of block lists for `tagger` was so far done through manual inspection of the names that occur most frequently in a large text corpus to identify those that would produce numerous false positives and should be disregarded. This process scales poorly, due to the manual labor involved.

The majority of the biomedical text mining community has been using deep learning-based and specifically Transformer-based methods [Miranda et al., 2021] to perform several tasks, including NER, RE and Question-Answering. We wanted to explore how we could also take advantage of these methods to upgrade the Jensenlab suite of web resources. The intrinsic nature of these resources necessitates named entity normalization in conjunction with NER, and a fast and lightweight tagging system allowing weekly updates. Moreover, given the lack of suitable corpora to train deep learning-based methods for named entity recognition and normalization across all entity types, our objective did not center around devising an entirely new method. Rather, we could clearly see a prospect in enhancing the precision of our dictionary-based NER system through the incorporation of state-of-the-art methods.

In this study we present an alternative method for block list generation, which can bring many of the benefits of deep learning to dictionary-based NER, without sacrificing the advantages of the latter. To address the limitations of manual block list creation, we automated this crucial step by unifying and comparing results of three biomedical NER methods. We sought to create a large comprehensive dataset of text spans where different NER methods agreed on entity boundaries and types. This consensus dataset served as the foundation for generating both positive and negative examples for four entity types: genes or gene products, diseases, species, and chemicals. We then trained a Transformer-based model, specifically BioBERT [Lee et al., 2019], to perform entity type classification using that dataset. Ultimately we employed this model to accurately identify problematic names for blocking, resulting in a substantial expansion of the existing block list, ensuring a precision enhancement without compromising recall. Additionally, we created document-specific lists to address ambiguous name occurrences within specific documents. The successful implementation of these strategies significantly enhanced the quality of all web resources populated with associations generated by `tagger`. Moreover, this work serves as a guide for automating the identification of names to be blocked in various dictionary-based text mining systems, setting a precedent for more efficient and accurate NER in the biomedical domain.

Materials and methods

The dictionary-based `tagger`

As mentioned above text mining is integral to a suite of web resources with associations among biomedical entities [Jensen, 2016]. The initial step in extracting these associations from the literature involves the recognition of biomedical entities by the `tagger`, laying the foundation for relation extraction (RE). It is evident that the quality of the NER system directly impacts the quality of the generated associations.

Blocking and allowing names for the `tagger` is a key step to ensuring good quality. It operates across two levels: global (i.e. corpus-wide) and local (i.e. document-specific), utilizing two distinct methods for incorporating terms: automatic and

manual additions. The generation of manual lists involves meticulous inspection of the most frequent names in the literature before addition, while that of automatic lists does not involve any human intervention. Both lists are combined to create a final list, favoring the manually curated list in case of conflicting overlaps between the two.

Operations on the global level involve both global blocking to identify names generally unsuitable for text mining, such as "Bad" or "ask", which should be altogether removed for increased precision, and global allowing to safeguard names verified and accurately labeled as biomedical entity names of the correct type (e.g. "ATM"). Furthermore, the globally curated allowing functionality acts as a protection against potential inaccuracies from an auto-generated global block list. In local contexts, blocking or allowing decisions are tailored to the document at hand. For instance, "wingless" predominantly signifies a protein, yet in select instances, it refers to apterous insects, and local blocking in these instances is preferred to incorrect tagging. Similarly, a name like "toy", which should be blocked globally, might be allowed in a specific document where it refers to the transcription factor "toy". Despite the potential for both manual and automatic approaches in local contexts, considering the amount of effort these require, only automatic additions of names to the local list make sense.

The `tagger` functions in a case-insensitive manner and allows for arbitrary insertion or deletion of spaces and hyphens in the names and punctuation characters before or after them, both important for capturing the orthographic variation of biomedical named entities [Pafilis et al., 2013]. By contrast, all lists mentioned above function in a case-sensitive manner, affecting only specific versions of a name when added therein (e.g. adding "bad" will have no effect on the tagging of "BAD").

During dictionary generation, clashes may arise, such as "NO" existing as a synonym in both the gene and chemical dictionaries. To resolve these clashes, a preference hierarchy based on source quality is implemented during the generation of the dictionaries for tagger. Diseases hold precedence over species, followed by genes or gene products, and finally chemicals. This hierarchy dictates the in the example above, "NO" will be tagged as a gene unless otherwise filtered. The resolution of such conflicts necessitates specific entity type filtering during dictionary creation. By employing filters, conflicts like overlapping gene and chemical names for "NO" can be addressed, ensuring accurate tagging.

The trust hierarchy in dictionaries and the inherent complexity of manually integrating terms for resolving dictionary clashes emphasize the significance of automatically blocking names after dictionaries have been built. This automatic process stands as the primary approach for enhancing the precision of `tagger` results, presenting a streamlined and effective means for optimizing accuracy for both NER and RE.

For more details on dictionary generation for the `tagger`, please refer to Jensen [2016].

Consensus dataset

The first step towards creating a method for automatically detecting problematic names in a biomedical dictionary is to identify high quality examples to train the method on. These come in the form of a labelled dataset that allows supervised training for the task of biomedical entity type classification. To ensure that such a dataset has high coverage, a very large pool of both positive and negative examples is required. Since

obtaining enough examples of properly labelled named entities via manual annotation is prohibitive — due to the time and resource demands of the effort — we opted for an automatic approach, which can provide a dataset that is simultaneously large and of high quality. To this end, we compared the NER results of PubTator [Wei et al., 2019], EVEX [Van Landeghem et al., 2013] and `tagger` [Jensen, 2016], thus identifying millions of text spans where all three methods agree on the boundaries and the type of entity tagged.

As mentioned, `tagger` is a dictionary-based method, with a dictionary based on Ensembl [Hubbard et al., 2002], Refseq [Maglott et al., 2000], PubChem [Wang et al., 2009], NCBI taxonomy [Schoch et al., 2020], and Disease Ontology [Schriml et al., 2012]. On the other hand, PubTator encompasses different text-mining tools [Huang et al., 2011, Wei et al., 2012, Leaman et al., 2013] to detect biomedical entities following different nomenclatures than `tagger`, while EVEX uses the Turku Event Extraction System [Björne et al., 2010] together with BANNER [Leaman and Gonzalez, 2008] and the McClosky-Charniak Parser [McClosky and Charniak, 2008]. The selection of the three systems is appropriate for creating a highly precise consensus dataset of training examples for genes or gene product (ggp), disease (dis), species (org), and chemical (che) named entities, as these methods rely on different architectures and/or nomenclatures to produce NER results for the four entity types they have in common.

To train a model for classifying entities, we designed a dataset consisting of biomedical entities within their textual context, all labeled with the biomedical entity's type. To achieve this, we constructed positive examples using the consensus results of all three aforementioned NER methods, i.e. matches where all three methods agree on boundaries and entity type, comprising 200-word contexts around instances of the four designated entity types (100 words to the left and right of each entity mention). At the same time, we compiled a negative set from contexts around nouns and noun phrases where none of the methods produced a match corresponding to any of the targeted named entity types (neg class).

Experimental setup

The task of entity type classification has clear analogies to NER, an area where the current state-of-the-art methods predominantly utilize models based on the Transformer architecture [Vaswani et al., 2017]. These models are initially pre-trained on large collections of text to produce a general language model, and can later be fine-tuned to perform specific tasks, such as NER. We have selected the cased BioBERT base model [Lee et al., 2019], a biomedical domain-specific pre-trained deep language representation model based on BERT [Devlin et al., 2018], to train a multi-class entity type classifier on the consensus dataset described above. This model has been pre-trained on the entire biomedical literature and has already shown good performance in NER tasks for biomedical texts.

BERT-based models are pre-trained using masked language modelling [Devlin et al., 2018], i.e. hiding certain words with a special mask token and asking the model to fill in the gaps. We have leveraged this feature of BioBERT to train our classifier to learn only how the contexts around each biomedical entity type look, without access to the text of the named entity mentions themselves. Specifically, we masked all entity mentions of interest in the consensus set, and set the label for each example based on the masked entity, as shown in Table 1. We have generated two datasets with the format described above: a small

Table 1. Examples of the labelled set used to train the model

Example	Label
Steroid excretion in patients receiving [MASK] compounds.	che
When [MASK] becomes mutated, it loses its function, resulting in abnormal cell proliferation.	ggp

che: chemical, ggp: gene or gene product

dataset with 187,500 examples and a large dataset of 12,562,500 examples, available through Zenodo.

We fine-tuned the model to classify the examples described above as belonging to one of the five training classes (ggp, org, dis, che, neg) with the output softmax [Bridle, 1990] layer configured to transform the contextualized representations generated by the BERT model into segment-level probabilities for each class. To select the best model, we tuned the hyperparameters of the BioBERT model through a grid search to find the best combination of values for the learning rate (5e-5, 3e-5, 2e-5, 1e-5, and 5e-6), mini batch size (32 and 64), number of epochs (2, 3, and 4), maximum sequence length (256), and context size (200). The values in parentheses for each parameter were those suggested in the BioBERT publication and some extensions to those, based on our initial experiments. The experiments were repeated four times and the results are expressed as a mean and standard deviation of the F1-score (micro-averaged over all labels in the sets). The abovementioned experiments were run using the small dataset described above by assigning 125,000 examples to the training set and 62,500 to the development set. The hyperparameters producing the best total mean F1-score on the development set were selected for training a model on the large dataset — 12.5 million examples were used for training and 62,500 to calculate the test set performance on this set.

Block List generation and prediction

To generate automated block lists, we used all PubMed abstracts (as of August 2022) and all full-texts available in the PMC BioC text mining collection [Comeau et al., 2019] (as of April 2022). We then ran `tagger` using the manually curated block lists only. We generated examples for all contexts surrounding the `tagger` matches of the four positive classes, and we used the best-performing model for entity type prediction on these examples.

As explained above, for each example, the classifier produces a probabilistic score of belonging to each class (including the negative class) and, based on these, we can calculate the score of not belonging to the `tagger`-assigned class $P(\neg C)$, where C stands for class. To generate a corpus-wide block list, we do an unweighted score average of all $P(\neg C)$ within each document for each name. We then average these document-level scores across the entire corpus — considering that matches in different documents are independent — and generate a single score per name of not belonging to the `tagger`-assigned class across the entire literature. To generate the global block list we had an additional requirement, that there are at least two documents with one mention for each name. Afterwards, we manually inspected the lists to identify the thresholds that we would use to add names to the global block list, since those could be different for each class.

The fact that we had a probabilistic score for each match allowed us to explore the use of local (document-level) predictions to resolve ambiguous names, by aggregating within-document scores for each name. This allowed us to test both the generation of lists of terms that could be locally blocked or allowed — the latter only for terms that are automatically blocked globally. Once again, the scores that would serve as thresholds for inclusion in these lists had to be manually identified by inspecting random samples of the lists. In order to identify names that would be locally allowed we calculated a ratio based on the formula below:

$$ratio = \frac{P(C|N) \cdot P(C|L)}{P(\neg C|N) \cdot P(\neg C|L)} \qquad (1)$$

where C stands for class and corresponds to the five entity types used to train the classifier (gene or gene product, disease, species, chemical and negative), $P(C|N)$ is the global probabilistic score of a term belonging to that specific class, $P(C|L)$ is the local probabilistic score estimate for the term belonging to that class, and $\neg C$ is "not C", so $P(\neg C|N) = (1 - P(C|N))$ and $P(\neg C|L) = (1 - P(C|L))$. This formula allows us to override even very high global confidence scores when trying to add names to the local allow list. The calculation of the ratio for identifying named to be local blocked is analogous to (1).

Evaluation

To evaluate the effects of block lists we generated four sets of results by performing four different `tagger` runs:

1. run with a combined automatically generated and manually curated block list (***curated+auto***): This run involved using a combination of both automatically generated and manually curated block lists for `tagger` and resembles what is currently done for Jensenlab web resources.
2. run with manually curated block lists (***curated_only***): in this run, only the manually curated block list was used.
3. run with automatically generated block lists (***auto_only***): in this run we only used block lists that were automatically generated from the fine-tuned BioBERT model. In order to generate these lists, we had to run `tagger` without any block list (only the built-in `tagger` regular expressions were used to block names) and we repeated the process for block list generation, using the thresholds that we determined from the process described in the previous section.
4. run without any block list (***no_block_list***): this involved running `tagger` without utilizing any block list. We also adapted the tagger code to exclude the use of built-in regular expressions. The adapted code is provided through Zenodo.

We conducted evaluations using two distinct approaches. Firstly, since the main incentive for updating the block lists is improving the Jensenlab suite of web resources, we aimed to assess the impact of block lists in co-occurrence-based relation extraction. Specifically, we evaluated the results from the four runs above against two datasets: the KEGG database [Kanehisa and Goto, 2000] gold standard used for evaluations by the STRING database [Szklarczyk et al., 2023], and the gold standard of protein-disease associations used by the DISEASES database [Grissa et al., 2022].

To evaluate the direct impact of automatically adding names in the block lists on NER, we calculated the precision and

relative recall change in a subset of `tagger` matches from the (***curated+auto***) and (***curated_only***). Namely, we checked 2000 matches from the (***curated_only***) run (500 from each of the targeted classes) and calculated `tagger`'s precision for each class. Then we selected a number of names for each class that would be automatically blocked and assessed the precision of the method and the relative change in recall as a result from the addition of those terms in the block list.

Results and discussion

Dataset generation and model training

By obtaining the consensus results of `tagger`, PubTator and EVEX, we generated a dataset with millions of text spans of positive and negative examples, which we split into a small and a large set as described in 2.3. The number of examples were balanced between the 5 classes, as shown in Table 2 for the training datasets. A manual inspection of 500 terms (100 of each class) from this dataset allowed us to calculate its precision, which was found to be 99.8% (Supplementary Table 1), showcasing the high quality of this dataset.

Table 2. Number of examples for each class in the large and small training sets

Entity type	Number of examples	
	large training set	small training set
Gene or gene product	2,292,475	23,105
Chemical	3,705,213	37,205
Disease	2,083,848	20,795
Species	1,918,464	19,402
Negative	2,500,000	24,493
Total	12,500,000	125,000

Our hyperparameter grid search on the small set revealed that the BioBERT$_{base}$ model with a learning rate of 2^{-5} and a batch size of 32 was the best model trained on the set of 125,000 examples, with a mean F-score of 94.83% (SD=0.0356%) on the development set. We used this set of hyperparameters to train a model on the large set for one epoch. This model achieved an accuracy of 96.67% (SD=0%) on the test set of 62,500 examples and is the one that is further used for all prediction runs. The fine-tuned Tensorflow model on the large set is available through Zenodo.

Block List generation

The `tagger` was executed using the full `tagger` dictionary and only manually curated lists on a corpus of the entire biomedical scientific literature as of August 2022, which consisted of 34,420,049 documents. The dictionary and block list files, as well as the input documents used in this run are available via Zenodo. There were a total of 75,419,774 gene or gene product, 78,615,064 chemical, 39,995,175 disease, and 62,921,879 species matches as a result of that run. For each match, a 200-word context was generated from the input document and classified using the fine-tuned model for entity type prediction.

Using the process detailed in 2.4 we generated an initial set of global block lists in order to identify the probabilistic

Fig. 1. Cumulative True Positive (TP) /False Positive (FP) curves to evaluate human (A) functional protein-protein associations and (B) protein–disease associations. The pairs are ranked based on their significance score. For details on the calculations of this score please refer to Franceschini et al. [2012]. The curves are showing only up to Cumulative FP count of 30,000 pairs.

score thresholds that we should set for the different names not belonging to their `tagger`-assigned class, after manual inspection. We decided to set the threshold empirically, so we looked at the relative densities of positives and negatives around particular threshold values, starting from $P(\neg C) = 0.5$. For genes or gene products, species and chemicals 0.5 was assessed as the best threshold choice, while for diseases the value was raised to 0.85 after exploring several thresholds.

We also had to manually determine the ratios for local allow/block lists. Manual inspection of these lists showed that the generation of good quality lists for diseases and species was not possible, and so we generated lists only for genes or gene products and chemicals, using a ratio (Equation 1) of 1000 as the threshold of inclusion. As for the local allow lists genes or gene products was the only class with good quality lists and the ratio for those was set to a very high value (1^{15}).

Introducing the lists above into the `tagger` dictionary approximately doubled the size of the global list from 148,143 names to 350,862 names. The local (document-specific) allow/block list was introduced for the first time in the text-mining system and contains 155,660 names blocked and 9,611 names allowed in 144,585 and 9,458 documents, respectively. This led to an overall 7.4% reduction in the unique `tagger` matches in the four targeted classes due to the additional names that were blocked (from 693,282,180 matches to 641,606,682 matches). Specifically, for chemicals the reduction is ∼11% (24,026,228 matches removed), for genes or gene products ∼9% (20,551,927 matches removed), for species ∼4% (4,897,488 matches removed), and for diseases ∼2% (2,199,855 matches removed).

Evaluation

To measure the effect of introducing automatically generated block lists on `tagger`'s performance, we run `tagger` using four different setups as described in Methods. We detected all co-occurring protein–protein and protein–disease pairs in the

literature resulting from these four runs and evaluated the performance of co-occurrence-based relation extraction using a functional protein–protein association gold standard from KEGG [Kanehisa and Goto, 2000] and a protein–disease gold standard from DISEASES [Grissa et al., 2022]. The results from this evaluation are shown in Figure 1.

Figure 1 shows that the incorporation of any block list in `tagger` markedly enhances the quality of its generated results. Notably, best results are achieved with our newly proposed method, i.e. by the combination of the automatically generated and the curated block lists. However, the differences between the three block list-including runs are not particularly pronounced. Even when focusing on the initial segments of the curves where more cumulative true positives are expected, the differences are still slim. A potential explanation for this result is that proteins present in the two gold standard datasets tend to be well-studied. This means that they will frequently show up in the literature and that problematic names are thus relatively easy to find both by manual curation (green line) and by the automatic approach (orange line). Consequently, these datasets may not accurately reflect the potential benefits derived from the automated blocking of names, as manual curation will almost certainly give worse coverage of the less studied proteins, which are not in these gold standards. We thus opted to employ a second strategy.

For the second strategy, we assessed the quality of automatically blocked names by manually inspecting them. 3 shows the precision of `tagger` per class when using only the curated block list and the effect of automatic blocking of names, allowing us to see the changes in the dictionary-based system's precision and recall. We will use the gene or gene product numbers from 3 to explain how the calculations for this evaluation are done. To calculate the initial precision of `tagger` for each class we have selected 500 matches from the **curated_only** run for each of the four targeted entity types, did a manual evaluation of the correct assignment to this class

Table 3. Precision and Relative Recall calculations for `tagger`

Entity type	`tagger` precision		Precision change	Relative recall change
	Before	After		
Gene or gene product	89.8%	97.8%	+8.0%	-0.9%
Chemical	76.2%	84.7%	+8.5%	-1.0%
Disease	98.4%	100%	+1.6%	-0.4%
Species	88.4%	91.9%	+3.5%	-0.2%
Macro-average	88.2%	93.6%	+5.4%	-0.6%

by tagger, counted the True Positives (TP) and False Positives (FP) and we calculate the precision as TP/(TP+FP).

The precision of `tagger` when ran using only the curated list is 89.8%. Then we selected 500*0.09=45 matches (9% is the percentage of reduction in `tagger` matches for genes and gene products due to the addition of the automatically blocked terms) and manually checked them to examine whether their addition to the block list was correct. 41 of these matches were correctly blocked and 4 were wrongly blocked. So when we take that into consideration and update the numbers in 500 hits we have: 449-4=445 TP (4 matches are wrongly blocked) and 51-41=10 FP (41 matches are correctly blocked). So the precision after the introduction of the block list is 97.8% and the relative change in recall 4/449=0.9%. That leads to an 8% increase in precision and 0.9% decrease in recall for that class, from the introduction of automatically generated block lists. All results from the manual checks are available in Supplementary Tables 2-9.

Overall, one can clearly see that while the introduction of the automatically generated block lists will inadvertently result in a recall reduction — due to the blocking of some good names — the precision gain clearly overshadows the former. The effect is more evident for classes where dictionary-based NER faces more problems, like chemicals, and very slight in cases where dictionary-based text mining already performs very well, like diseases. These results support our decision to introduce the automatically generated block lists in `tagger`'s dictionaries and have a positive effect for Jensenlab web resources, including the latest version of the STRING database. Additionally, for evaluating the effect of the new block list on dictionary-based species NER, we used the recently published S1000 corpus [Luoma et al., 2023]. The F-score increased by 1% (from 84.7% to 85.7%) in this dataset, which was a result of a 2.6% increase in precision and a 0.4% decrease in recall, showcasing an overall positive effect.

Conclusions

In this work we propose a workflow designed to automate the process of adding names in a block list for dictionary-based NER systems and use the `tagger` to assess the results of this process. We have generated and used a very large dataset of 12.5 million text spans, to generate positive and negative examples of contexts for four entity types, namely genes or gene products, diseases, species and chemicals, and a negative class. By training a highly accurate (F-score=96.7%) Transformer-based entity type classifier on this dataset, and using it to do entity type prediction on all `tagger` matches

resulting from a run with a curated block list, we have managed to effectively double the size of the global block list that `tagger` uses, which would not have been feasible by manual curation. At the same time, we have incorporated for the first time an extensive automated local allow/block list which supports the document-specific resolution of ambiguous names.

Evaluation of the newly generated lists demonstrated positive effects on both dictionary-based NER and RE. Subsequently, these enhanced lists have been directly incorporated into `tagger`, without altering how the tool works or adversely affecting its speed. The improved dictionaries and annotation results are thus made publicly available immediately, through the RESTful APIs that serve the web resources with text mining results produced by the `tagger`, including the widely used STRING database. This integration ensures immediate access to improved resources, advancing the utility and accuracy of `tagger` in several biomedical text mining applications.

Competing interests

No competing interest is declared.

Acknowledgements

We thank the CSC – IT Center for Science for generous computational resources. We would like to thank Dr. Rebecca Kirsch for providing the code to generate Figure 1.

Funding

This project has received funding from Novo Nordisk Foundation (Grant no.: NNF14CC0001) and from the Academy of Finland (Grant no.: 332844). K.N. has received funding from the European Union's Horizon 2020 research and innovation programme under the Marie Sklodowska-Curie (Grant no.: 101023676).

Data availability

All resources introduced in this study are available under open licenses from Zenodo `https://doi.org/10.5281/zenodo.10008720` and GitHub `https://doi.org/10.5281/zenodo.10289360`. Supplementary data are available at *Bioinformatics*.

References

M. Ashburner, C. A. Ball, J. A. Blake, D. Botstein, H. Butler, J. M. Cherry, A. P. Davis, K. Dolinski, S. S. Dwight, J. T. Eppig, et al. Gene ontology: tool for the unification of biology. *Nature genetics*, 25(1):25–29, 2000.

J. X. Binder, S. Pletscher-Frankild, K. Tsafou, C. Stolte, S. I. O'Donoghue, R. Schneider, and L. J. Jensen. Compartments: unification and visualization of protein subcellular localization evidence. *Database*, 2014, 2014.

J. Björne, F. Ginter, S. Pyysalo, J. Tsujii, and T. Salakoski. Complex event extraction at pubmed scale. *Bioinformatics*, 26(12):i382–i390, 2010.

J. S. Bridle. Probabilistic interpretation of feedforward classification network outputs, with relationships to statistical pattern recognition. In *Neurocomputing*, pages 227–236. Springer, 1990.

D. C. Comeau, C.-H. Wei, R. Islamaj Doğan, and Z. Lu. Pmc text mining subset in bioc: about three million full-text articles and growing. *Bioinformatics*, 35(18):3533–3535, 2019.

J. Devlin, M.-W. Chang, K. Lee, and K. Toutanova. Bert: Pre-training of deep bidirectional transformers for language understanding. *arXiv preprint arXiv:1810.04805*, 2018.

A. Franceschini, D. Szklarczyk, S. Frankild, M. Kuhn, M. Simonovic, A. Roth, J. Lin, P. Minguez, P. Bork, C. Von Mering, et al. String v9. 1: protein-protein interaction networks, with increased coverage and integration. *Nucleic acids research*, 41(D1):D808–D815, 2012.

D. Grissa, A. Junge, T. I. Oprea, and L. J. Jensen. Diseases 2.0: a weekly updated database of disease–gene associations from text mining and data integration. *Database*, 2022:baac019, 2022.

M. Huang, J. Liu, and X. Zhu. Genetukit: a software for document-level gene normalization. *Bioinformatics*, 27(7): 1032–1033, 2011.

T. Hubbard, D. Barker, E. Birney, G. Cameron, Y. Chen, L. Clark, T. Cox, J. Cuff, V. Curwen, T. Down, et al. The ensembl genome database project. *Nucleic acids research*, 30(1):38–41, 2002.

L. J. Jensen. One tagger, many uses: Illustrating the power of ontologies in dictionary-based named entity recognition. *bioRxiv*, page 067132, 2016.

L. Jeske, S. Placzek, I. Schomburg, A. Chang, and D. Schomburg. Brenda in 2019: a european elixir core data resource. *Nucleic acids research*, 47(D1):D542–D549, 2019.

M. Kanehisa and S. Goto. Kegg: kyoto encyclopedia of genes and genomes. *Nucleic acids research*, 28(1):27–30, 2000.

R. Leaman and G. Gonzalez. Banner: an executable survey of advances in biomedical named entity recognition. In *Biocomputing 2008*, pages 652–663. World Scientific, 2008.

R. Leaman, R. Islamaj Doğan, and Z. Lu. Dnorm: disease name normalization with pairwise learning to rank. *Bioinformatics*, 29(22):2909–2917, 2013.

J. Lee, W. Yoon, S. Kim, D. Kim, S. Kim, C. H. So, and J. Kang. BioBERT: a pre-trained biomedical language representation model for biomedical text mining. *Bioinformatics*, 36(4):1234–1240, 09 2019. ISSN 1367-4803. doi: 10.1093/bioinformatics/btz682. URL https://doi.org/10.1093/bioinformatics/btz682.

U. Leser and J. Hakenberg. What makes a gene name? named entity recognition in the biomedical literature. *Briefings in bioinformatics*, 6(4):357–369, 2005.

J. Luoma, K. Nastou, T. Ohta, H. Toivonen, E. Pafilis, L. J. Jensen, and S. Pyysalo. S1000: A better taxonomic name corpus for biomedical information extraction. *Bioinformatics*, 39(6):btad369, 2023.

D. R. Maglott, K. S. Katz, H. Sicotte, and K. D. Pruitt. Ncbi's locuslink and refseq. *Nucleic acids research*, 28(1):126–128, 2000.

D. McClosky and E. Charniak. Self-training for biomedical parsing. In *Proceedings of ACL-08: HLT, Short Papers*, pages 101–104, 2008.

A. Miranda, F. Mehryary, J. Luoma, S. Pyysalo, A. Valencia, and M. Krallinger. Overview of drugprot biocreative vii track: quality evaluation and large scale text mining of drug-gene/protein relations. In *Proceedings of the seventh BioCreative challenge evaluation workshop*, 2021.

D. Nadeau and S. Sekine. A survey of named entity recognition and classification. *Lingvisticae Investigationes*, 30(1):3–26, 2007.

E. Pafilis, S. P. Frankild, L. Fanini, S. Faulwetter, C. Pavloudi, A. Vasileiadou, C. Arvanitidis, and L. J. Jensen. The species and organisms resources for fast and accurate identification of taxonomic names in text. *PloS one*, 8(6):e65390, 2013.

E. Pafilis, P. L. Buttigieg, B. Ferrell, E. Pereira, J. Schnetzer, C. Arvanitidis, and L. J. Jensen. Extract: interactive extraction of environment metadata and term suggestion for metagenomic sample annotation. *Database*, 2016, 2016.

O. Palasca, A. Santos, C. Stolte, J. Gorodkin, and L. J. Jensen. Tissues 2.0: an integrative web resource on mammalian tissue expression. *Database*, 2018:bay003, 2018.

N. Perera, M. Dehmer, and F. Emmert-Streib. Named entity recognition and relation detection for biomedical information extraction. *Frontiers in cell and developmental biology*, page 673, 2020.

C. L. Schoch, S. Ciufo, M. Domrachev, C. L. Hotton, S. Kannan, R. Khovanskaya, D. Leipe, R. Mcveigh, K. O'Neill, B. Robbertse, et al. Ncbi taxonomy: a comprehensive update on curation, resources and tools. *Database*, 2020:baaa062, 2020.

L. M. Schriml, C. Arze, S. Nadendla, Y.-W. W. Chang, M. Mazaitis, V. Felix, G. Feng, and W. A. Kibbe. Disease ontology: a backbone for disease semantic integration. *Nucleic acids research*, 40(D1):D940–D946, 2012.

D. Szklarczyk, A. Santos, C. Von Mering, L. J. Jensen, P. Bork, and M. Kuhn. Stitch 5: augmenting protein–chemical interaction networks with tissue and affinity data. *Nucleic acids research*, 44(D1):D380–D384, 2016.

D. Szklarczyk, R. Kirsch, M. Koutrouli, K. Nastou, F. Mehryary, R. Hachilif, A. L. Gable, T. Fang, N. T. Doncheva, S. Pyysalo, et al. The string database in 2023: protein–protein association networks and functional enrichment analyses for any sequenced genome of interest. *Nucleic Acids Research*, 51(D1):D638–D646, 2023.

S. Van Landeghem, J. Björne, C.-H. Wei, K. Hakala, S. Pyysalo, S. Ananiadou, H.-Y. Kao, Z. Lu, T. Salakoski, Y. Van de Peer, et al. Large-scale event extraction from literature with multi-level gene normalization. *PloS one*, 8(4):e55814, 2013.

A. Vaswani, N. Shazeer, N. Parmar, J. Uszkoreit, L. Jones, A. N. Gomez, L. Kaiser, and I. Polosukhin. Attention is all you need. In *Proceedings of the 31st International Conference on Neural Information Processing Systems*, NIPS'17, page 6000–6010, Red Hook, NY, USA, 2017. Curran Associates Inc. ISBN 9781510860964.

X. Wang, C. Yang, and R. Guan. A comparative study for biomedical named entity recognition. *International Journal of Machine Learning and Cybernetics*, 9(3):373–382, 2018.

Y. Wang, J. Xiao, T. O. Suzek, J. Zhang, J. Wang, and S. H. Bryant. Pubchem: a public information system for analyzing bioactivities of small molecules. *Nucleic acids research*, 37 (suppl_2):W623–W633, 2009.

C.-H. Wei, H.-Y. Kao, and Z. Lu. Sr4gn: a species recognition software tool for gene normalization. *PloS one*, 7(6):e38460, 2012.

C.-H. Wei, A. Allot, R. Leaman, and Z. Lu. Pubtator central: automated concept annotation for biomedical full text articles. *Nucleic acids research*, 47(W1):W587–W593, 2019.

D. Westergaard, H.-H. Stærfeldt, C. Tønsberg, L. J. Jensen, and S. Brunak. A comprehensive and quantitative comparison of text-mining in 15 million full-text articles versus their corresponding abstracts. *PLoS computational biology*, 14(2):e1005962, 2018.