VirtuousPocketome: A Computational Tool for Screening Protein-ligand Complexes to Identify Similar Binding Sites

Lorenzo Pallante[1†], Marco Cannariato[1†], Lampros Androutsos[2], Eric A. Zizzi[1], Agorakis Bompotas[3], Xhesika Hada[1], Gianvito Grasso[4], Athanasios Kalogeras[3], Seferina Mavroudi[5], Giacomo di Benedetto[6], Konstantinos Theofilatos[2] and Marco A. Deriu[1*]

[1] Politecnico di Torino, Polito[BIO]MedLab, Department of Mechanical and Aerospace Engineering, Torino, 10129, Italy

[2] InSyBio PC, Patras, 265 04, Greece

[3] Industrial Systems Institute, Athena Research Center, 265 04 Patras, Greece.

[4] Dalle Molle Institute for Artificial Intelligence, Department of Innovative Technologies, Lugano-Viganello, 6962, Switzerland

[5] Department of Nursing, University of Patras, 265 04 Patras, Greece

[6] 7hc srl, Rome, Italy

* marco.deriu@polito.it

[†] These authors contributed equally to this work

ABSTRACT

Protein residues within binding pockets play a critical role in determining the range of ligands that can interact with a protein, influencing its structure and function. Identifying structural similarities in proteins offers valuable insights into their function and activation mechanisms, aiding in predicting protein-ligand interactions, anticipating off-target effects, and facilitating the development of therapeutic agents. Numerous computational methods assessing global or local similarity in protein cavities have emerged, but their utilization is impeded by complexity, impractical automation for amino acid pattern searches, and an inability to evaluate the dynamics of scrutinized protein-ligand systems. Here, we present a general, automatic and unbiased computational pipeline, named *VirtuousPocketome*, aimed at screening huge databases of proteins for similar binding pockets starting from an interested protein-ligand complex. We demonstrate the pipeline's potential by exploring a recently-solved human bitter taste receptor, i.e. the TAS2R46, complexed with strychnine. We pinpointed 145 proteins sharing similar binding sites compared to the analysed bitter taste receptor and the enrichment analysis highlighted the related biological processes, molecular functions and cellular components. This work represents the foundation for future studies aimed at understanding the effective role of tastants outside the gustatory system: this could pave the way towards the rationalization of the diet as a supplement to standard

33 pharmacological treatments and the design of novel tastants-inspired compounds to target other

34 proteins involved in specific diseases or disorders. The proposed pipeline is publicly accessible, can

35 be applied to any protein-ligand complex, and could be expanded to screen any database of protein

36 structures.

Introduction

In the field of structural biology, it is widely recognized that there is a strong relationship between

the three-dimensional structure of a protein and its function [1]. The recognition and analysis of

structural similarities in proteins can represent a valuable strategy to gain insights into protein

functions. In particular, the comparison of protein binding sites represents a challenging area of

interest in the field of biology and biochemistry to improve the understanding of protein-ligand

interactions, predict off-target effects, facilitate the development of more selective and effective

therapeutic agents, investigate drug repurposing strategies, and explore polypharmacological

treatments[2]. In particular, drug repurposing, also known as drug repositioning or drug reprofiling,

refers to the process of identifying new therapeutic uses for existing drugs that were originally

developed for a different indication[3]. This approach offers several advantages, including potentially

shorter development timelines, reduced costs, and a higher likelihood of success compared to

developing entirely new compounds[4]. On the other hand, polypharmacology refers to the ability of a

drug or a pharmacological agent to interact with multiple biological targets within an organism[5]. In

other words, a polypharmacological drug can affect multiple pathways, receptors, or proteins

simultaneously. This is in contrast to traditional drug development, where the focus is often on

designing drugs that specifically target a single molecular target associated with a particular disease.

Since several diseases involve multiple molecular targets, polypharmacology represents an

interesting modality in terms of efficacy and adaptability to complex biological environments[6].

The present work is inserted in this context and aims to develop a novel computational pipeline to

pinpoint protein binding sites sharing similarities with an investigated target of interest. The

identification of binding pockets with similar amino acid patterns can indicate potential off-target

proteins for a given ligand, which can help in the design of drugs with minimal side effects.

Additionally, the characterization of amino acid arrangements in binding pockets can contribute to

the development of structure-based drug design methods to engineer drugs targeting specific protein

families or selective ligands for individual proteins. This level of selectivity can be essential in the

treatment of diseases, particularly when multiple proteins share similar functions but are involved in

distinct physiological processes. As an example, we recently employed an embryonic version of the

workflow presented here to understand the druggability of a query-binding site searching for similar

motifs in proteins able to bind ligands of interest [7].

In the past years, several computational methods quantifying the global or local similarity of protein

cavities have been developed[2,8]. In general, most of these methods share three main steps: (i) three-

dimensional analysis of the structures of interest; (ii) structure comparison; and (iii) quantification

of similarity through a metric (a scoring function). Many different representations of a given

binding site are possible with varying degrees of retained information, e.g. the type of amino acid

residues that interact with the ligand, or representing the binding site through a surface onto which

the physical-chemical characteristics are projected, and even considering protein-ligand

interactions. The first two methods can be regarded as structure-based, i.e. they stem from

observing the structure of the protein. As far as the actual comparison strategies are concerned,

these can be (a) graphical-theoretical approaches, where the maximum common subgraph is

searched; (b) fingerprint approaches, where the shapes involved in the binding site are considered;

(c) approaches based on labelled 3D points and geometric hashing, i.e. 3D transformations that

align pairs of structures. Furthermore, comparison algorithms may or may not depend on the

alignment of the structures of interest. Comparison methods that rely on residues can use graphs,

fingerprints, or alternative approaches. In particular, the comparison reveals the similarity between

the residues, the type of residues, and the atomic composition; also, such methods perform well

where the sequence and atomic position of the structure of interest are well preserved. Those that

rely on surfaces can instead use graphs or labelled 3D points for comparison. These methods are

particularly used when dealing with binding sites in proteins that do not show significant

conservation in residues, atomic composition, orientation, or folding, but show considerable

selectivity towards common ligands. Indeed, in these cases, the distribution of the properties on the

surface of the binding site and the shape of the binding site are determining factors for the

selectivity of the ligands. And finally, methods that rely on interactions can use graphs or

fingerprints for comparison [9]. A summary of the main similarity search methods available in the

literature is reported in Table 1 and a detailed comparison of the existing methodologies is available

in recent litereature[9].

93
94   **Table 1.** Summary of the main methods for the similarity search of a protein binding site in previous literature with their relative type of representation of the binding site and strategy of comparison.

Method Name	Site Representation	Strategy of Comparison
SuMo (2003)[10]	Residue-based	3D Points
PINTS (2003)[11]	Residue-based	Others
eF-seek (2004) [12]	Surface-based	Graphs
TM-Align (2005) [13]	Residue-based	Others
SiteEngine (2005) [14]	Surface-based	Graphs
ContactMetricServer [15] (2006)	Residue-based	Others

PocketMatch (2008)[16,17]	Residue-based	Others
SiteAlign (2008)[18]	Residue-based	Fingerprints
MultiBind MAPPIS (2008)[19]	Surface-based	3D Points
PevoSOAR (2009) [20]	Surface-based	Others
fPOP (2009) [21]	Surface-based	Fingerprints
SMAP (2009)[22]	Residue-based	Residue-based
PESD-serv (2010) [23]	Interaction-based	Others
SeSAW (2010) [24]	Residue-based	Others
LabelHash (2010) [25]	Residue-based	Others
FuzCav (2010) [26]	Residue-based	Fingerprints
VolSite/Shaper (2012)[27]	Surface-based	Grids
KRIPO (2012) [28]	Interaction-based	Others
Pro-BIS ligand (2012) [29]	Surface-based	Graphs
PoSSuM (2012) [30]	Residue-based	Others
COFACTOR (2012) [31]	Residue-based	3D Points
SPRITE-ASSAM (2012) [32]	Residue-based	Graphs
SiteComp lin (2012) [33]	Interaction-based	Others
Iso-Cleft Finder (2013) [34]	Residue-based	Graphs
CatSId (2013) [35]	Residue-based	Graphs
IMAAAGINE (2013) [36]	Residue-based	Graphs
Apoc (2013) [37]	Residue-based	Others
Grim & TIFP (2013) [38]	Interaction-based	Graphs
ASSIST (2014) [39]	Residue-based	3D Points
SiteHopper (2014) [40]	Surface-based	Others
IsoMIF Finder (2015) [41,42]	Interaction-based	Graphs
RAPMAD (2015) [43]	Residue-based	Residue-based
G-LoSA (2016) [44]	Residue-based	Graphs
Geomfinder (2016) [45]	Residue-based	Others
PatchSearch (2019) [46]	Residue-based	Graphs
Drugreposer ER (2019) [47]	Residue-based	Graphs
DeeplyTough (2020) [48]	Interaction-based	Others

The possibility of screening a high number of proteins for similar binding pockets can be

particularly helpful and fruitful for those complex mechanisms and processes which may involve

similar receptors and ligands for very different functions. In this context, we decided to turn our

attention and use the proposed pipeline to explore some of the main actors involved in taste

perception, due to the strong relationship between food intake and homeostasis regulation, disease

onset, immune response and metabolism. The sense of taste is a sensory modality that plays a

fundamental role in discriminating ingestible substances and nutrients from potentially harmful

substances that must be avoided, especially in omnivorous species given the range of their feeding

strategies [49]. Humans, in particular, can perceive five primary taste qualities, i.e. sweet, umami,

bitter, salty, and sour, through the interaction of molecules contained in food and specialized

proteins, namely taste receptors, located on the papillae of the tongue. However, taste receptors are

also expressed in other tissues besides the oral cavity, including the skin [50,51], brain [52], pancreas [53,54],

heart [55,56], urethra [57], airway [58] and gastric [59] smooth muscle cells. Moreover, taste receptors are not

only involved in the gustatory function, but they participate in other regulatory activities, such as

regulation of metabolic activity [60,61], innate immune response and bronchodilatation [60,62], diabetes

and obesity, glucose level maintenance, appetite regulation, as well as hormone release [63], and

muscle contraction/relaxation [64].

In the present work, we decided to focus our attention on the bitter taste perception and relative

actors, given the high scientific output produced in recent years concerning this specific taste

sensation. Bitter taste receptors are the proteins responsible for the recognition of bitter foods,

normally associated with potentially harmful substances. From a structural point of view, bitter taste

receptors are GPCRs belonging to the taste 2 receptor family (*TAS2Rs*) [65] and are characterized by

seven transmembrane helices (TMD) connected by three Intracellular Loops (ICLs) and three

Extracellular Loops (ECLs)[66]. The structural core of the 7 TMD bundle is conserved across class-A

GPCR and TAS2Rs. This core plays a fundamental role in the ligand binding in the extracellular

(EC) region and information transduction in the intracellular (IC) region [67]. Bitter taste receptors

can be activated by a multitude of different agonists through various interaction types in their

unique orthosteric binding pocket [68,69]. Based on the chemical heterogeneity of their agonists,

TAS2Rs have been distinguished into *promiscuous*, such as TAS2R10, TAS2R14, and TAS2R46,

which are activated by a variety of chemically diverse compounds, and *selective*, activated instead

by a limited number of similar compounds [70].

In the present work, we herein propose a novel, general and automatic algorithm, named

VirtuousPocketome, to screen databases of protein structures to identify amino acid patterns that are

similar to the ones forming the ligand binding site of a query receptor. Compared to previous

literature, the novelty of this work resides in three main aspects: (i) the proposed pipeline accounts

for the dynamics of the protein-ligand interaction by considering multiple binding site

configurations obtained from a molecular dynamics (MD) trajectory; (ii) the identification of the

crucial protein-ligand binding interactions is completely automatic; (iii) the results of the similarity

search are filtered using an ad-hoc multi-step filtering process to exclude patterns unlikely to bind

the ligand of interest. The algorithm builds structural motifs of the target binding site of the query

receptor-ligand complex after clustering a molecular dynamics trajectory and then searches for

similar patterns inside a specific protein database using the ASSAM code [32] followed by additional

ad-hoc filtering steps. We applied our computational pipeline to screen the currently solved human

proteome for proteins that exhibit a highly similar local amino acid pattern to the one lining the

strychnine binding site in the human TAS2R46 bitter taste receptor. The rationale of the work is to

explore the taste transduction pathway with a proteomic perspective to elucidate the possible role of

tastants beyond the mere taste perception and to investigate whether other classes of proteins have a

conserved ability to recognize such ligands, with possible implications in nutrition, homeostasis,

and disease.

Results

Details concerning convergence of the MD simulations and structural equilibrium of investigated molecular models are reported in the Supplementary Information (see also Figure S1 and Figure S2). The last 50 ns of each simulation replica were considered as structural equilibrium and were concatenated to obtain a final 150 ns-long trajectory representing the ensemble of protein conformations. These concatenated trajectories were used for the subsequent analysis and to search for similar binding pockets within the human proteome through the pipeline described herein.

Motifs Creation

In the first step of the proposed pipeline, the motifs composed of the most important protein residues interacting with strychnine were identified. In particular, starting from the above-mentioned ensemble trajectory, residues within 10 Å from the position of the ligand have been extracted and their conformations clustered using the K-Means algorithm from MDAnalysis [71]. Three clusters were identified as the optimum number through the silhouette method. After extracting the motif cluster centroids, we used PLIP to narrow down the most important non-covalent interactions which define the final three motifs. In all three of them, the ligand formed a salt-bridge interaction with residue GLU265$^{7.39}$ and two hydrophobic interactions with residues TYR85$^{3.29}$ and TRP88$^{3.32}$, highlighting the stability of these contacts throughout the MD simulation. Furthermore, additional hydrophobic interactions were found with residues THR69$^{2.64}$, PHE252$^{6.58}$, and PHE261$^{7.35}$ for motif 0 and with VAL61$^{2.56}$, and VAL249$^{6.55}$ for motif 2 (Figure 1). The three defined motifs were used for the subsequent similarity search step with ASSAM.

To check the importance of the identified residues, we also evaluated the *interaction probability* of protein residues with strychnine during the entire concatenated trajectory (500 ns x 3 replicas = 1500 ns). We calculated the interactions between the ligand and the receptor in each frame of the simulation (one frame every 200 ps) and we divided the total occurrences of a specific interaction by the total number of frames, obtaining an *interaction probability*. In line with the results on the cluster centroids, residues TYR85, TRP88, and GLU265 demonstrated the highest values with interaction probability higher than 80% (see also Table S1 and Figure S3). Interestingly, some weak interactions with the ligand in the initial experimental structure, such as those with residues ASN65 and THR180, are lost during the molecular dynamics simulation.

Figure 1. Main interactions defining the three motifs for the bitter taste receptor interacting with strychnine. (A) Representative
snapshot of the bitter-ligand complex, (B) PLIP interaction analysis identifying Hydrophobic Interaction (HI) and Saltbridge
Interaction (SB), (C, D, E) site views of the three motifs identified. The bitter taste receptor is represented in grey, the strychnine in
blue and the interacting residues in green (hydrophobic interactions) and purple (salt bridges).

Similarity Search and Multi-step Filtering

The similarity search against the entire human proteome consisting of 58972 structures (see the

Database Curation section) resulted in a total of 6718 hits using the ASSAM code. The subsequent

steps, i.e. the SASA and docking filtering steps, yielded a total of 1852 and 257 hits respectively

(Figure 2A). In detail, we adopted a SASA threshold of 0.75, thus preserving all protein hits having

a SASA in the binding pocket of at least 75% of the SASA of the original query binding site; on the

other hand, we chose a docking threshold equal to 0.1, thus keeping the hits whose docking score

would not differ by more than the 10% from the docking score of the query protein/ligand complex.

The best hit in terms of docking score after the multi-step filtering process, namely PDB 3A4S, is

represented in Figure 2B, highlighting the correspondence between the original motifs in the bitter

taste receptor and the relative matching residues in the identified protein.

Figure 2. (A) Number of total structures in the original human proteome database and the number of selected hits from the similarity search and the subsequent multi-step filtering. (B) Binding site view of the strychnine bound to the best hit (PDB: 3A4S) according to the docking score at the end of the multi-step filtering process. Protein is rendered in grey, strychnine in blue, residues in the original motif of the bitter taste receptor in red and matching residues in the 3A4S structure in violet.

The pipeline automatically generated a report file (see 'Results.txt' file in the Supplementary Material) which includes the list of all the hits at the end of the screening process with additional information, such as PDB IDs with doi of the relative publication, protein classes, shared residues between hits and query, SASA and Docking Scores. The complete list of the 257 retrieved protein hits is reported in Table S2.

Functional Enrichment and Signaling Pathway Analyses

VirtuousPocketome retrieved 145 unique Uniprot IDs relative to the previously identified hits, meaning that multiple PDBs at the end of the multistep filtering process corresponded to the same protein. The DAVID software was then employed to analyse the Gene Ontology terms and the signalling pathways data as described in the Methods section.

The functional enrichment analysis revealed that the input genes were significantly enriched for a total of 16 GO terms in the Cellular Components category, 10 terms in the Biological Processes category and 14 terms in the Molecular Functions category, based on the corrected p-value. In addition, 0 KEGG and 0 Reactome pathways were found to be significantly enriched at the same p-value threshold. The best 5 GO terms for each of the above-mentioned categories are represented in

Figure 3, whereas all the significantly retrieved GO terms are represented in the Supplementary
Information (Figure S4 and Figure S5). Regarding the Biological Processes (BP), most of the
retrieved genes are related to metabolic processes (40.9%), including organic substance, cellular
and nitrogen compound metabolic processes. Besides, the most represented Molecular Functions
(MF) are related to the binding of different species, such as proteins, small compounds or ions, and
to enzyme activity, such as transferase, hydrolase, and oxidoreductase. Finally, regarding the last
analysed GO term, the most represented Cellular Components (CC) are cytoplasm and membrane
(39.0%).

Figure 3. Bar plots representing the best 5 retrieved GO terms for each category in the third level of the GO hierarchy relative to
Biological Processes (BP), Molecular Functions (MF) and Cellular Components (CC).

Discussion

Herein, we developed a novel computational pipeline, named VirtuousPocketome, to screen a
desired database for proteins sharing similar binding sites with a specific protein of interest.
VirtuousPocketome is based on four major steps: (i) the motifs creation step, which identifies the
most important residues involved in the interaction of the protein-ligand complex under
investigation; (ii) the similarity search step, in which the human solved proteome is screened for
similar motifs compared to the ones retrieved in the previous step; (iii) the multi-step filtering step,
which preserves only the protein hits with binding sites effectively accessible and with a certain
docking affinity for the query ligand; (iv) functional enrichment and signalling pathway analyses,

which identifies the most relevant cellular components, molecular functions, biological processes

and signalling pathways related to the protein hits identified in the previous steps.

VirtuousPocketome takes as input the molecular structure (and eventually also the molecular

dynamics trajectory) of a protein-ligand complex and gives as output a list of PDB structures

sharing similar binding sites. The developed protocol is automatic and unbiased and can be applied

to any protein-ligand complex.

To evaluate the developed code and prove its potential, we here selected the human TAS2R46 bitter

taste receptor bound to a bitter ligand, i.e. strychnine and we screened the entire human proteome to

search for similar structural motifs. The choice for this molecular system was driven by the recent

experimental determination of the TAS2R46-strychnine complex structure [72], as well as the fact that

strychnine is experimentally known to target not only TAS2R46 [68] but also other bitter taste

receptors, such as TAS2R10 [73], and even other proteins [74]. Moreover, bitter taste receptors have

been widely investigated through computational molecular modelling in past years, ensuring

enough data for comparison and evaluation of some of the results of the platform [69,73,75–78].

Furthermore, the strong relationship between food intake and health status, including the regulation

of homeostasis and metabolism, makes the chosen molecular machinery a particularly intriguing

and relevant testbed for our computational screening pipeline to pinpoint possible secondary targets

outside the gustatory system for food-related tastants.

The first step of the proposed pipeline, i.e. the motifs creation step, applied to the TAS2R46 bitter

taste receptor bound to strychnine pinpointed three major motifs of residues mostly involved in the

ligand binding. In particular, all three motifs shared a salt-bridge interaction with residue

GLU265$^{7.39}$ and two hydrophobic interactions with residues TYR85$^{3.29}$ and TRP88$^{3.32}$, whereas the

first motif comprised also hydrophobic interactions with residues THR69$^{2.64}$, PHE252$^{6.58}$, and

PHE261$^{7.35}$ and the third motif with VAL61$^{2.56}$, and VAL249$^{6.55}$ (Figure 1). Interestingly, some of

these residues have already been suggested by previous literature to be important interactions for

ligand binding of bitter taste receptors. In detail, GLU265$^{7.39}$ and TRP88$^{3.32}$ were demonstrated to

be pivotal in TAS2R46 activation by strychnine [72]. Moreover, mutagenesis studies have reported

the importance of residue GLU265$^{7.39}$ for agonist responsiveness of TAS2R46 [68] and the same

position has been also linked to ligand binding for similar receptors, including hydroxytryptamine

(5-HT) receptors [79,80], adrenergic receptors [81,82], purinergic receptors [83,84], and cholecystokinin-B

(CCK-B)/gastrin receptor [85]. Moreover, residue TRP88$^{3.32}$ is widely conserved among TAS2Rs and

was found to be crucial in the activation of TAS2R43, TAS2R30 and TAS2R46 [68,86]. The

importance of residue in position 3.29 (TYR85 for TAS2R46) was confirmed also for TAS2R10,

which shows a similar binding site to TAS2R46 and is also activated by strychnine [73]. These pieces

of the literature confirmed the reliability of the motifs creation step of the proposed pipeline to

pinpoint the most important and relevant residues involved in the ligand binding. It is worth

mentioning that the possibility of analysing a molecular dynamics trajectory allows the

identification of multiple motifs, three in the present case, one for each identified cluster centroid,

ensuring a more exhaustive sampling of the protein-ligand interactions.

Starting from the identified motifs, similar amino acid patterns were searched in the entire currently

solved human proteome, consisting of 58972 structures. The similarity search using the ASSAM

code resulted in 6718 hits. Then, the multi-step filtering reduced the number of detected sites to a

total of 257 PDB structures, which represent 0.44% of the original database and 3.83% of the

structures in ASSAM code output (Figure 2A). It is worth mentioning that in the final set of 257

hits notable entries include the potassium voltage-gated channel and acetylcholinesterase. The

potassium   voltage-gated   channel   is   known   to   be   modulated   by   strychnine

(https://pubchem.ncbi.nlm.nih.gov/bioassay/588834). Although there is no experimental assay in

the literature for the binding affinity between strychnine and acetylcholinesterase, strychnine is

recognized to bind to the acetylcholine receptor, which binds acetylcholine similarly to the

acetylcholinesterase[87,88]. The presented approach was revealed to be effective in discarding a high

number of spurious proteins whose matching motifs were unlikely to bind strychnine, due to

insufficient solvent exposure or low predicted affinity obtained from molecular docking. It is

essential to highlight that while this pipeline can identify structures with amino acid patterns similar

to a specified binding pocket, the actual ability of the ligand to interact with the identified proteins

needs validation through experimental methods. This study is presented as a screening platform

designed to pinpoint proteins that are more likely to be promising targets for the given ligand, with

the understanding that experimental testing is crucial for confirmation.

The functional enrichment analysis allowed us to pinpoint the main biological processes, molecular

functions, and cellular components related to the gene expressing the retrieved hit proteins at the

end of the VirtuousPocketome pipeline (Figure 3). Most of the biological processes highlighted are

connected to metabolic processes, which seems an intriguing result considering the strong

relationship between taste perception, food intake and metabolism. Indeed, these results might

indicate that strychnine has not only the ability to activate the TAS2R46 bitter taste receptor and

elicit the bitter taste sensation, but it should be also the potential trigger or modulator of proteins

directly involved in the metabolic processes. Moreover, the protein hits are mainly involved in

molecular functions related to the binding of proteins or other small compounds and are localized

mainly in the cytoplasm and membrane. These results seem pretty reasonable considering that

TAS2R46 is a transmembrane protein and a promiscuous bitter taste receptor, able to bind a wide

spectrum of chemical compounds. In light of these results, it is worth mentioning that strychnine is
known to bind glycine and acetylcholine receptors [74], which are membrane proteins involved in
transport and signalling functions. Therefore, the presented pipeline was able to detect similar
binding sites in receptors with the same localization and biological function of known strychnine
targets. In addition, strychnine is a rather promiscuous ligand with anti-plasmodial and anti-cancer
activity and other yet-unresolved molecular targets [89].

In conclusion, in the present work, we developed a novel, general and automatic pipeline for
identifying proteins sharing similar binding pockets with a query receptor-ligand complex by
screening the entire solved human proteome. The developed pipeline is also freely accessible at
https://virtuous.isi.gr/#/virtuous-pocketome and will be easily expanded in the future to other
protein databases. We used the TAS2R46-strychnine complex as a testbed for the proposed method
to investigate if other proteins except the taste receptors might share similar binding pockets for the
recognition of tastants. The proposed methodology allows for a deep investigation of the TAS2R46-
specific residues needed for the strychnine binding to pinpoint other human proteins sharing similar
binding pockets and investigate the potential roles that this tastant could play in contexts beyond the
gustatory system. The retrieved proteins could be further analyzed to predict whether the interaction
with the compound of interest results in their activation or modulation. This will increase our
understanding of possible secondary effects of tastants beyond the mere taste perception and their
impact on the biological processes and molecular functions in which the retrieved hit proteins are
involved. This approach can also assist the design of specific foods and ingredients to develop
personalised treatments able to target desired proteins or receptors involved in specific processes or
diseases with the ultimate goal of accessing the potential of the diet as a supplement to traditional
pharmacological treatments.

Methods

VirtuousPocketome Workflow

Overall Workflow

The proposed computational pipeline requires as mandatory inputs the coordinates (PDB file) of a
protein-ligand complex and the chain label(s) uniquely identifying the receptor(s) and the ligand in
the provided structure. In order to allow the ligand to accommodate in the binding site and to assess
the dynamic nature of the protein-ligand binding, the user can specify a molecular dynamics
trajectory (GROMACS xtc/trr/pdb file), thus considering several configurations of the investigated
complex. Moreover, additional custom parameters can also be defined by experienced users if
needed (details in the following).

At present, the code is limited to the screening of the entire human proteome, but it can be easily

expanded to any PDB-like database.

The overall workflow of the algorithm designed in the present work is divided into four main steps,

each of which will be described in detail in the following paragraphs: ***Motifs Creation, Similarity***

Search, Multi-step Filtering, and Enrichment and Signaling Pathway Analyses.

The main output consists of a Txt file collecting the PDBs of the identified proteins sharing similar

accessible binding site(s) compared to the query receptor-ligand complex. Additionally, the code

provides as output the list of unique UniProt IDs related to the retrieved proteins, plots summarising

the main results (see the Results section), and visualisation states of the molecular system under

investigation.

The overall workflow is represented in Figure 4 in a flow chart representation.

Figure 4. Flow Chart of the overall workflow of VirtuousPocketome.

For the implementation of this workflow, we mainly used GROMACS functionalities [90],

MDAnalysis modules [71], and pdb-tools [91]. The ASSAM source code was kindly provided by Prof.

M. Firdaus Raih from the Molecular Function Regulation Lab (http://mfrlab.org).

Step 1 - Motifs Creation

Starting from the provided PDB input file and the MD simulation (if present) of the protein-ligand

complex, a list of residues defining the binding site is retrieved based on the distance between the

ligand and the receptor. The default distance threshold is set to 10 Å, but this can be overridden

with a custom value provided by the user as an additional parameter. If the user only provides a

single PDB file of the protein-ligand complex, a single binding site is defined according to the

chosen distance threshold between the ligand and the protein. Conversely, if the user provides also

the MD trajectory, the obtained subset of coordinates from each frame of the simulation identifying

the ligand and the residues of the protein binding site are clusterized with the K-Means algorithms

implemented in MDAnalysis, which is based on the distances between atoms positions [71]. The user

can set the desired number of clusters (k), otherwise, the optimal number of clusters is retrieved

using the silhouette method ranging from a minimum of 2 clusters up to a maximum of 12 clusters.

The   silhouette   method,   as   provided   by   the   built-in   scikit-learn   function

(sklearn.metrics.silhouette_score), is an example of an evaluation metric to indicate if clusters are

well-defined. This method computes the mean distance between a sample and all other points

within the same class (a) and the mean distance between a sample and all other points in the nearest

neighbouring cluster (b). The Silhouette Coefficient, s, for a single sample, is then calculated as

reported in Equation 1:

$$s = \frac{b - a}{\max(a, b)} \tag{1}$$

Then, the total Silhouette Coefficient is calculated as the mean of the Silhouette Coefficient for each

sample. A higher Silhouette Coefficient score is indicative of denser and well-separated clusters,

aligning with the conventional understanding of a cluster. It suggests that the samples within each

cluster are tightly packed and distinct from samples in other clusters. This reflects a higher degree

of cohesion within clusters and a greater separation between them. Therefore, the algorithm

calculates the silhouette coefficient for different numbers of clusters (from 2 to 12) and then

chooses the optimal number of clusters according to the best-achieved silhouette coefficient score.

The subsequent centroids of the clusters are saved.

Starting from the previously defined binding sites, the subset of residues forming the binding site is

further refined, highlighting those residues involved in non-covalent interactions with the ligand.

These interacting residues are retrieved using the Protein-Ligand Interaction Profiler (PLIP)

software [92], which detects hydrogen bonds, hydrophobic contacts, pi-stacking, pi-cation

interactions, salt bridges, water bridges, metal complexes, and halogen bonds between ligands and

targets. This two-step analysis allows the definition of the most relevant protein residues for the

interaction with the ligand. This subset of residues will be defined as *motifs* in the following. If only

the PDB file is passed by the user, a single motif will be created; if an MD trajectory is provided, a

motif will be produced for each centroid of the binding site.

Step 2 - Similarity Search

In the second step, the similarity search for each extracted motif is carried out using the ASSAM software. The fundamental principles underlying the search methodologies of ASSAM are described in previous literature [32,93]. In brief, the protein structure is represented as a graph, where nodes represent individual amino acid side chains and the geometric relationships between nodes form the edges of the graph. Each node is composed of two pseudo-atoms, which generate vectors that correspond to the nodes in the graph. The positions of these pseudo-atoms are strategically chosen to emphasize the functional portion of the corresponding side chain. The geometric relationships between pairs of residues are defined by distances calculated between their corresponding vectors, and these relationships are represented as the edges of the graph. If we let S, M and E denote the start, middle and end of a vector, the edges of the graph encompass five components: SS, SE, ES, EE, and MM distances, although only a subset of these distances is typically used to specify a query pattern. ASSAM employs a maximal common subgraph (MCS) approach using the Bron and Kerbosch MCS algorithm to enumerate all possible correspondences with similar protein patterns [94].

The choice to utilize ASSAM was made after an extensive examination of tools documented in the literature for assessing protein binding pockets (see also Table 1). Specifically, we scrutinized various methods, emphasizing those deemed most suitable for our objectives and compatible with integration into our pipeline. We specifically looked for methods that could compare a particular binding site with a broad set of proteins in a database (customizable if necessary), be executable locally rather than solely as a web server, provide output data on similar residues between the query protein and the target protein, perform searches quickly, and not require the prior definition of binding sites for proteins in the search database. This analysis pointed ASSAM as the most appropriate for the present work. In particular, ASSAM was chosen for (i) the simplicity in defining the binding site to be searched, i.e. a coordinate file containing the residues of interest in PDB format, (ii) the possibility to screen against any desired database in PDB format, (iii) the comparably fast time to solution, and (iv) the possibility of considering and preserving both right-handed and left-handed orientations of the alpha-helices to retrieve the superpositions. A left-handed α-helical bundle superimposed onto a right-handed one is not equivalent, particularly concerning the handedness of the two groupings of amino acids. However, when it comes to chemical activity, two groupings of amino acids may exhibit the same behaviour despite having different handedness. The crucial factor, in this case, is the distance between the individual residues [32]. Thanks to the source code kindly provided by the ASSAM developers, the proposed pipeline does not rely on the ASSAM web-based analysis tools and runs entirely offline on-premises.

The output of the ASSAM search is formatted as a list, in which each row corresponds to a *hit*

protein found in the screened protein database, along with its PDB accession ID, which presents a

match with the residues of the input motif, also referred to as *query*. The matching residues between

the query and the hit are also indicated, as well as the root-mean-square deviation (RMSD) value

between query residues and hit residues after alignment. Finally, additional pieces of information

are retrieved, namely the number of the initial conformation from which the query motif was

created, and further information on the hit protein obtained from the RCSB Protein Data Bank site,

such as the DOI of the corresponding publication and the EC classification.

Step 3 - Multi-step Filtering

To further refine the output from the previous steps and select only the protein hits with accessible

and high-affinity binding sites, two additional filtering steps, i.e. (i) the SASA and (ii) the docking

filters, have been implemented.

The first step involves the calculation of the Solvent-Accessible Surface Area (SASA) using

GROMACS [90]. In detail, for each hit protein, the SASA, evaluated in nm^2, is calculated by

measuring the value for all the residues matching the residues of the query protein's motifs. Values

equal to zero indicate that the cleft identified by the residues is not solvent-exposed, but is rather

buried in the structure of the protein and therefore likely inaccessible for the solvent or the ligand.

Values that are greater than zero, on the other hand, indicate that the cleft formed by the hit residues

is on the surface of the corresponding protein and therefore might allow for ligand binding. Only

hits with the binding site having SASA greater than a predefined threshold of the SASA value of

the corresponding query motif are retained. The SASA criterion is summarised by equation (1):

$$SASA_{HIT} > SASA_{query} * SASA_{threshold} \#(1)$$

Where SASA$_{HIT}$ corresponds to the calculated SASA value of the given hit motif, $SASA_{query}$ is the

SASA value of the corresponding motif of the query protein-ligand complex, and $SASA_{threshold}$ is

the threshold to select only hits with the desired SASA. $SASA_{threshold}$ is set to 75% by default, but

the user can specify a custom value in the additional input parameters. The selection of this

threshold was imposed as a compromise to obtain a reasonable number of protein hits that could be

effectively and rationally considered while retaining targets with motifs that are solvent-exposed

and prone to ligand docking. The decision to set as default a high SASA threshold is based on the

importance of solvent-accessible surface area (SASA) in assessing the capability of a protein

binding site to accommodate ligands. Considering only SASA values considerably lower than the

original protein binding site could compromise the algorithm's ability to retain only those binding

sites most similar to the reference complex and thus more prone to ligand binding. Setting the

SASA threshold to higher values, on the other hand, may lead to the exclusion of potentially

promising binding sites and protein hits. As a result, users have the flexibility to adjust this

threshold based on their screening objectives.

The second filtering step relies on the molecular docking of the original ligand in the query complex

onto the retrieved hits from the previous steps. The docking procedure was implemented using

SPORES and PLANTS [95,96]. PLANTS software was chosen since it exhibited excellent

performance in terms of pose prediction and time to solution compared to other molecular docking

software [97,98] and since it has been already successfully used for molecular docking and virtual

screening campaigns on GPCRs [99–103]. These qualities make PLANTS particularly well-suited for

the present work. Only hits with binding sites exhibiting a docking score (DSCORE) similar to or

below the docking score of the original protein-ligand complex are retained. In particular, the

docking score of the selected hit ($DSCORE_{HIT}$) is compared with the docking score on the original

query complex ($\overline{DSCORE}_{query}$) adjusted by a defined percentage using the specified docking

threshold ($DSCORE_{threshold}$). The docking threshold is set by default as 10% of the original

protein-ligand complex docking score, if only a PDB is provided as input, or the 10% of the average

PLANTS docking scores between the centroids of the original protein-ligand complex, if the MD

trajectory was specified. The docking filtering criterion is therefore defined by equation (2):

$$DSCORE_{HIT} < \overline{DSCORE}_{query} + \left| \overline{DSCORE}_{query} \right| * DSCORE_{threshold} \#(2)$$

Step 4 - Enrichment and Signalling Pathway Analyses

In this step, functional enrichment and signalling pathway analyses were performed to collect

information regarding roles, functions, distributions, expressions and pathways in which the

identified targets from the previous steps are involved. The pipeline automatically retrieves the

unique UniProt IDs of the protein hits (since several PDB codes can correspond to the same protein)

and searches for related genes using the DAVID functional annotation program [104,105]. We decided

to focus our attention on the Gene Ontology (GO) terms [106] related to the Cellular Components

(CC), Biological Processes (BP) and Molecular Functions (MF). The resulting GO terms were used

to identify significantly enriched functional categories, using a statistical approach that takes into

account the size of the protein list, the number of genes associated with each GO term, and the

background gene set. We also performed pathway analysis using the Kyoto Encyclopedia of Genes

and Genomes (KEGG) and the Reactome databases to identify the most represented pathways [107–

109]. GO terms and KEGG pathways with corrected for multiple testing q-value < 0.1 were

considered to be significantly enriched. The correction of the p-values and the calculation of the q-

values were performed using the Benjamini-Hochberg FDR adjustment method [110]. The pipeline
automatically generates separate plots with the above-mentioned analysis.

Database Curation

The developed tool can screen a database of target proteins in the PDB format for binding pocket

similarities against a query protein-ligand complex. For the present work, we have collected and

refined all the experimentally solved PDB structures belonging to the human proteome. We first

retrieved all the solved PDB codes belonging to *homo sapiens* from the NCBI database [111] using a

dedicated Python API (Bio.Entrez package), and obtained a total of 60159 entries (1st February

2023). We downloaded all the found queries from the RCSB database (http://www.rcsb.org/) [112],

reaching a total of 59267 structures (892 PDBs were not available). Then, the database was cleaned

by removing (i) the chains in the PDBs not belonging to the human organism (such as in the case of

protein chimaeras), (ii) multiple models from each PDB, (iii) ANISOU and HETATM lines, (iv)

alternative locations of the atoms in the PDB by preserving the ones with the highest occupancy. At

the end of this cleaning protocol, we ended up with 58972 PDB files.

Molecular Modelling and Dynamics

System Setup

The previously described workflow was applied to search for proteins sharing similar binding

pockets with a human bitter taste receptor. We employed the recently-solved TAS2R46 human

bitter taste receptor bound with an agonist bitter compound, named strychnine (PDB ID: 7XP6) [72].

We first removed undesired molecules and structures from the PDB, preserving only the bitter taste

receptor and strychnine. Since the receptor structure presents some missing residues (157-172), we

downloaded the relative model (sequence P59540 of Homo Sapiens hTAS2R46) from the

AlphaFold Protein Structure Database [113]. The AlphaFold model was then aligned to the receptor in

the 7XP6 PDB. Missing residues in the original experimental structure were then built by homology

modelling with MOE (Molecular Operating Environment) software [114] using the relative portion of

the AlphaFold model as a template, thus filling the gap in the original experimental structure. Then,

the structure of strychnine was refined using MOE, assigning the correct protonation at neutral pH

and salt concentration of 0.15 M (see also Figure S6). As reported in previous literature[72], the

tertiary amine of the molecule is protonated and its total charge is +1, as also reported in the

DrugBank database (https://go.drugbank.com/drugs/DB15954).

The obtained complex was embedded into a POPC membrane using the CHARMM-GUI web

server [115]. The receptor was aligned with the membrane bilayer using the OPM web server included

in the CHARMM-GUI preparation protocol. The final number of POPC lipids (165) was set by a

trial-and-error approach to creating a box large enough to meet the minimum image convention for

the protein during the MD simulation: the final box size was set to 8.36 x 8.36 x 11.47 nm, with the

z direction perpendicular to the cell membrane plane. The system box was filled with water and

neutralized using NA^+ and CL^- ions at 0.15 M physiological concentration.

We used the AMBER forcefield to describe the molecular system: in detail, we used the Lipid-21

forcefield [116] for lipids, the AMBER19SB [117] for the protein, ions and water and the General Amber

Force Field (GAFF2) forcefield [118] to obtain the topology for strychnine, as implemented directly in

the CHARMM-GUI suite.

Simulation Protocol

The simulation workflow suggested by CHARMM-GUI was followed during minimisation,

equilibration with position restraints and final simulation production. First, the system was energy-

minimized using the steepest descent algorithm for 5000 steps. Then, six equilibration steps were

performed gradually reducing the position restraints on the lipids and protein-heavy atoms (from

1000 to 0 $kJmol^{-1}nm^{-1}$ for lipids, from 4000 to 50 $kJmol^{-1}nm^{-1}$ for the protein backbone and from

2000 to 0 $kJmol^{-1}nm^{-1}$ for protein side-chain heavy atoms). The system was equilibrated in the NVT

ensemble for 250 ps with a conservative timestep of 1 fs, using the Berendsen thermostat [119] with a

coupling time constant of 1 ps and a reference temperature of 303.15 K, which is above the phase-

transition temperature for POPC, and subsequently in the NPT ensemble for 125 ps with the same 1

fs timestep, followed by a further simulation of 375 ps with a 2 fs timestep, using the Berendsen

thermostat with the same parameters as before and the Berendsen barostat [119] with semi-isotropic

pressure coupling at 1 atm with a coupling time constant of 5 ps. Overall, the systems underwent

750 ps of equilibration.

The TAS2R46 bitter taste receptor system was then simulated for 400 ns without position restraints

with a 2 fs time step in the NPT ensemble. Temperature coupling was done with the Nose-Hoover

algorithm [120], whereas, pressure coupling with the Parrinello-Rahman algorithm [121]. The PME

algorithm was used for electrostatic interactions with a cut-off of 0.9 nm. A reciprocal grid of 72 x

72 x 96 cells was used with 4th-order B-spline interpolation. A single cut-off of 0.9 nm was used

for Van der Waals interactions. LINCS (LINear Constraint Solver) algorithm for h-bonds [122] was

applied in each simulation step.

Three simulation replicas were performed to ensure the reproducibility of the simulations and to

enlarge the simulation statics. All Molecular Dynamics (MD) simulations were performed using

GROMACS [90] and the Visual Molecular Dynamics (VMD) package was employed for the visual

inspection of the simulated systems [123].

References

1. Artymiuk, P. J., Poirrette, A. R., Rice, D. W. & Willett, P. A polymerase I palm in adenylyl cyclase? *Nature* **388**, 33–34 (1997).

2. Ehrt, C., Brinkjost, T. & Koch, O. A benchmark driven guide to binding site comparison: An exhaustive evaluation using tailor-made data sets (ProSPECCTs). *PLoS Comput Biol* **14**, e1006483 (2018).

3. Hodos, R. A., Kidd, B. A., Shameer, K., Readhead, B. P. & Dudley, J. T. *In silico* methods for drug repurposing and pharmacology. *WIREs Mechanisms of Disease* **8**, 186–210 (2016).

4. Independent Interdisciplinary Consultant, Oxford, United Kingdom & Flower, D. Drug Discovery: Today and Tomorrow. *Bioinformation* **16**, 1–3 (2020).

5. Kabir, A. & Muth, A. Polypharmacology: The science of multi-targeting molecules. *Pharmacological Research* **176**, 106055 (2022).

6. Chaudhari, R., Fong, L. W., Tan, Z., Huang, B. & Zhang, S. An up-to-date overview of computational polypharmacology in modern drug discovery. *Expert Opinion on Drug Discovery* **15**, 1025–1044 (2020).

7. Cannariato, M., Miceli, M. & Deriu, M. A. In silico investigation of Alsin RLD conformational dynamics and phosphoinositides binding mechanism. *PLOS ONE* **17**, e0270955 (2022).

8. Eguida, M. & Rognan, D. Estimating the Similarity between Protein Pockets. *IJMS* **23**, 12462 (2022).

9. Ehrt, C., Brinkjost, T. & Koch, O. A benchmark driven guide to binding site comparison: An exhaustive evaluation using tailor-made data sets (ProSPECCTs). *PLoS Comput Biol* **14**, e1006483 (2018).

10. Jambon, M., Imberty, A., Deléage, G. & Geourjon, C. A new bioinformatic approach to detect common 3D sites in protein structures: Detection of 3D Sites in Protein Structures. *Proteins* **52**, 137–145 (2003).

11. Stark, A., Sunyaev, S. & Russell, R. B. A Model for Statistical Significance of Local

Similarities in Structure. *Journal of Molecular Biology* **326**, 1307–1316 (2003).

12. Kinoshita, K. Identification of Protein Biochemical Function by Searching the Similar Shape

and Electrostatic Potential on the Molecular Surface of Proteins. *Seibutsu Butsuri* **44**, 150–154

(2004).

13. Zhang, Y. TM-align: a protein structure alignment algorithm based on the TM-score. *Nucleic*

Acids Research **33**, 2302–2309 (2005).

14. Shulman-Peleg, A., Nussinov, R. & Wolfson, H. J. SiteEngines: recognition and comparison of

binding sites and protein-protein interfaces. *Nucleic Acids Research* **33**, W337–W341 (2005).

15. Lisewski, A. M. & Lichtarge, O. Rapid detection of similarity in protein structure and function

through contact metric distances. *Nucleic Acids Research* **34**, e152–e152 (2006).

16. Nagarajan, D. & Chandra, N. PocketMatch (version 2.0): A parallel algorithm for the detection

of structural similarities between protein ligand binding-sites. in *2013 National Conference on*

Parallel Computing Technologies (PARCOMPTECH) 1–6 (IEEE, Bangalore, India, 2013).

doi:10.1109/ParCompTech.2013.6621397.

17. Yeturu, K. & Chandra, N. PocketMatch: A new algorithm to compare binding sites in protein

structures. *BMC Bioinformatics* **9**, 543 (2008).

18. Schalon, C., Surgand, J., Kellenberger, E. & Rognan, D. A simple and fuzzy method to align

and compare druggable ligand☐binding sites. *Proteins* **71**, 1755–1778 (2008).

19. Shulman-Peleg, A., Shatsky, M., Nussinov, R. & Wolfson, H. J. MultiBind and MAPPIS:

webservers for multiple alignment of protein 3D-binding sites and their interactions. *Nucleic*

Acids Research **36**, W260–W264 (2008).

20. Tseng, Y. Y., Dundas, J. & Liang, J. Predicting Protein Function and Binding Profile via

Matching of Local Evolutionary and Geometric Surface Patterns. *Journal of Molecular Biology*

387, 451–464 (2009).

21. Tseng, Y. Y., Chen, Z. J. & Li, W.-H. f POP: footprinting functional pockets of proteins by

comparative spatial patterns. *Nucleic Acids Research* **38**, D288–D295 (2010).

22. Xie, L., Xie, L. & Bourne, P. E. A unified statistical model to support local sequence order

independent similarity searching for ligand-binding sites and its application to genome-based

drug discovery. *Bioinformatics* **25**, i305–i312 (2009).

23. Das, S., Krein, M. P. & Breneman, C. M. PESDserv: a server for high-throughput comparison

of protein binding site surfaces. *Bioinformatics* **26**, 1913–1914 (2010).

24. Standley, D. M., Yamashita, R., Kinjo, A. R., Toh, H. & Nakamura, H. SeSAW: balancing

sequence and structural information in protein functional mapping. *Bioinformatics* **26**, 1258–

1259 (2010).

25. Moll, M., Bryant, D. H. & Kavraki, L. E. The LabelHash algorithm for substructure matching.

BMC Bioinformatics **11**, 555 (2010).

26. Weill, N. & Rognan, D. Alignment-Free Ultra-High-Throughput Comparison of Druggable

Protein–Ligand Binding Sites. *J. Chem. Inf. Model.* **50**, 123–135 (2010).

27. Desaphy, J., Azdimousa, K., Kellenberger, E. & Rognan, D. Comparison and Druggability

Prediction of Protein–Ligand Binding Sites from Pharmacophore-Annotated Cavity Shapes. *J.*

Chem. Inf. Model. **52**, 2287–2299 (2012).

28. Wood, D. J., Vlieg, J. D., Wagener, M. & Ritschel, T. Pharmacophore Fingerprint-Based

Approach to Binding Site Subpocket Similarity and Its Application to Bioisostere Replacement.

J. Chem. Inf. Model. **52**, 2031–2043 (2012).

29. Konc, J. & Janezic, D. ProBiS-2012: web server and web services for detection of structurally

similar binding sites in proteins. *Nucleic Acids Research* **40**, W214–W221 (2012).

30. Ito, J.-I., Tabei, Y., Shimizu, K., Tsuda, K. & Tomii, K. PoSSuM: a database of similar protein-

ligand binding and putative pockets. *Nucleic Acids Research* **40**, D541–D548 (2012).

31. Roy, A., Yang, J. & Zhang, Y. COFACTOR: an accurate comparative algorithm for structure-

based protein function annotation. *Nucleic Acids Research* **40**, W471–W477 (2012).

32. Nadzirin, N., Gardiner, E. J., Willett, P., Artymiuk, P. J. & Firdaus-Raih, M. SPRITE and

ASSAM: web servers for side chain 3D-motif searching in protein structures. *Nucleic Acids*

Research **40**, W380–W386 (2012).

33. Lin, Y., Yoo, S. & Sanchez, R. SiteComp: a server for ligand binding site analysis in protein

structures. *Bioinformatics* **28**, 1172–1173 (2012).

34. Kurbatova, N., Chartier, M., Zylber, M. I. & Najmanovich, R. IsoCleft Finder – a web-based

tool for the detection and analysis of protein binding-site geometric and chemical similarities.

F1000Res **2**, 117 (2013).

35. Kirshner, D. A., Nilmeier, J. P. & Lightstone, F. C. Catalytic site identification—a web server

to identify catalytic site structural matches throughout PDB. *Nucleic Acids Research* **41**, W256–

W265 (2013).

36. Nadzirin, N., Willett, P., Artymiuk, P. J. & Firdaus-Raih, M. IMAAAGINE: a webserver for

searching hypothetical 3D amino acid side chain arrangements in the Protein Data Bank.

Nucleic Acids Research **41**, W432–W440 (2013).

37. Gao, M. & Skolnick, J. APoc: large-scale identification of similar protein pockets.

Bioinformatics **29**, 597–604 (2013).

38. Desaphy, J., Raimbaud, E., Ducrot, P. & Rognan, D. Encoding Protein–Ligand Interaction

Patterns in Fingerprints and Graphs. *J. Chem. Inf. Model.* **53**, 623–637 (2013).

39. Caprari, S., Toti, D., Viet Hung, L., Di Stefano, M. & Polticelli, F. ASSIST: a fast versatile

local structural comparison tool. *Bioinformatics* **30**, 1022–1024 (2014).

40. Batista, J., Hawkins, P. C., Tolbert, R. & Geballe, M. T. SiteHopper - a unique tool for binding

site comparison. *J Cheminform* **6**, P57, 1758-2946-6-S1-P57 (2014).

41. Chartier, M., Adriansen, E. & Najmanovich, R. IsoMIF Finder: online detection of binding site

molecular interaction field similarities. *Bioinformatics* **32**, 621–623 (2016).

42. Chartier, M. & Najmanovich, R. Detection of Binding Site Molecular Interaction Field

Similarities. *J. Chem. Inf. Model.* **55**, 1600–1615 (2015).

43. Krotzky, T., Grunwald, C., Egerland, U. & Klebe, G. Large-Scale Mining for Similar Protein

Binding Pockets: With RAPMAD Retrieval on the Fly Becomes Real. *J. Chem. Inf. Model.* **55**,

165–179 (2015).

44. Lee, H. S. & Im, W. G-LoSA: An efficient computational tool for local structure-centric

biological studies and drug design: G-LoSA. *Protein Science* **25**, 865–876 (2016).

45. Núñez-Vivanco, G., Valdés-Jiménez, A., Besoaín, F. & Reyes-Parada, M. Geomfinder: a multi-

feature identifier of similar three-dimensional protein patterns: a ligand-independent approach.

J Cheminform **8**, 19 (2016).

46. Rey, J., Rasolohery, I., Tufféry, P., Guyon, F. & Moroy, G. PatchSearch: a web server for off-

target protein identification. *Nucleic Acids Research* **47**, W365–W372 (2019).

47. Ab Ghani, N. S., Ramlan, E. I. & Firdaus-Raih, M. Drug ReposER: a web server for predicting

similar amino acid arrangements to known drug binding interfaces for potential drug

repositioning. *Nucleic Acids Research* **47**, W350–W356 (2019).

48. Simonovsky, M. & Meyers, J. DeeplyTough: Learning Structural Comparison of Protein

Binding Sites. *J. Chem. Inf. Model.* **60**, 2356–2366 (2020).

49. Breslin, P. A. S. An Evolutionary Perspective on Food and Human Taste. *Current Biology* **23**,

R409–R418 (2013).

50. Ho, H. K. *et al.* Functionally expressed bitter taste receptor TAS2R14 in human epidermal

keratinocytes serves as a chemosensory receptor. *Exp Dermatol* **30**, 216–225 (2021).

51. Shaw, L. *et al.* Personalized expression of bitter 'taste' receptors in human skin. *PLoS ONE* **13**,

e0205322 (2018).

52. Singh, N., Vrontakis, M., Parkinson, F. & Chelikani, P. Functional bitter taste receptors are

expressed in brain cells. *Biochemical and Biophysical Research Communications* **406**, 146–151

(2011).

53. Kyriazis, G. A., Soundarapandian, M. M. & Tyrberg, B. Sweet taste receptor signaling in beta

cells mediates fructose-induced potentiation of glucose-stimulated insulin secretion. *Proc. Natl.*

Acad. Sci. U.S.A. **109**, (2012).

54. Kyriazis, G. A., Smith, K. R., Tyrberg, B., Hussain, T. & Pratley, R. E. Sweet Taste Receptors

Regulate Basal Insulin Secretion and Contribute to Compensatory Insulin Hypersecretion

During the Development of Diabetes in Male Mice. *Endocrinology* **155**, 2112–2121 (2014).

55. Foster, S. R. *et al.* Expression, Regulation and Putative Nutrient-Sensing Function of Taste

GPCRs in the Heart. *PLoS ONE* **8**, e64579 (2013).

56. Foster, S. R. *et al.* Bitter taste receptor agonists elicit G□protein□dependent negative inotropy

in the murine heart. *FASEB j.* **28**, 4497–4508 (2014).

57. Deckmann, K. *et al.* Bitter triggers acetylcholine release from polymodal urethral chemosensory

cells and bladder reflexes. *Proc. Natl. Acad. Sci. U.S.A.* **111**, 8287–8292 (2014).

58. Deshpande, D. A. *et al.* Bitter taste receptors on airway smooth muscle bronchodilate by

localized calcium signaling and reverse obstruction. *Nature Medicine* **16**, 1299–1304 (2010).

59. Avau, B. *et al.* Targeting extra-oral bitter taste receptors modulates gastrointestinal motility

with effects on satiation. *Scientific Reports* **5**, 1–12 (2015).

60. Iwatsuki, K. & Uneyama, H. Sense of Taste in the Gastrointestinal Tract. *J Pharmacol Sci* **118**,

123–128 (2012).

61. Raka, F., Farr, S., Kelly, J., Stoianov, A. & Adeli, K. Metabolic control via nutrient-sensing

mechanisms: role of taste receptors and the gut-brain neuroendocrine axis. *American Journal of*

Physiology-Endocrinology and Metabolism **317**, E559–E572 (2019).

62. Carey, R. M. & Lee, R. J. Taste Receptors in Upper Airway Innate Immunity. *Nutrients* **11**,

2017 (2019).

63. Behrens, M. & Lang, T. Extra-Oral Taste Receptors—Function, Disease, and Perspectives.

Front. Nutr. **9**, 881177 (2022).

64. Zhai, K. *et al.* Activation of bitter taste receptors (tas2rs) relaxes detrusor smooth muscle and

suppresses overactive bladder symptoms. *Oncotarget* **7**, 21156–21167 (2016).

65. Chandrashekar, J. *et al.* T2Rs Function as Bitter Taste Receptors. *Cell* **100**, 703–711 (2000).

66. Sutkeviciute, I. & Vilardaga, J.-P. Structural insights into emergent signaling modes of G

protein–coupled receptors. *Journal of Biological Chemistry* **295**, 11626–11642 (2020).

67. Di Pizio, A. *et al.* Comparing Class A GPCRs to bitter taste receptors. in *Biophysical Methods*

in Cell Biology vol. 132 401–427 (Elsevier Ltd, 2016).

68. Brockhoff, A., Behrens, M., Niv, M. Y. & Meyerhof, W. Structural requirements of bitter taste

receptor activation. *Proceedings of the National Academy of Sciences of the United States of*

America **107**, 11110–11115 (2010).

69. Slack, J. P. *et al.* Modulation of Bitter Taste Perception by a Small Molecule hTAS2R

Antagonist. *Current Biology* **20**, 1104–1109 (2010).

70. Meyerhof, W. *et al.* The molecular receptive ranges of human TAS2R bitter taste receptors.

Chemical Senses **35**, 157–170 (2009).

71. Gowers, R. *et al.* MDAnalysis: A Python Package for the Rapid Analysis of Molecular

Dynamics Simulations. in 98–105 (Austin, Texas, 2016). doi:10.25080/Majora-629e541a-00e.

72. Xu, W. *et al.* Structural basis for strychnine activation of human bitter taste receptor TAS2R46.

Science **377**, 1298–1304 (2022).

73. Born, S., Levit, A., Niv, M. Y., Meyerhof, W. & Behrens, M. The human bitter taste receptor

TAS2R10 is tailored to accommodate numerous diverse ligands. *Journal of Neuroscience* **33**,

201–213 (2013).

74. Jensen, A. A., Gharagozloo, P., Birdsall, N. J. M. & Zlotos, D. P. Pharmacological

characterisation of strychnine and brucine analogues at glycine and α7 nicotinic acetylcholine

receptors. *European Journal of Pharmacology* **539**, 27–33 (2006).

75. DiPizio, A. *et al.* Rational design of agonists for bitter taste receptor TAS2R14: from modeling

to bench and back. *Cellular and Molecular Life Sciences* **77**, (2020).

76. Fierro, F., Giorgetti, A., Carloni, P., Meyerhof, W. & Alfonso-Prieto, M. Dual binding mode of

"bitter sugars" to their human bitter taste receptor target. *Scientific Reports* **9**, 1–16 (2019).

77. Nicoli, A., Dunkel, A., Giorgino, T., de Graaf, C. & Di Pizio, A. Classification Model for the

Second Extracellular Loop of Class A GPCRs. *J. Chem. Inf. Model.* **62**, 511–522 (2022).

78. Topin, J. *et al.* Functional molecular switches of mammalian G protein-coupled bitter-taste

receptors. *Cellular and Molecular Life Sciences* **6**, 2020.10.23.348706 (2021).

79. Kuipers, W. *et al.* Study of the interaction between aryloxypropanolamines and Asn386 in helix

VII of the human 5-hydroxytryptamine1A receptor. *Mol Pharmacol* **51**, 889–896 (1997).

80. Oksenberg, D. *et al.* A single amino-acid difference confers major pharmacological variation

between human and rodent 5-HT1B receptors. *Nature* **360**, 161–163 (1992).

81. Suryanarayana, S., Daunt, D. A., Von Zastrow, M. & Kobilka, B. K. A point mutation in the

seventh hydrophobic domain of the alpha 2 adrenergic receptor increases its affinity for a

family of beta receptor antagonists. *J Biol Chem* **266**, 15488–15492 (1991).

82. Suryanarayana, S. & Kobilka, B. K. Amino acid substitutions at position 312 in the seventh

hydrophobic segment of the beta 2-adrenergic receptor modify ligand-binding specificity. *Mol*

Pharmacol **44**, 111–114 (1993).

83. Erb, L. *et al.* Site-directed mutagenesis of P2U purinoceptors. Positively charged amino acids in

transmembrane helices 6 and 7 affect agonist potency and specificity. *J Biol Chem* **270**, 4185–

4188 (1995).

84. Jiang, Q. *et al.* A Mutational Analysis of Residues Essential for Ligand Recognition at the

Human P2Y $_1$ Receptor. *Mol Pharmacol* **52**, 499–507 (1997).

85. Kopin, A. S., McBride, E. W., Quinn, S. M., Kolakowski, L. F. & Beinborn, M. The role of the

cholecystokinin-B/gastrin receptor transmembrane domains in determining affinity for subtype-

selective ligands. *J Biol Chem* **270**, 5019–5023 (1995).

86. Pronin, A. N. Identification of Ligands for Two Human Bitter T2R Receptors. *Chemical Senses*

29, 583–593 (2004).

87. Kuijpers, G. A. J., Vergara, L. A., Calvo, S. & Yadid, G. Inhibitory effect of strychnine on

acetylcholine receptor activation in bovine adrenal medullary chromaffin cells. *British J*

Pharmacology **113**, 471–478 (1994).

88. García-Colunga, J. & Miledi, R. Modulation of nicotinic acetylcholine receptors by strychnine.

Proc. Natl. Acad. Sci. U.S.A. **96**, 4113–4118 (1999).

89. Zlotos, D. P., Mandour, Y. M. & Jensen, A. A. Strychnine and its mono- and dimeric

analogues: a pharmaco-chemical perspective. *Nat. Prod. Rep.* **39**, 1910–1937 (2022).

90. Abraham, M. J. *et al.* GROMACS: High performance molecular simulations through multi-

level parallelism from laptops to supercomputers. *SoftwareX* **1–2**, 19–25 (2015).

91. Rodrigues, J. P. G. L. M., Teixeira, J. M. C., Trellet, M. & Bonvin, A. M. J. J. pdb-tools: a

swiss army knife for molecular structures. *F1000Res* **7**, 1961 (2018).

92. Adasme, M. F. *et al.* PLIP 2021: expanding the scope of the protein–ligand interaction profiler

to DNA and RNA. *Nucleic Acids Research* **49**, W530–W534 (2021).

93. Spriggs, R. V., Artymiuk, P. J. & Willett, P. Searching for Patterns of Amino Acids in 3D

Protein Structures. *J. Chem. Inf. Comput. Sci.* **43**, 412–421 (2003).

94. Bron, C. & Kerbosch, J. Algorithm 457: finding all cliques of an undirected graph. *Commun.*

ACM **16**, 575–577 (1973).

95. Korb, O., Stützle, T. & Exner, T. E. PLANTS: Application of Ant Colony Optimization to

Structure-Based Drug Design. in *Ant Colony Optimization and Swarm Intelligence* (eds.

Dorigo, M. et al.) vol. 4150 247–258 (Springer Berlin Heidelberg, Berlin, Heidelberg, 2006).

96. Korb, O., Stützle, T. & Exner, T. E. An ant colony optimization approach to flexible protein–

ligand docking. *Swarm Intell* **1**, 115–134 (2007).

97. Çınaroğlu, S. S. & Timuçin, E. Comparative Assessment of Seven Docking Programs on a

Nonredundant Metalloprotein Subset of the PDBbind Refined. *J. Chem. Inf. Model.* **59**, 3846–

3859 (2019).

98. Eldridge, M. D., Murray, C. W., Auton, T. R., Paolini, G. V. & Mee, R. P. Empirical scoring

functions: I. The development of a fast empirical scoring function to estimate the binding

affinity of ligands in receptor complexes. *Journal of computer-aided molecular design* **11**, 425–

45 (1997).

99. Sirci, F. *et al.* Virtual Fragment Screening: Discovery of Histamine H $_3$ Receptor Ligands Using

Ligand-Based and Protein-Based Molecular Fingerprints. *J. Chem. Inf. Model.* **52**, 3308–3324

(2012).

100. Kooistra, A. J., Leurs, R., De Esch, I. J. P. & De Graaf, C. Structure-Based Prediction of G-

Protein-Coupled Receptor Ligand Function: A β-Adrenoceptor Case Study. *J. Chem. Inf.*

Model. **55**, 1045–1061 (2015).

101. Bassani, D., Pavan, M., Sturlese, M. & Moro, S. Sodium or Not Sodium: Should Its Presence

Affect the Accuracy of Pose Prediction in Docking GPCR Antagonists? *Pharmaceuticals* **15**,

346 (2022).

102. Kooistra, A. J. *et al.* Function-specific virtual screening for GPCR ligands using a combined

scoring method. *Sci Rep* **6**, 28288 (2016).

103. De Graaf, C. *et al.* Crystal Structure-Based Virtual Screening for Fragment-like Ligands of the

Human Histamine H $_1$ Receptor. *J. Med. Chem.* **54**, 8195–8206 (2011).

104. Huang, D. W., Sherman, B. T. & Lempicki, R. A. Systematic and integrative analysis of large

gene lists using DAVID bioinformatics resources. *Nat Protoc* **4**, 44–57 (2009).

105. Sherman, B. T. *et al.* DAVID: a web server for functional enrichment analysis and functional

annotation of gene lists (2021 update). *Nucleic Acids Research* **50**, W216–W221 (2022).

106. The Gene Ontology Consortium. The Gene Ontology project in 2008. *Nucleic Acids Research*

36, D440–D444 (2008).

107. Gillespie, M. *et al.* The reactome pathway knowledgebase 2022. *Nucleic Acids Research* **50**,

D687–D692 (2022).

108. Kanehisa, M. KEGG: Kyoto Encyclopedia of Genes and Genomes. *Nucleic Acids Research*

28, 27–30 (2000).

109. Kanehisa, M., Furumichi, M., Sato, Y., Kawashima, M. & Ishiguro-Watanabe, M. KEGG for

taxonomy-based analysis of pathways and genomes. *Nucleic Acids Research* **51**, D587–D592

(2023).

110. Ferreira, J. A. & Zwinderman, A. H. On the Benjamini–Hochberg method. *The Annals of*

Statistics **34**, 1827–1849 (2006).

111. NCBI Resource Coordinators *et al.* Database resources of the National Center for

Biotechnology Information. *Nucleic Acids Research* **46**, D8–D13 (2018).

112. Berman, H. M. The Protein Data Bank. *Nucleic Acids Research* **28**, 235–242 (2000).

113. Jumper, J. *et al.* Highly accurate protein structure prediction with AlphaFold. *Nature* **596**,

583–589 (2021).

114. Molecular Operating Environment (MOE), 2022.02 Chemical Computing Group ULC, 1010

Sherbooke St. West, Suite #910, Montreal, QC, Canada, H3A 2R7, 2023. (2022).

115. Jo, S., Kim, T., Iyer, V. G. & Im, W. CHARMM-GUI: A web-based graphical user interface

for CHARMM. *J. Comput. Chem.* **29**, 1859–1865 (2008).

116. Dickson, C. J., Walker, R. C. & Gould, I. R. Lipid21: Complex Lipid Membrane Simulations

with AMBER. *J. Chem. Theory Comput.* **18**, 1726–1736 (2022).

117. Tian, C. *et al.* ff19SB: Amino-Acid-Specific Protein Backbone Parameters Trained against

Quantum Mechanics Energy Surfaces in Solution. *J. Chem. Theory Comput.* **16**, 528–552

(2020).

118. Wang, J., Wolf, R. M., Caldwell, J. W., Kollman, P. A. & Case, D. A. Development and

testing of a general amber force field. *Journal of Computational Chemistry* **25**, 1157–1174

(2004).

119. Berendsen, H. J. C., Postma, J. P. M., van Gunsteren, W. F., DiNola, A. & Haak, J. R.

Molecular dynamics with coupling to an external bath. *The Journal of Chemical Physics* **81**,

3684–3690 (1984).

120. Nosé, S. A unified formulation of the constant temperature molecular dynamics methods. *The*

Journal of Chemical Physics **81**, 511–519 (1984).

121. Parrinello, M. & Rahman, A. Polymorphic transitions in single crystals: A new molecular

dynamics method. *Journal of Applied Physics* **52**, 7182–7190 (1981).

122. Hess, B., Bekker, H., Berendsen, H. J. C. & Fraaije, J. G. E. M. LINCS: A linear constraint

solver for molecular simulations. *Journal of Computational Chemistry* **18**, 1463–1472 (1997).

123. Humphrey, W., Dalke, A. & Schulten, K. VMD: Visual molecular dynamics. *Journal of*

Molecular Graphics **14**, 33–38 (1996).

Acknowledgements

The present work has been developed as part of the VIRTUOUS project, funded by the European

Union's Horizon 2020 research and innovation program under the Marie Sklodowska-Curie-RISE

Grant Agreement No. 872181 (https://www.virtuoush2020.com/).

The authors would also like to acknowledge Prof. M. Firdaus Raih from the Molecular Function

Regulation Lab (http://mfrlab.org) for kindly providing us with the source code of ASSAM

software.

Author Contributions

Lorenzo Pallante: Conceptualization; Data curation; Formal analysis; Methodology; Software;
Validation; Visualization; Writing - original draft; Writing - review & editing.

Marco Cannariato: Conceptualization; Data curation; Formal analysis; Methodology; Software;
Validation; Visualization; Writing - original draft; Writing - review & editing.

Lampros Androutsos: Conceptualization; Data curation; Formal analysis; Investigation;
Validation; Visualization; Writing - review & editing.

Eric A. Zizzi: Conceptualization; Supervision; Methodology; Writing - review & editing;

Agorakis Bompotas: Supervision; Software; Methodology; Visualization; Writing - review &
editing;

Xhesika Hada: Conceptualization; Methodology; Writing - review & editing;

Gianvito Grasso: Supervision; Writing - review & editing;

Athanasios Kalogeras: Supervision; Writing - review & editing;

Seferina Mavroudi: Supervision; Writing - review & editing;

Giacomo Di Benedetto: Supervision; Writing - review & editing;

Konstantinos Theofilatos: Conceptualization; Supervision; Formal analysis; Validation; Writing -
review & editing;

Marco Agostino Deriu: Conceptualization; Formal analysis; Funding acquisition; Project
administration; Resources; Supervision; Validation; Visualization; Writing - review & editing.

Data Availability

861 All data to replicate the simulations are accessible at https://github.com/M3B-
862 Lab/VirtuousPocketome.

Additional Information

Competing Interests Statement

865 The authors declare no competing interests.

Figure Legends

Figure 1. Main interactions defining the three motifs for the bitter taste receptor interacting with
strychnine. (A) Representative snapshot of the bitter-ligand complex, (B) PLIP interaction analysis
identifying Hydrophobic Interaction (HI) and Saltbridge Interaction (SB), (C, D, E) site views of
the three motifs identified. The bitter taste receptor is represented in grey, the strychnine in blue and
the interacting residues in green (hydrophobic interactions) and purple (salt bridges).

Figure 2. (A) Number of total structures in the original human proteome database and the number
of selected hits from the similarity search and the subsequent multi-step filtering. (B) Binding site
view of the strychnine bound to the best hit (PDB: 3A4S) according to the docking score at the end
of the multi-step filtering process. Protein is rendered in grey, strychnine in blue, residues in the
original motif of the bitter taste receptor in red and matching residues in the 3A4S structure in
violet.

Figure 3. Bar plots representing the best 5 retrieved GO terms for each category in the third level of
the GO hierarchy relative to Biological Processes (BP), Molecular Functions (MF) and Cellular
Components (CC).

Figure 4. Flow Chart of the overall workflow of VirtuousPocketome.

Motif Creation

MD Trajectory

Kmeans

Dominant ligand-receptor conformation

PLIP

MOTIFS

Similarity Search

ASSAM

Multi-Step Filtering

GROMACS
INST. TEORNIE, FYZIK

SASA > 75%
SASA_original   NO   Discarded

YES

Keep unique PDBs

PLANTS

D-Score < D-Score_original +
10% |D-Score_original| NO   Discarded

YES

Analysis

DAVID

Functional Enrichment
Analysis with GO terms:
• Cellular Components (CC)
• Biological Processes (BP)
• Molecular Functions (MF)

Signalling Pathway
Analysis:
• KEGG
• Reactome