Title

Hybracter: Enabling Scalable, Automated, Complete and Accurate Bacterial Genome

Assemblies

Authors

George Bouras[1,2]*, Ghais Houtak[1,2], Ryan R. Wick[3], Vijini Mallawaarachchi[4], Michael J.

Roach[4,5], Bhavya Papudeshi[4], Lousie M. Judd[3], Anna E. Sheppard[6], Robert A. Edwards[4],

Sarah Vreugde[1,2]

Author institutional affiliations

[1] Adelaide Medical School, Faculty of Health and Medical Sciences, The University of

Adelaide, Adelaide, Australia.

[2] The Department of Surgery - Otolaryngology Head and Neck Surgery, University of

Adelaide and the Basil Hetzel Institute for Translational Health Research, Central Adelaide

Local Health Network, South Australia, Australia.

[3] Department of Microbiology and Immunology, University of Melbourne at the Peter

Doherty Institute for Infection and Immunity, Melbourne, Australia.

[4] Flinders Accelerator for Microbiome Exploration, College of Science and Engineering,

Flinders University, Adelaide, Australia.

[5] Adelaide Centre for Epigenetics and South Australian Immunogenomics Cancer Institute,

The University of Adelaide, Adelaide, Australia.

[6] School of Biological Sciences, The University of Adelaide, Adelaide, Australia.

* Correspondence: george.bouras@adelaide.edu.au;

Abstract

Improvements in the accuracy and availability of long-read sequencing mean that complete bacterial genomes are now routinely reconstructed using hybrid (i.e. short- and long-reads) assembly approaches. Complete genomes allow a deeper understanding of bacterial evolution and genomic variation beyond single nucleotide variants (SNVs). They are also crucial for identifying plasmids, which often carry medically significant antimicrobial resistance (AMR) genes. However, small plasmids are often missed or misassembled by long-read assembly algorithms. Here, we present Hybracter which allows for the fast, automatic, and scalable recovery of near-perfect complete bacterial genomes using a long-read first assembly approach. Hybracter can be run either as a hybrid assembler or as a long-read only assembler. We compared Hybracter to existing automated hybrid and long-read only assembly tools using a diverse panel of samples of varying levels of long-read accuracy with manually curated ground truth reference genomes. We demonstrate that Hybracter as a hybrid assembler is more accurate and faster than the existing gold standard automated hybrid assembler Unicycler. We also show that Hybracter with long-reads only is the most accurate long-read only assembler and is comparable to hybrid methods in accurately recovering small plasmids.

Data Summary

1. Hybracter is developed using Python and Snakemake as a command-line software tool for Linux and MacOS systems.

2. Hybracter is freely available under an MIT License on GitHub (https://github.com/gbouras13/hybracter) and the documentation is available at Read the Docs (https://hybracter.readthedocs.io/en/latest/).

3. Hybracter is available to install via PyPI (https://pypi.org/project/hybracter/) and Bioconda (https://anaconda.org/bioconda/hybracter). A Docker/Singularity container is also available at https://quay.io/repository/gbouras13/hybracter.

4. All code used to benchmark Hybracter, including the reference genomes, is publicly available on GitHub (https://github.com/gbouras13/hybracter_benchmarking) with released DOI (https://zenodo.org/doi/10.5281/zenodo.10910108) available at Zenodo.

5. The subsampled FASTQ files used for benchmarking are publicly available at Zenodo with DOI (https://doi.org/10.5281/zenodo.10906937).

6. All super accuracy simplex ATCC FASTQ reads sequenced as a part of this study can be found under BioProject PRJNA1042815.

7. All *Hall* et al. fast accuracy simplex and super accuracy duplex ATCC FASTQ read files (prior to subsampling) can be found in the SRA under BioProject PRJNA1087001.

8. All raw *Lermaniaux* et al. FASTQ read files and genomes (prior to subsampling) can be found in the SRA under BioProject PRJNA1020811.

9. All *Staphylococcus aureus* JKD6159 FASTQ read files and genomes can be found under BioProject PRJNA50759.

10. All *Mycobacterium tuberculosis* H37R2 FASTQ read files and genomes can be found under BioProject PRJNA836783.

11. The complete list of BioSample accession numbers for each benchmarked sample can be found in Supplementary Table 1.

71   12. The benchmarking assembly output files are publicly available on Zenodo with

72   DOI (https://doi.org/10.5281/zenodo.10906937).

73   13. All Pypolca benchmarking outputs and code are publicly available on Zenodo

74   with DOI (https://zenodo.org/doi/10.5281/zenodo.10072192).

Impact Statement

Complete bacterial genome assembly using hybrid sequencing is a routine and vital part of bacterial genomics, especially for identification of mobile genetic elements and plasmids. As sequencing becomes cheaper, easier to access and more accurate, automated assembly methods are crucial. With Hybracter, we present a new long-read first automated assembly tool that is faster and more accurate than the widely-used Unicycler. Hybracter can be used both as a hybrid assembler and with long-reads only. Additionally, it solves the problems of long-read assemblers struggling with small plasmids, with plasmid recovery from long-reads only performing on par with hybrid methods. Hybracter can natively exploit the parallelisation of high-performance computing (HPC) clusters and cloud-based environments, enabling users to assemble hundreds or thousands of genomes with one line of code. Hybracter is available freely as source code on GitHub, via Bioconda or PyPi.

Introduction

Reconstructing complete bacterial genomes using *de novo* assembly methods had been considered too costly and time-consuming to be widely recommended in most cases, even as recently as 2015 [1]. This was due to the reliance on short-read sequencing technologies, which does not allow for reconstructing regions with repeats and extremely high GC content [2]. However, since then, advances in long-read sequencing technologies have allowed for the automatic construction of complete genomes using hybrid assembly approaches. Originally, this involved starting with a short-read assembly followed by scaffolding the repetitive and difficult to resolve regions with long-reads [3,4]. This approach was implemented in the command-line tool Unicycler, which remains the most popular tool for generating complete bacterial genome assemblies [5]. As long-read sequencing has improved in accuracy and availability, with the latest Oxford Nanopore Technologies reads recently reaching Q20 (99%+) median accuracy, a long-read first assembly approach supplemented by short-read polishing has recently been favoured for recovering accurate complete genomes. Long-read-first approaches provide greater accuracy and contiguity than short-read-first approaches in difficult regions [6–11]. The current gold standard manual assembly tool Trycycler even allows for the potential recovery of perfect genome assemblies [7]. However, Trycycler requires significant microbial bioinformatics expertise and involves manual decision making, creating a significant barrier to useability, scalability and automation [12].

Several tools exist that generate automated long-read first genome assemblies, such as MicroPIPE [13], ASA3P [14], Bactopia [15] and Dragonflye [16]. However, these tools do not consider factors such as genome reorientation [17] and recent polishing best-practices [18], and often contain the assembly workflow as a sub-module within a more expansive end-to-end

pipeline. Additionally, none of the existing tools consider the targeted recovery of plasmids.

As long-read assemblers struggle particularly with small plasmids, this leads to incorrectly

recovered or missing plasmids in bacterial assemblies [19].

We introduce Hybracter, a new command-line tool for automated near-perfect long-read-first

complete bacterial genome assembly. It implements a comprehensive and flexible workflow

allowing for long-read assembly polished with long and short-reads (with subcommand

'hybracter hybrid' for one or more samples and subcommand 'hybracter hybrid-single' for a

single sample) or long-read only assembly polished with long-reads (with subcommand

'hybracter long' for one or more samples and subcommand 'hybracter long-single' for a

single sample) (Table 1). For ease of use and familiarity, Hybracter has been designed with a

command-line interface containing parameters similar to Unicycler. Additionally, thanks to

its Snakemake [20] and Snaketool [21] implementation, Hybracter seamlessly scales from a single

isolate to hundreds or thousands of genomes with high computational efficiency and supports

deployment on HPC clusters and cloud-based environments.

Methods

Assembly Workflow

Hybracter implements a long-read-first automated assembly workflow based on current best

practices [12]. The main subcommands available in Hybracter can be found in Table 1 and the

workflow is outlined in Figure 1. Hybracter begins with long-reads for all subcommands, and

uses short-reads for polishing for 'Hybracter hybrid' and 'Hybracter hybrid-single'

subcommands.

First, long-read input FASTQs are input long read sets are filtered and subsampled to a depth

of 100x with Filtlong[22], which prioritises the longest and highest quality reads, outperforming

random subsampling (See Supplementary Table 11). The reads also have adapters trimmed

using Porechop_ABI[23], with optional contaminant removal against a host genome using

modules from Trimnami (e.g. if the bacteria has been isolated from a host) [24]. Quality control

of short-read input FASTQs is performed with fastp [25] (Fig 1A). The estimated depth of the

short-reads is determined using Seqkit[26].

Long-reads are then assembled with Flye [27]. If at least 1 contig is recovered above the cut-off

'-c' chromosome length specified by the user for the sample, that sample will be denoted as

'complete'. All such contigs will then be marked as chromosomes and kept for downstream

polishing and reorientation if marked as circular by Flye. If zero contigs are above the cut-off

chromosome length, the assembly will be denoted as 'incomplete', and all contigs will be

kept for downstream polishing (Fig 1B).

For all complete samples, targeted plasmid assembly is then conducted using Plassembler [28]

(Fig 1C). All samples (i.e. complete and incomplete) are then polished once with Medaka[29],

which can be turned off using '--no_medaka' (Fig 1D). It is recommended to turn off Medaka

using '--no_medaka' for highly accurate Q20+ read sets where Medaka has been shown to

introduce false positive changes[11]. For all complete samples only, chromosome(s) marked as

circular by Flye will then be reoriented to begin with the dnaA chromosomal replication

initiator gene using Dnaapler[30]. These reoriented chromosomes are then polished for a second

time with Medaka to ensure the sequence around the original chromosome breakpoint is

polished.

If the user has provided short-reads with Hybracter hybrid, all samples' assemblies (complete

and incomplete) are then polished with Polypolish [18] followed by Pypolca [31,32] (Fig 1F). The

exact parameters depend on the depth of short-read sequencing[31]. If the estimated short-read

coverage is below 5x, only Polypolish with '--careful' is run, as Pypolca can rarely introduce

false positive errors at low depths. If the estimated short-read coverage is between 5-25x,

Polypolish with --careful parameter is run followed by Pypolca with --careful parameter.

Above 25x coverage, Polypolish with default parameters followed by Pypolca with --careful

is run. This is because Pypolca --careful has been shown to be the best polisher at depths

above 5x, and because Polypolish is able to fix potential errors in repeats Pypolca may miss.

By default, the last short-read polishing round is chosen as the final assembly. Alternatively,

users can choose the highest scoring polishing round according to the reference-free ALE [33]

score.

If only long-reads are available (Hybracter long), the mean coding sequence (CDS) length is

calculated for each assembly using Pyrodigal [34,35], with larger mean CDS lengths indicating a

better quality assembly. The polishing round with the highest mean CDS length is chosen as

the final assembly (Fig 1G).

For each sample, a final output assembly FASTA file is created, along with per contig and

overall summary statistic TSV files, as well as separate chromosome and plasmid FASTA

files for samples denoted as complete (Fig 1H). An overall 'hybracter_summary.tsv' file is

also generated, which summarises outputs for all samples. All main output files are explained

in more detail in Table 2. All the main outputs can be found in the 'FINAL_OUTPUT'

subdirectory, while all other intermediate output files are available in other subdirectories for

users who would like extra information about their assemblies, including all assembly

assessments, comparisons of all changes introduced by polishing, and Flye and Plassembler

output summaries. A full list of these supplementary outputs can be found in Hybracter's

Documentation (https://hybracter.readthedocs.io/en/latest/output/).

Figure 1: Outline of the Hybracter workflow.

Hybracter
Hybrid or Long-Only
Bacterial Assembly
Pipeline

Long-Reads

Short-Reads
(Hybracter Hybrid Only)

A   **Quality Control**
(Optional)

Long-Reads

Short-Reads

Trimnami (Contamination Removal)
Filtlong (Filtering & Subsampling)
Porechop-ABI

fastp
Seqkit

C   **Plasmid Assembly**

B   **Long-Reads Assembly**

Plassembler

Flye

Complete
Chromosome(s)

Incomplete
Contigs

Long-Read Polishing
(Two Rounds)

Chromosome Reorientation

Start With *DnaA* Gene
Dnaapler

D   Medaka

E

Short-Read Polishing

G **Quality**
Assessment

H   **Output**

F   Polypolish
Pypolca careful

Run on B,D,E,F

Assembly Statistics
Final Chromosome and Plasmid
Assemblies

ALE/Pyrodigal

195   Table 1.   Summary of the 4 Primary Hybracter Commands

Command	Input	Number of Samples	Description	Workflow Elements Included by Default (From Figure 1)
hybracter hybrid	5 column csv sample sheet specified with '--input' containing: • sample name • long-read FASTQ path, • estimated chromosome length • R1 short-read FASTQ path • R2 short-read FASTQ path	1+	Long-read first assembly followed by long then short-read polishing for multiple isolates. Snakemake implementation ensures efficient use of available resources	A, B, C, D, E, F, G, H
hybracter hybrid-single	• sample name (-s) • long-read FASTQ path (-l) • estimated chromosome length (-c) • R1 short-read FASTQ path (-1) • R2 short-read FASTQ path (-2)	1	Long-read first assembly followed by long then short-read polishing for a single isolate. Similar command line interface to Unicycler	A, B, C, D, E, F, G, H
hybracter long	3 column csv sample sheet specified with '--input' containing: • sample name • long-read FASTQ path, • estimated chromosome length	1+	Long-read first assembly followed by long-read polishing for multiple isolates. Snakemake implementation ensures efficient use of available resources	A (no fastp), B, C, D, E, G, H
hybracter long-single	• sample name (-s) • long-read FASTQ path (-l) • estimated chromosome length (-c)	1	Long-read first assembly followed by long-read polishing on a single isolate.	A (no fastp), B, C, D, E, G, H

198   Table 2.   Description of the Primary Hybracter Output Files

Output File	Description
{sample}_final.fasta	Final assembly FASTA file for the sample. Contains all chromosome(s) and plasmids for complete isolates and all contigs for incomplete isolates.
{sample}_chromosome.fasta	Final assembly FASTA file for the chromosomes(s) in a complete sample.
{sample}_plasmid.fasta	Final assembly FASTA file for the plasmids in a complete sample.
hybracter_summary.tsv	A TSV file combining the {sample}_summary.tsv files for all samples.
{sample}_summary.tsv	A TSV file containing columns denoting for the sample: • Assembly completeness • Total assembly length • Number of contigs assembled • The polishing round deemed to be most accurate and selected as the final assembly • The length of the longest contig • The estimated coverage of the longest contig • The number of circular plasmids recovered by Plassembler
{sample}_per_contig_stats.tsv	A TSV file containing columns denoting for the sample: • Contig name • Contig Type (chromosome or plasmid) (complete samples only) • Contig length • Contig GC% • Contig circularity (complete samples only)

Tool Selection

Tools were selected for inclusion in Hybracter either based on benchmarking from the

literature, or they were specifically developed for inclusion in Hybracter. Flye [27] was chosen

as the long-read assembler because it is more accurate for bacterial genome assembly than

other long-read assemblers with comparable runtimes, such as Raven [36], Redbean [37] and

Miniasm [38], while being dramatically faster than the comparably accurate Canu [6,39]. Medaka

[29] was chosen as the long-read polisher because of its ability to improve assembly continuity

in addition to accuracy [12,40]. The benchmarking results of this study also emphasise that it is

particularly good at fixing insertion and deletion (InDel) errors, which cause problematic

frameshifts and frequently lead to fractured or truncated gene predictions. However, it should

be re-iterated that for modern Q20+ datasets, Medaka may introduce errors[11] and should not

be used (using --no_medaka with Hybracter). Polypolish and Pypolca in various

combinations depending on short-read depth were selected as short-read polishers, as these

have been shown to achieve the highest performance with the lowest chance of introducing

errors when used in combination [31].

We developed three standalone programs included in Hybracter. These are Dnaapler[30],

Plassembler[28] and Pypolca[31]. Dnaapler was developed to ensure the chromosome(s) identified

by Hybracter are reoriented to consistently begin with the dnaA chromosomal replication

initiator gene. Full implementation details can be found in the manuscript, with expanded

functionality beyond this use case[30]. Plassembler was developed to improve the runtime and

accuracy when assembling plasmids in bacterial isolates. Full implementation details can be

found in the manuscript for hybrid mode [28]. Hybracter long utilises Plassembler containing a

post-publication improvement for long-reads only ('Plassembler long') released in v1.3.

Plassembler long assembles plasmids from only long-reads by treating long-reads as both

short-reads and long-reads. Plassembler long does this by utilising Unicycler in its pipeline to

create a de Bruijn graph-based assembly, treating the long-reads as unpaired single-end reads,

which are then scaffolded with the same long-read set.

The third tool is Pypolca[31,32]. Pypolca is a Python re-implementation of the POLCA short-

read genome polisher, originally created specifically for inclusion in Hybracter and with an

almost identical output format and performance. Compared to POLCA, Pypolca features

improved useability with a simplified command line interface, allows the user to specify an

output directory and introduces a '--careful' parameter. The performance of Pypolca, and

particularly Pypolca with the --careful parameter, are described in the manuscript[31].

Benchmarking

To compare Hybracter's functionality and performance, we benchmarked its performance

against other software tools. We focused on the most popular state-of-the-art assembly tools

for automated hybrid and long only bacterial genome assemblies. All code to replicate these

analyses can be found at the repository

(https://github.com/gbouras13/hybracter_benchmarking). All programs and dependency

versions used for benchmarking can be found in Supplementary Table 4. For the hybrid tools,

we chose Unicycler and Dragonflye with both long-read and short-read polishing (denoted

'Dragonflye hybrid'). Dragonflye was chosen as it is a popular long-read first assembly

pipeline [16]. Both tools were run using default parameters. By default, Dragonflye conducts a

long-read assembly with Flye that is polished by Racon[41] followed by Polypolish. For the

long-read only tool, we chose Dragonflye with long-read Racon based polishing only

(denoted 'Dragonflye long').

We used 30 samples for benchmarking, representing genomes from a variety of Gram-

negative and Gram-positive bacteria. We chose these samples as they have real hybrid read

sets in combination with manually curated genome assemblies produced using either

Trycycler or Bact-builder[42]—a consensus-building pipeline based on Trycycler. These

samples came from 5 different studies below. We used the published genomes from these

studies as representatives of the 'ground truth' for these samples. Where read coverage

exceeded 100x samples were subsampled to approximately 100x coverage of the approximate

genome size with Rasusa v0.7.0[43] , as this better reflects more realistic read depth of real life

isolate sequencing. Nanoq v0.10.0[44] was used to generate quality control statistics for the

subsampled long-read sets. Four isolates did not have 100x long-read coverage — the entire

long-read set was used instead. A full summary table of the read lengths, quality, Nanopore

kit and base-calling models used in these studies can be found in Supplementary Table 2.

Hybracter v0.7.0 was used to conduct benchmarking. Medaka long-read polishing was used

for all samples except the 5 ATCC super-accuracy model basecalled duplex read samples,

where '--no_medaka' was used.

These samples contained varying levels of long-read quality (reflecting improvements in

Oxford Nanopore Technologies long-read technology), with the median Q score of long-read

sets ranging from 10.6 to 26.8. The five studies are:

1. Five ATCC strain isolates (ATCC-10708 *Salmonella enterica*, ATCC-17802 *Vibrio*

paragaemolyticus, ATCC-25922 *Escherichia coli*, ATCC-33560 *Campylobacter*

jejuni and ATCC-BAA-679 *Listeria monocytogenes*) with R10 chemistry super-

accuracy model basecalled simplex long-reads made available as a part of this study.

2. The same 5 ATCC isolates with R10 chemistry fast model basecalled long-reads, and

R10 chemistry super-accuracy model basecalled duplex long-reads from *Hall* et al.[45]

3. Twelve diverse carbapenemase-producing Gram-negative bacteria from *Lerminiaux* et

al.[9]

4. *Staphylococcus aureus* JKD6159 sequenced with both R9 and R10 chemistry long-

read sets from *Wick* et al.[46]

5. *Mycobacterium tuberculosis* HR37v from *Chitale* et al.[42]

The full details for each individual isolate used can be found in Supplementary Tables 1 and

2.

Chromosome Accuracy

The assembly accuracy of the chromosomes recovered by each benchmarked tool was

compared using Dnadiff v1.3 packaged with MUMmer v3.23[47]. Comparisons were

performed on the largest assembled contig (denoted as the chromosome) by each method,

other than for ATCC-17802 *Vibrio parahaemolyticus*, where the two largest contigs were

chosen as it has two chromosomes.

Plasmid Recovery Performance and Accuracy

Plasmid recovery performance for each tool was compared using the following methodology.

Summary statistics are presented in Table 4. See Supplementary Table 7 for a full sample-by-

sample analysis. All samples were analysed using the 4-step approach outlined below using

summary length and GC% statistics for all contigs and the output of Dnadiff v1.3

comparisons generated for each sample and tool combination against the reference genome

plasmids:

1. The number of circularised plasmid contigs recovered for each isolate was compared

to the reference genome. If the tool recovered a circularised contig homologous to that

in the reference, it was denoted as completely recovered. Specifically, a contig was

denoted as completely recovered if it had a genome length within 250bp of the

reference plasmid, a GC% within 0.1% of the reference plasmid and whether the

Total Query Bases covered was within 250bp of the Total Reference Bases from

Dnadiff. For Dragonflye assemblies, some plasmids were duplicated or multiplicated

due to known issues with the long-read first assembly approach for small plasmids

[6,19,48]. Any circularised contigs that were multiplicated compared to the reference

plasmid were therefore denoted as misassembled.

2. For additional circularised contigs not found in the reference recovered, these were

tested for homology with NCBI nt database using the web version of blastn[48]. If there

was a hit to a plasmid, the Plassembler output within Hybracter was checked for

whether the contig had a Mash hit (i.e. a Mash distance of 0.2 or lower) to plasmids in

the PLSDB[49]. If there was a hit, the contig was denoted as an additional recovered

plasmid. There were 2 in total (see Supplementary Table 7 and supplementary data).

3. Plasmids with contigs that were either not circularised but homologous to a reference

plasmid, or circularised but incomplete (failing the genome length and Dnadiff criteria

in 1.) were denoted as partially recovered or misassembled.

4. Reference plasmids without any homologous contigs in the assembly were denoted as

missed.

Additional non-circular contigs that had no homology with reference plasmids and were not

identified as plasmids in step 2 were analysed on a contig-by-contig basis and denoted as

additional non-plasmid contigs (see Supplementary Table 7 for contig-by-contig analysis

details).

Runtime Performance Comparison

To compare the performance of Hybracter, we compared wall-clock runtime consumption on

a machine with an Intel® Core™ i9-13900 CPU @ 5.60 GHz on a machine running Ubuntu

20.04.6 LTS with a total of 32 available threads (24 total cores). We ran all tools with 8 and

16 threads and with 32 GB of memory to provide runtime metrics comparable to commonly

available consumer hardware. Hybracter hybrid and long were run with 'hybracter hybrid-

single' and 'hybracter long-single' for each isolate to generate a comparable per sample

runtime for comparison with the other tools. The summary results are available in Table 5

and the detailed results for each specific tool and thread combination are found in

Supplementary Table 8.

Depth Analysis

To assess the effect of long-read depth on assembly accuracy, we chose *Lerminiaux* Isolate B

(*Enterobacter cloacae*) and subsampled the long-read depth at each interval of 5x from 10x

to 100x estimated genome size. All 5 tools were run on these read sets. Where a complete

chromosome was assembled, Dnadiff (as described above) was used to compare the

chromosome assembly to the reference.

Sequencing

DNA extraction was performed with the DNeasy Blood and Tissue kit (Qiagen). Illumina

library preparation was performed using Illumina DNA prep (Illumina Inc.) according to the

manufacturer's instructions. Short-read whole genome sequencing was performed an Illumina

MiSeq with a 250bp PE kit. Oxford Nanopore Technologies library preparation ligation

sequencing library was prepared using the ONT SQK-NBD114-96 kit and the resultant

library was sequenced using an R10.4.1 MinION flow cell (FLO-MIN114) on a MinION

Mk1b device. Data was base-called with Super-Accuracy Basecalling (SUP) using the

basecaller model dna_r10.4.1_e8.2_sup@v3.5.1.

Pypolca Benchmarking

Pypolca v0.2.0 was benchmarked against POLCA (in MaSuRCA v4.1.0)[32] using 18 isolates

described above. These were all 12 *Lerminiaux* et al. isolates, the R10 JKD6159 isolate [46] and

the 5 ATCC samples we sequenced as a part of this study. Benchmarking was conducted on

an Intel® Core™ i7-10700K CPU @ 3.80 GHz on a machine running Ubuntu 20.04.6 LTS.

All short read FASTQs used for benchmarking are identical to those used to benchmark

Hybracter. The assemblies used for polishing were intermediate chromosome assemblies

from Flye v2.9.2[50] generated within Hybracter. The outputs from Pypolca and POLCA were

compared using Dnadiff v1.3 packaged with MUMmer v3.23[47] Overall, Pypolca and POLCA

yielded extremely similar results. 16/18 assemblies were identical. ATCC 33560 had 2 Single

Nucleotide Polymorphisms (SNPs) between Pypolca and POLCA and *Lerminiaux* Isolate I

also had 2 SNPs.

Results

Chromosome Accuracy Performance

All tools recovered complete circular contigs for each chromosome. SNVs, small InDels (under 60 bps), and large InDels (over 60 bps) were compared as a measure of assembly accuracy. To account for differences in genomic size between isolates, SNVs and small InDel counts were normalised by genome length.

The summary results are presented in Table 3 and visualised in Figure 2. The detailed results for each tool and sample are presented in Supplementary Table 5. Of the hybrid tools, Dragonflye hybrid and Hybracter hybrid produced the fewest SNVs (both with median 0) followed by Unicycler (median 34). Hybracter hybrid produced the fewest InDels (median 0), followed by Dragonflye hybrid (median 2.5) and Unicycler (median 11). Hybracter hybrid also produced the fewest InDels plus SNVs (median 1), followed by Dragonflye hybrid (median 4.5) and Unicycler (median 57.5).

Additionally, Hybracter hybrid showed superior performance in terms of large InDels, with a median of 0 and a total of 9 large InDels across the 30 samples, compared to 2 and 70 for Dragonflye hybrid, and 1 and 87 for Unicycler.

Overall, Hybracter hybrid produced the most accurate chromosome assemblies. For twelve isolates, Hybracter assembled a perfect chromosome (*Lerminiaux* et al.[9] Isolates A, B, C, D, G, H, I, J, L, *S. aureus* JKD6159 with R10 chemistry and *L. monocytogenes* ATCC BAA-679 with simplex and duplex super-accuracy model basecalled reads).

Hybracter hybrid also produced several near-perfect assemblies (defined as <10 total SNVs

plus InDels with no large insertions or deletions), including on some lower quality fast model

basecalled reads (Supplementary Table 5).

Figure 2: Comparison of the counts of single nucleotide variants (SNVs) and small (<60bp)

insertions and deletions (InDels) (A) and the total number of large (>60bp) InDels (B) for

the hybrid tools benchmarked (Hybracter hybrid in dark blue, Dragonflye hybrid in orange

and Unicycler in green). The counts of SNVs and small InDels (C) and the total number of

large InDels (D) for the long tools benchmarked (Hybracter long in light blue, Dragonflye

long in grey) are also shown. All data presented is from the benchmarking output run

with 8 threads.

404
405

406   Table 3. Small (<60bp) InDels, SNVs and large (>60bp) InDels of Chromosomes

407   Assemblies for all Benchmarked Isolates.

Tool	Type	Small InDels	SNVs	Small InDels + SNVs	Large InDels
Hybracter hybrid	Hybrid	Median = 0 Minimum = 0 Maximum = 41	Median = 0 Minimum = 0 Maximum = 26	Median = 1 Minimum = 0 Maximum = 67	Total = 9 Median = 0 Minimum = 0 Maximum = 2
Dragonflye hybrid	Hybrid	Median = 2.5 Minimum = 0 Maximum = 112	Median = 0 Minimum = 0 Maximum = 64	Median = 4.5 Minimum = 0 Maximum = 154	Total = 70 Median = 2 Minimum = 0 Maximum = 12
Unicycler	Hybrid	Median = 11 Minimum = 0 Maximum = 125	Median = 34 Minimum = 0 Maximum = 165	Median = 57.5 Minimum = 3 Maximum = 290	Total = 87 Median = 1 Minimum = 0 Maximum = 16
Hybracter long	Long	Median = 16 Minimum = 1 Maximum = 743	Median = 21.5 Minimum = 0 Maximum = 156	Median = 54 Minimum = 1 Maximum = 852	Total = 11 Median = 1 Minimum = 0 Maximum = 3
Dragonflye long	Long	Median = 125 Minimum = 2 Maximum = 4814	Median = 34.5 Minimum = 0 Maximum = 2172	Median = 170.5 Minimum = 2 Maximum = 6332	Total = 68 Median = 2 Minimum = 0 Maximum = 12

Similar results were found in the long-read only tool comparison. Hybracter long produced

the fewest SNVs (median 21.5) compared to Dragonflye long (median 34.5). Hybracter long

consistently had far fewer small InDels (median 16) and large InDels (total 11 across 30

samples) compared to Dragonflye long (median 125 and total 68 respectively). No perfect

chromosomes were assembled by either long-only tool, though Hybracter long did assemble

three near-perfect chromosomes (*L. monocytogenes* ATCC BAA-679 with simplex and

duplex super-accuracy model basecalled reads and ATCC 10708 *S. enterica* with duplex

super-accuracy model basecalled reads) and several chromosomes with fewer than 50 total

small InDels plus SNVs and 0 large InDels (*Lerminiaux* isolates A, G, H, L, J, and *S. aureus*

JKD6159 with R10 chemistry, ATCC 10708 *S. enterica* with simplex super-accuracy model

basecalled reads).

Overall, Hybracter long showed consistently worse performance than the hybrid tools

Hybracter hybrid and Dragonflye hybrid tools (though not Unicycler) as measured by SNVs

and small InDels. Combined with the lack of perfect assemblies even for duplex super-

accuracy model basecalled read assemblies, this suggests the continuing utility of short-read

polishing for the isolates surveyed.

Plasmid Recovery Performance and Accuracy

Hybracter in both hybrid and long modes was superior at recovering plasmids compared to

the other tools in the same class (Table 4). Hybracter hybrid was able to completely recover

65/69 possible plasmids (the other two were partially recovered), compared to 60/69 for

Unicycler and only 44/69 for Dragonflye hybrid. Hybracter hybrid did not miss a single

plasmid, while Unicycler missed 3/69 (all in Isolate E *Klebsiella pneumoniae* from

Lerminiaux et al.) and Dragonflye hybrid completely missed 9/69. In terms of plasmid

accuracy, Hybracter hybrid and Unicycler were similar in terms of SNVs plus small InDels,

with medians of 1.62 and 2.02 per 100kbp respectively (Supplementary Table 9), while

Hybracter hybrid produced fewer large InDels than Unicycler (44 vs 63 in total).

Interestingly, Hybracter long showed strong performance at recovering plasmids despite

using only long-reads, completely recovering 60/69 plasmids and completely missing only

4/69. This performance was far superior to Dragonflye long (44/69 completely recovered,

9/69 missed). In terms of accuracy, both long tools were similar and unsurprisingly less

accurate than the hybrid tools in terms of SNVs plus small InDels (medians of 8.74 per

100kbp for Hybracter long and 7.66 per 100kbp for Dragonflye long).

All five tools detected an additional 5411bp plasmid in *Lerminiaux* Isolate G not found in the

reference sequence and Hybracter in both hybrid and long modes detected a further 2519bp

small plasmid from this genome.

Hybracter hybrid recovers more plasmids than either Unicycler or Dragonflye because it uses

a dedicated plasmid assembler, Plassembler. In addition, Hybracter long, using only long-

reads had an identical complete plasmid recovery rate to Unicycler, which uses both long-

and short-reads (60/69 for both). These results suggest that Hybracter long, by applying

algorithms designed for short-reads on long-reads, largely solves the existing difficulties of

recovering small plasmids from long-reads, at least on the benchmarking dataset of

predominantly R10 Nanopore reads[19,51]. Even on the lower quality fast basecalled ATCC

reads, Hybracter long performed well, with only one sample failing to produce a plasmid

assembly similar to higher quality datasets (ATCC 10708 *S. enterica* – See Supplementary

Tables 6 and 7).

Another notable result from Hybracter hybrid is that in 10/30 samples, it assembled

additional non-plasmid contigs, which occurred in only 2/30 isolates for Unicycler. This is a

limitation of Hybracter hybrid, as the extra sensitivity to recover plasmids comes with the

cost of more false positive non-plasmid contigs that may be low-depth artefacts of

sequencing. Hybracter has a 'depth_filter' parameter (defaulting to 0.25x of the chromosome

depth) that filters out all non-circular putative plasmid contigs below this value.

It should be noted, however, that these contigs are not always an assembly artefact and can

provide additional information regarding the quality control and similarity of short and long-

read sets. In Plassembler implemented within Hybracter hybrid, the existence of such contigs

is often indicative of mismatches between long- and short-read sets[28], suggesting that there

may be some heterogeneity between long- and short-reads in those samples.

Table 4. The Total Number of Plasmids Recovered by Each Tool. There were 59 total

reference plasmids in the 30 samples.

Tool	Complete Plasmids Recovered	Total Plasmids Partially Recovered or Misassembled	Total Plasmids Missed	Additional Plasmids Recovered not in Reference	Samples with Additional Non-Plasmid Contigs Recovered
Hybracter hybrid	65	4	0	2	10
Unicycler	60	6	3	1	2

Dragonflye hybrid	44	16	9	1	10
Hybracter long	60	5	4	2	3
Dragonflye long	44	16	9	1	10

Runtime Performance Comparison

As shown in Table 5 and Figure 3, median wall-clock times with 8 threads for Dragonflye

hybrid (4m34s) were smaller than Hybracter hybrid (15m03s), which were in turn smaller

than Unicycler (50m25s). For the long-only tools, Dragonflye long (4m10s) was faster than

Hybracter long (11m46s). Hybracter long was consistently slightly faster than Hybracter

hybrid (Table 5).

The difference in runtime performance between Hybracter and Dragonflye is predominantly

the result of the included targeted plasmid assembly and the reorientation and assessment

steps in Hybracter that are not included in Dragonflye. Additionally, the results suggest

limited benefits to running Hybracter with more than eight threads. As explained in the

following section, if a user has multiple isolates to assemble, a superior approach is to modify

the configuration file specifying more efficient resource requirements for each job in

Hybracter.

Table 5. Wall-clock Runtime Summary Statistics for Each Tool.

Tool	Type	8 Threads (hh:mm:ss)	16 Threads (hh:mm:ss)
Hybracter hybrid	Hybrid	Median **=** 00:15:03 Minimum = 00:04:29 Maximum = 00:54:41	Median = 00:13:44 Minimum = 00:03:27 Maximum = 00:44:36
Dragonflye hybrid	Hybrid	Median = 00:04:34 Minimum = 00:01:32 Maximum = 00:07:27	Median = 00:03:46 Minimum = 00:01:22 Maximum = 00:06:01
Unicycler	Hybrid	Median = 00:50:25 Minimum = 00:12:04 Maximum = 01:13:32	Median = 00:34:10 Minimum = 00:08:36 Maximum = 00:48:23
Hybracter long	Long	Median **=** 00:11:46 Minimum = 00:03:26 Maximum = 00:36:09	Median **=** 00:10:20 Minimum = 00:03:17 Maximum = 00:29:50
Dragonflye long	Long	Median = 00:04:10 Minimum = 00:01:22 Maximum = 00:06:01	Median **=** 00:04:34 Minimum = 00:01:32 Maximum = 00:07:27

Figure 3: Comparison of wall-clock runtime (in seconds) of Hybracter hybrid, Dragonflye

hybrid, Unicycler, Hybracter long and Dragonflye long when run with 8 and 16 threads.

Parallelisation Allows for Improved Efficiency

Hybracter allows users to specify and customise a configuration file to maximise resource

usage and runtime efficiency. Users can modify the desired threads, memory and time

requirements for each type of job that is run within Hybracter to suit their computational

resources. So that resources are not idle for most users on single sample assemblies, large

jobs such as the Flye and Plassembler assembly steps default to 16 threads and 32 GB of

memory.

To emphasise the efficiency benefits of parallelisation, the 12 *Lerminiaux* et al. isolates were

also assembled using 'hybracter hybrid' with a customised configuration file designed to

improve efficiency on the machine used for benchmarking. Specifically, the configuration

was changed to specify 8 threads and 16 GB of memory allocated to big jobs (assembly,

polishing and assessment) and 4 threads and 8 GB of memory allocated to medium jobs

(reorientation). More details on changing Hybracter's configuration file to suit specific

systems can be found in the documentation

(https://hybracter.readthedocs.io/en/latest/configuration/). We limited the overall 'hybracter

hybrid' run with 32 GB of memory and 16 threads to provide a fair comparison. The overall

'hybracter hybrid' run was then compared to the sum of the 12 'hybracter hybrid-single' runs.

Overall, the 12 isolates took 01h48m57s in the combined run, as opposed to 04h38m45s from

the sum of the 12 'hybracter hybrid-single' and 07h04m04s from the sum of the 12 Unicycler

runs. This inbuilt parallelisation of Hybracter provides significant efficiency benefits if

multiple samples are assembled simultaneously. The performance benefit of Hybracter

afforded by Snakemake integration in parallel computing systems may be variable over

different architectures, but this provides an example case of potential efficiency and

convenience benefits.

Long-Read Depth Does Not Affect Hybrid Assembly Accuracy If a Complete Chromosome

is Assembled

Finally, we tested the effect of long-read depth on the accuracy of assemblies with all five

tools at an estimated long-read depth from 10x to 100x at every interval of 5x for an example

isolate (*Lerminiaux* Isolate B, *Enterobacter cloacae*) with super-accuracy model basecalled

simplex reads (Figure 4 and Supplementary Table 12). At 10x and 15x sequencing depth,

only Unicycler was able to assemble a complete chromosome. From 20x and above, all five

tools were able to assemble complete chromosomes. For the hybrid tools, once a complete

chromosome was assembled, increasing long-read depth had a negligible impact on accuracy

results (Figure 4). Notably, Hybracter hybrid was able to produce perfect assemblies from as

low as 20x long-read depth. For long-read only tools, increasing long-read depth did affect

accuracy. Increasing depth improved SNV accuracy for both Hybracter long and Dragonflye

long (Figure 4C). For small InDels, Hybracter long improved with extra depth, while

Dragonflye long actually performed worse (Figure 4A). Depth had minimal impact on large

InDels (Figure 4B).

Figure 4: Comparison of the counts of small (<60bp) (A) and large (>60bp) (B) insertions

and deletions (InDels) and SNVs (C) for Hybracter hybrid, Dragonflye hybrid, Unicycler,

Hybracter long and Dragonflye long chromosome assemblies of *Lerminiaux* Isolate B

(*Enterobacter cloacae*) at 5x intervals of sequencing depth from 10x to 100x.

Discussion

As long-read sequencing has improved in accuracy with reduced costs, it is now routine to

use a combination of long- and short-reads to generate complete bacterial genomes[3,5]. Recent

advances in assembly algorithms and accuracy improvements mean that a long-read first

hybrid assembly should be favoured with short-reads being used after assembly for polishing

[12], as opposed to the short-read first assembly approach (where long-reads are only used for

scaffolding a short-read assembly) utilised by the current gold standard automated assembler

Unicycler. The Unicycler approach is more prone to larger scale InDel errors as well as

smaller scale errors such as those caused by homopolymers or methylation motifs [6,11,52,53].

Additionally, it should be noted that it is already possible (while perhaps not routine) to

generate perfect hybrid bacterial genome assemblies using manual consensus approaches

requiring human intervention, such as Trycycler[7,54]. While manual approaches such as

Trycycler generally yield superior results to automated approaches, manually assembling

many complete genomes is challenging as considerable time, resources and bioinformatics

expertise are required.

The results of this study emphasise that the long-read first hybrid approach consistently

yields superior assemblies than the short-read first hybrid approach and should therefore be

preferred going forward. The only exception where a short-read first approach is to be

preferred is where a limited depth of long-read sequencing data is available (<20x depth). In

this instance, long-read first hybrid approaches may struggle to assemble a complete

chromosome, while short-read first approaches like Unicycler may be able to (Figure 4).

Interestingly, in the course of conducting benchmarking for this study, we found a large

number of discrepancies between older short-read first assembled 'reference genomes' for *S.*

aureus JKD6159 [55] and the five ATCC genomes benchmarked compared to updated

Trycycler long-read first references (See Supplementary Table 13). The number of

discrepancies ranged from 44 to 8,255 across the six genomes. Therefore, we recommend that

older short-read first reference genomes be updated if possible using a long-read assembly

approach (such as with Trycycler).

This study also shows that automated perfect hybrid genome assemblies are already possible

with Hybracter. This study and others[9,54] also confirm that a long-read first hybrid approach

remains preferable to long-read only assembly with Nanopore reads, as short-reads continue

to provide accuracy improvements in polishing steps. However, it is foreseeable that short-

reads will soon provide little or no accuracy improvements and will not be needed to polish

long-read only assemblies to perfection. Already, perfect long-read only assemblies are

possible, at least with manual intervention using Trycycler [7]. Accordingly, automated perfect

bacterial genome assemblies may soon become possible from long-reads only. Hybracter also

allows users to turn long-read polishing off altogether. It is already established that long-read

polishing can introduce errors and make long-read only assemblies worse with highly

accurate Nanopore and PacBio reads[11,31]. Therefore, this feature may become increasingly

useful as long-read sequencing continues to improve in accuracy and we recommend its use

for highly accurate Q20+ long-reads.

Hybracter was created to bridge the gap from the present to the future of automated perfect

hybrid and long-read-only bacterial genome assemblies. The results of this study show that

Hybracter in hybrid mode is both faster and more accurate than the current gold standard tool

for hybrid assembly Unicycler and is more accurate than Dragonflye in both modes. It should

be noted that if users want fast chromosome-only assemblies where accuracy is not essential

(for applications such as species identification or sequence typing), Dragonflye remains a

good option due to its speed.

Hybracter especially excels in recovering complete plasmid genomes compared to other

tools. By incorporating Plassembler, Hybracter recovers more complete plasmid genomes

than Unicycler in hybrid mode. Further, Hybracter long is comparable to Unicycler and

Hybracter hybrid when using long-reads only for plasmid recovery.

The high error rates of long-read sequencing technologies have prevented the application of

assembly approaches designed for highly accurate short-reads, such as constructing de Bruijn

graphs (DBGs) based on strings of a particular length k (k-mers) [56–58]. This resulted in

bioinformaticians initially utilising less efficient algorithms designed with long-reads in

mind, such as utilising overlap graphs in place of DBGs[27,37,39,59,60]. While DBGs have been

used for long-read assembly in some applications [61–63], adoption, especially in microbial

genomics, has been limited.

Although long-read first assembly methods enable complete chromosome and large plasmid

reconstruction, it is well established that long-read only assemblers struggle to assemble

small (<20kbp) plasmids accurately, often leading to missing or multiplicated assemblies[6,51].

These errors may be exacerbated if ligation chemistry-based sequencing kits are used[51].

Therefore, hybrid DBG based short-read first assemblies are traditionally recommended for

plasmid recovery[12].

Implemented in our post-publication changes to Plassembler described in this study,

Hybracter solves the problem of small plasmid recovery using long-reads. It achieves this by

implementing a DBG-based assembly approach with Unicycler. The same read set is used

twice, first as unpaired pseudo 'short' reads and then as long-reads; the long-read set

scaffolds a DBG-based assembly based on the same read set. This study demonstrates that

current long-read technologies, such as R10 Nanopore reads, are now accurate enough that

some short-read algorithms are applicable. Our results also suggest that similar DBG-based

algorithmic approaches could be used to enhance the recovery of small replicons in long-read

datasets beyond the use case presented here of plasmids in bacterial isolate assemblies. This

could potentially enhance the recovery of replicons such as bacteriophages[64] or other small

contigs from metagenomes using only long-reads[10,50].

Finally, consistent and resource efficient assemblies that are as accurate as possible in

recovering both plasmids and chromosomes are crucial, particularly for larger studies

investigating plasmid epidemiology and evolution. AMR genes carried on plasmids can have

complicated patterns of transmission involving horizontal transfer between different bacterial

species and lineages, transfer between different plasmid backbones, and integration into and

excision from the bacterial chromosome[65–67]. Accurate plasmid assemblies are crucial in

genomic epidemiology studies investigating transmission of antimicrobial resistant bacteria

within outbreak settings, as well as in a broader One Health context, where hundreds or even

thousands of assemblies may be analysed[68–71]. Hybracter will facilitate the expansion of such

studies, allowing for faster and more accurate automated complete genome assemblies than

existing tools. Additionally, by utilising Snakemake[20] with a Snaketool[21] command line

interface, Hybracter is easily and efficiently parallelised to optimise available resources over

various large-scale computing architectures. Individual jobs (such as each assembly,

reorientation, polishing or assessment step) within Hybracter are automatically sent to

different resources on a high performance computing (HPC) cluster using the HPC's job

scheduling system like Slurm[72]. Hybracter can natively use any Snakemake-supported cloud-

based deployments such as Kubernetes, Google Cloud Life Sciences, Tibanna, and Azure

Batch.

Conclusion

Hybracter is substantially faster than the current gold standard automated tool Unicycler,

assembles chromosomes more accurately than existing methods, and is superior at recovering

complete plasmid genomes. By applying DBG-based algorithms designed for short-reads on

current generation long-reads, Hybracter long also solves the problem of long-read-only

assemblers entirely missing or duplicating small circular elements such as plasmids.

Hybracter is resource efficient and natively supports deployment on high-performance

computer clusters and cloud environments for massively parallel analyses. We believe

Hybracter will prove to be an extremely useful tool for the automated recovery of complete

bacterial genomes from hybrid and long-read-only sequencing data suitable for massive

datasets.

Acknowledgements

This work was supported with supercomputing resources provided by the Phoenix HPC service at the University of Adelaide. We would particularly like to thank Fabien Voisin for his integral role in maintaining and running Phoenix. We would also like to thank Brad Hart for useful comments in testing Hybracter and Simone Pignotti, Yu Wan and Oliver Schwengers for providing helpful comments and GitHub pull requests.

Funding

G.H. was supported by The University of Adelaide International Scholarships and a THRF Postgraduate Top-up Scholarship. A.E.S was supported by a University of Adelaide Barbara Kidman Women's Fellowship. R.A.E was supported by an award from the NIH NIDDK RC2DK116713 and an award from the Australian Research Council DP220102915. S.V. was supported by a Passe and Williams Foundation senior fellowship.

Conflicts of Interest

The authors declare that there are no conflicts of interest.

References

References

1. Land, M. *et al.* Insights from 20 years of bacterial genome sequencing. *Funct Integr*

Genomics **15**, 141–161 (2015).

2. Goldstein, S., Beka, L., Graf, J. & Klassen, J. L. Evaluation of strategies for the assembly

of diverse bacterial genomes using MinION long-read sequencing. *BMC Genomics* **20**,

23 (2019).

3. De Maio, N. *et al.* Comparison of long-read sequencing technologies in the hybrid

assembly of complex bacterial genomes. *Microbial Genomics* **5**, e000294 (2019).

4. Wick, R. R., Judd, L. M., Gorrie, C. L. & Holt, K. E. Y. 2017. Completing bacterial

genome assemblies with multiplex MinION sequencing. *Microbial Genomics* **3**,

e000132.

5. Wick, R. R., Judd, L. M., Gorrie, C. L. & Holt, K. E. Unicycler: Resolving bacterial

genome assemblies from short and long sequencing reads. *PLOS Computational*

Biology **13**, e1005595 (2017).

6. Wick, R. R. & Holt, K. E. Benchmarking of long-read assemblers for prokaryote whole

genome sequencing. Preprint at https://doi.org/10.12688/f1000research.21782.4

(2021).

7. Wick, R. R. *et al.* Trycycler: consensus long-read assemblies for bacterial genomes.

Genome Biology **22**, 266 (2021).

8. Wick, R. ONT-only accuracy with R10.4.1. *Ryan Wick's bioinformatics blog*

https://rrwick.github.io/2023/05/05/ont-only-accuracy-with-r10.4.1.html

https://doi.org/10.5281/zenodo.7898220 (2023).

9. Lerminiaux, N., Fakharuddin, K., Mulvey, M. R. & Mataseje, L. Do we still need

Illumina sequencing data? Evaluating Oxford Nanopore Technologies R10.4.1 flow

cells and the Rapid v14 library prep kit for Gram negative bacteria whole genome

assemblies. *Can. J. Microbiol.* (2024) doi:10.1139/cjm-2023-0175.

10. Sereika, M. *et al.* Oxford Nanopore R10.4 long-read sequencing enables the

generation of near-finished bacterial genomes from pure cultures and metagenomes

without short-read or reference polishing. *Nat Methods* **19**, 823–826 (2022).

11. Wick, R. ONT-only accuracy: 5 kHz and Dorado. *Ryan Wick's bioinformatics blog*

https://rrwick.github.io/2023/10/24/ont-only-accuracy-update.html

https://doi.org/10.5281/zenodo.10038672 (2023).

12. Wick, R. R., Judd, L. M. & Holt, K. E. Assembling the perfect bacterial genome using

Oxford Nanopore and Illumina sequencing. *PLOS Computational Biology* **19**,

e1010905 (2023).

13. Murigneux, V. *et al.* MicroPIPE: validating an end-to-end workflow for high-quality

complete bacterial genome construction. *BMC Genomics* **22**, 474 (2021).

14. Schwengers, O. *et al.* ASA3P: An automatic and scalable pipeline for the assembly,

annotation and higher-level analysis of closely related bacterial isolates. *PLOS*

Computational Biology **16**, e1007134 (2020).

15. Petit, R. A. & Read, T. D. Bactopia: a Flexible Pipeline for Complete Analysis of

Bacterial Genomes. *mSystems* **5**, 10.1128/msystems.00190-20 (2020).

16. Petit III, R. A. Dragonflye: Assemble bacterial isolate genomes from Nanopore reads.

17. Hunt, M. *et al.* Circlator: automated circularization of genome assemblies using long

sequencing reads. *Genome Biology* **16**, 294 (2015).

18. Wick, R. R. & Holt, K. E. Polypolish: Short-read polishing of long-read bacterial

genome assemblies. *PLOS Computational Biology* **18**, e1009802 (2022).

19. Johnson, J., Soehnlen, M. & Blankenship, H. M. Long read genome assemblers

struggle with small plasmids. *Microbial Genomics* **9**, 001024 (2023).

20. Mölder, F. *et al.* Sustainable data analysis with Snakemake. Preprint at

https://doi.org/10.12688/f1000research.29032.2 (2021).

21. Roach, M. J. *et al.* Ten simple rules and a template for creating workflows-as-

applications. *PLOS Computational Biology* **18**, e1010705 (2022).

22. Wick, R. R. Filtlong. github. com/rrwick/Filtlong (2018).

23. Bonenfant, Q., Noé, L. & Touzet, H. Porechop_ABI: discovering unknown adapters in

Oxford Nanopore Technology sequencing reads for downstream trimming.

Bioinformatics Advances **3**, vbac085 (2023).

24. Roach, M. J. Trimnami: Trim lots of metagenomics samples all at once. (2023).

25. Chen, S., Zhou, Y., Chen, Y. & Gu, J. fastp: an ultra-fast all-in-one FASTQ preprocessor.

Bioinformatics **34**, i884–i890 (2018).

26. Shen, W., Le, S., Li, Y. & Hu, F. SeqKit: A Cross-Platform and Ultrafast Toolkit for

FASTA/Q File Manipulation. *PLOS ONE* **11**, e0163962 (2016).

27. Kolmogorov, M., Yuan, J., Lin, Y. & Pevzner, P. A. Assembly of long, error-prone reads

using repeat graphs. *Nat Biotechnol* **37**, 540–546 (2019).

28. Bouras, G., Sheppard, A. E., Mallawaarachchi, V. & Vreugde, S. Plassembler: an

automated bacterial plasmid assembly tool. *Bioinformatics* **39**, btad409 (2023).

29. medaka: Sequence correction provided by ONT Research.

30. Bouras, G., Grigson, S. R., Papudeshi, B., Mallawaarachchi, V. & Roach, M. J. Dnaapler:

A tool to reorient circular microbial genomes. *Journal of Open Source Software* **9**,

5968 (2024).

31. Bouras, G. *et al.* How low can you go? Short-read polishing of Oxford Nanopore

bacterial genome assemblies. 2024.03.07.584013 Preprint at

https://doi.org/10.1101/2024.03.07.584013 (2024).

32. Zimin, A. V. & Salzberg, S. L. The genome polishing tool POLCA makes fast and

accurate corrections in genome assemblies. *PLOS Computational Biology* **16**,

e1007981 (2020).

33. Clark, S. C., Egan, R., Frazier, P. I. & Wang, Z. ALE: a generic assembly likelihood

evaluation framework for assessing the accuracy of genome and metagenome

assemblies. *Bioinformatics* **29**, 435–443 (2013).

34. Larralde, M. Pyrodigal: Python bindings and interface to Prodigal, an efficient

method for gene prediction in prokaryotes. *Journal of Open Source Software* **7**, 4296

(2022).

35. Hyatt, D. *et al.* Prodigal: prokaryotic gene recognition and translation initiation site

identification. *BMC Bioinformatics* **11**, 119 (2010).

36. Vaser, R. & Šikić, M. Time- and memory-efficient genome assembly with Raven. *Nat*

Comput Sci **1**, 332–336 (2021).

37. Ruan, J. & Li, H. Fast and accurate long-read assembly with wtdbg2. *Nat Methods* **17**,

155–158 (2020).

38. Li, H. Minimap and miniasm: fast mapping and de novo assembly for noisy long

sequences. *Bioinformatics* **32**, 2103–2110 (2016).

39. Koren, S. *et al.* Canu: scalable and accurate long-read assembly via adaptive k-mer

weighting and repeat separation. *Genome Res.* **27**, 722–736 (2017).

40. Zhang, X. *et al.* Benchmarking of long-read sequencing, assemblers and polishers for

yeast genome. *Briefings in Bioinformatics* **23**, bbac146 (2022).

41. Vaser, R., Sović, I., Nagarajan, N. & Šikić, M. Fast and accurate de novo genome

assembly from long uncorrected reads. *Genome Res.* **27**, 737–746 (2017).

42. Chitale, P. *et al.* A comprehensive update to the Mycobacterium tuberculosis H37Rv

reference genome. *Nat Commun* **13**, 7068 (2022).

43. Hall, M. B. Rasusa: Randomly subsample sequencing reads to a specified coverage.

Journal of Open Source Software **7**, 3941 (2022).

44. Steinig, E. & Coin, L. Nanoq: ultra-fast quality control for nanopore reads. *Journal of*

Open Source Software **7**, 2991 (2022).

45. Hall, M. B. *et al.* Benchmarking reveals superiority of deep learning variant callers on

bacterial nanopore sequence data. 2024.03.15.585313 Preprint at

https://doi.org/10.1101/2024.03.15.585313 (2024).

46. Wick, R. R., Judd, L. M., Monk, I. R., Seemann, T. & Stinear, T. P. Improved Genome

Sequence of Australian Methicillin-Resistant Staphylococcus aureus Strain JKD6159.

Microbiology Resource Announcements **12**, e01129-22 (2023).

47. Kurtz, S. *et al.* Versatile and open software for comparing large genomes. *Genome*

Biology **5**, R12 (2004).

48. Sayers, E. W. *et al.* Database resources of the national center for biotechnology

information. *Nucleic Acids Research* **50**, D20–D26 (2022).

49. Galata, V., Fehlmann, T., Backes, C. & Keller, A. PLSDB: a resource of complete

bacterial plasmids. *Nucleic Acids Research* **47**, D195–D202 (2019).

50. Kolmogorov, M. *et al.* metaFlye: scalable long-read metagenome assembly using

repeat graphs. *Nat Methods* **17**, 1103–1110 (2020).

51. Wick, R. R., Judd, L. M., Wyres, K. L. & Holt, K. E. Y. 2021. Recovery of small plasmid

sequences via Oxford Nanopore sequencing. *Microbial Genomics* **7**, 000631 (2021).

52. Marinus, M. G. & Løbner-Olesen, A. DNA Methylation. *EcoSal Plus* **6**,

10.1128/ecosalplus.ESP-0003–2013 (2014).

53. Wick, R. R., Judd, L. M. & Holt, K. E. Performance of neural network basecalling tools

for Oxford Nanopore sequencing. *Genome Biology* **20**, 129 (2019).

54. Sanderson, N. D. *et al.* Comparison of R9.4.1/Kit10 and R10/Kit12 Oxford Nanopore

flowcells and chemistries in bacterial genome reconstruction. *Microbial Genomics* **9**,

000910 (2023).

55. Chua, K. *et al.* Complete Genome Sequence of Staphylococcus aureus Strain JKD6159,

a Unique Australian Clone of ST93-IV Community Methicillin-Resistant

Staphylococcus aureus. *Journal of Bacteriology* **192**, 5556–5557 (2010).

56. Bankevich, A. *et al.* SPAdes: A New Genome Assembly Algorithm and Its Applications

to Single-Cell Sequencing. *Journal of Computational Biology* **19**, 455–477 (2012).

57. Li, D., Liu, C.-M., Luo, R., Sadakane, K. & Lam, T.-W. MEGAHIT: an ultra-fast single-

node solution for large and complex metagenomics assembly via succinct de Bruijn

graph. *Bioinformatics* **31**, 1674–1676 (2015).

58. Compeau, P. E. C., Pevzner, P. A. & Tesler, G. How to apply de Bruijn graphs to

genome assembly. *Nature Biotechnology* **29**, 987–991 (2011).

59. Wong, J. *et al.* Linear time complexity de novo long read genome assembly with

GoldRush. *Nat Commun* **14**, 2906 (2023).

60. Amarasinghe, S. L. *et al.* Opportunities and challenges in long-read sequencing data

analysis. *Genome Biology* **21**, 30 (2020).

61. Ekim, B., Berger, B. & Chikhi, R. Minimizer-space de Bruijn graphs: Whole-genome

assembly of long reads in minutes on a personal computer. *Cell Syst* **12**, 958-968.e6

(2021).

62. Bankevich, A., Bzikadze, A. V., Kolmogorov, M., Antipov, D. & Pevzner, P. A. Multiplex

de Bruijn graphs enable genome assembly from long, high-fidelity reads. *Nat*

Biotechnol **40**, 1075–1081 (2022).

63. Lin, Y. *et al.* Assembly of long error-prone reads using de Bruijn graphs. *Proceedings*

of the National Academy of Sciences **113**, E8396–E8405 (2016).

64. Mallawaarachchi, V. *et al.* Phables: from fragmented assemblies to high-quality

bacteriophage genomes. *Bioinformatics* **39**, btad586 (2023).

65. Mathers, A. J. *et al.* Chromosomal Integration of the Klebsiella pneumoniae

Carbapenemase Gene, blaKPC, in Klebsiella Species Is Elusive but Not Rare.

Antimicrobial Agents and Chemotherapy **61**, e01823-16 (2017).

66. Houtak, G. *et al.* The intra-host evolutionary landscape and pathoadaptation of

persistent Staphylococcus aureus in chronic rhinosinusitis. *Microbial Genomics* **9**,

001128 (2023).

67. Sheppard, A. E. *et al.* Nested Russian Doll-Like Genetic Mobility Drives Rapid

Dissemination of the Carbapenem Resistance Gene blaKPC. *Antimicrobial Agents and*

Chemotherapy **60**, 3767–3778 (2016).

68. Hawkey, J. *et al.* ESBL plasmids in Klebsiella pneumoniae: diversity, transmission

and contribution to infection burden in the hospital setting. *Genome Medicine* **14**, 97

(2022).

69. Matlock, W. *et al.* Enterobacterales plasmid sharing amongst human bloodstream

infections, livestock, wastewater, and waterway niches in Oxfordshire, UK. *eLife* **12**,

e85302 (2023).

70. Roberts, L. W. *et al.* Long-read sequencing reveals genomic diversity and associated

plasmid movement of carbapenemase-producing bacteria in a UK hospital over 6

years. *Microbial Genomics* **9**, 001048 (2023).

71. Lerminiaux, N. *et al.* Plasmid genomic epidemiology of blaKPC carbapenemase-

producing Enterobacterales in Canada, 2010–2021. *Antimicrobial Agents and*

Chemotherapy **0**, e00860-23 (2023).

72. Yoo, A. B., Jette, M. A. & Grondona, M. SLURM: Simple Linux Utility for Resource

Management. in *Job Scheduling Strategies for Parallel Processing* (eds. Feitelson, D.,

862 Rudolph, L. & Schwiegelshohn, U.) 44–60 (Springer, Berlin, Heidelberg, 2003).

863 doi:10.1007/10968987_3.

Supplementary Figure 1: For lower quality samples only (all five ATCC fast model base-called samples, *S. aureus* JKD6159 with R9 chemistry and *M. tuberculosis* H37R2), this figure presents a comparison of the counts of small nucleotide variants (SNVs) and small (<60bp) insertions and deletions (InDels) (A) and the total number of large (>60bp) InDels (B) for the hybrid tools benchmarked (Hybracter hybrid in dark blue, Dragonflye hybrid in orange and Unicycler in green). The counts of SNVs and small InDels (C) and the total number of large InDels (D) for the long tools benchmarked (Hybracter long in light blue, Dragonflye long in grey) are also shown. All data presented is from the benchmarking output run with 8 threads.

Supplementary Figure 2: For simplex super-accuracy model basecalled samples (five ATCC, *S. aureus* JKD6159 with R10 chemistry and all twelve *Lerminiaux* et al. samples), this figure presents a comparison of the counts of small nucleotide variants (SNVs) and small (<60bp) insertions and deletions (InDels) (A) and the total number of large (>60bp) InDels (B) for the hybrid tools benchmarked (Hybracter hybrid in dark blue, Dragonflye hybrid in orange and Unicycler in green). The counts of SNVs and small InDels (C) and the total number of large InDels (D) for the long tools benchmarked (Hybracter long in light blue, Dragonflye long in grey) are also shown. All data presented is from the benchmarking output run with 8 threads.

Supplementary Figure 3: For duplex super-accuracy model basecalled samples (five ATCC samples), this figure presents a comparison of the counts of small nucleotide variants (SNVs) and small (<60bp) insertions and deletions (InDels) (A) and the total number of large (>60bp) InDels (B) for the hybrid tools benchmarked (Hybracter hybrid in dark blue, Dragonflye hybrid in orange and Unicycler in green). The counts of SNVs and small InDels (C) and the total number of large InDels (D) for the long tools benchmarked (Hybracter long in light blue, Dragonflye long in grey) are also shown. All data presented is from the benchmarking output run with 8 threads.