1

Benchmarking the identification of a single degraded protein to explore optimal search strategies for ancient proteins

Ismael Rodriguez Palomo[1], Bharath Nair[1,2], Yun Chiang[2,3], Joannes Dekker[2,4], Benjamin Dartigues[5], Meaghan Mackie[2,6,7,8], Miranda Evans[1,4], Ruairidh Macleod[1], Jesper V. Olsen[6], Matthew J. Collins[1,2]

[1] McDonald Institute for Archaeological Research, University of Cambridge, United Kingdom

[2] Globe Institute, University of Copenhagen, Denmark

[3] The Nice Institute of Chemistry, Université Côte d'Azur, Nice, France

[4] Department of Archaeology, University of York, United Kingdom

[5] Department of Science and Technology, University of Bordeaux, France

[6] Novo Nordisk Foundation Center for Protein Research, University of Copenhagen, Denmark

[7] School of Archaeology, University College Dublin, Ireland

[8] Archaeobiomics, Department of Life Sciences and Systems Biology, University of Turin, Italy

Keywords

Palaeoproteomics; beta-lactoglobulin; False Discovery Rate; benchmarking; *de novo*; open search

Abstract

Palaeoproteomics is a rapidly evolving discipline, and practitioners are constantly developing novel strategies for the analyses and interpretations of complex, degraded protein mixtures. The community has also established standards of good practice to interrogate our data. However, there is a lack of a systematic exploration of how these affect the identification of peptides, post-translational modifications (PTMs) and protein and their significance (through the False Discovery Rate) and correctness. We systematically investigated the performance of a wide range of sequencing tools and search engines in a controlled system: the experimental degradation of the single purified bovine β-lactoglobulin (BLG), heated at 95 ºC and pH 7 for 0, 4 and 128 days. We target BLG since it is one of the most robust and ubiquitous proteins in the archaeological record. We tested different reference database choices, a targeted dairy protein one, and whole bovine proteome and three digestion options (tryptic-, semi-tryptic- and non-specific searches), in order to evaluate the effects of search space and the identification of peptides. We also explored alternative strategies, including open search that allows for the global identification of PTMs based upon wide precursor mass tolerance and *de novo* sequencing to boost sequence coverage. We analysed the samples using Mascot, MaxQuant, Metamorpheus, pFind, Fragpipe and DeNovoGUI (pepNovo, DirecTag, Novor), and we benchmarked these tools and discussed the optimal strategy for the characterisation of ancient proteins.

Introduction

Proteomics software has been developed to identify and quantify proteins for different purposes and in various contexts, by processing and analysing mass spectrometry data (Aebersold & Mann, 2003). Many of these tools have been developed to analyse proteins in complex mixtures and map for post-translational modifications (PTMs). Most studies involve querying the mass spectra against a database of possible proteins (database search, *DBs*). Others aim at reconstructing the peptide sequences *de novo* from the spectra, without using any external data (*de novo* sequencing, *dnS*). Increasingly these methods are being applied beyond 'typical' tissues for which these software are optimised.

DBs approaches work effectively on modern tissues from well-studied organisms with complete sequence databases, typically matching up to 50% of MS/MS queries to peptides (peptide-spectrum matches, PSMs) in a typical tandem mass spectrometry experiment (Cox & Mann, 2008). Larger studies looking at PRIDE (Perez-Riverol et al., 2021) and MassIVE databases have determined that around 75% of submitted spectra remain unidentified (Griss et al., 2016; Bittremieux et al., 2022). Metaproteomics studies attempt to map proteins derived from complex samples such as microbiomes, in which it may be difficult to identify all the targets present without a proteogenomics strategy. The same is true for highly variable sequences, such as those found in immunoglobulins or novel sequences as found in cancers (Alfaro et al., 2017). *dnS* tools like PEAKS (Zhang et al., 2012) were initially developed in order to characterise these sequences. In addition to novel proteins introduced from the microbial community, the application of proteomics to food and forensics is complicated by an increase in the number of PTMs due to both enzymatic and chemical modifications or introduced by bacterial effectors (Liu et al., 2023).

Palaeoproteomics, the study of ancient proteins that are often fragmented and heavily modified, combines all of the above challenges. From studies of historical artworks to wider studies of material culture or skeletal remains in archaeology and palaeontology, chemical degradation adds further to the challenges of identification. In the field, most published ancient spectra remain unidentified. *De novo* sequencing has been decisive in studies looking at the phylogeny and evolutionary history of extinct organisms (Welker et al., 2015, 2019; Chen et al., 2019; Presslee et al., 2019; Cappellini et al., 2019). However, noise and missing ions might produce errors that can never be identified without matching to a database sequence. Muth and Renard (2018) evaluated the accuracy of different *dnS* software. They showed that only around 35% of the complete peptide sequences were correct on real HCD (higher-energy collisional dissociation) data and 85% on simulated data. On a different front, there are increasing efforts to minimise and identify modern

protein contaminants in ancient samples. Deamidation rates have been proposed and applied to
authenticate ancient proteins (Ramsøe et al., 2020, 2021). However, a clear correlation between
deamidation rates and time is yet to be established (Schroeter & Cleland, 2016). A deeper
understanding of deamidation and other degradation patterns is key for ancient protein
authentication.

At present, the field of palaeoproteomics has tended to use the same software tools as those
originally designed for identification on targeted tissues. And due to the awareness of the specific
challenges, the community sets and demands stringent approaches to interrogate the data (Hendy,
Welker, et al., 2018; Hendy, Warinner, et al., 2018; Warinner et al., 2022). This includes the
consideration of an increasingly wide array of post-translational modifications (PTMs), well-
represented databases which encompass every potential constituent of samples, robust rules on
the identification of peptides and proteins and statistically significant false discovery rates (FDRs)
(Benjamini & Hochberg, 1995; Choi & Nesvizhskii, 2008; Käll et al., 2008). PSMs leading to
extraordinary claims or novel peptides are manually checked, and at least 2 uniquely identified
peptides are required to claim the presence of a specific protein. However, there is a lack of a
systematic assessment of the effectiveness of these tools, approaches and standards in identifying
ancient degraded proteins. The number of new strategies, software and packages being
continuously developed to address problems with *dnS* and *DBs* already highlights issues with the
different strategies. Because of all this, there is an increasing demand for all raw data to be made
public in proteomics repositories for reanalysis. Along with it, the use of free and open-source
software, standards and formats facilitates reproducibility and the adoption of common practices.

When using *DBs* software to analyse mass spectrometry data obtained from ancient protein
samples, researchers often face decisions concerning parameter selection tailored to the specific
sample types. These choices require balancing compromises and relying on a clear research
question and hypothesis, and expert, multidisciplinary knowledge about the context of the samples.
Broadly, one needs to consider the size of the search space, significance of results, computational
resources and time. If the search space is too large, the memory usage and computation time
increase and the significance of the identifications is compromised (Jeong et al., 2012; Noble,
2015). On the other hand, if the search space is too small, there is the risk of missing proteins
present in the samples. *De novo* software does not require an external database, and therefore, it
frees researchers from these decisions and compromises. However, care must be taken with the
accuracy of the sequences, especially in phylogenetic and evolutionary studies dealing with novel
peptides of extinct, unsequenced species. In both *DBs* and *dnS*, peptides of interest are usually
validated using BLASTp or tBLASTn.

The search parameters that most impact the search space size and need more tuning are the type
of enzymatic cleavage, the protein database, and the PTMs targeted. Evaluating the degree of
sample degradation prompts the researcher to determine the suitable enzymatic cleavage method
(specific, semi-specific or non-specific) and the post-translational modifications (PTMs) to be
targeted during the search. The specific archaeological and palaeontological questions that the
researcher is trying to answer, along with the type of sample, determine the scope of the database.
The size of the search space in turn affects the significance of the results. To control for the
significance of multiple PSMs, the false discovery proportion (FDP) of a search is estimated using
a Target-Decoy Competition (TDC) (Moore et al., 2002; Elias & Gygi, 2007), from which a False
Discovery Rate (FDR) is obtained. A decoy database is built by reversing the sequences in the
target database and competes for PSMs. It therefore contains known incorrect sequences that
share statistical properties with the target database like amino acid distribution or peptide length. In
the end, it will result in incorrect PSMs that would have otherwise been considered positive. This
allows sorting PSMs by a matching score and setting filters so that an expected given fraction (the
FDR) of PSMs is false. Thus the FDR is just an expectation of the actual proportion of false
matches, the FDP. In fact, several studies have pointed out the divergence between the FDP and
FDR (He et al., 2015; Madej & Lam, 2023; Ebadi et al., 2023), and the "instability" of the TDC
approach that can lead to an underestimation of the FDP in high-resolution mass spectrometry
(Couté et al., 2020). Moreover, FDRs are challenging in the study of complex or uncharacterised
proteomes, as "treating each search result equally is methodically incorrect when peptides and
proteins are not equally likely to be measured by LC-MS/MS and identified by search engines"
(Wang et al., 2022).

In this study, we wish to explore which solution is optimal for degraded proteins given these
constraints. For this, we create a deliberately simple experimental dataset which focuses not on
the diversity of a complex mixture, but on the changes caused by mild and extreme degradation.
Our model is a suspension of a small and well-characterised protein, two isoforms of a 156 long
lectin, bovine β-Lactoglobulin (BLG), heated at neutral pH conditions for 0, 4 and 128 days,
respectively. The three time points are designed to test the ability of these datasets to identify a
mild (trypsin cleaved) and extreme example of protein degradation in which most surviving
peptides are amenable to mass spectrometry and enzymatic digestion is not necessary. We
explore a range of different software solutions and strategies to identify MS2 queries generated by
this experiment and discuss the results in connection with the common practices and challenges in
palaeoproteomics.

We chose BLG, as it is one of the most commonly preserved and identified proteins in dental
calculus and ceramics and thus has become the main protein used in archaeology to explore the
spread of dairying in the past (Bleasdale et al., 2021; Charlton et al., 2019; Gismondi et al., 2018/8;

Hendy, Colonese, et al., 2018; Hendy, Warinner, et al., 2018; Jeong et al., 2018; Scott et al., 2022;
Soncin et al., 2017; Tanasi et al., 2021; Warinner, Rodrigues, et al., 2014; Wilkin et al., 2021;
Wilkin, Ventresca Miller, et al., 2020). It is suggested that mineral surfaces play an important role in
the survival this protein (Fonseca et al., 2022), as it has been also found for other eggshell proteins
(Demarchi et al., 2016).

Materials and Methods

The target protein

144 BLG was purchased from Sigma Sigma Aldrich (CAS No.: 9045-23-2). It is a single purified protein
145 with purity greater than 90% and traces of other bovine milk proteins. No further purification was
146 undertaken.

Experimental setup

1.75 mg of BLG was dissolved in 7 mL of aqueous solution at pH ~7 (to a final concentration of
250 µg/mL) in borosilicate glass vials closed with screw caps with polytetrafluoroethylene (PTFE)
lining on the inside.

Samples and blanks were placed on a VWR® dry block heater with a heated lid maintained at a
constant temperature of 95 °C for 128 days. 200 µL was sampled from each glass vial at
designated time lengths (0, 4 d, and 128 days) to 1 mL Eppendorf Safe-Lock® tubes. A USB data
logger (ebro EBI 310-T1) connected to an external sensor was used for monitoring temperature
throughout the experiment. A schematic representation of the experimental setup is shown in
Figure 1 a).

Figure 1. Schematic representation of the experimental setup (a) and the peptide identification strategies tested, including the different software, databases, and digestion (b).

LC-MS/MS

The peptides from the 0 and 4-day experiments were extracted following a previously published protocol (Cappellini et al., 2019) for degraded samples that consist of denaturation, reduction, alkylation, enzyme digestion, and desalting. The peptides at 128 days were alkylated but not digested by trypsin.

20 to 25 µL of eluted samples were transferred to the MS analysis facility at the Novo Nordisk Foundation Center for Protein Research (CPR), University of Copenhagen. Samples were subjected to nanoflow liquid chromatography-tandem mass spectrometry (nano-LC MS/MS) using an in-house packed column on an EASY-nLC ™ 1200 system connected to an Orbitrap Exploris 480 (Thermo Scientific, Germany) mass spectrometer. A column temperature of 40 $^{\circ}$C was maintained with an integrated column oven. For each run, 3 uL of sample was separated using a linear gradient from 5% to 30% buffer B in 25 minutes followed by a 2-minute step to 45% buffer B. Following the linear gradient, the column was washed by increasing the concentration of buffer B to 80% in 2 minutes, and remaining there for 2 minutes. Finally, it was re-equilibrated back to 5% in 2 minutes and held for 2 minutes, resulting in a final acquisition time of 35 minutes.

The Orbitrap Exploris 480 was operated in data-dependent acquisition mode using a Top 10 method. The spray voltage was at 2 kV, the S-lens RF level was at 40%, and the ion transfer tube was kept at 275 °C. Full scan MS were acquired at a resolution of 120,000 in a mass range of 350-

177 1400 with an Automatic Gain Control (AGC) target of 300 and a maximum ion injection time of 25
178 ms. Fragment MS/MS spectra were recorded using Higher-energy Collisional Dissociation (HCD)
179 with a maximum ion injection time set to 118 ms with an AGC target value of 200 at a resolution of
180 60,000 with a fixed first mass of 100 *m/z*. Normalised collision energy (NCE) was 30 %. The
181 isolation window was set to 1.2 *m/z*, and the dynamic exclusion was 20 seconds.

Search strategies

Open and narrow database search

184 We chose various software based on different principles and algorithms (Table 1 and Figure 1b).
185 We chose a range of free, open-source and closed-source software. We decided to include
186 Mascot, which is licensed, since it is frequently used in palaeoproteomics.

Table 1. Software used for benchmarking			
Software	Type of search	Platform	Citation
Fragpipe v19.1 with MSFragger v3.7	*DBs* open	University of Cambridge HPC[1]. 56 CPUs in Intel Cascade Lake node and 3.5GB per CPU	Kong et al., 2017; Chang et al., 2020; da Veiga Leprevost et al., 2020; Geiszler et al., 2021
pFind 3	*DBs* open	MiniMax[2]. 24 AMD Ryzen Threadripper 3960X CPUs and 64 GB RAM	Chi et al., 2018
Metamorpheus	*DBs* Multi-notch	Mjolnir[3]. 20 CPUs in AMD EPYC 4773 node and 20GB CPU	Solntsev et al., 2018
MaxQuant v2.1.0.0	*DBs* narrow	MiniMax[2]. 24 AMD Ryzen Threadripper 3960X CPUs and 64GB RAM.	Tyanova et al., 2016
		University of Cambridge HPC[1]. 56 CPUs in Intel Cascade Lake node and 3.5GB per CPU[+]	
Mascot	*DBs* narrow	Mascot Server[4]	Perkins et al., 1999
Novor	*dnS*	MiniMax[2] with DeNovoGUI (Muth et al., 2014). 24 AMD Ryzen Threadripper 3960X CPUs and 64 GB RAM	Ma, 2015
DirecTag	*dnS* hybrid		Tabb et al., 2008
PepNovo+	*dnS*		Frank & Pevzner, 2005

Table 1. Software used for benchmarking, the type of search and the computing platform or system in which
they were run. [1]University of Cambridge High Performance Computing, Cambridge Service for Data-Driven
Discovery (CSD3) https://www.hpc.cam.ac.uk/high-performance-computing. [2]MiniMax Computer Asus
TRX40 Stone Magma High Performance Workstation, [3]Computing cluster at Globe Institute, University of
Copenhagen https://mjolnir-ucph.readthedocs.io, [4]Mascot Server https://www.matrixscience.com/server.html.

†Only tryptic and semi-tryptic runs were run on the University of Cambridge HPC, for time comparison with
Fragpipe on the same system.

The LC-MS/MS files were run in Thermo RAW file format on pFind3, Metamorpheus and
MaxQuant. ProteoWizard msconvert (Chambers et al., 2012) was used to convert them to
centroided mzML (using the "vendor" peak picking method) to run on Fragpipe. For Mascot and
DeNovoGUI the files were transformed to MGF (Mascot Generic Format).

DBs software can be categorised based on the approach for the identification of PTMs and the
precursor mass tolerance. In narrow-search, the targeted PTMs are defined *a priori,* and predicted
peptide mass including PTMs must match the measured precursor mass with a narrow error. In
contrast, open search allows wide precursor mass tolerances in order to identify peptides with
unaccounted PTMs "*on-the-fly*". Multi-notch allows for a specific set of precursor mass tolerances
instead of a range. We note that most narrow-search software (e.g. Mascot, MaxQuant) can in
theory also perform open search, by just establishing a large precursor mass tolerance. Unlike
specifically authored tools (e.g. pFind, Fragpipe or Metamorpheus), such software lacks other key
components for open search. In Fragpipe, MSFragger implements a localization-aware *open*
search and the fragment index allows a fast search (Kong et al., 2017; Yu et al., 2020), while
Crystal-C (Chang et al., 2020) discards artefacts, and PTMshepherd (Geiszler et al., 2021) helps
summarising and analysing open search results. pFind is also optimised for fast searches and is
also able to localise PTM mass shifts (Chi et al., 2018). Metamorpheus uses the G-PTM-D
workflow, which runs a multi-notch search and an augmented narrow database search to speed up
the process (Solntsev et al., 2018).

Table 2. Database Search Parameters			
Run #	Database	Enzymatic cleavage	# peptides
1	DB1: dairy database 227 proteins and 62,185 residues	Tryptic	9,302
2		Semi-tryptic	102,127
3		Non-specific	1,092,998
4	DB2: bovine proteome 37,606 proteins and 22,906,446 residues	Tryptic	3,640,393
5		Semi-tryptic	38,385,707
6		Non-specific	415,906,748

213 Table 2. The combination of search parameters used in each of the database search software. The number
214 of proteins, residues and peptides from each database and enzymatic cleavage combination is shown. The
215 number of peptides is calculated allowing up to 2 missed cleavages and peptide length range of 7 to and 25.

216 Table 2 shows the 6 combinations of parameters that will be run for each of the *DBs* software and
217 samples. This selection of parameters is explained in the sections below.

Dairy database and bovine proteome

Despite the fact that we know that the sample was purely composed of BLG and perhaps contaminants, in order to provide robust and comparable statistics with other studies we used two of the widely used database strategies. Broadly, we define a wide database as one that covers a limited set of proteins from a wide range of species. Many studies use a wide, targeted database, like in Bleasdale et al. (2021) or Wilkin et al. (2021), as they look for just dairy-specific proteins from different species. On the opposite side, a deep database is one that represents the whole known proteome or proteomes from a specific species or taxa. These are used, for example, in medical studies that focus on a specific organism, like a human, mouse or zebrafish. But in the study of ancient proteins usually a wide and deep strategy is adopted. A taxonomically broader database is used to explore the wider metaproteome, with the entire SwissProt and TrEMBL (c. 251 million protein entries) (Bairoch & Apweiler, 2000) being the most typical target (Warinner et al., 2014) although even larger ones are used (Jersie-Christensen et al., 2018).

Here we tested the two opposite types of databases: a wide one from (Evans et al., 2023) that includes common and reviewed dairy proteins (DB1) and as a deep one, the Bovine proteome (DB2) (Table 2 and Figure 1b). Both include common contaminants usually reported in palaeoproteomics (Evans et al., 2023) and 4 different bovine BLG variants. DB1 comprises 227 protein entries, while DB2 contains 37,606 proteins.

Digestion: tryptic, semi-tryptic and non-specific

Most proteomics protocols include a digestion step, usually with trypsin. However, in palaeoproteomics the most degraded samples require no digestion step, removing the challenge of untangling diagenesis from the proteolytic background (Demarchi et al., 2016). This is the case with the 128-days sample. To test the differences in performance between using a tryptic, semi-tryptic and non-specific search we applied all three approaches on our three samples, each with an increasing degree of degradation (Table 2 and Figure 1b). This is then reflected in the database search, which generates tryptic peptides (the two ends are tryptic, ie. result from a tryptic cleavage) out of the selected database to match the sample. However, in palaeoproteomics, samples are usually degraded, and hydrolysis generates a non-trivial amount of non-tryptic peptides. This means that the database search will also need to run on semi-tryptic mode, which generates peptides with just one tryptic end. The non-specific search produces all possible peptides within a certain length range. Semi-specific and especially non-specific searches, increase the search space dramatically and therefore the running time and memory requirements. If combined with a large database, it might not be feasible to run for some software and systems.

251 *De novo* sequencing

De novo sequencing generally does not require choosing and setting these parameters. The
peptide sequence is derived directly from the spectra. This means that it does not require that the
species and proteins are previously sequenced, and it can be used on extinct animals. This makes
it a valuable method in palaeoproteomics. These methods use machine learning techniques and
employ graphs as data structures and algorithms applied to them. We run Novor, pNovo+,
DirecTag and PepNovo+ using DeNovoGui (Muth et al., 2014) interface (Table 1 and Figure 1b).
Nevertheless, some software, such as DirecTag, follows a hybrid approach and uses a database to
extend sequence tags derived from the spectra (Tabb et al., 2008; Zhang et al., 2012). PepNovo+
is followed by a BLAST search of the peptides against a database. We ran DeNovoGui with both
sequence databases, DB1 and DB2 in order to understand how they can also affect these hybrid
methods. pNovo+ did not produce enough meaningful results and was discarded from further
analysis.

264 Other parameters

We set the rest of the parameters as default or to values commonly used in Palaeoproteomics, in
order to emulate what a standard run would be in a real scenario. We include glutamine and
asparagine deamidation, oxidation of methionine, and N-terminal acetylation as variable PTMs,
and cysteine carbamidomethylation as fixed. Peptide length range is 7 to 25 amino acids and the
peptide mass range is 500 to 5000 Da. We allow up to 2 missed cleavages and turn off the match
between runs feature in the software that implements it, so they can be compared and to keep
identifications independent between the 3 samples.

272 Collation of DBs results

The different software reports results using different formats. These include pepXML, mzIdentML
or a tab or comma-delimited table. We used Python 3.9 with lxml, pyteomics (Levitsky et al., 2019)
and pandas (Creators The pandas development team) packages to collate the results into a single
PSM data frame. Each row is a single PSM from each sample and run. We processed all the
results and extracted the following information from each PSM: Scan #, retention time, peptide
sequence, protein accession, start and end position, whether it is a decoy match, calculated mass,
delta mass, and q-value. We calculated PSM-level q-values using pyteomics *q_value* function. We
only include the best PSM per scan. When a peptide is matched against BLG from different
species, if the bovine BLG is one of them, the start and end positions of the peptide are reported
with respect to that one.

After removing decoy matches and non BLG proteins from the PSM data frame, we pivoted it into a
long format, taking each peptide's amino acid position into a single row. For example, a PSM row
with peptide sequence TPEVDDEALEK, which starts at position 141 in the protein, is turned into
11 rows, one per amino acid, and with positions 141, 142, 143, … and 152. When all PSMs are
considered, this allows for calculating each position's coverage along the protein sequence.

Mapping of *de novo* peptides

We mapped the *de novo* peptides back to the bovine BLG protein sequence allowing mismatches,
that in this case account for sequencing errors. Since leucine (L) and isoleucine (I), and aspartic
(D) and glutamic acid (E) and deamidated asparagine (N) and glutamine (Q) have the same mass
respectively, we 'blind' all the sequences, so that mismatches between these pairs are not counted
as errors. I and L are encoded as a B, D and N as a X and E and Q as Z. Having all sequences
blinded, we first create a 3, 4 and 5-mer index from the bovine BLG variants (BLG k-mer index).
Then for each peptide, we generate a list of C and N-terminal 3, 4 and 5-mers and matched
against the BLG k-mer index. These were used as seed matches that we extended by running a
pairwise alignment using the Needleman-Wunsch (Needleman & Wunsch, 1970) algorithm. When
a peptide matches to k-mers from different positions, the alignment with the highest identity is kept.
In case of a tie, we keep the one originating from a longer k-mer, giving preference to C-terminal
k-mers. We allow gaps in the alignment, accounting for errors in the *de novo* sequencing in which
an amino acid is skipped or extra ones are added, due to noise in the spectra or low fragmentation
coverage. Finally, alignments with overall identity below 70% are discarded. Figure 2 shows a
diagram of the procedure. Once the peptides are mapped we pivot the data into long format as
before, so we can calculate the coverage and accuracy of each position along the BLG sequence.

Figure 2. Schematic of the procedure to map the *de novo* peptides to the bovine β-lactoglobulin sequence, while allowing sequencing errors. 1) *de novo* peptides and BLG are 'blinded'. 2.1) C and N-terminal k-mers are extracted from the peptides. 2.2) BLG index is generated, with k-mers as keys pointing at the positions in the protein. 3) In this example, the peptide TPZVAZABZK matches 2 different k-mers from the BLG k-mer index, which come from the positions 65 and 147 in BLG respectively. 4), 5) This results in two possible alignments of the query peptide against BLG. 6) The alignment with the highest accuracy is kept and overall, only alignments with identity above 70% are considered. In case of ties, the alignment with the longest seed match and coming from a C-terminal k-mer would be kept.

Results and discussion

The LC-MSMS produced a total of 8,731 MS2 spectra for the 0 days sample and 9,108 and 10,141 for the 4 and 128 days respectively. The increase in the total number of spectra is consistent with the higher non-enzymatic hydrolysis expected in the more degraded samples, which would yield a wider variety of peptides.

Is FDR enough?

We calculated q-values for each PSMs in each database search software run and sample using pyteomics *q_value* function. Then we calculated the fraction of PSMs above a range of q-values from $1 \cdot 10^{-5}$ to $5 \cdot 10^{-2}$ and plotted the combined results in Figure 2. We observe several trends:

1) Columnwise, looking at each software separately, the fraction of identifications above the same FDR threshold, first slightly increases in the 4-days sample but then decreases in the 128-days.

2) At 0 days, within the same software, tryptic or semi-tryptic searches give the highest number of identifications, but as degradation increases, in the 4 and 128 days, non-specific searches identify more spectra.

3) In each software and sample, the sets of parameters producing more identifications are always the ones using the smaller, dairy-specific DB1.

Figure 3. Fraction of identified spectra for FDR thresholds from 0 to 0.05 (at 10^{-5} step) for *DBs* software. The rows represent the increasing heating time (0, 4, 128 days), with each software represented in a column, and the different runs represented with different colours.

We do not intend to examine here the quality of the identifications, or directly compare software performance solely based on FDR. We rather focus on how FDRs are widely affected by the interaction between the degradation state of the sample and the search space. The reasons behind the change in the FDR observed here are already known in proteomics and in statistics general: if by Increasing the search space, the proportion of peptides in the database that are not present in the samples also increases, there will be more chances of random and decoy matches with high scores (Jeong et al., 2012; Noble, 2015). Therefore, to achieve the same desired FDR, the score threshold to accept positive matches becomes more stringent, rendering less accepted PSMs (Jeong et al., 2012; Noble, 2015). This means that large databases containing a large

number of proteins that are present in the samples, like DB2, inadvertently boost the FDR and
apparently reduce the number of identifications. Something similar applies to the use of non-
specific searches for samples that are well-preserved and less degraded. This adds to the inherent
divergence between FDR and FDP of the TDC (He et al., 2015; Couté et al., 2020; Madej & Lam,
2023; Ebadi et al., 2023).

But the answer to this problem cannot just be to use small, targeted databases, even though it
would reduce the running time and the required computational resources. We can speculate what
would happen in the opposite scenario, using a very small database against a complex sample,
like that coming from dental calculus. To start, we might miss some of the contents of the sample.
Another more inadvertent effect is that wrong, low-quality matches between a spectrum and a
peptide might surface with a low enough FDR (since the search space is small). This is further
pronounced if the correct peptide, which could have competed and achieved a better PSM, is
absent in the database. This is why common contaminants are included in the searches, even
though we are not interested in them.

In general, we want the set of proteins and peptides that are in a sample and the set of proteins we
are looking for to match as closely as possible (Jeong et al., 2012; Noble, 2015). While the content
of a sample is not known *a priori*, it is clear in our simple system that using the whole bovine
proteome to interrogate our data is utterly unnecessary. Going into a more realistic scenario, with
real archaeological samples, having a clear research question and hypotheses and a good
understanding of the historical, archaeological, diagenetic and taphonomic context will always help
to delineate the optimal database and parameters given the compromises exposed. Studies like
those of Wilkin et al. (2020, 2021), Bleasdale et al. (2021) and Hendy et al. (2018; 2018) are
examples of different strategies and challenges regarding the complexity of samples and scope of
the databases. They highlight the difficulty of building an unbiased and targeted database that
encompasses all the contents of a sample. Targeted databases for different types of tissues like
bone or enamel, microbiomes or other mixtures like foodcrusts need to be further developed.

On Open search

In the previous section, we commented on the implications of the database and enzyme digestion
choices in the general TDC approach and FDR. However, the presence of a wide variety of PTMs
in ancient, degraded proteins, or even in a simple system like the target of this study, is another
parameter to consider. Usually in palaeoproteomics, researchers select *a priori* a list of expected
PTMs to look for, which are included in the theoretical spectra derived from the sequence
database. The PTMs can be fixed or variable and are added only to the specific amino acids. Then
a narrow precursor tolerance is used to match to the data (*Narrow search*). Increasingly, wide

precursor tolerances are being used in proteomics in general, in an attempt to consider and
discover novel PTMs. This has led to the development of specialised Open search software that
incorporates this feature in its workflow.

In Figure 2 we see the major differences between software when we look at *Narrow* versus Open
search. Open search furnishes more identifications in all 3 samples, provided that DB1 is used with
the appropriate enzymatic digestion (or lack thereof). *Open search* is capable of identifying spectra
from peptides bearing PTMs that are not accounted for and therefore remain unidentified (Chick et
al., 2015). This is so because, in practice, the search space in this software is much greater, while
at the same time implementing algorithms that allow a fast search. FragPipe finds mass shifts
other than the PTMs set in all other software, in 46.6%, 31.8% and 17% of the PSMs for the 0, 4
and 128 days, respectively. We counted PSMs above 0.05 FDR on the tryptic, semi-tryptic and
non-specific runs with the dairy database, respectively for the 0, 4 and 128 days. The decrease in
the identification of PTMs with the more degraded samples might seem counterintuitive.
Nonetheless, the backbone cleavage and accumulation of PTMs in the 128 days samples might be
so extensive that the Open search cannot even identify those spectra, and only a smaller fraction
of the modified peptides is identified. In addition to the problems with FDR already commented,
Kong et al. (2017) reported that 68% of spectra reassigned by open search MSFragger to a
different peptide than a narrow search, had greater support in the former. There are potential false
positives in spectra matched to unmodified peptides.

In order to highlight the differences between these approaches within Open search, we created a
Venn diagram in Figure 3 with the unique peptides identified in the different runs and for each of
the samples. Figure 3 shows that in FragPipe and Metamorpheus, on the 128 days sample, most
peptides are found only on the non-specific search, and the difference between the 3 types of
digestion grows with sample degradation. In contrast, in pFind most peptides are commonly found
in the 3 searches throughout the 3 samples, although the total decreases. pFind takes a different
approach than MSFragger or Metamorpheus; it finds k-mer tags in the spectra that then are
extended until there is a match to the peptide database, and given a mass shift (Chi et al., 2018).
This feature coupled with an open search makes pFind capable of finding non-tryptic peptides
even in tryptic search in the 128 days sample (Figure 2).

Figure 4. Venn diagrams for FragPipe (left), Metamorpheus (middle) and pFind (right) showing unique peptides identified by each digestion type run using the dairy database DB1.

pFind and FragPipe run much faster than other narrow search software (Kong et al., 2017; Chi et al., 2018). We also run a subset of the MaxQuant runs on the Cambridge HPC (Table 1) in order to be able to compare with Fragpipe in the same system. In this study, pFind runs about 30 times faster than MaxQuant on MiniMax and FragPipe about 40 times on Cambridge HPC. To achieve efficient search speed, MSFragger (within Fragpipe) generates a theoretical fragment index that is matched against the spectra (Kong et al., 2017). pFind in turn uses its tag extension strategy (Chi et al., 2018). Metamorpheus, which uses the enhanced G-PTM-D workflow, runs a multi-notch search, in which instead of setting a tolerance range of precursor mass shifts, it allows specific shifts corresponding to a wide selection of PTMs (Solntsev et al., 2018). This procedure still explores an expanded search space and allows discovery of PTMs.

De novo sequencing coverage and accuracy

We have seen that when we use external knowledge and data to search the spectra, we are always required to make choices that will affect the number, quality and significance of the identifications. Open search software can already search for unspecified PTMs. But *de novo* sequencing (*dnS*) software can in theory reconstruct the peptide sequence just from the spectra without the use of external data. However, sequencing errors might arise (Muth & Renard, 2018), which can have a high impact in the discovery of potential novel peptides from extinct or unsequenced organisms and phylogenetic studies. Therefore in practice, *de novo* is hardly applied alone and some software integrate a hybrid approach (Tabb et al., 2008; Zhang et al., 2012) or workflows use a complementary *DBs* step or a *blastp* for validation (Welker et al., 2015, 2019; Chen et al., 2019; Presslee et al., 2019; Cappellini et al., 2019).

In this section we look at the interplay between degradation and sequence coverage and accuracy of *dnS*. We also discuss how the choice of the database affects the accuracy of the results in this case. Since we have a very simple system, with a single and known protein, it is easy to map the *de novo* sequenced peptides to the protein to obtain sequence coverage and also identify sequence errors. We follow the procedure explained in Mapping of de novo peptides and Figure 2. We set a threshold of 70% overall identity between the peptides and the protein sequence, below which peptides are discarded.

We found that overall, alignments coming from C-terminal seed matches have a greater identity than those from N-terminal k-mers, when none of them are given priority (Figure S1). This is in line with previous studies reporting that long b-ions are unstable and therefore y-ions are preferentially generated in HCD (Shao et al., 2014; Medzihradszky & Chalkley, 2015) Therefore, HCD produces better ion coverage on the C-terminal and less sequencing errors. Following this, we subsequently gave priority to C-terminal alignments to break ties (Figure 2).

As with *DBs*, we studied the effect of the size of the sequence database for hybrid *de novo* methods. In particular, when the database contains a great number of sequences that are not in the sample. When the larger DB2 is used, the accuracy of the peptides decreases in DirecTag and PepNovo+. In contrast, Novor achieves almost identical results (Figure S2). Within DeNovoGUI, DirecTag and PepNovo+ rely on an external database, either for a tagging hybrid method or for a subsequent *blastp*, respectively. Novor does not use a database at any point. We can draw a parallel observation as when the FDR is inadvertently boosted in *DBs* if the database contains many irrelevant sequences. In this case, incorrectly *de novo* sequenced peptides or tags are queried against a plethora of sequences from DB2, resulting in spurious matches that end up validating or wrongly extending them.

To study sequence accuracy along the BLG we take every BLG sequenced peptide position and 1)
count how many times it appears and 2) identify if it is correct or not in order to calculate the
accuracy at each position. Incorrect amino acids produce a negative count. We did this for every
DBs and *dnS* run. In Figure 4, we show A) DirecTag with DB2, B) Novor, C) sequence accuracy for
DirecTag, Novor and PepNovo+ and D) pFind coverage with semi-tryptic search and DB1 for
comparison. This way, we look at how the coverage changes and accuracy decreases along the
BLG sequence as degradation progresses. We identify areas with no or nearly no coverage in the
128 days sample (highlighted in red in the x-axis position scale in Figure 4). These overall present
the most significant changes and most acute decrease in accuracy. DirecTag (Figure 4 A and C)
and PepNovo (Figure 4 C) have both accuracies close to 1 for all areas that have coverage, while
Novor presents more mistakes, and even shows positions that are attributed to areas without
coverage in any other run. The blue highlight in figure 4 is an example of a well covered section by
other software, for which Novor presents errors. In line with the database effect, DirecTag and
PepNovo+ are more conservative and overall present less hits (150 for the best position), because
sequencing errors are prevented and wrong peptides discarded upon matching against a
database. Novor, in contrast, attempts at sequencing everything and returns many peptides that
contain errors. However, as seen before, the database dependence of DirecTag and PepNovo+
makes them prone to making mistakes when using too large a database with irrelevant
sequences.

De novo sequencing is a critical tool in palaeoproteomic studies looking at the phylogenetic
relations of extinct animals (Welker et al., 2015, 2019; Chen et al., 2019; Presslee et al., 2019;
Cappellini et al., 2019). Crucially, these studies use PEAKS, MaxQuant and BLAST, in sequential
workflows tailored to the identification and validation of single amino acid polymorphisms and novel
peptides. The combination of hybrid methods and *dnS* and *DBs* reflects the compromise between
the discovery of novel sequences and the minimization of sequencing errors. As seen in figures 3
and 4, sequencing errors can accumulate in highly degraded proteins and regions. Software that
does not rely on any external database is more affected by this. At the same time, a database can
be a curse, rather than a blessing, if it contains too many irrelevant sequences, like DB2.
Therefore, these studies use databases restricted to a specific species, or type of protein like
collagen or tissue, like bone or enamel proteomes.

Figure 5. Sequence coverage and accuracy. Coverage is measured in the y-axes as the number of times an amino acid position is covered by an identified peptide, while accuracy is the proportion of those that are correctly identified. The x-axis shows the BLG protein sequence and position, which includes the signal peptide. Panel A) shows sequence coverage from DirecTag with DB1 and B) from Novor. Panel C) shows the overall accuracy for the 3 *de novo* tools (each of them being from 0 to 1, adding up to 3) using DB1. Panel D) sequence coverage using pFind *DBs* with semi-tryptic and DB1. Values below 0 correspond to mismatches between the peptide sequence and the actual BLG sequence.

By looking at the positional coverage, we can also infer physico-chemical properties of the BLG
that are relevant in palaeoproteomics. The grey highlighted region (position 55-69) is a section that
presents better coverage at 128 days, which might suggest that it is accessible by proteomics
protocols more easily after extensive degradation and denaturation has occurred. The opposite
happens to the area marked green (141-151), one of the most encountered BLG peptides in the
literature (Wilkin et al., 2020, 2021). Here, in contrast, it is hardly identified after extensive
degradation. This suggests that the real conditions in which the peptide is found, mainly the
presence of a mineral surface, contributes to its preservation, as it has been suggested using
molecular simulations (Fonseca et al., 2022).

Conclusion

Palaeoproteomics is a maturing discipline that is developing new strategies to overcome its own
challenges. Teams working on computational proteomics are constantly releasing new software
and updates with new features. These implement a wide variety of underlying methods and
algorithms that we broadly group in *de novo* sequencing or database search. Palaeoproteomics
frequently borrows methodology and software from the broader field of proteomics. Yet there are
unique challenges to applying these tools to palaeoproteomics, such as the difficulties associated
with selecting a properly constrained database or accounting and identifying PTMs. It is therefore
important to assess the pertinence and validity of the different strategies and parameters in the
study of ancient proteins. Here we have done so by using a simple and progressively degraded
protein model, β-lactoglobulin, heated at pH 7 for 0, 4 and 128 days.

We highlight the importance of constraining the search space in *DBs* to improve the significance
and reduce computing times. Setting the enzymatic digestion according to the level of degradation
and using targeted databases are the most important factors. At the same time, wide precursor
mass tolerances in Open search software can identify peptides with PTMs that would have been
otherwise unidentified, as they would not match any theoretical database-derived spectra. Or even
be misidentified as an unmodified spectra. *De novo* sequencing goes one step further in freeing
researchers from database selection, which we have shown to hugely impact the results..
However, the possibility of sequencing mistakes cannot be disregarded and in practice, external
databases and complementary *DBS* are commonly used. Recently, new *dnS* programs like
Casanovo (Yilmaz et al., 2022), InstaNovo (Eloff et al., 2023), or π-HelixNovo (Yang et al., 2023)
are reporting promising performance. They use transformer neural network architecture, (as used
in Large Language Models), which seem suited to protein sequences as they can be seen as
another language. A language that is revealed in spectral data, in which the presence or absence
of peaks and their intensities are intercorrelated.

As it has already been done in more informal and *ad-hoc* approaches, we devise a standardised
approach that combines the powers of the different approaches discussed here. *De novo*
sequencing software, especially those using transformers, and Open search can be used to
discover novel sequences and PTMs and initially constrain the search space of possible protein
contents and modifications in a complex sample. Using this information, a final, constrained *narrow*
database search with targeted database and PTMs would boost identifications confidently.

Data and code availability

530 Python and R notebooks used to process the *DBs* and *dn*S data can be found in
531 https://github.com/ismaRP/PPbenchmark.git and 10.5281/zenodo.10358625. RAW LC-MSMS and
532 PSM data resulting from the analysis with Fragpipe, pFind, Metamorpheus, MaxQuant, Mascot and
533 DeNovoGUI can be accessed in Zenodo 10.5281/zenodo.10362061. MaxQuant and Fragpipe
534 parameters and workflow files are also included.

Acknowledgements

IRP is currently funded by the European Union's Horizon 2020 Research and Innovation
Programme under the Marie Skłodowska-Curie grant agreement No 956410. At the time of
producing and writing this work BN was funded by European Union's Horizon 2020 Research and
Innovation Programme under the Marie Skłodowska-Curie grant agreement No. 801199 and with
MC by the European Union's EU Framework Programme for Research and Innovation Horizon
2020 under Grant Agreement No. 787282 (B2C). MC and MM were also supported by the Danish
National Research Foundation (DNRF128). YC and JD are funded by the European Union's
Horizon 2020 Research and Innovation Programme under the Marie Skłodowska-Curie grant
agreement No. 956351.

Conflict of interest disclosure

546 The authors declare that they comply with the PCI rule of having no financial conflicts of interest in
547 relation to the content of the article.

References

Aebersold R, Mann M (2003) Mass spectrometry-based proteomics. *Nature*, **422**, 198–207.

https://doi.org/10.1038/nature01511

Alfaro JA, Ignatchenko A, Ignatchenko V, Sinha A, Boutros PC, Kislinger T (2017) Detecting protein variants

by mass spectrometry: a comprehensive study in cancer cell-lines. *Genome medicine*, **9**, 62.

https://doi.org/10.1186/s13073-017-0454-9

Bairoch A, Apweiler R (2000) The SWISS-PROT protein sequence database and its supplement TrEMBL in

2000. *Nucleic acids research*, **28**, 45–48. https://doi.org/10.1093/nar/28.1.45

Benjamini Y, Hochberg Y (1995) Controlling the false discovery rate: A practical and powerful approach to

multiple testing. *Journal of the Royal Statistical Society*, **57**, 289–300.

https://doi.org/10.1111/j.2517-6161.1995.tb02031.x

Bittremieux W, May DH, Bilmes J, Noble WS (2022) A learned embedding for efficient joint analysis of

millions of mass spectra. *Nature methods*, **19**, 675–678. https://doi.org/10.1038/s41592-022-01496-1

Bleasdale M, Richter KK, Janzen A, Brown S, Scott A, Zech J, Wilkin S, Wang K, Schiffels S, Desideri J,

Besse M, Reinold J, Saad M, Babiker H, Power RC, Ndiema E, Ogola C, Manthi FK, Zahir M, Petraglia

M, Trachsel C, Nanni P, Grossmann J, Hendy J, Crowther A, Roberts P, Goldstein ST, Boivin N (2021)

Ancient proteins provide evidence of dairy consumption in eastern Africa. *Nature communications*, **12**,

632. https://doi.org/10.1038/s41467-020-20682-3

Cappellini E, Welker F, Pandolfi L, Ramos-Madrigal J, Samodova D, Rüther PL, Fotakis AK, Lyon D,

Moreno-Mayar JV, Bukhsianidze M, Rakownikow Jersie-Christensen R, Mackie M, Ginolhac A, Ferring

R, Tappen M, Palkopoulou E, Dickinson MR, Stafford TW Jr, Chan YL, Götherström A, Nathan SKSS,

Heintzman PD, Kapp JD, Kirillova I, Moodley Y, Agusti J, Kahlke R-D, Kiladze G, Martínez-Navarro B,

Liu S, Sandoval Velasco M, Sinding M-HS, Kelstrup CD, Allentoft ME, Orlando L, Penkman K, Shapiro

B, Rook L, Dalén L, Gilbert MTP, Olsen JV, Lordkipanidze D, Willerslev E (2019) Early Pleistocene

enamel proteome from Dmanisi resolves Stephanorhinus phylogeny. *Nature*, **574**, 103–107.

https://doi.org/10.1038/s41586-019-1555-y

Chambers MC, Maclean B, Burke R, Amodei D, Ruderman DL, Neumann S, Gatto L, Fischer B, Pratt B,

Egertson J, Hoff K, Kessner D, Tasman N, Shulman N, Frewen B, Baker TA, Brusniak M-Y, Paulse C,

Creasy D, Flashner L, Kani K, Moulding C, Seymour SL, Nuwaysir LM, Lefebvre B, Kuhlmann F, Roark

J, Rainer P, Detlev S, Hemenway T, Huhmer A, Langridge J, Connolly B, Chadick T, Holly K, Eckels J,

Deutsch EW, Moritz RL, Katz JE, Agus DB, MacCoss M, Tabb DL, Mallick P (2012) A cross-platform

toolkit for mass spectrometry and proteomics. *Nature biotechnology*, **30**, 918–920.

https://doi.org/10.1038/nbt.2377

Chang H-Y, Kong AT, da Veiga Leprevost F, Avtonomov DM, Haynes SE, Nesvizhskii AI (2020) Crystal-C: A

Computational Tool for Refinement of Open Search Results. *Journal of proteome research*, **19**, 2511–

2515. https://doi.org/10.1021/acs.jproteome.0c00119

Chen F, Welker F, Shen C-C, Bailey SE, Bergmann I, Davis S, Xia H, Wang H, Fischer R, Freidline SE, Yu

T-L, Skinner MM, Stelzer S, Dong G, Fu Q, Dong G, Wang J, Zhang D, Hublin J-J (2019) A late Middle

Pleistocene Denisovan mandible from the Tibetan Plateau. *Nature*, **569**, 409–412.

https://doi.org/10.1038/s41586-019-1139-x

Chick JM, Kolippakkam D, Nusinow DP, Zhai B, Rad R, Huttlin EL, Gygi SP (2015) A mass-tolerant

database search identifies a large proportion of unassigned spectra in shotgun proteomics as modified

peptides. *Nature biotechnology*, **33**, 743–749. https://doi.org/10.1038/nbt.3267

Chi H, Liu C, Yang H, Zeng W-F, Wu L, Zhou W-J, Niu X-N, Ding Y-H, Zhang Y, Wang R-M, Wang Z-W,

Chen Z-L, Sun R-X, Liu T, Tan G-M, Dong M-Q, Xu P, Zhang P-H, He S-M (2018) Open-pFind enables

precise, comprehensive and rapid peptide identification in shotgun proteomics. *bioRxiv*, 285395.

https://doi.org/10.1101/285395

Choi H, Nesvizhskii AI (2008) False discovery rates and related statistical concepts in mass spectrometry-

based proteomics. *Journal of proteome research*, **7**, 47–50. https://doi.org/10.1021/pr700747q

Couté Y, Bruley C, Burger T (2020) Beyond Target-Decoy Competition: Stable Validation of Peptide and

Protein Identifications in Mass Spectrometry-Based Discovery Proteomics. *Analytical chemistry*, **92**,

14898–14906. https://doi.org/10.1021/acs.analchem.0c00328

Cox J, Mann M (2008) MaxQuant enables high peptide identification rates, individualized p.p.b.-range mass

accuracies and proteome-wide protein quantification. *Nature biotechnology*, **26**, 1367–1372.

https://doi.org/10.1038/nbt.1511

Creators The pandas development team *pandas-dev/pandas: Pandas*.

https://doi.org/10.5281/zenodo.10107975

Demarchi B, Hall S, Roncal-Herrero T, Freeman CL, Woolley J, Crisp MK, Wilson J, Fotakis A, Fischer R,

Kessler BM, Rakownikow Jersie-Christensen R, Olsen JV, Haile J, Thomas J, Marean CW, Parkington

J, Presslee S, Lee-Thorp J, Ditchfield P, Hamilton JF, Ward MW, Wang CM, Shaw MD, Harrison T,

Domínguez-Rodrigo M, MacPhee RDE, Kwekason A, Ecker M, Kolska Horwitz L, Chazan M, Kröger R,

Thomas-Oates J, Harding JH, Cappellini E, Penkman K, Collins MJ (2016) Protein sequences bound to

mineral surfaces persist into deep time. *eLife*, **5**. https://doi.org/10.7554/eLife.17092

Ebadi A, Freestone J, Noble WS, Keich U (2023) Bridging the False Discovery Gap. *Journal of proteome*

research, **22**, 2172–2178. https://doi.org/10.1021/acs.jproteome.3c00176

Elias JE, Gygi SP (2007) Target-decoy search strategy for increased confidence in large-scale protein

identifications by mass spectrometry. *Nature methods*, **4**, 207–214. https://doi.org/10.1038/nmeth1019

Eloff K, Kalogeropoulos K, Morell O, Mabona A, Jespersen JB, Williams W, van Beljouw SPB, Skwark M,

Laustsen AH, Brouns SJJ, Ljungars A, Schoof EM, Van Goey J, Keller U auf D, Beguir K, Carranza NL,

Jenkins TP (2023) De novo peptide sequencing with InstaNovo: Accurate, database-free peptide

identification for large scale proteomics experiments. *bioRxiv*, 2023.08.30.555055.

https://doi.org/10.1101/2023.08.30.555055

Evans M, Lundy J, Lucquin A, Hagan R, Kowalski Ł, Wilczyńki J, Bickle P, Adamczak K, Craig OE, Robson

HK, Hendy J (2023) Detection of dairy products from multiple taxa in Late Neolithic pottery from Poland:

an integrated biomolecular approach. *Royal Society open science*, **10**, 230124.

https://doi.org/10.1098/rsos.230124

Fonseca B, Freeman CL, Collins MJ (2022) Conformational analysis and water dynamics: a molecular

dynamics study on the survival of a β-lactoglobulin peptide in the archaeological record. *Chemical*

physics, **561**, 111602. https://doi.org/10.1016/j.chemphys.2022.111602

Frank A, Pevzner P (2005) PepNovo: de novo peptide sequencing via probabilistic network modeling.

Analytical chemistry, **77**, 964–973. https://doi.org/10.1021/ac048788h

Geiszler DJ, Kong AT, Avtonomov DM, Yu F, Leprevost F da V, Nesvizhskii AI (2021) PTM-Shepherd:

Analysis and Summarization of Post-Translational and Chemical Modifications From Open Search

Results. *Molecular & cellular proteomics: MCP*, **20**, 100018. https://doi.org/10.1074/mcp.TIR120.002216

Griss J, Perez-Riverol Y, Lewis S, Tabb DL, Dianes JA, Del-Toro N, Rurik M, Walzer MW, Kohlbacher O,

Hermjakob H, Wang R, Vizcaíno JA (2016) Recognizing millions of consistently unidentified spectra

across hundreds of shotgun proteomics datasets. *Nature methods*, **13**, 651–656.

https://doi.org/10.1038/nmeth.3902

He K, Fu Y, Zeng W-F, Luo L, Chi H, Liu C, Qing L-Y, Sun R-X, He S-M (2015) A theoretical foundation of

the target-decoy search strategy for false discovery rate control in proteomics. *arXiv*

https://doi.org/10.48550/arXiv.1501.00537

Hendy J, Colonese AC, Franz I, Fernandes R, Fischer R, Orton D, Lucquin A, Spindler L, Anvari J, Stroud E,

Biehl PF, Speller C, Boivin N, Mackie M, Jersie-Christensen RR, Olsen JV, Collins MJ, Craig OE,

Rosenstock E (2018) Ancient proteins from ceramic vessels at Çatalhöyük West reveal the hidden

cuisine of early farmers. *Nature communications*, **9**, 4064. https://doi.org/10.1038/s41467-018-06335-6

Hendy J, Warinner C, Bouwman A, Collins MJ, Fiddyment S, Fischer R, Hagan R, Hofman CA, Holst M,

Chaves E, Klaus L, Larson G, Mackie M, McGrath K, Mundorff AZ, Radini A, Rao H, Trachsel C, Velsko

IM, Speller CF (2018) Proteomic evidence of dietary sources in ancient dental calculus. *Proceedings.*

Biological sciences / The Royal Society, **285**. https://doi.org/10.1098/rspb.2018.0977

Hendy J, Welker F, Demarchi B, Speller C, Warinner C, Collins MJ (2018) A guide to ancient protein studies.

Nature ecology & evolution, **2**, 791–799. https://doi.org/10.1038/s41559-018-0510-x

Jeong K, Kim S, Bandeira N (2012) False discovery rates in spectral identification. *BMC bioinformatics*, **13**

Suppl 16, S2. https://doi.org/10.1186/1471-2105-13-S16-S2

Jersie-Christensen RR, Lanigan LT, Lyon D, Mackie M, Belstrøm D, Kelstrup CD, Fotakis AK, Willerslev E,

Lynnerup N, Jensen LJ, Cappellini E, Olsen JV (2018) Quantitative metaproteomics of medieval dental

calculus reveals individual oral health status. *Nature communications*, **9**, 4744.

https://doi.org/10.1038/s41467-018-07148-3

Käll L, Storey JD, MacCoss MJ, Noble WS (2008) Assigning significance to peptides identified by tandem

mass spectrometry using decoy databases. *Journal of proteome research*, **7**, 29–34.

https://doi.org/10.1021/pr700600n

Kong AT, Leprevost FV, Avtonomov DM, Mellacheruvu D, Nesvizhskii AI (2017) MSFragger: ultrafast and

comprehensive peptide identification in mass spectrometry-based proteomics. *Nature methods*, **14**,

513–520. https://doi.org/10.1038/nmeth.4256

Levitsky LI, Klein JA, Ivanov MV, Gorshkov MV (2019) Pyteomics 4.0: Five Years of Development of a

Python Proteomics Framework. *Journal of proteome research*, **18**, 709–714.

https://doi.org/10.1021/acs.jproteome.8b00717

Liu X, Jin J, Yuan Y, Xian W, Tang Z, Fu J (2023) The ever increasing necessity of mass spectrometry in

dissecting protein post-translational modifications catalyzed by bacterial effectors.

Ma B (2015) Novor: real-time peptide de novo sequencing software. *Journal of the American Society for*

Mass Spectrometry, **26**, 1885–1894. https://doi.org/10.1007/s13361-015-1204-0

Madej D, Lam H (2023) Modeling Lower-Order Statistics to Enable Decoy-Free FDR Estimation in

Proteomics. *Journal of proteome research*, **22**, 1159–1171.

https://doi.org/10.1021/acs.jproteome.2c00604

Medzihradszky KF, Chalkley RJ (2015) Lessons in de novo peptide sequencing by tandem mass

spectrometry. *Mass spectrometry reviews*, **34**, 43–63. https://doi.org/10.1002/mas.21406

Moore RE, Young MK, Lee TD (2002) Qscore: an algorithm for evaluating SEQUEST database search

results. *Journal of the American Society for Mass Spectrometry*, **13**, 378–386.

https://doi.org/10.1016/S1044-0305(02)00352-5

Muth T, Renard BY (2018) Evaluating de novo sequencing in proteomics: already an accurate alternative to

database-driven peptide identification? *Briefings in bioinformatics*, **19**, 954–970.

https://doi.org/10.1093/bib/bbx033

Muth T, Weilnböck L, Rapp E, Huber CG, Martens L, Vaudel M, Barsnes H (2014) DeNovoGUI: an open

source graphical user interface for de novo sequencing of tandem mass spectra. *Journal of proteome*

research, **13**, 1143–1146. https://doi.org/10.1021/pr4008078

Needleman SB, Wunsch CD (1970) A general method applicable to the search for similarities in the amino

acid sequence of two proteins. *Journal of molecular biology*, **48**, 443–453.

https://doi.org/10.1016/0022-2836(70)90057-4

Noble WS (2015) Mass spectrometrists should search only for peptides they care about. *Nature methods*,

12, 605–608. https://doi.org/10.1038/nmeth.3450

Perez-Riverol Y, Bai J, Bandla C, García-Seisdedos D, Hewapathirana S, Kamatchinathan S, Kundu DJ,

Prakash A, Frericks-Zipper A, Eisenacher M, Walzer M, Wang S, Brazma A, Vizcaíno JA (2021) The

PRIDE database resources in 2022: a hub for mass spectrometry-based proteomics evidences. *Nucleic*

acids research, **50**, D543–D552. https://doi.org/10.1093/nar/gkab1038

Perkins DN, Pappin DJ, Creasy DM, Cottrell JS (1999) Probability-based protein identification by searching

sequence databases using mass spectrometry data. *Electrophoresis*, **20**, 3551–3567.

https://doi.org/10.1002/(SICI)1522-2683(19991201)20:18<3551::AID-ELPS3551>3.0.CO;2-2

Presslee S, Slater GJ, Pujos F, Forasiepi AM, Fischer R, Molloy K, Mackie M, Olsen JV, Kramarz A,

Taglioretti M, Scaglia F, Lezcano M, Lanata JL, Southon J, Feranec R, Bloch J, Hajduk A, Martin FM,

Salas Gismondi R, Reguero M, de Muizon C, Greenwood A, Chait BT, Penkman K, Collins M, MacPhee

RDE (2019) Palaeoproteomics resolves sloth relationships. *Nature ecology & evolution*.

https://doi.org/10.1038/s41559-019-0909-z

Ramsøe A, Crispin M, Mackie M, McGrath K, Fischer R, Demarchi B, Collins MJ, Hendy J, Speller C (2021)

Assessing the degradation of ancient milk proteins through site-specific deamidation patterns. *Scientific*

reports, **11**, 7795. https://doi.org/10.1038/s41598-021-87125-x

Ramsøe A, van Heekeren V, Ponce P, Fischer R, Barnes I, Speller C, Collins MJ (2020) DeamiDATE 1.0:

Site-specific deamidation as a tool to assess authenticity of members of ancient proteomes. *Journal of*

archaeological science, **115**, 105080. https://doi.org/10.1016/j.jas.2020.105080

Schroeter ER, Cleland TP (2016) Glutamine deamidation: an indicator of antiquity, or preservational quality?

Rapid communications in mass spectrometry: RCM, **30**, 251–255. https://doi.org/10.1002/rcm.7445

Shao C, Zhang Y, Sun W (2014) Statistical characterization of HCD fragmentation patterns of tryptic

peptides on an LTQ Orbitrap Velos mass spectrometer. *Journal of proteomics*, **109**, 26–37.

https://doi.org/10.1016/j.jprot.2014.06.012

Solntsev SK, Shortreed MR, Frey BL, Smith LM (2018) Enhanced Global Post-translational Modification

Discovery with MetaMorpheus. *Journal of proteome research*, **17**, 1844–1851.

https://doi.org/10.1021/acs.jproteome.7b00873

Tabb DL, Ma Z-Q, Martin DB, Ham A-JL, Chambers MC (2008) DirecTag: accurate sequence tags from

peptide MS/MS through statistical scoring. *Journal of proteome research*, **7**, 3838–3846.

https://doi.org/10.1021/pr800154p

Tyanova S, Temu T, Cox J (2016) The MaxQuant computational platform for mass spectrometry-based

shotgun proteomics. *Nature protocols*, **11**, 2301–2319. https://doi.org/10.1038/nprot.2016.136

da Veiga Leprevost F, Haynes SE, Avtonomov DM, Chang H-Y, Shanmugam AK, Mellacheruvu D, Kong AT,

Nesvizhskii AI (2020) Philosopher: a versatile toolkit for shotgun proteomics data analysis. *Nature*

methods, **17**, 869–870. https://doi.org/10.1038/s41592-020-0912-y

Warinner C, Korzow Richter K, Collins MJ (2022) Paleoproteomics. *Chemical reviews*, **122**, 13401–13446.

https://doi.org/10.1021/acs.chemrev.1c00703

Warinner C, Rodrigues JFM, Vyas R, Trachsel C, Shved N, Grossmann J, Radini A, Hancock Y, Tito RY,

Fiddyment S, Speller C, Hendy J, Charlton S, Luder HU, Salazar-García DC, Eppler E, Seiler R, Hansen

LH, Castruita JAS, Barkow-Oesterreicher S, Teoh KY, Kelstrup CD, Olsen JV, Nanni P, Kawai T,

Willerslev E, von Mering C, Lewis CM Jr, Collins MJ, Gilbert MTP, Rühli F, Cappellini E (2014)

Pathogens and host immunity in the ancient human oral cavity. *Nature genetics*, **46**, 336–344.

https://doi.org/10.1038/ng.2906

Welker F, Collins MJ, Thomas JA, Wadsley M, Brace S, Cappellini E, Turvey ST, Reguero M, Gelfo JN,

Kramarz A, Burger J, Thomas-Oates J, Ashford DA, Ashton PD, Rowsell K, Porter DM, Kessler B,

Fischer R, Baessmann C, Kaspar S, Olsen JV, Kiley P, Elliott JA, Kelstrup CD, Mullin V, Hofreiter M,

Willerslev E, Hublin J-J, Orlando L, Barnes I, MacPhee RDE (2015) Ancient proteins resolve the

evolutionary history of Darwin's South American ungulates. *Nature*, **522**, 81–84.

https://doi.org/10.1038/nature14249

Welker F, Ramos-Madrigal J, Kuhlwilm M, Liao W, Gutenbrunner P, de Manuel M, Samodova D, Mackie M,

Allentoft ME, Bacon A-M, Collins MJ, Cox J, Lalueza-Fox C, Olsen JV, Demeter F, Wang W, Marques-

Bonet T, Cappellini E (2019) Enamel proteome shows that Gigantopithecus was an early diverging

pongine. *Nature*, **576**, 262–265. https://doi.org/10.1038/s41586-019-1728-8

Wilkin S, Miller AV, Taylor WTT, Miller BK, Hagan RW, Bleasdale M, Scott A, Gankhuyg S, Ramsøe A,

Uliziibayar S, Trachsel C, Nanni P, Grossmann J, Orlando L, Horton M, Stockhammer PW, Myagmar E,

Boivin N, Warinner C, Hendy J (2020) Dairy pastoralism sustained eastern Eurasian steppe populations

for 5,000 years. *Nature Ecology & Evolution*, **4**, 346–355. https://doi.org/10.1038/s41559-020-1120-y

Wilkin S, Ventresca Miller A, Fernandes R, Spengler R, Taylor WT-T, Brown DR, Reich D, Kennett DJ,

Culleton BJ, Kunz L, Fortes C, Kitova A, Kuznetsov P, Epimakhov A, Zaibert VF, Outram AK, Kitov E,

Khokhlov A, Anthony D, Boivin N (2021) Dairying enabled Early Bronze Age Yamnaya steppe

expansions. *Nature*, **598**, 629–633. https://doi.org/10.1038/s41586-021-03798-4

Yang T, Ling T, Sun B, Liang Z, Xu F, Huang X, Xie L, He Y, Li L, He F, Wang Y, Chang C (2023)

Introducing π-HelixNovo for practical large-scale de novo peptide sequencing. *bioRxiv*,

2023.07.15.549133. https://doi.org/10.1101/2023.07.15.549133

Yilmaz M, Fondrie WE, Bittremieux W, Oh S, Noble WS (2022) *De novo* mass spectrometry peptide

sequencing with a transformer model. *bioRxiv*, 2022.02.07.479481.

https://doi.org/10.1101/2022.02.07.479481

Yu F, Teo GC, Kong AT, Haynes SE, Avtonomov DM, Geiszler DJ, Nesvizhskii AI (2020) Identification of

modified peptides using localization-aware open search. *Nature communications*, **11**, 4065.

https://doi.org/10.1038/s41467-020-17921-y

Zhang J, Xin L, Shan B, Chen W, Xie M, Yuen D, Zhang W, Zhang Z, Lajoie GA, Ma B (2012) PEAKS DB:

757 de novo sequencing assisted database search for sensitive and accurate peptide identification.

758 *Molecular & cellular proteomics: MCP*, **11**, M111.010587. https://doi.org/10.1074/mcp.M111.010587

Supplementary figures

760 Figure S1. Accuracy distribution of *de novo* peptides aligned to the bovine β-lactoglobulin. In this plot, we
761 chose the best alignment for each peptide, irrespective of whether it came from a N or C-terminal kmer seed
762 alignment. We separate the accuracy of alignments coming from either a N-terminal (blue) or C-terminal
763 (orange) seed k-mer.