A long-context language model for deciphering and generating bacteriophage

genomes

Bin Shao[1*]

[1] Department of Molecular and Cellular Biology, Harvard University, Cambridge, MA, USA

*Correspondence should be addressed to Bin Shao (shaobinlx@gmail.com)

Abstract: Inspired by the success of large language models, we develop a long-context generative model

for genomes. Our multiscale transformer model was pre-trained on unannotated bacteriophage

genomes with byte-level tokenization. We demonstrate the foundational capabilities of our model

including the prediction of essential genes, genetic variant effects, regulatory element activity and

taxonomy of unannotated sequences. Furthermore, it generates *de novo* sequences up to 96K base

pairs, which contain functional regulatory elements and novel proteins with phage-related functions.

Large pre-trained language models have drastically transformed the natural language processing (NLP)

field[1,2]. Drawing on the similarity of natural language and genome sequences, genomic language models

have been developed. These models were trained on large scale genomic datasets, and they effectively

predict regulatory elements, uncover co-regulation patterns in proteins, and identify the genome-wide

variant effects[3–7]. However, it remains an open question whether language models can be tailored to

generate genome-scale sequences with functional elements, while retaining the capacity to decipher

the intricate relationships within DNA sequences.

Most of the current genomic language models used masked language modeling like Bidirectional

Encoder Representations from Transformers (BERT)[1]. This approach is not ideal for tasks that require

generating new contents. In addition, they face technical constraints such as short context size and the

aggregation of sequences in k-mer tokenization. These limitations hinder their ability to learn from

genome-scale data with the level of resolution needed for designing functional elements.

In this work, we introduce megaDNA, a long-context language model that demonstrates foundational

capacities in understanding and generating genomic sequences. Our model draws inspiration from the

Generative Pre-trained Transformers (GPT) model[2], which is renowned for its proficiency in generating

long and coherent texts. We utilized a multiscale transformer structure[8] that enables us to train the

model on unannotated whole bacteriophage genomes at the single nucleotide-level. Without further

training, our model can predict gene essentiality across the phage genome in a zero-shot manner. The

model embeddings can be directly applicable to predict functional properties of both regulatory

elements and proteins. Moreover, the trained model generates sequences up to 96K base pairs (bp),

sharing a similar genomic structure with the natural bacteriophage genomes. We found functional

promoters and ribosome binding sites (RBS) in the 5' untranslated regions (5'UTR) of the predicted

genes. The proteins from the generated sequences are predicted to be structurally plausible. Our model

is available from GitHub: https://github.com/lingxusb/megaDNA

To construct the training dataset, we collected bacteriophage genomes with high confidence from three

sources including the NCBI genebank, the Metagenomic Gut Virus (MGV) catalogue[9], and the Gut Phage

Database (GPD)[10] (Supplementary Fig. 1). After data cleaning, we constructed a dataset of 99.7K

bacteriophage genomes to pre-train our model (Methods). The training data was byte-level tokenized,

and we employed a multi-scale transformer structure with three layers and a long-context window in

model training, as proposed by Yu et al.[8]

We hypothesize that our pretrained language model captures the structural patterns of bacteriophage

genomes, allowing the model's loss to approximate the fitness of genome sequences. To test this

hypothesis, we conducted *in silico* mutagenesis analysis to predict essential genes in the lambda phage

genome[11] (Fig. 1b). Without any supervised training, we found mutations within the coding sequences of

essential genes result in higher losses than non-essential genes (Fig. 1c). Consequently, changes in

model loss can be used a zero-shot predictor of essential genes (AUROC: 0.86, Fig. 1d). Similarly,

mutations in the start and stop codons of essential genes lead to higher model losses than non-essential

genes (Fig. 1d, Supplementary Fig. 2).

Sequence embeddings from language models capture rich contextual information. We further explored

the utility of our model's embeddings for a range of predictive tasks. We first evaluated our model's

ability to predict effects of sequence mutations on protein functions (Fig. 1e). Mutated gene coding

sequences were used as inputs, and a regressor was trained on model embeddings to predict the

mutational effects. Our model's prediction performance closely matched the state-of-the-art model

DeepSequence[12] (Fig. 1f), including for a protein not existing in the training dataset (Supplementary Fig.

3). Moreover, our model successfully predicted the impact of SNPs across the T7 bacteriophage

genome[13], even with limited training samples (Fig. 1g, Supplementary Fig. 4).

Expression of phage genes relies on the protein synthesis machinery in host bacteria cells. We

investigated the potential of the model embeddings to predict regulatory element activity in bacteria

(Fig. 1 h). Our model effectively predicted the translation efficiencies of 5'UTR in non-model organisms

such as *K. Oxytoca, P. Protegens*, as well as for high-throughput gene expression libraries in *E. coli*[14] (Fig.

1i). The model performance is also robust to the training sample size (Supplementary Fig. 5).

Lastly, we extended our model to identify taxonomy of unannotated sequences (Fig. 1j). We collected

unannotated sequences from bacteriophage, bacteria, and archaea. The embeddings from our model

separated these sequences in a low-dimensional space (Fig. 1k). By training a linear regressor based on

model embeddings, we achieved a high classification accuracy (average AUROC of 0.98, Supplementary

Fig. 6). This high level of accuracy was consistent across different layers of our model (Supplementary

Fig. 7). Since the training data doesn't contain genome sequences of bacteria or archaea, these results

demonstrate the broad applicability of our model.

Our approach enables *de novo* generation of genome sequence of bacteriophage (Fig. 2a). We

generated a total of 1,024 sequences longer than 1K bp. geNomad[15] was used for functional annotation

of the generated sequences. Among all these sequences, 607 have a virus score larger than zero. The

average sequence length is 43K bp, and the average number of predicted genes per sequence is 67,

which are similar to the training dataset (mean length: 48K bp, average number of predicted genes: 68).

The gene length distribution is close to that of the training dataset (Fig. 1b, average gene length: 558 bp

vs 646 bp), while the predicted gene numbers show wider spread (Supplementary Fig. 8). The median

virus score of these generated sequences is 0.84 and the maximum score is 0.97, comparable to the

virus scores of natural bacteriophage genomes which range from 0.70 to 0.98 (Fig. 1c). 223 out of 607

generated sequences (37%) are predicted to be Caudoviricetes by geNomad (Fig. 1d). As a comparison,

98% of the genomes in the training dataset were classified as Caudoviricetes. Additionally, 388

sequences were predicted to have bacterial hosts with a probability greater than 0.95, as determined by

the DeepHost model[16] (Supplementary Fig. 9).

We then examined the 5'UTR of the annotated genes in the generated sequences to determine if they

contain functional regulatory elements such as promoters and RBS to initiate transcription and

translation. We chose the generated sequence #87 for further analysis due to its high predicted virus

score (0.96) and its relatively small size (28K bp). Using a machine learning tool (Promoter Calculator)[17],

we identified the -35 box and -10 box of the promoter within the 5'UTR of the predicted phage

stabilization protein. Notably, their sequences are close to the established consensus motifs: TTGACA

and TATAAT (Fig. 1f). Prior to the start codon of the same gene, we observed a region enriched in

adenine (A) and guanine (G) nucleotides, indicative of a functional ribosome binding site (Fig. 1f).

Analyzing all 5'UTR of the predicted genes from this sequence, we found a significantly higher promoter

activity compared to random sequences of the same length (Fig. 1g). Intriguingly, the proportion of A

and G nucleotides peaked around 10 bp upstream of the start codon, aligning closely to the optimal

position for an RBS to drive translation initiation (Fig. 1h). This trend of A/G enrichment is also

consistent across all the generated sequences (Supplementary Fig. 10). In short, our generated

sequences harbor functional regulatory sequences that could enable expression of the predicted genes.

In our generated sequences, 343 annotated genes were predicted to match geNomad markers. These

genes share very little homology with the training dataset (Supplementary Table 1). We employed

ESMfold[18] to predict their structures and calculated the average predicted local distance difference test

(pLDDT) scores. This score reflects the confidence of ESMfold on the predicted structures. The median

pLDDT score for these proteins is higher than that of random peptide sequences (28 vs 18). We further

randomly sampled 10K annotated genes from all the generated sequences and found high pLDDT scores

for them (median value of 36, Supplementary Fig. 11), suggesting that these generated proteins are

more likely to adopt a stable conformation. Functional annotation of all annotated proteins using

deepFRI[19] reveals several large families with diverse functional roles, including the transporter activity

and the structural molecule activity (Fig. 1j). Among these, several proteins were predicted to have DNA-

binding activity, and the predicted structure resembles the canonical helix-turn-helix (HTH) domain in

this protein family (Supplementary Fig. 12).

To the best of our knowledge, our work presents the first long-context generative model for genomic

sequences. Our language model effectively learns the language of gene coding and regulatory sequences

via a single step of self-supervised training on unannotated whole genomes. The generated sequences

match the length of natural bacteriophage genomes and display functional genomic architectures. It is

worth noting that these sequences have not been optimized at the codon or gene level to allow for

efficient self-replication in bacteria. However, with further scaling up and fine-tuning, we envision that

generative genomic models have the potential to enable *de novo* design of the whole genome, offering

opportunities for breakthroughs in medicine, agriculture, and environmental science. This field also

faces ongoing challenges in ethical considerations, biosafety, and regulatory frameworks, which are

critical for the responsible advancement of generative modeling in synthetic biology.

Figures

 Figure 1. Foundational capacities of our language model.

a) Overview of the model applications. **b**) *In silico* mutagenesis analysis to identify essential genes in the

bacteriophage genome. **c**) Model loss variation across the lambda phage genome in the mutagenesis

analysis. Upper, essential and non-essential genes in the genome. Lower: changes in model loss for 50

bp non-overlapping windows across the genome (blue). Moving averages of model loss across 5,000 bp

windows are denoted in red. **d**) Zero-shot prediction of essential genes by calculating the effects of

mutations in the gene coding region (blue), start codon (orange), and stop codon (green). Area Under

the ROC Curve (AUROC) scores are reported. **e**) Prediction of mutational effects on protein functions

using model embeddings. **f**) Prediction of mutational effects for the deep mutational scanning

experiment of the *infA* gene. Spearman correlation coefficients of the predicted and reported fitness

from 5-fold cross validation tests are reported (Blue: megaDNA, gray: DeepSequence). n is the number

of training samples. **g**) Prediction of the impacts of Single Nucleotide Polymorphisms (SNPs) in the T7

bacteriophage genome. Spearman correlation of the predicted and reported fitness from 5-fold cross

validation tests are reported. **h**) Prediction of regulatory element activity using model embeddings. **i**)

Prediction of translation efficiencies for non-model organisms and high-throughput gene expression

libraries. For *K. oxytoca, P. protegens* and *E. coli DH10B*, we evaluated the model performance on

endogenous genes. Five-Fold cross-validation tests were used for all calculations. **j**) Distinguishing

taxonomies of unannotated sequences using model embeddings. **k**) UMAP visualization of model

embeddings for sequences from bacteriophages, bacteria, and archaea (model middle layer, n=5000 per

group). For f, g and i, error bars denote standard deviation (n = 5).

Figure 2. Language model generates sequences with functional genomic structures.

a) The workflow schematic. **b**) Comparison of gene length distributions between predicted genes in generated sequences (n = 40,399) and a randomly sampled subset of genes from the training dataset (n = 10,000). **c**) Comparison of the predicted virus scores for generated sequences and the training dataset. **d**) Predicted taxonomy for the generated sequences. Only taxonomies with > 1 sequence are shown. **e**) Functional annotation of a selected sequence fragment (generated sequence #87). **f**) Predicted promoter activity for all the 5'UTRs in the generated sequence #87 (n = 44), along with the promoter activity of the random sequences with the same length. **g**) Proportions of adenine (A) and guanine (G) nucleotides preceding the start codon of all the predicted genes in the generated sequence #87. **h**) Mean predicted pLDDT scores for proteins with geNomad markers from generated sequences (sample size: n = 343; median value: 28) against random peptide sequences of the same lengths (sample size: n = 343; median value: 18). A sample generated protein is shown on the right. **j**) Top 10 predicted functions of proteins derived from the generated sequences.

References

1.   Devlin, J., Chang, M.-W., Lee, K. & Toutanova, K. Bert: Pre-training of deep bidirectional
transformers for language understanding. *arXiv preprint arXiv:1810.04805* (2018).

2.   Brown, T. *et al.* Language models are few-shot learners. *Adv Neural Inf Process Syst* **33**, 1877–
1901 (2020).

3.   Ji, Y., Zhou, Z., Liu, H. & Davuluri, R. V. DNABERT: pre-trained Bidirectional Encoder
Representations from Transformers model for DNA-language in genome. *Bioinformatics* **37**,
2112–2120 (2021).

4.   Dalla-Torre, H. *et al.* The nucleotide transformer: Building and evaluating robust foundation
models for human genomics. *bioRxiv* 2021–2023 (2023).

5.   Benegas, G., Batra, S. S. & Song, Y. S. DNA language models are powerful predictors of genome-
wide variant effects. *Proceedings of the National Academy of Sciences* **120**, e2311219120 (2023).

6.   Hwang, Y., Cornman, A. L., Kellogg, E. H., Ovchinnikov, S. & Girguis, P. R. Genomic language
model predicts protein co-regulation and function. *bioRxiv* 2023–2024 (2023).

7.   Nguyen, E. *et al.* Hyenadna: Long-range genomic sequence modeling at single nucleotide
resolution. *arXiv preprint arXiv:2306.15794* (2023).

8.   Yu, L. *et al.* Megabyte: Predicting million-byte sequences with multiscale transformers. *arXiv*
preprint arXiv:2305.07185 (2023).

9.   Nayfach, S. *et al.* Metagenomic compendium of 189,680 DNA viruses from the human gut
microbiome. *Nat Microbiol* **6**, 960–970 (2021).

10. Camarillo-Guerrero, L. F., Almeida, A., Rangel-Pineros, G., Finn, R. D. & Lawley, T. D. Massive
expansion of human gut bacteriophage diversity. *Cell* **184**, 1098–1109 (2021).

11. Piya, D. *et al.* Systematic and scalable genome-wide essentiality mapping to identify nonessential
genes in phages. *PLoS Biol* **21**, e3002416- (2023).

12. Riesselman, A. J., Ingraham, J. B. & Marks, D. S. Deep generative models of genetic variation
capture the effects of mutations. *Nat Methods* **15**, 816–822 (2018).

13. Robins, W. P., Faruque, S. M. & Mekalanos, J. J. Coupling mutagenesis and parallel deep
sequencing to probe essential residues in a genome or gene. *Proceedings of the National*
Academy of Sciences **110**, E848–E857 (2013).

14. Evfratov, S. A. *et al.* Application of sorting and next generation sequencing to study 5′-UTR
influence on translation efficiency in Escherichia coli. *Nucleic Acids Res* **45**, 3487–3502 (2017).

15. Camargo, A. P. *et al.* Identification of mobile genetic elements with geNomad. *Nat Biotechnol* 1–
10 (2023).

16. Ruohan, W., Xianglilan, Z., Jianping, W. & Shuai Cheng, L. I. DeepHost: phage host prediction with
convolutional neural network. *Brief Bioinform* **23**, bbab385 (2022).

17. LaFleur, T. L., Hossain, A. & Salis, H. M. Automated model-predictive design of synthetic
promoters to control transcriptional profiles in bacteria. *Nat Commun* **13**, 5159 (2022).

18. Lin, Z. *et al.* Language models of protein sequences at the scale of evolution enable accurate
structure prediction. *BioRxiv* **2022**, 500902 (2022).

19. Gligorijević, V. *et al.* Structure-based protein function prediction using graph convolutional
networks. *Nat Commun* **12**, 3168 (2021).

20. Kelsic, E. D. *et al.* RNA Structural Determinants of Optimal Codons Revealed by MAGE-Seq. *Cell
Syst* **3**, 563-571.e6 (2016).

21. Ryu, M.-H. *et al.* Control of nitrogen fixation in bacteria that associate with cereals. *Nat Microbiol*
5, 314–330 (2020).

22. Espah Borujeni, A., Zhang, J., Doosthosseini, H., Nielsen, A. A. K. & Voigt, C. A. Genetic circuit
characterization by inferring RNA polymerase movement and ribosome usage. *Nat Commun* **11**,
5001 (2020).

23. McInnes, L., Healy, J. & Melville, J. Umap: Uniform manifold approximation and projection for
dimension reduction. *arXiv preprint arXiv:1802.03426* (2018).

Methods

Model training

Our training dataset was curated from three sources. Firstly, we downloaded all the complete virus

genomes from NCBI genebank, retaining only those with "phage" in the organism's name. Secondly, the

phage genomes from MGV were downloaded, and we only included genomes with a completeness

score larger than 95% and classified under the order Caudovirales. Our third source was GPD, and we

kept all the genomes with a completeness score above 0.95. Following the initial collection, we

undertook an additional round of filtering. We used geNomad to predict the taxonomy of these

genomes and then deleted all the genomes whose predicted host is not a unicellular organism. All

genomes smaller than 96K bp were used to construct the final training dataset.

Our megaDNA model utilized a three-layer transformer structure[8]. Each layer had a depth of 8 and

progressively larger dimensions (local: 196, middle: 256, global: 512). The sequence lengths for three

layers are 16, 64, 128. The model contains 145M parameters in total. We assigned numerical tokens (1,

2, 3, and 4) to the nucleotides A, T, C, and G, respectively. For model training, we used a batch size of 1

and set the learning rate at 0.0002. The learning rate was progressively increased during the initial

50,000 steps as part of a warmup schedule. We utilized the Adam optimizer and applied gradient

clipping with a norm of 0.5 to prevent gradient explosion.

In silico **mutagenesis of phage genomes**

Lambda phage genome sequences and annotations were downloaded from NCBI (Accession number:

NC_001416.1). Essential genes were identified according to Piya et al[11]. We conducted *in silico*

mutagenesis using a 50 bp sliding window across the genome, and each nucleotide was randomly

mutated to A, T, C, or G with equal probability. The impact of mutations was assessed by computing the

model loss, which is further compared with their original counterparts. For both essential gens and non-

essential genes, we calculated the mean model loss for all the windows within the gene coding region.

Mann-Whitney U test was used to evaluate statistical differences between these two groups

(*scipy.stats.mannwhitneyu*). Furthermore, mutations targeting the start and stop codons of all coding

genes were simulated. We also generated a control set comprising an equivalent number of 3-nt

mutations randomly distributed across the genome. The effect of these mutations on model loss was

analyzed to infer their impact on fitness. The changes in model loss were used a predictor of gene

essentiality, and we computed the Receiver Operating Characteristic (ROC) curve and the Area Under

the ROC Curve (AUROC).

Prediction of mutational effects on protein function

The DNA sequences of the mutated genes were used as the model input. Embeddings from three

different layers of the model were extracted (dim = 196, 256, 512). These embeddings were

concatenated to form a 964-dimensional vector representing each gene coding sequence. We used the

5-fold cross validation to evaluate the prediction performance of our model. In each fold, one fifth of the

data was held out as test data while the remaining data were used as training data. A Ridge regression

model was trained on the input and fitness values in the training dataset with default parameters

(*sklearn.linear_regression.RidgeCV*). The predictive performance of this model was then evaluated on

the test dataset. The infA gene dataset was obtained from Kelsic et al[20]. For the T7 bacteriophage

dataset[13], genome sequence and annotations were downloaded from NCBI (Accession number:

V01146.1). The model performance was evaluated for each gene in the same manner.

Prediction of translation efficiency

We assessed the translation efficiency (TE) of genes in *Klebsiella oxytoca, Pseudomonas protegenes Pf-5*,

and *Escherichia coli DH10B* by calculating the ratio of average ribosome density (RD) to mRNA

expression. The ribosome density of each gene was calculated by averaging all ribosome occupancies

over the length of the gene. The mRNA expression in FPKM (fragments per kilobase of transcript per

million mapped reads) of each gene that was calculated by averaging the height of RNA-seq profile over

the length of the gene. The ribosome profiling and RNA-seq datasets of *K. oxytoca* and *P. protegenes* Pf-

5 were obtained from the Sequence Read Archive with the accession code PRJNA579767[21]. The *E. coli*

DH10B datasets were obtained from NCBI GEO database with accession number GSE152664[22]. We used

the DNA sequences spanning from -160 to 160 relative to the start codon as the input to our model.

Model embeddings were extracted from three layers (dim = 196, 256, 512) and concatenated together

to form a 964-dim vector for each input sequence. To mitigate the influence of lowly expressed genes on

TE calculations, we focused on the top 25% expressed genes in *Klebsiella oxytoca* and *Escherichia coli*

DH10B, and the top 20% expressed genes in *P. protegenes Pf-5*. We used 5-fold cross validation to

evaluate the performance of our model. In each fold, a ridge regression model was trained on the input

and TE values in the training dataset with default parameters (*sklearn.linear_regression.RidgeCV*). The

trained model was then used to predict TE values in the test dataset. For the Evfratov et al. dataset[14], 20

nt and 30 nt 5'UTR sequences were used as the input. The model performance was evaluated as

previously described.

Classification taxonomy of unannotated sequences

We analyzed 10K bp sequences randomly sampled from bacteriophage, bacteria, and archaea genomes

downloaded from NCBI genebank (n = 5,000 each). For the total of 15,000 sequences, sequence

embeddings were generated using our model across three layers (dim = 196, 256, 512). For embedding

visualization, we used Uniform Manifold Approximation and Projection (UMAP)[23] as implemented in the

python package *umap-learn*. To classify these sequences, we employed a logistic regression model to

evaluate the predictive performance of the embeddings across multiple classes

(*sklearn.linear_model.LogisticRegression*). The model's performance was assessed using a 5-fold

Stratified K-Fold cross-validation. This method ensures that each fold is a good representative of the

whole by maintaining the same proportion of samples for each class as in the complete dataset. Within

each fold, the model was trained on a subset of the data and then used to predict probabilities on the

test subset. For each class, we computed the Receiver Operating Characteristic (ROC) curve and the Area

Under the ROC Curve (AUROC).

Model inference

We generated sequences from the trained model using a predefined set of parameters. Specifically, we

adjusted the temperature to 0.95 to ensure a balance between variety and coherence in the sequences

and kept the filter threshold at 0.0 to avoid limiting the range of token probabilities. For model training

and inference, we utilized Nvidia's A100 GPU (40GB) and 3090 Ti GPU (24GB) and used the PyTorch

version 2.1.1 software package.

Analysis of the generated sequence

geNomad[15] was used for sequence annotation of all generated sequences. The 100 base pair regions

preceding the start codon of each predicted gene was designated as the 5'UTR. We employed the

Promoter Calculator[17] to find the promoters in these regions. Only the promoter with the highest

predicted activity was annotated. For protein structure prediction, we used the pretrained ESMfold

model v1[18]. The chunk size of the model was set to be 64 for proteins longer than 700 AA and 128 for

shorter proteins. We limited our structure calculation to proteins less than 1000 AA in length. Function

prediction for these proteins was carried out using the default deepFRI model[19], as available on GitHub

(https://github.com/flatironinstitute/DeepFRI). We used a score cutoff of 0.5 which was reported to be

significant in the original publication. Bacteria host prediction was done using DeepHost species-level

model[16] with default parameters (https://github.com/deepomicslab/DeepHost). Predictions with a

probability greater than 0.95 were used in the following analysis.

Data availability

The bacteriophage genomes were downloaded from public databases including NCBI genebank

(ftp://ftp.ncbi.nlm.nih.gov/genomes/genbank/), MGV (https://portal.nersc.gov/MGV), and GPD

(https://www.sanger.ac.uk/data/gut-phage-database/).

Code availability

Our trained model and model inference codes are available from GitHub:

https://github.com/lingxusb/megaDNA

Supplementary Figure 1: **Genome size distributions of three data sources.** Distributions of genome

sizes within the training dataset: NCBI (n = 16,609), MGV (n = 53,032) and GPD (n = 30,032).

Supplementary Figure 2: **Model loss changes due to codon mutations**. **a**) Changes in model loss for random 3-nt mutations and mutations in start codon and stop codons of genes in the lambda phage genome (n = 73). **b**) Changes in model loss for mutations in start codons of essential genes (n = 29) and non-essential genes (n = 44). **c**) Changes in model loss for mutations in stop codons of essential genes (n = 29) and non-essential genes (n = 44). For a, b and c, p-values from the Mann-Whitney U test are shown. The central line inside the box represents the median value. The top and bottom borders of the box represent the third (upper) and first (lower) quartiles, respectively.

Supplementary Figure 3: **Prediction of mutational effects of beta-lactamase.** Spearman correlation of the predicted and reported fitness for mutants from 5-fold cross validation tests are shown. n is the number of training samples for megaDNA. Blue and gray colors represent results from megaDNA and DeepSequence. Error bars denotes standard deviation.

Supplementary Figure 4: **Length and mutation coverage for the genes in T7 bacteriophage genome.**

Upper**:** gene lengths. Lower: the ratio of observed SNPs to all possible SNPs per gene.

Supplementary Figure 5: **Impact of window position and training sample size on translation efficiency prediction. a**) Impact of the input window position for the prediction of translation efficiency of endogenous genes in *E. coli*. Positions are reported relative to the start codons. **b**) Effect of training sample number on the prediction performance of 5'UTR activity in the Evfratov et al. dataset. For a and b, results from 5-fold cross validation tests are shown. Error bars denotes standard deviation.

Supplementary Figure 6: **Taxonomy prediction of unannotated sequences**. Embeddings from the middle layer was used to classify sequences into virus, bacteria, and archaea. The model's performance was assessed using a 5-fold Stratified K-Fold cross-validation test. The receiver operating characteristic (ROC) curves are shown (n = 5,000 for each category). The mean ROC curve (AUROC) scores from 5-fold cross-validation tests are reported.

Supplementary Figure 7: **Sequence embedding of different model layers and the taxonomy prediction performance.** Sequence embeddings from the local layer (**a**) and global layer (**b**), and their respective taxonomy prediction performances (**c**) and (**d**). The model's performance was assessed using 5-fold Stratified K-Fold cross-validation tests. The receiver operating characteristic (ROC) curves are shown (n = 5,000 for each category). The mean ROC curve (AUROC) scores from 5-fold cross-validation tests are reported.

Supplementary Figure 8: Gene number distributions for the generated sequences and the training dataset. Comparison of the number of predicted genes in generated sequences (n = 607) versus those in the training dataset (n = 99,673)

Supplementary Figure 9: **Frequencies of the predicted bacteria hosts for the generated sequences.**

Host prediction was done using DeepHost[16] (n = 388). Predictions with a probability greater than 0.95 were used in the analysis.

Supplementary Figure 10: Proportions of adenine (A) and guanine (G) nucleotides preceding the start

codon for all the generated sequences. Blue line denotes the mean A+G nucleotides proportion profile

for all the generated sequences with a virus score larger than zero (n = 607). The shaded region

represents the standard derivation of all profiles.

<u>Supplementary Figure 11:</u> Mean pLDDT scores for proteins derived from the generated sequences.

The distribution of mean pLDDT score for a randomly sampled subset of all the generated proteins is

shown (sample size: n = 10,000; median value: 36).

Iron-sulfur cluster binding
GO:0051536
score: 0.92683

DNA binding
GO:0003677
score: 0.83517

Structural molecule activity
GO:0005198
score: 0.95713

Ion transmembrane transporter activity
GO:0015075
score: 0.70163

Supplementary Figure 12: **Representative proteins from the generated sequence with predicted**

functions and structures. The protein structures were predicted using ESMfold[18] and the functions were

annotated using deepFRI[19]. Predicted scores and GO terms from deepFRI are shown.

Supplementary Table 1: BLAST analysis of the generated genes. We conducted BLAST analysis to

compare the generated genes with geNomad markers (n = 343) against the training dataset. Using

default settings, we found hits for 3 out of the 343 genes. Only one hit is shown if there are multiple

identical matches across reference genomes.

Query	Reference	BLAST results
Generated sequence #202, gene #97 (length = 2,346)	MGV-GENOME-0232742 (length = 33,859)	Score = 58.4 bits (31), Expect = 3e-05 Identities = 31/31 (100%), Gaps = 0/31 (0%) Strand=Plus/Minus Query 787 TTTGCAAAGCAGAACTATACGATGTTGGACA 817 ||||||||||||||||||||||||||||||| Sbjct 25855 TTTGCAAAGCAGAACTATACGATGTTGGACA 25825
Generated sequence #209, gene #102 (length = 888)	MN176228.1 Bacillus phage 049ML003 (length = 44,817)	Score = 54.7 bits (29), Expect = 1e-04 Identities = 29/29 (100%), Gaps = 0/29 (0%) Strand=Plus/Plus Query 517 GGGCCAAAAGGTGATACAGGAGCAAAAGG 545 ||||||||||||||||||||||||||||| Sbjct 7393 GGGCCAAAAGGTGATACAGGAGCAAAAGG 7421
Generated sequence #561 gene #14 (length = 2,721)	MGV-GENOME-0359033 1-89291/89291 (length = 89,291)	Score = 52.8 bits (28), Expect = 0.002 Identities = 32/34 (94%), Gaps = 0/34 (0%) Strand=Plus/Minus Query 2432 AAGCAAAGAAATTTATCAATAATGCTTTCAAAGA 2465 |||||||||||||||||||||||||||| || || Sbjct 86302 AAGCAAAGAAATTTATCAATAATGCTTTTAATGA 86269
	MGV-GENOME-4432828 (length = 88,796)	Score = 52.8 bits (28), Expect = 0.002 Identities = 28/28 (100%), Gaps = 0/28 (0%) Strand=Plus/Plus Query 2432 AAGCAAAGAAATTTATCAATAATGCTTT 2459 |||||||||||||||||||||||||||| Sbjct 2497 AAGCAAAGAAATTTATCAATAATGCTTT 2524