A single computational objective drives specialization of streams in visual cortex

Dawn Finzi[1,2,✉]**, Eshed Margalit** ⬤[3]**, Kendrick Kay**[4*]**, Daniel L. K. Yamins**[1,2,5,*]**, and Kalanit Grill-Spector** ⬤[1,5,*]

[1]Department of Psychology, Stanford University, Stanford, CA 94305

[2]Department of Computer Science, Stanford University, Stanford, CA 94305

[3]Neurosciences Graduate Program, Stanford University, Stanford, CA 94305

[4]Center for Magnetic Resonance Research, Department of Radiology, University of Minnesota, Minneapolis, MN 55455

[5]Wu Tsai Neurosciences Institute, Stanford University, Stanford, CA 94305

[*]co-senior author

Human visual cortex is organized into Dorsal, Lateral, and Ventral streams. A long-standing hypothesis is that the functional organization into streams emerged to support distinct visual behaviors. Here, we use a neural network-based computational model and a massive fMRI dataset to test why visual streams emerge. We find that models trained for stream-specific visual behaviors poorly capture neural responses and organization. Instead, a self-supervised Topographic Deep Artificial Neural Network, which encourages nearby units to respond similarly, successfully predicts neural responses, spatial segregation, and functional differentiation across streams. These findings challenge the prevailing view that streams evolved to separately support different behaviors, and suggest instead that functional organization arises from a single principle: balancing the learning of generally useful representations from visual inputs with local spatial constraints.

processing streams | topography | vision | neural network

Correspondence: *dfinzi@stanford.edu*

Confronted by the blooming, buzzing confusion of the world around us, we perform a diverse range of computations upon our rich visual inputs: accurately identifying objects in our surroundings, their locations, and their actions in less than a sixth of a second. To accomplish this amazing feat, seemingly effortlessly, the human visual system contains extensive neural machinery including more than two dozen visual areas which are organized into three anatomically distinct, and hierarchical processing streams spanning the occipital, temporal, and parietal lobes [1, 2]: (1) the Ventral stream, which ascends from early visual cortex (EVC: V1, V2, V3) in the occipital lobe to the inferior aspects of the temporal lobe, (2) the Lateral stream, ascending from EVC through lateral occipito-temporal cortex to the superior temporal sulcus (STS), and (3) the Dorsal stream, ascending from EVC superiorly along occipito-parietal cortex. The logic of the functional organization of the visual system has been studied across decades of empirical [3, 4, 5, 6], information systems [1, 2], and computational [7, 8, 9, 10] research. Yet why the visual system is organized into multiple processing streams remains an open question.

The dominant theory in neuroscience - which we will refer to as the *multiple behavioral demands hypothesis* - argues that the organization into streams is an outcome of the need to rapidly extract behaviorally-relevant information from dense visual input. This hypothesis suggests that the visual system is optimized for independent visual behaviors that can be done in parallel with dedicated neural machinery, yielding a fast and efficient system [1, 2, 3, 11, 12, 13, 14, 15, 9]). Consider trying to safely cross a busy intersection: we must immediately recognize whether the approaching objects are cars, gauge how far away from us they are, and track whether they are accelerating through a yellow light or slowing to a stop. One way to achieve this would be to break down the processing of the visual input into separate distinct tasks, which can be independently optimized for. Supporting this hypothesis, empirical data suggests that the Ventral stream supports visual recognition and categorization [3, 4, 16, 15], the Lateral stream supports perception of visual dynamics [17], particularly actions [18] and social information [19, 20], and the Dorsal stream supports spatial perception and visually guided actions [3, 4].

An alternative *spatial constraints hypothesis* suggests that a set of physical constraints, such as wiring length, could produce the segregation of the visual system into streams. According to Nelson and Bower [21], "if the brain's estimated 10^{11} neurons were placed on the surface of a sphere and fully interconnected by individual axons 0.1 µm in radius, the sphere would have to have a diameter of more than 20 km to accommodate the connections." As a result of physical constraints and a need for fast processing, there is a known bias in the brain toward short-range connections [22, 8]. One way to minimize wiring length locally is to encourage nearby neurons to respond similarly [1]. Indeed, locally correlated responses are evident in the many cortical topographic maps, such as retinotopic maps [23, 24] in which nearby neurons in cortex process nearby regions of the visual field. From an information theoretic standpoint, having neurons that are frequently involved in processing related information close together enhances neural processing by making it faster and more efficient [1, 2].

Thus, we ask: is the functional organization of visual cortex into streams due to optimization for multiple distinct behaviors, or due to balancing spatial and information constraints? Computational breakthroughs using deep artificial neural networks (DANNs) have substantially advanced mechanistic understanding of the visual system. These neural-inspired architectures are organized hierarchically, take as inputs visual images (referred to as image-computable), are optimized during training to perform a task by minimizing a training loss function, and have been particularly successful at predicting the functional [15, 25, 26] and spatial [27, 28, 29] organization of the Ventral stream. For example, a key insight from DANNs is that models trained on categorization, the stream-hypothesized behavior of the Ventral stream, better predict responses in the macaque Ventral stream than other models [15]. As such, DANNs offer an exciting new opportunity for an in-silico testing bed to answer the question: why are there processing streams? By instantiating our hypotheses computationally as optimization goals of DANNs and testing them vs. neural data, we move to a new era of computational testing of theories of the visual system. In this framework, we will instantiate DANNs that are optimized during training to perform the computational goal corresponding to each hypothesis, and then test how well each model predicts the human visual system's functional and spatial organization into streams.

a) Formalizing the *multiple behaviors hypothesis* using task optimized models

b) Formalizing the *spatial constraints hypothesis* using topographic deep neural networks

c) Linking models to the brain

Measure brain and model responses to the same images

Find optimal 1-to-1 mapping that maximizes functional alignment while maintaining spatial continuity

Activations for each model unit

Natural Scenes Dataset

Fixation dot

8.4°

Activations for each voxel

Pairwise distances between responses

Initial cost matrix

$1 -$ Pearson's r

Units (U)

Voxels (V)

Updated cost matrix

$1 -$ Pearson's r

Hungarian matching algorithm

Unit-to-voxel assignments

Unit u_i

Voxel v_j

Ex. for unit u_i

Previously assigned v_j

New "spatially-valid" zone for assignment

d) Evaluation

Spatial correspondence

Functional correspondence

Training task
Detection
Action
Categorization

Location on TDANN cortical sheet

Figure 1. To test competing theories, we use two candidate model classes: **(a) Multiple behaviors (MB) models: object detection, action recognition, & object categorization.** We train separate DANNs optimized for each of the three tasks. Units are sampled from the final convolutional layer of the backbone architecture for all models and pooled to create candidate source units that are mapped to the brain. **(b) Spatial constraints (SC) models: Topographic Deep Artificial Neural Networks (TDANNs)** developed in [27] contain units that are assigned positions on a simulated cortical sheet prior to training and are trained to minimize the sum of a functional loss and a spatial loss, controlled by a free parameter α. Units from the final convolutional layer are used as candidate source units for mapping to the brain. **(c) Overview of 1-to-1 mapping approach for linking model to brain.** The goal is to find the overall best functional match between model units and brain voxels. 10,000s of images of natural scenes were presented to 8 individuals and candidate models. Responses are extracted from model units and brain voxels, and correlations between each unit-voxel pair are computed. Correlations are transformed into an initial cost matrix ($1 -$ correlation). Using the Hungarian optimization algorithm [30] we determine an initial assignment such that each unit is assigned to a unique voxel and the average cost across all unit-voxel pairings is minimized (black: assignment). To promote general smoothness in the mapping, neighboring units' assigned voxels are used to calculate "spatially-valid zones", such that any voxels outside a unit's zone are set to have a prohibitive cost (indicated in white, see Alg. 1 for details). This updated cost matrix is used to redetermine unit-to-voxel assignments, repeated for 100 iterations. **(d) Evaluation.** Success in capturing the organization of the visual system into processing streams is evaluated by determining spatial (left) and functional (right) correspondence. For MB models, optimal spatial alignment would mean all object detection units map to Dorsal, action recognition to Lateral, and categorization to Ventral. For SC models, optimal alignment would mean clustered units on the simulated cortical sheet map to distinct streams. Functional correspondence measures correlation with brain responses on left out images, benchmarked against stream-specific noise ceilings (light gray.

Results

Formalizing two key competing hypotheses for stream organization via neural network models

We instantiate the multiple behavioral demands hypothesis by training three DANNs for their stream-specific visual behaviors - Dorsal: object detection [31], Lateral: action recognition [32], Ventral: object categorization [33] (Fig. 1a). We chose these tasks as they are the computer vision equivalents of the proposed behaviors each stream is thought to support. As the multiple behavioral demands hypothesis argues that each stream has been optimized over evolution both functionally and structurally (e.g., dedicated neural circuitry), each model is trained separately for the stream-hypothesized task. We reason that this will allow optimized task training and encourage learning of maximally different representations.

We instantiate the spatial constraints hypothesis using a topographic DANN (TDANN, [27, 34]), as it implements a spatial constraint during training and has been effective in predicting the Ventral stream functional topography [27]. In the TDANN, model units in each layer are assigned a position on a 2D simulated cortical sheet, and a spatial constraint is balanced together with contrastive self-supervised learning (SimCLR [35], Fig. 1b) using separate spatial and task losses during training. The spatial constraint encourages nearby units to have more correlated responses than distant units, and SimCLR encourages two snapshots of the same image (differing in incidental properties such as color or field of view) to have similar representations that are distinct from others [35]. We choose SimCLR because it is one of the best performing self-supervised approaches and because it generates broadly useful representations that are beneficial for a range of visual tasks [36]; we use an intermediate spatial weight, as prior research shows that that this combination best replicates the functional topography of the Ventral stream [27]

For the multiple behaviors models we use a ResNet-50 backbone [33], as these larger models achieve better task performance than shallower models with fewer parameters, and previous research has shown a positive correlation between a model's task performance and its ability to predict neural responses in the Ventral stream [15]. For the spatial constraints models, we use a ResNet-18 backbone because it has a better match between the number of model layers and areas in the brain [37]. We additionally implement two controls. First, for the multiple behaviors models, we include models trained on the same hypothesized tasks for each stream, but using a ResNet-18 backbone to match the spatial constraints model. Second, we train an additional set of spatial constraints models on a supervised categorization task, as a large body of research suggests that a categorization task results in best prediction of Ventral stream responses [15, 38, 25] and this allows us to better disentangle the effects of the spatial and task loss components.

Evaluating the correspondence between models and visual cortex

Testing the extent to which the models can recapitulate the functional organization of visual cortex into processing streams requires evaluating the functional and spatial match between model units and brain data. This necessitates: (i) measuring brain and model responses on the same stimuli to test functional correspondence, and (ii) a 1-to-1 mapping between model units and brain voxels in order to determine the spatial assignment of model units to streams. To fulfill (i) we leverage the Natural Scenes Dataset (NSD) [39]. The NSD is a massive, high-resolution, and high quality (Supplemental Fig. S1) fMRI dataset that measured responses to thousands (8000-10000) of natural images in each of eight individuals. Importantly, the NSD generates differential responses across the Dorsal, Lateral, and Ventral visual streams in each of the individuals, verifying that the streams are functionally distinct (Supplemental Fig. S2). To fulfill (ii), we develop a new algorithm that finds the unit-to-voxel pairings that have the highest functional similarity (highest correlation between responses for common set of images) while maintaining spatial continuity. The algorithm first calculates the functional similarity between all unit-to-voxel pairs (cost matrix). Then it uses an iterative version of the Hungarian algorithm [30] with an additional spatial prior (Fig. 1c, Alg. 1) to minimize the cost matrix and find the optimal mapping. Notably, this 1-to-1 mapping between units and voxels not only provides a window into spatial organization but also provides a more stringent test of models [40, 41], allowing more rigorous testing of DANN models of the brain [42].

We use a two-stage approach to evaluate functional and spatial correspondence. First, using the unique images seen by each participant, we find a direct model-to-brain mapping between units in the model's convolutional end-layer and the union of voxels in the anatomical regions of interest (ROIs) corresponding to the ends of each stream in each participant (Fig. 2c) using the procedure delineated above. Second, once this mapping is determined, we assess the spatial and functional correspondence between the candidate model and the brain. We assess spatial correspondence qualitatively by visualizing where each model unit was matched onto its corresponding voxel on the cortical sheet (Fig. 2a), and quantitatively by computing how many units are mapped into each stream (Methods: Evaluating spatial correspondence; Fig. 2b). To assess the level of functional correspondence in an unbiased way, we evaluate the functional similarity (correlation) between the responses of each model unit and its paired brain voxel

on an independent set of 515 left-out NSD images seen by all eight participants (between 5-9% of the total images viewed, depending on the participant, Fig. 2c).

To assess the maximal performance that models can achieve under this framework, we estimate the noise ceiling of the brain data, hypothesizing that the best model for the human brain is another human brain [43]. We determine the noise ceiling by applying the same 1-to-1 mapping algorithm, using 80% of the 515 shared images for matching, and evaluating the spatial and functional correspondence between participants' brains across voxels in each stream using the remaining 20% of images (brain-to-brain noise ceiling; horizontal gray bars throughout). Results show that the vast majority of voxels in each stream in one participant are mapped to the correct, corresponding stream in other participants (Supplemental Fig. S3), which also serves to validate our novel mapping algorithm. We then compare the spatial and functional correspondence between candidate models and the NSD across subjects, hemispheres, and model seeds. In total, we evaluate 1216 model-to-brain mappings.

Given the approach we have described for evaluating brain-model correspondence, a model would strongly match the brain if (i) its units are mapped to the correct stream and (ii) the responses of units to NSD images are highly correlated with voxel responses, approaching the noise ceiling. Re (i), the multiple behavioral demands hypothesis predicts that units trained on detection will be best matched to voxels of the Dorsal stream, those trained on action recognition will be matched to the Lateral stream, and those on categorization will be matched to the Ventral stream (Fig. 1d). In contrast, the spatial constraints hypothesis predicts that units clustered on the simulated cortical sheet of the TDANN will be mapped to distinct streams (Fig. 1d).

The multiple behaviors models fail to capture the functional organization of visual cortex into streams, while the spatial constraints models provide a better match

We first test which models predict the spatial segregation into streams. To qualitatively assess the spatial correspondence, we visualize the topography of unit-to-voxel assignments on the cortical sheet of each participant (Fig. 2a and Fig. S4). Unit-to-voxel assignments for the multiple behaviors ResNet-50 models are noisy, with no clustering by stream (Fig. 2a). The spatial correspondence is not different from 33% chance level for the Dorsal and Ventral streams ($ps > .2$), and is significantly lower than chance for the Lateral stream ($t(7) = -4.9, p = 0.002$). That is, only a third of voxels for the detection and categorization trained models were mapped to the Dorsal and Ventral streams, respectively, and less than a third of units from the action-recognition trained model were mapped the Lateral stream (Fig. 2b). In contrast, the multiple behaviors models based on the shallower ResNet-18 architecture provide a significantly better spatial correspondence across all three streams (Supplemental Table 1). Qualitatively, we also observe some clustering of training task by stream. E.g., there is an increase in action-trained units of the ResNet-18 model mapped to the Lateral stream compared to the ResNet-50 model (Fig. 2a). Despite these improvements, the correspondence of the multiple behaviors models remains lacking. Spatially, across all three streams only about 50% of the task-trained units are assigned to their corresponding stream (Fig. 2b).

In contrast to the multiple behaviors models, the self-supervised spatial constraints model captures stream topography. Three distinct clusters of units map to the three different streams, qualitatively more smoothly on the cortical sheet than for the multiple behaviors models (Fig. 2a). Quantitatively, the self-supervised spatial constraints model achieves significantly higher spatial correspondence than the multiple behaviors models across all three streams (all $ps \leq .012$, Supplemental Table 1, Fig. 2b), with the majority of units mapped to the corresponding stream. For the Ventral stream, the spatial correspondence even approaches the noise ceiling (Fig. 2b-gray bars). The spatial correspondence of the supervised, categorization-trained spatial constraints model is similar to that of the self-supervised spatial constraints model for the three streams, and also significantly outperforms the multiple behaviors ResNet-18 models in Dorsal ($p = 6.1\mathrm{x}10^{-8}$) and Ventral ($p = 1.8\mathrm{x}10^{-21}$).

While our results so far suggest that the spatial constraints model, the TDANN trained with self-supervision, captures the stream structure better than the multiple behaviors models, it is possible that the multiple behaviors models still provide a better functional match to the brain than the self-supervised TDANN. To quantify the functional correspondence, we compared the functional similarity of responses on a set of 515 left out images between the corresponding units and voxels of each stream.

Functionally, unit-voxel correspondences for the multiple behaviors models are poor and significantly lower than the noise ceiling (all $ps \leq 1.2\mathrm{x}10^{-5}$, Fig. 2c). For all streams and tasks, functional similarity is below $r = 0.13$ for the ResNet-50 models and at or below $r = 0.15$ for ResNet-18 models. Surprisingly, there is no dissociation of stream by visual behavior. In fact, for both the ResNet-18 and ResNet-50 multiple behaviors models, units trained on object categorization yield the highest functional correlations to brain responses not just for the Ventral stream as predicted by the multiple behavioral demands hypothesis, but also for the Dorsal and Lateral streams. Nonetheless, the ResNet-18 multiple behaviors models generate significantly better functional correspondence in Dorsal and Lateral

streams than the ResNet-50 models (all $ps \leq .018$, Supplemental Tables 1 and 2), consistent with recent work suggesting an emerging decoupling between task performance and match to the brain [44].

a) Model to brain topography

b) Model to brain spatial correspondence

c) Model to brain functional correspondence

Figure 2. The spatial constraints model better matches the spatial and functional organization of the human visual system into streams (a) Unit-to-voxel mapping on an example participant's flattened cortical surface. Top: multiple behaviors (MB) models, each voxel is colored based on the training task for its assigned unit. Bottom: spatial constraints (SC) model, voxels are colored by location on the simulated cortical sheet of the last convolutional layer; polar angle (red -> green -> blue) and eccentricity (opacity, which decreases away from center). **(b)** Quantification of spatial correspondence. For multiple behaviors models, we show the percentage of voxels for each stream that are assigned to the model trained on their hypothesized task. For spatial constraints models, we show the percentage of voxels for each stream that are assigned to the corresponding third of the simulated cortical sheet (max correspondence, up to rotation and reflection). Each symbol represents a model-to-subject mapping. **(c)** Quantification of functional correspondence. Unit-to-voxel correlations on the test set (left-out 515 images). Each participant's data reflects the average correlation across all voxels for the corresponding stream. For (b) and (c) colored bars: mean across participants and hemispheres; horizontal gray bars: mean noise ceiling across participants and hemispheres ± SD. Lighter colors represent controls. Supervised (Categorization) and self-supervised (SimCLR) spatial constraints models shown for an optimal weighting of the spatial loss ($\alpha = 2.5$ for supervised, $\alpha = 0.25$ for self-supervised). *Acronyms*: lh: left hemisphere; rh: right hemisphere. RN: ResNet; Det: detection; Act: action; Cat: categorization.

In contrast, the functional correspondence of model units from the self-supervised spatial constraints model to cortex is significantly higher than the multiple behaviors models for all streams (Fig. 2c, Supplemental Table 2). Functional correspondence is almost double that of the best multiple behaviors ResNet-18 models across streams (improvement, Dorsal: mean 91% increase, Lateral: 65%, Ventral: 133%). Notably, the functional correspondence approaches the brain-to-brain noise ceiling (Fig. 2c-gray bars) in both the Dorsal and Ventral streams. The categorization-trained spatial constraints model also achieves significantly better functional correspondence across all three streams than the corresponding ResNet-18 trained on categorization (all $ps \leq .044$, Supplemental Tables 1 and 2). This difference between the object categorization spatial constraints model and the standard object categorization model is particularly striking for the Ventral stream, suggesting that not only does the spatial constraint in the TDANN change the layout of units, but it also changes their response properties to be more "brain-like". Notably, across models tested, the self-supervised spatial constraints model still provides the best functional and spatial match to the brain (Supplemental Tables 1 and 2).

Our analyses so far reveal that the multiple behaviors models do not explain the organization of cortex into streams. We find that neither highly performant models based on ResNet-50 [33, 32, 31], nor models based on ResNet-18 matching the TDANN backbone architecture [45, 27, 34], recapitulate stream functional organization (Fig. 2). In contrast, the success of the spatial constraints model in matching both functional and spatial brain organization, above and beyond the multiple behaviors models, suggests a new explanation of why the brain is organized into visual processing streams.

Two key factors for stream organization: self-supervision and a balanced spatial constraint

We next ask what factors contribute to the emergence of streams in the spatial constraints models. The spatial constraints model has two key components that may affect its performance: the training task and the relative strength of the spatial constraint. Thus, we test spatial constraints models (5 seeds each), trained with either contrastive self-supervision (SimCLR) or supervised categorization, across a range of spatial weightings (α) from $\alpha = 0$, where the model is essentially a standard ResNet-18 minimizing only the task loss, to $\alpha = 25$, at which point the effect of task is dwarfed by the spatial constraint during training. This allows us to evaluate whether there is a broad or narrow range of parameters that gives rise to the stream organization and if similar or different parameters produce spatial and functional correspondences between models and the brain.

We first visualized the spatial topography of spatial constraints model units mapped to their corresponding voxels on the cortical sheet as a function of training task and spatial weight (Fig. 3a). Spatial constraints models trained with no spatial weight ($\alpha = 0.0$) generate unit-to-voxel mappings which have no spatial structure for both self-supervised and supervised training tasks. I.e., when there is no spatial constraint during training, no functional topography develops in the spatial constraints model's simulated cortical sheet (Fig. 3a, Supplemental Fig. S5 and S6) and consequently the spatial correspondence is noisy and poor. This suggests that the retinotopic initialization of units on the simulated cortical sheet is insufficient for the emergence of stream structure.

For spatial constraints models trained with the self-supervised contrastive task, the clearest stream structure is evident when trained with an intermediate spatial weight of $\alpha = 0.25$, with each contiguous third of the simulated cortical sheet largely mapping to a distinct stream (Fig. 3a-top); this structure is also visible using a continuous spatial gradient (Supplemental Fig. S5, see Supplemental Fig. S6 for corresponding visualizations on the model simulated cortical sheet). But when the spatial weight is increased to $\alpha = 2.5$ the stream structure is diminished. In contrast, for spatial constraints models trained on a supervised categorization task, training with a stronger spatial weight ($\alpha = 2.5$) is required for the stream structure to emerge (Fig. 3a-bottom).

As the spatial constraints models contain simulated cortical sheets, we can estimate more stringently the spatial correspondence between models and the brain by quantifying the similarity between the spatial topography of units on the simulated cortical sheet and that of voxels across the cortical sheet using a distance similarity metric, which measures the correlation between units' distances on the simulated cortical sheet and distances of their corresponding voxels on the cortical sheet (see Methods: Evaluating spatial correspondence). Distance similarity is high if nearby units on the simulated cortical sheet are mapped to nearby voxels on the cortical surface. Across all three streams, self-supervised spatial constraints models (purple) provide a better spatial match than supervised (gold) spatial constraints models (Fig. 3b-top), with large and significant gaps (Supplemental Tables 3 to 5). Additionally, spatial correspondence varies significantly with the level of the spatial constraint and there is a significant interaction between the spatial constraint and training task (Supplemental Tables 3 to 5). Self-supervised spatial constraints models achieve peak spatial correspondence at $0.25 \leq \alpha \leq 0.5$ (Fig. 3b-top) across all streams. In contrast, the categorization trained spatial constraints model produces peak spatial correspondence for the Ventral stream at $\alpha = 2.5$ but for the Dorsal and Lateral streams only at $\alpha = 25.0$.

a) Model to brain topography

b) Model to brain spatial and functional similarity

c) Peak functional similarity at brain-like effective dimensionality

Figure 3. Both self-supervised training and a mid-weight spatial constraint are key to predicting the functional organization into streams. (a) Mapping between spatial constraints models and the brain for an example flattened right hemisphere. Voxels are colored by location on the simulated cortical sheet (see inset). Left: spatial constraints models trained with no spatial weighting ($\alpha = 0$); Middle: spatial constraints models trained with $\alpha = 0.25$, best functional similarity for self-supervised spatial constraints models; Right: spatial constraints models trained with $\alpha = 2.5$, best functional similarity for spatial constraints models trained on categorization. **(b)** Across all three streams, the spatial and functional match to brain is best for self-supervised spatial constraints models trained with $0.25 \leq \alpha \leq 0.5$. Top row: Distance similarity between unit-voxel pairings per stream. Data averaged over unit-voxel pairing for lowest third of distances. Bottom row: average functional similarity (correlation) between unit-voxel pairings per stream. Values are averaged across model seeds and hemispheres; shaded region: SD across participants. Purple: self-supervised spatial constraints model (SimCLR); Gold: supervised spatial constraints model (categorization). Horizontal gray bar: noise ceiling, mean ± SD. **(c)** Spatial constraints models with the most brain-like functional similarity also have the most brain-like effective dimensionality. Horizontal shaded gray bar: brain-to-brain functional similarity, averaged across participants and hemispheres (±SD across target participants). Vertical shaded gray bar: effective dimensionality of brain responses by stream, averaged across participants and hemispheres (±SD across participants). Each circle: one model seed and participant combination, averaged across hemispheres. Circles are colored by training task, and sized by spatial weight (see legend). Arrows, bolded circles: models with the highest functional correspondence (b) for each of the spatial constraints training tasks ($0.25 \leq \alpha \leq 0.5$: self-supervised; $\alpha = 2.5$: categorization).

Quantification of the functional similarity between the spatial constraints models and the brain across training tasks and spatial weights mirrors the spatial correspondence, with significantly better functional correspondence for the self-supervised than the supervised model and a significant task by spatial weight interaction (Fig. 3b-bottom, Supplemental Tables 6 to 8). Across all three streams, spatial constraints models trained with self-supervision and an intermediate spatial weight ($0.25 \leq \alpha \leq 0.5$) generate the best functional match to the brain. The functional match of the best spatial constraints model approaches the noise ceiling in the Dorsal and Ventral streams. In contrast, across all streams spatial constraints models trained on categorization require a larger spatial weight ($\alpha = 2.5$) to functionally match responses, and even for the Ventral stream do not provide a better functional match to the brain

than the self-supervised spatial constraints models. Together these analyses reveal that across all three streams, self-supervised spatial constraints models with a spatial weight $0.25 \leq \alpha \leq 0.5$ provide the best spatial and functional match to the brain. In other words, the spatial constraint and training task that yields the best functional match also yields the best spatial match, and vice versa, suggesting that both task and spatial constraints are needed to generate the functional organization into streams.

What might explain this high functional match between self-supervised spatial constraints models with a balanced spatial weight and the brain? One potential factor lies in the dimensionality of model and brain representations. A characteristic of visual cortex as a computational system is that the dimensionality of its representational space, that is, the effective dimensionality of encoded information, strikes a balance between efficiency and robustness [46, 47]. Information encoding is most efficient when stimulus responses are uncorrelated and high-dimensional, but most robust when correlated and low-dimensional. The eigenspectra of visual cortex neural responses to natural scenes decay according to a power law with exponent $\alpha \approx 1$ [46, 48], meaning that responses are differentiable and robust to small input perturbations, but sufficiently high-dimensional to encode the relevant information. Traditional DANNs, on the other hand, exhibit much higher effective dimensionality than neural responses [48, 49], and this increase in effective dimensionality is linked to decreased robustness to noise and vulnerability to adversarial attacks [49]. While models with high effective dimensionality have been shown to still provide a good basis space for predicting brain responses using linear regression [49], we hypothesize that a model of visual cortex should ideally encode information through similar dimensional geometries as measure by effective dimensionality. Thus, we test whether spatial constraints models that are more functionally similar to the brain are also more similar to the brain in their effective dimensionality. Fig. 3c-gray bars shows the functional similarity (horizontal bar) vs. the effective dimensionality of the human brain (vertical bar) in each stream (mean $\pm$ SD: Dorsal = 13.2 ± 1.3; Lateral = 14.3 ± 3.4; Ventral = 16.7 ± 1.9). We find that self-supervised spatial constraints models (Fig. 3c-purple) have lower effective dimensionality than supervised categorization spatial constraints models (Fig. 3c-gold). Furthermore, spatial constraints models with larger spatial weighting during training exhibit lower effective dimensionality. Comparing the spatial constraints models to the brain data reveals that across all streams the effective dimensionality of the self-supervised spatial constraints models is most similar to the brain at a spatial weight of $0.25 \leq \alpha \leq 0.5$ (Fig. 3c-purple arrows). While the supervised spatial constraints models are similar in effective dimensionality to the human Ventral stream, they exceed the effective dimensionality of the Lateral and Dorsal streams (Fig. 3c-gold arrows). Strikingly, in all streams, the self-supervised spatial constraints models that have the most brain-like effective dimensionality also have the most brain-like functional correspondence.

Observed functional differentiation between streams emerges organically from spatial constraints

Our findings suggest that visual processing streams can emerge in a network that learns via a single, self-supervised task, under a spatial constraint to minimize wiring. Nonetheless, empirical findings reveal that there are functional differences across visual processing streams [3, 12, 19]. A large body of work suggests neurons in the Ventral stream are involved in visual categorization [15, 51, 16] but neurons in the Dorsal stream are involved in spatial tasks such as determining an object's location [3]. Additionally, neurons in different streams have receptive fields that are non-uniformly distributed across the visual field. For example, face-selective regions in the Ventral stream that are involved in face recognition have population receptive fields (pRFs) that are more central than those of face-selective regions in the Lateral stream [52, 53] which support dynamic and social aspects of face processing [54, 55]. Is the emergence of streams from a single training task at odds with functional differentiation across streams? To gain initial insights into this question, we test the extent to which spatial constraints model units assigned to different streams exhibit the above stream-relevant functional properties.

Specifically, we first test whether spatial constraints model units assigned to the Dorsal and Ventral streams contribute to stream-specific hypothesized behaviors such as determining the object's position [50], associated with the Dorsal stream's role in determining where an object is, and determining the object's category (a 1000-way Imagenet categorization task [56, 35]), associated with the Ventral stream role in determining what the object is. While position [50, 52] and category [57, 16, 58, 59] can be decoded from both Dorsal and Ventral streams, we hypothesize that if functional differentiation emerges in spatial constraints models, then units assigned to the Dorsal stream will outperform Ventral units in determining object position and units assigned to the Ventral stream [51, 57], will out-perform Dorsal stream units on object categorization. We find that this is indeed the case: Dorsal units achieve significantly higher performance than Ventral units on predicting object position (mean $\pm$ SD: Ventral = $47.9\% \pm 0.2\%$; Dorsal = $49.7\% \pm 0.3\%$; $t(7) = -16.4$, $p = 7.7 \times 10^{-7}$), Fig. 4a). In contrast, Ventral units achieve significantly higher accuracy than Dorsal units on object categorization (mean $\pm$ SD: Ventral = $43.6\% \pm 0.06\%$; Dorsal = $43.1\% \pm 0.2\%$; $t(7) = 9.48$, $p = 1.1 \times 10^{-14}$, Fig. 4b). This functional differentiation extends to other tasks, spatial weights, and the Lateral stream (Supplemental Fig. S7).

a) Transfer task examples & estimating eccentricity

b) Object position

c) Object category

d) Eccentricity of units

Figure 4. Functional segregation, in alignment with known stream properties, emerges from the spatial constraints model. Data shown is for self-supervised spatial constraints models trained with $0.25 \leq \alpha \leq 0.5$. Each point: a model seed, subject, and hemisphere combination. Triangles: left hemisphere; circles: right. **(a)** Examples of the two transfer tasks: object position prediction (left) and object categorization (middle). Schematic illustrating the principle of eccentricity (right). Red dot = center of the visual field. Yellow circle = receptive field. **(b)** Task transfer performance (R^2) on the object position task (location in pixels of the object's center [50]) for units assigned to either the Dorsal (green) or Ventral (red) stream. **(c)** Task transfer performance (percentage correct) on the 1000-way object categorization task on the Imagenet validation set for units mapped to the Dorsal (green) or Ventral (red) stream; **(d)** Average receptive field eccentricity for face-selective units assigned to the Lateral stream (blue) or Ventral (red) stream.

Secondly, as recent research reported more central pRFs in face-selective regions in the Ventral than the Lateral
stream [52, 53], reflecting differences in the functions these regions are hypothesized to support, we evaluate the
mean eccentricity of receptive fields (overlapping an $8° \times 8°$ stimulus) of face-selective units assigned to the Ventral
and Lateral streams, respectively. Results show a qualitative model-to-brain correspondence (Fig. 4c): Ventral
face-selective units have significantly more central mean eccentricity than Lateral units (mean $\pm$ SD: Ventral =
2.82 ± 0.03; Lateral = 2.94 ± 0.02; $t(15) = -8.2, p = 7.7\text{x}10^{-5}$).

Discussion

We find that a single, biologically plausible, computational principle - self-supervised learning of the statistics of visual inputs under a spatial constraint that encourages nearby units to have correlated responses - explains the functional and spatial organization of the human visual system into processing streams. Intriguingly, even though the model is trained with a single self-supervised task, units associated with different streams develop different functional properties that are useful for different visual behaviors [3, 4, 17, 18, 19]. We find that both a self-supervised task and an intermediate spatial weight are needed for the visual stream structure to emerge and notably, the spatial constraint that produces the best model-to-brain spatial correspondence also produces the best model-to-brain functional correspondence. These data not only suggest that the functional and spatial dimensions of cortex are intertwined but also necessitate a rethinking of an idea inherent in philosophy [60], psychology [61, 62], computational theory [7, 9, 10], and neuroscience [63], that different portions of our visual system have evolved to support distinct visual behaviors. Instead, our results support an intriguing new perspective: evolution may lead to the emergence of a flexible and information efficient [1, 2, 48] visual system that can learn useful task-general representations in an self-supervised manner, while being constrained by the physical size and wiring constraints of cortical tissue.

While the self-supervised spatial constraints model outperforms the multiple behaviors models, there are still gaps between model performance and the cortical noise ceiling. Spatially, the topography of the simulated cortical sheets generated clustering by stream but does not replicate the ordering of streams (Fig. 2). Future directions enhancing models with long-range connections between the Ventral and Dorsal streams (e.g., VOF [64, 65]) and log-polar retinal-to-cortical transforms can examine if other biological factors can fill in the gaps in model-to-brain spatial correspondence. Functionally, the model-to-brain correspondence for the spatial constraints models approaches the noise ceiling for the Ventral and Dorsal stream data, but a gap remains for the Lateral stream. As the Lateral stream is thought to be involved in processing dynamic aspects of visual inputs, future neural datasets including responses to videos may bridge this gap.

This advancement in understanding as to why the visual stream is organized into streams would not have been possible without conceptual, empirical, and methodological innovations, including the TDANN model which is both end-to-end trainable and simulates the topographic arrangement of units on the cortical sheet [27, 34], the development of a 1-to-1 mapping algorithm between model units and brain voxels, and a massive fMRI dataset across the entire visual system [39] that enables comparing DANNs to the human brain. Recent success of DANNs in explaining neural responses in the visual system [15, 25, 26, 38] has elicited excitement that this class of models has the potential to explain why the brain is organized the way it is [66, 63, 67, 10, 68, 69]. At the same time, there is considerable theoretical debate as to how to evaluate if a model accurately explains the brain [43, 40, 67, 70] as commonly used metrics, such as linear regression between model units and brain responses, do not distinguish between models [38, 41, 40] (Supplemental Fig. S8 - this analysis also serves to replicate [15, 36] using the models tested within this study and the NSD). We show that a more stringent criterion - a 1-to-1 mapping between model units and brain voxels - is not only necessary to directly test spatial correspondences between models and the brain, but also is able to distinguish between models of the brain. With this mapping advancement, we provide compelling evidence for a definitive advantage of a more biologically-plausible self-supervised training over the best-to-date supervised training [36, 15, 25, 38] in explaining responses in visual cortex. This more stringent 1-to-1 model-to-brain mapping surprisingly revealed that even under the same type of spatial constraint, self-supervised contrastive training better predicts Ventral stream responses than categorization training, whereas a large body of studies suggested that categorization either best, or equivalently, predicts Ventral stream responses [36, 15, 25, 38]. As we found that the best categorization spatial constraints model requires a stronger spatial weight than the best self-supervised spatial constraints model, we hypothesize that the categorization task imposes a stronger, less flexible learning regime that is at odds with the spatial constraint. These findings, together with computational-theoretical advancements in developing metrics to compare systems that preserve neural tuning [41, 40] not just representational space [15, 9, 71, 38, 10, 72], underscore the necessity of using stricter metrics not only to adjudicate between putative models of the brain, but also to glean new understanding of biological systems.

The success of the spatial constraints model underscores the necessity of modeling brain topography alongside function, as opposed to modeling only brain functional responses as is the prevalent approach [15, 25, 36, 63, 67, 69, 68]. This follows insights from several recent studies that have investigated the emergence of regional topographic maps in the Ventral stream [28, 73, 34, 27] suggesting that wiring [28], smoothness [73], and a balancing of spatial and functional constraints [27] can produce topographic organization. Our findings are also theoretically aligned with work in mice showing that a dual-pathway model trained with a self-supervised predictive loss function outperforms individual task-optimized models in fitting mouse Ventral and Dorsal visual cortex [71]. However, we show that explicitly modeling separate pathways is not necessary to recapitulate the segregation of visual cortex into streams. Instead, the key insight from the present work is that a local spatial constraint that allows fast processing [1] and may

contribute to minimizing local wiring length [74, 8] can percolate up to create broad-scale stream structure. As parallel processing streams exist in other species [75], cortical systems [76, 77, 78, 79], and spatial scales [80, 81], future research can test if the same principles trained on other sensory and multi-modal inputs lead to the emergence of parallel processing streams across the brain. Overall, this study suggests a paradigm shift: end-to-end computational models of the brain that learn from sensory inputs need to include physical constraints, not just behavioral goals, to accurately predict the functional organization of the brain.

References

1. Semir Zeki and Stewart Shipp. The functional logic of cortical connections. *Nature*, 335(6188):311–317, 1988.

2. David C Van Essen, Charles H Anderson, and Daniel J Felleman. Information processing in the primate visual system: an integrated systems perspective. *Science*, 255(5043):419–423, 1992.

3. Leslie G Ungerleider and Mortimer Mishkin. Two cortical visual systems. analysis of visual behavior. *Analysis of Visual Behavior*, pages 549–586, 1982.

4. Melvyn A Goodale and A David Milner. Separate visual pathways for perception and action. *Trends in Neurosciences*, 15(1):20–25, 1992.

5. Brian A Wandell, Serge O Dumoulin, and Alyssa A Brewer. Visual field maps in human cortex. *Neuron*, 56(2):366–383, 2007.

6. Kalanit Grill-Spector and Rafael Malach. The human visual cortex. *Annu. Rev. Neurosci.*, 27(1):649–677, 2004.

7. David Marr. Vision: A computational investigation into the human representation and processing of visual information, 1982.

8. Robert A Jacobs and Michael I Jordan. Computational consequences of a bias toward short connections. *Journal of Cognitive Neuroscience*, 4(4):323–336, 1992.

9. Daniel LK Yamins and James J DiCarlo. Using goal-driven deep learning models to understand sensory cortex. *Nature neuroscience*, 19(3):356–365, 2016.

10. Martin Schrimpf, Jonas Kubilius, Ha Hong, Najib J Majaj, Rishi Rajalingham, Elias B Issa, Kohitij Kar, Pouya Bashivan, Jonathan Prescott-Roy, Franziska Geiger, et al. Brain-score: Which artificial neural network for object recognition is most brain-like? *bioRxiv*, page 407007, 2020.

11. Leslie G Ungerleider and James V Haxby. 'what'and 'where'in the human brain. *Current Opinion in Neurobiology*, 4(2):157–165, 1994.

12. Mortimer Mishkin, Leslie G Ungerleider, and Kathleen A Macko. Object vision and spatial vision: two cortical pathways. *Trends in Neurosciences*, 6:414–417, 1983.

13. Patrick Mineault, Shahab Bakhtiari, Blake Richards, and Christopher Pack. Your head is there to move you around: Goal-driven models of the primate dorsal pathway. *Advances in Neural Information Processing Systems*, 34, 2021.

14. H Steven Scholte, Max M Losch, Kandan Ramakrishnan, Edward HF de Haan, and Sander M Bohte. Visual pathways from the perspective of cost functions and multi-task deep neural networks. *cortex*, 98:249–261, 2018.

15. Daniel LK Yamins, Ha Hong, Charles F Cadieu, Ethan A Solomon, Darren Seibert, and James J DiCarlo. Performance-optimized hierarchical models predict neural responses in higher visual cortex. *Proceedings of the National Academy of Sciences*, 111(23):8619–8624, 2014.

16. Kalanit Grill-Spector and Kevin S Weiner. The functional architecture of the ventral temporal cortex and its role in categorization. *Nature Reviews Neuroscience*, 15(8):536–548, 2014.

17. Kevin S Weiner and Kalanit Grill-Spector. Neural representations of faces and limbs neighbor in human high-level visual cortex: evidence for a new organization principle. *Psychological Research*, 77(1):74–97, 2013.

18. Moritz Wurm and Alfonso Caramazza. Action and object representation in the ventral" what" stream. *PsyArXiv*, 2021.

19. David Pitcher and Leslie G Ungerleider. Evidence for a third visual pathway specialized for social perception. *Trends in Cognitive Sciences*, 2020.

20. Leyla Isik, Kami Koldewyn, David Beeler, and Nancy Kanwisher. Perceiving social interactions in the posterior superior temporal sulcus. *Proceedings of the National Academy of Sciences*, 114(43):E9145–E9152, 2017.

21. Mark E Nelson and James M Bower. Brain maps and parallel computers. *Trends in neurosciences*, 13(10):403–408, 1990.

22. David C van Essen. A tension-based theory of morphogenesis and compact wiring in the central nervous system. *Nature*, 385(6614):313–318, 1997.

23. David H Hubel and Torsten N Wiesel. Receptive fields, binocular interaction and functional architecture in the cat's visual cortex. *The Journal of physiology*, 160(1):106, 1962.

24. Brian A Wandell and Jonathan Winawer. Imaging retinotopic maps in the human brain. *Vision research*, 51(7): 718–737, 2011.

25. Seyed-Mahdi Khaligh-Razavi and Nikolaus Kriegeskorte. Deep supervised, but not unsupervised, models may explain it cortical representation. *PLoS Computational Biology*, 10(11):e1003915, 2014.

26. Umut Güçlü and Marcel AJ van Gerven. Deep neural networks reveal a gradient in the complexity of neural representations across the ventral stream. *Journal of Neuroscience*, 35(27):10005–10014, 2015.

27. Eshed Margalit, Hyodong Lee, Dawn Finzi, James J DiCarlo, Kalanit Grill-Spector, and Daniel LK Yamins. A unifying principle for the functional organization of visual cortex. *bioRxiv*, pages 2023–05, 2023.

28. Nicholas M Blauch, Marlene Behrmann, and David C Plaut. A connectivity-constrained computational account of topographic organization in primate high-level visual cortex. *Proceedings of the National Academy of Sciences*, 119(3):e2112566119, 2022.

29. Talia Konkle and George A Alvarez. A self-supervised domain-general learning framework for human ventral stream representation. *Nature communications*, 13(1):491, 2022.

30. James Munkres. Algorithms for the assignment and transportation problems. *Journal of the Society for Industrial and Applied Mathematics*, 5(1):32–38, 1957.

31. Shaoqing Ren, Kaiming He, Ross Girshick, and Jian Sun. Faster r-cnn: Towards real-time object detection with region proposal networks. *Advances in Neural Information Processing Systems*, 28, 2015.

32. Christoph Feichtenhofer, Haoqi Fan, Jitendra Malik, and Kaiming He. Slowfast networks for video recognition. In *Proceedings of the IEEE/CVF international conference on computer vision*, pages 6202–6211, 2019.

33. Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 770–778, 2016.

34. Hyodong Lee, Eshed Margalit, Kamila M Jozwik, Michael A Cohen, Nancy Kanwisher, Daniel LK Yamins, and James J DiCarlo. Topographic deep artificial neural networks reproduce the hallmarks of the primate inferior temporal cortex face processing network. *bioRxiv*, 2020.

35. Ting Chen, Simon Kornblith, Mohammad Norouzi, and Geoffrey Hinton. A simple framework for contrastive learning of visual representations. 2020. doi: $10.48550/ARXIV.2002.05709$. URL https://arxiv.org/abs/2002.05709.

36. Chengxu Zhuang, Siming Yan, Aran Nayebi, Martin Schrimpf, Michael C Frank, James J DiCarlo, and Daniel LK Yamins. Unsupervised neural network models of the ventral visual stream. *Proceedings of the National Academy of Sciences*, 118(3):e2014196118, 2021.

37. Jonas Kubilius, Martin Schrimpf, Aran Nayebi, Daniel Bear, Daniel LK Yamins, and James J DiCarlo. Cornet: modeling the neural mechanisms of core object recognition. *bioRxiv*, 2018.

38. Colin Conwell, Jacob S Prince, Kendrick N Kay, George A Alvarez, and Talia Konkle. What can 1.8 billion regressions tell us about the pressures shaping high-level visual representation in brains and machines? *BioRxiv*, pages 2022–03, 2022.

39. Emily J Allen, Ghislain St-Yves, Yihan Wu, Jesse L Breedlove, Jacob S Prince, Logan T Dowdle, Matthias Nau, Brad Caron, Franco Pestilli, Ian Charest, et al. A massive 7T fMRI dataset to bridge cognitive neuroscience and artificial intelligence. *Nature Neuroscience*, 25(1):116–126, 2022.

40. Alex H Williams, Erin Kunz, Simon Kornblith, and Scott Linderman. Generalized shape metrics on neural representations. *Advances in Neural Information Processing Systems*, 34:4738–4750, 2021.

41. Meenakshi Khosla and Alex H Williams. Soft matching distance: A metric on neural representations that captures single-neuron tuning. *arXiv preprint arXiv:2311.09466*, 2023.

42. Andrew Saxe, Stephanie Nelli, and Christopher Summerfield. If deep learning is the answer, what is the question? *Nature Reviews Neuroscience*, 22(1):55–67, 2021.

43. Rosa Cao and Daniel Yamins. Explanatory models in neuroscience: Part 2–constraint-based intelligibility. *arXiv preprint arXiv:2104.01489*, 2021.

44. Drew Linsley, Ivan F Rodriguez Rodriguez, Thomas Fel, Michael Arcaro, Saloni Sharma, Margaret Livingstone, and Thomas Serre. Performance-optimized deep neural networks are evolving into worse models of inferotemporal visual cortex. *Advances in Neural Information Processing Systems*, 36, 2024.

45. Wei Liu, Dragomir Anguelov, Dumitru Erhan, Christian Szegedy, Scott Reed, Cheng-Yang Fu, and Alexander C Berg. Ssd: Single shot multibox detector. In *Computer Vision–ECCV 2016: 14th European Conference, Amsterdam, The Netherlands, October 11–14, 2016, Proceedings, Part I 14*, pages 21–37. Springer, 2016.

46. Carsen Stringer, Marius Pachitariu, Nicholas Steinmetz, Matteo Carandini, and Kenneth D Harris. High-dimensional geometry of population responses in visual cortex. *Nature*, 571(7765):361–365, 2019.

47. Larry F Abbott, Kanaka Rajan, and Haim Sompolinsky. Interactions between intrinsic and stimulus-evoked activity in recurrent neural networks. *The dynamic brain: an exploration of neuronal variability and its functional significance*, pages 1–16, 2011.

48. Nathan CL Kong, Eshed Margalit, Justin L Gardner, and Anthony M Norcia. Increasing neural network robustness improves match to macaque v1 eigenspectrum, spatial frequency preference and predictivity. *PLOS Computational Biology*, 18(1):e1009739, 2022.

49. Eric Elmoznino and Michael F Bonner. High-performing neural network models of visual cortex benefit from high latent dimensionality. *bioRxiv*, pages 2022–07, 2022.

50. Ha Hong, Daniel LK Yamins, Najib J Majaj, and James J DiCarlo. Explicit information for category-orthogonal object properties increases along the ventral stream. *Nature neuroscience*, 19(4):613–622, 2016.

51. James V Haxby, M Ida Gobbini, Maura L Furey, Alumit Ishai, Jennifer L Schouten, and Pietro Pietrini. Distributed and overlapping representations of faces and objects in ventral temporal cortex. *Science*, 293 (5539):2425–2430, 2001.

52. Dawn Finzi, Jesse Gomez, Marisa Nordt, Alex A Rezai, Sonia Poltoratski, and Kalanit Grill-Spector. Differential spatial computations in ventral and lateral face-selective regions are scaffolded by structural connections. *Nature communications*, 12(1):2278, 2021.

53. Magdalena W Sliwinska, Caitlin Bearpark, Julia Corkhill, Aimee McPhillips, and David Pitcher. Dissociable pathways for moving and static face perception begin in early visual cortex: Evidence from an acquired prosopagnosic. *Cortex*, 130:327–339, 2020.

54. David Pitcher, Bradley Duchaine, and Vincent Walsh. Combined tms and fmri reveal dissociable cortical pathways for dynamic and static face perception. *Current Biology*, 24(17):2066–2070, 2014.

55. Brad Duchaine and Galit Yovel. A revised neural framework for face processing. *Annual review of vision science*, 1(1):393–416, 2015.

56. Jia Deng, Wei Dong, Richard Socher, Li-Jia Li, Kai Li, and Li Fei-Fei. Imagenet: A large-scale hierarchical image database. In *2009 IEEE Conference on Computer Vision and Pattern Recognition*, pages 248–255, 2009. doi: 10.1109/CVPR.2009.5206848.

57. Maryam Vaziri-Pashkam and Yaoda Xu. Goal-directed visual processing differentially impacts human ventral and dorsal visual representations. *Journal of Neuroscience*, 37(36):8767–8782, 2017.

58. Rory Sayres and Kalanit Grill-Spector. Relating retinotopic and object-selective responses in human lateral occipital cortex. *Journal of neurophysiology*, 100(1):249–267, 2008.

59. Amanda K Robinson, Genevieve L Quek, and Thomas A Carlson. Visual representations: Insights from neural decoding. *Annual Review of Vision Science*, 9(1):313–335, 2023.

60. Jerry A Fodor. *The modularity of mind*. MIT press, 1983.

61. Rainer Goebel. A connectionist approach to high-level cognitive modeling. In *12th Annual Conference. CSS Pod*, pages 852–859. Psychology Press, 2022.

62. Jeffrey S Bowers, Gaurav Malhotra, Marin Dujmović, Milton Montero, Christian Tsvetkov, Guillermo Puebla, Federico G Adolfi, John Hummel, Rachel Flood Heaton, Benjamin Evans, et al. Disagreement and confusion over the status of dnns as models of vision. 2023.

63. Nancy Kanwisher, Meenakshi Khosla, and Katharina Dobs. Using artificial neural networks to ask 'why'questions of minds and brains. *Trends in Neurosciences*, 2023.

64. Jason D Yeatman, Kevin S Weiner, Franco Pestilli, Ariel Rokem, Aviv Mezer, and Brian A Wandell. The vertical occipital fasciculus: a century of controversy resolved by in vivo measurements. *Proceedings of the National Academy of Sciences*, 111(48):E5214–E5223, 2014.

65. Kevin S Weiner, Jason D Yeatman, and Brian A Wandell. The posterior arcuate fasciculus and the vertical occipital fasciculus. *Cortex; a journal devoted to the study of the nervous system and behavior*, 97:274, 2017.

66. Radoslaw M Cichy and Daniel Kaiser. Deep neural networks as scientific models. *Trends in cognitive sciences*, 23(4):305–317, 2019.

67. Adrien Doerig, Rowan P Sommers, Katja Seeliger, Blake Richards, Jenann Ismael, Grace W Lindsay, Konrad P Kording, Talia Konkle, Marcel AJ Van Gerven, Nikolaus Kriegeskorte, et al. The neuroconnectionist research programme. *Nature Reviews Neuroscience*, pages 1–20, 2023.

68. Blake A Richards, Timothy P Lillicrap, Philippe Beaudoin, Yoshua Bengio, Rafal Bogacz, Amelia Christensen, Claudia Clopath, Rui Ponte Costa, Archy de Berker, Surya Ganguli, et al. A deep learning framework for neuroscience. *Nature neuroscience*, 22(11):1761–1770, 2019.

69. Grace W Lindsay. Convolutional neural networks as a model of the visual system: Past, present, and future. *Journal of cognitive neuroscience*, 33(10):2017–2031, 2021.

70. Anna A Ivanova, Martin Schrimpf, Stefano Anzellotti, Noga Zaslavsky, Evelina Fedorenko, and Leyla Isik. Is it that simple? linear mapping models in cognitive neuroscience. *bioRxiv*, page 438248, 2021.

71. Shahab Bakhtiari, Patrick Mineault, Timothy Lillicrap, Christopher Pack, and Blake Richards. The functional specialization of visual cortex emerges from training parallel pathways with self-supervised predictive learning. *Advances in Neural Information Processing Systems*, 34:25164–25178, 2021.

72. Simon Kornblith, Mohammad Norouzi, Honglak Lee, and Geoffrey Hinton. Similarity of neural network representations revisited. In *International conference on machine learning*, pages 3519–3529. PMLR, 2019.

73. Fenil R Doshi and Talia Konkle. Cortical topographic motifs emerge in a self-organized map of object space. *Science Advances*, 9(25):eade8187, 2023.

74. Dmitri B Chklovskii, Thomas Schikorski, and Charles F Stevens. Wiring optimization in cortical circuits. *Neuron*, 34(3):341–347, 2002.

75. David C Van Essen and Jack L Gallant. Neural mechanisms of form and motion processing in the primate visual system. *Neuron*, 13(1):1–10, 1994.

76. Josef P Rauschecker and Biao Tian. Mechanisms and streams for processing of "what" and "where" in auditory cortex. *Proceedings of the National Academy of Sciences*, 97(22):11800–11806, 2000.

77. Takahiro Osada, Akitoshi Ogawa, Akimitsu Suda, Koji Nakajima, Masaki Tanaka, Satoshi Oka, Koji Kamagata, Shigeki Aoki, Yasushi Oshima, Sakae Tanaka, et al. Parallel cognitive processing streams in human prefrontal cortex: Parsing areal-level brain network for response inhibition. *Cell Reports*, 36(12), 2021.

78. Judith Tanné-Gariépy, Eric M Rouiller, and Driss Boussaoud. Parietal inputs to dorsal versus ventral premotor areas in the macaque monkey: evidence for largely segregated visuomotor pathways. *Experimental Brain Research*, 145(1):91–103, 2002.

79. Simone Vossel, Joy J Geng, and Gereon R Fink. Dorsal and ventral attention systems: distinct neural circuits but collaborative roles. *The Neuroscientist*, 20(2):150–159, 2014.

80. BT Thomas Yeo, Fenna M Krienen, Jorge Sepulcre, Mert R Sabuncu, Danial Lashkari, Marisa Hollinshead, Joshua L Roffman, Jordan W Smoller, Lilla Zöllei, Jonathan R Polimeni, et al. The organization of the human cerebral cortex estimated by intrinsic functional connectivity. *Journal of neurophysiology*, 2011.

81. Richard F Betzel and Danielle S Bassett. Multi-scale brain networks. *Neuroimage*, 160:73–83, 2017.

 # Supplementary Information

Materials and methods

Code and data availability

Original code for this study is available at https://github.com/dawnfinzi/spacestream. The neural data analyzed in this study comes from the Natural Scenes Dataset (NSD) [1] available at http://naturalscenesdataset.org/.

Training: Neural network architectures and training tasks

Multiple behaviors models. To test the *multiple behavioral demands hypothesis*, we used three models, each trained on a different task: object categorization, action recognition, and object detection. We chose these tasks as these are the computer vision equivalents of the proposed behaviors each stream is thought to support (Ventral: what is it, Lateral: what is it doing, Dorsal: where is it).

We used two versions of multiple behaviors models: one version with a ResNet-50 base architecture, for optimal task performance, and one version with a ResNet-18 base architecture as a control to more closely match the TDANN architecture, and the number of visual areas in primate cortex [2, 3]. For the object categorization model, we used the base model (ResNet-50 or ResNet-18) [4] trained on object categorization on ILSVRC-2012 (ImageNet Large-Scale Visual Recognition Challenge [5]). For the action recognition model, we used the SlowFast model architecture [6], which is a dual-pathway network with a 3D ResNet backbone trained on the Kinetics-400 video dataset [7]. Finally, for the ResNet-50 object detection model, we used a Faster R-CNN [8] trained on MS-COCO [9]. For the ResNet-18 object detection control model, we used a single-stage object detection network, SSD [10], for greater correspondence with the other multiple behaviors models, and trained on Pascal VOC (2007 and 2012) [11] instead of MS-COCO [9]. While MS-COCO is considered state-of-the-art for object detection and Pascal VOC is an older, smaller dataset, switching to Pascal VOC avoided any potential confound with the images used for the neuroimaging data collection and removed the possibility that the low spatial correspondence for the Resnet-50 based multiple behaviors models was in part due to an artificially inflated match between the object detection model and non-Dorsal voxels with high SNR.

We randomly subsampled an equal number of units from layer 4.1 or its equivalent from each network (ignoring any "visually non-responsive" units that did not respond to any of the images) so that the total number of units was equal to the total number of voxels. In order to allow for the most direct comparison against spatial constraints models, the units sampled from the task-trained models were assigned random positions on a two-dimensional simulated cortical sheet. We then followed the same pre-optimization procedure as in Initialization of model unit position: *Stage 2* in order to be able to fairly apply the same mapping algorithm.

Spatial constraints models. We implemented the *spatial constraints hypothesis* using a Topographic Deep Artificial Neural Network (TDANN) architecture. The TDANN is based on the ResNet-18 model architecture, with two key differences: (1) model units are assigned positions on a 2D simulated cortical sheet and (2) the model is trained to jointly minimize a spatial and a task loss. All TDANN models were built using the ResNet-18 [4] base architecture (from the *torchvision* implementation) and trained using modifications to the VISSL framework [12]. ResNet-18 was chosen because it has been shown to achieve strong task performance, accurately predict neuronal responses across the visual system [13], and has roughly comparable number of layers to stages (areas) in the primate visual system [14, 3]. Models were trained for 200 epochs using the ILSVRC-2012 [5] training set, with each model being trained from five different random initial seeds. We optimized the network parameters using stochastic gradient descent with momentum (with γ set to 0.9), a batch size of 512, and a learning rate initialized to 0.6, which then decayed according to a cosine learning schedule [15] Models were trained using a self-supervised contrastive objective "SimCLR" [16] or a supervised 1000-way object categorization task.

Initialization of model unit position Prior to training, model units in each layer were assigned fixed positions in a two-dimensional simulated cortical sheet specific to that layer. The size of the cortical sheet in each layer, and the size of the "cortical zone" used during training (computation of the spatial loss is restricted to units within the same cortical zone), was determined by the presumed correspondence, based on previous work comparing convolutional neural networks (CNNs) and the primate visual system [17, 18, 19], between model layers and human visual areas (see [2] for further details). Positions were then assigned in a two-stage process.

Stage 1: Retinoptopic initialization As each layer convolves over the outputs of the previous layer, the resulting responses are structured into spatial grids. To maintain this inherent organization, we assigned each model unit to a specific area of the simulated cortical sheet that aligns with its spatial receptive field.

Stage 2: Pre-optimization of positions In CNNs, filter weights are shared between units at different locations,

which means that local updates to one unit affect all units with the same filter weights. This global coordination constraint makes it challenging to achieve local smoothness when the units are arbitrarily positioned. To address this, a pre-optimization of unit positions was necessary to identify a set of positions that enables learning smooth cortical maps. We spatially shuffled the units of a pre-trained model on the cortical sheet, so that nearby units had correlated responses to a set of sine grating images. The use of sine gratings is based on studies that show that propagating retinal waves drive development of the visual system in the womb in primates and other mammals [20, 21, 22, 23]

The spatial shuffling works as follows: 1) Randomly select a cortical zone. 2) Compute pairwise response correlations for all units in the zone 3) Select a random pair of units, and swap their locations in the cortical sheet. 4) If swapping positions decreases local correlations (measured as an increase in the Spatial Loss function described below), undo the swap. 5) Repeat steps 3-4 500 times. 6) Repeat steps 1-5 10,000 times.

Loss functions   We trained the TDANN models using a weighted sum of two types of loss functions: a task loss, which served to encourage learning of visual representations and a spatial loss, which encourages local correlations in responses to visual inputs. Optimization on the total loss function leads to both successful visual representation learning and minimization of inter-layer wiring length [2].

Spatial loss   The spatial loss function encourages nearby model units on the simulated cortical sheet to be correlated in their responses to the training stimuli. Specifically, SL_l is the spatial correlation loss computed for the l-th layer and SL_l is computed on a given batch by randomly sampling a local cortical zone and calculating for pairs of units, (1) correlation (Pearson's r) between the response profiles, ($\overrightarrow{R}$), and (2) the the stabilized reciprocal Euclidean distances ($\overrightarrow{D}$):

$$\overrightarrow{D} = \frac{1}{(1 + \overrightarrow{d}\,)} \tag{S1}$$

where $\overrightarrow{d}$ is the vector of pairwise cortical distances. These two terms are then related as follows:

$$\mathrm{SL}_l = 1 - \mathrm{Corr}\left(\overrightarrow{R}, \overrightarrow{D}\right) \tag{S2}$$

such that SL_l is minimized when nearby units have correlated responses to the training stimuli.

Task loss   The task loss (TL) is computed from the output of the final model layer. We tested two candidate TLs: supervised object categorization cross-entropy loss [24] and the self-supervised SimCLR objective [16]. The SimCLR objective is a contrastive loss function which works by creating two "views", or augmentations, of each image in a batch, using random cropping, horizontal flips, color distortion, and Gaussian blur. These views are passed to the network and the final layer outputs are passed through a 2-layer multi-layer perceptron (MLP), producing a low-dimensional representation of each view which serves as the input to the loss function. The SimCLR loss function then attempts to maximize the similarity of representations for two views of the same source image, while pushing that representation away from all other images in the batch.

Overview of training   In sum, the model is trained on Imagenet [5] to minimize this total loss, which is the sum of the weighted spatial loss for each layer and the task loss as follows:

$$\mathrm{Total\ Loss} = \mathrm{TL} + \alpha \sum_{l \in \mathrm{layers}} \mathrm{SL}_l \tag{S3}$$

where α is the weight of the spatial loss component (fixed across all layers), and SL_l is the spatial correlation loss computed for the l-th layer.

The total model training process consists of 6 steps:

1. The ResNet-18 model is trained using the task loss only.

2. Positions are initialized to preserve coarse retinotopy in each layer (Stage 1).

3. Positions are pre-optimized in an iterative process that preserves retinotopy while bringing together units with correlated responses to sine gratings (Stage 2).

4. After pre-optimization, positions are permanently frozen.

5. All network weights are randomly re-initialized.

6. The network is trained to minimize the total loss.

Testing: Evaluating theories

Neural data. As our neural comparison, we used the Natural Scenes Dataset (NSD) [1], a high-resolution fMRI dataset that densely sampled responses to up to 10,000 natural images in each of eight individuals over the course of 32-40 scan sessions. Full details on data collection and processing can be found in Allen et al. [1]. Briefly, scanning was conducted at 7T using gradient-echo EPI at 1.8-mm isotropic resolution with whole-brain coverage. Images were taken from Microsoft's COCO image database [9], square cropped to 425 pixels x 425 pixels, and presented at fixation at a size of 8.4° x 8.4° for 3 seconds with 1 second gaps in between images. Data were preprocessed using one temporal resampling (to correct for slice timing differences) and one spatial resampling (to correct for head motion, EPI distortions and gradient non-linearities), resulting in upsampled 1.0mm resolution (temporal resolution 1.0 s). Single-trial beta weights were estimated using a general linear model approach designed to optimize the quality of single trial betas (GLMsingle [25]). The single-trial responses from the NSD public data release (beta version b3) were then z-scored across images for each voxel and session and then averaged across 3 trial repeats. We used cortex-based alignment to align all data to the fsaverage surface. Throughout reporting of the results, we refer to the brain units of measurement as "voxels" for interpretability, though they are more technically "vertices" as we are using the fsaverage preparation.

ROIs We defined regions of interest (ROIs) for early, intermediate, and high-level visual cortex for each of the three streams based on a combination of anatomical landmarks, noise ceiling estimates (Supplemental Fig. S1), and a constraint to roughly match the number of voxels per stream. We focus only on the high-level visual ROIs for the purposes of this paper and compare the end point of the models to the end points of the processing stream in each brain. However, the full details for drawing all seven (one early, three intermediate and three higher-level) ROIs are included here for completeness and because the high-level ROIs share boundaries with the intermediate ROIs. ROIs were drawn on the fsaverage surface as follows:

Early visual cortex ROI: The early visual cortex ROI was drawn as the union of the V1v, V1d, V2v, V2d, V3v and V3d ROIs from the Wang retinotopic atlas [26]. Additionally, V2v and V2d, as well as V3v and V3d, were connected such that the part of the occipital pole typically containing foveal representations was included in the ROIs.

Intermediate ROIs: Three intermediate ROIs were drawn corresponding to each of the three streams: Ventral, Lateral and Dorsal. All three ROIs border the early visual cortex ROI on the posterior side. The intermediate Ventral ROI was drawn to reflect the inferior boundary of hV4 from the Wang atlas [26] and includes the inferior occipital gyrus (IOG), with the anterior border of the ROI drawn based on the anterior edge of the inferior occipital sulcus (IOS). The intermediate Lateral ROI was drawn directly superior to the intermediate ventral ROI, with the superior and anterior borders determined as the LO1 and LO2 boundaries from the Wang atlas [26]. The intermediate Dorsal ROI was drawn directly superior to that to include V3A and V3B from the Wang atlas.

Higher-level ROIs: Three higher-level ROIs were drawn for each of the Ventral, Lateral and Dorsal streams, bordering their respective intermediate ROIs on their posterior edges. The ventral ROI was drawn to follow the anterior lingual sulcus (ALS), including the anterior lingual gyrus (ALG) on its inferior border and to follow the inferior lip of the inferior temporal sulcus (ITS) on its superior border. The anterior border was drawn based on the midpoint of the occipital temporal sulcus (OTS). The lateral ROI was drawn such that the higher-level ventral ROI was its inferior border and the superior lip of the superior temporal sulcus (STS) was used to mark the anterior/superior boundary. The rest of the superior boundary traced the edge of angular gyrus, up to the tip of the posterior STS (pSTS). The dorsal ROI was drawn to reflect the boundary of the lateral ROI on its inferior edge and to otherwise trace the borders of and include the union of IPS0, IPS1, IPS2, IPS3, IPS4, IPS5 and SPL1 from the Wang retinotopic atlas.

These ROIs, defined by the authors, correspond to the "streams" ROIs included in the NSD public data release. The three higher-level ROI were then trimmed using the prepared noise ceiling maps for beta version b3 and the fsaverage surface [1]. The noise ceiling estimates represent the amount of variance contributed by the signal expressed as a percentage of the total amount of variance in the data, for the average of responses across three trial presentations. An approximate cutoff of 10% was used to guide trimming of the higher-level ROIs, such that we were left with reduced ROIs where all voxels had a noise ceiling $\geq 10\%$ theoretically predictable variance. These ROIs were contiguous and roughly matched in size (number of voxels per ROI right hemisphere: Dorsal = 6688, Lateral = 6839, Ventral = 5638; left hemisphere: Dorsal = 6182, Lateral = 5849, Ventral = 6126).

Model data. For each of our DANN models, we extracted features in response to the same set of 73,000 total NSD images seen by participants in the scanner. Features were extracted from convolutional layer 4.1 or equivalent. This layer was chosen as past work shows that it has the best functional correspondence to higher-level visual areas, including on the NSD [3, 2, 27]. For the SlowFast network, features were averaged over the temporal dimension. This results in a matrix of features of the form *number of images* x *number of units*, where the number of units is 7 x 7 x 512 = 25,088, i.e. the total number of units in layer 4.1, for the TDANN models, and 19,164 total subsampled

units for the multiple behaviors models (6,388 units per model), which matches the maximum number of voxels per hemisphere. Thus, for all models, the number of source units was of the same order of magnitude as the number of target voxels [28, 29].

1-to-1 mapping between model units and brain voxels. To evaluate the model correspondence to the brain we developed a 1-to-1 mapping algorithm mapping between model units to brain voxels. We reason that units in a neural network model abstract neural computations and thus may be a good model for the aggregated neural response of a voxel (i.e., in the Goldilocks zone of computational abstraction [30]). To test this reasoning and validate the approach we first developed the algorithm between brain-to-brain, for two reasons. First, in the case of brain-to-brain mapping we are mapping voxels in one brain to voxels in a another brain so this tests by definition a mapping between corresponding structures. Second, if the stream organization is not recovered in the 1-to-1 mapping applied between brain-to-brain then we would not be able to test the experimental hypotheses between model and brain.

We found that incorporation of the spatial prior (see below) into the mapping significantly improves accuracy in assignment (Supplemental Fig. S1). Once satisfied with the mapping algorithm in the brain-to-brain case, we used that algorithm with as few modifications as possible (only neighborhood radius and stimuli used, detailed below) to map model-to-brain.

For each pair of subjects (source subject mapped to target subject), we used the single-trial z-scored betas for each source voxel and each target voxel in response to the 515 images shared across all subjects (80% used for assignment, 20% used for evaluation) and computed the correlations between each pair of voxels. This correlation matrix was then transformed into a cost matrix (1 − correlation) and assignment was first attempted purely on the basis of this cost matrix ("functional only") using the Hungarian algorithm [31], a combinatorial optimization algorithm which solves the assignment problem in polynomial time. The "functional only" algorithm performed above chance in assigning voxels to the correct streams but did not fully recover the spatial organization (Supplemental Fig. S1). We thus added a minimal smoothness constraint to the optimization procedure; the smoothness constraint encourages neighboring voxels in the target space to "pick" neighboring voxels in the source space (given a small local radius of 5 mm; full algorithm provided below: Alg. 1). As this recovered more of the known spatial organization in the voxel-to-voxel case (Supplemental Fig. S1), this was the mapping algorithm we chose to then apply in the unit-to-voxel case. To convert the radius of 5 mm used in the voxel-to-voxel case to the model space, we calculated what percentage of the max voxel-to-voxel distance (237 mm) the brain radius cutoff was and then multiplied that percentage by the max model distance (12.9). This yielded a model radius cutoff of approximately 0.27, resulting in the following two radii used in the unit-to-voxel case, 5 mm for the brain distances and 0.27 for the model distances. Additionally, in the unit-to-voxel case, we leveraged the full set of unique images (up to 9485 per individual) to link models to individual brains. The 515 shared images were then reserved for evaluating theories.

Total models tested. We evaluated 5 instances initialized with different random seeds per each of the spatial constraints models across 2 training tasks (SimCLR and categorization) and 7 levels of spatial weightings (α), as well as 2 base architectures (ResNet-18 and ResNet-50) for each of the 3 multiple behaviors models (detection/action/categorization). Each model was then mapped to the 2 hemispheres for each of the 8 participants, totaling 1216 model-to-brain mappings tested.

Evaluating spatial correspondence. We evaluated the spatial correspondence in two ways. First, to compare the multiple behaviors models and the spatial constraints models directly we calculated a percentage spatial correspondence metric. In the case of multiple behaviors models, this is calculated as the percentage of voxels for each stream that were assigned to the multiple behaviors model trained using that stream's corresponding task (i.e. Ventral and object categorization). In the case of spatial constraints models, we divided the TDANN simulated cortical sheet into three sections (candidate stream partition scheme), assuming a log-polar transform, and calculated the highest percentage of voxels that match the partition scheme across candidate partitions (reflection and $5°$ rotations).

Second, when comparing across the spatial constraints models which have simulated cortical sheets, we additionally calculated a distance similarity metric. The distance similarity metric measures for each unit-to-voxel pairing, the normalized distances on the model cortical sheet (from that unit to other units) and normalized distances on the actual cortical surface (for the assigned voxel to the other units' assigned voxels). For each unit, this metric is calculated across only the closest 33% of units, to simulate stream boundaries, which has the additional benefit of discounting high distances where there are few pairs. This results in two vectors, where each element in the vector is the normalized distance between a pair of units (first vector), or between their assigned voxels (second vector), and the correlation between these two vectors is calculated. This calculation is then repeated for all unit-to-voxel pairings and averaged. The same calculation was performed in the brain-to-brain case to determine the actual cortical level of distance similarity. We report the average distance similarity across unit-to-voxel pairings.

Algorithm 1 1-to-1 mapping with spatial prior (Fig. 1c)

Require: Cost matrix C of dimension $N_s \times N_t$, where N_s is the number of source units and N_t is the number of target units, and each entry in C is $1-$ the pairwise correlation of the response vectors. Source distance matrix, D_s, of dimension $N_s \times N_s$, with the pairwise distances between all units in the source space. Target distance matrix, D_t, of dimension $N_t \times N_t$, with the pairwise distances between all units in the target space. Radius r to use as neighborhood size.

    procedure MAPPING ALGORITHM(C, D_s, D_t, r)
        Assignments $A \leftarrow \texttt{Hungarian}(C)$ ▷ Initialized based on "functional only" mapping
        while Mean movement of assignments from iteration to iteration has not converged **do**
            $C_{\text{temp}} \leftarrow C.\texttt{copy()}$
            for each target unit, v_t **do**
                Find all neighboring target units, V_{tn} within distance r
                Initialize candidate matrix, V_{sn}
                for each unit in V_{tn} **do**
                    Find their assigned source unit, v_s, from A
                    $v_{sn} \leftarrow$ all units in source space within distance r from v_s
                    Append v_s and v_{sn} to V_{sn}
                end for
                Fit a 2D Gaussian, G, to point cloud, V_{sn} in source space
                $M_{sn} \leftarrow \texttt{mahalanobis}(V_{sn}, G)$
                for each unit, u, in V_{sn} **do**
                    if $M_{sn}[u] > 2$ **then**
                        Remove u from V_{sn}
                    end if
                end for
                $C_{\text{temp}}[v_t, \neg V_{sn}] = 1000$ ▷ all source units not in V_{sn} are set to have a prohibitive cost
            end for
            $A \leftarrow \texttt{Hungarian}(C_{\text{temp}})$
        end while
        return A
    end procedure

Evaluating functional correspondence. To evaluate functional correspondence between candidate models and the brain, we report the 1-to-1 correlations calculated on the left-out set of 515 shared images, using the unit-to-voxel assignments determined by the mapping procedure. Each unit-to-voxel correlation was normalized by the individual voxel noise ceiling (r) of that assigned voxel (see [1] for information on the calculation of the intra-individual voxel noise ceilings in NSD). 1-to-1 correlations were calculated on an individual subject and hemisphere basis for each of the candidate models. The voxel-to-voxel assignments were used to calculate the overall inter-individual i.e. brain-to-brain noise ceiling (correlations evaluated on test set of 20% of the shared images, averaged across 5 splits for each source and target subject combination).

Linear regression. To compare the 1-to-1 mapping results to the commonly used mapping method of linear regression between model units and the brain [18, 32, 13] (Supplemental Fig. S8), we also calculated model to brain correspondence by regressing model responses from the final convolution layer onto individual voxel responses using ridge regression. As in [13], to decrease computational costs without sacrificing performance, we first projected unit activations into a lower dimensional space using a subsample of the ImageNet validation images and retained the first 1000 PCs. Performance was evaluated on a left-out test set (8/9 train, 1/9 test, shared images excluded, 10 splits) for each subject separately. Test R^2 for each voxel is normalized by the individual voxel noise ceiling (R^2). To evaluate the upper-bound model performance given the shared variance across subjects, we again calculated a brain-to-brain noise ceiling for each stream by repeating the same ridge regression procedure as for model-to-brain but instead using all other subjects' responses to predict the left-out subject (80/20 train-test split using the set of 515 shared images, 10 splits).

Effective dimensionality

To calculate effective dimensionality, i.e. the dimensionality of the space of how information is represented by a system (also referred to as the latent dimensionality), we considered the responses of the subset of units assigned to each stream by subject. Using the unit activations (in the case of the models) or z-scored betas (in the case of

the human subjects), we computed the eigenspectrum of these responses to the MSCOCO images used in NSD. Following [33] and [34], we computed effective dimensionality from the eigenvalues (λ) as:

$$ED = \frac{\left(\sum_{i=1}^{N} \lambda_i\right)^2}{\sum_{i=1}^{N} \lambda_i^2} \tag{S4}$$

where N is the number of eigenvectors. Intuitively, if the eigenspectrum decays slowly, that means there are many informative dimensions, and the ED, which in words is simply the squared sum of the eigenvalues over the sum of squares of the eigenvalues, will be high. On the other hand, if the eigenspectrum decays rapidly, meaning that information is largely encoded in only a few dimensions, then the ED will be low.

Task transfer

We tested performance of self-supervised spatial constraints model units mapped to the Dorsal and Ventral stream on new tasks - position prediction and object categorization, respectively - associated with each stream (results for the Lateral stream and additional tasks in Supplementary Fig. S7). We refer to this as task transfer performance as the model was not trained on any of these tasks and model weights were frozen. Performance on the transfer task was tested for the self-supervised spatial constraints models which best match the brain ($0.25 \leq \alpha \leq 0.5$ in Fig. 4, full results across spatial weightings in Supplementary Fig. S7) and each hemisphere of each subject.

Position task. We evaluated the performance of spatial constraints model units assigned to each stream on predicting the vertical and the horizontal locations in pixels of an object center in an image, using the stimulus set from Hong et al., which has also been used in the evaluation of neural network models of the mouse [36] and primate [32, 37] visual systems. This stimulus set consists of 5760 gray-scale images of 64 distinct objects chosen from one of eight categories (animals, boats, cars, chairs, faces, fruits, planes, tables) placed on randomly chosen, realistic background scene images. Object position, pose and size in this stimulus set varied at different levels from no variation, to medium variation and high variation levels.

For each TDANN model and individual subject, smaller "stream models" were created for each of the three streams by selecting the 5000 units assigned to that stream with the highest correlations. We extracted activations from these units and reduced the dimensionality of the activations to 1000 dimensions using principal components analysis (PCA). We used Ridge regression, with the regularization parameter, α, cross-validated from

$$\alpha \in [0.01, 0.1, 1, 10] \tag{S5}$$

to predict the vertical and the horizontal locations in pixels of the object center in the image. We performed five-fold cross-validation on the training split of the no- and medium-variation image subsets, consisting of 3200 images, and computed performance on the test split of the high-variation set consisting of 1280 images. Ten different category-balanced train-test splits were randomly selected. We report R^2 on the high-variation test set, averaged across the 10 splits.

Categorization task. To evaluate the performance of TDANN units assigned to each stream on a downstream categorization task, we used the 1000-way ImageNet object categorization task [5]. For each model and individual subject, smaller "stream models" were created for each of the three streams as in the position prediction task. A single linear layer was then trained directly from the outputs of those units. The linear layer was trained for 28 epochs of the ILSVRC-12 ImageNet training set (1,281,167 images) with a batch size of 1,024 and a learning rate which was initialized to 0.04 and decreased by a factor of 10 every eight epochs. We report the top-1 performance on the held-out validation set (50,000 images).

Model unit selectivity and receptive field properties

Previous studies reported that voxels in face-selective regions in the Lateral stream are more peripheral than those in face-selective regions of the Ventral stream [38]. To test if this functional feature was also present in the spatial constraints model, we identified face-selective units in each stream and then estimated the eccentricity of their receptive fields. To identify face-selective units in the spatial constraints model, we used the functional localizer (fLoc) stimulus set [39]. fLoc contains stimuli from five categories, each with two subcategories consisting of 144 images each. The categories are faces (adult and child faces), bodies (headless bodies and limbs), written characters (pseudowords and numbers), places (houses and corridors), and objects (string instruments and cars). These stimuli have been previously used to localize and describe category-selective responses in human higher visual

cortex in fMRI studies [39, 38, 40]. Selectivity was assessed by computing the t-statistic over the set of functional localizer stimuli and defining a threshold above which units were considered selective.

$$t = \frac{\mu_{\text{on}} - \mu_{\text{off}}}{\sqrt{\frac{\sigma_{\text{on}}^2}{N_{\text{on}}} + \frac{\sigma_{\text{off}}^2}{N_{\text{off}}}}},$$
(S6)

where μ_{on} and μ_{off} are the mean responses to the "on" categories (adult and child faces) and "off" categories (all non-face categories), respectively, σ^2 are the associated variances of responses to exemplars from those categories, and N is the number of exemplars being averaged over. As in fMRI experiments, units with $t > 3$ were classified as face-selective. For each unit, eccentricity was then calculated based on the unit's (x,y) position from the center of the $7x7$ filter, converted to degrees of visual angle (by multiplying by $8°$ input stimulus / 7 grid size). From there, we divided these units based on which stream they were assigned to and report the mean eccentricity across face-selective units for each model seed x subject x hemisphere combination.

Supplementary tables

Table 1. Linear mixed-effects model to test effect of candidate model type on spatial correspondence for each of the three streams. To test if there were differences between candidate models on spatial correspondence with the brain, we used linear mixed-effects models, with fixed effects for candidate model type (intercept denotes multi-behavior candidate model with ResNet-18 base, i.e. MB ResNet-18) and a random intercept for each subject. Model specification was as follows: spatial correspondence $\sim$ candidate model type + 1 | subject. A separate model was run for each of the three streams. Positive values indicate better spatial correspondence than the MB ResNet-18 (first row) and negative values indicate worse spatial correspondence. For example, the β coefficient of -15.87 for MB ResNet-50 in Dorsal indicates that there is an average decrease of 15.87% in spatial correspondence for the MB ResNet-50 model relative to the MB ResNet-18 model, while the β coefficient of 11.91 for the supervised TDANN indicates an average increase of 11.91%, again relative to the MB ResNet-18 value of 50.2%. Corrected p-values indicate p-values Bonferroni-corrected for multiple comparisons between candidate model types. Significant predictors ($p < .05$) are shown in bold. MB = multiple behavior. SC = spatial constraints. These statistics are related to Fig 2b.

		Coefficients$\pm$SE	z-value	p-value	corrected p-value
Dorsal	**Intercept (MB ResNet-18)**	**50.20$\pm$1.54**	**32.61**	**2.6x10^{-233}**	
	MB ResNet-50	**-15.87$\pm$2.12**	**-7.48**	**7.5x10^{-14}**	**2.2x10^{-13}**
	SC self-supervised	**6.13$\pm$2.12**	**2.89**	**.004**	**.012**
	SC supervised	**11.91$\pm$2.12**	**5.61**	**2.0x10^{-8}**	**6.1x10^{-8}**
Lateral	**Intercept (MB ResNet-18)**	**50.58$\pm$1.43**	**35.28**	**1.3x10^{-272}**	
	MB ResNet-50	**-19.89$\pm$1.65**	**-12.06**	**1.8x10^{-33}**	**5.3x10^{-33}**
	SC self-supervised	**7.71$\pm$1.65**	**4.67**	**3.0x10^{-6}**	**8.9x10^{-6}**
	SC supervised	-2.51$\pm$1.65	-1.52	0.13	0.38
Ventral	**Intercept (MB ResNet-18)**	**48.35$\pm$1.34**	**36.14**	**5.9x10^{-286}**	
	MB ResNet-50	**-13.99$\pm$1.89**	**-7.39**	**1.4x10^{-13}**	**4.3x10^{-13}**
	SC self-supervised	**21.85$\pm$1.89**	**11.55**	**7.5x10^{-31}**	**2.2x10^{-30}**
	SC supervised	**18.22$\pm$1.89**	**9.63**	**6.1x10^{-22}**	**1.8x10^{-21}**

Table 2. Linear mixed-effects model to test effect of candidate model type on functional correspondence for each of the three streams. To test if there were differences between candidate models on functional correspondence with the brain, we used linear mixed-effects models, with fixed effects for candidate model type (intercept denotes multi-behavior candidate model with ResNet-18 base, i.e. MB ResNet-18) and a random intercept for each subject. Model specification was as follows: functional correspondence $\sim$ candidate model type + 1 | subject. A separate model was run for each of the three streams. Positive values indicate better functional correspondence than the MB ResNet-18 (first row) and negative values indicate worse functional correspondence. For example, the β coefficient of -0.01 for MB ResNet-50 in Ventral indicates that there is an average decrease in the correlation with brain responses of 0.01 for the MB ResNet-50 model relative to the MB ResNet-18 model, while the β coefficient of 0.18 for the self-supervised SC model indicates a massive average increase in correlation of 0.18, again relative to the MB ResNet-18's value of 0.14, meaning that the self-supervised SC model had an average correlation across subjects of 0.32 to Ventral brain responses. Corrected p-values indicate p-values Bonferroni-corrected for multiple comparisons between candidate model types. Significant predictors ($p < .05$) are shown in bold. MB = multiple behavior. SC = spatial constraints.. These statistics are related to Fig 2c.

		Coefficients$\pm$SE	z-value	p-value	corrected p-value
Dorsal	**Intercept (MB ResNet-18)**	**0.11$\pm$0.00**	**24.86**	**1.8x10^{-136}**	
	MB ResNet-50	**-0.01$\pm$0.01**	**-2.74**	**.01**	**.018**
	SC self-supervised	**0.10$\pm$0.01**	**21.26**	**2.7x10^{-100}**	**8.2x10^{-100}**
	SC supervised	**0.05$\pm$0.01**	**11.39**	**4.7x10^{-30}**	**1.4x10^{-29}**
Lateral	**Intercept (MB ResNet-18)**	**0.15$\pm$0.01**	**19.82**	**2.1x10^{-87}**	
	MB ResNet-50	**-0.03$\pm$0.01**	**-4.98**	**6.5x10^{-7}**	**1.9x10^{-6}**
	SC self-supervised	**0.09$\pm$0.01**	**15.30**	**7.9x10^{-53}**	**2.4x10^{-52}**
	SC supervised	**0.02$\pm$0.01**	**2.44**	**0.015**	**0.044**
Ventral	**Intercept (MB ResNet-18)**	**0.14$\pm$0.01**	**22.42**	**2.6x10^{-111}**	
	MB ResNet-50	-0.01$\pm$0.01	-2.29	.022	.067
	SC self-supervised	**0.18$\pm$0.01**	**31.74**	**4.0x10^{-221}**	**1.2x10^{-220}**
	SC supervised	**0.11$\pm$0.01**	**19.56**	**3.4x10^{-85}**	**1.0x10^{-84}**

To test for the effects of TDANN spatial weightings ($\alpha \in [0.0, 0.1, 0.25, 0.5, 1.25, 2.5, 25]$) and training task (self-supervised simCLR vs. supervised object categorization) on (1) model-to-brain distance similarity (Fig. 3b-top) and (2) model-to-brain functional similarity (Fig. 3b-bottom), we ran repeated-measures ANOVAs separately for each stream with the factors spatial weighting and training task. Results are reported in Tables 3-11. Num DF indicates numerator degrees of freedom and Den DF indicates denominator degrees of freedom.

Table 3. Distance similarity (r) for Dorsal.

	F	Num DF	Den DF	p-value
Spatial weighting	71.83	6.0	42.0	1.7×10^{-20}
Training task	72.21	1.0	7.0	6.2×10^{-5}
Spatial weighting:Training task	35.24	6.0	42.0	7.2×10^{-15}

Table 4. Distance similarity (r) for Lateral.

	F	Num DF	Den DF	p-value
Spatial weighting	90.60	6.0	42.0	2.0×10^{-22}
Training task	91.54	1.0	7.0	2.9×10^{-5}
Spatial weighting:Training task	45.86	6.0	42.0	7.0×10^{-17}

Table 5. Distance similarity (r) for Ventral.

	F	Num DF	Den DF	p-value
Spatial weighting	152.15	6.0	42.0	7.5×10^{-27}
Training task	258.05	1.0	7.0	8.8×10^{-7}
Spatial weighting:Training task	138.17	6.0	42.0	5.1×10^{-26}

Table 6. Functional similarity (r) for Dorsal.

	F	Num DF	Den DF	p-value
Spatial weighting	210.92	6.0	42.0	1.0×10^{-29}
Training task	520.02	1.0	7.0	7.9×10^{-8}
Spatial weighting:Training task	370.10	6.0	42.0	1.1×10^{-34}

Table 7. Functional similarity (r) for Lateral.

	F	Num DF	Den DF	p-value
Spatial weighting	189.58	6.0	42.0	9.0×10^{-29}
Training task	548.94	1.0	7.0	6.6×10^{-8}
Spatial weighting:Training task	523.86	6.0	42.0	8.2×10^{-38}

Table 8. Functional similarity (r) for Ventral.

	F	Num DF	Den DF	p-value
Spatial weighting	487.47	6.0	42.0	3.6×10^{-37}
Training task	890.56	1.0	7.0	1.2×10^{-8}
Spatial weighting:Training task	694.57	6.0	42.0	2.4×10^{-40}

Supplementary figures

Figure S1. Voxel-wise noise ceiling estimates and ROI boundaries. Noise ceiling estimates (% explainable variance) across all image repeats per subject and then averaged across subjects, visualized on the fsaverage surface. Values are thresholded at 10% explainable variance, the cutoff used to guide drawing of the higher-level ROI boundaries. Figure illustrates that, (1) by design, much of the reliable signal is included in the ROIs drawn, and (2) the noise ceiling is high (minimum 10% explainable variance and numerous voxels above 50% explainable variance) across Ventral, Lateral, and Dorsal. Dashed black line: region shown in main text figures.

Figure S2. Representations differ across streams in NSD. (a) Multidimensional scaling of representation structure. For each individual and ROI, we computed the similarity (Pearson's *r*) between distributed responses across the ROI to all pairs of shared images, resulting in a representational similarity matrix (RSM) from which we extract the flattened lower triangle as a representation vector. Representation vectors were correlated across all subject and ROI combinations (corrected by the trial-to-trial reliability) to generate a 2nd-order RSM, which characterizes the similarity of representations across subjects and ROIs. To visualize the structure, we computed a multidimensional scaling (MDS) of this matrix. We find a rough hierarchical progression from early visual cortex (EVC) ROIs in the top-right (gray), to mid-level ROIs (light colors, middle), to high-level ROIs in the lower-left. Additionally, there is a large-scale separation by stream for high-level ROIs, rather than subject or hemisphere, with lateral high-level ROIs (blue) separated and more superior from a tight ventral cluster (magenta), which is in turn, largely distinct from the dorsal ROIs (green, though these show greater between subject variability). (b) Comparison of ROIs as models of each other, using representational similarity analysis (RSA) and linear regression (Ridge regression). Pearson's *r* and R^2 values are normalized by the respective noise ceilings (NC). Each dot represents a subject. White: within-ROI (i.e. subject-to-subject noise ceiling); Gray and Black bars: ROI X's prediction of ROI Y's responses. (c) To further test whether each stream showed a distinct representational structure, we parcellated cortex into 1000 equally spaced ROIs and then calculated the correlation between each pair of parcels. Each comparison was grouped based on whether both parcels were located within the same stream (black) or whether they were located in two different streams (white), revealing significantly higher correlations within than across streams for this three-stream organization (main effect of within vs. across: *p*=4.19x10^{-7}). The difference in parcel correlations within vs. across streams did not simply reflect anatomical proximity, as the neighboring lateral and dorsal streams showed the greatest differentiation.

Figure S3. Validating the 1-to-1 mapping algorithm by testing how well it maps one brain onto another brain. (a) Right hemisphere voxels in Target (Subj. 2) brain colored by their assignment to streams in Source (Subj. 1) right hemisphere voxels using the algorithm [31] that matches each unit to a voxel solely based on functional similarity. Essentially, all spatial information was removed and voxels in the Target brain were assigned to voxels from the Source brain purely on the basis of how correlated they were in their responses to the shared stimuli across subjects. We refer to this mapping as functional only. (b) Right hemisphere voxels in Target (Subj. 2) brain colored by their assignment to Source (Subj. 1) right hemisphere voxels using the full algorithm that additionally incorporates a gentle smoothness constraint, which encourages neighboring voxels in the target space to "pick" neighboring voxels in the source space (algorithm used in main text). (c) Spatial correspondence between brains using the functional only or full algorithm. Bars: Comparison of right hemisphere voxel-to-voxel correspondence. Data show substantially higher correspondences when using the full algorithm in both the right (Ventral: $t(7) = 41.3, p = 1.3 \times 10^{-9}$, Lateral: $t(7) = 15.6, p = 1.1 \times 10^{-6}$, Dorsal: $t(7) = 27.0, p = 2.5 \times 10^{-8}$) and left hemisphere (panel f; Ventral: $t(7) = 18.2, p = 3.7 \times 10^{-7}$, Lateral: $t(7) = 18.1, p = 4.0 \times 10^{-7}$, Dorsal: $t(7) = 21.8, p = 1.1 \times 10^{-7}$). Data plotted for high-level ROIs across three streams, averaged across source subjects for each target subject. Color represents stream (pink: Ventral, blue: Lateral, and green: Dorsal). Dotted line: chance level (33%). Error bar: 95% CI, each dot is a subject. Data show that the full algorithm achieves a better brain-to-brain mapping. (d), (e), and (f), same for left hemisphere.

Figure S4. Mapping between candidate multiple behaviors and spatial constraints models and the brain for an example participant's flattened cortical surface. Unit-to-voxel mapping visualized on an example participant's flattened cortical surface. Top: multiple behaviors (MB) models, each voxel is colored based on the training task for its assigned unit. Bottom: spatial constraints (SC) models, voxels are colored by location on the simulated cortical sheet of the last convolutional layer; polar angle (red -> green -> blue) and eccentricity (opacity, which decreases away from center). For each row, the control models are on the right (ResNet-18 base architecture for the multiple behavior models and supervised categorization training for the spatial constraints models). The visualizations on the left are the same as Figure 2a, replotted here to facilitate comparison.

Figure S5. Mapping between spatial constraints models and the brain for an example flattened right hemisphere using a continuous gradient. Voxels are colored by location on the simulated cortical sheet (see inset). This rainbow gradient color scheme is "stream-agnostic" in that it does not presuppose the existence of three streams, yet stream clustering emerges. Left: spatial constraints models trained with no spatial weighting ($\alpha = 0$); Middle: spatial constraints models trained with $\alpha = 0.25$, best functional similarity for self-supervised spatial constraints models; Right: spatial constraints models trained with $\alpha = 2.5$, best functional similarity for spatial constraints models trained on categorization.

Figure S6. Model-to-brain 1-to-1 mapping visualized on the simulated cortical sheet of the last convolutional layer of the spatial constraints models model. TDANN model-to-brain mapping visualized on the simulated cortical sheet, for TDANNs trained using the self-supervised, SimCLR task (a) or the supervised, object categorization task (b). This visualization is the reverse of the visualization in Fig. 2a and Fig. 3a of the main text. Here, each square panel shows model units (each dot is a model unit) on the simulated cortical sheet. Units are colored based on the spatial location of their assigned voxel in an example target brain. Opacity of the units reflects the strength of the model-to-brain correlation between responses to NSD images and units are colored by stream (top) or superior-to-inferior spatial gradient (y-position in flat map, bottom). This second color scheme is "stream-agnostic" in that it does not presuppose the existence of three streams, yet stream clustering emerges at self-supervised $0.25 \leq \alpha \leq 0.5$. Each column displays the model-to-brain mapping for an example subject and model seed for a particular spatial weight.

Figure S7. Adding the spatial loss component to the spatial constraints models during training can improve later transfer performance for some tasks. Transfer performance for units from the self-supervised spatial constraints models across a range of weightings (α) on the spatial loss function for four tasks: object categorization, object position estimation, object pose estimation (y-axis rotation), and object size estimation. For three of the four tasks: position, pose, and size estimation, the addition of a spatial loss term improves performance, with peak performance in the same range of weighting on the spatial loss term that leads to best correspondence with the brain ($0.25 \leq \alpha \leq 1.25$). Units were divided by their assigned stream and then assessed on transfer performance using supervised linear readouts. Results are averaged across model seeds (5), subjects (8) and hemispheres (2) totaling 80 models per point, with the exception of (a) where results represent only one model seed, due to compute constraints. Shaded error bar: ± SE. Larger circles indicate model by stream combinations evaluated main text Figure 4.

Figure S8. Linear (ridge) regression mapping between spatial constraints model units and voxels for each stream. R^2 under a linear regression mapping (ridge regression) between model units and voxels for each stream, as a function of the weighting on the spatial constraint and the functional training objective. R^2 values are normalized by the noise ceiling of each voxel such that 1.0 corresponds to the intrinsic data noise ceiling. While calculating functional correspondence using linear regression, a commonly-used, less strict mapping of model-units-to-brain, estimates a higher functional correspondence, it critically masks the effects of training task and spatial constraint. In fact, the improved functional correspondence to the brain between TDANNs trained with biologically-plausible self-supervised training and models trained on supervised object categorization nearly vanishes when models are evaluated using linear regression. Of note, these analyses also serve to replicate the canonical finding that when evaluated using linear regression, object categorization trained DANNs are highly predictive of Ventral stream neural responses, as the supervised models trained with no spatial weight ($\alpha = 0$) in this analysis are equivalent to off-the-shelf object categorization trained ResNet 18 models. As in previous studies [18, 32], we see noise-corrected variance explained for the Ventral stream around 50% for both the supervised object categorization models and self-supervised models trained using SimCLR (mean $\pm$ SD: categorization = $49\% \pm 4\%$, simCLR = $52\% \pm 4\%$). While exact numbers are not reported in [32], from Fig. 2B average Pearson correlations for IT appear to be around roughly 0.75 for both the ResNet-18 models trained using SimCLR and supervised object categorization. This corresponds to variance explained of 56%, a highly similar magnitude to our reported results here using NSD.

References

1. Emily J Allen, Ghislain St-Yves, Yihan Wu, Jesse L Breedlove, Jacob S Prince, Logan T Dowdle, Matthias Nau, Brad Caron, Franco Pestilli, Ian Charest, et al. A massive 7T fMRI dataset to bridge cognitive neuroscience and artificial intelligence. *Nature Neuroscience*, 25(1):116–126, 2022.

2. Eshed Margalit, Hyodong Lee, Dawn Finzi, James J DiCarlo, Kalanit Grill-Spector, and Daniel LK Yamins. A unifying principle for the functional organization of visual cortex. *bioRxiv*, pages 2023–05, 2023.

3. Jonas Kubilius, Martin Schrimpf, Aran Nayebi, Daniel Bear, Daniel LK Yamins, and James J DiCarlo. Cornet: modeling the neural mechanisms of core object recognition. *bioRxiv*, 2018.

4. Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 770–778, 2016.

5. Jia Deng, Wei Dong, Richard Socher, Li-Jia Li, Kai Li, and Li Fei-Fei. Imagenet: A large-scale hierarchical image database. In *2009 IEEE Conference on Computer Vision and Pattern Recognition*, pages 248–255, 2009. doi: 10.1109/CVPR.2009.5206848.

6. Christoph Feichtenhofer, Haoqi Fan, Jitendra Malik, and Kaiming He. Slowfast networks for video recognition. In *Proceedings of the IEEE/CVF international conference on computer vision*, pages 6202–6211, 2019.

7. Will Kay, Joao Carreira, Karen Simonyan, Brian Zhang, Chloe Hillier, Sudheendra Vijayanarasimhan, Fabio Viola, Tim Green, Trevor Back, Paul Natsev, et al. The kinetics human action video dataset. *arXiv preprint arXiv:1705.06950*, 2017.

8. Shaoqing Ren, Kaiming He, Ross Girshick, and Jian Sun. Faster r-cnn: Towards real-time object detection with region proposal networks. *Advances in Neural Information Processing Systems*, 28, 2015.

9. Tsung-Yi Lin, Michael Maire, Serge Belongie, James Hays, Pietro Perona, Deva Ramanan, Piotr Dollár, and C Lawrence Zitnick. Microsoft COCO: Common objects in context. In *European conference on computer vision*, pages 740–755. Springer, 2014.

10. Wei Liu, Dragomir Anguelov, Dumitru Erhan, Christian Szegedy, Scott Reed, Cheng-Yang Fu, and Alexander C Berg. Ssd: Single shot multibox detector. In *Computer Vision–ECCV 2016: 14th European Conference, Amsterdam, The Netherlands, October 11–14, 2016, Proceedings, Part I 14*, pages 21–37. Springer, 2016.

11. M. Everingham, L. Van Gool, C. K. I. Williams, J. Winn, and A. Zisserman. The PASCAL Visual Object Classes Challenge 2012 (VOC2012) Results, 2012.

12. Priya Goyal, Quentin Duval, Jeremy Reizenstein, Matthew Leavitt, Min Xu, Benjamin Lefaudeux, Mannat Singh, Vinicius Reis, Mathilde Caron, Piotr Bojanowski, et al. Vissl, 2021.

13. Martin Schrimpf, Jonas Kubilius, Ha Hong, Najib J Majaj, Rishi Rajalingham, Elias B Issa, Kohitij Kar, Pouya Bashivan, Jonathan Prescott-Roy, Franziska Geiger, et al. Brain-score: Which artificial neural network for object recognition is most brain-like? *bioRxiv*, page 407007, 2020.

14. Daniel J Felleman and David C Van Essen. Distributed hierarchical processing in the primate cerebral cortex. *Cerebral Cortex*, 1(1):1–47, 1991.

15. Ilya Loshchilov and Frank Hutter. Sgdr: Stochastic gradient descent with warm restarts. *arXiv preprint arXiv:1608.03983*, 2016.

16. Ting Chen, Simon Kornblith, Mohammad Norouzi, and Geoffrey Hinton. A simple framework for contrastive learning of visual representations. 2020. doi: 10.48550/ARXIV.2002.05709. URL https://arxiv.org/abs/2002.05709.

17. Seyed-Mahdi Khaligh-Razavi and Nikolaus Kriegeskorte. Deep supervised, but not unsupervised, models may explain it cortical representation. *PLoS Computational Biology*, 10(11):e1003915, 2014.

18. Daniel LK Yamins, Ha Hong, Charles F Cadieu, Ethan A Solomon, Darren Seibert, and James J DiCarlo. Performance-optimized hierarchical models predict neural responses in higher visual cortex. *Proceedings of the National Academy of Sciences*, 111(23):8619–8624, 2014.

19. Jonas Kubilius, Martin Schrimpf, Kohitij Kar, Rishi Rajalingham, Ha Hong, Najib Majaj, Elias Issa, Pouya Bashivan, Jonathan Prescott-Roy, Kailyn Schmidt, et al. Brain-like object recognition with high-performing shallow recurrent anns. *Advances in Neural Information Processing Systems*, 32, 2019.

20. Markus Meister, Rachel OL Wong, Denis A Baylor, and Carla J Shatz. Synchronous bursts of action potentials in ganglion cells of the developing mammalian retina. *Science*, 252(5008):939–943, 1991.

21. Jinwoo Kim, Min Song, Jaeson Jang, and Se-Bum Paik. Spontaneous retinal waves can generate long-range horizontal connectivity in visual cortex. *Journal of Neuroscience*, 40(34):6584–6599, 2020.

22. Todd McLaughlin, Christine L Torborg, Marla B Feller, and Dennis DM O'Leary. Retinotopic map refinement requires spontaneous retinal waves during a brief critical period of development. *Neuron*, 40(6):1147–1160, 2003.

23. Xinxin Ge, Kathy Zhang, Alexandra Gribizis, Ali S Hamodi, Aude Martinez Sabino, and Michael C Crair. Retinal waves prime visual motion detection by simulating future optic flow. *Science*, 373(6553):eabd0830, 2021.

24. Alex Krizhevsky, Ilya Sutskever, and Geoffrey E Hinton. Imagenet classification with deep convolutional neural networks. In *Advances in Neural Information Processing Systems*, pages 1097–1105, 2012.

25. Jacob S Prince, Ian Charest, Jan W Kurzawski, John A Pyles, Michael J Tarr, and Kendrick N Kay. Improving the accuracy of single-trial fmri response estimates using glmsingle. *Elife*, 11:e77599, 2022.

26. Liang Wang, Ryan EB Mruczek, Michael J Arcaro, and Sabine Kastner. Probabilistic maps of visual topography in human cortex. *Cerebral Cortex*, 25(10):3911–3931, 2015.

27. Dawn Finzi, Daniel LK Yamins, Kendrick Kay, and Kalanit Grill-Spector. Do deep convolutional neural networks accurately model representations beyond the ventral stream? In *2022 Conference on Cognitive Computational Neuroscience*, 2022.

28. Alex H Williams, Erin Kunz, Simon Kornblith, and Scott Linderman. Generalized shape metrics on neural representations. *Advances in Neural Information Processing Systems*, 34:4738–4750, 2021.

29. Meenakshi Khosla and Alex H Williams. Soft matching distance: A metric on neural representations that captures single-neuron tuning. *arXiv preprint arXiv:2311.09466*, 2023.

30. Adrien Doerig, Rowan P Sommers, Katja Seeliger, Blake Richards, Jenann Ismael, Grace W Lindsay, Konrad P Kording, Talia Konkle, Marcel AJ Van Gerven, Nikolaus Kriegeskorte, et al. The neuroconnectionist research programme. *Nature Reviews Neuroscience*, pages 1–20, 2023.

31. James Munkres. Algorithms for the assignment and transportation problems. *Journal of the Society for Industrial and Applied Mathematics*, 5(1):32–38, 1957.

32. Chengxu Zhuang, Siming Yan, Aran Nayebi, Martin Schrimpf, Michael C Frank, James J DiCarlo, and Daniel LK Yamins. Unsupervised neural network models of the ventral visual stream. *Proceedings of the National Academy of Sciences*, 118(3):e2014196118, 2021.

33. Marco Del Giudice. Effective dimensionality: A tutorial. *Multivariate behavioral research*, 56(3):527–542, 2021.

34. Eric Elmoznino and Michael F Bonner. High-performing neural network models of visual cortex benefit from high latent dimensionality. *bioRxiv*, pages 2022–07, 2022.

35. Ha Hong, Daniel LK Yamins, Najib J Majaj, and James J DiCarlo. Explicit information for category-orthogonal object properties increases along the ventral stream. *Nature neuroscience*, 19(4):613–622, 2016.

36. Aran Nayebi, NC Kong, C Zhuang, JL Gardner, AM Norcia, and DL Yamins. Mouse visual cortex as a limited resource system that self-learns an ecologically-general representation. *BioRxiv*, pages 1–37, 2022.

37. Rishi Rajalingham, Elias B Issa, Pouya Bashivan, Kohitij Kar, Kailyn Schmidt, and James J DiCarlo. Large-scale, high-resolution comparison of the core visual object recognition behavior of humans, monkeys, and state-of-the-art deep artificial neural networks. *Journal of Neuroscience*, 38(33):7255–7269, 2018.

38. Dawn Finzi, Jesse Gomez, Marisa Nordt, Alex A Rezai, Sonia Poltoratski, and Kalanit Grill-Spector. Differential spatial computations in ventral and lateral face-selective regions are scaffolded by structural connections. *Nature communications*, 12(1):2278, 2021.

39. Anthony Stigliani, Kevin S Weiner, and Kalanit Grill-Spector. Temporal processing capacity in high-level visual cortex is domain specific. *Journal of Neuroscience*, 35(36):12412–12424, 2015.

40. Marisa Nordt, Jesse Gomez, Vaidehi S Natu, Alex A Rezai, Dawn Finzi, Holly Kular, and Kalanit Grill-Spector. Cortical recycling in high-level visual cortex during childhood development. *Nature human behaviour*, 5(12): 1686–1697, 2021.