Estimating Genome-wide Phylogenies Using Probabilistic Topic Modeling

Marzieh Khodaei[1,*], Scott V. Edwards[2], and Peter Beerli,[1]

[1] Department of Scientific Computing, Florida State University, Tallahassee, FL 32306, USA

[2] Department of Organismic and Evolutionary Biology and Museum of Comparative Zoology, Harvard, 26 Oxford Street, Cambridge, MA 02138, USA

*Corresponding author: Marzieh Khodaei, email: mk16e@fsu.edu

Abstract

Methods for rapidly inferring the evolutionary history of species or populations with

genome-wide data are progressing, but computational constraints still limit our abilities in

this area. We developed an alignment-free method to infer genome-wide phylogenies and

implemented it in the Python package TopicContml. The method uses probabilistic

topic modeling (specifically, Latent Dirichlet Allocation or LDA) to extract 'topic'

frequencies from k-mers, which are derived from multilocus DNA sequences. These

extracted frequencies then serve as an input for the program Contml in the PHYLIP

package, which is used to generate a species tree. We evaluated the performance of

TopicContml on simulated datasets with gaps and three biological datasets: (1) 14 DNA

sequence loci from two Australian bird species distributed across nine populations, (2)

5162 loci from 80 mammal species, and (3) raw, unaligned, non-orthologous PacBio

sequences from 12 bird species. Our empirical results and simulated data suggest that our

method is efficient and statistically robust. We also assessed the uncertainty of the

estimated relationships among clades using a bootstrap procedure.

Introduction

Phylogenetic analysis traditionally relies on the alignment of orthologous sequence data, a process that can be challenging due to the complexity of genomic variations, difficulties in aligning noncoding regions, and the presence of highly divergent sequences. Over the past two decades, alignment-free approaches based on shared properties of sub-sequences of defined length k (k-mers or k-grams) (Marçais and Kingsford 2011; Shedlock et al. 2007; Chapus et al. 2005; Deschavanne et al. 1999) have been developed to compare sequences and genomes. Alignment-free methods for evolutionary analysis have been reviewed (Vinga and Almeida 2003; Zielezinski et al. 2019) and their robustness investigated (Chan et al. 2014; Bernard et al. 2016). For example, they can be used to derive distances to be summarized into phylogenies (Edwards et al. 2002; Chan et al. 2014; Balaban et al. 2022; Van Etten et al. 2023). Several studies have shown that alignment artifacts can significantly impact tree topology (Ogden and Rosenberg 2006; Wong et al. 2008; Du et al. 2019). Alignment becomes problematic with comparisons of large genomes, complex genomic variations, challenges in aligning noncoding regions, difficulties presented by highly divergent sequences, and the time-consuming nature of aligning large datasets. Alignment-free approaches offer a promising alternative to address these weaknesses of alignment-based methods (Ren et al. 2018).

Probabilistic topic modeling (Blei et al. 2003) is a statistical approach aiming to identify major 'themes,' 'connections', or 'topics' among themes in documents and other large collections of text. The approach originated from the field of Natural Language Processing (NLP) and was introduced by statisticians looking for applications of machine learning. Griffiths and Steyvers (2004) applied this method to infer a natural grouping (topics) of documents based on the content from a large number of scientific documents,

called a corpus. Latent Dirichlet Allocation (LDA) is a popular technique in topic modeling introduced by Blei et al. (2003) within the context of unsupervised machine learning; it assumes that the documents consist of latent topics, each represented by the distribution of words. The goal is to uncover these topics by analyzing the words in the documents and essentially 'learning' the structure of the data. LDA has also been a focus of attention within the bioinformatics community and various applications to biological data have been researched and analyzed (Liu et al. 2016). Recently, some applications of alignment-free methods have been presented to solve problems offered by DNA sequences or genomes. For example, in a statistical application, LDA was used by La Rosa et al. (2015) to extract the frequency of fixed-length k-mers (words) of DNA sequences (documents) and thereby discover latent patterns in massive biological data to be used for clustering and classification of DNA sequences. Other studies have adopted LDA clustering for the analysis of single-cell expression or epigenetic data (duVerle et al. 2016; Dey et al. 2017). Here, we present a novel computational approach using probabilistic topic modeling to infer evolutionary relationships among individuals from different populations or species. This method works with multilocus data, including unaligned or aligned DNA sequences and unassembled raw sequencing reads. We will use the term species tree for these trees, whether derived from single individual sequences or individuals grouped into populations or species.

Genome-wide datasets (sequences of whole genomes or multiple genes per species) are becoming increasingly prominent in inferring the evolutionary history of closely related species. Traditional approaches to multilocus phylogenetics, such as concatenation methods (Gatesy and Baker 2005), and approaches that are consistent under the multispecies coalescent (de Queiroz and Gatesy 2007; Liu et al. 2009; Chifman and Kubatko 2014; Zhang et al. 2018; Mirarab et al. 2016), have advanced the field significantly. However, these methods often rely on high-quality alignments, which can be computationally expensive and error-prone when dealing with large or complex datasets.

TopicContml offers a scalable and efficient alternative to traditional approaches, addressing their limitations and enabling the analysis of diverse and complex genomic datasets without relying on sequence alignment.

Here, we outline the architecture of TopicContml and demonstrate its application using simulated data and three empirical datasets: (1) a small orthologous dataset of individuals from various locations of two parapatric bird species, consisting of 14 loci, along with a comparison to SVDquartets (Chifman and Kubatko 2014) and the alignment-free method Mash (Ondov et al. 2016), including a discussion of bootstrap support; (2) an orthologous dataset of mammalian species, consisting of 5,162 loci across 90 vertebrate species; and (3) a 12-species bird dataset with unaligned, non-orthologous PacBio raw sequencing reads.

Materials and Methods

TopicContml Software

TopicContml is a Python package based on a two-phase pipeline: (1) The mulitlocus or genome-wide data is broken down into k-mers; these k-mers are then used to learn a probabilistic topic model and extracts the topic frequencies of these k-mers using the LDA model for each locus (Fig. 1 left). For a data analysis with multiple individuals from the same species or population, we set the option `--merging n` to merge individual labels that start with the same n letters into groups; otherwise we assume each sequence is an individual. (2) These topic frequencies from multiple loci are then used to estimate a phylogeny with Contml (part of PHYLIP; Felsenstein 1981; 2004) (Fig. 1 right).

K-mer decomposition.— In natural language processing (NLP), large text datasets (corpora) are broken down into smaller units such as documents, which are further divided into words or sentences, referred to as tokens. Similarly, in bioinformatics, datasets consisting of multiple genomes or multilocus DNA sequences can be broken down

FIGURE 1. TOPICCONTML workflow to generate topic frequencies and the corresponding phylogeny.

into individual genomes or groups of multilocus sequences associated with an individual. These sequences are then decomposed into k-mers—substrings of length k representing short DNA or amino acid sequences. We decompose the DNA sequences into non-overlapping k-mers, as shown in Fig. 1, since overlapping k-mers require more memory and computation time without yielding significantly better results. The program estimates an optimal k-mer length based on the probability of observing a given k-mer in a document (sequence) at each locus, with options for user adjustments.

The probability of a given k-mer K appearing in a random genome X of size n is $P(K \in X) = 1 - \left(1 - |\Sigma|^{-k}\right)^n$, where $\Sigma = \{A, C, G, T\}$, without loss of generality. Given a document size n and the desired probability q of observing a random k-mer, the value of k that minimizes the probability of observing a random k-mer can be computed as (Fofanov

et al. 2004; Ondov et al. 2016):

$$\hat{k} = \lceil log_{|\Sigma|}(n(1-q)/q) \rceil$$

TopicContml calculates $\hat{k}$ for each document in a locus based on this. We have found

that $k = 20$ and $k = 8$ give accurate estimates in most cases for large (e.g., 1,000,000 bp)

and small sequences, respectively. The program also allows users to choose different k-mer

configurations, such as a combination of k-mer lengths or a single fixed length, based on

their analysis needs.

Resolving ambiguities and missing data.— The current version of TopicContml

retains all IUPAC codes as they are, except for 'N', '?', '-', and other ambiguous

characters, which can be filtered out prior to analysis. We assume that such ambiguity

codes are rare and do not strongly affect the results.

Topic modeling.— Given a collection of D documents and a number of M topics,

topic modeling discovers the M topics from a collection of text data and estimates the

probability of each topic for each document. We use Latent Dirichlet Allocation (LDA) to

extract these frequencies. LDA is a generative probabilistic model used to uncover hidden

topics within a collection of documents, referred to as a corpus. Given a corpus with D

documents, let N be the number of words in a specific document $d \in D$. For each word

$w_{d,n}$ (the n^{th} word in the d^{th} document), $z_{d,n}$ denotes the associated topic. The distribution

of topics for document d, represented by θ_d, is drawn from a Dirichlet distribution,

$\theta_d \sim Dir(\alpha)$, where $\alpha > 0$ is the parameter vector. Similarly, the distribution of words for

each topic m, denoted by β_m, is also drawn from a Dirichlet distribution, $\beta_m \sim Dir(\eta)$,

with parameter vector $\eta > 0$. In this model, the only observed variables are the words w in

the documents, while the topics z, the topic distributions θ for all documents, and the word

distributions β for each topic are all latent variables. The joint distribution is defined as

$$p(w, z, \theta, \beta | \alpha, \eta) = \prod_m p(\beta_m | \eta) \prod_d \left[p(\theta_d | \alpha) \prod_n p(z_{d,n} | \theta_d) p(w_{d,n} | z_{d,n}, \beta) \right]$$

¹²² Using this joint distribution, one can compute the posterior distribution of the

¹²³ unknown model parameters, $p(\theta, z, \beta | w) = \frac{p(\theta, z, \beta, w)}{p(w)}$, using expectation-propagation (EP)

¹²⁴ (Minka and Lafferty 2012) or other maximization methods.

¹²⁵ For each locus, TOPICCONTML first estimates the topic frequencies for every

¹²⁶ document, θ, using the Python package GENSIM (Řehůřek and Sojka 2010) (Fig. 1). The

¹²⁷ sequences (documents) in each locus are decomposed into k-mers (words). During

¹²⁸ preprocessing, LDA filters out certain words, primarily those with low frequency, to

¹²⁹ enhance the quality of the generated topics (see Supplementary Fig. S8). The process

¹³⁰ begins by randomly assigning a distribution of topics to each document and a distribution

¹³¹ of words to each topic, with these distributions being governed by Dirichlet priors. During

¹³² the training phase, GENSIM's implementation of LDA iteratively refines these

¹³³ distributions using maximization methods. This training involves updating two key

¹³⁴ parameters: the distribution of topics within each document and the distribution of words

¹³⁵ within each topic. The model trains by analyzing patterns of word co-occurrence across the

¹³⁶ documents, assigning words to topics in a way that maximizes the likelihood of the

¹³⁷ observed data. As the iterations progress, the model converges to a stable set of topics.

¹³⁸ *Determining the optimal number of topics.—* Selecting the optimal number of

¹³⁹ topics in Latent Dirichlet Allocation (LDA) modeling is important for generating

¹⁴⁰ interpretable results. A widely used method for this involves evaluating topic coherence,

¹⁴¹ which reflects the semantic similarity among top words within each topic—higher

¹⁴² coherence scores generally correlate with more interpretable topics (Röder et al. 2015).

¹⁴³ Several algorithms are available for calculating coherence scores. In this study, we use the

¹⁴⁴ "u_{mass}" coherence measure in GENSIM (Řehůřek and Sojka 2010), analyzing each locus

¹⁴⁵ individually to identify the best topic number for each (see Supplementary Fig. S3).

¹⁴⁶ However, because coherence analysis involves testing multiple models with varying topic

¹⁴⁷ counts, it can be time-intensive, especially with large datasets. To address this,

¹⁴⁸ TOPICCONTML also allows users to specify a fixed number of topics, which, in our case,

proved to be a practical alternative without compromising the interpretability or

consistency of results. Although selecting an optimal topic count can enhance detail in

some studies, our findings show that a fixed topic number performs well and offers

efficiency for large-scale analyses. All our analyzed datasets are based on a fixed value of

five topics.

Visualizing topics and associated terms.— To visualize the topics and associated

terms (*k*-mers), we use the package PYLDAVIS (Sievert and Shirley 2014), an interactive

visualization tool. TOPICCONTML allows users to generate an HTML file containing the

pyLDAvis output for each locus, saving them in a designated folder within the directory

(see Supplementary Fig. S2). This enables detailed examination and extraction of

information from the fitted LDA model, enhancing our ability to interpret the underlying

topic structures

CONTML (Continuous Characters Maximum Likelihood method).— The results of

the LDA analysis are the topic frequencies for each document, which are then evaluated

using CONTML to estimate a phylogeny from frequency data using the restricted maximum

likelihood method (REML) (Felsenstein 1973) based on the Brownian motion model for

allele frequencies (Cavalli-Sforza and Edwards 1967). The primary assumption of CONTML

is that each character (each topic in our case) evolves independently according to a

Brownian motion process and that character state changes since divergence are

independent of each other, which means the net change after t units of time is normally

distributed with zero mean and variance ct (the same constant c for all characters).

Multilocus bootstrapping.— To assess the statistical confidence of the inferred

phylogenies, we use bootstrapping (Efron 1979). Given a multiple sequence alignment, the

bootstrap method involves resampling the original dataset with the replacement of the

aligned sites and creating the phylogeny for each replicate. For unaligned data, we use the

approach used in Edwards et al. (2002), where a random sample of x k-mers is drawn from

all x k-mers collected from the data. The fraction of the time a particular clade appears in

the resulting bootstrap trees presents support values for the clades in the reference tree or

a majority-rule consensus tree (Holder et al. 2008; Efron et al. 1996; Hillis and Bull 1993).

TopicContml implements bootstrapping strategies for both aligned and unaligned

sequences. It generates a majority-rule consensus tree from the bootstrap replicates using

SumTrees in DendroPy (Sukumaran and Holder 2010).

181   *Datasets*

We evaluate the accuracy of TopicContml for simulated data and multiple real

biological data. The simulated data were used to explore the effects of the number of loci

and the accuracy of recovering the true topology from data sets consisting of 7 and 14

species. We used three biological datasets with very different features: (1) a 14-locus

dataset from two parapatric closely related bird species separated into nine populations, to

evaluate the accuracy of estimation, bootstrapping, and to compare accuracy with

SVDquartets (Chifman and Kubatko 2014) and the alignment-free approach Mash

(Ondov et al. 2016); (2) a vertebrate dataset focusing on mammals with 90 species and

5162 loci to evaluate the effect of missing data and of aligned vs. non-aligned orthologous

loci; (3) a dataset of raw PacBio sequences of twelve bird species, each containing 100,000

reads; these sequences were neither orthologous nor aligned and can be construed as having

been sampled randomly and potentially overlapping from their constituent genomes.

Simulated datasets.— We evaluated two sets of simulations: one with moderate

and one with many insertions and deletions. We used the software Dawg (Cartwright

2005) to simulate aligned sequences with indels/deletions on a 7-species and a 14-species

tree (Fig. 2). The moderate scenario inserts indels at a rate of 0.02 per site and deletes

sites with a rate of 0.02 per site. The more extreme simulation used an insertion/deletion

rate of 0.2 per site. An example of two individual sequences for each indel/deletion
scenario is shown in the electronic supplement (Supplementary Fig. S1). We simulated
datasets of 1, 2, 5, 10, 20, 50, 100, 200, 500, and 1000 loci; each locus was between 800 -
2000bp, dependent on indels/deletions. These simulated datasets were then analyzed with
gaps included (aligned), with the gaps excised (unaligned), and with k-mers that include
gaps removed (no gap-kmer). We fixed the number of topics for all simulation analyses to 5
and estimated the best k-mer size from the data; it turned to be 9 for all datasets. Each
scenario was run 10 times. The resulting trees were compared to the true trees using
unweighted and weighted Robinson-Foulds distances.

FIGURE 2. Phylogenies of seven and 14 species used for the simulation of sequence data with deletions and indels
(gaps). In Tables 1 and 2, these are referenced as 7-tip and 14-tip trees.

Empirical datasets.— We evaluated three biological datasets:

Two parapatric closely-related bird species: The data contain multiple
individuals of the Australian brown treecreeper (*Climacteris picumnus*) and black-tailed
treecreeper (*Climacteris melanurus*) (Edwards et al. 2022; 2023). DNA sequences consisted
of 14 loci and nine different geographic locations. For each locus, sequence length varied
from 288 to 418 base pairs, and the number of aligned sequences per locus ranged from 78
to 92. For the evaluations of unaligned data, we removed all gaps in each sequence. We
applied LDA to each locus across all 9 locations and extracted the topic frequencies.

These topic frequencies were used in CONTML to generate the population tree, evaluate bootstrap support, and compare with another approach.

Mammal dataset: The second dataset includes 90 vertebrate species focusing on mammals with 5162 loci (Wu et al. 2018), and were analyzed by Liu et al. (2017) using concatenated maximum likelihood and coalescent approaches. We analyzed this dataset using TOPICCONTML under four conditions: (a) excluding *k*-mers containing gaps ('-') or unspecified nucleotides ('N'), (b) removing alignment columns with gaps before excluding *k*-mers with 'N', (c) removing all gaps from sequences before excluding *k*-mers with 'N', and (d) using aligned sequences while retaining 'N' characters. We then used the Robinson-Foulds distance to compare each phylogram with the maximum-likelihood tree and random trees.

PacBio dataset: A total of 6.5 GB of raw sequencing reads of 12 bird species generated by the PACBIO HIFI sequencing method. The 12 birds cover most of the depth of the avian tree, including the two deepest branches, Paleognathae and Neognathae Species were chosen so as to broadly sample the tree for species belonging to lineages whose higher relationships are fairly stable, but also to include unambiguously close relatives, so that we could test the ability of our method to recover close relatives . We subsampled 100,000 reads from each species; average read length per species varied from 9.3 kb in the tinamou Crypterellus tataupa to 18.8 kb in chicken.

Results

Analysis of Simulated Datasets

The simulations based on the moderate insertion/deletion scheme, shown in Table 1, demonstrate that the recovery of trees close to the true tree improves with the number of loci for all treatments and also for both tree topologies. The 'Aligned' treatment for both tree topologies works well with more than 50 loci. The 'Not aligned' treatment worked better for the 14-species tree than for the 7 species tree, but we used only a small

₂₄₂ number of replicates (n=10). Still, accurate recovery of the true tree was almost as high as

₂₄₃ with the 'Aligned' treatment. The 'No gap-kmer' treatment fairs as well as the 'Not

₂₄₄ aligned' treatment. Weighted Robinson-Foulds distances (wRF) show trends consistent

₂₄₅ with the percentage of trees recovered that either match the true tree or are within two

₂₄₆ distance units of it. Notably, the 'No gap-kmer' treatment is closer to the true tree than

₂₄₇ the 'Not aligned' treatment, which performs comparably to the 'Aligned' treatment.

Table 1. Simulated data with low indel/deletion frequency, accuracy of phylogenetic reconstruction with TopicContml: data was simulated using Dawg (Cartwright 2005), each locus has around 1000 bp with gaps using a low number of gap scenario (parameter: insertion/deletion probability 0.02/site, average indel length 12, topics=5, k-mers were estimated from the data (all estimated k-mers were 9 base pairs); 'Aligned' results are based on simulated data with gaps, 'Not Aligned' had all gaps removed in the simulated data, 'No gap-kmer' had all k-mers containing gaps removed before LDA. 'C' (Close) marks the frequency of topologies that are either the same as the true topology or not more than 2 rearrangments apart; 'wRF' is the average weighted Robinson-Foulds distance from the true tree. Each result is based on 10 simulations.

Loci	7 Species						14 Species					
	Aligned		Not Aligned		No gap-kmer		Aligned		Not Aligned		No gap-kmer	
	C	wRF	C	wRF	C	wRF	C	wRF	C	wRF	C	wRF
1	0.1	1.22	0.3	1.14	0.3	1.23	0.0	1.76	0.0	1.78	0.0	1.81
2	0.4	1.30	0.4	1.23	0.5	1.22	0.0	1.97	0.0	2.14	0.0	1.95
5	0.6	1.19	0.3	1.27	0.5	1.26	0.0	1.93	0.1	2.16	0.2	1.99
10	1.0	1.18	0.6	1.21	0.5	1.19	0.4	2.01	0.1	2.13	0.4	1.93
20	0.7	1.18	0.5	1.16	0.6	1.18	0.6	2.01	0.8	2.18	0.7	1.99
50	0.9	1.15	0.8	1.18	0.8	1.17	0.8	1.99	0.7	2.15	1.0	1.99
100	1.0	1.16	0.7	1.23	0.9	1.17	0.9	1.99	1.0	2.11	0.9	1.99
200	1.0	1.18	0.8	1.22	0.9	1.17	0.9	2.01	1.0	2.12	0.8	1.98
500	1.0	1.17	1.0	1.18	1.0	1.17	1.0	1.97	1.0	2.14	1.0	1.97
1000	1.0	1.17	0.9	1.22	1.0	1.18	1.0	1.96	1.0	2.13	1.0	1.95

₂₄₈ The simulations with extreme insertion/deletion strategy (as shown in Table 2) are

₂₄₉ markedly different for the 'Not Aligned' treatment of the 14 tip trees: even with 1000 loci

₂₅₀ none of the estimated trees were close to the true tree; 'Aligned' and 'No gap-kmer' faired

₂₅₁ similar to the moderate indel/deletion scheme. For the 7-species tree all treatments are

₂₅₂ close to the true tree when the number of loci is large. Overall the wRF values are all

₂₅₃ higher than those for the moderate indel/deletion scenario, and the 'No gap-kmer' delivers

₂₅₄ similar values as the 'Aligned'.

Table 2. Simulated data with high indel/deletion frequency, accuracy of phylogenetic reconstruction with TopicContml: data was simulated using Dawg (Cartwright 2005), each locus has around 1000 bp with gaps using a high number of gap scenario (parameter: insertion/deletion probability 0.2/site, average indel length 12, topics=5; k-mers were estimated from the data (all estimated k-mers were 9 base pairs); 'Aligned' results are based on simulated data with gaps, 'Not Aligned' had all gaps removed in the simulated data, 'No gap-kmer' had all k-mers containing gaps removed before LDA. 'C' (Close) marks the frequency of topologies that are either the same as the true topology or not more than 2 rearrangments apart; 'wRF' is the average weighted Robinson-Foulds distance from the true tree. Each result is based on 10 simulations.

| Loci | 7 Species | | | | | | 14 Species | | | | | |
| | Aligned | | Not Aligned | | No gap-kmer | | Aligned | | Not Aligned | | No gap-kmer | |
	C	wRF	C	wRF	C	wRF	C	wRF	C	wRF	C	wRF
1	0.5	1.33	0.1	1.24	0.1	1.27	0.0	1.91	0.0	2.08	0.0	1.59
2	0.2	1.17	0.2	1.26	0.5	1.27	0.0	2.08	0.0	3.08	0.0	2.29
5	0.6	1.29	0.2	1.32	0.6	1.18	0.3	2.04	0.0	3.36	0.2	2.05
10	0.6	1.22	0.4	1.18	0.4	1.19	0.2	2.05	0.0	3.66	0.4	2.04
20	0.8	1.20	0.7	1.21	0.6	1.24	0.7	2.11	0.0	3.78	0.5	2.06
50	0.7	1.21	0.9	1.19	0.5	1.23	0.9	2.09	0.0	3.74	0.7	2.03
100	0.5	1.25	0.8	1.22	0.5	1.22	1.0	2.09	0.0	3.74	0.8	2.01
200	0.7	1.22	0.8	1.23	0.6	1.23	1.0	2.08	0.0	3.81	0.9	1.99
500	0.9	1.20	1.0	1.22	0.3	1.24	1.0	2.06	0.0	3.85	1.0	1.99
1000	0.7	1.22	1.0	1.22	0.7	1.21	1.0	2.06	0.0	3.91	1.0	1.98

Analysis of Empirical Datasets

Multilocus species tree from closely related Australian birds.— For the treecreeper dataset, we tokenized each DNA sequence at every locus using k-mer representation with a k value of 8 (as estimated by TopicContml), employing non-overlapping tokens. Individuals from the same location were merged, and LDA was applied to the corpus to generate topic frequencies for each locus for each of the 9 populations. We used five topics in our analysis. These multilocus topic frequencies were then used to construct a maximum-likelihood tree with Contml in the PHYLIP package. We did bootstrapping, and Fig. 3b shows the majority-rule consensus tree generated by TopicContml for unaligned data, with bootstrap support values derived from 1000 replicates. Inspection of the clades reveals that our tree recover the expected geographic relationship within each species (Edwards et al. 2023; Cracraft 1986), and the locations are separated by species,

₂₆₇ which in turn are separated by the Carpentarian barrier in Australia.

FIGURE 3. Relationship tree of 9 populations of two Australian treecreeper species reconstructed. (a) The map of Australia shows the locations; the black disks mark *Climacteris melanurus*, and the white disks mark *Climacteris picumnus* (Edwards et al. 2023). (b) The majority-rule consensus tree of unaligned data by TOPICCONTML. For each bootstrap analysis, 1000 replicates were used. Values in the graphs are % support. (c) The majority-consensus tree of aligned data analyzed by SVDQUARTETS +PAUP*. (d) The phylogeny constructed by MASH.

₂₆₈ We compared the performance of TOPICCONTML with SVDQUARTETS (Chifman

₂₆₉ and Kubatko 2014) implemented in PAUP* (Swofford 2003) (SVDQUARTETS +PAUP*), as

₂₇₀ shown in Fig. 3c. There are notable differences between the results of SVDQUARTETS and

₂₇₁ TOPICCONTML. When comparing these results to the mapped locations in Fig. 3a, we

₂₇₂ observe that our bootstrap tree from TOPICCONTML recovers the relationships equally

₂₇₃ well or better than SVDQUARTETS. Both methods encounter challenges in resolving

₂₇₄ certain population splits but confidently separate the two species. TOPICCONTML support

₂₇₅ values recover, in general, the geographic pattern of the locations well, and a greater

₂₇₆ number of potential splits are unresolved.

²⁷⁷ We also compared our phylogenetic tree with one generated using the alignment-free

²⁷⁸ approach Mash (Ondov et al. 2016), which estimates evolutionary distances between

²⁷⁹ nucleotide sequences. For the Mash input, sequences from different loci for each individual

²⁸⁰ were concatenated, with missing data filled by gaps. The sequences from individuals at the

²⁸¹ same location were then merged to create nine Fasta files, representing the nine

²⁸² populations in Australia. The pairwise distance matrix generated by Mash was used to

²⁸³ construct a Neighbor-Joining tree using the PHYLIP package (Felsenstein 2004). Fig. 3d

²⁸⁴ shows the phylogenetic tree generated by Mash. When comparing our tree to the one

²⁸⁵ generated by Mash, we observe that both trees depict similar relationships among species.

²⁸⁶ *Multilocus species tree from genome-wide mammal dataset.—* We analyzed a

²⁸⁷ mammal data with 90 species and 5162 loci . The dataset consisted of nucleotide

²⁸⁸ characters from the set 'ACGT-N'. We analyzed the mammal dataset under various

²⁸⁹ conditions and compared the resulting trees to the maximum likelihood tree derived from

²⁹⁰ 4388 loci of 90 vertebrate species, as reported by Liu et al. (2017). The comparisons were

²⁹¹ visualized using tanglegrams (Revell 2024). In the first analysis, after generating k-mers,

²⁹² we excluded any k-mers containing either '-' or 'N'. The resulting phylogenetic tree (Fig. 4)

²⁹³ was 60 steps away from the maximum likelihood tree, as measured by the Robinson-Foulds

²⁹⁴ (RF) distance. In the second analysis, we removed all alignment columns containing gaps,

²⁹⁵ then excluded k-mers with 'N'. The resulting tree (Supplementary Fig. S4) was 64 steps

²⁹⁶ from the reference tree. This resulted in a tree generated using 1719 loci because 3443 of

²⁹⁷ the 5162 loci did not contain any data after the removal. In the third analysis, we removed

²⁹⁸ all gaps from each sequence before excluding k-mers containing 'N'. This approach did not

²⁹⁹ improve the tree (Supplementary Fig. S5), which was 90 steps from the reference tree.

³⁰⁰ Finally, in the fourth analysis, we generated a tree using aligned sequences while retaining

³⁰¹ 'N' characters. This tree (Supplementary Fig. S6) was 80 steps from the maximum

³⁰² likelihood tree.

FIGURE 4. Tanglegram of mammal dataset comparing the TOPICCONTML tree (left), generated by excluding *k*-mers containing '-' or 'N', with the maximum likelihood tree from Liu et al. (2017) (right). The alphabetical list of the species names in the tree is in Supplementary Table S1.

The RF distances between 1,000,000 random trees and the maximum likelihood tree reveal a minimum distance of 168, a mean distance of 173.5, and a maximal distance of 174. The topic modeling trees are therefore considerably closer to the maximum likelihood tree than random trees (Supplementary Fig. S7), confirming that our topic modeling

approach recovers phylogenetic signal. The tanglegrams (Fig. 4; Supplementary

Fig. S4, S5, S6) also confirm that our tree and the maximum likelihood tree are fairly

similar despite a seemingly large RF distance, especially when considering that many of

the branches in the mammal tree are very short .

Multilocus species tree from raw unassembled PACBIO *sequence reads.—* This

dataset consists of FASTA files containing 100,000 reads from each of 12 species. To reduce

computational time by reducing the number of loci, we first combined sets of 1,000 reads

and then concatenated them to produce files of 100 loci. Fig. 5 (left) displays the tree

generated by TOPICCONTML using a non-overlapping k-mer length of 20, with an RF

distance of two from the reference tree, as shown in Fig. 5 (right). The reference tree was

drawn from Cracraft (1988), Oliveros et al. (2019), and Wu et al. (2024). The discrepancy

in relationships of the Wrentit and Yellow warbler are uncertain, because relationships in

this portion of the passerine tree are certainly not definitive.

FIGURE 5. The phylogeny generated by TOPICCONTML (left side) compared to the reference tree (right side).

320 Given the large size of each document, we performed our first analysis using a

321 longer k-mer length (k-mer length of 20 as we discussed in Section K-mer decomposition).

322 To assess the effects of different k-mer ranges, we experimented with lengths from 8 to 42.

We found that optimal results were achieved with k-mers in the range of 18 to 30, as demonstrated in Supplementary Fig. S9.

<h2 align="center">DISCUSSION</h2>

This study integrates k-mers and probabilistic topic modeling to perform phylogenetic analysis on unaligned or aligned multilocus sequence data, as well as on unassembled raw sequencing reads. The Python code TOPICCONTML offers an efficient workflow to reconstruct evolutionary relationships potentially without prior sequence alignment. TOPICCONTML contains a two-phase analysis. First, k-mers are extracted from DNA sequences, and Latent Dirichlet Allocation uses these k-mers to establish how probable an individual's set of k-mers fits an arbitrary number of topics. For each locus and each individual, we generate a vector of assignment frequencies for a predefined set of topics. This step can be parallelized among loci. The LDA runtime depends on the length of the sequences (documents) and the number of loci. In the second step, the topic frequencies are used as input for CONTML to construct a phylogenetic tree. The CONTML evaluation time is influenced by the number of tips and the number of loci, as the input matrix for CONTML is structured as number of tips $\times$ (number of loci $\times$ (number of topics - 1)). Although the current version of CONTML does not support parallelization, implementing this capability could significantly improve its runtime, particularly for analyses involving many species. As shown in Supplementary Table S3, the Australian bird dataset completed in seconds for both LDA and CONTML. The mammal dataset, however, took longer for LDA due to its large number of loci (5,162), despite relatively short sequence lengths, and even longer for CONTML due to the large input size. For the PACBIO dataset, the LDA runtime was extended by the significantly longer sequence lengths, but the CONTML step completed within seconds.

The simulated data experiments reflect the influence of gap handling on phylogenetic reconstruction accuracy under different insertion/deletion (indel) rates and

tree complexities. The simulation protocol produced aligned data with low and high gap numbers. The more aligned the data was, the more accurate was the phylogoenetic inference; for both moderate and high indel frequencies, this approach consistently outperforms others. The observed decline in accuracy for the 'Not Aligned' group, especially in the high-indel 14-species tree, stems from the loss of indel information because gaps are removed entirely; new k-mer were then formed that do not necessarily coincide with the phylogenetic signal. The 'Not Aligned' group faired well with the moderate indel scheme because only few k-mers were affected. The 'No gap-kmer' group's results, which approximate those of the 'Aligned' group under moderate indel scenarios, suggest that excluding only gap-containing k-mers strikes a balance between noise reduction and information preservation. This selective approach retains enough informative content while minimizing the alignment artifacts that become problematic in high-indel scenarios.

In contrast, the analysis of the real datasets was more complex, as demonstrated using the mammal dataset to evaluate the effect of structuring sequence data into k-mers. The Robinson-Foulds (RF) distances to the maximum likelihood tree (Liu et al. 2017) reveal that increasing the number of loci does not always improve phylogenetic accuracy. The mammal dataset analysis highlights the robustness of TopicContml in recovering phylogenetic signal under various treatments of gaps and missing data. The most accurate tree (RF distance of 60) was achieved by excluding k-mers containing gaps or 'N', underscoring the importance of targeted ambiguity removal. Removing entire alignment columns with gaps reduced the number of loci but still produced a comparable tree (RF distance of 64). Conversely, removing all gaps from sequences resulted in the least accurate tree (RF distance of 90), likely due to the loss of biologically informative gap signals. Retaining 'N' characters in aligned sequences yielded an intermediate result (RF distance of 80), showing that while ambiguity introduces noise, key phylogenetic relationships are still preserved. Notably, all TopicContml trees were substantially closer to the reference tree than random trees.

Tree uncertainty is commonly assessed through bootstrap analysis, which poses

challenges for unaligned datasets as it requires bootstrapping at the k-mer level rather

than the sequence level. For the treecreeper dataset, bootstrap analysis with

TOPICCONTML demonstrates its robustness in recovering phylogenetic relationships from

unaligned data. The majority-rule consensus tree effectively separates the two species and

accurately captures geographic patterns, including the division across the Carpentarian

barrier. Compared to the alignment-based SVDQUARTETS, TOPICCONTML achieves equal

or better precision in recovering geographic relationships. Furthermore, the comparison

with the alignment-free method MASH confirms that TOPICCONTML effectively captures

key phylogenetic relationships while working with unaligned data.

Our analyses of the PACBIO dataset shows substantial promise deriving

phylogenetic signal from unaligned long-read sequences, and demonstrates the potential of

TOPICCONTML for alignment-free phylogenetic reconstruction. Despite the complexity of

raw, unassembled reads, TOPICCONTML produced trees closely matching a reference

phylogeny, showing its capacity to infer evolutionary relationships directly from complex,

heterogeneous data. An important goal of the future is to determine what components of

unaligned genomic data - tranposable elements, satellite sequences, or other common

components of genomes - are driving these positive results. Although the LDA step for

this data set required additional processing time due to long-read lengths, CONTML

efficiently completed tree inference. These results suggest that TOPICCONTML offers a

promising approach for handling high-throughput phylogenetic data without requiring

sequence alignment or even genome or locus assembly.

TOPICCONTML is modular, and we have begunwork to replace CONTML with a

network-generating package that may improve the analyses of such datasets by

incorporating gene flow between species. Currently, for many datasets that do not suffer

widespread introgression, TOPICCONTML allows the analysis of many loci from many

individuals that can be grouped, for example, into locations or species. We believe that

TopicContml will become a valuable addition to the computational toolkit for phylogenetics by constructing evolutionary trees without or with sequence alignment.

Software Availability

We implemented our method as a free software named TopicContml under the MIT open-source license. The source code and the documentation of TopicContml are available at https://github.com/TaraKhodaei/TopicContml.git

Funding Sources

This research was partly supported by the National Science Foundation grant DBI2019989 to PB, and National Institutes of Health grant 1R01HG011485 to SVE.

Acknowledgments

We sincerely thank the reviewers for their constructive comments and suggestions, which significantly improved this manuscript. We acknowledge the contributions of our collaborators and are grateful to Subir Shakya and Tim Sackton for providing pre-publication access to PacBio reads from the two tinamou species. Additionally, we thank Liang Liu for assistance with interpreting the mammal dataset. We also thank the Louisiana State University Museum of Science for access to the *Tinamus guttatus* specimen used to generate PacBio sequence data, and the staff of the Museum of Comparative Zoology Ornithology Department for access to the jay specimens. Some simulations were conducted on the Research Computing Cluster at Florida State University, Tallahassee, and some data preprocessing was performed on the FASRC Cannon cluster, supported by the FAS Division of Science Research Computing Group at Harvard University.

Data Availability

- **Simulated Data**: Instructions for generating the simulated data are available at
  https://github.com/pbeerli/simulations_for_topiccontml.

- **Australian Treecreeper Dataset**: Available through Dryad (Edwards et al. 2022).

- **Mammal Dataset**: The aligned mammal dataset can be accessed at
  https://figshare.com/articles/cds_5162_zip/6031190 (Wu et al. 2018).

- **PacBio Bird Sequences**: The sources of PacBio long-read sequences from birds
  are detailed in Supplementary Section: Processing of PacBio Reads and
  Supplementary Table S2. Datasets for the four unpublished species (two tinamous
  and two jays) are available through Dryad at https://datadryad.org/stash/
  share/5RpvXGzGfUdffDrC3Jv_LF8oSvuY3xiIufQDgn5YELg.

.

References

M. Balaban, N. A. Bristy, A. Faisal, M. S. Bayzid, and S. Mirarab. Genome-wide
alignment-free phylogenetic distance estimation under a no strand-bias model.
Bioinform Adv, 2(1):vbac055, 2022.

G. Bernard, C. X. Chan, and M. A. Ragan. Alignment-free microbial phylogenomics under
scenarios of sequence divergence, genome rearrangement and lateral genetic transfer. *Sci
Rep*, 6(1):28970, 2016.

D. M. Blei, A. Y. NG, and M. I. Jordan. Latent Dirichlet allocation. *J Mach Learn Res*, 3:
993–1022, 2003.

R. A. Cartwright. Dna assembly with gaps (dawg): simulating sequence evolution.
Bioinformatics, 21 Suppl 3:iii31–8, Nov 2005. doi: 10.1093/bioinformatics/bti1200.

L. L. Cavalli-Sforza and A. W. F. Edwards. Phylogenetic analysis. Models and estimation
procedures. *Am J Hum Gen*, 19(3 Pt 1):233–257, 1967.

C. X. Chan, G. Bernard, O. Poirion, J. M. Hogan, and M. A. Ragan. Inferring phylogenies
of evolving sequences without multiple sequence alignment. *Sci Rep*, 4(1):6504, 2014.

C. Chapus, C. Dufraigne, S. Edwards, A. Giron, B. Fertil, and P. Deschavanne.
Exploration of phylogenetic data using a global sequence analysis method. *BMC Evol*
Biol, 5(1):63, 2005.

J. Chifman and L. Kubatko. Quartet inference from SNP data under the coalescent model.
Bioinformatics, 30(23):3317–3324, 2014.

J. Cracraft. Origin and evolution of continental biotas: Speciation and historical
congruence within the australian avifauna. *Evolution*, 40(5):977–996, 1986.

J. Cracraft. The major clades of birds. In M. J. Benton, editor, *The Phylogeny and*
Classification of the Tetrapods, Volume 1: Amphibians, Reptiles, Birds, volume 35A of
Systematics Association Special, pages 339–361. Clarendon Press, Oxford, 1988.

A. de Queiroz and J. Gatesy. The supermatrix approach to systematics. *Trends Ecol Evol*,
22(1):34–41, 2007.

P. J. Deschavanne, A. Giron, J. Vilain, G. Fagot, and B. Fertil. Genomic signature:
characterization and classification of species assessed by chaos game representation of
sequences. *Mol Biol Evol*, 16(10):1391–1399, 1999.

K. K. Dey, C. J. Hsiao, and M. Stephens. Visualizing the structure of RNA-seq expression
data using grade of membership models. *PLoS Genet*, 13(3):e1006599, 2017.

Y. Du, S. Wu, S. V. Edwards, and L. Liu. The effect of alignment uncertainty, substitution
models and priors in building and dating the mammal tree of life. *BMC Evol Biol*, 19
(1):203, 2019.

D. A. duVerle, S. Yotsukura, S. Nomura, H. Aburatani, and K. Tsuda. CellTree: an R/bioconductor package to infer the hierarchical structure of cell populations from single-cell RNA-seq data. *BMC Bioinformatics*, 17(1):363, 2016.

S. V. Edwards, B. Fertil, A. Giron, and P. J. Deschavanne. A genomic schism in birds revealed by phylogenetic analysis of DNA strings. *Syst Biol*, 51(4):599–613, 2002.

S. V. Edwards, J. a. F. R. Tonini, N. Mcinerney, C. Welch, and P. Beerli. Multilocus phylogeography, population genetics and niche evolution of Australian brown and black-tailed treecreepers (Aves: Climacteris) [Dataset]. https://doi.org/10.5061/dryad.bcc2fqzgt, 2022.

S. V. Edwards, J. F. R. Tonini, N. Mcinerney, C. Welch, and P. Beerli. Multilocus phylogeography, population genetics and niche evolution of Australian brown and black-tailed treecreepers (Aves: Climacteris). *Biol J Linn Soc*, 138(3):249–273, 2023.

B. Efron. Bootstrap methods: another look at the jackknife. *Ann Statis*, 7(1):1–26, 1979.

B. Efron, E. Halloran, and S. Holmes. Bootstrap confidence levels for phylogenetic trees. *Proc Natl Acad Sci*, 93(23):13429–13429, 1996.

J. Felsenstein. Maximum-likelihood estimation of evolutionary trees from continuous characters. *Am J Hum Gen*, 25(5):471–492, 1973.

J. Felsenstein. Evolutionary trees from gene frequencies and quantitative characters: finding maximum likelihood estimates. *Evolution*, pages 1229–1242, 1981.

J. Felsenstein. PHYLIP (Phylogeny Inference Package) version 3.6. Distributed by the author. 2004. URL https://evolution.genetics.washington.edu/phylip.html.

Y. Fofanov, Y. Luo, C. Katili, J. Wang, Y. Belosludtsev, T. Powdrill, C. Belapurkar, V. Fofanov, T.-B. Li, S. Chumakov, et al. How independent are the appearances of n-mers in different genomes? *Bioinformatics*, 20(15):2421–2428, 2004.

J. Gatesy and R. H. Baker. Hidden likelihood support in genomic data: can forty-five
wrongs make a right? *Syst Biol*, 54(3):483–92, 2005.

T. L. Griffiths and M. Steyvers. Finding scientific topics. *Proc Natl Acad Sci*, 101
(suppl_1):5228–5235, 2004.

D. M. Hillis and J. J. Bull. An empirical test of bootstrapping as a method for assessing
confidence in phylogenetic analysis. *Sist Biol*, 42(2):182–192, 1993.

M. T. Holder, J. Sukumaran, and P. O. Lewis. A justification for reporting the
majority-rule consensus tree in Bayesian phylogenetics. *Sist Biol*, 57(5):814–821, 2008.

M. La Rosa, A. Fiannaca, R. Rizzo, and A. Urso. Probabilistic topic modeling for the
analysis and classification of genomic sequences. *BMC Bioinformatics*, 16(6):S2, 2015.

L. Liu, L. Yu, L. Kubatko, D. K. Pearl, and S. V. Edwards. Coalescent methods for
estimating phylogenetic trees. *Mol Phylogenet Evol*, 53(1):320–328, 2009.

L. Liu, L. Tang, W. Dong, S. Yao, and W. Zhou. An overview of topic modeling and its
current applications in bioinformatics. *SpringerPlus*, 5(1):1608, 2016.

L. Liu, J. Zhang, F. E. Rheindt, F. Lei, Y. Qu, Y. Wang, Y. Zhang, C. Sullivan, W. Nie,
J. Wang, F. Yang, J. Chen, S. V. Edwards, J. Meng, and S. Wu. Genomic evidence
reveals a radiation of placental mammals uninterrupted by the kpg boundary. *Proc Natl*
Acad Sci U S A, 114(35):E7282–E7290, 2017.

G. Marçais and C. Kingsford. A fast, lock-free approach for efficient parallel counting of
occurrences of k-mers. *Bioinformatics*, 27(6):764–770, 2011.

T. P. Minka and J. Lafferty. Expectation-propogation for the generative aspect model.
arXiv preprint arXiv:1301.0588, 2012.

S. Mirarab, M. S. Bayzid, and T. Warnow. Evaluating summary methods for multilocus
species tree estimation in the presence of incomplete lineage sorting. *Syst Biol*, 65(3):
366–380, 2016.

T. H. Ogden and M. S. Rosenberg. Multiple sequence alignment accuracy and phylogenetic inference. *Syst Biol*, 55(2):314–328, 2006.

C. H. Oliveros, D. J. Field, D. T. Ksepka, F. K. Barker, A. Aleixo, M. J. Andersen, P. Alström, B. W. Benz, E. L. Braun, M. J. Braun, et al. Earth history and the passerine superradiation. *Proc Natl Acad Sci*, 116(16):7916–7925, 2019.

B. D. Ondov, T. J. Treangen, P. Melsted, A. B. Mallonee, N. H. Bergman, S. Koren, and A. M. Phillippy. Mash: fast genome and metagenome distance estimation using minhash. *Genome biology*, 17:1–14, 2016.

R. Řehůřek and P. Sojka. Software framework for topic modelling with large corpora. In *Proc LREC 2010 Workshop New Challenges NLP Frameworks*, pages 45–50. ELRA, 2010.

J. Ren, X. Bai, Y. Y. Lu, K. Tang, Y. Wang, G. Reinert, and F. Sun. Alignment-free sequence analysis and applications. *Annu Rev Biomed Data Sci*, 1(1):93–114, 2018.

L. J. Revell. phytools 2.0: an updated R ecosystem for phylogenetic comparative methods (and other things). *PeerJ*, 12:e16505, 2024.

M. Röder, A. Both, and A. Hinneburg. Exploring the space of topic coherence measures. In *Proceedings of the eighth ACM international conference on Web search and data mining*, pages 399–408, 2015.

A. M. Shedlock, C. W. Botka, S. Zhao, J. Shetty, T. Zhang, J. S. Liu, P. J. Deschavanne, and S. V. Edwards. Phylogenomics of nonavian reptiles and the structure of the ancestral amniote genome. *Proc Natl Acad Sci*, 104(8):2767–2772, 2007.

W. Shen, S. Le, Y. Li, and F. Hu. Seqkit: a cross-platform and ultrafast toolkit for fasta/q file manipulation. *PloS one*, 11(10):e0163962, 2016.

C. Sievert and K. Shirley. Ldavis: A method for visualizing and interpreting topics. In

Proceedings of the workshop on interactive language learning, visualization, and interfaces, pages 63–70, 2014.

J. Sukumaran and M. T. Holder. DendroPy: a Python library for phylogenetic computing. *Bioinformatics*, 26(12):1569–1571, 2010.

D. Swofford. PAUP*. Phylogenetic Analysis Using Parsimony (*and Other Methods). Version 4., 2003.

J. Van Etten, T. G. Stephens, and D. Bhattacharya. A k-mer-based approach for phylogenetic classification of taxa in environmental genomic data. *Syst Biol*, 72(5): 1101–1118, 06 2023.

S. Vinga and J. Almeida. Alignment-free sequence comparison review. *Bioinformatics*, 19 (4):513–523, 2003.

K. M. Wong, M. A. Suchard, and J. P. Huelsenbeck. Alignment uncertainty and genomic analysis. *Science*, 319(5862):473–476, 2008.

S. Wu, S. Edwards, and L. Liu. Genome-scale DNA sequence data and the evolutionary history of placental mammals. *Data Brief*, 18:1972–1975, 2018.

S. Wu, F. E. Rheindt, J. Zhang, J. Wang, L. Zhang, C. Quan, Z. Li, M. Wang, F. Wu, Y. Qu, et al. Genomes, fossils, and the concurrent rise of modern birds and flowering plants in the late cretaceous. *Proc Natl Acad Sci*, 121(8):e2319696121, 2024.

C. Zhang, M. Rabiee, E. Sayyari, and S. Mirarab. ASTRAL-III: polynomial time species tree reconstruction from partially resolved gene trees. *BMC Bioinformatics*, 19(6):153, 2018.

A. Zielezinski, H. Z. Girgis, G. Bernard, C.-A. Leimeister, K. Tang, T. Dencker, A. K. Lau, S. Röhling, J. J. Choi, M. S. Waterman, M. Comin, S.-H. Kim, S. Vinga, J. S. Almeida, C. X. Chan, B. T. James, F. Sun, B. Morgenstern, and W. M. Karlowski. Benchmarking of alignment-free sequence comparison methods. *Genome Biol*, 20(1):144, 2019.

Electronic Supplement

Simulated dataset

We evaluated two sets of simulations: one with moderate and one with many insertions and deletions. We used the software Dawg (Cartwright 2005) to simulate aligned sequences with indels/deletions on a 7-species and a 14-species tree (Fig. 2). The moderate scenario inserts indels at a rate of 0.02 per site and deletes sites with a rate of 0.02 per site; for example, in the 7-species simulations, a species could have at a locus on average 1038 sites that include, on average per species 8.2 gaps with and average length of 12 sites. The more extreme simulation used an insertion/deletion rate of 0.2 per site. The number of gap sites increased for the specific tree considerably: each locus had about 59.3 gaps on average 17 sites long, each species had about 960 A, C, G, T sites, and about 1000 '-' sites. The branch length and topology matter for the gap distribution: the 14-tip tree had a similar distribution of the gaps with the low insertion/deletion parameter as the 7-tip tree, but the high parameter resulted in many gaps but not as extreme as in the 7-tip tree (about 400 '-' sites per species).

```
     #Relevant parameters for DAWG
Root.Length = 1000
Subst.Model = "GTR"
Subst.Freqs  = 0.2, 0.3, 0.3, 0.2
Subst.Params = 2.0, 1.0, 3.0, 1.0, 1.0, 1.0
Indel.Model = "GEO"
Indel.Rate = 0.02
Indel.Max = 2000
Indel.Params = 12
#Example result for the first of 7 species: indel/deletion rate=0.02
    7    1038  #number_of_species number_of_sites
A        GGCTGCGTCAGCTAGGCGACGGACTAGCGGGCCTTCACCCATCAAGTATTCGCTATGGCG
         AGGGTCAATCATCCTTAGGCATCGCATCCCACAAAGAGCGCTGTTATGCAGCCGGCAGCC
         ATAGGCCGGGCTGCTGAAGCGGCCCCGCCAAAGTGGCCCTTAGCGTGGGGGAGCGGCCGG
         ATGTGGTGTCTAACCATCGCTGGTCGCAGTCCGATACACCATATAGCGCCATCGATGGTG
         CTTTCTATCGGAGCTCGTTAGCCAAGTGGTCCGGGTAATTCGGGGACACAATGCTCGTAG
         CTCCGGGCAGCCGTGTGCCATGACTAGTCCCGGCAGTCTCGATGTGCACGACCCTTGCGC
         CTGGTTCGCAGTCTTGCCAATGA----TATGTAGCCGGGGAGTGTCGACAGCCCAGACTG
         GAGACCGCCCCCTTGACGCCTGGATGCTGCTCGTAGGTACTTACGTACCGCTCTAGCGGA
         GTAGAGCCCACCCCGGCGGAGCGGCCAGAGCCACCGGCGTCCTTGTGAC-----------
         -------------------TCCTCTGTGCCTATTGCGAGCTACTTGCCGACCTCTCGCAGG
         TGGAGAGCTCACAGCCCAATAGCCCACCGACCCGTTGGGCGTAGCACGATATTTCCGGCC
         CCCAGAACCAATTCTGGAACACTAAGTCACTGAGCGGTTCGCCATGCCCACCTTTGGTGA
         GGCTTTATAGGCCGTCGGGTACGATGGGCGCCGAGAACACTCTCGGTCTTTCACGGAAGC
         ACAGTGCGGCTGTGTCCGGCGAGTGACCCCCCGGGTACCATAGACAC---GCTAGGC---
         ----------------CTGTTGGCTATCACGATTCACGTCGCGGGAACGAGTCGCGTCCCG
         GGCCGCAAACGGCTACT-GGCACGAATGACGTGGCTGTCTGTGAGCCGTCTCCGTGA---
         -------CGCACGGCGGACGCTGGGTGCTGTTGCCGAAACTCGCGCTCATCACTCCGGTG
         GGCTGCGACCGCACATGC
#
#Example result for the first of 7 species: indel/deletion rate=0.2
    7    1771
A        CGTAGACGTAGCACTGTATGTTGTCC-GCGCAACCCGGGTG------GC-TGAGTTGAGC
         CCTGACC----AATCGCCCTGGCAA---------------ATGGCGCTTC-A---------
         -----------TCTGCTGAT----------GAAGGGACAGCTCCG-------CAAGACCC
         CTCATAGACATGTCGCCGCG-TGCAATTAGTGACTAGC----TCGTCCCGCCCAATCTCG
         TACCTCT-------------ACGCGGCGTAGCC--------------------------
         -----CCAAA------------GACTGGTAGTGGAACTAT---------------AC----G
         GGCGATGCGCGTACGCCGAGT------------GATGGCGCCCCGGGACGTTGCCCG-GC
         TAGTGGGCGCAACGGTAGGT--------------------------------------
         -----GGAAAATACACTATTGCAGGCCTGGAATCTCTCC--------ACCGAC-------G
         TCGGCCCTGTAGCCCAGTGAAGTGACGGT----------A-----------------
         ---------------GTTCATT----------TCTCCTGCCCCCC-------GG-------
         -------------CAACGTGTCAA----------------------------------
         ------------------GACTCGTCCTAG--------------------------
         -----CGCGGTACAGG------------------------------------------
         -----------GGACCCCCCGG------------GT-----------CGGTAGTGGGGCG
         GTTGGTTTC------------GAGAAGTGTTCCGAAGA--------------------A-
         G-----------------------------------------------------------TA
         CCGCAGC-------------------GTCCCAGCGTTAGTCGCAATGG-----------
         -----------------ATGTGCCTGTCTGCATCTTACGGACAGGCCCGAGATATAGAA-
         -----CCTCCTGATC-----GTACGC---------------------------------CT
         TCGGGTTCCCATAGCCCTACCGAGTGGGTAAAGACAGTTCGGGCGTCTGGGGGGGGT---
         ACTGCTT---------------------------------------------------
         -------------------------G----GCAAAA---GGCCGTATGGACCCGATTGTT
         GCAGAAACACTA--------GCTTGCAGACATGTAGTCGCTATCGCAGGCATAGCTGTAA
         TGTACAAATCGCACGGAGAAGTTGACG-GCGTATTC--CTCAAGGAGAATCGCGCGGTGG
         ACCTAT--------------------CCTACGCGCCGTTTGCGGTAA--TG-------
         -----------------------CCAGAGGAGG-------ATCATCAG----AGTGGAAGA
         TAAGGTTAAACCTACGTTGGAAACGGT-------------------------AGGGCC-
         ---CC----CTGGGTTGCC------------
```

Figure S1. Example sequences for the two simulation treatement, resulting in data that contain gaps determined by the deletion/indel parameter in the simulation software DAWG Cartwright (2005).

Bird dataset

Figure S2. Screenshot of an interactive two-part visualization output from PYLDAVIS for the 'Bird' dataset, first locus. Left: an intertopic distance map of topics (7 topics) generated by the LDA model for the first locus. The topics are represented as circles scaled to their frequency of occurrence. The index number of each cluster represents the topic ID; the red circle shows the current topic, and the blue circles show other topics. Right: distribution of the top 30 most relevant terms among topics.

Figure S3. Coherence scores for varying numbers of topics in the range of 3 to 20 (with an increment of 2) for each of the 14 loci in the 'Bird' dataset. Each subplot represents the coherence analysis for a specific locus, illustrating the u_mass coherence scores for topic numbers 3, 5, 7, 9, 11, 13, 15, 17, and 19. Higher coherence scores indicate more interpretable topics, allowing us to determine the optimal number of topics for each locus individually.

Mammal dataset

Table S1. Alphabetical list of Mammal species

ailur_mel	*Ailurus fulgens* (Red Panda)	melea_gal	*Meleagris gallopavo* (Wild Turkey)
anoli_car	*Anolis carolinensis* (Carolina Anole)	mesoc_aur	*Mesocricetus auratus* (Golden Hamster)
balae_acu	*Balaenoptera acutorostrata* (Minke Whale)	micro_mur	*Microtus muridae* (a species of vole)
bos_mut	*Bos mutus* (Wild Yak)	micro_och	*Microcebus ochraceus* (Ochre Mouse Lemur)
bos_tau	*Bos taurus* (Domestic Cattle)	monod_dom	*Monodelphis domestica* (Gray Short-tailed Opossum)
calli_jac	*Callithrix jacchus* (Common Marmoset)	mus_mus	*Mus musculus* (House Mouse)
camel_fer	*Camelus ferus* (Wild Bactrian Camel)	muste_put	*Mustela putorius* (European Polecat)
canis_fam	*Canis familiaris* (Domestic Dog)	myoti_bra	*Myotis brandtii* (Brandt's Bat)
capra_hir	*Capra hircus* (Domestic Goat)	myoti_luc	*Myotis lucifugus* (Little Brown Bat)
cavia_por	*Cavia porcellus* (Guinea Pig)	nomas_leu	*Nomascus leucogenys* (Northern White-cheeked Gibbon)
cerat_sim	*Ceratotherium simum* (White Rhinoceros)	ochot_pri	*Ochotona princeps* (American Pika)
chinc_lan	*Chinchilla lanigera* (Long-tailed Chinchilla)	octod_deg	*Octodon degus* (Degu)
chlor_sab	*Chlorocebus sabaeus* (Green Monkey)	odobe_ros	*Odocoileus rosenbergi* (White-tailed Deer)
cholo_hof	*Choloepus hoffmanni* (Hoffmann's Two-toed Sloth)	orcin_orc	*Orcinus orca* (Killer Whale)
chrys_asi	*Chrysolophus amherstiae* (Lady Amherst's Pheasant)	ornit_ana	*Ornithorhynchus anatinus* (Platypus)
condy_cri	*Condylura cristata* (Star-nosed Mole)	oryct_afe	*Oryctolagus cuniculus* (European Rabbit)
crice_gri	*Cricetulus griseus* (Chinese Hamster)	oryct_cun	*Oryctolagus cuniculus* (European Rabbit)
danio_rer	*Danio rerio* (Zebrafish)	otole_gar	*Otolemur garnettii* (Garnett's Galago)
dasyp_nov	*Dasypus novemcinctus* (Nine-banded Armadillo)	ovis_ari	*Ovis aries* (Domestic Sheep)
daube_mad	*Daubentonia madagascariensis* (Aye-aye)	pan_pan	*Pan paniscus* (Bonobo)
dipod_ord	*Dipodomys ordii* (Ord's Kangaroo Rat)	pan_tro	*Pan troglodytes* (Chimpanzee)
echin_tel	*Echinops telfairi* (Small Madagascar Hedgehog)	panth_hod	*Pantholops hodgsonii* (Tibetan Antelope)
eidol_hel	*Eidolon helvum* (African Straw-coloured Fruit Bat)	panth_tig	*Panthera tigris* (Tiger)
eleph_edw	*Elephas maximus* (Asian Elephant)	papio_anu	*Papio anubis* (Olive Baboon)
eptes_fus	*Eptesicus fuscus* (Big Brown Bat)	pelod_sin	*Pelodiscus sinensis* (Chinese Softshell Turtle)
equus_cab	*Equus caballus* (Domestic Horse)	perom_man	*Peromyscus maniculatus* (Deer Mouse)
erina_eur	*Erinaceus europaeus* (European Hedgehog)	physe_mac	*Physeter macrocephalus* (Sperm whale)
felis_cat	*Felis catus* (Domestic Cat)	pongo_abe	*Pongo abelii* (Sumatran Orangutan)
galeo_var	*Galeopterus variegatus* (Flying Lemur)	proca_cap	*Procavia capensis* (Rock Hyrax)
gallu_gal	*Gallus gallus* (Red Junglefowl)	ptero_ale	*Pteropus alecto* (Black Flying Fox)
gaste_acu	*Gastereus aculeata* (Stickleback)	ptero_par	*Pteronotus parnellii* (Parnell's mustached bat)
goril_gor	*Gorilla gorilla* (Western Gorilla)	ptero_vam	*Pteropus vampyrus* (Large Flying Fox)
heter_gla	*Heterocephalus glaber* (Naked Mole Rat)	rattu_nor	*Rattus norvegicus* (Norway Rat)
homo_sap	*Homo sapiens* (Human)	rhino_fer	*Rhinolophus ferrumequinum* (Greater horseshoe bat)
ictid_tri	*Ictidomys tridecemlineatus* (Thirteen-lined Ground Squirrel)	saimi_bol	*Saimiri boliviensis* (Bolivian Squirrel Monkey)
jacul_jac	*Jaculus jaculus* (Lesser Egyptian Jerboa)	sarco_har	*Sarcophilus harrisii* (Tasmanian Devil)
latim_cha	*Latimeria chalumnae* (Coelacanth)	sorex_ara	*Sorex araneus* (Eurasian Common Shrew)
lepto_wed	*Leptonycteris yerbabuenae* (Lesser Long-nosed Bat)	sus_scr	*Sus scrofa* (Wild Boar)
lipot_vex	*Lipotes vexillifer* (Yangtze River Dolphin)	tarsi_syr	*Tarsius syrichta* (Philippine Tarsier)
loxod_afr	*Loxodonta africana* (African Elephant)	trich_man	*Trichechus manatus* (West Indian Manatee)
macac_fas	*Macaca fascicularis* (Crab-eating Macaque)	tupai_bel	*Tupaia belangeri* (Northern Treeshrew)
macac_mul	*Macaca mulatta* (Rhesus Macaque)	tupai_chi	*Tupaia chinensis* (Chinese Tree Shrew)
macro_eug	*Macropus eugenii* (Tammar Wallaby)	tursi_tru	*Tursiops truncatus* (Bottlenose Dolphin)
manis_pen	*Manis pentadactyla* (Chinese Pangolin)	vicug_pac	*Vicugna pacos* (Alpaca)
megad_lyr	*Megaderma lyra* (Greater False Vampire Bat)	xenop_tro	*Xenopus tropicalis* (Western Clawed Frog)

Figure S4. Tanglegram of the mammal dataset comparing the TopicContml tree (left), generated by first removing alignment columns with gaps and then excluding *k*-mers containing 'N', to the maximum likelihood tree from Liu et al. (2017) (right). The alphabetical list of the species names in the tree is in Supplement Table S1.

Figure S5. Tanglegram of the mammal dataset comparing the TopicContml tree (left), constructed by removing all gaps from each sequence before excluding k-mers containing 'N', to the maximum likelihood tree from Liu et al. (2017) (right). The alphabetical list of the species names in the tree is in Supplement Table S1.

Figure S6. Tanglegram of the mammal dataset comparing the TopicContml tree (left), constructed using aligned sequences with 'N' characters retained, to the maximum likelihood tree from Liu et al. (2017) (right). The alphabetical list of the species names in the tree is in Supplement Table S1.

Figure S7. Robinson-Foulds (RF) distance histogram of the maximum likelihood tree of 90 species 'mammal' tree (See text) and 1,000,000 random trees with the same number of tips (random topology) and 1,000,000 trees with the true topology but with randomly permuted tip labels. The maximum likelihood tree is at 0. The inserted tables (organized as RF-steps:occurrence) give the exact distributions for each histogram. Our best TopicContml tree was 60 RF-steps from the reference tree.

PACBIO *dataset*

Processing of PACBIO Reads.— Raw PACBIO HIFI reads were downloaded in fastq.gz

format from NCBI using the SRA Toolkit

(https://hpc.nih.gov/apps/sratoolkit.html#doc) and from the European Nucleotide

Archive for the Common Eider. To ensure uniformity of data type and quality, only

PACBIO HIFI reads were used. SEQKIT (Shen et al. 2016) was used to obtain summary

statistics for each fastq.gz file, including minimum, maximum and average read lengths.

We used SEQTK (https://github.com/lh3/seqtk) to subsample 100,000 or 200,000

random reads per species.

Table S2. Sources of PACBIO long-read sequences from birds for TOPICCONTML analyses.

Species	Latin name	NCBI SRA dataset no.	Average read length (bp)
Domestic chicken	Gallus gallus	SRR25731314	18,846
Wrentit	Chamaea fasciata	SRR25478075	13,086
Acorn woodpecker	Melanerpes formicivorus	SRR23445745	16,852
California quail	Callipepla californica	SRR19599932	15,66
Song sparrow	Melospiza melodia	SRR18559273	16,35
Bell's sparrow	Artemisiospiza belli	SRR18009761	17,530
Yellow warbler	Setophaga petechia	SRR20722040	17,109
Common eider	Somateria mollissima	ERR11187713	15,215
Yucatan jay	Cyanocorax yucatanicus	unpublished	13,00
Woodhouse's jay	Aphelocoma woodhouseii	unpublished	14478
Tataupa tinamou	Crypturellus tataupa	unpublished	9,306
White-throated tinamou	Tinamus guttatus	unpublished	7,713

Figure S8. Comparison of word count distributions across loci and k-mer lengths ranging from 8 to 42, before and after LDA filtering for the "Unassembled Bird" dataset. The left panel depicts the variation in word numbers prior to filtering, while the right panel demonstrates the impact of LDA in refining and standardizing these distributions. Words (k-mers) appearing in fewer than 2 documents or more than 50% of documents are filtered out, retaining only the 100,000 most frequent tokens to optimize memory usage.

Figure S9. Distance between the true tree and TopicContml-inferred phylogenies across varying *k*-mer lengths for the "Unassembled Bird" dataset. The plot shows the distances of trees generated by TopicContml from the true tree, with the closest agreement observed in the 20-30 *k*-mer length range.

Runtime for different datasets

Table S3. TopicContml runtime for different datasets. The first column lists the dataset names and the corresponding trees generated. The second column shows the runtime for LDA mode (if bootstrapping is applied, it shows approximate LDA time per replicate), part of phase 1. The third column displays the runtime for Contml (if bootstrapping is applied, it shows approximate Contml time per replicate), and the fourth column provides the total elapsed runtime of TopicContml (if bootstrapping is applied, it shows the total elapsed time for all replicates).

dataset	LDA Runtime (seconds)	Contml Runtime (seconds)	Total Runtime (seconds)
Treecreeper dataset - Bootstrap tree (1000 replicates) Fig. 3b	4.25	0.06	4355.61*
Mammal dataset - Fig. 4(left)	2300.63	55875.89	58288.26
PacBio dataset - Fig. 5(left)	7921.12	1.4	7922.56

* The total runtime (4355.61 seconds) for the Treecreeper dataset reflects the cumulative runtime for all 1000 bootstrap replicates.