From expert opinion to empirical evidence: Data-driven parametrization of urban connectivity models using movement-proxy data

Lisa Merkens: 1) Terrestrial Ecology Research Group, Department for Life Science Systems, TUM School of Life Sciences, Technical University of Munich, Freising, Germany

2) Studio Animal-Aided Design, Berlin, Germany

ORCID: 0009-0007-0079-134X

Soyeon Bae: 1) Terrestrial Ecology Research Group, Department for Life Science Systems, TUM School of Life Sciences, Technical University of Munich, Freising, Germany

2) Centre of Biodiversity and Sustainable Land Use, University of Göttingen, Göttingen, Germany

ORCID: 0000-0003-1961-1226

Elin Eberl: Terrestrial Ecology Research Group, Department for Life Science Systems, TUM School of Life Sciences, Technical University of Munich, Freising, Germany

Elio Lauppe: Terrestrial Ecology Research Group, Department for Life Science Systems, TUM School of Life Sciences, Technical University of Munich, Freising, Germany

Florian Mesarek: Terrestrial Ecology Research Group, Department for Life Science Systems, TUM School of Life Sciences, Technical University of Munich, Freising, Germany

Daniel Stauffer-Bescher: Terrestrial Ecology Research Group, Department for Life Science Systems, TUM School of Life Sciences, Technical University of Munich, Freising, Germany

Thomas E. Hauck: Research Unit Landscape Architecture and Landscape Planning, Faculty of Architecture and Planning, Technical University of Vienna, Vienna, Austria

ORCID: 0009-0000-8007-009X

Wolfgang W. Weisser: Terrestrial Ecology Research Group, Department for Life Science
Systems, TUM School of Life Sciences, Technical University of Munich, Freising, Germany

ORCID: 0000-0002-2757-8959

Anne Mimet: Université d'Angers, BIODIVAG, Angers, France

ORCID: 0000-0001-9498-436X

Corresponding author: Lisa Merkens, lisa.merkens@tum.de

Terrestrial Ecology Research Group, Department for Life Science Systems, TUM School of
Life Sciences, Technical University of Munich, Freising, Germany
39

Abstract

The landscape connectivity of cities is increasingly recognized as crucial for biodiversity conservation and ecosystem services. Yet, modelling ecological connectivity in cities remains challenging because landscape resistance is often based on expert judgment rather than empirical evidence, leading to varying modelling results and limited use for planning. We developed and tested a data-driven framework for empirically parametrizing resistance and movement-distance parameters in functional connectivity models from movement-proxy data – information on the presence/absence of animal movement from direct observation or camera traps. At each step, we ensured that the connectivity model reflected the behavioural and spatial properties of the observations. We applied the framework for the common blackbird (*Turdus merula*) in Munich, Germany. We used observations of flying blackbirds as movement-proxy data in a logistic regression framework, testing alternative combinations of resistance and movement distances. Model selection identified the parameter sets best supported by the data. The resulting parameters were validated using repeated out-of-sample validation and compared against an expert-based connectivity model. Connectivity derived from empirically estimated parameters increased the probability of observing flying blackbirds. Across repeated validations, the empirical model achieved a mean AUC of 0.76 and R^2 of 0.17. It performed moderately better than the expert-based model. Depending on their height, buildings exhibited varying resistance to flying blackbirds. Results indicate that expert assessments may oversimplify urban barriers. The approach provides a transparent, reproducible framework for using movement-proxy data to derive maps of landscape resistance. It offers a step toward more data-driven urban connectivity modelling.

1. Introduction

Urban ecosystems increasingly serve as important refuges for biodiversity and providers of ecosystem services to people (Kowarik et al. 2025). Green and blue spaces such as parks, gardens, rivers, and remnant woodlands contribute to ecological functioning, mitigate urban heat, and improve human wellbeing (Marselle et al. 2021; Croeser et al. 2021) while preserving biodiversity, including rare and endangered species (Ives et al. 2016; Lepczyk et al. 2023). Recognizing this, international policy frameworks, most notably the Kunming–Montreal Global Biodiversity Framework (Convention on Biological Diversity), explicitly call for increasing the connectivity of urban green spaces to conserve and improve their ability to host biodiversity or provide ecosystem services. Yet, despite growing political attention, cities still lack robust tools to assess and monitor ecological connectivity in ways that meaningfully reflect how wildlife moves through urban landscapes (Habrich and Fahrig 2025).

Ecological connectivity, defined as the degree to which the landscape facilitates or impedes movement among resource patches (Taylor et al. 1993) is central in urban ecology (Goddard et al. 2010). In cities, where habitat is highly fragmented and interspersed with impermeable built structures, maintaining functional connections among greenspaces is crucial for population persistence, gene flow, and daily movements of wildlife (LaPoint et al. 2015). Many species depend on the ability to move across heterogeneous landscapes to forage, breed, or disperse (Goddard et al. 2010; Braaker et al. 2017). Connectivity is also crucial for the delivery of key urban ecosystem services, such as human mental well-being or pollination (Lynch 2019). Thus, understanding and modelling connectivity in urban contexts has become essential for designing ecologically resilient cities.

Over the past two decades, urban connectivity modelling has become a major field within urban ecology and landscape planning (LaPoint et al. 2015; Lookingbill et al. 2022; Habrich and Fahrig 2025). As summarized by Habrich & Fahrig (2025), assessments range from simple metrics of habitat amount to more complex approaches such as functional connectivity and organism-based permeability estimation. Among these, functional connectivity models typically based on least-cost paths or circuit theory have become dominant in urban research because they balance data requirements with biological realism (Calabrese and Fagan 2004). These models typically use multi-class land-cover maps and assign resistance scores to different surfaces based on their assumed difficulty for species to traverse. In urban environments, this framework captures the mosaic nature of the landscape more realistically than binary patch-matrix models (LaPoint et al. 2015; Habrich and Fahrig 2025).

However, a recent systematic review by Habrich & Fahrig (2025) pointed out that many urban connectivity models still assume, rather than demonstrate, that their parameters reflect functional movement. A central challenge arises from the subjective assignment of resistance values (Unnithan Kumar et al. 2022). Resistance scores are commonly derived from expert judgment or literature synthesis (Zeller et al. 2012; Unnithan Kumar et al. 2022; Riordan Short et al. 2023), which may not accurately capture the true permeability of urban

surfaces for a given species. For example, for songbirds in urban environments, maximum
expert resistance values range from 50 to 1000 and the relative resistance of streets, buildings
and water surfaces varies between studies (Ersoy et al. 2019; Balbi et al. 2021; Bourgeois et
al. 2025). This can lead to misleading connectivity maps (Sawyer et al. 2011; Reed et al.
2017) and limits confidence in their application for planning (Habrich & Fahrig, 2025).

At the same time, direct movement data such as GPS tracking, telemetry, or landscape
genetics are often unavailable for urban species. These datasets are costly, logistically
challenging, and may not align with the temporal or spatial scale of interest (Mateo-Sánchez
et al. 2015; Reed et al. 2017). For example, genetic connectivity reflects long-term dispersal
and cannot inform planning for short-term movements (Mateo-Sánchez et al. 2015), whereas
GPS data can include prolonged resting phases that obscure directed movement (LaPoint et
al. 2013; Péron 2019). Therefore, recent studies have explored opportunistic or movement-
proxy data, such as roadkill records, capture-recapture data, camera-trap detections, or direct
visual or acoustic movement observations (LaPoint et al. 2013; Shimazaki et al. 2016; Mimet
et al. 2020; Balbi et al. 2021; Gelmi□Candusso et al. 2025). While Mimet et al. (2020) and
Shimazaki et al. (2016) have taken the first steps in demonstrating how these datasets can be
used to derive model parameters, they are mostly reserved for post hoc validation (LaPoint et
al. 2013; Balbi et al. 2021; Gelmi□Candusso et al. 2025).

Integrating such movement-proxy data directly into model calibration offers a promising way
forward. Verbeylen et al. (2003) demonstrated the use of statistical model selection to test
multiple resistance scenarios and empirically identify those that best supported by data, but
did not use data that reflects actual movement. Using movement-proxy data could enable the
derivation of parameters that align with observed movement patterns and can flexibly
incorporate diverse data types. However, as emphasized by Habrich and Fahrig (2025),
ensuring that the biological process represented by the data matches the spatial and temporal
scale of the model is crucial for correct modelling results.

In this study, we extend the approach of Verbeylen et al. (2003) to develop an empirically
parameterized functional connectivity model for the common blackbird (*Turdus merula*) in
Munich, Germany. Using direct movement observations from urban field surveys as
movement-proxy data, we empirically estimate resistance and movement-distance parameters
through model selection. We analyse the spatial properties of these movements and adapt the
connectivity model to reflect them accurately. Because high-resolution tracking data were
unavailable for this species and region, we compared the empirically parameterized model to
an existing expert-based model (Ersoy et al. 2019). This comparison allows us to assess
whether empirical calibration improves ecological realism relative to the most widely applied
approach of expert parametrization. Finally, we discuss how incorporating movement-proxy
data into model parameterization can enhance the ecological realism and practical relevance
of functional connectivity modelling for biodiversity-informed urban planning.

2. Methods

2.1 Methods overview

When using empirical data to parameterize connectivity models, it is essential that both the spatial scale (e.g. home-range versus dispersal movements) and the modelled metrics (e.g. patch- versus path-based connectivity) correspond to the ecological processes represented by the data. In this study, we demonstrate how movement-proxy observations, presence or absence of moving individuals, can inform model parameterization when tracking data are unavailable. While detailing the use of model selection to identify the parameters best explaining the data, we also describe how we adapted the connectivity model to ensure that the spatial scales and modelled metrics fit the observation data used for parameterization.

Our workflow comprised six sequential steps, each linking a general modelling decision to a specific implementation in our study (Figure 1). (1) We identify the ecological processes represented by the observation data and the spatial scales at which they operate. (2) Based on this, we define suitable modelling resolution and movement extent. (3) We map resource locations representing potential destinations of movement. (4) We create alternative scenarios for landscape resistance and movement distance. (5) We build a graph-based connectivity model linking resource cells through least-cost paths calculated from the resistance scenarios and prune implausible links according to the distance scenarios. (6) We apply model selection to determine the combination of resistance and distance parameters that best explain the observed movement data. Finally, we compare the empirically calibrated model with an existing expert-based resistance model to evaluate improvements in predictive performance and ecological realism and perform several sensitivity analyses to identify the less robust steps in the modelling workflow. To assess model generality and robustness, we implemented repeated out-of-sample cross-validation, where the parameterization and validation were conducted on randomized subsets of the data.

Fig. 1 Conceptual workflow for empirical parameterization of a connectivity model and its adaptation to the home range connectivity of the blackbird. Each step (1–6) corresponds to a section of the Methods. The diagram illustrates how general modelling decisions (grey) were implemented through a combination of ecological reasoning (green) and statistical evaluation (blue). Each step ensures that the behavioural and spatial properties of the observation data (i.e. directed within-home-range movements) are reflected in the model structure and parameters. The workflow progresses from identifying the relevant movement process (Step 1) and spatial scale (Step 2), to mapping resources (Step 3), testing resistance and distance scenarios (Step 4), selecting the appropriate network metric (Step 5), and empirically determining resistance and distance parameters via GLMM-based model selection (Step 6). The final output is a fully parameterized, data-driven connectivity model aligned with the ecological processes represented by the observations.

181   Table 1: Definitions of the most important terms for model description and their variables.

Term	Definition	Variable
Resource cell	A pixel on the map that provides resources for the target species (e.g. food, shelter)	$R_l = 1$
Resource patch	Adjacent resource cells that allow individuals to move freely without encountering resistance	
Link	Connection between two nodes of the landscape graph	(A, B)
Resistance value	Quantified resistance to the movement of the target species through a cell	r_l
Path	A path p_{AB} between two nodes A and B is a line that traverses the resistance surface	p_{AB}
Cost distance	The cost distance d_{AB} of the path p_{AB} between two nodes A and B is the sum of all resistance cells traversed by path p_{AB}	d_{AB}
Least-cost path (LCP)	The least-cost path LCP_{AB} is the path p_{AB} between nodes A and B that minimizes the cost distance d_{AB}, i.e. the least-cost path LCP_{AB} is the path of lowest cumulative resistance between two nodes	$LCP_{AB} = \arg\min_{p \in \mathcal{P}_{AB}} d_{AB}(p)$ where $\mathcal{P}_{AB}$ is the set of all paths between nodes A and B
Node isolation distance	Maximum allowed cost-distance between two directly connected nodes	d_{iso}

Pruned graphs	Graph with links longer than node isolation distance d_{iso} removed	$L_{pruned} = \{(A,B) \in L \mid d_{AB}$
Pruning the longest lengths		

2.2 Data sources

2.2.1 Study area and species

Munich (48° 8' 23" N, 11° 34' 28" E, 529 m asl) is Germany's third-largest city with a
population exceeding 1.5 million and the highest population density among German
municipalities (5100 persons/km2 in 2022) (Stadtverwaltung, n.d.). Despite its urban
character, Munich's green spaces cover approximately 13.4% of the city's total area with the
English Garden encompassing 375 ha that connect the city center with outer areas
(muenchen.de, n.d.).

The common blackbird *(Turdus merula)*, an urban dweller frequently found in European
cities, was initially a forest species (Mohring et al. 2021). Blackbirds primarily feed on
earthworms, invertebrates, and fruits on the ground, in open areas or under canopies (Snow
1966, p. 19). Both males and females establish territories, with suitable nest-sites in trees or
shrubs being crucial for territory establishment (Snow 1966). The radius of home ranges for
male blackbirds in cities is up to 180 m, but it varies with sex and building density (Snow
1966; Ferry et al. 1981). Due to its distinctive look and song, the common blackbird is an
easily identifiable urban species and, therefore, an ideal study subject.

2.2.2 Movement-proxy and species occurrence data

We derived two distinct datasets on *T. merula* occurrence and movement to parameterize and
validate the connectivity model (Supplementary Information S1). The datasets differ in
behavioural interpretation and spatial sampling design (Table 1).

Dataset 1 comprises visual and acoustic detections representing general presence or absence
of blackbirds across the study area. These data were collected through random point
observations along gradients of traffic density and greenness and were used in Step 3 to
identify resource cells contributing to blackbird occurrence.

Dataset 2 includes observations of blackbirds flying across streets, i.e. locations offering no
foraging or nesting opportunities. These flight events were recorded along 10 × 60 m
transects and interpreted as directed movements between resource patches. Resources could
be nesting, roosting or foraging sites. The dataset was used in Step 6 to estimate resistance
values and typical movement distances via model selection. Also, this dataset was used in an
out-of-sample cross-validation to compare the performance of our empirically-driven
parametrization approach to an expert-driven approach.

Table 2: Overview of the datasets used in the parametrization and testing of the connectivity
model

	Dataset 1	Dataset 2
Data type	Presence/absence of blackbird in area	Number of moving blackbirds across street transect
Sampling of observation points	Random sampling along gradients of traffic density and greenness	Random sampling along gradients distance from city centre and greenness
# Data points	104 points	217 transects
Observed area	Point observations; perimeter of 50 m	Transect observations on 10 x 60 m transects across a street
Observation period	10 min	4 min
Observation	A trained ornithologist noted whether blackbird was seen or heard	Trained ecologists counted the number of blackbirds crossing the street
Use in modelling	*Step 3* – identification of used resources	*Step 6* – determination of best *node isolation* and *resistance scenario*

2.2.3 Land cover data

We obtained the following high-resolution remote sensing data from the Bavarian State
Office for Digitization, Broadband and Surveying (https://www.ldbv.bayern.de/index.html): a
digital elevation model at 1 m resolution, a surface model at 40 cm resolution, and color-
infrared orthophotos at 20 cm resolution. These were used to create a 40 cm resolution land
cover map for Munich in 2017. The map encompasses vegetation classes (grass, shrubs,
trees), building height classes (< 10 m, 10 – 18 m, > 18 m), streets, agricultural areas, and
water bodies (Supplementary Information S2). These land cover classes are the classes
typically considered to be most relevant for urban ecological connectivity modelling
(Pundsack et al. 2025).

2.3 Step 1) Define behavioural process

Data in Dataset 2 represent home-range movements, rather than long-distance dispersal.
Specifically, they capture directed flights between distinct resource patches located within an
individual's typical home-range extent. In this study, a *resource patch* is defined as a
continuously vegetated area that allows blackbirds to move freely under canopy or shrub
cover without encountering resistance from buildings or vehicular traffic.

These movements between resource patches correspond to the "transit" or "transfer" phase of
daily activity, connecting feeding, roosting, and nesting areas (Morales et al. 2004). Because
our observations only recorded individuals flying across streets between resource patches,
movements occurring entirely within a patch (e.g., short foraging or exploratory movements)
(Bailey et al. 1996) were not observed and therefore not modelled. These considerations
guided choices for movement scales, modelling resolution, and the choice of graph-based
metrics, all tailored to represent functional connectivity of resource patches within the home
range rather than dispersal connectivity at the population scale.

2.4 Step 2) Define spatial scale

2.4.1 Home range area

243 Estimates of common blackbird (*Turdus merula*) home range size in urban environments vary
244 between 80 m and 180 m in radius (Ferry et al. 1981; Török and Ludvig 1988; Snow 2008).
245 To represent the most intensively used core area of the home range, we set the home-range
246 radius to 100 m, which defined the search radius for identifying relevant resources in Step 3).

2.4.2 Maximum movement distance in connectivity model

248 To represent potential commuting movements within this home-range extent, we decided to
249 test potential movement distances of up to 150 m in the landscape graph (Step 4). This upper
250 limit allows for movements crossing substantial parts of the home range, while excluding rare
251 exploratory or dispersal events.

2.4.3 Spatial resolution of connectivity model

To balance ecological realism and computational efficiency, the original 0.4 m land-cover
data were aggregated to 10 m cells, calculating the proportion of each land-cover class per
cell. This resolution captures the fine-scale heterogeneity relevant to blackbird foraging and
movement decisions (e.g., shrubs, small lawns) while reflecting the species' perceptual and
locomotor scale (Supplementary Information S3). At this resolution, several resource cells fit
within a single home range, maintaining ecological detail while keeping model complexity
manageable.

2.5 Step 3) Identify resource locations

The first step in constructing the connectivity model was to identify which land-cover types
constitute relevant resources for the common blackbird (*Turdus merula*) and to map their
spatial distribution across the study area. This mapping defined the potential destinations of
movement and determined which cells could later serve as nodes in the landscape graph.

To identify resource types associated with blackbird occurrence, we used Dataset 1, which
contains presence/absence observations across urban gradients in Munich. We hypothesized
that specific vegetation features, such as trees, grass and shrubs, increase the probability of
blackbird presence, whereas impervious surfaces would have weaker or negative effects. For
each observation point, we calculated the proportion of tree, shrub, and grass cover within a
100 m radius, corresponding to the estimated home-range radius (Section 2.4).

We applied Classification and Regression Trees (CARTs) to model blackbird presence as a
function of these potential resource types. CARTs were chosen for their ability to handle

categorical response variables, non-linear relationships, and interactions among predictors,
while maintaining transparent and interpretable results (De'ath and Fabricius 2000; Bel et al.
2009). In contrast to more complex ensemble methods such as Random Forests, CARTs
allow clear ecological interpretation of threshold responses and are easily translated into
landscape classifications (Cutler et al. 2007; Pesch et al. 2011; Mimet et al. 2019). Model
performance was evaluated using a confusion matrix based on the training data.

Applying the fitted CART model to the complete study area identified areas where vegetation
cover exceeded the minimum resource requirements for blackbird occurrence. Given the
generally high vegetation cover in Munich, nearly all areas met these thresholds. We
therefore retained the entire city for connectivity modelling.

Within these suitable areas, we designated resource cells as all 10 m pixels containing at least
20 m² of the land cover identified as a resource according to the CART, following the
considerations of Bourgeois et al. (2024). For example, if the CART identified shrubs as an
important predictor for blackbird occurrence, all cells with a minimum shrub cover of 20 m^2
became graph nodes. The resulting resource map delineated the spatial distribution of
resource cells (R□ = 1) and non-resource cells (R□ = 0) and formed the foundation for
constructing the landscape graph described in Section 2.7.

2.6 Step 4) Resistance and movement-distance scenarios

Resistance values in connectivity models summarize multiple behavioural processes:
movement preferences, avoidance, energetic costs, perceptual limits, and mortality risk
(Zeller et al. 2012). We adopted a scenario-based parameterization combined with model
selection (Verbeylen et al. 2003). This approach tests multiple ecologically plausible
combinations of resistance and movement-distance parameters and identifies those that best
explain observed movement patterns (Dataset 2).

2.6.1 Resistance scenarios

We generated a set of candidate resistance maps $\mathcal{R}_1, \dots, \mathcal{R}_n$ by varying the resistance values
assigned to different land-cover types. In each scenario, resource cells identified in Section
2.5 were assigned a resistance value of 1, representing undisturbed movement. Vegetation not
classified as a resource, as well as agricultural and open water areas, were assigned a
moderate resistance of 10 to reflect their open and less structured nature (Tremblay and St.
Clair 2009). Because Dataset 2 contained few observation points near water bodies or
agricultural land, their influence on movement could not be estimated directly from the data;
therefore, their resistance values were defined a priori.

Anthropogenic structures such as streets and buildings were assumed to impose stronger
barriers due to increased predation risk, energetic cost, and reduced permeability (Tremblay
and St. Clair 2009, 2011; Shimazaki et al. 2016). We therefore assigned them resistance
values higher than those for vegetation, ranging from 10 to 1000 (Bourgeois et al. 2024). To
represent ecological realism, taller buildings were always assigned equal or greater resistance
than lower buildings, but no prior assumption was made about their resistance relative to
roads.

This factorial design yielded 24 distinct resistance scenarios, encompassing all combinations
of plausible relative resistance orders under these constraints. Each resistance map was
produced by summing the weighted contributions of land-cover types within each 10 m cell
of the land-cover map, yielding a continuous resistance surface consistent with the spatial
resolution defined in Section 2.4.

2.6.2 Movement-distance scenarios

We further defined a set of candidate node-isolation distances $D = \{30, 60, 90, 150 \text{ m}\}$,
representing the maximum distance over which direct movement between two resource cells
is assumed possible. These distances were selected based on reported within-home-range
movement distances and home-range radii of urban blackbirds (Ferry et al. 1981; Török and
Ludvig 1988; Cresswell 1999; Snow 2008).

Combined, these 24 resistance and four distance scenarios yielded 96 resistance-distance
scenarios tested through model selection (Section 2.8).

2.7 Graph-based connectivity model

2.7.1 Step 5) Define node

To represent fine-scale functional connectivity within blackbird home ranges, we
implemented a cell-based landscape graph rather than a traditional patch-based approach. In
patch-based graphs, multiple contiguous resource cells are aggregated into single habitat
patches, and movement is assumed to occur only between their edges. By contrast, in a cell-
based graph, each resource cell acts as an individual node, and movements can occur both
within and between resource clusters (Table 1) (Figure S3). This finer spatial representation
allows for a more continuous depiction of potential movement pathways (Drielsma et al.
2007; Saura and Pascual-Hortal 2007).

Cell-based graphs are particularly suitable for representing within-home-range movements,
such as the directed flights observed in our data (Dataset 2). These movements typically
connect nearby resource sites, trees, shrubs, or small vegetation patches, across short
distances (tens to hundreds of metres) and through partially permeable barriers like streets or
courtyards. Aggregating these features into large patches would obscure the fine-scale
resource heterogeneity and redundant paths between patches available to individuals. As
supported in recent studies (Goicolea et al. 2021; Van Moorter et al. 2023), such redundant
pathways are a critical feature of realistic connectivity models, as they reflect the diversity of
movement choices animals can make within complex landscapes.

Nodes in our graph corresponded to resource cells identified in Section 2.5. The 10 m grid
resolution (Section 2.4) thus defined both the spatial extent and size of individual nodes.

2.7.2 Step 7) Modelling framework

To represent potential movement routes between resource cells, we applied the least-cost path
(LCP) framework (Adriaensen et al. 2003). LCPs estimate the route between two locations
that minimizes the cumulative resistance, defined as the total "cost distance" d_{AB} across all
traversed cells (McClure et al. 2016). This approach assumes that animals move through their
familiar environment in a manner that minimizes energetic expenditure and exposure to risk,

selecting paths of lowest cumulative cost (McClure et al. 2016). In our case, this approach is
particularly appropriate because long, directed home-range movements, such as those
observed for blackbirds moving between resource sites within their territory, occur within a
well-known spatial context. Individuals are likely to rely on spatial memory to optimize
travel routes, avoiding energetically expensive or dangerous areas such as roads and built
structures (McClure et al. 2016; Blazquez-Cabrera et al. 2016). Unlike circuit-theory
approaches, which simulate undirected random walks and are better suited to dispersal-scale
movement (McRae 2006), LCPs explicitly represent directed movements that link known
resource locations.

In graph-based connectivity models, including all possible links between nodes can result in
unrealistic or biologically implausible movement pathways, particularly when modelling
movements that occur within an animal's home range. Animals typically move between
nearby resource sites or "stepping stones" and avoid long, exposed crossings without cover
(Bélisle and Desrochers 2002). Consequently, unrestrained link generation may create paths
that greatly exceed the spatial extent of realistic movements, thereby inflating connectivity
estimates and computational demands (Mimet et al. 2016). Following established practice in
landscape graph analyses (Foltête et al. 2012b), all links with a cumulative cost distance
$d_{AB} > d_{\mathrm{iso}}$ were removed from the graph.

From each set of least-cost paths generated under the 24 resistance scenarios (Section 2.7.2),
we constructed four pruned graphs. Each graph corresponded to one of the four candidate
movement distances: 30, 60, 90, and 150 m, reflecting the range of empirically plausible
within-home-range movement distances for urban blackbirds.

2.7.3 Step 7) Connectivity metric

We computed the link-based Betweenness Centrality (BC) that identifies the edges most
central to the network's overall flow, i.e. those expected to be traversed most often under the
least-cost assumptions (Girardet et al. 2015). Because our empirical data capture movements
between resource patches (Dataset 2) rather than occupancy or activity within patches, link-
based metrics are most appropriate for reflecting the ecological process under study (Girardet
et al. 2015). If observations were limited to presence or absence within patches, node-based
metrics could more directly represent connectivity. Formally, for a given link l, BC is defined
as

$$BC(l) = \sum_{A=1}^{N} \sum_{B=1, B>A}^{N} \mathbf{1}_{l \in L_{AB}} \, e^{-\alpha \, d_{AB}} \tag{1}$$

384 Where L_{AB} is the set of links traversed by the least-cost path between nodes A and B and the
385 indicator function $\mathbf{1}_{l \in L_{AB}}$ ensures that only links occurring on the path are included. The
386 weighting term $e^{-\alpha d_{AB}}$ reflects movement probability along the path with cost distance d_{AB} ,
387 with the decay parameter α defined as:

$$\alpha = \frac{-\log(\varphi)}{d_{iso}} \tag{2}$$

so that movement probability drops to φ at node isolation d_{iso} (Bodin and Saura 2010).
Typical values for φ are 0.05 or 0.01 (Bodin and Saura 2010).

The graph-based model was constructed using the Graphab 2.8 software (Foltête et al. 2012a)
via the graph4lg R package v. 1.8 (Savary et al. 2023). For each combination of resistance
and movement distance, we generated least-cost graphs and calculated link-based BC values.
To parameterize the connectivity model using statistical model selection, it was necessary to
obtain continuous connectivity values for all parts of the study area. (Foltête et al. 2012b).
Therefore, we interpolated the BC values from links by adapting Graphab's interpolation
workflow to a continuous surface representing the entire landscape.

2.8 Step 8) Calibrate model parameters

2.8.1 Model selection

To empirically determine the most plausible resistance values and movement distances, we
applied a model selection procedure comparing the predictive performance of connectivity
maps derived from different combinations of resistance and node-isolation scenarios
(Verbeylen et al. 2003). For each combination of resistance scenario R_k and node isolation
distance d_l, we constructed a corresponding landscape graph and generated a continuous
connectivity map $BC^{(k,l)}(x,y)$ (Section 2.7.5). This parameterization procedure was repeated
within each out-of-sample training subset of the validation (Section 2.9), ensuring that
resistance and movement parameters were estimated independently for every training–test
split.

From these maps, we extracted connectivity values $BC^{(k,l)}(x_i, y_i)$ at the observation locations
where blackbird movements were recorded (Dataset 2). Each observation represented the
presence (1) or absence (0) of movement across a street segment. The probability of
observing movement at each location was modelled as a function of the predicted
connectivity and relevant local covariates using the following generalized linear mixed model
(GLMM):

$$PA_{movingBird} = \log(connectivity + 1) \\ + resources + pedestrians \\ + (1|observer) \tag{3}$$

where connectivity is the mean interpolated BC value within the observation transect,
resources the proportion of resource cells, and pedestrians the number of pedestrians counted
during data collection. We accounted for the number of pedestrians during observation to
capture the disturbance that the flying blackbirds could experience, which is not directly
covered by the sources of resistance in the connectivity model. The random intercept for
observer accounts for potential observer-related variation in detection.

Model fitting was conducted in R using the lme4 package (Bates et al. 2015). We used
DHARMa (Hartig 2022) to test for outliers, overdispersion, zero inflation and
homoscedasticity.

2.8.2 Best resistance and movement distance values

To identify the combination of resistance and node isolation distance that best predicted observed blackbird movements, we compared all 96 GLMMs (24 resistance scenarios × 4 isolation distances) using the Akaike Information Criterion (AIC) (Verbeylen et al. 2003). The most parsimonious parameter set $(\mathcal{R}_{k*}, d_{l*})$ minimized the AIC across all models. Within each repetition of the out-of-sample cross-validation, the best-performing parameter combination was recorded, and resistance and distance values were averaged across the top-ranked models before validation. This procedure allowed us to determine which combination of resistance and distance values provided the best fit to the empirical movement data, thereby directly estimating parameter values rather than validating pre-defined ones.

Because model uncertainty may remain when several parameter combinations perform similarly well, we applied an evidence-based model averaging approach. All models within a $\Delta\text{AIC} \leq 2$ of the best-performing model were considered statistically equivalent with differences in statistical performance being too low to identify one best model (Grilo et al. 2011). To account for model selection uncertainty, we averaged the resistance and node-isolation distance values across these top-ranked models, following the principle of AIC-based model averaging (Anderson and Burnham 2002):

$$\overline{\mathcal{R}} = \frac{1}{N} \sum_g \mathcal{R}_{k_g}, \overline{d}_{iso} = \frac{1}{N} \sum_g d_{l_g} \tag{4}$$

where g indexes the models within the $\Delta\text{AIC} \leq 2$ range and N is their number. This approach provides parameter estimates that are less sensitive to small variations in data and more robust to the choice of any single best-fitting model (Anderson and Burnham 2002). The resulting averaged resistance map $\bar{\mathcal{R}}$ and isolation distance $\bar{d}_{iso}$ represent the empirically derived parameterization that best explained the observed movement probabilities.

2.9 Validation and model comparison

2.9.1 Monte Carlo cross-validation

To evaluate the predictive performance and robustness of the empirically parameterized connectivity model, we implemented a repeated out-of-sample validation (also known as Monte Carlo cross-validation). Prior to the final model validation, we assessed the robustness of the parameterization to varying data sizes by repeating the full procedure with 33 % and 66 % of the total Dataset 2 (Supplementary Information S4). Parameter estimates for resistance and movement distance remained consistent across these reduced-sample analyses, indicating that the calibration approach is stable even with substantially fewer data points. Based on this robustness, we opted for a 50:50 train–test split in the repeated out-of-sample validation. This design provides a larger independent test set, thereby reducing the influence of individual or spatially clustered observations on validation outcomes while maintaining sufficient data for reliable parameter estimation.

The full dataset of movement observations was randomly partitioned ten times into training (50 %) and test (50 %) subsets. In each repetition, the complete parameterization procedure (Sections 2.6–2.8) was applied exclusively to the training data to derive resistance and node-

isolation parameters. These parameters were then used to construct a connectivity model and generate an interpolated Betweenness Centrality (BC) map, which was evaluated against the independent test data. This repeated random-subsampling approach provides robust estimates of model performance and parameter stability while avoiding over-fitting to a single partition of the data.

For the withheld test data, mean BC values were extracted at each observation transect, and the probability of observing blackbird movement was predicted using the GLMM already used for parametrization (equation 3). Predictive accuracy was quantified by the area under the receiver-operating-characteristic curve (AUC) using the pROC R package (Robin et al. 2011) and by R^2 from glmmTMB package (Brooks et al. 2017), computed for each repetition (Grilo et al. 2011). The ten repetitions hence provided independent estimates of model performance and variability arising from data partitioning.

2.9.2 Comparison with expert-based model

We further compared our empirically parameterized model with an expert-driven model for the common blackbird published by Ersoy et al. (2019). Based on their expert-derived resistance values (resistance = 1 for trees and shrubs, resistance = 25 for all other land-cover classes), we created a corresponding resistance map for Munich. To isolate the effect of resistance values while keeping all other parameters constant, we repeated our modelling workflow using the expert-derived resistance map of Munich but applied the node-isolation distance identified from our data-driven parameterization within the same repetition. Otherwise, we strictly followed our modelling workflow as described in section 2.7. This comparison directly quantifies the added predictive value of empirically derived resistance values relative to expert-defined ones.

2.9.3 Performance metrics and synthesis

For each repetition, we summarized model performance by reporting AUC and R^2 values for (1) the model with expert resistance and (2) our full empirically-derived model. The resulting distributions across the ten repetitions provided a measure of both the consistency and magnitude of these performance differences. Finally, the resistance values and node-isolation distances estimated across all repetitions were averaged to obtain a final, data-driven parameter set used for generating the overall connectivity map presented in Section 3.

2.10 Sensitivity analyses

Sensitivity analyses were conducted to identify parameters that strongly influence the outcome of the connectivity modelling (Cariboni et al., 2007; Rayfield et al., 2010). We evaluated the robustness of the parametrization procedure to changes in the home-range radius used for resource identification and the spatial resolution of the input data (Supplementary Information 6). o test the effect of home-range definition, we repeated the CART analysis using radii of 80 m and 120 m instead of 100 m. To evaluate the influence of spatial resolution, we compared the selection of model parameters obtained at modelling resolutions of 6 m and 20 m.

3. Results

3.1 Results of data-driven connectivity model

3.1.1 Resource identification

The CART analysis predicting blackbird occurrence from resource cover achieved a prediction accuracy of 0.82 and a Kappa value of 0.57, indicating good model performance beyond random expectation (Donker et al. 1993). Blackbird occurrence increased with tree cover exceeding 16% or shrub cover above 1.7% within a 100 m radius. Grass cover showed no significant relationship with occurrence (Supplementary Information S5). The results were robust to alternative home range radii (80 m, 120 m), with trees and shrubs consistently identified as key predictors of occurrence.

3.1.2 Parameterization of resistance and movement distance

Mean node isolation distances and resistance values were obtained by averaging across the best models within $\Delta AIC < 2$ per repetition. The resulting mean node-isolation distance was 83 m, corresponding to the typical range of long, directed movements within blackbird home ranges. Empirically derived resistance values indicated that high-rise buildings posed the strongest barrier to movement (mean resistance = 427), followed by medium-rise buildings (128). Low buildings had a mildly higher resistance (56) than streets (52). These results suggest that among the urban land cover types, especially high and medium-sized buildings differ in their resistance to blackbird movement relative to low buildings and streets. This relative difference was not accounted for by the expert-based resistance (Ersoy et al. 2019). Additionally, all empirically derived resistances were higher than the expert-based values (25) reported by Ersoy et al. (2019).

The relative order of resistance values was additionally supported by the frequency with which different resistance maps were selected. Model selection frequencies revealed high consistency for tall buildings, where most top models supported very high resistance (1000) and few supported lower values. For medium buildings, intermediate to high resistance (100–1000) was most frequently selected. Resistance of streets and low buildings exhibited greatest uncertainty, with values of 10, 100, and 1000 all appearing among the best models (Figure 2a). Node-isolation distances were also variable with highest frequency of intermediate movement distances (Figure 2b).

531
Fig. 2 Empirically derived movement parameters for the common blackbird (*Turdus merula*)
across ten out-of-sample cross-validation repetitions. (a) Mean resistance values (± SD) for
the four urban land-cover classes included in model calibration, displayed on a logarithmic
scale. (b) Mean node-isolation distance (± SD) representing the spatial scale of movement
most consistent with the observed street-crossing data. Individual points indicate values
estimated for each repetition. The dashed line in panel (a) marks the uniform resistance value
(25) used in the expert-based model of Ersoy et al. (2019).

3.1.3 Spatial patterns of connectivity

539
The resulting connectivity map (Figure 3c) showed high connectivity in rural areas and
suburban zones with dense shrub and tree coverage. Additionally, connectivity was high
around the large green spaces and rivers within the city centre, particularly within the English
Garden in Munich's northeast and along the Isar River in the southeast. However,
connectivity was lowest in the dense urban core characterized by tall buildings and
impervious surfaces. Agricultural areas at the city fringes also showed low connectivity.

Areas of low uncertainty in connectivity were primarily found where overall connectivity was
low, particularly within the dense urban core and the surrounding agricultural landscapes. In
contrast, highest uncertainty occurred where connectivity was concentrated along narrow or
isolated pathways, such as corridors crossing arable fields. In general, areas of high predicted

connectivity also exhibited greater variability among model runs. This mainly indicates that
the absolute magnitude of connectivity in these zones may be uncertain. Nevertheless, their
relative importance as movement corridors remains robust.

Fig. 3 Land cover, empirically derived resistance, and resulting connectivity surfaces for the
common blackbird (*Turdus merula*) in Munich, Germany, including associated uncertainty.
(a) Land-cover classification used for resistance parameterization and connectivity modelling,
with zooms showing suburban (yellow frame) and dense urban (black frame) areas. (b) Mean
resistance surface (left) and its coefficient of variation (right) across cross-validated models.
(c) Mean connectivity surface (left) and its coefficient of variation (right) across alternative
resistance and distance parameterizations. The coefficient of variation (CV) expresses the
relative variability among model outputs (CV = SD / mean), providing a normalized measure
of uncertainty. High CV values indicate areas where predicted resistance or connectivity is
most sensitive to model assumptions, while low values denote stable and robust estimates.

3.1.4 Model performance

Connectivity calculated from empirically derived parameters increased the probability of
observing blackbird movements across in nine out of ten validation repetitions (Figure 4).

The empirical model achieved a mean AUC of 0.76 (range 0.69–0.85) and a mean R^2 of 0.17
(range 0.02-0.32) across the ten repeated test-training splits, indicating acceptable to good
discrimination ability (Hosmer et al. 2013). In nine out of ten GLMMs, the coefficient for
log-transformed connectivity was positive, confirming that areas with higher modelled
permeability were more likely to contain movement observations. The mean effect size
corresponded to roughly a 13% in the odds of observing blackbird movement for each one-
unit increase in log(connectivity), highlighting a consistent positive association between
modelled connectivity and observed movement patterns. As shown in Figure 4, predicted
probabilities rose steadily with increasing connectivity, and while repetition-specific
responses varied in steepness, all but one showed a clearly positive trend.

Fig. 4 Relationship between empirically derived connectivity and blackbird occurrence
probability. Blue lines show predictions from each of the ten out-of-sample repetitions; the
black line shows the mean relationship.

3.2 Comparison with expert-based model

582
The repeated out-of-sample validation revealed that our fully empirical model performed
moderately better than the variant using expert resistance (Ersoy et al. 2019) (Figure 5). On
average, AUC and R^2 values were 0.012 higher for the empirical model than for the expert-
based model, indicating a small but consistent performance gain. This suggests that the
expert-based model also performs acceptably, but that the empirically-based model provides
additional information relevant to discriminate between areas of blackbird movement and
those without.

Fig. 5 Results of the repeated out-of-sample validation (Monte Carlo cross-validation) comparing empirical and expert-based connectivity models. (a) AUC and (b) R² values for the ten validation repetitions. The empirical model was parameterized using movement-proxy data, while expert-based models used resistance from Ersoy et al. (2019). Boxes indicate interquartile ranges and points represent individual validation repetitions.

4. Discussion

Our results demonstrate that empirically calibrating resistance and movement-distance parameters yields connectivity models that are ecologically consistent with observed movement behaviour and modestly outperform expert-based approaches in predictive accuracy. While the overall improvement in AUC and R^2 was moderate, the empirically parameterized approach provides a stronger process-based justification for the resulting resistance values and movement scales. The consistency of parameter estimates across repetitions further supports the robustness of the derived resistance maps, while the model selection framework allows the spatial delineation of areas with higher or lower confidence in simulated connectivity. Together, these results underscore the importance of data-driven calibration for enhancing the ecological realism, reproducibility, and interpretability of functional connectivity models in urban landscapes.

4.1 Ecological realism of empirically derived movement parameters

The empirically derived parameters are consistent with established knowledge of blackbird ecology, suggesting that the calibration procedure captured ecologically meaningful movement processes. The positive effects of shrubs and trees, but not grass, on blackbird occurrence align with previous studies from both rural and urban contexts (Mohring et al. 2021). The estimated node-isolation distance of approximately 80 m corresponds closely to the typical length of directed movements observed in wild blackbirds foraging or commuting between feeding and nesting sites (Török and Ludvig 1988; Cresswell 1999). Together, these findings suggest that the modelled movement scale accurately represents movements within the home range rather than long-distance dispersal.

Urban land-cover types differed markedly in their estimated resistance. High-rise buildings exhibited the strongest resistance to movement, followed by medium-rise and low buildings. This pattern implies that dense, vertical urban structures pose substantial barriers to blackbird movements. The high resistance could reflect increased energetic costs and mortality risks when crossing built-up areas. The results are consistent with previous studies showing that urban birds avoid highly sealed or exposed areas and that buildings inhibit movement more strongly than other sealed surfaces (Tremblay and St. Clair 2009; Balbi et al. 2021). The model selection procedure consistently assigned high resistance to tall and medium buildings, suggesting that these estimates are relatively robust across repetitions. In contrast, resistance values for streets were more variable. This variability could reflect the heterogeneity within the "street" class, which includes a broad range of sealed surfaces differing in traffic intensity and other disturbances. The validation of an urban connectivity model for passerines by Balbi et al. (2021) supports that streets of high traffic density have higher resistance to bird movement. Consequently, the model may have alternated between different resistance values for streets between repetitions, depending on the local characteristics of the training dataset.

Overall, empirically derived resistances were substantially higher than those that experts suggested for the *Turdus merula* in the study by Ersoy et al. (2019). This could indicate that

the expert map may have underestimated the difficulty of movement through built
environments and oversimplified the resistance values of different urban land covers. This
divergence highlights a key advantage of data-driven calibration: even for urban-tolerant
species such as the blackbird, expert judgement may yield overly optimistic assumptions
about matrix permeability. In contrast, empirically estimated resistance values better reflect
the actual behavioural constraints imposed by the urban matrix. The resulting resistance and
connectivity maps depict realistic spatial gradients in movement cost, with highest
permeability along vegetated suburban corridors, riparian strips, and large urban parks, and
lowest permeability in the dense city centre dominated by tall buildings and impervious
surfaces.

Model performance metrics further support the ecological plausibility of the empirically
parameterized model. The proportion of variance in movement probability explained by
connectivity is, for many repetitions, comparable to those reported for other urban species
using tracking data (Braaker et al. 2014). This confirms a good predictive capacity given the
complexity of behavioural data. Connectivity had a consistently positive effect on movement
probability across nine out of ten cross-validation folds, indicating that long, directed
blackbird movements between resource patches are shaped by both structural barriers and
resource distribution (Ersoy et al. 2019; Balbi et al. 2021). The model therefore captures key
ecological processes governing blackbird movement in urban environments and underscores
the importance of small-scale connectivity for maintaining functional movement pathways
under variable resource availability.

4.2 Comparison with expert-based model

Including the expert-based resistance map of Ersoy et al. (2019) within our model selection
procedure provided a direct empirical test of its performance compared to the approach
selected in many urban connectivity studies (Habrich and Fahring 2025). Across all cross-
validation folds, the expert resistance surface consistently produced higher AIC and lower R^2
values than the best-fitting empirical models, indicating a poorer fit to observed movement
data. This demonstrates that the expert-derived resistance values did not fully capture the
fine-scale behavioural constraints shaping blackbird movement in the urban matrix.

Under the repeated out-of-sample validation, the empirically parameterized model achieved
modestly higher AUC and R^2 values on average than the expert-based variants, suggesting
that empirical calibration not only improves ecological interpretability but also enhances
predictive capacity when evaluated under balanced data partitions. However, the difference in
performance was only modest. Possibly, the smoother gradients of the expert maps may have
generalized better to the data points included only in the test subset, while the empirically
derived resistances, although more behaviourally realistic, were more sensitive to the specific
spatial configuration of movement observations.

Taken together, these findings underline the complementary strengths of expert-based and
empirically parameterized approaches. Expert maps provide stable, generalized estimates of

urban permeability, while empirical calibration offers stronger process-based justification and
quantifies where expert assumptions deviate from observed behaviour. Integrating both and
using expert knowledge as an informed prior refined through empirical model selection can
yield connectivity models that are both generalizable and ecologically grounded.

4.3 Limitations

Our modelling framework demonstrates that movement-proxy data can provide meaningful
empirical information for calibrating urban connectivity models. The consistency of
parameter estimates across cross-validation folds indicates that the parameterization
procedure produces stable results even under varying subsets of data. This stability contrasts
with the stronger fluctuations observed in validation metrics and suggests that parameter
calibration may provide a more robust assessment of landscape permeability than single
validation tests, which are more sensitive to the specific configuration of observation points.
The ability to derive parameter uncertainty and to map areas of high and low model
confidence further strengthens the transparency and interpretability of the approach.

Nevertheless, several limitations must be acknowledged. The use of movement-proxy data
inherently introduces a degree of uncertainty regarding behavioural interpretation. Although
the dataset captured active movements across the urban matrix, it may still integrate multiple
behavioural states (e.g., commuting, foraging, or exploration), each associated with different
spatial scales and sensitivities to landscape features. However, during the modelling, we
strongly considered the spatial and behavioural properties inherent to our dataset and how to
correctly reflect them in the connectivity model to counteract one of the main weaknesses
outlined by Habrig and Fahrig (2025): the spatial mismatch between the model and the data
used for validating it. Since we selected streets as sampling locations for the movement
observations and the sampling season was before the juvenile dispersal, we were confident to
assume that the vast majority of observed movements were directed movements between
patches within the home range (McKellar et al. 2015; Dzialak et al. 2015).

A further limitation concerns the model's sensitivity to spatial resolution. When the resistance
surface was resampled at different grain sizes, the resistance estimates changed partially. This
scale sensitivity is consistent with earlier findings that connectivity metrics depend on spatial
resolution (Arponen et al. 2012), especially in highly urban areas (Lin et al. 2021).
Identifying an ecologically meaningful resolution that corresponds to the perceptual range
and movement scale of the focal species, therefore, remains a key requirement for robust
urban connectivity modelling (Schooley and Wiens 2003). During the use of connectivity
modelling and this parametrization procedure in particular, this could be addressed by
performing explicit sensitivity analyses, systematically evaluating how changes in spatial
resolution influence parameter estimates, model performance, and the resulting connectivity
maps. Such analyses would help determine the optimal resolution for balancing ecological
realism, computational efficiency, and transferability across spatial contexts.

The restricted number of parameter combinations tested is another limitation. While the
factorial design of resistance and distance values was sufficient to detect major patterns,
relevant intermediate combinations might not have been explored. A more continuous
parameter search, or Bayesian optimization, could help identify finer-scale optima and
improve model precision. Furthermore, the relatively coarse representation of some land-
cover classes, particularly "streets," likely contributed to the variability in resistance
estimates. Incorporating finer-grained information such as traffic density, noise levels, or
pedestrian intensity could yield a more realistic depiction of urban permeability (LaPoint et
al. 2015).

Finally, our empirical calibration does not replace individual-based movement data such as
GPS tracking or high-resolution telemetry, which remain the most direct means of
quantifying animal movement and behaviour. However, such data are often logistically
prohibitive or spatially limited. The strength of the presented approach lies in its ability to use
simpler, opportunistically collected movement observations to infer realistic resistance
patterns at a city-wide scale. By providing a transparent, statistically grounded framework for
parameter estimation and uncertainty assessment, the method complements traditional expert-
based and tracking-based approaches and can guide future data collection efforts toward
critical areas of uncertainty.

4.4 Outlook

This study demonstrates how empirically derived movement parameters can enhance both the
ecological realism and predictive ability of functional connectivity models in complex urban
landscapes. By integrating direct movement observations into model calibration, we move
beyond assumption-based parameterization and provide a transparent, data-driven framework
that links landscape structure to observed movement behaviour. The resulting model not only
performs better than expert-based approaches but also offers a stronger process-based
foundation and a quantifiable measure of parameter uncertainty – an essential feature for
applying connectivity models as decision-support tools in urban planning.

The methodological approach presented here is transferable to other species and cities,
provided that movement-proxy data are available or can be collected opportunistically. The
increasing availability of urban biodiversity observations through citizen science platforms,
automated sensors, and camera-trap networks offers new opportunities to derive empirical
resistance surfaces across taxa. Integrating these diverse data streams into statistical
parameterization frameworks could lead to a new generation of empirically grounded, multi-
species connectivity models that better capture the behavioural diversity of urban wildlife.

From an applied perspective, empirically parameterized connectivity models can inform the
spatial prioritization of green infrastructure by identifying corridors and stepping stones that
most effectively support functional movement. Integrating empirical calibration into the
urban landscape planning workflow offers a path toward more evidence-based, ecologically

meaningful connectivity assessments that align with international biodiversity and urban resilience targets.

References

Adriaensen F, Chardon JP, De Blust G, et al (2003) The application of 'least-cost' modelling as a functional landscape model. Landscape and Urban Planning 64:233–247. https://doi.org/10.1016/S0169-2046(02)00242-6

Anderson DR, Burnham KP (2002) Avoiding Pitfalls When Using Information-Theoretic Methods. The Journal of Wildlife Management 66:912. https://doi.org/10.2307/3803155

Arponen A, Lehtomäki J, Leppänen J, et al (2012) Effects of Connectivity and Spatial Resolution of Analyses on Conservation Prioritization across Large Extents. Conservation Biology 26:294–304. https://doi.org/10.1111/j.1523-1739.2011.01814.x

Bailey DW, Gross JE, Laca EA, et al (1996) Mechanisms That Result in Large Herbivore Grazing Distribution Patterns. Journal of Range Management 49:386. https://doi.org/10.2307/4002919

Balbi M, Croci S, Petit EJ, et al (2021) Least‑cost path analysis for urban greenways planning: A test with moths and birds across two habitats and two cities. Journal of Applied Ecology 58:632–643. https://doi.org/10.1111/1365-2664.13800

Bates D, Mächler M, Bolker B, Walker S (2015) Fitting Linear Mixed-Effects Models Using lme4. J Stat Soft 67:. https://doi.org/10.18637/jss.v067.i01

Bel L, Allard D, Laurent JM, et al (2009) CART algorithm for spatial data: Application to environmental and ecological data. Computational Statistics & Data Analysis 53:3082–3093. https://doi.org/10.1016/j.csda.2008.09.012

Bélisle M, Desrochers A (2002) Gap-crossing decisions by forest birds: an empirical basis for parameterizing spatially-explicit, individual-based models. Landscape Ecology 17:219–231. https://doi.org/10.1023/A:1020260326889

Blazquez-Cabrera S, Gastón A, Beier P, et al (2016) Influence of separating home range and dispersal movements on characterizing corridors and effective distances. Landscape Ecol 31:2355–2366. https://doi.org/10.1007/s10980-016-0407-5

Bodin Ö, Saura S (2010) Ranking individual habitat patches as connectivity providers: Integrating network analysis and patch removal experiments. Ecological Modelling 221:2393–2405. https://doi.org/10.1016/j.ecolmodel.2010.06.017

Bourgeois M, Boutreux T, Vuidel G, et al (2024) Assessing the strategic role of urban green spaces for habitat connectivity in multi-family residential plots. Urban Forestry & Urban Greening 99:128471. https://doi.org/10.1016/j.ufug.2024.128471

Braaker S, Kormann U, Bontadina F, Obrist MK (2017) Prediction of genetic connectivity in urban ecosystems by combining detailed movement data, genetic data and multi-path

787   modelling. Landscape and Urban Planning 160:107–114.
788   https://doi.org/10.1016/j.landurbplan.2016.12.011

789   Braaker S, Moretti M, Boesch R, et al (2014) Assessing habitat connectivity for ground-
790   dwelling animals in an urban environment. Ecological Applications 24:1583–1595.
791   https://doi.org/10.1890/13-1088.1

792   Brooks M E, Kristensen K, Benthem K J ,van, et al (2017) glmmTMB Balances Speed and
793   Flexibility Among Packages for Zero-inflated Generalized Linear Mixed Modeling.
794   The R Journal 9:378. https://doi.org/10.32614/RJ-2017-066

795   Calabrese JM, Fagan WF (2004) A comparison-shopper's guide to connectivity metrics.
796   Frontiers in Ecology and the Environment 2:529–536. https://doi.org/10.1890/1540-
797   9295(2004)002%255B0529:ACGTCM%255D2.0.CO;2

798   Convention on Biological Diversity Kunming-Montreal Global Biodiversity Framework
799   [Internet]. Conference of Parties to the UN

800   Cresswell W (1999) Travel distance and mass gain in wintering blackbirds. Animal
801   Behaviour 58:1109–1116. https://doi.org/10.1006/anbe.1999.1244

802   Croeser T, Garrard GE, Thomas FM, et al (2021) Diagnosing delivery capabilities on a large
803   international nature-based solutions project. npj Urban Sustain 1:32.
804   https://doi.org/10.1038/s42949-021-00036-8

805   Cutler DR, Edwards TC, Beard KH, et al (2007) RANDOM FORESTS FOR
806   CLASSIFICATION IN ECOLOGY. Ecology 88:2783–2792.
807   https://doi.org/10.1890/07-0539.1

808   De'ath G, Fabricius KE (2000) Classification and Regression Trees: A powerful yet simple
809   technique for ecological data analysis. Ecology 81:3178–3192.
810   https://doi.org/10.1890/0012-9658(2000)081%255B3178:CARTAP%255D2.0.CO;2

811   Donker DK, Hasman A, Van Geijn HP (1993) Interpretation of low kappa values.
812   International Journal of Bio-Medical Computing 33:55–64.
813   https://doi.org/10.1016/0020-7101(93)90059-F

814   Drielsma M, Manion G, Ferrier S (2007) The spatial links tool: Automated mapping of
815   habitat linkages in variegated landscapes. Ecological Modelling 200:403–411.
816   https://doi.org/10.1016/j.ecolmodel.2006.08.017

817   Dzialak MR, Olson CV, Webb SL, et al (2015) Incorporating within- and between-patch
818   resource selection in identification of critical habitat for brood-rearing greater sage-
819   grouse. Ecol Process 4:5. https://doi.org/10.1186/s13717-015-0032-2

820   Ersoy E, Jorgensen A, Warren PH (2019) Identifying multispecies connectivity corridors and
821   the spatial pattern of the landscape. Urban Forestry & Urban Greening 40:308–322.
822   https://doi.org/10.1016/j.ufug.2018.08.001

823   Ferry C, Frochot B, Leruth Y (1981) Territory and Home Range of the Backcap (Sylvia
824   Atricapilla) and Some Other Passerines, Assessed and Compared By Mapping and
825   Capture-Recapture. Studies in Avian Biology 119–120

Foltête J-C, Clauzel C, Vuidel G (2012a) A software tool dedicated to the modelling of
landscape networks. Environmental Modelling & Software 38:316–327.
https://doi.org/10.1016/j.envsoft.2012.07.002

Foltête J-C, Clauzel C, Vuidel G, Tournant P (2012b) Integrating graph-based connectivity
metrics into species distribution models. Landscape Ecol 27:557–569.
https://doi.org/10.1007/s10980-012-9709-4

Gelmi☐Candusso TA, Chin ATM, Ruppert JLW, Fortin M ☐J. (2025) Urban planning for
wildlife connectivity: A multispecies assessment of urban sprawl and SLOSS
renaturalization strategies. Journal of Applied Ecology 62:1007–1023.
https://doi.org/10.1111/1365-2664.70007

Girardet X, Conruyt-Rogeon G, Foltête J-C (2015) Does regional landscape connectivity
influence the location of roe deer roadkill hotspots? Eur J Wildl Res 61:731–742.
https://doi.org/10.1007/s10344-015-0950-4

Goddard MA, Dougill AJ, Benton TG (2010) Scaling up from gardens: biodiversity
conservation in urban environments. Trends in Ecology & Evolution 25:90–98.
https://doi.org/10.1016/j.tree.2009.07.016

Goicolea T, Gastón A, Cisneros-Araujo P, et al (2021) Deterministic, random, or in between?
Inferring the randomness level of wildlife movements. Mov Ecol 9:33.
https://doi.org/10.1186/s40462-021-00273-7

Grilo C, Ascensão F, Santos-Reis M, Bissonette JA (2011) Do well-connected landscapes
promote road-related mortality? Eur J Wildl Res 57:707–716.
https://doi.org/10.1007/s10344-010-0478-6

Habrich AK, Fahrig L (2025) Systematic Map of Urban Connectivity Research Reveals a
Dearth of Validation of Connectivity Estimates. Curr Landscape Ecol Rep 10:5.
https://doi.org/10.1007/s40823-025-00106-y

Hartig F (2022) _DHARMa: Residual Diagnostics for Hierarchical (Multi-Level / Mixed)
Regression Models_

Hosmer D, Lemeshow S, Sturdivant RX (2013) Assessing the Fit of the Model. In: Applied
Logistic Regression. John Wiley & Sons, Ltd, pp 153–225

Ives CD, Lentini PE, Threlfall CG, et al (2016) Cities are hotspots for threatened species: The
importance of cities for threatened species. Global Ecology and Biogeography
25:117–126. https://doi.org/10.1111/geb.12404

Kowarik I, Fischer LK, Haase D, et al (2025) Promoting urban biodiversity for the benefit of
people and nature. Nat Rev Biodivers. https://doi.org/10.1038/s44358-025-00035-y

LaPoint S, Balkenhol N, Hale J, et al (2015) Ecological connectivity research in urban areas.
Functional Ecology 29:868–878. https://doi.org/10.1111/1365-2435.12489

LaPoint S, Gallery P, Wikelski M, Kays R (2013) Animal behavior, cost-based corridor
models, and real corridors. Landscape Ecol 28:1615–1630.
https://doi.org/10.1007/s10980-013-9910-0

Lepczyk CA, Aronson MF, La Sorte FA (2023) Cities as sanctuaries. Frontiers in Ecol &
Environ 21:251–259. https://doi.org/10.1002/fee.2637

Lin Y, An W, Gan M, et al (2021) Spatial Grain Effects of Urban Green Space Cover Maps
on Assessing Habitat Fragmentation and Connectivity. Land 10:1065.
https://doi.org/10.3390/land10101065

Lookingbill TR, Minor ES, Mullis CS, et al (2022) Connectivity in the Urban Landscape
(2015–2020): Who? Where? What? When? Why? and How? Curr Landscape Ecol
Rep 7:1–14. https://doi.org/10.1007/s40823-021-00068-x

Lynch AJ (2019) Creating Effective Urban Greenways and Stepping-stones: Four Critical
Gaps in Habitat Connectivity Planning Research. Journal of Planning Literature
34:131–155. https://doi.org/10.1177/0885412218798334

Marselle MR, Lindley SJ, Cook PA, Bonn A (2021) Biodiversity and Health in the Urban
Environment. Curr Envir Health Rpt 8:146–156. https://doi.org/10.1007/s40572-021-
00313-9

Mateo-Sánchez MC, Balkenhol N, Cushman S, et al (2015) Estimating effective landscape
distances and movement corridors: comparison of habitat and genetic data. Ecosphere
6:1–16. https://doi.org/10.1890/ES14-00387.1

McClure ML, Hansen AJ, Inman RM (2016) Connecting models to movements: testing
connectivity model predictions against empirical migration and dispersal data.
Landscape Ecol 31:1419–1432. https://doi.org/10.1007/s10980-016-0347-0

McKellar AE, Langrock R, Walters JR, Kesler DC (2015) Using mixed hidden Markov
models to examine behavioral states in a cooperatively breeding bird. Behavioral
Ecology 26:148–157. https://doi.org/10.1093/beheco/aru171

McRae BH (2006) Isolation by resistance. Evolution 60:1551–1561.
https://doi.org/10.1111/j.0014-3820.2006.tb00500.x

Mimet A, Buitenwerf R, Sandel B, et al (2019) Recent global changes have decoupled
species richness from specialization patterns in North American birds. Global Ecol
Biogeogr 28:1621–1635. https://doi.org/10.1111/geb.12978

Mimet A, Clauzel C, Foltête J-C (2016) Locating wildlife crossings for multispecies
connectivity across linear infrastructures. Landscape Ecol 31:1955–1973.
https://doi.org/10.1007/s10980-016-0373-y

Mimet A, Kerbiriou C, Simon L, et al (2020) Contribution of private gardens to habitat
availability, connectivity and conservation of the common pipistrelle in Paris.
Landscape and Urban Planning 193:.
https://doi.org/10.1016/j.landurbplan.2019.103671

Mohring B, Brischoux F, Angelier F (2021) Vineyards, but not cities, are associated with
lower presence of a generalist bird, the Common Blackbird (Turdus merula), in
Western France. Avian Res 12:3. https://doi.org/10.1186/s40657-020-00239-0

Morales JM, Haydon DT, Frair J, et al (2004) Extracting more out of relocation data:
Building movement models as mixtures of random walks. Ecology 85:2436–2445.
https://doi.org/10.1890/03-0269

Péron G (2019) The time frame of home□range studies: from function to utilization.
Biological Reviews 94:1974–1982. https://doi.org/10.1111/brv.12545

Pesch R, Schmidt G, Schroeder W, Weustermann I (2011) Application of CART in
ecological landscape mapping: Two case studies. Ecological Indicators 11:115–122.
https://doi.org/10.1016/j.ecolind.2009.07.003

Pundsack M, Merkens L, Weisser WW, Mimet A (2025) A Copernicus pipeline to create a
highly resolved land cover map for modelling urban biodiversity in European cities.
MethodsX 103415. https://doi.org/10.1016/j.mex.2025.103415

Reed GC, Litvaitis JA, Callahan C, et al (2017) Modeling landscape connectivity for bobcats
using expert□opinion and empirically derived models: how well do they work? Anim
Conserv 20:308–320. https://doi.org/10.1111/acv.12325

Riordan□Short E, Pither R, Pither J (2023) Four steps to strengthen connectivity modeling.
Ecography 2023:e06766. https://doi.org/10.1111/ecog.06766

Robin X, Turck N, Hainard A, et al (2011) pROC: an open-source package for R and S+ to
analyze and compare ROC curves. BMC Bioinformatics 12:77.
https://doi.org/10.1186/1471-2105-12-77

Saura S, Pascual-Hortal L (2007) A new habitat availability index to integrate connectivity in
landscape conservation planning: Comparison with existing indices and application to
a case study. Landscape and Urban Planning 83:91–103.
https://doi.org/10.1016/j.landurbplan.2007.03.005

Savary P, Vuidel G, Rudolph T, Daniel A (2023) graph4lg: Build Graphs for Landscape
Genetics Analysis

Sawyer SC, Epps CW, Brashares JS (2011) Placing linkages among fragmented habitats: do
least-cost models reflect how animals use landscapes?: Least-cost modelling for
habitat linkage design. Journal of Applied Ecology 48:668–678.
https://doi.org/10.1111/j.1365-2664.2011.01970.x

Schooley RL, Wiens JA (2003) Finding habitat patches and directional connectivity. Oikos
102:559–570. https://doi.org/10.1034/j.1600-0706.2003.12490.x

Shimazaki A, Yamaura Y, Senzaki M, et al (2016) Urban permeability for birds: An
approach combining mobbing-call experiments and circuit theory. Urban Forestry &
Urban Greening 19:167–175. https://doi.org/10.1016/j.ufug.2016.06.024

Snow DW (2008) Territory in the blackbird Turdus merula. Ibis 98:438–447.
https://doi.org/10.1111/j.1474-919X.1956.tb01428.x

Snow DW (1966) The migration and dispersal of British Blackbirds. Bird Study 13:237–255.
https://doi.org/10.1080/00063656609476125

Taylor PD, Fahrig L, Henein K, Merriam G (1993) Connectivity Is a Vital Element of
Landscape Structure. Oikos 68:571. https://doi.org/10.2307/3544927

Török J, Ludvig É (1988) Seasonal changes in foraging strategies of nesting blackbirds
(Turdus merula L.). Behav Ecol Sociobiol 22:329–333.
https://doi.org/10.1007/BF00295101

Tremblay MA, St. Clair CC (2009) Factors affecting the permeability of transportation and
riparian corridors to the movements of songbirds in an urban landscape. Journal of
Applied Ecology 46:1314–1322. https://doi.org/10.1111/j.1365-2664.2009.01717.x

Tremblay MA, St. Clair CC (2011) Permeability of a heterogeneous urban landscape to the
movements of forest songbirds: Songbird movements in urban landscapes. Journal of
Applied Ecology 48:679–688. https://doi.org/10.1111/j.1365-2664.2011.01978.x

Unnithan Kumar S, Turnbull J, Hartman Davies O, et al (2022) Moving beyond landscape
resistance: considerations for the future of connectivity modelling and conservation
science. Landsc Ecol 37:2465–2480. https://doi.org/10.1007/s10980-022-01504-x

Van Moorter B, Kivimäki I, Noack A, et al (2023) Accelerating advances in landscape
connectivity modelling with the ConScape library. Methods Ecol Evol 14:133–145.
https://doi.org/10.1111/2041-210X.13850

Verbeylen G, De Bruyn L, Adriaensen F, Matthysen E (2003) Does matrix resistance
influence Red squirrel (Sciurus vulgaris L. 1758) distribution in an urban landscape?
Landscape Ecology 18:791–805.
https://doi.org/10.1023/B:LAND.0000014492.50765.05

Zeller KA, McGarigal K, Whiteley AR (2012) Estimating landscape resistance to movement:
a review. Landscape Ecol 27:777–797. https://doi.org/10.1007/s10980-012-9737-0