DrugHIVE: A Deep Hierarchical Variational Autoencoder for the Structure-Based Design of Drug-Like Molecules

Jesse A. Weller[1,2] and Remo Rohs[1,2,3,4,*]

[1]Department of Quantitative and Computational Biology, [2]Department of Physics and Astronomy, [3]Department of Chemistry, and [4]Thomas Lord Department of Computer Science, University of Southern California, 1050 Childs Way, Los Angeles, CA 90089

*Correspondence: rohs@usc.edu

ABSTRACT:

Rapid advancement in the computational methods of structure-based drug design has led to their widespread adoption as key tools in the early drug development process. Recently, the remarkable growth of available crystal structure data and libraries of commercially available or readily synthesizable molecules have unlocked previously inaccessible regions of chemical space for drug development. Paired with improvements in virtual ligand screening methods, these expanded libraries are having a significant impact on the success of early drug design efforts. However, screening-based approaches are limited in their scalability due to computational limits and the sheer scale of drug-like space. A method within the quickly evolving field of artificial intelligence (AI), deep generative modeling, is extending the reach of molecular design beyond classical methods by learning the fundamental intra- and inter-molecular relationships in drug-target systems from existing data. In this work we introduce DrugHIVE, a deep structure-based generative model that enables fine-grained control over molecular generation. We demonstrate DrugHIVE's capacity to accelerate a wide range of common drug design tasks such as de novo generation, molecular optimization, scaffold hopping, linker design, and high throughput pattern replacement. Our method is highly scalable and can be applied to high confidence AlphaFold predicted receptors, extending our ability to generate high quality drug-like molecules to a majority of the unsolved human proteome.

1. INTRODUCTION

Success in drug development depends largely on the quality of initial candidate molecules identified during the early drug discovery process[1,2]. Historically, a major obstacle to finding better candidates has been the limited size of drug-like molecular libraries which until recently have been limited to a few million compounds. In the last few years, the number of commercially available or readily synthesizable drug-like chemicals have grown into the billions of compounds[3–5], though this remains a miniscule fraction of the total drug-like chemical space—estimated to be as large as 10^{60} compounds[6]. Structure based virtual ligand screening (VLS) approaches have also been limited until recently to well below 10^7 compounds. With the advent of virtually enumerated libraries and fragment based virtual screening techniques[7,8], this capacity has increased into the billions and will possibly extend to the tera-scale in the near future[9]. These techniques are having significant impact in accelerating and lowering the cost of early drug discovery by drastically growing the initial candidate pool and mitigating the need for expensive large-scale high throughput screening (HTS). However, they still rely on the explicit enumeration of chemical libraries and therefore will not be trivially scalable to significant fractions of the almost infinite drug-like space[10]. Other critical steps in the early drug development process are limited due to their manual nature, such as the systematic modification of candidates during hit-to-lead optimization. Although progress has been made in leveraging computational tools applying structure-based drug design (SBDD)[11], these costly and time-consuming tasks still rely significantly on, and are therefore limited by, the expertise and

intuition of human intelligence[2]. Overcoming such limitations and expanding the reach of computational drug design to greater scales of chemical space will require new approaches.

Recent advances in artificial intelligence and generative modeling, which have yielded impressive results on a number of previously intractable problems in the biological sciences[12,13], provide a promising new approach. Rather than further optimizing the exhaustive search of chemical space, deep generative models are capable of learning distributions over molecular data and have already been successfully applied to large drug-like chemical datasets for de novo molecular generation[14,15]. Lately, efforts have turned toward modeling drug-target interactions by training models on datasets of ligand-bound receptor crystal structures[16–19]. By learning the joint probability distribution of ligands bound to their receptors, these models can generate new molecules conditioned on the receptor structure, effectively narrowing the regions of chemical space in which to search for new drugs. As the field progresses, generative models are being designed with new capabilities such as scaffold hopping, fragment growing, linker design, and molecular property optimization, all to better meet the needs of early drug design. Perhaps the most important benefit of the generative modeling approach is the capacity to generalize the drug-target interactions learned from existing data to new receptor structures. This is in stark contrast to the classical VLS and HTS approaches in which the significant time and cost of screening large molecular libraries must be repeated with each new target.

In this work, we propose DrugHIVE (Figure 1), a deep structure-based <u>Dru</u>g generating <u>HI</u>erarchical <u>V</u>ariational auto<u>E</u>ncoder. Unlike previous encoder-decoder models, our approach employs a hierarchical prior structure which represents more naturally the distribution of molecular structure space. The use of a hierarchical prior leads to the encoding of input molecular structures at varying spatial scales and enables the generation of new molecules with a high level of spatial control—a necessity for many drug design tasks.

Owing to its hierarchical structure, DrugHIVE can generate molecules in myriad ways. Here we demonstrate the capacity of DrugHIVE for performing a wide range of common drug design tasks. We show a vastly improved ability to optimize the drug-like properties and predicted affinity of molecules with the automated, multi-objective optimization of the FDA approved ACE inhibitor, Lisinopril. We demonstrate the design of a new ATM kinase inhibitor optimized for selectivity against the Vps34 kinase. We apply our model to the automated replacement of Pan-Assay Interference Compounds (PAINS) patterns, the linking of fragments from a fragment screening experiment, substructure optimization (scaffold hopping), and the growing of molecular structures (fragment growing). Finally, we demonstrate that our model can successfully generate and optimize ligands with improved predicted binding affinity for receptors using AlphaFold2 (AF) predicted structures, extending the limits of generative molecular design beyond the set of currently available crystal structures.

2. RESULTS

2.1. De Novo drug generation with prior sampling

DrugHIVE excels in generating new molecules with drug-like properties and a high predicted binding affinity for their target receptors. We test the ability of DrugHIVE to generate new candidate ligands for a set of 100 diverse receptors from the test dataset and compare the results against a random set of molecules from the ZINC drug-like subset (see Figure S2). For each receptor, we generate molecules by sampling randomly from the latent prior and then compute the estimated binding affinity and properties of each molecule. The molecules generated by DrugHIVE have lower

Figure 1: Overview of DrugHIVE. (a) Input data to the model can come from experimental structures, predicted structures, or drug-like molecule libraries**.** The model is trained on data from experimental structures and drug-like molecules. Generation can be performed using any of the three data types. **(b)** The prior of DrugHIVE has a hierarchical structure, with varying spatial scales being represented**. (c)** Molecular information is the input of the model in the form of multi-channel atomic density grids, with ligand grids input into the ligand encoder and receptor grids input into the protein encoder. Atomic occupancy (dark grey density) is represented at full grid resolution whereas atom type channels (colored density) are downsampled by a factor of 2 before being input into the network. **(d)** The DrugHIVE model is comprised of a ligand encoder, a protein encoder, and ligand decoder. Information from the protein encoder is passed into both the ligand encoder and decoder. **(e)** The model outputs atomic occupancy (full resolution) and atom type grids (half resolution) which are then fit with a molecular structure. First, atoms are fit to the atomic occupancy density and atomic types are assigned using the upsampled atom type density, then a bond fitting algorithm is applied to connect the atoms. Finally atomic positions and bond lengths are relaxed using force field optimization. (f) DrugHIVE can automate many common drug design tasks such as linker design, substructure modification (scaffold hopping), fragment growing, and pattern replacement.

predicted binding affinities, on average, than the ZINC molecules. Approximately 10.3% of the DrugHIVE generated ligands have a higher predicted affinity than the reference ligand. This is about double the value (4.6%) of a random sample of the ZINC dataset, which means that screening efficiency is significantly higher for DrugHIVE generated molecules. To further demonstrate, we generate 1000 molecules for the Rho-associated protein kinase 1 (ROCK 1) receptor (PDB ID 3WTJ), an important target with a documented role in cancer migration, invasion, and metastasis[20]. Approximately 12% of the generated ligands have a higher predicted binding affinity than the crystal ligand (RKI-1447), a Type I kinase inhibitor with reported IC50=14.5nM.

In Figure S1, we compare the properties of the reference ligands in the PDBbind[21] dataset and a random sample of the molecules from the ZINC[5] dataset with those of the generated ligands from DrugHIVE. The properties of the generated molecules fall well within the distributions of the training datasets, which is an indicator that the model effectively learns the training distributions. We also observe a significant distribution shift between the molecules generated with and without protein receptors, which indicates that the model is indeed conditioning on receptor information during generation.

2.2. Multi-objective optimization of drug properties via evolutionary latent search

DrugHIVE can generate new ligands with a high degree of control over similarity to a reference molecule using prior-posterior sampling (Figure 2d). Each ligand-receptor complex has a unique representation in the encoded latent space, so if we start with a given reference ligand latent representation (posterior) and interpolate toward a randomly sampled point (prior), the resulting molecules will have a higher average diversity and lower molecular similarity to the reference as we interpolate toward the prior sampled point (Figure 2e). Similarly, the distribution of binding affinities shifts away from that of the reference ligand and significantly widens (Figure 2f). Taking advantage of this high level of control over variation, we implement an evolutionary algorithm to search the latent space and optimize the properties of a reference molecule. In Figure 2a-c we show the optimization process for the ligand Lisinopril bound to the human angiotensin-converting enzyme (ACE) receptor (PDB ID 1O86).

In Figure 2a, we show the successful optimization of binding affinity (Vina), drug-likeness (QED), synthesizability (SA), and hydrophobicity (alogP) values. For QED, SA, and alogP, we perform multi-objective optimization by including binding affinity as a secondary target in the fitness function. We see a significant improvement for each target property, including a 44% improvement in predicted binding affinity for the best molecule despite the fact that Lisinopril, an FDA approved ACE inhibitor in humans used treat hypertension, heart failure, and myocardial infarction, has been shown to show strong inhibition of the target receptor, with a reported experimental K_i=0.27nM[22]. Further, we successfully increase the drug-likeness from a low value of 0.27 to a high value of 0.93 and a moderate synthetic accessibility score of 0.58 to a high value of 0.82, in both cases while simultaneously improving binding affinity. In Figure 2c, we first optimize the alogP value in the upward direction, beginning with the slightly hydrophilic Lisinopril (alogP=-0.73) and ending with a very hydrophobic molecule (alogP=6.78). We then take the resulting molecule and optimize the alogP value in the downward direction, reversing the process to result in a hydrophobic molecule (alogP= −1.56).

In Figure 2g, we show results from the generation and optimization of a set of ligands for selectivity toward the human ataxia-telangiectasia mutated (ATM) kinase and against the human vacuolar protein sorting (Vps34) kinase. It has recently been shown that ATM kinase is an important potential target for the treatment of Huntington's disease and that it is important for ATM inhibitors to exhibit high selectivity over Vps34[23]. We use DrugHIVE to generate an initial set of ligands for the ATM receptor (PDB ID 7NI5), which we then optimize for selectivity against the Vps34 receptor (PDB ID 4UWH). The results show considerable improvement of selectivity, with the best molecule having a significantly better binding affinity (Vina) score for ATM (−9.3 kcal/mol) compared to Vps34 (−6.1 kcal/mol). These experiments demonstrate that the latent encoding learned by DrugHIVE is a powerful representation of chemical space, enabling effective multi-objective optimization of molecular structures with a high degree of control.

Figure 2: Prior-posterior sampling and multi-objective evolutionary optimization. **(a)** Optimization of the drug molecule Lisinopril bound to the human angiotensin converting enzyme (ACE) receptor (PDB ID 1O86). (left) Boxplots showing the distributions of generated molecules at each optimization step. Each boxplot represents a distribution of 400 molecules. (right) Best molecule from optimization procedure and reported properties, with green text indicating successful improvement. **(b)** Initial molecule (Lisinopril) for the optimization process. **(c)** Optimization of hydrophobicity (alogP) in the downward direction. Starting point was the best molecule from the previous (upward) hydrophobicity optimization. **(d)** Plot of average diversity and similarity to reference molecule for molecules generated from a diverse set of 100 PDB structures (test set) at varying prior-posterior interpolation values. Blue dashed line: average diversity of the reference ligands in the test set. Black dashed line: average similarity of reference ligands in the test set. **(e)** The distribution of $\Delta Vina$ scores of generated ligands as a function of interpolation value. $\Delta Vina$ is calculated as the predicted affinity (*Vina*) score of the reference ligand minus that of the generated ligand. **(f)** Schematic of prior-posterior sampling procedure. **(g)** Generation of molecules with optimized selectivity for the human ataxia-telangiectasia mutated (ATM) kinase and against the human vacuolar protein sorting (Vps34) kinase. (left) Superimposed aligned structures of ATM (PDB ID 7NI5) and Vps34 (PDB ID 4UWH) kinases. (top-right) The best molecule from optimization procedure and reported properties. (bottom-right) Boxplots showing the distribution of selectivity ($\Delta Sel = Vina_{ATM} - Vina_{Vps34}$) of generated molecules at each optimization step.

2.3. Lead Optimization with Spatial Prior-posterior Interpolation

The hierarchical prior structure of DrugHIVE preserves spatial context and allows molecules to be spatially modified by applying prior-posterior sampling on a spatial subset of the latent representation (as shown in Figure 3b). To demonstrate, we apply this method to the common drug design problems of linker design, substructure modification (scaffold hopping), fragment growing, and molecular pattern replacement (see Figure 3a).

Linker Design—Fragment based screening is a common tool in the early drug discovery toolkit[24], the result of which is a set of relatively small molecular fragments with modest affinity for the target receptor. Given two or more such fragments, the challenge is to then connect the individual fragments into a coherent, high-affinity drug-like molecule. Ordinarily, this is a manual and time-consuming process, but we show that our model can be used to automatically connect a set of individual fragments as oriented in the target receptor. As an example (Figure 3a), we show that DrugHIVE successfully designs a molecular linker to connect the individual fragments from a screening

experiment for replication protein A (PDB ID 4LUV)[25]. The resulting ligands have a Vina score better than either of the individual fragments, with a significant proportion of high affinity candidates also having good drug-like properties with high QED and SA scores.

Fragment Growing—Another common drug design task is to take an existing molecule with modest binding affinity and grow the structure to improve its affinity for the target. Our model can be used to automatically design new substructures to add to an existing molecular structure. To demonstrate, we show that DrugHIVE successfully grows a molecule from a fragment screening experiment for replication protein A (PDB ID 4LUV)[25], significantly increasing its predicted binding affinity for the target receptor (see Figure 3a,d).

Substructure Modification (Scaffold Hopping)—A common drug optimization technique is the systematic replacement of either chemical scaffolds or R-groups on a candidate molecule in order to improve its properties or grow a candidate set[26]. Starting with the ligand (PDB ID 3JU) bound to the von-Hippel Lindau (VHL) tumor suppressor (PDB ID 4W9F), we show how automatic substructure optimization can be achieved using spatial prior-posterior sampling. We apply BRICS[27] decomposition to break the ligand, an agonist with reported $K_d = 3.27\mu M$[28], into molecular fragments. For each fragment, we generate a set of molecules for which we only modify the fragment substructure, leaving the rest of the molecule unchanged (see Figure 3a). For each of the BRICS fragments, we can then analyze the distribution of properties for the generated molecules to learn the contribution of each fragment to that particular property. In Figure 3c we show that, depending on which fragment is modified, there are significant differences in the effect on each of the properties ($\Delta Vina$, alogP, TPSA, QED). For instance, we can see that drug-likeness scores are improved only for fragment 2, and that modification of fragment 3 leads to the strongest decrease in hydrophobicity (alogP) values while having almost no effect on topological polar surface area (TPSA). We can also see that modification of fragment 1 leads to the strongest decrease in binding affinity score, while fragment 3 has relatively little effect.

Pattern Replacement—Given a molecular SMILES or SMARTS pattern, we can modify the molecular structure(s) corresponding to that pattern for a single molecule or a set of molecules, using DrugHIVE to generate a new set of molecules with the input pattern replaced. This functionality could be used to modify fragments with known toxic, promiscuous, or otherwise undesirable properties in existing or newly generated drug collections, mitigating the need to screen out candidates with otherwise promising qualities. One application of this is in the replacement of PAINS patterns, which are a set of molecular substructures shown to be correlated with false positive results in HTS assays[29]. It should be noted that these molecular patterns do not always lead to experimental interference and therefore screening decisions must be taken with some care[30]. To avoid both the risks of false positive experimental results and false negative screening decisions, we can simply replace all PAINS patterns in an existing collection using generative spatial modification. As an example, we apply this capability to modify all PAINS structures in a set of molecules previously generated for the peptide binding protein OppA (PDB ID 1B51). In Figure 3a, we show a collection of molecules resulting from replacing one query pattern. This pattern replacement function could be scaled to large collections of molecules, as the compute time per molecule is on par with fast virtual docking algorithms.

Figure 3: Spatial prior-posterior sampling. (a) Examples of substructure optimization (fragment hopping), linker design, fragment growing, and high throughput pattern replacement. Yellow highlighted region indicates the part of the molecule to be modified and blue highlighted region indicates the part to be retained. (b) Schematic of spatial prior-posterior sampling procedure. (c) Boxplots showing the distributions of properties for each of the modified fragments from the substructure modification experiment. Black dashed line: property value of initial molecule. (d) Boxplots showing the distribution of predicted binding affinity (Vina) scores for the generated molecules from the fragment growing (left) and linker design (right) experiments, with Vina score for individual fragments shown (black dashed lines).

2.4. Drug design for predicted target structures

DrugHIVE makes progress in overcoming a historical limitation of structure-based drug design, specifically the reliance on a high-resolution crystal structure of the target receptor, by generating high affinity molecules for receptors using only AlphaFold predicted structures. Protein crystal data is growing rapidly, with the number of deposited structures to the PDB averaging over 9,000 per year in the last decade[31]. Still, less than 20% of the human proteome is currently resolved[32]. Recently, the success of sequence-to-structure prediction models such as AlphaFold2[12] have provided high accuracy structures for previously unknown proteins, perhaps already filling in a majority of the missing structural data for foldable regions of the human proteome with high confidence structures[32]. To test the effectiveness of using predicted structures for generative drug design, we generate ligands for a test set of target receptors for which we have both the AF prediction and the PDB crystal structure. The process for AF target curation is outlined in Figure 4a. It is important to stress that no crystal structure alignment information was used in selecting the AF targets. Filtering is based solely on sequence alignment, to ensure adequate sequence similarity, and AF confidence score (pLDDT), to remove low confidence predictions.

We dock the AF-generated ligands into both the AF and crystal receptors and compare the binding affinity predictions to ligands generated for the PDB receptor. In Figure 4b, we show the distribution *ΔVina* scores for the AF and PDB generated ligands docked to corresponding PDB receptors. The range of affinities is very similar between the two sets, with a slightly better median value of the AF-generated ligands. The proportion of ligands with a better docking score than the crystal ligand is

around 20% for both sets, and slightly better for the AF generated ligands. We also show that there is good correlation between the Vina scores when docked to both the PDB and AF receptors for AF-generated ligands (*R*=0.8) and PDB-generated ligands (*R*=0.6).

Further, we show in Figure 4c that DrugHIVE can optimize the predicted affinity of ligands using the AF pocket. We run the optimization process beginning with Lisinopril placed in the AF predicted structure corresponding to PDB ID 1O86, resulting in a molecule with a similarly high predicted binding affinity compared to the same optimization process using the PDB pocket (Figure 2a). We then docked all molecules generated during the optimization process into the PDB pocket and calculated the Pearson correlation coefficient for the two sets of affinity scores. The correlation is high (*R*=0.8), with the AF-docked scores consistently underestimating the PDB-docked scores—a bias that is exaggerated for higher affinity ligands. Despite this underestimation, the high correlation allows for the DrugHIVE optimization process to significantly improve binding affinity scores of the initial ligand.

Figure 4: Molecular generation using AlphaFold predicted structures. (a) Overview of the pipeline for creating the dataset of AlphaFold (AF) test structures. **(b)** Comparison of AF-generated molecules with crystal structure (PDB) generated molecules. (left) AF-generated molecules receive slightly better predicted binding affinity scores compared to PDB-generated molecules, with a larger portion of high affinity molecules (predicted affinity better than crystal ligand). (right) Scatterplots showing significant correlation for predicted *Vina* scores between molecules docked to AF and PDB structures. The AF-generated molecules receive a slightly higher Pearson correlation (*R*=0.8) compared to the PDB-generated molecules (*R*=0.6). **(c)** Evolutionary molecular optimization of the drug Lisinopril bound to human angiotensin converting enzyme (ACE) receptor (PDB ID 1O86) using the AF-predicted receptor structure. (top left) The best molecule from optimization process along with reported properties. The predicted binding affinity for the PDB receptor is shown. (bottom) Boxplots showing the distributions of *Vina* score for molecules at each step of the optimization process docked to the AF and PDB receptors. (top-right) Scatterplot showing a high correlation (Pearson *R*=0.9) between AF and PDB docking scores for all molecules from the optimization process. **(d)** Random examples of molecules generated for PDB ID 1CET using the PDB receptor (green) and the AF receptor (magenta). All molecules are displayed in the PDB receptor.

3. DISCUSSION

We introduce DrugHIVE, a new approach to the structure-based design of drug-like molecules based on a deep hierarchical variational autoencoder architecture. Our motivation in designing DrugHIVE was based on the observation that, even though molecular systems clearly possess structure and properties at varying spatial scales, previous encoder-decoder models have failed to adequately capture these relationships. DrugHIVE's hierarchical prior enables the model to better learn the distribution of intra- and inter-molecular relationships and generate high affinity drug-like molecules with an unprecedented degree of spatial control. In particular, DrugHIVE displays an impressive ability to optimize the properties of molecules over a wide range of values within the context of a protein receptor by performing local exploration of the latent space.

Beyond finding a more natural representation of chemical space, our second motivation in designing the model was improving practical applicability for drug-design tasks. Many tasks in early drug design are time consuming and rely significantly on the intuition and expertise of researchers. While such expert knowledge will always be a crucial part of the process, generative models can help speed up cycle times by automating the modification and de-novo design of molecular structures. In this work, we show how DrugHIVE can be used to perform rapid and effective linker design, scaffold hopping, fragment growing, and high throughput pattern replacement—all of which ordinarily require careful expert attention. Currently, DrugHIVE can only generate molecules that fit within the input density grid, which limits its applicability to larger molecules. The grid width that we chose (24 Å) fits most drug-like molecules, but extending this approach to larger structures quickly grows the computational requirements. Our dual-resolution implementation mitigates this issue significantly, but grids larger than 48 Å would still require expensive multi-GPU training. Although we think that the space-filling property of the grid-based representation has significant advantages, other generative methods such as graph and point-cloud based models are being developed to avoid these limitations[15,16,18].

DrugHIVE demonstrates that generative models provide an exciting new avenue for expanding our reach into the vast drug-like chemical space, the majority of which is unexplored and inaccessible. For the 100 diverse protein structures in our test dataset, 10.3% of the molecules DrugHIVE generates have a predicted affinity higher than that of the crystal ligand—significantly higher value than the 4.6% observed for a randomly chosen ZINC screening set. This means that performing hit identification by screening generated molecules already surpasses the efficiency of current screening datasets and will surely improve as the field progresses. Additionally, none of the generated molecules exist in the training dataset, which means that DrugHIVE can access previously unexplored regions of chemical space. The synthesizability of generated molecules does appear to be lower than that of current screening libraries, which is a significant practical factor in successful hit identification. This is partly due to the relatively low synthesizability of crystal ligands compared to that of drug-like molecule collections—especially those collections built from chemical synthesis enumeration such as REAL[4]. Future work to improve synthesizability of generated molecules could significantly improve their utility for hit identification.

DrugHIVE is not limited to existing crystal structures. Even though recent work has called into question the utility of using AF predicted structures in drug design applications[33], our experiments show that molecular generation with DrugHIVE using AF structures does generalize well to PDB structures. We show that over 20% of ligands generated for a diverse set of AF predicted structures have higher predicted affinities than the crystal ligand when docked to the PDB crystal structure, with a high correlation between docking scores (R=0.8). Further, we show that optimization of binding affinity using the AF predicted structure yields molecules with significantly improved predicted

binding affinities for the PDB structure. This means in the case where the crystal structure is not available, docking to a high-confidence AF structure should give a rough estimate of the crystal structure docking score—though not necessarily the correct binding pose. The implications are significant given that 58% of the human proteome residues, and perhaps all of the remaining foldable regions without crystal data, are currently predicted with high confidence by AlphaFold2[32,34]. Finally, it is important to note our model is agnostic to docking algorithms, so as virtual docking methods improve, so will the performance of DrugHIVE in many drug design tasks.

By developing a model with more fine-grained control over molecular generation, we hope to accelerate the impact of generative models on early drug discovery. We demonstrate the great potential that generative models have for automating a wide array of design tasks. Further progress and widespread adoption of these methods has the potential to significantly accelerate and lower the cost of pre-clinical trials drug development. With an estimated cost of $0.04 to $0.20 per thousand generated molecules at current cloud computing rates, on par with current high-throughput virtual screening methods, DrugHIVE is a powerful and scalable tool for automated structure-based drug design.

4. METHODS

4.1. DrugHIVE model

The DrugHIVE model is illustrated in Figure 1. Input molecules are first converted to molecular density grids, where each atom is represented by a multi-channel pseudo-Gaussian density and each channel represents a different atomic feature. For each atom, an identical atomic density is placed in each grid channel corresponding to its features—similar to Ragoza et al.[17]. In this work, we use a total of 15 feature channels: 9 atomic elements (C, N, O, F, P, S, Cl, Br, I) and 6 other atomic features (H-bond donor, H-bond acceptor, aromaticity, positive charge, neutral charge, negative charge). The molecular grid is input into the network via two pathways (Figure 1c). A single-channel full resolution grid, representing atomic occupancy, is input into the top of the network. All other atomic feature channels are downsampled by a factor of two and input into the network after the first downsampling layer. Model outputs mirror this arrangement. By segregating occupancy from atomic features in this fashion, we retain atom position information while significantly decreasing grid sparsity and memory load.

The DrugHIVE model (Figure 1d) is based on the hierarchical variational autoencoder (HVAE) architecture[35–37]. The goal is to learn the distribution of ligand density conditioned on receptor density from the dataset. However, unlike for a standard VAE, the latent representation of an HAVE naturally retains spatial context (Figure 1b). Therefore, we have a generative model of the form $p(D_{lig}, D_{rec}, \mathbf{z}) = p(\mathbf{z})p(D_{lig}|\mathbf{z}, D_{rec})$, where $p(D_{lig}|\mathbf{z}, D_{rec})$ is the likelihood function (decoder), the prior is represented as $p(\mathbf{z}) = \prod_i p(z_i|z_{<i})$ and the approximate posterior as $q(\mathbf{z}|D_{lig}, D_{rec}) = \prod_i q(z_i|z_{<i}, D_{lig}, D_{rec})$. We represent the likelihood function and approximate posterior as neural networks p_θ and q_ϕ, respectively. The latent representation is a set of variables partitioned into a set of disjoint groups $\mathbf{z} = \{z_1, ..., z_n\}$ where each group is conditioned on the lower groups in the hierarchy, $z_i \sim q(z_i|D_{lig}, D_{rec}, z_{<i})$. Because the individual latent variables retain spatial context at varying resolutions (as shown in Figure 1b), we hypothesize that the structure of the latent space is a better reflection of molecular structure space.

4.2. Atom fitting

The output of our model is a molecular density grid which must then be mapped to a molecular structure (Figure 1e). To achieve this, we employ custom atom-fitting and bond-fitting algorithms. The atom-fitting algorithm first iteratively places atomic coordinates within the grid with the goal of minimizing the residual density,

$$C_{fit} = \arg\min_{C} \left\| D_{occ,gen} - d(C) \right\|^2 \tag{1}$$

where $D_{occ,gen}$ is the predicted atomic occupancy density and d is the mapping from coordinates to density grid D. Next, atomic features are assigned to each atom using the density in the upsampled atomic feature grid. Atomic number is assigned to the highest density value across all atomic number channels at each atom location. The remaining atomic features are assigned based on a density threshold value, with disputes between conflicting features (e.g., formal charge $\pm$ 1) resolved by selecting the feature with the highest density value. Next, bonds are added based on the geometry and features of the atom set, similar to Ragoza et al.[17], to create a molecular structure.

4.3. Training

The model is trained to minimize the objective,

$$\mathcal{L} = \alpha_{recon}\mathcal{L}_{recon} + \alpha_{KL}\mathcal{L}_{KL} + \alpha_{steric}\mathcal{L}_{steric} \tag{2}$$

where $\mathcal{L}_{recon}$ is the reconstruction loss, $\mathcal{L}_{KL}$ is the Kullback-Leibler (KL) divergence between the prior and posterior distributions, $\mathcal{L}_{steric}$ is the loss for steric clash between the ligand and receptor density, and each α is a scaling term.

$$\mathcal{L}_{KL} = -D_{KL}(q_\phi(\mathbf{z}|D_{lig}, D_{rec}) \,||\, p(\mathbf{z})) \tag{3}$$

$$\mathcal{L}_{recon} = -\log p_\theta(D_{lig}|D_{rec}, \mathbf{z}) \tag{4}$$

$$\mathcal{L}_{steric} = \log p_\theta(D_{rec}|D_{rec}, \mathbf{z}) \tag{5}$$

Because the grid representation is sparse, we apply a mask to scale the reconstruction loss for zero grid values in order focus the loss signal on non-empty grid locations. We achieve this by scaling the loss for zero grid values by a factor γ, yielding the scaled reconstruction loss,

$$\mathcal{L}_{recon} = \sum_i -\gamma_i \log p_\theta(D_{lig,i} \,|\, D_{rec,i}, \mathbf{z}). \tag{6}$$

4.4. Data

We use two datasets in the training and evaluation of DrugHIVE, PDBbind (v2020, refined set)[21] and a subsample of the ZINC drug-like subset[5]. We chose the PDBbind refined set as it provides a set of high-quality crystal structures of ligands bound to protein receptors. We remove structures with ligands that are too wide to fit well into the density grid (>16 Å) or that have too many atoms (>43). A test set of 100 structures was selected from the dataset by first clustering all receptor structures by 30% sequence identity and then randomly assigning clusters until the desired split is achieved. We also train on subsample of the ZINC dataset as unbound drug molecules to improve training and reduce overfitting to the relatively small number of example ligands in the PDBbind dataset. To

acquire the subsample, we start with the ZINC drug-like subset and sample about 27 million molecules uniformly by alogP and number of heavy atoms, filtering out the small number of structures with heavy atoms not in our atomic element set ($Z \in \{C, N, O, F, P, S, Cl, Br, I\}$).

For evaluation of generating from AlphaFold predicted structures, we use a dataset of 100 AF structures for which we also have the PDB structure. To create this dataset, we first identify all structures from the PDBbind dataset where the receptor pocket is comprised of a single protein chain and that chain is available from the AlphaFold Protein Structure Database[38]. We then perform sequence and structural alignment of the AF structure to the PDB structure using PyMOL *align* function[39], filtering out receptor structures with less than 70% sequence identity. We then extract the binding pocket by cutting off any excess residues based on sequence alignment and remove all residues with atoms >24 Å from the ligand. We then filter out any structures without a high confidence score (pLDDT < 70) for any residue within 5 Å of the ligand. Finally, we randomly sample 100 of the remaining receptors for the AF test set.

4.5. Sampling

DrugHIVE has multiple sampling modes. Once a model is trained, new molecular structures can be generated by inputting a protein structure into the protein encoder and a randomly sampled set of values from the prior into the ligand decoder. We call this mode *prior sampling,* and the result is a randomly generated density that can then be fit with a molecular structure (see Figure 2d-f). Since known ligands can be encoded into a set of latent values, we can repeat the same procedure using the latent values from a previously encoded ligand structure instead of randomly sampling from the prior. We call this *posterior sampling*, and the result is an output density very similar to the true input ligand density.

We combine these two sampling modes into what we call *prior-posterior sampling (*Figure 2f) to generate densities of varying similarity to an initial ligand density. To achieve this, we repeat the procedure for posterior sampling while also sampling a random set of values from the latent prior. Then starting with the values sampled from the posterior, we then interpolate toward the values sampled from the prior:

$$z_i = z_{i,post} + \beta_i(z_{i,prior} - z_{i,post}), \tag{7}$$

with β_i being the interpolation factors. The latent representation has multiple scales, and one can specify a different interpolation factor for each scale. Since different molecular properties are encoded at different scales (see Figure S4), this leads to a high degree of control over the variation of molecular details in generating new structures. Finally, since each latent tensor retains spatial context, we can do *spatial prior-posterior sampling* (Figure 3b) by performing prior-posterior sampling over a spatial subset of the density grid.

The latent space of DrugHIVE is comprised of a set of tensors, each representing information at a specific resolution of molecular space (see Figure 1b). This varying resolution is the result of downsampling layers in the neural network. Each latent tensor retains spatial context, so we can do *spatial prior-posterior sampling* by performing prior-posterior sampling over a subset of the density grid (see Figure 3b). For this sampling mode, we choose a region of the input grid on which to perform prior-posterior sampling. For each latent tensor, we determine which values correspond to the modification region and which fall outside by mapping the tensor values back to the full resolution grid. We then perform prior-posterior sampling, setting the interpolation factors equal to zero for all latent values outside of the modification region. The result is a generated structure similar to the input

ligand except for within the modification region, which will differ more or less according to interpolation factor value.

Another means of controlling the generation process is through a scaling (temperature) factor on the variance of each latent variable. The DrugHIVE latent prior is a high dimensional normal distribution, where each latent value is sampled from a distribution, $z_i \sim N(\mu_i, \sigma_i \tau_i)$, where μ_i is the mean, σ_i is the variance and τ_i is the temperature factor. As with the prior-posterior interpolation factor, the temperature factor can be varied across latent scales and spatial subsets. The default temperature factor during training is 1. Generally speaking, decreasing the temperature factor has the effect of lowering the variability of generated samples[35,37].

4.6. Evolutionary molecular optimization

Evolutionary (genetic) algorithms are employed in a wide range of multi-objective non-gradient optimization problems and have a long history of use in drug discovery[40]. They mimic the process of biological evolution to effectively search through spaces of high complexity where ordinary search methods would be prohibitively inefficient or difficult to implement. We apply an evolutionary algorithm coupled with prior-posterior sampling to search the latent space of DrugHIVE and optimize molecular properties. In our case, the genetic information is represented by the latent encoding of molecules and the mutation rate is represented by the prior-posterior interpolation factor (β).

Initialization step: Generate an initial population of N_c molecules. Apply the fitness function and cluster the molecules (Tanimoto similarity < 0.2), keeping the most fit individual from each cluster. Select the N_p best molecules from the current population as "parents".

Optimization step (repeat until converged): Generate a new population of N_c "child" molecules from parents. Apply the fitness function and cluster, keeping the most fit individual from each cluster. Replace least fit parents with child molecules having better fitness score.

The fitness function will vary based on desired outcomes but, in general, will be some measure of distance between the observed molecular property value(s) and the desired ones. For example, in the case of binding affinity optimization, the predicted binding affinity score is used as the fitness measure. To perform multi-objective optimization, the fitness function can be a combination of (e.g., weighted sum) of individual fitness scores. In our non-affinity property optimization experiments, we seek to maintain predicted binding affinity while optimizing the targeted property by removing all child molecules from the population with a binding affinity score worse than a threshold value.

4.7. Force field optimization

Prior to docking, we perform force field optimization on all molecular structures using the MMFF94 force field[41] in RDKit. Unlike some other groups, we do not use the Universal Force Field[42] due to a lack of robustness in convergence that we empirically observed in this work. We also do not relax structures in the context of the receptor for a couple of important reasons. The first reason for this is that docking algorithms are designed to take as input an energy minimized ligand structure. Many docking algorithms, especially those using the AutoDock Vina scoring function, use the intramolecular strain of the ligand as a component of the docking score, and so it is very important not to input an artificially strained molecule as input[43,44]. In fact, even ligands from crystal structures that are geometrically distorted by the receptor are recommended to have their structures optimized before proceeding to docking[43]. Second, convergence to an optimal minimum becomes less reliable as the size of the system grows. For this reason, including the surrounding receptor atoms in the

calculation, even if fixed to their initial positions, leads to a higher likelihood of convergence failure and false positives. This step is especially important with de-novo generated structures, which are likely to be far from an energy minimum. Using unconverged structures or, even worse, choosing to skip force field optimization on structures before docking could lead to significantly exaggerated docking scores (see Figure S3).

4.8. Evaluation properties and metrics

Binding affinity is estimated for each ligand with the *Vina* docking score calculated with QuickVina 2[45], a speed optimized version of AutoDock Vina. We define *ΔVina* as the difference between the Vina score of a generated ligand and the reference ligand (e.g., the ligand from the crystal structure). Molecular *similarity* is calculated as one minus the Tanimoto distance between the molecular fingerprints of a pair of molecules. Molecular *diversity* is defined on a set of molecules as the average Tanimoto distance between each pair in the set. The Quantitative Estimate of Drug-Likeness (*QED*) score estimates the drug-likeness of a molecule by combining a set of molecular properties[46]. The Synthetic Accessibility (*SA)* score estimates the ease of synthesis of a molecule[47].

4.9. Evaluation

We evaluate our method against a set of randomly sampled molecules from the ZINC20 drug-like subset by comparing the predicted binding affinity of the molecules. We generate 200 molecules for each of the receptors in the test set using DrugHIVE prior sampling. We then perform force field optimization on each of the molecules using the MMFF94 force field in RDKit (see Section 4.7: Force Field Optimization). For each molecule, we virtually dock to the corresponding receptor using QuickVina 2 (with default settings and a 20 Å wide bounding box) to predict the binding affinity. We plot the resulting distributions in Figure S2. Because *Vina* affinity is strongly correlated with number of atoms in the molecule, we also plot the predicted affinity vs. number of atoms.

5. ACKNOWLEDGEMENTS

The authors acknowledge helpful discussions with other members of the Rohs lab, including Dr. Jared M. Sagendorf. This work was supported by the National Institutes of Health [grant R35GM130376 to R.R.] and Human Frontier Science Program [grant RGP0021/2018 to R.R.].

6. DECLARATION OF CONFLICT OF INTEREST

The authors and the University of Southern California have filed a provisional patent application for DrugHIVE method.

7. REFERENCES

1. Sun, D., Gao, W., Hu, H. & Zhou, S. Why 90% of clinical drug development fails and how to improve it? *Acta Pharm. Sin. B* **12**, 3049–3062 (2022).

2. Hughes, J., Rees, S., Kalindjian, S. & Philpott, K. Principles of early drug discovery. *Br. J. Pharmacol.* **162**, 1239–1249 (2011).

3. Warr, W. A., Nicklaus, M. C., Nicolaou, C. A. & Rarey, M. Exploration of Ultralarge Compound Collections for Drug Discovery. *J. Chem. Inf. Model.* **62**, 2021–2034 (2022).

4. Grygorenko, O. O. *et al.* Generating Multibillion Chemical Space of Readily Accessible Screening Compounds. *iScience* **23**, 101681 (2020).

5. Irwin, J. J. *et al.* ZINC20—A Free Ultralarge-Scale Chemical Database for Ligand Discovery. *J. Chem. Inf. Model.* **60**, 6065–6073 (2020).

6. Bohacek, R. S., McMartin, C. & Guida, W. C. The art and practice of structure-based drug design: A molecular modeling perspective. *Med. Res. Rev.* **16**, 3–50 (1996).

7. Sadybekov, A. A. *et al.* Synthon-based ligand discovery in virtual libraries of over 11 billion compounds. *Nature* 1–8 (2021) doi:10.1038/s41586-021-04220-9.

8. Beroza, P. *et al.* Chemical space docking enables large-scale structure-based virtual screening to discover ROCK1 kinase inhibitors. *Nat. Commun.* **13**, 6447 (2022).

9. Sadybekov, A. V. & Katritch, V. Computational approaches streamlining drug discovery. *Nature* **616**, 673–685 (2023).

10. Kirkpatrick, P. & Ellis, C. Chemical space. *Nature* **432**, 823–823 (2004).

11. Batool, M., Ahmad, B. & Choi, S. A Structure-Based Drug Discovery Paradigm. *Int. J. Mol. Sci.* **20**, 2783 (2019).

12. Jumper, J. *et al.* Highly accurate protein structure prediction with AlphaFold. *Nature* **596**, 583–589 (2021).

13. Watson, J. L. *et al.* De novo design of protein structure and function with RFdiffusion. *Nature* **620**, 1089–1100 (2023).

14. Gómez-Bombarelli, R. *et al.* Automatic Chemical Design Using a Data-Driven Continuous Representation of Molecules. *ACS Cent. Sci.* **4**, 268–276 (2018).

15. Hoogeboom, E., Satorras, V. G., Vignac, C. & Welling, M. Equivariant Diffusion for Molecule Generation in 3D. in *Proc. 39th Internat. Conf. Machine Learning* 8867–8887 (PMLR, 2022).

16. Luo, S., Guan, J., Ma, J. & Peng, J. A 3D Generative Model for Structure-Based Drug Design. Preprint at https://doi.org/10.48550/arXiv.2203.10446 (2022).

17. Ragoza, M., Masuda, T. & Koes, D. R. Generating 3D molecules conditional on receptor binding sites with deep generative models. *Chem. Sci.* **13**, 2701–2713 (2022).

18. Schneuing, A. *et al.* Structure-based Drug Design with Equivariant Diffusion Models. Preprint at https://doi.org/10.48550/arXiv.2210.13695 (2023).

19. Peng, X. *et al.* Pocket2Mol: Efficient Molecular Sampling Based on 3D Protein Pockets. Preprint at http://arxiv.org/abs/2205.07249 (2022).

20. Patel, R. A. *et al.* RKI-1447 Is a Potent Inhibitor of the Rho-Associated ROCK Kinases with Anti-Invasive and Antitumor Activities in Breast Cancer. *Cancer Res.* **72**, 5025–5034 (2012).

21. Liu, Z. *et al.* Forging the Basis for Developing Protein-Ligand Interaction Scoring Functions. *Acc. Chem. Res.* **50**, 302–309 (2017).

22. Natesh, R., Schwager, S. L. U., Sturrock, E. D. & Acharya, K. R. Crystal structure of the human angiotensin-converting enzyme–lisinopril complex. *Nature* **421**, 551–554 (2003).

23. Van de Poël, A. *et al.* Structure-Based Exploration of Selectivity for ATM Inhibitors in Huntington's Disease. *J. Med. Chem.* **64**, 5018–5036 (2021).

24. Kirsch, P., Hartman, A. M., Hirsch, A. K. H. & Empting, M. Concepts and Core Principles of Fragment-Based Drug Design. *Molecules* **24**, 4309 (2019).

25. Frank, A. O. *et al.* Discovery of a Potent Inhibitor of Replication Protein A Protein–Protein Interactions Using a Fragment-Linking Approach. *J. Med. Chem.* **56**, 9242–9250 (2013).

26. Hu, Y., Stumpfe, D. & Bajorath, J. Recent Advances in Scaffold Hopping. *J. Med. Chem.* **60**, 1238–1246 (2017).

27. Degen, J., Wegscheid-Gerlach, C., Zaliani, A. & Rarey, M. On the Art of Compiling and Using 'Drug-Like' Chemical Fragment Spaces. *ChemMedChem* **3**, 1503–1507 (2008).

28. Galdeano, C. *et al.* Structure-Guided Design and Optimization of Small Molecules Targeting the Protein–Protein Interaction between the von Hippel–Lindau (VHL) E3 Ubiquitin Ligase and the Hypoxia Inducible Factor (HIF) Alpha Subunit with in Vitro Nanomolar Affinities. *J. Med. Chem.* **57**, 8657–8663 (2014).

29. Baell, J. B. & Holloway, G. A. New Substructure Filters for Removal of Pan Assay Interference Compounds (PAINS) from Screening Libraries and for Their Exclusion in Bioassays. *J. Med. Chem.* **53**, 2719–2740 (2010).

30. Baell, J. B. & Nissink, J. W. M. Seven Year Itch: Pan-Assay Interference Compounds (PAINS) in 2017—Utility and Limitations. *ACS Chem. Biol.* **13**, 36–44 (2018).

31. Berman, H. M. *et al.* The Protein Data Bank. *Nucleic Acids Res.* **28**, 235–242 (2000).

32. Porta-Pardo, E., Ruiz-Serra, V., Valentini, S. & Valencia, A. The structural coverage of the human proteome before and after AlphaFold. *PLoS Comput. Biol.* **18**, e1009818 (2022).

33. Arnold, C. AlphaFold touted as next big thing for drug discovery — but is it? *Nature* **622**, 15–17 (2023).

34. Tunyasuvunakool, K. *et al.* Highly accurate protein structure prediction for the human proteome. *Nature* **596**, 590–596 (2021).

35. Child, R. Very Deep VAEs Generalize Autoregressive Models and Can Outperform Them on Images. Preprint at https://doi.org/10.48550/arXiv.2011.10650 (2021).

36. Maaløe, L., Fraccaro, M., Liévin, V. & Winther, O. BIVA: A Very Deep Hierarchy of Latent Variables for Generative Modeling. (2019) doi:10.48550/arXiv.1902.02102.

37. Vahdat, A. & Kautz, J. NVAE: A Deep Hierarchical Variational Autoencoder. Preprint at https://doi.org/10.48550/arXiv.2007.03898 (2021).

38. Varadi, M. *et al.* AlphaFold Protein Structure Database: massively expanding the structural coverage of protein-sequence space with high-accuracy models. *Nucleic Acids Res.* **50**, D439–D444 (2022).

39. Schrödinger, LLC. The PyMOL Molecular Graphics System, Version 2.5.

40. Devi, R. V., Sathya, S. S. & Coumar, M. S. Evolutionary algorithms for de novo drug design – A survey. *Appl. Soft Comput.* **27**, 543–552 (2015).

41. Halgren, T. A. Merck molecular force field. I. Basis, form, scope, parameterization, and performance of MMFF94. *J. Comput. Chem.* **17**, 490–519 (1996).

42. Rappe, A. K., Casewit, C. J., Colwell, K. S., Goddard, W. A. I. & Skiff, W. M. UFF, a full periodic table force field for molecular mechanics and molecular dynamics simulations. *J. Am. Chem. Soc.* **114**, 10024–10035 (1992).

43. Forli, S. *et al.* Computational protein–ligand docking and virtual drug screening with the AutoDock suite. *Nat. Protoc.* **11**, 905–919 (2016).

44. Cosconati, S. *et al.* Virtual screening with AutoDock: theory and practice. *Expert Opin. Drug Discov.* **5**, 597–607 (2010).

45. Alhossary, A., Handoko, S. D., Mu, Y. & Kwoh, C.-K. Fast, accurate, and reliable molecular docking with QuickVina 2. *Bioinformatics* **31**, 2214–2216 (2015).

46. Bickerton, G. R., Paolini, G. V., Besnard, J., Muresan, S. & Hopkins, A. L. Quantifying the chemical beauty of drugs. *Nat. Chem.* **4**, 90–98 (2012).

47. Ertl, P. & Schuffenhauer, A. Estimation of synthetic accessibility score of drug-like molecules based on molecular complexity and fragment contributions. *J. Cheminform.* **1**, 1–11 (2009).