TEMINET: A Co-Informative and Trustworthy Multi-Omics Integration Network for Diagnostic Prediction

Haoran Luo [1,2], Hong Liang [2], Hongwei Liu [2], Zhoujie Fan [1], Yanhui Wei [2], Xiaohui Yao [1,2,*] and Shan Cong [1,2,*]

[1] Qingdao Innovation and Development Center, Harbin Engineering University, Qingdao, Shandong 266000, China

[2] College of Intelligent Systems Science and Engineering, Harbin Engineering University, Harbin, Heilongjiang 150001, China

[*] Correspondence: xiaohui.yao@hrbeu.edu.cn, shan.cong@hrbeu.edu.cn

Abstract: Advancing the domain of biomedical investigation, integrated multi-omics data have shown exceptional performance in elucidating complex human diseases. However, as the variety of omics information expands, precisely perceiving the informativeness of intra- and inter-omics becomes challenging due to the intricate interrelations, thus posing significant obstacles in multi-omics data integration. To address this, we introduce a novel multi-omics integration approach, referred to as TEMINET. This approach enhances diagnostic prediction by leveraging an intra-omics co-informative representation method and a trustworthy learning strategy used to address inter-omics fusion. Considering the multifactorial nature of complex diseases, TEMINET utilizes intra-omics features to construct disease-specific networks, then applies graph attention networks and a multi-level framework to capture more collective informativeness than pairwise relations. To perceive the contribution of co-informative representations within intra-omics, we design a trustworthy learning strategy to identify the reliability of each omics in integration. To integrate inter-omics information, a combined beliefs fusion approach is deployed to harmonize the trustworthy representations of different omics types effectively. Our experiments across four different diseases using mRNA, methylation, and miRNA data demonstrate that TEMINET achieves advanced performance and robustness in classification tasks.

Keywords: multi-omics; graph-based neural network; trustworthy; disease diagnosis; biomarker identification

1. Introduction

In light of recent advancements in the acquisition of high-throughput omics data, multi-omics integration has emerged as a rapidly expanding research field, aiming to provide a more comprehensive understanding of the underlying biological processes and molecular mechanisms involved in complex diseases [1,2]. Compared to single-omics studies, integrating multiple types of omics data enables the capture of complementary information across various molecular layers, leading to a more holistic view of biological systems [3]. Traditional approaches often involve statistical tools, which may have limited capacity to fully capture the complex, non-linear relationships present in multi-omics datasets. In recent years, the application of artificial neural networks (ANN) to multi-omics studies has emerged as a promising avenue for addressing these limitations [4–6]. ANN approaches can learn intricate patterns within the data, enabling more accurate predictions and classifications, as well as the identification of previously unexplored relationships between molecular entities. These methods have shown great potential in various biomedical applications, such as disease prediction, patient stratification, and the discovery of novel biomarkers [7].

Despite significant achievements, the stability and biological explainability of many existing multi-omics integration approaches remain underdeveloped, primarily because of the insufficient exploration of both intra- and inter-omics interaction information. Existing

studies, which are divided into early, intermediate, and late integration strategies, exhibit a tendency to utilize the fitting capabilities of ANNs for information integration [7–9]. Early integration methods, such as FCNNs [10–12] and autoencoders (AE) [13–15], perform integration through concatenating representations. These approaches treat intra-omics as an individual molecule and inter-omics as an individual modality. When facing modalities with different distributions and highly homogeneous, they are less likely to perform effectively. Intermediate fusion emphasizes the interactions within inter-omics information, rather than perceiving each omics type individually. For example, variational AEs (VAEs) are widely used to perform a fusion of homogeneous data types in a joint manner [16,17]. Despite the advantages of coordinated representation learning in intermediate fusion, it operates under the presumption of equal contribution from each modality, which is challenging for the fitting capabilities of ANNs, especially in cases of feature imbalance, severe missing modalities, or substantial noise interference. Considering the uncertainty of such situations, trustworthy learning methodologies have been adopted, transforming the operation from feature embedding to a decision-level process, thereby stabilizing and enhancing the outcomes of late integration strategies. Han et al. [18] introduce a dynamic fusion approach for multi-modal classification. This method employs true-class probability to asses the classification confidence across different omics and then adjusts through modality confidence weighting for integration. Wang et al. [19] propose Mogonet, which employs a View Correlation Discovery Network (VCDN) to integrate initial classifications instead of fusing features across modalities, thereby utilizing label-correlated information in the shared space to produce final classification labels. We observe that by perceiving and integrating the informativeness of each modality and inter-modality from distinct samples in trustworthy multimodal learning, practical applications can be significantly enhanced. However, traditional intra-modality information embedding may inadequately capture the full scope of informativeness, primarily due to the biological explainability of intra-omics. Such studies may overlook essential aspects of the underlying biological processes, potentially leading to a limited understanding of the complex molecular networks driving various biological systems[20]. Ultimately, this could result in challenges in effective integration.

Acknowledging the interrelations of molecular functions is essential in omics research, due to the multifactorial nature of complex diseases [21,22], rather than viewing each genetic factor as an independent entity. To address these challenges, there is a growing number of investigations directed toward the construction of pre-established disease networks by reconfiguring omics data into graph-based structures, reflecting a growing recognition of the importance of contextualized molecular interactions in understanding disease mechanisms. For instance, Ramirez et al. [23] employ a GCN approach for cancer classification, leveraging a framework of gene co-expression based on Spearman correlating analysis. Althubaiti et al. [24] utilize the DeepMOCCA framework, combining omics data with protein-protein interaction networks for improved cancer prognosis predictions. Furthermore, Xing et al. [25] adopt an approach involving a weighted correlating method to build prior knowledge graphs. This method is particularly advantageous for unraveling disease-specific complexities. Therefore, inspired by the effectiveness of network representations in omics studies, we are motivated to adopt a graph-based representation to enhance the informativeness of intra-omics. This approach is intuitive, easy to interpret, and has the potential to better preserve the inherent structure and capture functional interactions from omics data, resulting in improved disease prediction performance.

Based on the above observations, we propose a multi-omics integration framework, named TEMINET, for disease predictive diagnosis that leverages graph attention networks and an uncertainty-based trustworthy strategy. Specifically, we construct a disease-specific network for each omics data to represent large-scale, unstructured, and irregular data effectively. We apply hierarchical graph attention networks to capture co-informative intra-omics representations. Then, a trustworthy learning mechanism is employed to assess the reliability of informativeness by using uncertainty information. Combine beliefs

fusion integrates informativeness and uncertainty into an inter-omics fusion embedding for executing subsequent tasks. We conduct extensive experiments to show the effectiveness and robustness of TEMINET for multi-omics prediction. Our results demonstrate that the combination of graph-based feature representation and uncertainty-based trustworthy learning integration surpasses the state-of-the-art models on four disease classification tasks. We further employ a global interpretation approach to identify important biomarkers and analyze their disease-related functional relevance.

2. Materials and Methods

2.1. Overview of TEMINET

The proposed method is illustrated in Figure 1. It begins with constructing a co-expression graph for the omics data of each subject via the WGCNA. The second step involves generating initial classification results for each omics data through a multi-level GAT process, utilizing three layers to extract intra-omics features from the initial GAT network G_0, with further updating in GAT networks G_1 and G_2. Thirdly, the uncertainty of each initial distribution is parameterized using subjective logic. Based on the Dempster-Shafer theory, the integration of multi-omics evidence comes from the inference of overall uncertainty and classification probability. The whole inference process concludes with the final label prediction of each subject.

2.2. Dataset Overview

Table 1. Overview of datasets used in this investigation.

Dataset	Source	Subjects	Number of origin data			Number of data for study		
			mRNA	methy	miRNA	mRNA	methy	miRNA
ROSMAP	AMPAD	Normal Control: 169, Alzheimer's Disease: 182	55,889	23,788	309	200	200	200
BRCA	TCGA	Luminal A: 436, Luminal B: 147, HER2-enriched: 46, Normal-like: 115, Basal-like: 131	20,531	20,106	503	1,000	1,000	503
LGG	TCGA	Grade *II*: 246, Grade *III*: 264	20,531	20,114	548	2,000	2,000	548
KIPAN	TCGA	KICH: 66, KIRC: 318, KIRP: 274	20,531	20,111	445	2,000	2,000	445

In our investigation, we performed analysis using four public benchmark datasets provided by Wang et al. [19], including ROSMAP for binary classification (distinguishing between Alzheimer's disease (AD) and normal control (NC)), BRCA for the classification of breast invasive carcinoma into PAM50 subtypes (including five categories), low-grade glioma (LGG) for distinguishing between grade *II* and grade *III*, and KIPAN referring to the classification of renal cell carcinoma subtypes. The study utilized three categories of omics data: mRNA expression, DNA methylation, and miRNA expression. Table 1 provides comprehensive details regarding these datasets.

2.3. Intra-omics Network Construction

The development of functional interaction networks is integral to understanding the pathogenesis of complex diseases. To leverage synergistic relationships among intra-omics molecules, the initial step in our methodology involved implementing Weighted Correlation Network Analysis (WGCNA [26]) to construct intra-omics co-expression networks, as shown in Figure 1(B). The construction of the intra-omics graph G_0 for each subject involved several key stages: Firstly, an adjacency matrix was formed through WGCNA, with each entry indicating the correlation strength between pairs of omics features. Secondly, this matrix was transformed into an edge matrix by applying a threshold. Thirdly, a co-expression network was constructed for individual subjects, assigning omics data expression values to nodes as their features.

Figure 1. Framework of TEMINET. **(A)** TEMINET operates on a sample-wise basis with multi-omics information for each individual sample being imported into the model. **(B)** The first intra-omics network is built using the WGCNA. **(C)** The intra-omic information at each omics-level is augmented using the multi-level GAT. **(D)** The evidence is evaluated by the subject logic module to obtain uncertainty. During the integration phase, the trustworthy informativeness and uncertainty from each omics are amalgamated into a composite embedding encompassing inter-omics information. The fusing representation is subsequently applied to implement a downstream classification task.

In this context, an initial co-expression graph network of each patient is denoted as $G_0 = G(V_0^{d \times 1}, E_0^{d \times d})$. Here, $V^{d \times 1}$ symbolizes the attributes of d nodes. $E^{d \times d}$ represents the edge matrix derived from the co-expression correlations computed via WGCNA. Specifically, for each subject n, a feature vector of dimension $1 \times d$ is generated, where d represents

the number of features. For a group of N subjects within a single omics data, an $N \times d$ matrix is formulated to calculate the co-expression matrix $A^{d \times d}$. The correlation A_{ij} between node v_i and v_j is given by

$$A_{ij} = \left(\frac{1}{2} \left(1 + \frac{\sum_{n=1}^{N} (v_{i,n} - \bar{v}_i)(v_{j,n} - \bar{v}_j)}{\sqrt{\sum_{n=1}^{N} (v_{i,n} - \bar{v}_i)^2} \sqrt{\sum_{n=1}^{N} (v_{j,n} - \bar{v}_j)^2}} \right) \right)^{\beta}, \tag{1}$$

where $\bar{v}_i$ and $\bar{v}_j$ denote the mean values of nodes v_i and v_j, and β denotes an adjustable parameter set by WGCNA. The edge matrix $E_0^{d \times d}$ is then obtained by binarizing the values from the matrix $A^{d \times d}$. In conclusion, the construction of intra-omics co-expression networks is implemented for each dataset of mRNA, methylation, and miRNA, respectively.

2.4. Intra-omics Informative Augmentation

To leverage the information embedding in nodes and their associations within co-expression matrices effectively, we introduced the GAT [27] to enhance the disease-specific characteristics of the omics dataset. GAT incorporated masked self-attention based layers to enable dynamic weighting of neighboring node contributions, which allowed GAT to selectively focus on more pertinent adjacent nodes, thereby diminishing the impact of nodes that are lesser-significant. As a result, GAT exhibited a superior ability to discern intricate and non-structure connections, as well as variations within the topology of the graph.

Specifically, an initial network for each omics subject n, denoted as $G_0 = G(V_0^n, E_0)$ from Stage (B), is updated through a GAT layer. Initially, for a node h_i within this network, the normalization of attention coefficients α_{ij} with its neighboring nodes h_j are calculated as follows:

$$\alpha_{ij} = \frac{\exp(\text{LeakyRelu}(\alpha([W_C h_i \parallel W_C h_j])))}{\sum_{h_l \in N_i} \exp(\text{LeakyRelu}(\alpha([W_C h_i \parallel W_C h_l])))}, \quad h_j \in N_i, \tag{2}$$

where $\parallel$ is the concatenation operation, and W_C is the shared parameter matrix for linear transformation. To ensure a more stable self-attention update, a multi-head approach is introduced [27]. We conducted a process in which the attention-layer functions were implemented T times, each with unique parameters. The outcomes from these replications, indicated as h'_i, are then conducted an aggregating concatenation in sequence as follows:

$$h'_i = \parallel_{t=1}^{T} \sigma \left(\sum_{j \in N_i} \alpha_{ij}^t W_R^t h_j \right), \tag{3}$$

where α_{ij}^t represents the attention coefficients from the t-th attention head, and W_R^t is the weight matrix associated with the t-th head.

To enhance the exploration of internal feature relationships, we have incorporated the multi-level feature representation approach implemented by Xing et al. [25]. The foundational network G_0 encapsulates data corresponding to the primal features. Subsequently, G_1 evolves from G_0 via the deployment of a multi-head GAT attention-layer. Analogously, G_2 is generated from G_1. This progression through three progressive graph network layers creates a hierarchical integration structure, systematically amalgamating features across the GAT layers. Ultimately, the vectors produced from these transformation stages are fused, resulting in comprehensive feature representations. This design facilitates a dynamic optimization of feature interplays within the network, leading to a more substantial and comprehensive representation of the fundamental biology mechanisms. Using a similar process, we also implemented the DNA methylation and miRNA informative augmentation for each subject.

2.5. Trust-driven Multi-omics Fusion

In traditional multi-omics integration methods, the trustworthiness of different datasets is often not adequately considered, leading to potential inaccuracies in understanding complex biological processes. To address this, we introduced an uncertainty-based trustworthy learning approach in our integration method [28]. This approach is designed to enhance trustworthiness and precision in multi-omics data integration by quantifying inherent uncertainty in each modality. It leverages this measure of uncertainty to jointly perceive informativeness across intra- and inter-omics. Given that uncertainty assessments define confidence in predictions, the evidence of a dataset with lower uncertainty should obtain higher trustworthiness and be assigned a larger contribution to multi-omics integration.

Evidence in a classifier is generally considered the outputs of a neural network processed through an activation function like softmax. In our study, the evidence $e^m = [e_1^m, \cdots, e_K^m]$ for the m^{th} omics category across K classes is generated from GAT-enhanced features. In the augmentation module, GAT-enhanced features are transformed into evidence through a sequence of fully connected layers and an active layer. Here, we set a cross-entropy loss $\mathcal{L}_{GAT}^m$ to modify the GAT augmentation module.

Secondly, to obtain the uncertainty, we applied subjective logic [29] to the evidence $e^m = [e_1^m, \cdots, e_K^m]$. For each class k in the m^{th} omics category, the belief mass b_k^m and uncertainty mass u^m are calculated, ensuring $u^m + \sum_{k=1}^{K} b_k^m = 1$. The concentration parameters α^m of the Dirichlet distribution are determined from the evidence, where $\alpha_k^m = e_k^m + 1$. The belief mass for each class is computed as $b_k^m = \frac{e_k^m}{S^m}$ and the overall uncertainty as $u^m = \frac{K}{S^m}$, with $S^m = \sum_{i=1}^{K} (e_i^m + 1)$. This formulation quantifies the confidence in each class prediction and the overall uncertainty in the classification for the m^{th} omics category. In summary, for the m^{th} omics category, the more evidence gathered for each of the K classes, the higher the probability assigned to the respective class, thus reducing uncertainty. Conversely, a scarcity of evidence leads to increased uncertainty. Utilizing subjective logic, this approach models second-order probabilities and uncertainties for the m^{th} omics category, effectively countering the overconfidence often seen in traditional neural network classifiers.

Thirdly, within the methodological framework for multi-omics fusion, we applied the Dempster-Shafer theory to synthesize evidence from different classes. This process consolidates independent probability mass assignments from each class into a unified joint mass. Dempster rule orchestrates this fusion to merge belief and uncertainty across the omics spectrum, symbolized as:

$$\mathbf{M^F} = \mathbf{M^1} \oplus \mathbf{M^2} \oplus \cdots \mathbf{M^m}. \tag{4}$$

Taking the fusion of two omics categories as an example, where $\mathbf{M^1}$ is represented as $[b_1^1, b_2^1, \cdots, b_K^1, u^1]$ and $\mathbf{M^2}$ as $[b_1^2, b_2^2, \cdots, b_K^2, u^2]$, the fusion process is initiated as follows:

$$\mathbf{M^F} = \mathbf{M^1} \oplus \mathbf{M^2}, \tag{5}$$

and

$$b_k^{\mathbf{F}} = \frac{1}{1-C}(b_k^1 b_k^2 + b_k^1 u^2 + b_k^2 u^1), \; u^{\mathbf{F}} = \frac{1}{1-C} u^1 u^2, \tag{6}$$

where $\frac{1}{1-C}$ denotes the scale factor for normalization. After the $\mathbf{M^F} = \{\{b_k^{\mathbf{F}}\}_{k=1}^K, u^{\mathbf{F}}\}$ obtained, the final evidence can be inferred with $e_k = b_k \times S$ and $S = \frac{K}{u}$.

Furthermore, we introduced an enhanced cross-entropy loss function by integrating sample-specific evidence as follows:

$$\mathcal{L}_{E-ce}(\alpha_i) = \sum_{k=1}^{K} y_{ik}(\psi(S_i) - \psi(\alpha_{ik})), \tag{7}$$

where α_i is the parameter of the Dirichlet distribution for the ith sample, and $\psi(\cdot)$ is the digamma function. Building on this, an overall sample-specific loss function, which combines the adjusted cross-entropy loss with a Kullback-Leibler divergence term to effectively manage the evidence for incorrect labels, is defined as:

$$\mathcal{L}(\alpha_i) = \mathcal{L}_{E-ce}(\alpha_i) + \lambda_t KL[D(\mathbf{p}_i|\tilde{\alpha}_i) \parallel D(\mathbf{p}_i|1)]. \tag{8}$$

The $\tilde{\alpha}_i = y_i + (1 - y_i)\alpha_i$ is the modified attribute of the Dirichlet distribution, and λ is a balance factor greater than zero. This design helps penalize incorrect class evidence while preserving the evidence for the correct class. To ensure the informative augmentation and evidence fusion are updated simultaneously, a total loss is defined as:

$$\mathcal{L}_{global} = \sum_{i=1}^{N} [\mathcal{L}(\alpha_i) + \sum_{m=1}^{M} \mathcal{L}(\alpha_i^m) + \gamma \sum_{m=1}^{M} \mathcal{L}_{GAT}^m], \tag{9}$$

where γ denotes an adjusted attribute. We deployed $\gamma = 1$ across our investigations.

2.6. Identifying biomarkers with TEMINET

In the realm of biomedical research, the elucidation of biomarkers is pivotal for unraveling the intricacies of biological processes and providing insight into diverse outcomes. Concurrently, there is a growing need in clinical research for interpretable models that elucidate underlying disease mechanisms and bolster model credibility. Consequently, we applied a global interpretation method to identify the importance of biomarkers in our model. Specifically, to evaluate omics features in computational models, normalization of these features to a scale from zero to one is initially implemented. Feature ablation involves individually removing features to evaluate their impact on model efficacy, with a focus on classification capability. The importance of each feature is determined by observing the reduction in model performance post-ablation. In binary classification and multi-class classification tasks, the F1 score and F1 macro score are used to measure performance reduction resulting from feature ablation. This process is implemented with the best-performing model. For multi-omics data, we implemented this strategy in each type of omics data.

3. Results

Our research evaluates the effectiveness of the proposed model relative to current methodologies across diverse classification tasks. We also explore the advantages of incorporating additional omics datasets to enhance classification accuracy. In the comparative analysis of various methodologies, accuracy (ACC) is a common metric employed for binary and multi-class classifications. In addition to ACC, binary classifications also utilize the F1 score (F1) and the area under the receiver operating characteristic curve (AUC). For multi-class classifications, the ACC, the weighted average F1 score (F1_weighted), and the macro-averaged F1 score (F1_macro) are used. Our experimental framework replicates the same settings and provides the mean and standard deviation of these evaluative results.

Fourteen computational approaches are investigated, which include six classic classifiers employing early integration strategies: K-nearest neighbor classifier (KNN) [30], support vector machine (SVM) [31], Lasso [32], random forest (RF) [33], XGboost [34], and fully connected neural networks (NN) [35]. Furthermore, five multi-omics classifiers are analyzed: group-regularized ridge regression [36], BPLSDA for projecting data into latent structures with discriminant analysis [37], block PLSDA with additional sparse constraints (BSPLSDA) [37], concatenation of final representations (CF) [38] for late-stage multi-omics data, gated multimodal fusion (GMU) [39] that integrates intermediate representations, along with three advanced methods, Mogonet [19], MODILM [40], and Dynamic [18].

3.1. Classification performance comparison

Table 2. Comparison with advanced methods on the ROSMAP and LGG datasets. Top-performing results are emphasized in boldface. Metrics marked with ∗ signify a substantial improvement of our model over the suboptimal method, as evidenced by an independent t-test yielding $P < 0.05$.

Method	ROSMAP (two categories)			LGG (two categories)		
	ACC (%)	F1 (%)	AUC (%)	ACC (%)	F1 (%)	AUC (%)
KNN	65.7±3.6	67.1±4.4	70.9±4.5	72.9±3.4	73.8±3.3	79.9±3.8
SVM	77.0±2.4	77.8±1.6	77.0±2.6	75.4±4.6	75.7±5.0	75.4±4.6
Lasso	69.4±3.7	73.0±3.3	77.0±3.5	76.1±1.8	76.7±2.2	82.3±2.7
RF	72.6±2.9	73.4±2.1	81.1±1.9	74.8±1.2	74.2±1.0	82.3±1.0
XGBoost	76.0±4.6	77.2±4.5	83.7±3.0	75.6±4.0	76.7±3.2	84.0±2.3
NN	75.5±2.1	76.4±2.1	82.7±2.5	73.7±2.3	74.8±2.4	81.0±3.7
GRridge	76.0±3.4	76.9±2.9	84.1±2.3	74.6±3.8	75.6±3.6	82.6±4.4
BPLSDA	74.2±2.4	75.5±2.3	83.0±2.5	75.9±2.5	73.8±3.1	82.5±2.3
BSPLSDA	75.3±3.3	76.4±3.5	83.8±2.1	68.5±2.7	66.2±3.0	73.0±2.6
CF	78.4±1.1	78.8±0.5	88.0±0.5	81.1±1.2	82.2±0.4	88.1±0.4
GMU	77.6±2.5	78.4±1.6	86.9±1.6	80.3±1.5	80.8±1.2	88.6±1.2
Mogonet	81.5±2.3	82.1±2.2	87.4±1.2	81.6±1.6	81.4±1.4	84.0±2.7
MODILM	84.3±1.2	85.0±0.8	89.1±1.2	82.8±0.7	82.5±2.3	86.1±1.5
Dynamic	84.2±1.3	84.6±0.7	**91.2±0.7**	83.3±1.0	83.7±0.4	88.5±0.4
Ours	**87.9±0.4**∗	**88.2±0.4**∗	87.6±1.3	**84.3±0.7**∗	**84.1±0.9**	**88.6±1.2**

Table 3. Comparison with advanced methods on the BRCA and KIPAN datasets. Top-performing results are emphasized in boldface. Metrics marked with ∗ signify a substantial improvement of our model over the suboptimal method, as evidenced by an independent t-test yielding $P < 0.05$.

Method	BRCA (five categories)			KIPAN (three categories)		
	ACC (%)	F1-W[1] (%)	F1-M[1] (%)	ACC (%)	F1-W[1] (%)	F1-M[1] (%)
KNN	74.2±2.4	73.0±2.3	68.2±2.5	96.7±1.1	96.7±1.1	96.0±1.4
SVM	72.9±1.8	70.2±1.5	64.0±1.7	99.5±0.3	99.5±0.3	99.4±0.4
Lasso	73.2±1.2	69.8±1.5	64.2±2.6	97.4±0.2	97.4±0.2	97.2±0.4
RF	75.4±0.9	73.3±1.0	64.9±1.3	98.1±0.6	98.1±0.6	97.5±1.1
XGBoost	78.1±0.8	76.4±1.0	70.1±1.7	99.3±0.8	99.3±0.8	98.9±1.4
NN	75.4±2.8	74.0±3.4	66.8±4.7	99.1±0.5	99.1±0.5	99.1±0.5
GRridge	74.5±1.6	72.6±1.9	65.6±2.5	99.4±0.4	99.4±0.4	99.3±0.4
BPLSDA	64.2±0.9	53.4±1.4	36.9±1.7	93.3±1.3	93.3±1.3	91.9±2.1
BSPLSDA	63.9±0.8	52.2±1.6	35.1±2.2	91.9±1.2	91.8±1.3	89.5±1.4
CF	81.5±0.8	81.5±0.9	77.1±0.9	99.2±0.5	99.2±0.5	98.8±0.9
GMU	80.0±3.9	79.8±5.8	74.6±5.8	97.7±1.6	97.6±1.7	95.8±3.2
Mogonet	82.9±1.8	82.5±1.6	77.4±1.7	**99.9±0.2**	**99.9±0.2**	**99.9±0.2**
MODILM	84.5±0.9	84.0±1.6	80.4±1.2	99.2±0.8	99.2±0.8	99.2±0.8
Dynamic	87.7±0.3	**88.0±0.5**	84.5±0.5	**99.9±0.2**	**99.9±0.2**	**99.9±0.3**
Ours	**88.0±0.8**	85.5±1.3	**88.2±0.7**∗	**99.9±0.2**	**99.9±0.2**	**99.9±0.2**

[1] The terms F1-M and F1-W denote the F1 macro and weighted scores, respectively.

In Table 2, a comparative analysis between the proposed model and established methods on ROSMAP and LGG datasets was provided. Compared to alternative approaches, the outcomes demonstrated that our suggested model performed better on binary classification tests. TEMINET outperformed the suboptimal method in many evaluation metrics, though not in the AUC metric for the ROSMAP dataset. The outcomes demonstrated the advantages of integrating informative data utilizing a multi-level graph-based attention framework and disease-specific networks. Moreover, the proposed model significantly exceeded the performance of MODILM (GAT). This advantage was likely due to the incorporation of uncertainty-based adaptive fusion, enhancing the capability of the model to

select and utilize the informative modalities, thus ensuring a more precise characterization of each subject. As shown in Table 3, the proposed method continued to lead in overall performance, yet it showed a slightly lower efficacy in the five-class BRCA task when compared to the top-performing method in this specific area. This further indicated the strength of our model in leveraging disease-specific network analysis and graph attention mechanisms, underscoring its potential despite the room for improvement in certain multi-class classification tasks.

3.2. Ablation comparison of model key component

Table 4. The study examined key components of TEMINET on benchmark datasets, with the top-performing performances highlighted.

Dataset	Metric	NN[1]	NN[1]+Trust	GAT+NN[1]	Our model
ROSMAP	ACC (%)	76.6 ± 2.3	82.5±0.9	84.3±1.6	**87.9±0.4**
	F1 (%)	77.7 ± 1.9	82.3±0.6	84.5±1.6	**88.2±0.4**
	AUC (%)	81.9 ± 1.7	**88.5±0.6**	**88.5±0.6**	87.6±1.3
LGG	ACC (%)	74.0 ± 3.9	81.9±0.8	82.4±0.5	**84.3±0.7**
	F1 (%)	75.6 ± 3.6	81.5±0.4	82.2±1.3	**84.1±0.9**
	AUC (%)	82.4 ± 3.6	87.1±0.4	87.7±1.3	**88.6±1.2**
BRCA	ACC (%)	79.6 ± 1.2	84.2±0.5	87.7±0.4	**88.0±0.8**
	F1-W[2] (%)	78.4 ± 1.4	84.4±0.9	**88.2±0.5**	85.5±1.3
	F1-M[2] (%)	72.3 ± 1.8	80.6±0.9	84.8±1.7	**88.2±0.7**
KIPAN	ACC (%)	98.8 ± 1.1	99.7±0.3	98.9±0.4	**99.9±0.2**
	F1-W[2] (%)	98.8 ± 1.1	99.7±0.3	98.9±0.5	**99.9±0.2**
	F1-M[2] (%)	98.1 ± 1.6	99.4±0.5	98.7±0.7	**99.9±0.2**

[1] The NN refers to a neural network.

[2] The terms F1-M and F1-W denote the F1 macro and weighted scores, respectively.

In an extensive ablation study of our framework, as shown in Table 4, performance metrics were compared against established benchmarks. Our model incorporated an advanced uncertainty-based mechanism and omic-specific co-expression networks and achieved increases in ACC and F1, particularly within the ROSMAP dataset, where it outstripped the GAT+NN model by 4.3 % and 4.4%. However, there was a slight decrement in the AUC by 1.0% compared to the second-best models. This outcome suggested that while our model advanced predictive accuracy, it did so with a trade-off in AUC performance, signaling an area for further refinement in balancing predictive precision with generalizability across diverse datasets. The result of the LGG and KIPAN datasets also revealed improvements across all metrics, reflecting the exceptional ability of our model to capture intricate data patterns. For the BRCA dataset, our model exhibited enhancement in both ACC and the F1-M, yet it encountered a slight decrease in the F1-W score, indicating potential for further refinement in the equilibrium of precision and recall.

3.3. Ablation study comparing integration performance across varied omics categories

In our investigation, we analyzed the effectiveness of different omics data combinations for classification performance. Figure 2 showed that using all three omics types outperformed combinations of just two. This result underlined the individual and substantial contributions provided by different omics categories. Moreover, it confirmed the advantage of integrating multiple omics approaches. Our results indicated that TEMINET enhanced classification performance by incorporating multi-omics informative data. Notably, these improvements were more pronounced with the progressive addition of various omics types.

Figure 2. The efficacy of the proposed approach on different omics data combinations is assessed, presenting mean values and standard errors for comparison.

3.4. Robustness study involving comparisons with advanced methods

Figure 3. The robustness of the proposed approach is evaluated by comparing it with advanced methods. KIPAN is excluded from this comparison as it is relatively easy to classify.

In the robustness experiments, we increase the masked ratio to heighten the uncertainty of a specified modality. This method assesses the robustness of our model by comparing the reduction in accuracy as the data becomes increasingly incomplete or uncertain. Figure 3 demonstrates that TEMINET exhibits superior stability, with consistently lower accuracy reduction ratios across all masked ratios, compared to Mogonet and Dynamic. The robustness of TEMINET is attributed to its use of a graph-based topology and an uncertainty-based trust mechanism. While Mogonet also employs a graph-based approach by constructing similarity graphs among samples and incorporating the VCDN trust mechanism, its performance is moderate. Conversely, the Dynamic method, which relies on an encoder network and a confidence-based trust mechanism, displays a greater decrease in accuracy, indicating reduced robustness relative to TEMINET. The findings underscore that TEMINET not only maintains lower accuracy reduction ratios but also exhibits stability across various levels of data masking, highlighting the effectiveness of its graph-based approach and uncertainty-based trust mechanism in preserving model robustness.

3.5. Important biomarkers identified by TEMINET

Table 5. Top five significant disease-specific biomarkers identified by the TEMINET.

Dataset	Omics data type		
	mRNA expression	DNA methylation	miRNA expression
ROSMAP	*MEIS3, NPNT, KIF5A, GPIHBP1, SAMD4A, CDK18*	cg04126866, cg08367223, cg27091787, cg19485804, cg24192663	hsa-miR-132, hsa-miR-129-5p, hsa-miR-146b-5p, hsa-miR-129-3p, hsa-miR-143
BRCA	*CA9, GPM6B, FAM171A1, RARA, KLHL29*	*A2LD1, A2ML1, ABAT, ABCA13, ABCC11*	hsa-mir-3614, hsa-mir-3677, hsa-mir-760, hsa-mir-937, hsa-mir-1269
LGG	*ADD3, AGXT2L1, AMOT, DAAM2, FAM189A2*	—	—
KIPAN	—	*LOC649395*	hsa-mir-126, hsa-mir-1270-1, hsa-mir-1270-2, hsa-mir-1271, hsa-mir-145

In interpreting the model, the primary objective was to identify biomarkers of significance. As shown in Table 5, the five most discriminating biomarkers based on their differential values were reported. Those biomarkers with identical values received the same ranking. If the number of tied positions exceeded the threshold for reporting (i.e., five distinct ranks), a random set from the tied group was chosen to fulfill the report. Subsequently, we conducted a brief review of the existing literature to elucidate the biological significance and disease association of these identified biomarkers.

As shown in Table 5, existing advances in AD research have identified biomarkers associated with its pathogenesis. As the most significant mRNA biomarker of AD identified by the TEMINET, *MEIS3* was revealed by differential expression analysis to be considerably linked with cognitive decline and increased neurofibrillary tangle density [41,42]. Complementing this, cg19485804 (*NGEF*) emerged from LASSO regression analysis as another insight[43], notably associated with the APP mutation in mouse models. The downregulation of *NGEF* in the CVN-AD model suggested a critical role in modifying actin dynamics and consequently disrupting neuronal growth cone motility [44]. Furthermore, the microRNA miR-132 has been associated with the progression of Aβ and tau pathologies, with its reduced levels in circulation suggesting its utility as a potential diagnostic insight for AD. In the realm of breast cancer, *CA9* has been identified as a mRNA biomarker. A study has shown that BRCA patients with lower levels of *CA9* derive more benefit from adjuvant therapies, suggesting that *CA9* expression could be instrumental in tailoring patient-specific treatment plans [45]. The interaction between IGF2BP3, TRIM25, and miR-3614 delineated a novel regulatory pathway crucial for tumor cell proliferation. The protective role of IGF2BP3 in safeguarding TRIM25 mRNA from degradation and its influence on miR-3614 maturation presented new potential targets for therapeutic intervention in BRCA [46]. In LGG, our model did not reveal any methylation or miRNA biomarkers. However, *ADD3* was identified as the leading mRNA biomarker. Essential for actin cytoskeleton assembly, *ADD3* deficiency in GBM cells triggered pro-angiogenic signaling, enhancing VEGFR expression in endothelial cells, which could have implications for angiogenesis in LGG [47]. Suggested as a tumor suppressor and survival predictor on chromosome 10q, *ADD3* was valuable for prognostic assessments in LGG [48]. In kidney-related cancers, miR-126 has been recognized for its strong prognostic potential in clear cell renal cell carcinoma (ccRCC) [49], while miR-1271, markedly upregulated in ccRCC tissues, emerges as a significant marker for assessing disease severity [50]. These findings affirmed the robust capability of TEMINET in elucidating complex biological markers pertinent to disease mechanisms and therapy responsiveness.

4. Discussion and conclusion

The advancement in high-throughput techniques and individualized healthcare approaches has produced various supervised data collections critical for predictive applications such as pinpointing disease conditions, classifying tumor stages, and distinguishing cancer subtypes. The fusion of multi-omics information demonstrates enhanced efficacy in disease prediction compared to single omics approaches. For clinical applications, these integration models must not only provide precise diagnostic guidance but also cover a wide range of diseases. This underscores the necessity for models that exhibit both high accuracy and strong generalization across diverse medical conditions.

To achieve optimal multi-omics integration, the informativeness of modality representation has increasingly attracted attention. On the one hand, this informativeness reflects the quality of features specific to each omics type. This quality is not only contingent on the methodologies employed for feature representation but also on the inherent quality of the data. This is because data quality can be compromised during collection, storage, and processing, leading to potential loss and degradation. On the other hand, the informativeness of a modality significantly determines its contribution to the integration process. This contribution is measured by the extent to which data from a modality can complement or enhance the understanding that other omics types provide. It's not merely about the quantity of data each modality brings but the unique biological insights it offers that cannot be captured by others. Therefore, evaluating the informativeness of each modality representation is essential for ensuring that the most informative and relevant features are utilized for better predictive accuracy and deeper biological understanding.

In this study, we introduced TEMINET, a framework optimized for the trustworthy integration of multi-omics datasets. The advanced performance of TEMINET was credited to its joint observation of intra-omics molecular interactions and inter-omics informativeness. The framework addressed multifaceted complexities in disease pathogenesis by amalgamating omics data with topological models. Our approach involves constructing individual graphs for each subject within each omics data. This data formation strategy allows us to leverage the inner topological information among intra-omics molecules obtained from disease-specific data to improve model performance. It emphasized the importance of the interplay between genetic factors in revealing the underlying causes of diseases. Evidence from investigations revealed consistent outperformance of TEMINET across multiple metrics in four distinct tasks. This confirms that enhancing intra-omics informativeness can significantly improve the application performance of trustworthy learning strategies in multi-omics integration. Moreover, the combination ablation experiment substantiated the hypothesis that the growing variety of omics data types had significantly improved integration capabilities. Applied across four diverse diseases, TEMINET enhanced the understanding of disease mechanisms and patient stratification, revealing biomarkers as potential insights and offering precise classifications that aided healthcare professionals in developing personalized therapeutic interventions based on these deeper insights into patient conditions.

However, the model exhibits several limitations. While it concentrates on specific omics interactions, the model might overlook the broader dynamics between different omics. This oversight could reduce AUC performance, indicating that a more balanced approach should be considered in future developments. The handling of complex omics-specific co-expression networks by the model, though effective in certain datasets, is computationally demanding. This is particularly evident in its performance with the BRCA dataset, indicating potential scalability issues for larger datasets. Moving forward, our efforts will focus on enhancing the algorithm of the model to integrate and interpret broad inter-omics patterns more effectively, aiming for a comprehensive understanding of complex disease mechanisms.

Author Contributions: Conceptualization, Xiaohui Yao and Shan Cong; methodology, Haoran Luo and Hong Liang; investigation, Haoran Luo and Hongwei Liu; data preparation, Haoran Luo and

Zhoujie Fan; writing—original draft, Haoran Luo and Shan Cong; writing—review and editing, Yanhui Wei, Xiaohui Yao, and Shan Cong. All authors have read and agreed to the published version of the manuscript.

Data Availability Statement: The raw omics data of ROSMAP is available at https://doi.org/10.7303/syn2580853. The raw omics data of BRCA, LGG, and KIPAN are available at https://portal.gdc.cancer.gov/. Codes are available at https://github.com/Yaolab-fantastic/TEMINET.

References

1. Tarazona, S.; Arzalluz-Luque, A.; Conesa, A. Undisclosed, unmet and neglected challenges in multi-omics studies. *Nature Computational Science* **2021**, *1*, 395–402.
2. Joshi, A.; Rienks, M.; Theofilatos, K.; Mayr, M. Systems biology in cardiovascular disease: a multiomics approach. *Nature Reviews Cardiology* **2021**, *18*, 313–330.
3. Hampel, H.; Nisticò, R.; Seyfried, N.T.; Levey, A.I.; Modeste, E.; Lemercier, P.; Baldacci, F.; Toschi, N.; Garaci, F.; Perry, G.; et al. Omics sciences for systems biology in Alzheimer's disease: State-of-the-art of the evidence. *Ageing Research Reviews* **2021**, *69*, 101346.
4. Reel, P.S.; Reel, S.; Pearson, E.; Trucco, E.; Jefferson, E. Using machine learning approaches for multi-omics data analysis: A review. *Biotechnology Advances* **2021**, *49*, 107739.
5. Kang, M.; Ko, E.; Mersha, T.B. A roadmap for multi-omics data integration using deep learning. *Briefings in Bioinformatics* **2022**, *23*, bbab454.
6. Krassowski, M.; Das, V.; Sahu, S.K.; Misra, B.B. State of the field in multi-omics research: from computational needs to data mining and sharing. *Frontiers in Genetics* **2020**, *11*, 610798.
7. Picard, M.; Scott-Boyer, M.P.; Bodein, A.; Périn, O.; Droit, A. Integration strategies of multi-omics data for machine learning analysis. *Computational and Structural Biotechnology Journal* **2021**, *19*, 3735–3746.
8. Zitnik, M.; Nguyen, F.; Wang, B.; Leskovec, J.; Goldenberg, A.; Hoffman, M.M. Machine learning for integrating data in biology and medicine: Principles, practice, and opportunities. *Information Fusion* **2019**, *50*, 71–91.
9. Stahlschmidt, S.R.; Ulfenborg, B.; Synnergren, J. Multimodal deep learning for biomedical data fusion: a review. *Briefings in Bioinformatics* **2022**, *23*, bbab569.
10. Park, C.; Ha, J.; Park, S. Prediction of Alzheimer's disease based on deep neural network by integrating gene expression and DNA methylation dataset. *Expert Systems with Applications* **2020**, *140*, 112873.
11. Xie, G.; Dong, C.; Kong, Y.; Zhong, J.F.; Li, M.; Wang, K. Group lasso regularized deep learning for cancer prognosis from multi-omics and clinical features. *Genes* **2019**, *10*, 240.
12. Zhao, L.; Dong, Q.; Luo, C.; Wu, Y.; Bu, D.; Qi, X.; Luo, Y.; Zhao, Y. DeepOmix: A scalable and interpretable multi-omics deep learning framework and application in cancer survival analysis. *Computational and structural biotechnology journal* **2021**, *19*, 2719–2725.
13. Chaudhary, K.; Poirion, O.B.; Lu, L.; Garmire, L.X. Deep learning–based multi-omics integration robustly predicts survival in liver cancer. *Clinical Cancer Research* **2018**, *24*, 1248–1259.
14. Lee, T.Y.; Huang, K.Y.; Chuang, C.H.; Lee, C.Y.; Chang, T.H. Incorporating deep learning and multi-omics autoencoding for analysis of lung adenocarcinoma prognostication. *Computational Biology and Chemistry* **2020**, *87*, 107277.
15. Franco, E.F.; Rana, P.; Cruz, A.; Calderon, V.V.; Azevedo, V.; Ramos, R.T.; Ghosh, P. Performance comparison of deep learning autoencoders for cancer subtype detection using multi-omics data. *Cancers* **2021**, *13*, 2013.
16. Simidjievski, N.; Bodnar, C.; Tariq, I.; Scherer, P.; Andres Terre, H.; Shams, Z.; Jamnik, M.; Liò, P. Variational autoencoders for cancer data integration: design principles and computational practice. *Frontiers in genetics* **2019**, *10*, 1205.
17. Ronen, J.; Hayat, S.; Akalin, A. Evaluation of colorectal cancer subtypes and cell lines using deep learning. *Life science alliance* **2019**, *2*.
18. Han, Z.; Yang, F.; Huang, J.; Zhang, C.; Yao, J. Multimodal Dynamics: Dynamical Fusion for Trustworthy Multimodal Classification. In Proceedings of the Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR), June 2022, pp. 20707–20717.
19. Wang, T.; Shao, W.; Huang, Z.; Tang, H.; Zhang, J.; Ding, Z.; Huang, K. MOGONET integrates multi-omics data using graph convolutional networks allowing patient classification and biomarker identification. *Nature Communications* **2021**, *12*, 1–13.
20. Muzio, G.; O'Bray, L.; Borgwardt, K. Biological network analysis with deep learning. *Briefings in bioinformatics* **2021**, *22*, 1515–1530.
21. Cowen, L.; Ideker, T.; Raphael, B.J.; Sharan, R. Network propagation: a universal amplifier of genetic associations. *Nature Reviews Genetics* **2017**, *18*, 551–562.
22. Hasin, Y.; Seldin, M.; Lusis, A. Multi-omics approaches to disease. *Genome biology* **2017**, *18*, 1–15.
23. Ramirez, R.; Chiu, Y.C.; Hererra, A.; Mostavi, M.; Ramirez, J.; Chen, Y.; Huang, Y.; Jin, Y.F. Classification of cancer types using graph convolutional neural networks. *Frontiers in physics* **2020**, *8*, 203.
24. Althubaiti, S.; Kulmanov, M.; Liu, Y.; Gkoutos, G.V.; Schofield, P.; Hoehndorf, R. DeepMOCCA: A pan-cancer prognostic model identifies personalized prognostic markers through graph attention and multi-omics data integration. *BioRxiv* **2021**, pp. 2021–03.

25. Xing, X.; Yang, F.; Li, H.; Zhang, J.; Zhao, Y.; Gao, M.; Huang, J.; Yao, J. Multi-level attention graph neural network based on co-expression gene modules for disease diagnosis and prognosis. *Bioinformatics* **2022**, *38*, 2178–2186.
26. Langfelder, P.; Horvath, S. WGCNA: an R package for weighted correlation network analysis. *BMC bioinformatics* **2008**, *9*, 1–13.
27. Veličković, P.; Cucurull, G.; Casanova, A.; Romero, A.; Lio, P.; Bengio, Y. Graph attention networks. *arXiv preprint arXiv:1710.10903* **2017**.
28. Han, Z.; Zhang, C.; Fu, H.; Zhou, J.T. Trusted Multi-View Classification with Dynamic Evidential Fusion. *IEEE Transactions on Pattern Analysis and Machine Intelligence* **2022**.
29. Jsang, A. *Subjective Logic: A formalism for reasoning under uncertainty*; Springer Publishing Company, Incorporated, 2018.
30. Evelyn, F.; JL, H. Discriminatory Analysis. Nonparametric Discrimination: Consistency Properties. *International Statistical Review/Revue Internationale de Statistique* **1989**, *57*, 238.
31. Cortes, C.; Vapnik, V. Support-vector networks. *Machine learning* **1995**, *20*, 273–297.
32. Ranstam, J.; Cook, J. LASSO regression. *Journal of British Surgery* **2018**, *105*, 1348–1348.
33. Ho, T.K. Random decision forests. In Proceedings of the Proceedings of 3rd International Conference on Document Analysis and Recognition. IEEE, 1995, Vol. 1, pp. 278–282.
34. Chen, T.; Guestrin, C. Xgboost: A scalable tree boosting system. In Proceedings of the Proceedings of the 22nd acm sigkdd international conference on knowledge discovery and data mining, 2016, pp. 785–794.
35. Schwenker, F.; Trentin, E. Pattern classification and clustering: A review of partially supervised learning approaches. *Pattern Recognition Letters* **2014**, *37*, 4–14.
36. Van De Wiel, M.A.; Lien, T.G.; Verlaat, W.; van Wieringen, W.N.; Wilting, S.M. Better prediction by use of co-data: adaptive group-regularized ridge regression. *Statistics in medicine* **2016**, *35*, 368–381.
37. Singh, A.; Shannon, C.P.; Gautier, B.; Rohart, F.; Vacher, M.; Tebbutt, S.J.; Lê Cao, K.A. DIABLO: an integrative approach for identifying key molecular drivers from multi-omics assays. *Bioinformatics* **2019**, *35*, 3055–3062.
38. Hong, D.; Gao, L.; Yokoya, N.; Yao, J.; Chanussot, J.; Du, Q.; Zhang, B. More diverse means better: Multimodal deep learning meets remote-sensing imagery classification. *IEEE Transactions on Geoscience and Remote Sensing* **2020**, *59*, 4340–4354.
39. Arevalo, J.; Solorio, T.; Montes-y Gómez, M.; González, F.A. Gated multimodal units for information fusion. *arXiv preprint arXiv:1702.01992* **2017**.
40. Zhong, Y.; Peng, Y.; Lin, Y.; Chen, D.; Zhang, H.; Zheng, W.; Chen, Y.; Wu, C. MODILM: towards better complex diseases classification using a novel multi-omics data integration learning model. *BMC Medical Informatics and Decision Making* **2023**, *23*, 1–18.
41. Tang, S.; Buchman, A.S.; Wang, Y.; Avey, D.; Xu, J.; Tasaki, S.; Bennett, D.A.; Zheng, Q.; Yang, J. Differential gene expression analysis based on linear mixed model corrects false positive inflation for studying quantitative traits. *Scientific Reports* **2023**, *13*, 16570.
42. Li, Q.S.; De Muynck, L. Differentially expressed genes in Alzheimer's disease highlighting the roles of microglia genes including OLR1 and astrocyte gene CDK2AP1. *Brain, Behavior, & Immunity-Health* **2021**, *13*, 100227.
43. Shi, C.; Gottschalk, W.K.; Colton, C.A.; Mukherjee, S.; Lutz, M.W. Alzheimer's Disease Protein Relevance Analysis Using Human and Mouse Model Proteomics Data. *Frontiers in systems biology* **2023**, *3*.
44. Shamah, S.M.; Lin, M.Z.; Goldberg, J.L.; Estrach, S.; Sahin, M.; Hu, L.; Bazalakova, M.; Neve, R.L.; Corfas, G.; Debant, A.; et al. EphA receptors regulate growth cone dynamics through the novel guanine nucleotide exchange factor ephexin. *Cell* **2001**, *105*, 233–244.
45. Span, P.; Bussink, J.; Manders, P.; Beex, L.; Sweep, C. Carbonic anhydrase-9 expression levels and prognosis in human breast cancer: association with treatment outcome. *British journal of cancer* **2003**, *89*, 271–276.
46. Wang, Z.; Tong, D.; Han, C.; Zhao, Z.; Wang, X.; Jiang, T.; Li, Q.; Liu, S.; Chen, L.; Chen, Y.; et al. Blockade of miR-3614 maturation by IGF2BP3 increases TRIM25 expression and promotes breast cancer cell proliferation. *EBioMedicine* **2019**, *41*, 357–369.
47. Kiang, K.M.Y.; Zhang, P.; Li, N.; Zhu, Z.; Jin, L.; Leung, G.K.K. Loss of cytoskeleton protein ADD3 promotes tumor growth and angiogenesis in glioblastoma multiforme. *Cancer Letters* **2020**, *474*, 118–126.
48. Kiang, K.M.Y.; Sun, S.; Leung, G.K.K. ADD3 deletion in glioblastoma predicts disease status and survival. *Frontiers in Oncology* **2021**, *11*, 717793.
49. Carlsson, J.; Christiansen, J.; Davidsson, S.; Giunchi, F.; Fiorentino, M.; Sundqvist, P. The potential role of miR-126, miR-21 and miR-10b as prognostic biomarkers in renal cell carcinoma. *Oncology Letters* **2019**, *17*, 4566–4574.
50. Cochetti, G.; Cari, L.; Nocentini, G.; Maula, V.; Suvieri, C.; Cagnani, R.; Rossi De Vermandois, J.A.; Mearini, E. Detection of urinary miRNAs for diagnosis of clear cell renal cell carcinoma. *Scientific Reports* **2020**, *10*, 21290.