1

Influence of social and semantic contexts on phonetic encoding in

naturalistic conversations

Etienne Abassi[1] & Robert J. Zatorre[1]

[1]Montreal Neurological Institute – McGill University,

[1]Centre for Research in Brain, Language and Music (CRBLM)

[1]International Laboratory for Brain, Music and Sound Research (BRAMS)

Correspondence to:

E.A.* etienne.abassi@gmail.com

R.Z. robert.zatorre@mcgill.ca

Competing interests: All authors declare that they have no financial or non-financial competing

interests.

ABSTRACT

Social interactions occupy a significant part of life, and understanding others' conversations is key to navigating our social world. While the role of semantics in speech comprehension is well-established at the word or sentence level, its influence on larger conversational scales, alongside social context, is less understood. The present study examined how semantic and social contexts modulate phonetic encoding during natural conversations using a speech-in-noise paradigm. Participants listened to AI-generated dialogues (two speakers) or monologues (one speaker) in an intact or sentence-scrambled order. Each trial contained five sentences, with the fifth sentence embedded in multi-talker babble noise. The same sentence was then repeated without noise, with one word either altered or unchanged. Healthy adults identified whether the sentence matched the in-noise version. Through several online experiments (N=211), both social and semantic contexts showed influences on speech-in-noise processing, with improved performance for dialogues over monologues and for intact over sentence-scrambled conversations. These results suggest that both semantic and social factors shape speech comprehension, emphasizing their role in auditory cognition. This finding raises important questions about predictive and other mechanisms involved in processing complex, multi-sentence conversations, underscoring the critical role of social interaction in communication.

KEYWORDS

Phonetic encoding, Conversations, Context, Social, Semantic

I. INTRODUCTION

During our lifetime, we humans deploy complex abilities to navigate our social world (Adolphs, 2001, 2009). Consequently, a significant portion of our existence is devoted to engaging in social interactions with others. Not only do we interact in the first person, but listening to others' interactions also serves critical functions in understanding our social world. Hence, successful understanding of others relies on the seamless integration of sensory input and cognitive mechanisms, enabling us to understand speech across diverse and often challenging auditory environments. Central to this process is phonetic encoding, the mapping of acoustic signals onto linguistic representations, which underpins speech comprehension (Clements, 1985; Jakobson et al., 1951; Lahiri & Reetz, 2010; Sapir, 1925; Yi et al., 2019). While much of the existing research has examined how speech is processed in controlled environments using single sentences or words, real-world communication involves multiple layers of complexity, including listening contexts that influence how phonetic encoding unfolds (Kuperberg & Jaeger, 2016; Sohoglu et al., 2012). Understanding the mechanisms by which these contexts shape speech perception is critical for advancing theories of auditory cognition and improving interventions for individuals with hearing loss.

Semantic context, or the coherence and meaning embedded in speech, has long been recognized as a critical factor in speech processing, and plays a pivotal role in phonetic encoding. Coherent sentences allow listeners to predict upcoming words and phonetic structures, reducing cognitive load and improving processing efficiency (Sohoglu et al., 2012; Zekveld et al., 2011, 2012, 2013). For example, sentences with meaningful content enable listeners to disambiguate phonetic details, particularly in acoustically challenging environments such as noisy or multi-talker settings (Kuperberg & Jaeger, 2016; O'Neill et al., 2021). These predictive mechanisms are

often conceptualized within the framework of predictive coding, which posits that the brain

generates expectations based on prior input to minimize the mismatch between sensory input and

cognitive predictions (Clark, 2013; Friston, 2005; Rao & Ballard, 1999). Semantic congruence

facilitates phonetic encoding by reinforcing expectations and enhancing signal clarity, while

semantic incongruence or nonsense sentences disrupt these processes and impose greater cognitive

demands (Golestani et al., 2009, 2013; Zekveld et al., 2011).

Research on semantic context has typically focused on isolated words or sentences. For

instance, studies have shown that listeners process phonemes more accurately when words appear

in semantically predictable sentences (Roland et al., 2012; Zekveld et al., 2013) and that speech

patterns at different timescales are processed using different mechanisms and/or brain circuitry.

Indeed, shorter timescales, such as phonemes and syllables, primarily engage the left middle

superior temporal gyrus (mid-STG), while longer units like words or sentences recruit the left

anterior STG (DeWitt & Rauschecker, 2012; Lerner et al., 2011). Additionally, EEG recording

during speech naturalistic listening shows that semantic contexts can enhance early auditory

responses as well as speech envelope reconstruction (Broderick et al., 2019). However, most work

to date has examined semantic processing in highly constrained contexts, such as isolated words,

word pairs, or single sentences presented in controlled, low-variability environments. While these

approaches offer experimental precision, they do not fully capture the richness of everyday

language use. In natural speech, particularly in conversation, meaning is built incrementally across

multiple utterances, supported by broader semantic and pragmatic cues. Studies using connected

speech materials, such as the Connected Speech Test (Cox et al., 1987), a standardized measure of

speech intelligibility using short conversational passages presented in background noise, or

naturalistic corpora like the LUCID database (Baker & Hazan, 2010, 2011), suggest that broader

semantic context improves intelligibility. However, these studies typically do not isolate the

specific effects of context on phonetic encoding. The present study addresses this gap by

examining how semantic context within prototypical conversations influences phonetic encoding.

Here, we focus on how large-scale semantic congruency in the context of conversations can

support lower-level auditory encoding, shedding light on the interaction between linguistic

prediction and speech perception in more ecologically valid settings.

While semantic context focuses on the linguistic coherence of speech, social context, on

the other hand, encompasses the interactional dynamics and relational cues present in

communication. As such, it may represent another critical factor influencing phonetic encoding.

Here, dynamic exchanges between speakers, such as turn-taking and conversational flow, may

engage cognitive systems that are tuned to socially relevant stimuli while providing listeners with

additional scaffolding for auditory processing. For instance, dialogues involving alternating

speakers provide structural and temporal cues that enhance speech comprehension compared to

monologues (Fox Tree, 1999). These interactional dynamics may facilitate phonetic encoding by

directing attention to relevant acoustic signals and reinforcing cognitive predictions about speaker

behavior (Levy et al., 2003). Social context is further enriched by factors such as speaker identity,

familiarity, and social relationships. Familiar voices are processed more efficiently than unfamiliar

ones (Domingo et al., 2020; Johnsrude et al., 2013), as listeners can leverage prior knowledge to

disambiguate phonetic details and interpret speech more effectively (Belin et al., 2000). Similarly,

shared social knowledge and relational dynamics can modulate auditory processing by providing

additional contextual scaffolding. For example, listeners process speech more accurately when

they share a common linguistic background with the speaker (Adank et al., 2009; Lev-Ari &

Keysar, 2010; Smith & Bisazza, 1982), although the overall evidence for interlanguage benefits is

mixed, with several studies reporting only marginal or null effects (Bent & Bradlow, 2003; Hayes-

Harb et al., 2008; Major et al., 2002; Munro et al., 2006). On a last note, social context can also

influence speech perception not only through interactional dynamics, but also via social

evaluation. Indeed, prior work has shown that listeners' perceptions of intelligibility are shaped by

attitudes, stereotypes, and expectations about the speaker, even when acoustic cues are held

constant (Babel & Russell, 2015; Lev-Ari & Keysar, 2010; McGowan, 2015; Niedzielski, 1999;

Rubin, 1992). These findings highlight the broader role of social cognition in auditory processing

(Drager & Kirtley, 2016). Overall, these effects suggest that social interaction engages specialized

neural and cognitive systems that enhance phonetic encoding and speech comprehension.

Dialogues, as a prototypical form of social interaction, offer particularly rich opportunities for

examining the influence of social context. Unlike monologues, dialogues involve interactive turn-

taking, which creates temporal predictability and facilitates attentional engagement. Previous

studies have shown that listeners perceive dialogues as more intelligible than monologues, even

when the content is identical, suggesting that interactional dynamics enhance cognitive processing

(Branigan et al., 2011; Pickering & Garrod, 2021; Tolins et al., 2018). However, the mechanisms

underlying this advantage remain poorly understood.

Going further, the influence of context in sensory processing of a stimulus is not only

known in the auditory modality but also in the visual modality (Brandman & Peelen, 2017; Oliva

& Torralba, 2007), where recent work showed that the neural representation of a single body within

a dyad is sharpened when the two bodies are represented face-to-face (as if interacting) as

compared to back-to-back (Abassi et al., 2020; Bellot et al., 2021). This effect shows that a given

social context can have a significant influence on the perception of a visual stimulus and its neural

processing. Both visual and auditory systems are organized hierarchically, progressing from early

sensory encoding (e.g., pitch or shape) to the integration of higher-level features such as linguistic

content or social intent (Iamshchinina et al., 2022). These layered structures allow top-down

influences, such as contextual or social expectations, to shape perception in both modalities. For

instance, just as the presence of an interacting body pair enhances neural encoding of a single body

in vision (Abassi et al., 2020), we hypothesize that dialogue-based interaction may enhance

encoding of verbal sentences in auditory scenes. Drawing on this analogy, we suggest that social

context may similarly modulate auditory perception, particularly under challenging listening

conditions. Here, the social context involves intricate mechanisms related to the interplay between

two or more speakers, elements that are generally overlooked in the examination of higher-order

top-down cues. Thus, building on the literature of both social audition and vision, a major aim of

this study is isolating the effects of social interaction on phonetic encoding, controlling for

semantic content to focus on the contribution of interactional cues such as speaker alternation and

conversational flow.

On a last point, individual differences in a listener's sensitivity to social contexts may

influence phonetic encoding, particularly through variations in social traits. Indeed, the Autism

Spectrum Quotient (AQ), a widely used measure of autism-related traits in both neurodiverse and

neurotypical populations (Baron-Cohen et al., 2001), has been consistently linked to reduced

sensitivity to social stimuli. More specifically, neurotypical individuals with higher AQ scores

demonstrate diminished sensitivity in visual tasks involving social stimuli, such as processing

dyadic body interactions (Abassi & Papeo, 2022), faces (Wyer et al., 2012), biological motion (van

Boxtel et al., 2017), and animals (Yang et al., 2024). These findings suggest a general link between

individual differences in social-related traits and integration of social cues in the visual modality,

which may extend to auditory perception in contexts emphasizing social interaction dynamics. In

parallel, higher AQ scores have been associated with enhanced attention to fine phonetic details

(Ota et al., 2015; Stewart & Ota, 2008; Yu, 2010), suggesting a potential advantage in auditory

tasks focusing on precise acoustic distinctions. However, this strength may not fully compensate

for the reduced sensitivity to social dynamics in tasks requiring the integration of social cues for

phonetic processing. This dual influence highlights how individuals with higher AQ scores might

excel in isolated phonetic tasks but face challenges in contexts where social dynamics are critical

for guiding perceptual processes. By including AQ scores in the present study, we aim to

investigate how sensitivity to social interaction dynamics may modulate the effects of semantic

and social contexts on phonetic encoding.

Overall, in the current study we investigated the influence of semantic and social contexts

on phonetic encoding. Specifically, we hypothesized that both semantic coherence and dynamic

social interactions would enhance the encoding of phonetic information. In addition, we also

sought to explore whether their effects are independent or interacting. To test these hypotheses,

we manipulated the semantic context (intact vs. sentence-scrambled conversations) and social

context (dialogues vs. monologues) in which a sentence was heard, using a speech-in-noise

paradigm to measure perceptual sensitivity. Speech-in-noise paradigms provide an effective

framework for studying phonetic encoding under controlled conditions that approximate real-

world listening challenges. By introducing competing auditory stimuli, these tasks require listeners

to draw on higher-order cognitive mechanisms, such as context-based predictions, to process

speech effectively (Zekveld et al., 2013). In our design, semantic coherence may primarily enhance

phonetic encoding by increasing linguistic predictability, whereas social context may offer cues

related to speaker dynamics and turn-taking structure. While our focus is on identifying the

contribution of each context, our factorial design also allows us to test whether their effects are

independent or interacting. By combining speech-in-noise tasks with controlled manipulations of

semantic and social cues, we aimed to isolate the mechanisms through which large-scale high-

level contexts could enhance speech perception. However, unlike previous research, which has

often focused on isolated words or sentences, our study examines how these factors operate at the

level of larger-scale naturalistic conversations, offering a more comprehensive understanding of

real-world speech perception.

To address these questions, we conducted two main experiments (summarized in Table 1).

Experiment 1 was a preliminary study aimed at identifying an appropriate signal-to-noise ratio

(SNR) for use in the main experiment. Experiment 2 tested the effects of semantic and social

context on speech processing across several presentation formats, using different groupings and

block structures to control for potential order effects. The implications of this research extend

beyond basic auditory science, as individuals with hearing loss or social-cognitive impairments

often struggle to process speech in complex environments where both semantic and social cues

play a critical role (Ciorba et al., 2012; Nordvik et al., 2018). By elucidating the mechanisms

underlying phonetic encoding in these contexts, this study lays the groundwork for developing

more ecologically valid assessment tools and assistive technologies, such as hearing aids that

leverage conversational dynamics and contextual predictions to enhance speech processing.

II. METHODS

A. Participants. A total of 295 participants took part in our on-line study (Exp 1: 80 participants,

29 females, 3 sex unreported, mean age 29.8 years +/- 6.2 SD; Exp 2: 215 participants, 85 females,

2 sex unreported, mean age 31.6 years +/- 5.6 SD). Overall, the minimal sample size for each

experiment was based on previous literature using analogous word-recognition tasks in multi-

talker babble noise. More specifically, Killion et al. (2004) found significant results for the

QuickSIN test (which measures whole sentences recognition in noise) using 16 participants and

Wilson (2003) used 24 participants for the Word-In-Noise (WIN) test (which assesses isolated

words recognition in noise), while in our current study we had a minimum of 40 participants for

each experimental subset (see below). All participants read and signed an informed consent form

prior to participating in the study and were remunerated 6£ for ~40 minutes of their time, paid

through the on-line platform (prolific.com). They were all American English first-language

speakers with normal hearing (determined by self-report online), aged between 18 and 40 years.

They were recruited on the Prolific platform and the study was restricted only to people with a

desktop computer or a laptop. Prior to enrolling in the study, online participants were instructed

that wearing headphones or earbuds was mandatory to participate. They were also asked to be in

a silent and calm environment, as well as avoid having any object around them that may disturb

their attention, such as a smartphone or a TV on.

B. Stimuli.

1. Stimuli features. The main stimulus set consisted of AI generated English two-speaker

dialogues or one-speaker monologues (factor: social context) arranged in intact or sentence-

scrambled order (factor: semantic context) (Fig. 1). In the current study, we use the term

"conversation" as a general label to describe all four stimulus conditions, for the sake of simplicity

and consistency across the manuscript. However, only the intact dialogue condition fully meets

the conventional definition of a "conversation", featuring multiple speakers, turn-taking, and

coherent topical flow. The other conditions systematically altered aspects of this structure: In the

monologue conditions, the same dialogues were rendered by a single speaker, thus preserving

sentence content but eliminating speaker alternation. In the scrambled conditions, sentence order

was randomized, disrupting semantic coherence at the conversational level while maintaining

semantic coherence at the sentence-level. All stimuli were created using a combination of

ChatGPT (GPT-3.5, *OpenAI*) to generate the contents of the conversations and Google text-to-

speech AI to convert the textual conversations into natural-sounding speech. The entire set of

stimuli and materials for generation can be found online at

www.zlab.mcgill.ca/downloads/Stimuli_from_Abassi_2025. A sample is also provided as

supplementary files (*SuppPub2.zip*).

2. Speech voices AI generation. The choice of using AI-generated stimuli instead of recorded

human actors voices was made for two main reasons: 1) AI generation allowed us to create auditory

stimuli that were purely prototypical of real speech and, importantly, devoid of any fluctuation in

the inner features of speech that naturally occurred from humans' speakers (i.e., variations in

rhythm, intonation, articulation, etc…), that could have created confounds between sentences or

conditions. This point was especially important in light of the specific conditions we were

studying, for which the individual sentences features had to be exactly identical across conditions.

2) AI generation allowed us to have very fine control of specific features of speech that we wanted

to be able to easily modulate (i.e., fundamental frequency, pitch and prosody). AI-generated speech

may lack features of truly natural conversation, such as prosodic entrainment across speakers or

adaptive rhythm over time. However, our goal was not to simulate fully natural conversations, but

to create prototypical and tightly controlled conversational stimuli, especially with regard to

timing, pitch range, and segmental clarity. For this reason, we prioritized consistency and acoustic

control over naturalness *per se*, and we did not conduct formal perceptual validation. Informal

pilot testing confirmed that the speech was easily understood by naïve listeners and that it sounded

quite natural.

We selected a fundamental frequency (f0) of 120 Hz for the male voice, and of 181 Hz for

the female voice using the built-in-function of Google text-to-speech AI that permits to increment

or decrement the overall pitch of a voice by a custom number of semi-tones. Thus, for a chosen f0,

we looped between the text-to-speech AI generator and custom MATLAB codes to measure the

f0, by decrementing or incrementing by one semitons until we reached our chosen f0. Here, the

chosen f0 values for the female and male voices were separated by 4 semi-tones, and this two f0

were chosen in a set of 10 semi-tones ranging from 120 Hz to 203 Hz. We selected this overall f0

range so it was large enough to cover a representative range of f0 in the general population (see

Cristina Oliveira et al., 2021). The remaining semi-tones were used as f0 for the 8 competing

voices used as multi-talker babble noise, for which details are given below (see also supplementary

figure 1, featuring a graphical similarity representation of the distribution of semi-tones across

male and female voices). For the voice's identities used in the final generation, we chose 2 voices

among a list of 10 proposed voices by the text-to-speech generator (male voice identity: "en-US-

Wavenet-J"; female voice identity: "en-US-Wavenet-G"), with the criteria of their initial f0 before

fine-tuning being the closest to the f0 we aimed to reach.

3. Speech content AI generation. Each conversation was then carefully constructed to ensure that

dialogues and monologues had the same sentence structures and themes, isolating the effect of

social context. Indeed, dialogues featured alternating male and female voices, providing turn-

taking cues and interactive dynamics that were absent in monologues, which were all produced by

the same voice. This design allowed us to investigate how the presence of two interacting voices,

versus a single continuous voice, influences the listener's processing of speech. More specifically,

we first used ChatGPT to generate the text of 35 five-sentence conversations based on five themes

(Music, Cinema, Sport, Literature and Travel). An example of the ChatGPT prompts used is *"On*

the topic of music, write X conversations of 5 sentences each between two persons with a maximum

of 15 words per sentence". We did not use the exact conversation contents as generated by

ChatGPT, but rather made modifications such as word, syntax, and length changes to enhance the

naturalistic aspect of each item. For each five-sentence conversation, we manually created a sixth

sentence by changing a single word from the original (fifth) sentence. The change was designed

to be subtle, maintaining grammaticality and plausibility within the sentence while introducing a

distinct phonetic form. For example, *"He is a **true** genius"* was changed to *"He is a **pure** genius"*

The substituted words were chosen to differ phonologically from the original, while avoiding

semantic or pragmatic violations. To avoid predictability, the location of the altered word varied

across sentences (beginning, middle, or end) and was not fixed. The modified words had the same

number of syllables as the target word and were drawn from the same broad grammatical category

(typically adjectives, nouns, or verbs). This semi-controlled approach allowed for natural-

sounding stimuli while minimizing systematic cues. Thus, the manipulations were exclusively

related to the *context* within which the target sentence was presented, and not to the structure or

content of the target sentence itself.

4. Prosody generation. To enhance prosodic naturalness, we used Speech Synthesis Markup

Language (SSML), an XML-based standard developed by the World Wide Web Consortium

(W3C) to control expressive features of synthetic speech, such as pitch, speaking rate, volume,

and pausing (W3C, 2010). SSML allows users to insert markup tags into text that guide how speech

synthesis engines render prosody. In our case, we used it to manually adjust pitch and rate within

sentences. For example, we used *<prosody rate="fast" pitch="+4st">* to increase speed and pitch

on specific words. While SSML does not encode linguistic prosodic features (like pitch accents or

boundary tones) directly, it provides precise control over acoustic cues. This helped ensure that

individual sentences were prosodically varied and easily interpretable, even if the resulting speech

did not fully replicate the dynamic prosody of natural human dialogue. The complete list of

sentences with their prosody tags is available in the stimuli dataset package given in supplementary

materials (*SuppPub2.zip*). We then selected two voices from the list proposed by Google text-to-

speech AI: one female voice (*'en-US-Wavenet-G'*) and one male voice (*'en-US-Wavenet-J'*). We

finally converted each text sentence of each conversation into auditory speech for the two voices,

and we normalized all audio tracks to have the same root mean squared (RMS) amplitude across

all sentences.

5. Sentences arrangements. We then arranged the sentences into conversations as follows. For

intact dialogues, half of the conversations began with the female voice and alternated with the male

voice, and for the other half it was the opposite. For monologues, half of the conversations were

composed of the female voice only, while the other half was composed of the male voice only.

Furthermore, for both dialogues and monologues, sentence-scrambled conversations were created

by randomly shifting sentences across the conversations (i.e., across distinct topics), except for the

fifth sentences. Sentence positions were also fully randomized within each conversation, rather

than swapped across conversations, to prevent accidental preservation of overarching structures

such as question-answer pairs or turn-taking patterns.

In total, we created 240 conversational stimuli (60 stimuli by unique condition, half primed

with female voice and half primed with male voice). Between every sentence, we added a silent

gap randomized between 400 and 600 ms, except between the fifth and the sixth sentences, where

a silent gap of 1 s. was added. On average, each full conversation had a total duration of ~18 s.

Social context

	Dialogue	*Monologue*
Intact	I am in the mood for some jazz music *I love Jazz ! Do you have a favorite artist?* Miles Davis is one of my favorites! *Me too! I love his trumpet playing* Yes! He is a **true** genius! Yes! He is a **pure** genius!	I am in the mood for some jazz music I love Jazz ! Do you have a favorite artist? Miles Davis is one of my favorites! Me too! I love his trumpet playing Yes! He is a **true** genius! Yes! He is a **pure** genius!
Scrambled	I am in the mood for some jazz music *No, I didn't know about it! Did you go?* That's great! which sport? *No, I'm still reading it. It's really good!* Yes! He is a **true** genius! Yes! He is a **pure** genius!	I am in the mood for some jazz music No, I didn't know about it! Did you go? That's great! which sport? No, I'm still reading it. It's really good! Yes! He is a **true** genius! Yes! He is a **pure** genius!

—— Speaker 1   —— *Speaker 2*

Figure 1. Example of conversations composing the stimuli set. Stimuli are arranged following a 2x2 design with factors social context (Dialogue / Monologue) and semantic context (Intact / Scrambled). For dialogues, sentences presented in green standard text alternating with brown italic text represent the alternation between the two speakers (one female and one male). Sentences presented over grey background illustrate that the fifth sentence of each conversation was always embedded in noise. The last sentence could be either the same or different than the previous one, with only one word changed between the sentences, as represented in bold red. The entire set of stimuli can be found online at *www.zlab.mcgill.ca/stimuli* ('Stimuli_from_Abassi_2025') or attached in supplementary materials (*SuppPub2.zip*).

6. One-sentence stimuli. In addition to dialogues and monologues, we created a set of 50 one-sentence stimuli that were different than the sentences used in the conversations and were used as a baseline condition to control for inter-individual variability in performance in processing speech-in-noise. For each of these sentences, we created a second sentence by hand, that was the same as the first sentence with the change of a single word from the original sentence, and the location of the altered word varied across sentences (beginning, middle, or end). Similarly to the main

experiment (conversations), the word change itself was unrelated to the content of the

conversation—that is, it was a neutral word within the sentence that would be equally appropriate

in the context. We then converted these sentences into natural-sounding speech for both female

and male voices, using the same method as for the conversations. For example, one of the ChatGPT

prompts used to generate the text of these one-sentence stimuli was *"Write X sentences on the*

topic of music with a maximum of 15 words per sentence". We then added prosody tags following

SSML rules and transformed them into audio using Google text-to-speech. In total, we created

100 one-sentence stimuli (50 for female and 50 for male), for an average duration of ~5 s. each.

7. Multi-talker babble noise. In a last step, we embedded the fifth sentence of each conversation,

as well as all the one-sentence baseline stimuli into 8-voices multi-talker babble noise. We used

multi-talker babble noise as a masker for our stimuli because we wanted it to be as naturalistic as

possible (for a review on the different types of maskers, see Assmann & Summerfield, 2004)).

Detailed information about the noise features and its generation are given in supplementary

information 1. After generating the 24 audio distractor sentences for each of the 8 voices, we

created the multi-talker noise stimuli using custom Matlab codes, closely following the method of

Van Engen & Bradlow (2007): 1) Each audio track was normalized to have the same RMS

amplitude across all tracks; 2) For each talker, two randomly chosen sentences were concatenated

to ensure the duration of the noise tracks would exceed the durations of all target sentences; 3) A

random multiple of 100 ms (0–500 ms) of silence was added at the beginning of each concatenated

sentences to stagger the talkers once they were mixed together; 4) All eight talkers were mixed,

by randomly choosing one concatenated sentence by talker, and the initial 500 ms of the

concatenated sentences was removed to eliminate noise that did not contain all eight talkers; 5)

The first 100 ms of the complete noise tracks was faded in. In total, we produced 120 multi-talker

noise stimuli. In a final step, we mixed the fifth target sentences of each of the previously generated

conversations or each of the one-sentence stimuli with a randomly chosen noise stimulus for the

entire duration of the target sentences with the addition of 100ms before and after the sentences

during which there was only noise. Here, the level of the multi-talker masking noise was held

constant, while the amplitude of the target stimuli was decreased by Signal-to-Noise Ratios (SNRs)

of -1, -4, and −6 dB, where -4 and -6 dB are known to produce a speech reception threshold (see

Plomp & Mimpen, 1979) that is in the range of 40 % to 60 % depending on the studies and methods

(Brungart et al., 2001; Dingemanse & Goedegebure, 2020; Festen & Plomp, 1990; Hagerman,

1984; McArdle et al., 2005; Miller et al., 1951). These values were also tested in prior in-the-lab

pilot testing (unpublished data) to estimate a range of SNRs that would adequately capture the skill

level of young healthy participants, while limiting floor or ceiling effects as well as subject

frustration (Coffey et al., 2019).

D. Procedure.

1. Overview. We used a speech-in-noise paradigm to study how semantic and social contexts

interact with phonetic encoding of a sentence. Importantly, we used a task that required the listener

to identify if a word had been changed, but that word was not itself relevant to the content of the

dialogue (e.g., see figure 1, in which the changed word was "true" vs "pure", both of which fit the

meaning of the sentence, and neither of which is related to the dialogue's content). This

manipulation allowed us to focus on the phonetic encoding of a word rather than its underlying

meaning, moving beyond traditional measures of intelligibility by focusing on the deeper cognitive

processes that enable robust speech perception. Here, we note that we didn't explicitly ask the

participants to perform the task on a specific word change, but rather to identify a change between

the original sentence and the repeated one. The exact instruction given to the participant was *"Your*

task is to determine, as quickly as possible, whether the repeated sentence is exactly the same or different than the one presented in noise. It's crucial to note that even subtle changes between the repeated sentences should be reported as different. Only when two sentences are precisely identical should you consider them the same".

2. Experiments rationales. We conducted two main experiments (see table I for a summary of the experiments and their specificity). Experiment 1 was a preliminary study designed to select a correct SNR (-4 dB or -6 dB) to be used in the subsequent experiments and was composed of two participant groups: one with dialogues only (Exp. 1a) and one with monologues only (Exp. 1b). Experiment 2 addressed the effects of semantic and social contexts while controlling for effects of different experimental conditions/orders (Carvalho & Goldstone, 2014a, 2014b; Francis & Ciocca, 2003), and was composed of 3 participant groups: Experiment 2a was composed of separate blocks of dialogues-only trials and blocks of monologues-only trials, each featuring both intact and sentence-scrambled conversations within each block; Experiment 2b was composed of separate blocks of intact conversations only and blocks of sentence-scrambled conversations only, each featuring both dialogues and monologues within each block; and Experiment 2c was composed of blocks featuring all four conditions within each block. All experiments (for which details are given below) were developed using PsychoPy (Peirce et al., 2019), then transformed into JavaScript using the PsychoJS library as implemented in PsychoPy and hosted on the Pavlovia platform (*www.pavlovia.org*) for online running of the experiments.

Experiment	Conditions	SNR	Block 1	Block 2	Block 3	Participants (included)
1a	Dialogues	-4 dB -6 dB	**Baseline** (x2) (one sentence)	**Dialogues** Intact / Scrambled	**Dialogues** Intact / Scrambled	39
1b	Monologues	-4 dB -6 dB	**Baseline** (x2) (one sentence)	**Monologues** Intact / Scrambled	**Monologues** Intact / Scrambled	39
2a	Dialogues Monologues	-4 dB	**Baseline** (one sentence)	**Dialogues** Intact / Scrambled	**Monologues** Intact / Scrambled	72
2b	Dialogues Monologues	-4 dB	**Baseline** (one sentence)	**Intact** Dialogues / Monologues	**Scrambled** Dialogues / Monologues	65
2c	Dialogues Monologues	-4 dB	**Baseline** (one sentence)	**Dialogues / Monologues** Intact / Scrambled	**Dialogues / Monologues** Intact / Scrambled	74

Table I. Summary of specificities of designs, conditions and signal-to-noise ratios (SNRs) for each experiment.

3. Experimental procedure. Prior to beginning an experiment, participants went through a series of checks to ensure optimal hearing conditions while performing the tasks (Zhao et al., 2022), for which details are given in supplementary information 2. Following this, participants had to read and sign electronically the consent form, after which they were allowed to participate in the study. Each experiment (for which specific differences are given below) was preceded by a training task that was exactly the same as the testing task. For each training task, sentence-in-noise SNRs were of -1 dB for the first half of the stimuli and of -4 dB for the second half, while each training trial was followed by feedback. Each experiment consisted of two main tasks: 1) a baseline task, in which only one-sentence stimulus was presented in noise, that was used to control the level of understanding of sentences-in-noise for each participant without prior social or semantic context given, and 2) a conversational task, in which dialogues or monologues in intact or sentence-scrambled order were presented. For both tasks, immediately after hearing a sentence in noise, the participants heard it again but without noise. Half of the time, these repeated sentences were exactly the same as the one presented with noise, while the other half had a one-word difference. The task was to determine, as quickly as possible, whether the repeated sentence was exactly the same or different than the one presented in noise. A typical trial began with a waiting time of 500

ms. with a fixation cross at the center of the screen, followed by the presentation of the auditory

stimulus, then by a visual reminder of the response buttons until the participants pressed one of

the two buttons. Every 32 trials, the participants were invited to take a break. The response buttons

were counterbalanced across participants (i.e., half of the participants used the left arrow for the

'same' trials and right arrow for the 'different' trials, while the other half did the opposite). The

first voice heard was also counterbalanced across participants (i.e., half heard the female voice

first in the first presented stimuli, while the other half heard the male voice in first). For all tasks,

the order of trials was pseudo-randomized to avoid the presentation of more than 3 of the same

trial type (same/different), target voice (male/female), social factor (dialogue/monologue),

semantic factor (intact/scrambled) or SNR (-4/-6 dB for Exp. 1 only). At the end of the experiment,

participants completed the 50-item Autism-Spectrum Quotient scale (AQ; Baron-Cohen et al.,

2001), for which details and rationale are given below.

All responses (Accuracy, reaction time [RTs] and AQ questionnaire) were collected with

Pavlovia and processed with Matlab. Measure of reaction times began directly after the last

sentence was heard until the participant pressed one of the two response buttons.

4. Experimental designs.

Experiment 1. Experiment 1 was conducted to choose a correct SNR for measuring our effects of

interest in the subsequent experiments and included two groups, with one group presented with

dialogues only (Exp. 1a; 40 participants) and one group presented with monologues only (Exp. 1b;

40 participants). Here, we expected a correct SNR to not produce ceiling of floor effects with

accuracy scores and to produce our effect of interest (i.e. better performance for intact over

sentence-scrambled conversations using *d'* scores and/or RTs). For each group, half of the unique

stimuli were presented with an SNR of -6dB, while the other half was presented with an SNR of -

4dB, and stimuli were randomly assigned in one or the other half for each participant. The

alternation of -4dB and -6dB stimuli was randomized. For the two groups, the experiment began

with two training tasks: one with 8 baseline trials and the other with 4 conversation trials. The

order of the training tasks was counterbalanced over participants. Following the training,

participants underwent the experiment that consisted of two baseline blocks (32 trials each) and

two conversation blocks (32 trials each) interleaved, for which the order was counterbalanced

across participants.

Experiment 2a. Experiment 2a included 74 participants and was composed of blocks of dialogues

only or monologues only, while a same block featured both intact and scrambled conversations.

For each participant, half of the unique stimuli was presented in the dialogue condition and

repeated across the intact and scrambled conditions while the other half was presented in the

monologue condition and repeated across the intact and scrambled conditions, and stimuli were

randomly assigned in one or the other half for each participant using 6 predefined lists. Experiment

2a used an SNR of -4 dB and was conducted as follows. At first a training task featured 6 baseline

trials, followed by a testing task of 44 baseline trials. Afterwards, participants were presented with

one block of dialogues only and one block of monologues only (32 trials each, with half intact and

half sentence-scrambled conversations, presented in random order). The order of blocks was

counterbalanced across participants. Each block was preceded by a training task of 4 trials of the

same condition.

Experiment 2b. Experiment 2b included 66 participants and was composed of blocks of intact

conversations only or sentence-scrambled conversations only, while a same block featured both

dialogues and monologues. For each participant, half of the unique stimuli was presented in the

intact condition and repeated across dialogues and monologues while the other half was presented

in the scrambled condition and repeated across dialogues and monologues, and stimuli were

randomly assigned in one or the other half for each participant using 6 predefined lists. Experiment

2b used an SNR of -4 dB and was conducted as follows. At first a training task featured 6 baseline

trials, followed by a testing task of 44 baseline trials. Afterwards, participants were presented with

one block of intact conversations only and one block of sentence-scrambled conversation only (32

trials each, with half dialogues and half monologues presented in random order). The order of

blocks was counterbalanced across participants. Each block was preceded by a training task of 4

trials of the same condition.

Experiment 2c. Experiment 2c included 75 participants and was composed of blocks featuring all

conditions randomly intermixed (i.e., both dialogues and monologues in both intact and sentence-

scrambled orders, not blocked into conditions). For each participant, half of the unique stimuli

were presented in the dialogue condition and repeated across the intact and scrambled conditions

while the other half were presented in the monologue condition and repeated across the intact and

scrambled conditions, and stimuli were randomly assigned in one or the other half for each

participant using 6 predefined lists. Experiment 2c used an SNR of -4 dB and was conducted as

follows. At first a training task featured 6 baseline trials, followed by a testing task of 44 baseline

trials. Afterwards, participants were presented with two blocks (32 trials each) featuring all

conditions.

5. Autism Quotient (AQ) task. For experiment 2, at the end of each acquisition participants

completed the 50-item Autism-Spectrum Quotient scale (AQ; Baron-Cohen et al., 2001) which

measures the degree to which an adult with normal intelligence shows traits associated with the

ASD (Autistic Spectrum Disorders), in the domain of social skills, attention-switching, attention

to details, communication, and imagination. Subjects responded to each item using a 4-point rating

scale, ranging from "definitely agree" to "definitely disagree". Calculation of the AQ quotient was

performed following the instructions provided by Baron-Cohen et al. (2001). Higher scores

indicate greater ASD traits while lower scores indicate fewer ASD traits.

E. Data preprocessing. For all experiments, the following data preprocessing steps were applied:

1) For each participant, trials for which RTs were >3 SD above the participant mean were discarded

from further analyses; 2) For each participant, trials in which the response was inaccurate were

discarded for RTs only; 3) Participants were excluded from the study if their mean RTs averaged

across all conversation conditions was >3 SD above the subgroup mean (Participants exclusions

per experiment: *Exp. 1a:* 1/40; *Exp. 1b:* 1/40; *Exp. 2a:* 2/74; *Exp. 2b:* 1/66; *Exp. 2c:* 1/75; *Total of*

participants exclusions: 6/295; ~2.03 %). After exclusions, statistical analyses for all conditions

within an experiment included 39 participants for experiment 1a, 39 participants for experiment

1b and 211 participants for experiment 2.

F. Analyses.

1. Main analyses. For all experiments, d-prime scores (*d'*) and mean RTs were used to compare

the effect of intact vs. scrambled conversation across dialogues and monologues. Here, we

computed *d'* scores for each participant as this measure, derived from signal detection theory,

captures perceptual sensitivity while controlling for response bias by incorporating both hit and

false alarm rates (Green et al., 1966; Hautus et al., 2021; Stanislaw & Todorov, 1999). Thus, we

chose *d'* scores over raw accuracy because it provides a more robust and unbiased estimate of

participants' ability to detect subtle phonetic changes, making it particularly well-suited for the

two-alternative forced choice paradigm used in our study. *d'* scores were computed with the *psyphy*

package (Knoblauch, 2023) run through R studio (R Core Team, 2023), using a differencing

approach (Hautus et al., 2021). For Experiment 1, we additionally computed accuracy to compare

potential ceiling or floor effects as a function of the SNR. We then used Jamovi (Doğan Şahin &

Can Aybek, 2020) to ran linear mixed effect models (LMMs) as follow. For experiment 1,

separately for *d'* and RTs we ran two LMMs (one for Exp. 1a with dialogues only and one for Exp.

1b with monologues only) with 2 factors [Semantic context (Intact / Scrambled) x SNR (-4 dB / -

6 dB)], baseline as covariate and subjects as random factor. For experiment 2, separately for *d'*

and RTs we ran one LMM with 3 factors [Experimental design (a / b / c) x Semantic context (Intact

/ Scrambled) x Social context (Dialogue / Monologue)], baseline as covariate, and subjects as

random factors. Because d′ scores and RTs were calculated per condition for each participant, the

analysis was conducted on aggregated data at the subject level and item-level variability was not

modeled. For each of these models, baseline performance was included as a covariate to take into

account individual variability in performing the speech-in-noise task prior to manipulating the

context. To evaluate the effects of the experimental factors, we extracted the estimated marginal

means from these models and submitted them to fixed-effects omnibus tests in Jamovi. This

approach allowed us to evaluate overall factor-level effects rather than contrasts against a specific

reference level. In addition, we also ran the same LMM analysis for experiment 2 without

including the baseline as a covariate, and we found that the model fit was better with the baseline

than without the baseline (supplementary table I), although with very similar results

(supplementary table II).

2. AQ analysis. In addition, we examined whether individual differences in processing

conversations were related to autistic traits, as measured by the AQ. Specifically, we conducted

one-tailed partial Spearman correlations, separately for dialogues and monologues, between

individual AQ scores and the difference in performance between intact and scrambled

conversations, while controlling for baseline performance as a potential confound. Here, we used

a one-tail test because we had a clear hypothesis regarding the direction of our expected effect, a

negative correlation, that would show that the lower the AQ score, the higher the difference of

performance between intact and scrambled conversations. This hypothesis was directly driven

from the results of an analogous study in the visual modality (Abassi & Papeo, 2022), that showed

a negative correlation between individual AQ score and a measure of behavioral performances in

visual processing of facing body dyads (as if interacting) as compared to non-facing body dyads,

as well as other studies that showed similar relationship between AQ and visual sensitivity to other

type of social stimuli (van Boxtel et al., 2017; Wyer et al., 2012; Yang et al., 2024). We then

compared the difference of magnitudes of the Spearman *rhos* (Lenhard & Lenhard, 2014) between

dialogues and monologues.

III. RESULTS

A. Experiment 1. Experiment 1 was conducted to choose a correct SNR for measuring our effects

of interest in the subsequent experiments. To do so, based on prior in-the-lab pilots (unpublished

data) we selected two SNRs of -6 and -4 dB. For the SNR of -6 dB we found a mean baseline

accuracy of 61.9 % (+/- 1.9 Standard Error of the Mean [SEM]) for Exp. 1a and 64.5 % (+/- 1.8

SEM) for Exp. 1b, while for the SNR of -4 dB, we found a mean baseline accuracy of 73.2 % (+/-

1.8 SEM) for Exp. 1a and 72.3 % (+/- 1.8 SEM) for Exp. 1b. For the main task, for the SNR of -6

dB we found a mean average accuracy of 61.7 % (+/- 1.8 SEM) for Exp. 1a and 60.2 % (+/- 1.9

SEM) for Exp. 1b, while for the SNR of -4 dB we found a mean average accuracy of 78.1 % (+/-

1.8 SEM) for Exp. 1a and 77.1 % (+/- 1.5 SEM) for Exp. 1b.

Using *d'* scores, for Exp. 1a (dialogues only), the 2 SNR x 2 Semantic context LMM (fig.

2a) showed a main effect of SNR and no main effect of semantic context. Critically, it did show a

significant interaction between SNR and Semantic context (table IIa). This interaction arises from

a larger difference for intact vs. scrambled conversations for a SNR of -4 dB as compared to a

SNR of -6 dB. Post-hoc *t*-tests showed that this difference was significantly higher for intact than

scrambled conversations for a SNR of -4 dB ($t(38) = 2.49, p = 0.017$), while there was no difference

for a SNR of -6 dB ($t(38) = 0.35, p > 0.250$). Using RTs (fig. 2b), we didn't find any significant

effects (table IIb). For Exp. 1b (monologues), we didn't find any effects using *d'* (table IIc; fig. 2c)

or RTs (table IId; fig. 2d).

To summarize, we first found that an SNR of -6 dB was producing accuracies in the range

of 60-65 %, while an SNR of -4 dB was producing accuracies in the range of 72-78 %, that was a

first indication that an SNR of -6 dB might be too close to chance level as compared to -4 dB. In

addition, only with a SNR of -4 dB we found our effect of interest using *d'* (i.e., a significantly

better performance for intact vs. scrambled dialogues in Exp. 1a). For this reason, we used an SNR

of -4 dB for all subsequent experiments.

Figure 2. Behavioral data for experiment 1. Performances for intact and sentence-scrambled conversations using

d-primes *(d')* and response times (RTs) with SNRs of -4 dB and -6 dB for Exp. 1a (Dialogues only: **a.; b.**) and Exp.

1b (Monologues only: **c.; d.**). Error bars represent standard errors of the mean. *p ≤ 0.05.

a. Dialogues - *d'* scores

	F	**df**	**df (res)**	**p**
SNR	37.94	1	44.7	**<.001**
Semantic	1.53	1	38	0.223
Baseline	17.07	1	67.3	**<.001**
SNR x Semantic	4.18	1	38	**0.048**

c. Monologues - *d'* scores

	F	**df**	**df (res)**	**p**
SNR	58.76	1	36.7	**<.001**
Semantic	0.06	1	73	0.802
Baseline	5.83	1	73.9	**0.018**
SNR x Semantic	0.72	1	76	0.398

b. Dialogues - RTs

	F	**df**	**df (res)**	**p**
SNR	1.40	1	38.9	0.243
Semantic	1.62	1	75.6	0.207
Baseline	41.82	1	46.5	**<.001**
SNR x Semantic	0.23	1	76	0.635

d. Monologues - RTs

	F	**df**	**df (res)**	**p**
SNR	2.31	1	39.5	0.137
Semantic	2.68	1	38	0.110
Baseline	189.33	1	48.2	**<.001**
SNR x Semantic	0.34	1	38	0.564

Table II. Results of the Linear Mixed Effect models with *d'* scores and RTs for dialogues (Exp. 1a: a.; b.) and

monologues (Exp. 1b: c.; d.).

B. Experiment 2. Raw accuracy scores for each condition were as follows: Intact Dialogues: 75.6

% (SD: 14.5); Scrambled Dialogues: 74.0 % (SD: 14.4); Intact Monologues: 75.2 % (SD: 14.2);

Scrambled Monologues: 72.4 % (SD: 15.7); Baseline: 69.3 % (SD: 10.5). These values are

reported for descriptive purposes only, all inferential statistics for performance were conducted on

d' scores, which better reflect perceptual sensitivity in this task. Using *d'* scores (fig. 3a; Table

IIIa), the 3 Design x 2 Semantic context x 2 Social context LMM showed only a significant main

effect of semantic context, characterized by higher d-primes for intact than sentence scrambled

conversations, and no interactions. Using RTs (fig. 3b; Table IIIb) the same analysis showed a

significant effect of social context, characterized by lower RTs for dialogues than monologues, as

well as a significant effect of semantic context, characterized by lower RTs for intact than

sentence-scrambled conversations. It also showed a marginal trend for an interaction between

experimental design and social factor, and no other effects or interactions.

Figure 3. Behavioral data for experiment 2. Performances for intact and sentence-scrambled dialogues and

monologues using d-primes (**a.**) and response times (**b.**). Error bars represent standard errors of the mean. Asterisks

(*) represent main effects of the Omnibus test derived from our linear mixed models.

a. *d'* scores

	F	df	df (res)	p
Design	0.42	2	207	0.655
Social	1.60	1	384	0.207
Semantic	7.35	1	210	**0.007**
Baseline	75.54	1	207	**<.001**
Design x Social	0.04	2	384	0.956
Design x Semantic	0.40	2	210	0.670
Social x Semantic	1.75	1	416	0.186
Design x Social x Semantic	0.39	2	416	0.679

b. RTs

	F	df	df (res)	p
Design	1.33	2	207	0.266
Social	4.40	1	208	**0.037**
Semantic	9.55	1	208	**0.002**
Baseline	154.55	1	207	**<.001**
Design x Social	2.84	2	208	*0.061*
Design x Semantic	1.59	2	208	0.206
Social x Semantic	0.02	1	208	0.889
Design x Social x Semantic	0.75	2	208	0.472

Table III. Results of the Linear Mixed Effect models with *d'* scores (a.) and RTs (b.) for Experiment 2.

C. Relationship between individual AQ scores and phonetic encoding. Using the data of experiment 2, we next examined whether individual differences in autistic traits (measured via AQ scores) were associated with sensitivity to semantic context, and whether this relationship varied depending on the social context of the conversation. To do so, we computed a difference score (Intact – Scrambled) reflecting the perceptual benefit of semantic coherence for each participant, separately for dialogues and monologues. These scores isolate the effect of semantic context within each social setting, allowing us to assess whether AQ modulates this effect differently depending on whether speech occurs in a socially interactive (dialogue) or non-interactive (monologue) context. Here, we didn't find significant partial Spearman correlations using the *d'* score (Dialogues; $rho(211) = -0.04$; $p > 0.250$; Monologues; $rho(211) = 0.07$; $p = 0.161$) with no differences between dialogues and monologues ($z = -1.1$ $p = 0.136$). However, using RTs, only for dialogues and not for monologues we found that there was a trend for a negative correlation between AQ and processing of intact vs. scrambled conversations (Dialogues: $rho(211) = -0.10$, p

= 0.067; Monologues: rho(211) = 0.02, p > 0.250). Furthermore, we also found a trend for a lower

correlation for dialogues as compared to monologues ($z = -1.38$ $p = 0.085$).

IV. DISCUSSION

We investigated how semantic and social contexts modulate phonetic encoding during

processing of naturalistic conversations using a novel speech-in-noise task. First, we found that

semantic context significantly enhanced phonetic encoding. Specifically, participants performed

better (lower response time and better performance) when processing semantically coherent

conversations compared to sentence scrambled ones. Second, social context also had a significant

effect, with dialogues providing greater benefits (lower response time, but no effect on

performance) to phonetic encoding than monologues. Finally, we found a trend for a negative

correlation between individual differences in AQ traits and performances in processing intact vs.

scrambled conversations for dialogues only.

Our finding that semantic coherence within a full conversation enhances phonetic encoding

aligns well with existing research on predictive coding theories of auditory perception. Predictive

coding posits that the brain generates top-down expectations based on semantic context to

minimize mismatches between sensory input and prior knowledge (Clark, 2013; Friston, 2005). In

our study, participants performed better when processing semantically coherent conversations,

demonstrating the benefits of predictive mechanisms in noisy environments where bottom-up

auditory signals are degraded. These results are consistent with previous work showing that

semantic congruence facilitates words and phonemes identification while reducing cognitive load

(Golestani et al., 2009, 2013; Sohoglu et al., 2012; Zekveld et al., 2011, 2012, 2013). However,

our study extends these findings into a new domain by showing effects of semantic context at the

larger scale of naturalistic, multi-sentence conversations. Here, while prior research has

established the role of semantic context within short linguistic units (Broderick et al., 2019; Roland

et al., 2012), our results suggest that predictive mechanisms also operate over longer timescales,

integrating information across whole conversations. Indeed, in our paradigm, unlike most prior

studies, the target sentence embedded in noise was not itself semantically anomalous; it was only

anomalous or not with respect to the preceding conversational context.

While much of the prior research has framed these effects within the predictive coding

framework, other complementary mechanisms may also explain the influence of semantic context

on speech processing. First, semantic priming effects, whereby exposure to semantically related

words activates shared neural networks, may also facilitate phonetic encoding by reinforcing

linguistic expectations (Daltrozzo et al., 2011; Foss, 1982; Kutas & Federmeier, 2011). This

process likely operates at multiple levels of representation, from lexical access to sentence-level

coherence, allowing listeners to extract meaning even when speech is partially masked by noise.

Secondly, semantic context may also interact with attentional mechanisms, prioritizing coherent

information over incongruent or irrelevant input. Research on the cocktail party effect has shown

that semantic predictability can help listeners segregate target speech from competing noise, even

in multi-talker environments (Bronkhorst, 2015; Tóth et al., 2020). These findings suggest that

semantic coherence not only aids phonetic encoding but also enhances the perceptual organization

of auditory scenes, contributing to the broader goal of communication in complex environments.

Interestingly, our study highlights the robustness of semantic effects across whole conversations,

suggesting that listeners dynamically integrate information over longer timescales. This temporal

dimension aligns well with research showing that discourse-level processing involves distinct

neural mechanisms, including prefrontal and temporo-parietal networks, that support integration

of meaning across sentences (Kutas & Federmeier, 2011; Menenti et al., 2012). Future research

should explore how these long-range mechanisms interact with immediate predictive processes to

shape phonetic encoding.

Our second and more novel findings pertain to social context effects, that showed better

performances for dialogues over monologues. This result extends prior research emphasizing the

role of interactional dynamics in speech processing. While the benefits of turn-taking and temporal

predictability in dialogues are well-documented (Branigan et al., 2011; Fox Tree, 1999; Menenti

et al., 2012; Pickering & Garrod, 2021; Tolins et al., 2018), this effect has been usually linked to

the internal content of a dialogue as compared to a monologue, rather than to its intrinsic social

value as an interaction. Indeed, dialogues usually contain information that monologues lack, such

as discourses markers and/or different perspectives from multiple interlocutors, that may help in

the understanding of the information that is shared (Pickering & Garrod, 2021). While this

hypothesis can provide a partial explanation for this advantage in certain situations, it cannot apply

to our study. Here, we used identical contents for both dialogues and monologues, with the only

change being the vocal timbre of the speakers and their alternation or not. Furthermore, our task

required the listener to identify if a word had been changed, but that word was not itself relevant

to the content of the dialogue (e.g., see figure 1, in which the changed word was "true" vs "pure":

both of which fit the meaning of the sentence, and neither of which is related to the dialogue's

content). Thus, instead of emphasizing the content of the dialogue, we rather hypothesize that the

presence of social cues, such as two speakers interacting with each other, triggers a sharpening of

the acoustics of the sentences by the perceptual system, that is emphasizing some features of the

auditory signal to facilitate comprehension, that would be higher for dialogues over monologues.

This account suggests in turn that dialogues would provide additional cognitive engagement

through social cues such as turn-taking and speaker interaction, which are absent in monologues.

Hence, dialogues, due to their interactive nature, would create a richer social context that may

engage listeners more deeply by eliciting greater social attention and enhancing speech processing.

This process could be mediated by neural systems specialized for processing socially relevant

stimuli, such as the superior temporal sulcus (STS) and medial prefrontal cortex (Schilbach et al.,

2006, 2008). This hypothesis is in line with recent findings in the domain of visual perception

showing that a human body is better perceived when facing another body (i.e., mimicking a social

interaction), as compared to facing in an opposite direction (Abassi et al., 2020; Papeo et al., 2017;

Papeo & Abassi, 2019; Vestner et al., 2019, 2021), suggesting a domain-general effect that would

enhance perceptual encoding in the presence of socially relevant settings, regardless of sensory

modality.

Another unexplored factor is the role of joint attention in dialogues, where listeners

anticipate and align with the speaker's focus of attention. Studies in developmental psychology

have shown that joint attention is critical for language acquisition and auditory processing (Mundy,

2018; Tomasello, 2005), suggesting that similar mechanisms may also operate in adult

conversations to enhance comprehension. Additionally, the contingency of dialogue responses,

where listeners predict speaker turns based on context, may activate reward systems (McNaughton

et al., 2023; Stivers et al., 2009), further enhancing attention and processing efficiency.

Interestingly, the absence of familiar speakers in our study highlights that interactional dynamics

alone, independent of familiarity (Domingo et al., 2020; Johnsrude et al., 2013), can drive social

context effects. Here, research on speaker familiarity would suggest that combining familiarity

with dialogue-based cues could even amplify these benefits (Fleming et al., 2014; Yu et al., 2023).

Future studies could investigate how these factors interact to optimize phonetic encoding in real-

world scenarios.

An additional consideration is how our task relates to the broader concepts of intelligibility

or phonetic encoding. While intelligibility is commonly defined as the successful recognition of

spoken words under varying conditions (Mattys et al., 2012), phonetic encoding refers to the

fidelity with which acoustic-phonetic information is mapped onto linguistic representations (Yi et

al., 2019). These processes are closely linked: phonetic encoding is a foundational step that

supports intelligibility. However, our task was designed to emphasize the former by focusing on

subtle phonetic contrasts (e.g., "true" vs. "pure", or "time" vs. "year") where the alternative words

were both grammatically plausible and semantically neutral with respect to the broader

conversational context. In this way, listeners could not rely on sentence meaning to detect changes

but instead had to encode and retain fine-grained phonetic detail. Thus, although our measure

involves elements of intelligibility, particularly in noise, it targets how well listeners encode and

retrieve phonetic forms under varying contextual conditions. By framing our results in terms of

phonetic encoding, we highlight the influence of high-level semantic and social cues on early

perceptual stages of speech processing.

One more point to highlight is that effects of social context were found only with response

time, while effects of semantic context were found with both response time and accuracy. A first

reason for this difference across tasks may be that our social condition task could be more fine-

tuned (e.g., by using an adaptive SNR; see Soleymani et al., 2019) to better take into account

individual variabilities that would be reflected in performance on the task and especially measures

of accuracy (such as d' scores), that are more sensitive to floor or ceiling effects than RTs (Magnus

et al., 2017; Willoughby et al., 2023). Another reason for the discrepancy could be due to the nature

of the measured effects themselves. Indeed, it has been proposed that RTs and measures of

accuracy may be affected by different attentional cues via distinct cognitive and/or neural

mechanisms (Prinzmetal et al., 2005; van Ede et al., 2012 but see Mulder & Van Maanen, 2013).

Thus, effects of social and semantic contexts may rely on different attentional cues, that may be

reflected in measuring RTs and d-primes, while the exact nature of these different cues, if they

exist, would need a more thorough exploration. On a last point, we note that we found only a

marginal trend for an interaction of our conditions with the experimental design, showing that

there is only a minimal effect of presentation order in our experiment.

We also note the lack of interaction between semantic and social contexts. Indeed, while

both factors independently enhanced phonetic encoding, their effects appeared to operate

additively rather than synergistically. This absence of interaction challenges theoretical

frameworks suggesting that social and semantic cues are integrated to optimize speech processing

(Menenti et al., 2012; Pickering & Garrod, 2021). One potential explanation lies in the modularity

of processing streams for semantic and social information. Neural evidence suggests that semantic

processing primarily engages regions such as the angular gyrus and inferior frontal gyrus

(Humphries et al., 2007), while social interaction cues involve the STS and medial prefrontal

cortex (Hasson et al., 2012; Schilbach et al., 2008). Although these networks are interconnected,

their relative independence may explain why semantic and social effects did not interact in our

study. It is possible that these processing streams converge at later stages, such as during

integration of discourse-level meaning or higher-order inference-making, which were not directly

tested in our task. Another possibility is that our task design, which isolated semantic and social

factors, may have limited opportunities for these effects to interact. For example, the lack of

speaker familiarity or shared conversational goals in our stimuli may have reduced the potential

for synergistic effects. Indeed, research on common ground, the shared knowledge between

conversational partners, has shown that mutual understanding enhances speech comprehension

(Holler & Stevens, 2007; Horton & Keysar, 1996; Keysar et al., 2000). Future studies could test

whether incorporating shared goals or familiar speakers facilitates interaction between semantic

and social contexts. Finally, the additive effects observed in our study may reflect the distinct

timescales at which semantic and social factors operate. Semantic coherence influences phonetic

encoding already at the level of immediate word or sentence processing, while social context

effects unfold over longer conversational exchanges. Understanding how these factors converge

may require further investigation, particularly using experimental designs that manipulate both

immediate and extended contextual cues, or other experimental methods such as neuroimaging.

An additional contribution of this study is the exploratory analysis of individual differences

in social traits, measured by the AQ. While the negative correlation between AQ scores and the

benefit of semantic coherence in dialogues over monologues was only a trend, and of low

magnitude, it is consistent with previous findings suggesting that individuals with higher AQ

scores may be less sensitive to social interaction cues (Bayliss et al., 2005). Similar negative

associations between AQ and sensitivity to social stimuli have been reported in the visual modality

(Abassi & Papeo, 2022; van Boxtel et al., 2017; Wyer et al., 2012; Yang et al., 2024), raising the

possibility of a domain-general mechanism affecting how social cues are integrated across sensory

systems. These observations do not contradict prior work showing enhanced attention to fine

phonetic detail in individuals with higher AQ (Ota et al., 2015; Stewart & Ota, 2008; Yu, 2010),

but may reflect a trade-off between local auditory precision and reduced sensitivity to social

dynamics. While the present results provide only tentative support for this idea, they underscore

the relevance of individual variability in social traits when investigating the interplay between

social and semantic context in speech perception.

In sum, our findings contribute to several theoretical frameworks in auditory cognition and

social perception. First, our results support predictive coding theories, demonstrating that both

semantic and social contexts facilitate phonetic encoding, likely through top-down mechanisms.

The robustness of these effects across large-scale conversations suggests that predictive

mechanisms operate hierarchically, integrating information at multiple levels of linguistic and

social processing. Second, our findings highlight the role of social interactional dynamics in

engaging cognitive systems specialized for processing socially relevant stimuli, consistent with

theories of dialogue-based processing and to neurocognitive models emphasizing the role of

specialized neural circuits to social cognition (Pitcher & Ungerleider, 2021). Finally, the trend-

level relationship between AQ and sensitivity to social context suggests a balance between

enhanced detail-focused processing and reduced integration of social information, consistent with

the weak central coherence hypothesis of autism, which proposes a cognitive style favoring local

detail over global context (Happé & Frith, 2006; Hoy et al., 2004; Jolliffe & Baron-Cohen, 1999).

However, the variability observed within AQ-related effects here should be understood in the

context of a neurotypical population, since we drew our sample from a general population, and

none of our participants had a known diagnosis of autism.

These findings also have practical implications for designing interventions and assistive

technologies for individuals with hearing losses. For example, auditory training programs could

incorporate semantically coherent narratives and simulate conversational dynamics to enhance

speech processing in noisy environments. Similarly, hearing aids and other assistive devices could

incorporate algorithms that prioritize interactional dynamics, such as turn-taking, to improve real-

world communication outcomes. In a future research, we will extend the examination of the neural

mechanisms underlying these effects using neuroimaging techniques to explore how different

contexts modulate brain activity (see Landsiedel & Koldewyn, 2023; Olson et al., 2023). Here we

predict that, using fMRI, we may find modulation and sharpening of brain activity in voice-

selective regions of the auditory cortex, such as the STS, as a function of the semantic and/or social

context. On another aspect, expanding the scope of this research to include older adults, individuals

with hearing impairments, or non-native speakers could provide a broader understanding of how

contextual factors impact diverse populations. Further explorations could also replicate our current

findings using real human voices from naturalistic conversations, that might carry additional

features of canonical social interactions. Finally, integrating cross-modal research on auditory and

visual sensitivity for social interactions (see Abassi et al., 2024 for a review on social vision; see

also Abassi & Papeo, 2024 for cross category research) could offer a more comprehensive

perspective on disentangling the domain-general and domain-specific mechanisms underlying

social cognition.

V. SUPPLEMENTARY MATERIAL. See supplementary material at [URL will be inserted by

AIP] for the stimuli set, additional figure and tables.

VI. ACKNOWLEDGMENTS. This research was supported by the Fondation Pour l'Audition

through a postdoctoral fellowship to EA (FPA RD-2022-1) and by the Grand Prix Scientifique

from the Fondation Pour l'Audition to RJZ (2021). RJZ holds a Canada Research Chair and is

funded by the Canadian Institutes of Health Research..

VII. AUTHOR DECLARATIONS. All authors declare that they have no financial or non-

financial conflict of interests to disclose. They also declare that all procedures used in the current

study were performed in compliance with the code of ethics of the World Medical Association's

Declaration of Helsinki and have been approved by the Faculty of Medicine Institutional Review

Board of McGill University on the 3rd of October 2022 (reference number: A08-B75-22B / 22-07-

116).

VIII. DATA AVAILIBILITY. The entire set of stimuli and materials for generation can be found

online at *www.zlab.mcgill.ca/downloads/Stimuli_from_Abassi_2025*. A sample is also provided as

supplementary files (*SuppPub2.zip*) and can be used under the term of a CC-BY-NC-SA 4.0

license. The collected online data are freely available upon email request to E.A.

IX. REFERENCES

Abassi, E., Papeo, L. (2020). The representation of two-body shapes in the human visual cortex. *Journal*
of Neuroscience, *40*(4), 852–863. https://doi.org/10.1523/JNEUROSCI.1378-19.2019

Abassi, E., & Papeo, L. (2022). Behavioral and neural markers of visual configural processing in social
scene perception. *NeuroImage*, 119506. https://doi.org/10.1016/j.neuroimage.2022.119506

Abassi, E., & Papeo, L. (2024). Category-selective representation of relationships in visual cortex.
Journal of Neuroscience, *44*(5). https://doi.org/10.1523/JNEUROSCI.0250-23.2023

Abassi, E., Bognár, A., de Gelder, B., Giese, M., Isik, L., Lappe, A., Mukovskiy, A., Solanas, M. P.,
Taubert, J., & Vogels, R. (2024). Neural Encoding of Bodies for Primate Social Perception. *Journal*
of Neuroscience, *44*(40), 1221242024. https://doi.org/10.1523/JNEUROSCI.1221-24.2024

Adank, P., Evans, B. G., Stuart-Smith, J., & Scott, S. K. (2009). Comprehension of Familiar and
Unfamiliar Native Accents Under Adverse Listening Conditions. *Journal of Experimental*
Psychology: Human Perception and Performance, *35*(2), 520–529.
https://doi.org/10.1037/A0013552

Adolphs, R. (2001). *The neurobiology of social cognition*. 231–239.

Adolphs, R. (2009). The social brain: Neural basis of social knowledge. *Annual Review of Psychology*,
60, 693–716. https://doi.org/10.1146/annurev.psych.60.110707.163514

Assmann, P., & Summerfield, Q. (2004). The Perception of Speech Under Adverse Conditions. *Speech*
Processing in the Auditory System, 231–308. https://doi.org/10.1007/0-387-21575-1_5

Babel, M., & Russell, J. (2015). Expectations and speech intelligibility. *The Journal of the Acoustical*
Society of America, *137*(5), 2823–2833. https://doi.org/10.1121/1.4919317

Baker, R., & Hazan, V. (2010). *LUCID: a corpus of spontaneous and read clear speech in British English*
(pp. 3–6).

Baker, R., & Hazan, V. (2011). DiapixUK: Task materials for the elicitation of multiple spontaneous
speech dialogs. *Behavior Research Methods*, *43*(3), 761–770. https://doi.org/10.3758/S13428-011-
0075-Y

Baron-Cohen, S., Wheelwright, S., Skinner, R., Martin, J., & Clubley, E. (2001). The autism-spectrum
quotient (AQ): Evidence from asperger syndrome/high-functioning autism, males and females,
scientists and mathematicians. *Journal of Autism and Developmental Disorders*, *31*(1), 5–17.
https://doi.org/10.1023/A:1005653411471

Bayliss, A. P., Pellegrino, G. Di, & Tipper, S. P. (2005). Sex differences in eye gaze and symbolic cueing
of attention. *Quarterly Journal of Experimental Psychology Section A: Human Experimental*
Psychology, *58*(4), 631–650. https://doi.org/10.1080/02724980443000124

Belin, P., Zatorre, R. J., Lafallie, P., Ahad, P., & Pike, B. (2000). Voice-selective areas in human auditory
cortex. *Nature 2000 403:6767*, *403*(6767), 309–312. https://doi.org/10.1038/35002078

Bellot, E., Abassi, E., & Papeo, L. (2021). Moving Toward versus Away from Another: How Body
Motion Direction Changes the Representation of Bodies and Actions in the Visual Cortex. *Cerebral*
Cortex, *31*(5), 2670–2685. https://doi.org/10.1093/cercor/bhaa382

Bent, T., & Bradlow, A. R. (2003). The interlanguage speech intelligibility benefit. *The Journal of the*
Acoustical Society of America, *114*(3), 1600–1610. https://doi.org/10.1121/1.1603234

Brandman, T., & Peelen, X. M. V. (2017). Interaction between Scene and Object Processing Revealed by
Human fMRI and MEG Decoding. *Journal of Neuroscience*, *37*(32), 7700–7710.
https://doi.org/10.1523/JNEUROSCI.0582-17.2017

Branigan, H. P., Catchpole, C. M., & Pickering, M. J. (2011). What makes dialogues easy to understand?
Language and Cognitive Processes, *26*(10), 1667–1686.
https://doi.org/10.1080/01690965.2010.524765

Broderick, M. P., Anderson, A. J., & Lalor, E. C. (2019). Semantic Context Enhances the Early Auditory
Encoding of Natural Speech. *Journal of Neuroscience*, *39*(38), 7564–7575.
https://doi.org/10.1523/JNEUROSCI.0584-19.2019

Bronkhorst, A. W. (2015). The cocktail-party problem revisited: early processing and selection of multi-

talker speech. *Attention, Perception, and Psychophysics*, *77*(5), 1465–1487.

https://doi.org/10.3758/S13414-015-0882-9

Brungart, D. S., Simpson, B. D., Ericson, M. A., & Scott, K. R. (2001). Informational and energetic

masking effects in the perception of multiple simultaneous talkers. *The Journal of the Acoustical*

Society of America, *110*(5), 2527–2538. https://doi.org/10.1121/1.1408946

Carvalho, P. F., & Goldstone, R. L. (2014a). Effects of Interleaved and Blocked Study on Delayed Test of

Category Learning Generalization. *Frontiers in Psychology*, *5*(AUG), 87396.

https://doi.org/10.3389/FPSYG.2014.00936

Carvalho, P. F., & Goldstone, R. L. (2014b). The benefits of interleaved and blocked study: Different

tasks benefit from different schedules of study. *Psychonomic Bulletin and Review*, *22*(1), 281–288.

https://doi.org/10.3758/S13423-014-0676-4

Ciorba, A., Bianchini, C., Pelucchi, S., & Pastore, A. (2012). The impact of hearing loss on the quality of

life of elderly adults. *Clinical Interventions in Aging*, *7*, 159–163.

https://doi.org/10.2147/CIA.S26059

Clark, A. (2013). Whatever next? Predictive brains, situated agents, and the future of cognitive science.

Behavioral and Brain Sciences, *36*(3), 181–204. https://doi.org/10.1017/S0140525X12000477

Clements, G. N. (1985). The geometry of phonological features. *Phonology*, *2*(1), 225–252.

https://doi.org/10.1017/S0952675700000440

Coffey, E. B. J., Arseneau-Bruneau, I., Zhang, X., & Zatorre, R. J. (2019). The Music-In-Noise Task

(MINT): A Tool for Dissecting Complex Auditory Perception. *Frontiers in Neuroscience*, *13*, 199.

https://doi.org/10.3389/FNINS.2019.00199

Cox, R. M., Alexander, G. C., & Gilmore, C. (1987). Development of the Connected Speech Test (CST).

Ear and Hearing, *8*(5 Suppl), 119S-126S. https://doi.org/10.1097/00003446-198710001-00010

Cristina Oliveira, R., Gama, A. C. C., & Magalhães, M. D. C. (2021). Fundamental Voice Frequency:

Acoustic, Electroglottographic, and Accelerometer Measurement in Individuals With and Without

Vocal Alteration. *Journal of Voice*, *35*(2), 174–180. https://doi.org/10.1016/J.JVOICE.2019.08.004

Daltrozzo, J., Signoret, C., Tillmann, B., & Perrin, F. (2011). Subliminal Semantic Priming in Speech.

PLOS ONE, *6*(5), e20273. https://doi.org/10.1371/JOURNAL.PONE.0020273

DeWitt, I., & Rauschecker, J. P. (2012). Phoneme and word recognition in the auditory ventral stream.

Proceedings of the National Academy of Sciences of the United States of America, *109*(8), 2709.

https://doi.org/10.1073/PNAS.1113427109

Dingemanse, G., & Goedegebure, A. (2020). Efficient Adaptive Speech Reception Threshold

Measurements Using Stochastic Approximation Algorithms. *Trends in Hearing*, *23*, 1–17.

https://doi.org/10.1177/2331216520919199

Doğan Şahin, M., & Can Aybek, E. (2020). Jamovi: An Easy to Use Statistical Software for the Social

Scientists. *International Journal of Assessment Tools in Education*, *6*(4), 670–692.

https://doi.org/10.21449/IJATE.661803

Domingo, Y., Holmes, E., & Johnsrude, I. S. (2020). The Benefit to Speech Intelligibility of Hearing a

Familiar Voice. *Journal of Experimental Psychology: Applied*, *26*(2), 236–247.

https://doi.org/10.1037/XAP0000247

Drager, K., & Kirtley, M. J. (2016). Awareness, salience, and stereotypes in exemplar-based models of

speech production and perception. *Awareness and Control in Sociolinguistic Research*, 1–24.

Festen, J. M., & Plomp, R. (1990). Effects of fluctuating noise and interfering speech on the speech-

reception threshold for impaired and normal hearing. *The Journal of the Acoustical Society of*

America, *88*(4), 1725–1736. https://doi.org/10.1121/1.400247

Fleming, D., Giordano, B. L., Caldara, R., & Belin, P. (2014). A language-familiarity effect for speaker

discrimination without comprehension. *Proceedings of the National Academy of Sciences of the*

United States of America, *111*(38), 13795–13798. https://doi.org/10.1073/PNAS.1401383111

Foss, D. J. (1982). A discourse on semantic priming. *Cognitive Psychology*, *14*(4), 590–607.

https://doi.org/10.1016/0010-0285(82)90020-2

Fox Tree, J. E. (1999). Listening in on monologues and dialogues. *Discourse Processes*, *27*(1), 35–53.

https://doi.org/10.1080/01638539909545049

Francis, A. L., & Ciocca, V. (2003). Stimulus presentation order and the perception of lexical tones in

Cantonese. *The Journal of the Acoustical Society of America*, *114*(3), 1611–1621.

https://doi.org/10.1121/1.1603231

Friston, K. (2005). A theory of cortical responses. *Philosophical Transactions of the Royal Society B:*

Biological Sciences, *360*(1456), 815–836. https://doi.org/10.1098/RSTB.2005.1622

Golestani, N., Hervais-Adelman, A., Obleser, J., & Scott, S. K. (2013). Semantic versus perceptual
interactions in neural processing of speech-in-noise. *NeuroImage*, *79*, 52–61.
https://doi.org/10.1016/J.NEUROIMAGE.2013.04.049

Golestani, N., Rosen, S., & Scott, S. K. (2009). Native-language benefit for understanding speech-in-
noise: The contribution of semantics. *Bilingualism: Language and Cognition*, *12*(3), 385–392.
https://doi.org/10.1017/S1366728909990150

Green, D. M., Swets, J. A., & others. (1966). *Signal detection theory and psychophysics* (Vol. 1). Wiley
New York.

Hagerman, B. (1984). Clinical Measurements of Speech Reception Threshold in Noise. *Scandinavian*
Audiology, *13*(1), 57–63. https://doi.org/10.3109/01050398409076258

Happé, F., & Frith, U. (2006). The weak coherence account: Detail-focused cognitive style in autism
spectrum disorders. *Journal of Autism and Developmental Disorders*, *36*(1), 5–25.
https://doi.org/10.1007/S10803-005-0039-0

Hasson, U., Ghazanfar, A. A., Galantucci, B., Garrod, S., & Keysers, C. (2012). Brain-to-brain coupling:
a mechanism for creating and sharing a social world. *Trends in Cognitive Sciences*, *16*(2), 114–121.
https://doi.org/10.1016/J.TICS.2011.12.007

Hautus, M. J., Macmillan, N. A., & Creelman, C. D. (2021). *Detection theory: A user's guide*. Routledge.

Hayes-Harb, R., Smith, B. L., Bent, T., & Bradlow, A. R. (2008). The interlanguage speech intelligibility
benefit for native speakers of Mandarin: Production and perception of English word-final voicing
contrasts. *Journal of Phonetics*, *36*(4), 664–679. https://doi.org/10.1016/J.WOCN.2008.04.002

Holler, J., & Stevens, R. (2007). The Effect of Common Ground on How Speakers Use Gesture and
Speech to Represent Size Information. *Journal of Language and Social Psychology*, *26*(1), 4–27.
https://doi.org/10.1177/0261927X06296428

Horton, W. S., & Keysar, B. (1996). When do speakers take into account common ground? *Cognition*,
59(1), 91–117. https://doi.org/10.1016/0010-0277(96)81418-1

Hoy, J. A., Hatton, C., & Hare, D. (2004). Weak Central Coherence: A Cross-Domain Phenomenon
Specific to Autism? *Autism, 8(3),* 267-281. https://doi.org/10.1177/1362361304045218

Humphries, C., Binder, J. R., Medler, D. A., & Liebenthal, E. (2007). Time course of semantic processes
during sentence comprehension: An fMRI study. *NeuroImage*, *36*(3), 924–932.
https://doi.org/10.1016/J.NEUROIMAGE.2007.03.059

Iamshchinina, P., Karapetian, A., Kaiser, D., & Cichy, R. M. (2022). Resolving the time course of visual
and auditory object categorization. *Journal of Neurophysiology, 127(6), 1622-1628.*
https://doi.org/10.1152/JN.00515.2021

Jakobson, R., Fant, C. G., & Halle, M. (1951). Preliminaries to speech analysis: The distinctive features
and their correlates. *Language, 29(4),* 472-481. https://doi.org/10.2307/409957

Johnsrude, I. S., Mackey, A., Hakyemez, H., Alexander, E., Trang, H. P., & Carlyon, R. P. (2013).
Swinging at a Cocktail Party: Voice Familiarity Aids Speech Perception in the Presence of a
Competing Voice. *Psychological Science*, *24*(10), 1995–2004.
https://doi.org/10.1177/0956797613482467

Jolliffe, T., & Baron-Cohen, S. (1999). A test of central coherence theory: linguistic processing in high-
functioning adults with autism or Asperger syndrome: is local coherence impaired? *Cognition*,
71(2), 149–185. https://doi.org/10.1016/S0010-0277(99)00022-0

Keysar, B., Barr, D. J., Balin, J. A., & Brauner, J. S. (2000). Taking Perspective in Conversation: The
Role of Mutual Knowledge in Comprehension. *Psychological Science*, *11*(1), 32–38.
https://doi.org/10.1111/1467-9280.00211

Killion, M. C., Niquette, P. A., Gudmundsen, G. I., Revit, L. J., & Banerjee, S. (2004). Development of a
quick speech-in-noise test for measuring signal-to-noise ratio loss in normal-hearing and hearing-
impaired listeners. *The Journal of the Acoustical Society of America*, *116*(4), 2395.
https://doi.org/10.1121/1.1784440

Knoblauch, K. (2023). *psyphy: Functions for Analyzing Psychophysical Data in R*. https://CRAN.R-
project.org/package=psyphy

Kuperberg, G. R., & Jaeger, T. F. (2016). What do we mean by prediction in language comprehension?
Language, Cognition and Neuroscience, *31*(1), 32–59.
https://doi.org/10.1080/23273798.2015.1102299

Kutas, M., & Federmeier, K. D. (2011). Thirty years and counting: Finding meaning in the N400
component of the event-related brain potential (ERP). *Annual Review of Psychology*, *62*(Volume 62,
2011), 621–647. https://doi.org/10.1146/ANNUREV.PSYCH.093008.131123

Lahiri, A., & Reetz, H. (2010). Distinctive features: Phonological underspecification in representation and
processing. *Journal of Phonetics*, *38*(1), 44–59. https://doi.org/10.1016/J.WOCN.2010.01.002

Landsiedel, J., & Koldewyn, K. (2023). Auditory dyadic interactions through the "eye" of the social
brain: How visual is the posterior STS interaction region? *Imaging Neuroscience*, *1*, 1–20.
https://doi.org/10.1162/imag_a_00003

Lenhard, W., & Lenhard, A. (2014). *Testing the Significance of Correlations*.
https://doi.org/10.13140/RG.2.1.2954.1367

Lerner, Y., Honey, C. J., Silbert, L. J., & Hasson, U. (2011). Topographic Mapping of a Hierarchy of
Temporal Receptive Windows Using a Narrated Story. *The Journal of Neuroscience*, *31*(8), 2906.
https://doi.org/10.1523/JNEUROSCI.3684-10.2011

Lev-Ari, S., & Keysar, B. (2010). Why don't we believe non-native speakers? The influence of accent on
credibility. *Journal of Experimental Social Psychology*, *46*(6), 1093–1096.
https://doi.org/10.1016/J.JESP.2010.05.025

Levy, D. A., Granot, R., & Bentin, S. (2003). Neural sensitivity to human voices: ERP evidence of task
and attentional influences. *Psychophysiology*, *40*(2), 291–305. https://doi.org/10.1111/1469-
8986.00031

Magnus, B. E., Willoughby, M. T., Blair, C. B., & Kuhn, L. J. (2017). Integrating Item Accuracy and
Reaction Time to Improve the Measurement of Inhibitory Control Abilities in Early Childhood.
Assessment, *26*(7), 1296-1306. https://doi.org/10.1177/1073191117740953

Major, R. C., Fitzmaurice, S. F., Bunta, F., & Balasubramanian, C. (2002). The Effects of Nonnative
Accents on Listening Comprehension: Implications for ESL Assessment. *TESOL Quarterly*, *36*(2),
173–190. https://doi.org/10.2307/3588329

Mattys, S. L., Davis, M. H., Bradlow, A. R., & Scott, S. K. (2012). Speech recognition in adverse
conditions: A review. *Language and Cognitive Processes*, *27*(7–8), 953–978.
https://doi.org/10.1080/01690965.2012.705006

McArdle, R. A., Wilson, R. H., & Burks, C. A. (2005). Speech recognition in multitalker babble using
digits, words, and sentences. *Journal of the American Academy of Audiology*, *16*(9), 726–739.
https://doi.org/10.3766/JAAA.16.9.9

McGowan, K. B. (2015). Social Expectation Improves Speech Perception in Noise. *Language and*
Speech, *58*(4), 502–521. https://doi.org/10.1177/0023830914565191

McNaughton, K. A., Kirby, L. A., Warnell, K. R., Alkire, D., Merchant, J. S., Moraczewski, D., Yarger, H. A., Thurm, A., & Redcay, E. (2023). Social-interactive reward elicits similar neural response in autism and typical development and predicts future social experiences. *Developmental Cognitive Neuroscience*, *59*, 101197. https://doi.org/10.1016/J.DCN.2023.101197

Menenti, L., Garrod, S. C., & Pickering, M. J. (2012). Toward a neural basis of interactive alignment in conversation. *Frontiers in Human Neuroscience*, *6*, 24405. https://doi.org/10.3389/FNHUM.2012.00185

Miller, G. A., Heise, G. A., & Lichten, W. (1951). The intelligibility of speech as a function of the context of the test materials. *Journal of Experimental Psychology*, *41*(5), 329–335. https://doi.org/10.1037/H0062491

Mulder, M. J., & Van Maanen, L. (2013). Are Accuracy and Reaction Time Affected via Different Processes? *PLOS ONE*, *8*(11), e80222. https://doi.org/10.1371/JOURNAL.PONE.0080222

Mundy, P. (2018). A review of joint attention and social-cognitive brain systems in typical development and autism spectrum disorder. *European Journal of Neuroscience*, *47*(6), 497–514. https://doi.org/10.1111/EJN.13720

Munro, M. J., Derwing, T. M., & Morton, S. L. (2006). The mutual intelligibility of L2 speech. *Studies in Second Language Acquisition*, *28*(1), 111–131. https://doi.org/10.1017/S0272263106060049

Niedzielski, N. (1999). The Effect of Social Information on the Perception of Sociolinguistic Variables. *Journal of language and social psychology, 18(1), 62-85.* https://doi.org/10.1177/0261927X99018001005

Nordvik, O., Laugen Heggdal, P. O., Brännström, J., Vassbotn, F., Aarstad, A. K., & Aarstad, H. J. (2018). Generic quality of life in persons with hearing loss: A systematic literature review. *BMC Ear, Nose and Throat Disorders*, *18*(1), 1–13. https://doi.org/10.1186/S12901-018-0051-6

Oliva, A., & Torralba, A. (2007). The role of context in object recognition. *Trends in Cognitive Sciences*, *11*(12), 520–527. https://doi.org/10.1016/j.tics.2007.09.009

Olson, H. A., Chen, E. M.-Y., Lydic, K. O., & Saxe, R. R. (2023). Left-Hemisphere Cortical Language Regions Respond Equally to Observed Dialogue and Monologue. *Neurobiology of Language*, *4*(4), 575–610. https://doi.org/10.1162/NOL_A_00123

O'Neill, E. R., Parke, M. N., Kreft, H. A., & Oxenham, A. J. (2021). Role of semantic context and talker

variability in speech perception of cochlear-implant users and normal-hearing listeners. *The Journal*

of the Acoustical Society of America, *149*(2), 1224–1239. https://doi.org/10.1121/10.0003532

Ota, M., Stewart, M. E., Petrou, A. M., & Dickie, C. (2015). Lexical effects on children's speech

processing: Individual differences reflected in the Autism-Spectrum Quotient (AQ). *Journal of*

Speech, Language, and Hearing Research, *58*(2), 422–433. https://doi.org/10.1044/2015_JSLHR-L-

14-0061

Papeo, L., & Abassi, E. (2019). Seeing social events: The visual specialization for dyadic human–human

interactions. *Journal of Experimental Psychology: Human Perception and Performance*, *45*(7), 877–

888. https://doi.org/10.1037/xhp0000646

Papeo, L., Stein, T., & Soto-Faraco, S. (2017). The Two-Body Inversion Effect. *Psychological Science*,

28(3), 369–379. https://doi.org/10.1177/0956797616685769

Peirce, J., Gray, J. R., Simpson, S., MacAskill, M., Höchenberger, R., Sogo, H., Kastman, E., & Lindeløv,

J. K. (2019). PsychoPy2: Experiments in behavior made easy. *Behavior Research Methods*, *51*(1),

195–203. https://doi.org/10.3758/S13428-018-01193-Y

Pickering, M. J., & Garrod, S. (2021). *Understanding Dialogue: Language Use and Social Interaction*.

https://philpapers.org/rec/PICUDL-2

Pitcher, D., & Ungerleider, L. G. (2021). Evidence for a Third Visual Pathway Specialized for Social

Perception. *Trends in Cognitive Sciences*, *25*(2), 100–110.

https://doi.org/10.1016/J.TICS.2020.11.006

Plomp, R., & Mimpen, A. M. (1979). Improving the reliability of testing the speech reception threshold

for sentences. *International Journal of Audiology*, *18*(1), 43–52.

https://doi.org/10.3109/00206097909072618

Prinzmetal, W., McCool, C., & Park, S. (2005). Attention: Reaction time and accuracy reveal different

mechanisms. *Journal of Experimental Psychology: General*, *134*(1), 73–92.

https://doi.org/10.1037/0096-3445.134.1.73

R Core Team. (2023). *R: A Language and Environment for Statistical Computing*. https://www.R-

project.org/

Rao, R. P. N., & Ballard, D. H. (1999). Predictive coding in the visual cortex: a functional interpretation

of some extra-classical receptive-field effects. *Nature Neuroscience 1999 2:1*, *2*(1), 79–87.

https://doi.org/10.1038/4580

Roland, D., Yun, H., Koenig, J. P., & Mauner, G. (2012). Semantic similarity, predictability, and models

of sentence processing. *Cognition*, *122*(3), 267–279.

https://doi.org/10.1016/J.COGNITION.2011.11.011

Rubin, D. L. (1992). Nonlanguage factors affecting undergraduates' judgments of nonnative English-

speaking teaching assistants. *Research in Higher Education*, *33*(4), 511–531.

https://doi.org/10.1007/BF00973770

Sapir, E. (1925). Sound Patterns in Language. *Language*, *1*(2), 37. https://doi.org/10.2307/409004

Schilbach, L., Eickhoff, S. B., Rotarska-Jagiela, A., Fink, G. R., & Vogeley, K. (2008). Minds at rest?

Social cognition as the default mode of cognizing and its putative relationship to the "default

system" of the brain. *Consciousness and Cognition*, *17*(2), 457–467.

https://doi.org/10.1016/J.CONCOG.2008.03.013

Schilbach, L., Wohlschlaeger, A. M., Kraemer, N. C., Newen, A., Shah, N. J., Fink, G. R., & Vogeley, K.

(2006). *Being with virtual others : Neural correlates of social interaction*. *44*, 718–730.

https://doi.org/10.1016/j.neuropsychologia.2005.07.017

Smith, L. E., & Bisazza, J. A. (1982). The comprehensibility of three varieties of English for college

students in seven countries. *Language Learning*, *32*(2), 259–269. https://doi.org/10.1111/J.1467-

1770.1982.TB00971.X

Sohoglu, E., Peelle, J. E., Carlyon, R. P., & Davis, M. H. (2012). Predictive Top-Down Integration of

Prior Knowledge during Speech Perception. *Journal of Neuroscience*, *32*(25), 8443–8453.

https://doi.org/10.1523/JNEUROSCI.5069-11.2012

Soleymani, R., Selesnick, I. W., & Landsberger, D. M. (2019). ALTIS: A new algorithm for adaptive

long-term SNR estimation in multi-talker babble. *Computer Speech and Language*, *58*, 231–246.

https://doi.org/10.1016/j.csl.2019.05.001

W3C (2010). *Speech Synthesis Markup Language (SSML) Version 1.1*. https://www.w3.org/TR/speech-

synthesis11/

Stanislaw, H., & Todorov, N. (1999). Calculation of signal detection theory measures. *Behavior Research*

Methods, Instruments, and Computers, *31*(1), 137–149. https://doi.org/10.3758/BF03207704

Stewart, M. E., & Ota, M. (2008). Lexical effects on speech perception in individuals with "autistic"
traits. *Cognition*, *109*(1), 157–162. https://doi.org/10.1016/J.COGNITION.2008.07.010

Stivers, T., Enfield, N. J., Brown, P., Englert, C., Hayashi, M., Heinemann, T., Hoymann, G., Rossano,
F., De Ruiter, J. P., Yoon, K. E., & Levinson, S. C. (2009). Universals and cultural variation in turn-
taking in conversation. *Proceedings of the National Academy of Sciences of the United States of*
America, *106*(26), 10587–10592. https://doi.org/10.1073/PNAS.0903616106

Tolins, J., Zeamer, C., & Fox Tree, J. E. (2018). Overhearing Dialogues and Monologues: How Does
Entrainment Lead to More Comprehensible Referring Expressions? *Discourse Processes*, *55*(7),
545–565. https://doi.org/10.1080/0163853X.2017.1279516

Tomasello, M. (2005). *Constructing a language: A usage-based theory of language acquisition*. Harvard
university press.

Tóth, B., Honbolygó, F., Szalárdy, O., Orosz, G., Farkas, D., & Winkler, I. (2020). The effects of speech
processing units on auditory stream segregation and selective attention in a multi-talker (cocktail
party) situation. *Cortex*, *130*, 387–400. https://doi.org/10.1016/J.CORTEX.2020.06.007

van Boxtel, J. J. A., Peng, Y., Su, J., & Lu, H. (2017). Individual differences in high-level biological
motion tasks correlate with autistic traits. *Vision Research*, *141*, 136–144.
https://doi.org/10.1016/j.visres.2016.11.005

van Ede, F., de Lange, F. P., & Maris, E. (2012). Attentional Cues Affect Accuracy and Reaction Time
via Different Cognitive and Neural Processes. *Journal of Neuroscience*, *32*(30), 10408–10412.
https://doi.org/10.1523/JNEUROSCI.1337-12.2012

Van Engen, K. J., & Bradlow, A. R. (2007). Sentence recognition in native- and foreign-language multi-
talker background noise. *The Journal of the Acoustical Society of America*, *121*(1), 519–526.
https://doi.org/10.1121/1.2400666

Vestner, T., Gray, K. L. H., & Cook, R. (2021). Visual search for facing and non-facing people: The
effect of actor inversion. *Cognition*, *208*, 104550.
https://doi.org/10.1016/J.COGNITION.2020.104550

Vestner, T., Tipper, S. P., Hartley, T., Over, H., & Rueschemeyer, S.-A. A. (2019). Bound together:
Social binding leads to faster processing, spatial distortion, and enhanced memory of interacting
partners. *Journal of Experimental Psychology: General*, *148*(7), 1251–1268.
https://doi.org/10.1037/xge0000545

Willoughby, M. T., Camerota, M., King, K. M., Nduku, T., & Piper, B. (2023). Leveraging item-level
accuracy and reaction time to address ceiling effects in the measurement of inhibitory control in
preschool-aged children. *Frontiers in Psychology*, *14*. https://doi.org/10.3389/FPSYG.2023.861441

Wilson, R. H. (2003). Development of a speech-in-multitalker-babble paradigm to assess word-
recognition performance. *Journal of the American Academy of Audiology*, *14*(9), 453–470.
https://doi.org/10.1055/S-0040-1715938

Wyer, N. A., Martin, D., Pickup, T., & Neil Macrae, C. (2012). Individual Differences in (Non-Visual)
Processing Style Predict the Face Inversion Effect. *Cognitive Science*, *36*(2), 373–384.
https://doi.org/10.1111/j.1551-6709.2011.01224.x

Yang, G., Wang, Y., & Jiang, Y. (2024). Social perception of animacy: Preferential attentional orienting
to animals links with autistic traits. *Cognition*, *251*, 105900.
https://doi.org/10.1016/J.COGNITION.2024.105900

Yi, H. G., Leonard, M. K., & Chang, E. F. (2019). The Encoding of Speech Sounds in the Superior
Temporal Gyrus. *Neuron*, *102*(6), 1096. https://doi.org/10.1016/J.NEURON.2019.04.023

Yu, A. C. L. (2010). Perceptual Compensation Is Correlated with Individuals' "Autistic" Traits:
Implications for Models of Sound Change. *PLOS ONE*, *5*(8), e11950.
https://doi.org/10.1371/JOURNAL.PONE.0011950

Yu, K., Zhou, Y., Zhang, L., Li, L., Li, P., & Wang, R. (2023). How Different Types of Linguistic
Information Impact Voice Perception: Evidence From the Language-Familiarity Effect. *Language*
and Speech, *66*(4), 1007–1029. https://doi.org/10.1177/00238309221143062

Zekveld, A. A., Rudner, M., Johnsrude, I. S., Festen, J. M., van Beek, J. H. M., & Rönnberg, J. (2011).
The Influence of Semantically Related and Unrelated Text Cues on the Intelligibility of Sentences in
Noise. *Ear and Hearing*, *32*(6), e16–e25. https://doi.org/10.1097/AUD.0B013E318228036A

Zekveld, A. A., Rudner, M., Johnsrude, I. S., Heslenfeld, D. J., & Rönnberg, J. (2012). Behavioral and
fMRI evidence that cognitive ability modulates the effect of semantic context on speech
intelligibility. *Brain and Language*, *122*(2), 103–113.
https://doi.org/10.1016/J.BANDL.2012.05.006

Zekveld, A. A., Rudner, M., Johnsrude, I. S., Rönnberg, J., & R€, J. (2013). The effects of working
memory capacity and semantic cues on the intelligibility of speech in noise. *The Journal of the*
Acoustical Society of America, *134*(3), 2225–2234. https://doi.org/10.1121/1.4817926

Zhao, S., Brown, C. A., Holt, L. L., & Dick, F. (2022). Robust and Efficient Online Auditory

Psychophysics. *Trends in Hearing*, *26*. https://doi.org/10.1177/23312165221118792

1159

SUPPLEMENTARY MATERIALS

Supplementary Information 1: Generation of multi-talker babble noise.

Noise features. The features of the multi-talker babble noise was set as follow: 1) We used a total of 8 competing voices (4 females and 4 males), that is a good compromise between creating sufficient interference with the target voices while keeping a reasonable amount of competing voices (Cooke, 2006; Li & Lutman, 2006; Miller, 1947; Simpson & Cooke, 2005); 2) We selected the f0 of the competing voices so they would not overlap with the target voices, as having too close f0 between target and competing voices may interfere too much with the task (Assmann, 1999; Bird, 1997; Brokx & Nooteboom, 1982; David et al., 2017; Lee & Humes, 2012); 3) We selected a f0 range between ~120 Hz and ~203 Hz by steps of around one semi-tone between each voice (see supplementary Figure 1), so the range would be large enough to cover a representative range of f0 in the general population (see Cristina Oliveira et al., 2021).

Noise distractor sentences generation. To generate the content of the noise distractor sentences, we used ChatGPT to generate 24 semantically anomalous sentences in English. Anomalous sentences were used here to eliminate the possibility that participants might extract an entire meaningful sentence from a speaker other than the target while keeping correct grammar (Van Engen & Bradlow, 2007). An example of the ChatGPT prompts used is *"Write X semantically anomalous but syntactically correct sentences"* and an example of the anomalous sentences generated is *"Her purple umbrella whistled a dolphin".* We then selected eight voices from the list proposed by Google text-to-speech AI: 4 females voices (*'en-US-News-K'; 'en-US-News-L'; 'en-US-Wavenet-E'; 'en-US-Wavenet-C'*) and 4 male voices (*'en-US-Wavenet-D'; 'en-US-News-N'; 'en-US-Wavenet-I'; 'en-US-News-M'*). Prior to generating the audio speech for the noise, we set the f0 parameter for each voice as follows. For all voices we used the vowel /ɑ/ as a reference

(Cristina Oliveira et al., 2021; De Krom, 1994), then for each voice we measured the original f0 of the voice for the duration of this vowel using the built-in function 'pitch' of Matlab (R2022b; The MathWorks Inc.) and time windows of 52 ms., and we defined the f0 as the median of the f0 measured for all time windows. Using Matlab, we then calculated by how much we should increase or decrease the original f0 of the voice to get to the custom f0 we wanted.

Supplementary Information 2: Check of optimal on-line experimental conditions.

Prior to beginning an experiment, participants went through a series of checks to ensure optimal 'auditory hygiene' while performing the tasks. To do so, we used guidelines and scripts from (Zhao et al., 2022). More specifically, participants first heard multi-talker babble noise alone without target sentences and they were instructed to adjust their audio volume to a comfortable level, so they would not be exposed to overly loud sounds during the experiment. They then performed a headphone screening using Antiphase tone (Woods et al., 2017) to confirm that they were wearing headphones. More specifically, for this task participants had to correctly detect an acoustic target in an intensity-discrimination task. On each trial, they were presented with three consecutive 200 Hz sinusoidal tones in random order, and they were asked to determine which of the tones was perceptually the softest. Two of the tones were presented diotically: 1) the 'standard', and 2) the 'target' that was presented at -6 dB relative to the standard. The third tone (the 'foil') had the same amplitude as the standard but was presented dichotically such that the left and right signals had opposite polarity (anti-phase, 180°). Over headphones, the standard and foil should have the same loudness, making the target clearly distinguishable as softer. In contrast, over loudspeakers the left and right signals interact destructively before reaching the listener's ears, resulting in a weaker acoustic signal at both ears, and thus a weaker loudness sensation for the foil than the target, causing participants to respond incorrectly. If participants failed 5 out of 6 trials, they were

proposed to redo the headphone check a second time. If they failed the headphone check a second time, they were not allowed to carry on with the experiment and the study automatically stopped for them.

Supplementary Figure 1. Dissimilarity matrix for Euclidean distances between fundamental frequencies of the voices. Captions in red represent the target voices for female (F3) and male (M3). Captions in black represent the concurrent voices of females (F1, F2, F4, F5) and males (M1, M2, M4, M5) that are used in the multi-talker babble noise

Supplementary Table I. Comparison of Linear Mixed Effect models fits with and without including the baseline as a covariate.

a. d'

Info	With Baseline	Without Baseline	Δ	Comment
LogLikelihood	-955	-985	30.62	
AIC	1950	2009	-59.23	Less is better
BIC	2044	2099	-54.49	Less is better

b. RTs

Info	With Baseline	Without Baseline	Δ	Comment
LogLikelihood	22.2	-31.8	53.98	
AIC	-4.4	101.6	-105.96	Less is better
BIC	90.36	191.6	-101.23	Less is better

Supplementary Table II. Results of the Linear Mixed Effect models with d' (a.) and RTs (b.) for Experiment 2 without baseline as a covariate.

a. d'

	F	df	df (res)	p
Design	2.33	2.00	208.00	0.100
Social	1.61	1.00	398.00	0.205
Semantic	7.35	1.00	210.00	**0.007**
Design x Social	0.05	2.00	398.00	0.956
Design x Semantic	0.40	2.00	210.00	0.670
Social x Semantic	1.74	1.00	416.00	0.188
Design x Social x Semantic	0.38	2.00	416.00	0.681

b. RTs

	F	df	df (res)	p
Design	0.82	2	208	0.440
Social	4.40	1	208	**0.037**
Semantic	9.55	1	208	**0.002**
Design x Social	2.84	2	208	0.061
Design x Semantic	1.59	2	208	0.206
Social x Semantic	0.02	1	208	0.889
Design x Social x Semantic	0.75	2	208	0.472

Supplementary Bibliography

Assmann, P. F. (1999). Fundamental frequency and the intelligibility of competing voices. *Proceedings of the 14th International Congress of Phonetic Sciences*, 179–182.

Bird, J. (1997). *Effects of a difference in fundamental frequency in separating two sentences.*

Brokx, J. P. L., & Nooteboom, S. G. (1982). Intonation and the perceptual separation of simultaneous voices. *Journal of Phonetics*, *10*(1), 23–36. https://doi.org/10.1016/S0095-4470(19)30909-X

Cooke, M. (2006). A glimpsing model of speech perception in noise. *The Journal of the Acoustical Society of America*, *119*(3), 1562–1573. https://doi.org/10.1121/1.2166600

Cristina Oliveira, R., Gama, A. C. C., & Magalhães, M. D. C. (2021). Fundamental Voice Frequency: Acoustic, Electroglottographic, and Accelerometer Measurement in Individuals With and Without Vocal Alteration. *Journal of Voice*, *35*(2), 174–180. https://doi.org/10.1016/J.JVOICE.2019.08.004

David, M., Lavandier, M., Grimault, N., & Oxenham, A. J. (2017). Sequential stream segregation of voiced and unvoiced speech sounds based on fundamental frequency. *Hearing Research*, *344*, 235–243. https://doi.org/10.1016/J.HEARES.2016.11.016

De Krom, G. (1994). Consistency and Reliability of Voice Quality Ratings for Different Types of Speech Fragments. *Journal of Speech and Hearing Research*, *37*(5), 985–1000. https://doi.org/10.1044/JSHR.3705.985

Lee, J. H., & Humes, L. E. (2012). Effect of fundamental-frequency and sentence-onset differences on speech-identification performance of young and older adults in a competing-talker background. *The Journal of the Acoustical Society of America*, *132*(3), 1700. https://doi.org/10.1121/1.4740482

Li, G., & Lutman, M. E. (2006). *Sparseness and speech perception in noise*. http://www.isca-speech.org/archive/interspeech_2006/i06_1466.html

Miller, G. A. (1947). The masking of speech. *Psychological Bulletin*, *44*(2), 105–129. https://doi.org/10.1037/H0055960

Simpson, S. A., & Cooke, M. (2005). Consonant identification in N-talker babble is a nonmonotonic function of N. *The Journal of the Acoustical Society of America*, *118*(5), 2775–2778. https://doi.org/10.1121/1.2062650

Van Engen, K. J., & Bradlow, A. R. (2007). Sentence recognition in native- and foreign-language multi-talker background noise. *The Journal of the Acoustical Society of America*, *121*(1), 519–526. https://doi.org/10.1121/1.2400666

Woods, K. J. P., Siegel, M. H., Traer, J., & McDermott, J. H. (2017). Headphone screening to facilitate web-based auditory experiments. *Attention, Perception, and Psychophysics*, *79*(7), 2064–2072. https://doi.org/10.3758/S13414-017-1361-2/FIGURES/6

Zhao, S., Brown, C. A., Holt, L. L., & Dick, F. (2022). Robust and Efficient Online Auditory Psychophysics. *Trends in Hearing*, *26*. https://doi.org/10.1177/23312165221118792/ASSET/IMAGES/LARGE/10.1177_23312165221118792-FIG12.JPEG