Raw signal segmentation for estimating RNA modifications and structures from Nanopore direct RNA sequencing data

Guangzhao Cheng, Aki Vehtari, and Lu Cheng[*]

Department of Computer Science, Aalto University, Finland

[*]Correspondence to: lu.cheng.ac@gmail.com

Abstract

Estimating RNA modifications from Nanopore direct RNA sequencing data is an important task for the RNA research community. Current computational methods could not provide satisfactory results due to the inaccurate segmentation of the raw signal. We develop a new method, SegPore, that utilizes a molecular jiggling translocation hypothesis to segment the raw signal. SegPore is a pure white-box model with a superior interpretability, which significantly reduces structured noise in the raw signal. Based on the improved signal segmentation, SegPore+m6Anet has achieved state-of-the-art performance in m6A identification. Additionally, we demonstrate SegPore's interpretable results and decent performances on inosine modification estimation and RNA secondary structure estimation. An interesting discovery in RNA structure estimation is that the end points of the reads take place at the start of stem structures along the reverse transcription direction. Our results indicate SegPore's capability to concurrently estimate multiple modifications at the individual molecule level from the same Nanopore direct RNA sequencing data, as well as shed light on RNA structure estimation from a novel angle.

Introduction

RNA modifications play important roles in different diseases, such as Acute Myeloid Leukemia (Yankova, Aspris and Tzelepis 2021) and Fragile X Syndrome (Prieto, Folci and Martin 2020), as well as biological processes, such as cell differentiation (Bellodi et al. 2013; Lee et al. 2019) and immune response (Quin et al. 2021). To date, researchers have identified over 150

different types of RNA modifications (Boccaletto et al. 2022; Chen, Owens and Liu 2023;

Zimna et al. 2023; Ohira and Suzuki 2024), highlighting the complexity and diversity of RNA

regulation. RNA modifications are pivotal for RNA secondary structures, e.g., modifications in

tRNA are essential for accurate and efficient decoding of the mRNA codons into proteins

(Agris et al. 2017). N1-methylpseudouridine (m1Ψ) is used to enhance the efficacy of COVID-

19 mRNA vaccines (Nance and Meier 2021), which showcases the practical applications of

RNA modifications.

To identify RNA modifications, researchers generally resort to immunoprecipitation methods

such as MeRIP-Seq (Meyer et al. 2012), miCLIP (Linder et al. 2015) and m6ACE-Seq (Koh,

Goh and Goh 2019), where a m6A antibody is used to target m6A in these protocols. Like

ChIP-seq, we could infer m6A locations on the transcripts from the generated next-generation

sequencing (NGS) data. RNA structure estimation protocols such as SHAPE-MaP (Siegfried

et al. 2014) follow a similar idea by attaching chemical adducts to nucleotides in loop regions

but not stem structures, where the chemical adducts are treated as modifications. A reactivity

score profile obtained from the sequencing data is then used to estimate the RNA structure.

However, there are several limitations of these NGS-based RNA modification estimation

methods. First, a modification-specific antibody is needed for each modification, while there

are more than 150 modifications. Second, these methods could not directly measure RNA

modifications, i.e., they infer m6A locations on transcripts from the NGS data. As a result,

researchers could not get modification estimations on single molecules. The direct RNA

sequencing (DRS) of Oxford Nanopore Technologies (ONT) is a new sequencing technology

that could address both challenges.

The direct RNA sequencing measures the current intensity as an RNA molecule translocates

through the pore. For ONT pore version R9.4, five nucleotides reside in the pore, which is

termed as *5mer* (Jain et al. 2018). The 5mer blocks certain numbers of ions passing through

the pore, the amount of which is measured as the current intensity in a unit of time. During the

translocation process, each 5mer stays in the pore for a short period, and the current

measurement varies around a baseline level. Due to differences in size, shape, order, and

chemical properties of the nucleotides of a 5mer, the current level varies across different

5mers. The basic idea of Nanopore sequencing is to infer the original nucleotides from the

currents of different 5mers. As a reference, ONT has provided the mean and standard

deviation (std) of the current intensity for each 5mer of RNA based on their training data. Since

nucleotides with a larger size could block more ions, e.g., Adenine and Guanine, their current

signal levels are lower than Cytosine and Uridine.

The raw signal of DRS could be utilized to estimate RNA modifications and RNA structures.

DRS directly records the raw current signals for each nucleotide on the RNA molecule. For a

normal nucleotide and its modification, e.g., Adenosine and m6A, different current signals are

generated due to their chemical property difference. In theory, we could infer each nucleotide

and its modification state from the raw signals of a RNA molecule. Given the capability of

estimating RNA modifications, researchers could estimate RNA structures from DRS data

(Stephenson et al. 2022). However, these tasks are challenging from the computational

perspective.

The central computational problem of DRS is the segmentation of raw current signal. The raw

current signal is split into segments and assigned to corresponding 5mers, which determines

the RNA sequence, as well as the modifications. Current mainstream methods for segmenting

raw signals are represented by Nanopolish (Loman, Quick and Simpson 2015; Simpson et al.

2017) and Tombo (Stoiber et al. 2017). Nanopolish employs a Hidden Markow Model (HMM)

for the raw signal segmentation, while Tombo segments the raw signal by scanning for large

signal shifts. Due to the lack of the RNA translocation process modelling, these methods could

not provide accurate segmentation results. Consequently, the derived raw signal segments

contain unwanted noises that deteriorate the performance of downstream tasks such as RNA

modification and structure estimation.

The second challenge is that an RNA modification may only induce a minor change in the

current signal of the corresponding 5mer. This means we can only distinguish 5mers with

significant changes in their current signal, i.e., those with a high signal-to-noise ratio. This

problem would be mitigated if we could reduce the noise level in the current signal. In other

words, downstream tasks such as estimation of RNA modifications and structures, may

achieve a better performance given the de-noised raw signal segments. Therefore, it is

necessary to model the physical DRS process to gain a better understanding of the noises,

which is missing in current RNA modification estimation methods.

Moreover, current RNA modification methods are hindered by limitations in data availability

and interpretability. Present RNA modification detection methods can be classified into two

groups: comparison-mode group and single-mode group (Zhong et al. 2023). The

comparison-mode group, such as DiffErr (Parker et al. 2020), DRUMMER (Price et al. 2020),

xPore (Pratanwanich et al. 2021) and Nanocompore (Leger et al. 2021), compares modified

and unmodified samples, which requires both modification-abundant and modification-sparse

datasets for the model training. The single-mode group, such as m6Anet (Hendra et al. 2022),

employs deep neural networks (DNN) to classify modified and unmodified nucleotides by

feeding various features (e.g., mean, std, dwell time) of the raw signal segments provided by

Nanopolish or Tombo. The training data are generated from modification-abundant samples,

where the signal segment features are used as input and estimated modifications given by

NGS-base methods are used as the labels. Note that current methods are modification-

specific, i.e. one method only handles one type of modification. As a result, the amount of

training data increases linearly as the number of RNA modification types to be studied.

Additionally, we may not be able to generate the training data due to technical reasons, e.g.

removing a certain type of RNA modification from the samples. The RNA modification

estimation task would be much simpler if we could take the mean of a raw signal segment and

compare it against a reference table to determine its modification state. This brings out the

interpretability problem of current DNN-based methods, which utilize the input features in a

complicated way for the modification estimation. It is impossible to gain straightforward

interpretations why an input raw signal segment corresponds to its estimated modification

state.

To address the above challenges, we have developed SegPore, which is capable of

diminishing noise using a novel signal segmentation algorithm and offers the flexibility to

estimate various modifications by a customized 5mer parameter table. Due to the change of

the segmentation algorithm, we have re-implemented almost all components of the traditional

RNA modification estimation workflow. SegPore consists of (1) a hierarchical hidden Markov

model (HHMM) for segmenting the raw current signal of DRS, (2) alignment algorithms for

aligning raw current signal segments with reference sequence, and (3) a Gaussian mixture

model (GMM) for RNA modification estimation. SegPore provides interpretable segmentation

results, which facilitates various downstream analyses. We demonstrate its capabilities in the

estimation of RNA modifications (m6A and inosine) and RNA secondary structure.

124 Results

125 RNA translocation hypothesis

It is challenging to segment the raw current signal due to its complexity. To solve this problem,

we need to know how exactly the RNA molecule moves through the pore. In traditional

basecalling algorithms such as Guppy and Albacore, we implicitly assume that the RNA

molecule is translocated through the pore by the motor protein in a monotonic fashion, i.e.,

the RNA is pulled through the pore unidirectionally. In the DNN training process of Guppy and

Albacore, we try to align the current signal with the reference RNA sequence. The alignment

is unidirectional, which is the source of the implicit monotonic translocating assumption.

Figure 1. RNA translocation hypothesis. (*A*) Jiggling RNA translocation hypothesis. Top panel shows the raw current signal of Nanopore direct RNA sequencing. The gray areas are SegPore estimated transition blocks. Here we focus on three neighboring 5mers and consider the center 5mer (CTACG) as the current 5mer. The RNA molecule might be translocated forward or backward for a short period during the translocation process of the current 5mer. If the RNA molecule is pulled backward, the previous 5mer ("prev" state) is placed in the pore and the current signal is similar to the previous 5mer's baseline (mean and std highlighted by red lines and shades). If the RNA is pushed forward, the current signal is similar to the next 5mer's baseline ("prev" state). (*B*) Example raw current signals that supports this jiggling hypothesis, with dash rectangles highlighting relevant base blocks. Measurements assigned to the previous and next 5mer are highlighted as red and blue points. It is obvious to observe that red points are close to the previous 5mer's baseline and blue points are close to the next 5mer's baseline. The raw current signals were extracted from mESC WT samples of the training data in the m6A benchmark experiment.

However, the raw current data suggests that the motor protein translocates RNA back and

forth. Fig. 1B shows several example fragments of DRS raw current signal (Zhong et al. 2023),

each of which roughly corresponds to three neighboring 5mers. The highlighted spikes have

similar current intensities, either as the previous 5mer or the next 5mer. Similar patterns are

widely observed across the whole data. This suggests that the RNA molecule may move

forward and backward while passing through the pore. This observation can also be supported

by previous reports (Caldwell and Spies 2017; Craig et al. 2017), in which the helicase (the

motor protein) translocates the DNA strand through the nanopore in a back-and-forth manner.

Based on the reported kinetic model (Craig et al. 2017), we hypothesize that the RNA is

translocated through the pore in a jiggling manner. On average, the motor protein sequentially

translocates 5mers on the RNA strand forward, and each 5mer resides in the pore for a short

time. During the short period of a single 5mer, the motor protein may swiftly drive the RNA

molecule forward and backward by 0.5~1 nucleotide in the translocation process of the current

5mer (Fig. 1A), which makes the measured current intensity occasionally similar to the

previous or the next 5mer. When the motor protein does not move the RNA molecule, we

assume that the 5mer inside the pore oscillates thermodynamically, generating current

intensities around its baseline. Additionally, we assume there is a sharp change in the current

intensity between two consecutive 5mers, which serves as their boundary.

We also assume that the raw current signal of a read can be segmented into a series of

alternating base and transition blocks (Fig. 1). In the ideal case, a base block corresponds to

the base state where the 5mer resides in the pore and jiggles between neighboring 5mers,

i.e., the current 5mer can transiently jump to the previous or the next 5mer. A transition block

corresponds to the transition state between two consecutive base states where one 5mer

translocates to the next 5mer in the pore. The current signal should be relatively flat in the

base blocks, while a sharp change is expected in the transition blocks. In practice, the number

of transition blocks is generally overestimated since we are not able to distinguish the

transitions within a base block and between base blocks. As a result, multiple base blocks

may correspond to only one 5mer, which is determined by the SegPore alignment algorithms.

SegPore Workflow

The SegPore workflow (Fig. 2) contains six steps: (1) preprocess fast5 files to pair the raw

current signal segments with reference RNA sequence fragments, (2) segment each raw

current signal using the hierarchical hidden Markov model (HHMM) into base and transition

blocks, (3) align the derived base blocks with the paired RNA sequence, (4) estimate the

modification state for each 5mer of the RNA sequence, (5) fit a two-component Gaussian

Mixture Model (GMM) for each unique 5mer across different RNA reference sequences, and

(6) use results of step 5 to update relevant parameters. Step 3~6 will iterate several times until

the estimated parameters stabilize. Detailed descriptions are provided in Methods and

Supplementary Note 1-3.

Figure 2. SegPore workflow. (*A*) The general workflow. First, basecalling and mapping are performed using Guppy and Minimap2 such that a raw current signal fragment is paired with a reference sequence fragment. Meanwhile, the raw current signal of a read is split into segments by HHMM and an estimated mean (μ_i) is derived for each segment. Then, the current signal segments (σ_i) are aligned with the 5mer list of the corresponding reference sequence fragment using the full/partial alignment algorithm, given a 5mer parameter table. Here we use A_j to denote A at jth position on the reference. Next, all aligned to the same 5mer at different genomic locations are pooled together and a two-component GMM is fitted to re-estimate the 5mer parameters. One GMM component models the unmodified state and the other models the modified state, while the hidden variable of the GMM specifies the modification state of the 5mer on each read. The parameter estimation process is iterated several times on the training data to gain a stable estimation of the 5mer parameter table. The final 5mer parameter table is used for estimating the modification states on the test data. (*B*) Hierarchical hidden Markov model. The outer HMM partitions current signal into alternating base blocks and transition blocks. An inner HMM approximates the emission probability of a base block by considering neighboring 5mers. A linear model approximates the emission probability of a transition block. (*C*) Full/partial alignment algorithms. Each row is an estimated mean of a base block given by HHMM. Each column is a 5mer of the reference sequence. One 5mer can be aligned to multiple means. (*D*) Gaussian mixture model (GMM) for estimating modification states. The green component codes the unmodified state of a given 5mer. The blue component codes the modified state of the given 5mer. Each component has three parameters: mean (μ), std (σ) and weight (ω).

The final outcomes of SegPore are the "eventalign" and modification state estimation. The

SegPore eventalign is similar to the output of Nanopolish "eventalign" command, which is the

pairing between raw current signal segments and 5mers of the corresponding RNA reference

sequences. For selected 5mers, SegPore outputs the modification rate for each site and the

modification state of the given site on each read. The key element of SegPore is the 5mer

parameter table, which specifies the mean and std of each 5mer in an unmodified or modified

state (Fig. 2A). Since the peaks (modified and unmodified state) are separable for a limited

number of 5mers, we could only obtain the modification parameters for these 5mers in 5mer

parameter table, i.e. SegPore could not provide the modification state estimation for other

5mers.

m6A identification

We demonstrate SegPore's performance on raw data segmentation and m6A identification

using independent public datasets as training and test data. It is well known that there are 18

DRACH (where D denotes A, G or U, and H denotes A, C or U) motifs for m6A (Linder et al.

2015). In this study, we concentrate on estimating the m6A modification on the DRACH motif.

We first estimate the 5mer parameter table of m6A modification from the training data using

public Nanopore direct RNA sequencing (DRS) data from three wild type samples of HEK293T

cells (Pratanwanich et al. 2021). To get the 5mer parameter table for m6A modification, we

concatenate fast5 files of all samples and run the full SegPore workflow. We iterate the

parameter estimation process five times to gain a stabilized 5mer parameter table, which

contains modification parameters for ten 5mers. Their modification state distribution

significantly differs from the unmodified state distribution, with moderate support of read

counts and genomics locations.

Next, we perform segmentation and m6A identification on test data, which is the DRS data

from wild type mouse embryonic stem cells (mESCs) in a benchmark study (Zhong et al. 2023).

Zhong et al. benchmarked a set of tools with different input requirements. Considering the

similarity of the methods and input requirements, we select single-mode tools as baselines:

Tombo, MINES (Lorenz et al. 2020), Nanom6A (Gao et al. 2021), m6Anet, and Epinano (Liu

et al. 2019). We process the test data using standard SegPore workflow with 5mer parameter

table estimated from the training data. As a result, we get SegPore eventalign for all 5mers,

modification rates for selected sites (differentiable motifs), modification states of these sites

on each read. To demonstrate the performance of SegPore eventalign on downstream tasks,

we feed the SegPore eventalign results to m6Anet, which is termed as SegPore+m6Anet.

Figure 3. m6A identification. (*A*) Histogram of current signal mapped to an example modified genomic location (chr10:128548315, GGACT) across all reads in training data given by Nanopolish (left) and SegPore (right). (*B*) Histogram of current signal mapped to GGACT at all annotated m6A genomic locations of the training data given by Nanopolish (left) and SegPore (right). (*C*) Benchmark results on all DRACH motifs. (*D*) Benchmark results on six selected motifs. (*E*) Modification rate of selected genomic locations (upper panel) and modification states of all reads mapped to an example gene (ENSMUSG00000003153, lower panel). The black borders in the heatmap highlight the bi-clustering results.

SegPore demonstrates the improved segmentation results compared with Nanopolish. Fig.

3A shows the eventalign results of Nanopolish and SegPore at an example genomic location

with m6A modifications. The histogram shows the distribution of the raw signal segment mean

of all reads mapped to the genomic location. Compared with Nanopolish eventalign results,

the bimodal distribution is more obvious in SegPore results. We next pooled all reads mapped

to modification genomic locations (based on the ground truth) for the classical m6A motif

"GGACT". Fig. 3B illustrates the current signal distribution over all reads mapped to these

locations, where prominent peaks are observed in SegPore but not in Nanopolish. The results

suggest that SegPore is able to remove a certain degree of noise from the raw current signal,

which makes the modification distribution clearer.

SegPore exhibits decent performance on m6A identification on the test data. Given the ground

truth miCLIP2 (Kortel et al. 2021) data, we calculate the area under the curve (AUC) of the

receiver operating characteristic (ROC) curve and precision-recall (PR) curve for each

method. Fig. 3C shows the benchmark results on all DRACH motifs, where SegPore+m6Anet shows the best performance (ROC AUC=89.2%, PR AUC=43.0%). Next, we demonstrate SegPore's modification estimation performance on selected 5mers. We selected six m6A motifs ("GGACT", "GGACA", "GGACC", "AGACA", "AGACC", "AGACT") based on the following two criteria (1) modified and unmodified peaks are significantly different and (2) the 5mer is both abundant in the training and test data (Supplementary Fig. 1). As shown in Fig. 3D, SegPore's ROC AUC is 82.8%, where the best is 89.2% (SegPore+m6Anet). SegPore's PR AUC is 37.6%, where the best is 48.0% (Nanopolish+m6Anet). The results suggest the decent performance of SegPore in m6A identification.

SegPore naturally identifies m6A modifications at the single molecule level. Fig. 3E demonstrates high modification genomic locations (modification rate > 0.1, also supported by ground truth) of an example gene ENSMUSG00000003153, where rows are reads and columns are genomic locations. Biclustering was performed on the heatmap to illustrate the modification patterns, which resulted in 6 clusters of the reads and 3 clusters of the genomic locations. The heatmap suggests that modifications at the 6th, 7th, and 8th genomic locations are specific to cluster 4, 5, 6 of the reads, which correspond to different modification mechanisms. It is also obvious that the majority of reads at the 3rd and 5th genomic locations are modified across other clusters.

Inosine identification

Thanks to the flexibility of the 5mer parameter table, SegPore can be easily extended to estimate other RNA modifications using the same computational framework. We next test the performance of SegPore on inosine identification, which is another RNA modification of adenine (Slotkin and Nishikura 2013; Nishikura 2016; Eisenberg and Levanon 2018; Nguyen et al. 2022). The *in virto* transcription (IVT) data and H9 human embryonic stem cells (hESCs) data in a public dataset (Nguyen et al. 2022) were used for this task. The 5mer parameter table of inosine was obtained from IVT data, and the H9 data was for testing.

First, we explain the training process. The IVT data contained eight pure-G samples and eight

pure-I samples, which were merged into one pure-G and one pure-I sample, respectively. The

pure-G sample was an unmodified sample where A, C, G, U nucleotides were used in the

synthesis of a designed RNA molecule. The designed sequence contains 81 different XXGXX

5mers, where X is A, C or U/T. The pure-I sample was a modified sample where A, C, I

(inosine), U were used for synthesizing the same RNA molecule. The "G" nucleotides in the

RNA sequence could either be replaced by A or I nucleotides, which provided data to infer

distributions of 5mers in the form of XXA/IXX. We run standard SegPore workflow on the pure-

G sample and pure-I sample to get a stabilized 5mer parameter table, which contains

modification states for 61 selected 5mers (Supplementary Fig. 2A). Note that the mean of

XXGXX and XXAXX are fixed, whose values are specified by the 5mer parameter table of

ONT.

The derived 5mer parameter table nicely depicts the selected 5mer distributions. Fig. 4A

shows three example patterns of 5mer distributions, which are the densities derived from raw

signal segments aligned to the selected 5mers on the reference sequence. We obtain the

XXGXX distributions from the pure-G sample and XXA/IXX distributions from the pure-I

sample. For the pure-G sample, we expect only one peak for XXGXX, while we expect two

peaks for XXAXX and XXIXX in the pure-I sample. There are three general patterns: (1) G is

replaced by A or I in the pure-I sample, but we cannot differentiate the peaks of XXAXX and

XXIXX (top panel) (2) G is replaced by A or I, and the peaks of A and I can be clearly identified

(center panel) (3) G is only replaced by I and the peak of I is significantly different to the ONT

reference A peak (bottom panel). The selected 5mers belong to the second and third patterns

(Supplementary Fig. 2A). Supplementary Fig. 2B shows that the mean of XXIXX is generally

between that of XXAXX and XXGXX, which agrees with the findings in the original publication

(Nguyen et al. 2022).

Figure 4. Inosine identification. (*A*) Current signal distributions of example 5mers in IVT data, which are classified into three patterns. The shaded area is the smoothed density of current signal of a given 5mer across different reads and different genomic locations. The fitted Gaussian density curves are given by estimated 5mer parameters. For each pattern, the top panel shows the distributions for 5mers like XXGXX (X is A, C, T/U) in the pure-G sample, while the bottom panel shows distributions of the same 5mers with the center nucleotide replaced by A or I. These examples represent three patterns of 5mers: (1) 5mers that show no difference between A and I (2) 5mers that show significant difference between A and I and (3) 5mers that show significant difference between A and I, but the component weight of A is low. (*B*) Current signal distribution of example 5mers CAACA or CAICA pooled from different reads and different genomic locations in IVT data (training data) and H9 data (test data). (*C*) Modification rate distributions in positive control (inosine modification sites) and negative control (unmodified sites). Modification states are given by the ground truth.

We test the performance of SegPore on H9 DRS data, which consists of ten wild type samples.

We used the 5mer table estimated from the training data and ran the standard SegPore

workflow on H9 data, which provides the modification rate of each genomic location that

matches the selected 5mers. Due to data availability, we only find the ground truth of locations

on Chromosome 3 and 11 from the original publication (Nguyen et al. 2022). Out of these

locations, 37 inosine modification sites match our selected 5mers, which are used as the

positive control, and 241 unmodified sites match our selected 5mers, which are used as the

negative control. Fig. 4b shows the current signal distribution of one selected 5mer CAACA

by pooling all relevant sites on positive control, which exhibits two clear peaks for CAACA and

CAICA. This suggests a high consistency of 5mer distributions between the IVT data and the

H9 data. Fig. 4C shows the modification rate distribution in the positive and negative controls.

It can be seen that the modification rates of positive control are higher than that of negative

control on average (t-test, p-value=2.22e-11).

RNA structure estimation

RNA structure can be probed by sequencing based approaches such as SHAPE-MaP and nanoSHAPE. Their idea is to treat the RNA molecules with chemical adducts, which are only attached to single stranded parts but not double stranded parts of RNA molecules. The chemically treated RNA is then subjected to short-read sequencing (SHAPE-Map) or Nanopore sequencing (nanoSHAPE). In short-read sequencing, a nucleotide attached by an adduct turns out to be a mutation, while it is recognized as a modification in Nanopore sequencing. The mutation rate or modification rate is then transformed to a reactivity score that is utilized by the RNAfold software (Lorenz et al. 2011) to generate RNA structure.

SegPore can be used to identify the modifications and predict RNA structure from Nanopore sequencing data. As an illustration, we analyze the public Nanopore sequencing data of pri-miR-17~92 RNA in the nanoSHAPE (Stephenson et al. 2022), for which the ground truth structure (based on SHAPE-MaP) is available. In this dataset, we choose Nanopore sequencing data of two samples: one *in vitro* transcribed (IVT) sample with no modifications and one adduct treated sample with modifications. Following standard SegPore workflow, we first segment raw current signals of reads in both samples. Since all reads are from the same reference sequence, we directly align the derived signal segments with 5mers of the pri-miR-17~92 reference sequence. Then, for each location (5mer) of the reference sequence, we fit a two-component Gaussian mixture model to all signal segments aligned to that location in both samples, with one component representing the unmodified state and the other representing the modified state. Next, we estimate the modification rate and reactivity score for each location of the reference sequence based on the fitted GMM parameters. In the end, pri-miR-17~92 RNA sequence and the reactivity scores are fed into RNAfold software (Lorenz et al. 2011) to generate the final RNA structure.

Figure 5. RNA (pri-miR-17~92) structure estimation using SegPore. (*A*) Six example sites chosen from the loop part of six conserved hairpin structures, with the corresponding 5mers displayed at the bottom. The top panel is from the unmodified sample (in vitro transcription) and the lower panel is from the modified sample (adduct treated), whose modified component is highlighted in red. (*B*) Arc diagrams of RNA structure based on SHAPE-Map (blue) and SegPore (green). X-axis is the 5'-3' location on the reference sequence. (*C*) Reactivity scores of SHAPE-MaP and SegPore. A high reactivity score is associated with a high modification rate in the modified sample. (*D*) SegPore predicted RNA structure, with different colors denoting peak regions in the alignment end location distribution. The crossings indicate the stem structures near potential stop locations during reverse transcription. The numbers indicate the 5'-3' locations of the nucleotides. The reverse transcription is from 3' to 5', i.e. from location 951 to 1. (*E*) The same arc diagrams as (*B*) with peak regions highlighted. (*F*) Alignment end location distribution for both the unmodified and modified samples. X-axis indicates 5'-3' locations on the reference sequence. Y-axis is the probability density.

The RNA structure given by SegPore nicely agrees with the ground truth (SHAPE-MaP), as

shown in Fig. 5B. The conserved six hairpin structures, each marked by a dashed line in the

center, are almost identical between SegPore and SHAPE-MaP predictions. Six example sites

in the loop part from each hairpin structure are selected to illustrate the modifications in Fig.

5A, where a large component of modification (highlighted in red) is observed in the modified

sample. This result is consistent with the expected outcome of the SHAPE protocol as the

loops are single stranded, where adducts are attached and recognized as modifications. The

reactivity scores of SHAPE-MaP and SegPore are similar (Fig. 5C), and peaks are located at

similar sites. It can be seen that peak regions in Fig. 5C generally correspond to single

stranded regions with no base pairing in Fig. 5B.

After aligning the raw signal with the reference sequence, large amounts of reads in both

unmodified (86.3%) and modified samples (95.7%) do not cover the full-length reference

sequence. We are curious about the cause and examine the distribution of the alignment end

locations on the reference sequence. Fig. 5F shows that the distributions are very similar

between the unmodified and modified samples, which precludes the adduct modifications from

being the cause. Comparing the peak regions in Fig. 5F with the RNA structure in Fig. 5D and

Fig. 5E, we find that the peak regions are generally located right before stem structures, i.e.,

a stretch of paired bases. Note that the reverse transcription starts from 3' to 5', it is obvious

that the peak regions are right next to the downstream stem structures, the start locations of

which are highlighted by crossing signs in Fig. 5D.

The above finding suggests that peaks are associated with reverse transcription in the

Nanopore sequencing library preparation. Here, we hypothesize that the reverse transcriptase

enzyme loses its momentum when it hits stem structures highlighted by crossings in Fig. 5D,

as it takes lots of energy to unwind the stem structures. When the reverse transcriptase

enzyme stalls on the RNA molecule, we hypothesize that the RNA molecule fractures near

the stalled locations due to the thermodynamic movements of the reverse transcriptase

enzyme. Therefore, a partial read corresponds to a fractured RNA molecule in the reverse

transcription.

Discussion

The key computational problem in DRS is how to segment the raw current signal. We

developed a segmentation algorithm that utilized the jiggling property in the physical process

of DRS and demonstrated that the segmentation led to cleaner current signals in m6A, inosine

identification, as well as RNA structure estimation. We have shown that m6Anet achieved

better performances based on SegPore's improved segmentation. We believe that the de-

noised current signals will be beneficial for other downstream tasks. However, some open

questions remain to be addressed in the future. In SegPore, we assume a drastic change

between two consecutive 5mers, which may hold for 5mers with large difference in their

current baselines but may not hold for those with small difference. Another question is the

physical meaning of derived base blocks. In the ideal case, one base block corresponds to

one 5mer, while multiple base blocks are aligned with one 5mer in the real case. One guess

is that the HHMM may partition the current signal of one 5mer into several base blocks, during

which the 5mer may oscillate between different sub-states, i.e., each sub-state of the same

5mer has different baselines.

Different from DNN-based methods, SegPore offers great interpretability to the estimation of

RNA modifications, which makes it applicable to different modifications. SegPore codes

current intensity levels for different 5mers in a parameter table, where unmodified and modified

5mers are modeled using two Gaussian distributions. Given 5mer parameter tables of different

RNA modifications, e.g., m6A, inosine, pseudouridine, etc., we can estimate various

modifications from the same DRS data. Since we directly model the current level of 5mers

with RNA modifications, SegPore naturally provides the modification states on the single RNA

molecule level. This capability will be particularly powerful for studying RNA modifications in

various disease contexts. However, the amount of 5mers with significant changes in their

modification states is relatively small. We may need larger training data to improve the

accuracy and expand 5mers to 7mers or 9mers to consider more context information, on which

significant baseline change might be observed on more kmers.

In RNA structure experiment, we also found there was an association between the end points

of reads and the stem structures of the RNA molecule. We hypothesize that the RNA molecule

fractures are near the stem structures. If stronger stem structures are associated with a larger

proportion of partial reads, we may use this information to probe the binding energy of the

stems and incorporate it in the RNA structure estimation, which is a unique angle provided by

DRS. SegPore differs from the original structure estimation method NanoSHAPE in the

following aspects (1) we use SegPore's segmentation results instead of Nanopolish's, (2) we

estimate RNA modifications using GMM while NanoSHAPE uses outlier detection, and (3) the

reactivity score profiles are calculated differently. Due to the improved segmentation, SegPore

increased the mapping rate of full-length RNA sequences. In our experiment, SegPore

identified 21% of reads to be full-length, while Nanopolish only identified 5%.

Computation speed is another concern in handling the fast5 files. We implemented a GPU-

accelerated inference algorithm in SegPore, which has a 10~20 fold speedup compared with

the CPU-based implementation. We believe that the GPU-implementation will unlock the full

potential of SegPore for a wider range of downstream tasks and larger datasets.

Methods

5mer parameter table

390   We download the kmer models "r9.4_180mv_70bps_5mer_RNA" from GitHub repository of

391   ONT (https://github.com/nanoporetech/kmer_models). The columns "level_mean" and

392   "level_stdv" were used as the mean and std for unmodified 5mers in a parameter table. We

393   denoted it as the 5mer parameter table of ONT, which was used for initialization in SegPore.

SegPore workflow

Preprocessing

We first perform basecalling of the input fast5 file using Guppy. Then we map the basecalled

sequence to the reference sequences using Minimap2 (Li 2018). After that, we obtain the

paired raw current signal segments and corresponding fragments of the reference sequence

using Nanopolish eventalign. Meanwhile, we obtain the raw current signal segments

corresponding to the polyA tail. Finally, we standardize the raw current signal of each read

based on its polyA tail, such that the mean and std of the polyA tail are the same across

different reads.

Signal Segmentation via hierarchical Hidden Markov model

The RNA translocation hypothesis naturally leads to a hierarchical hidden Markov model (HHMM) for segmenting the raw current signal. As shown in Fig. 2B, our HHMM has two layers. The outer HMM divides the raw current signal into alternating base and transition blocks, as indicated by hidden states "B" and "T" in Fig. 2B. The inner HMM models a single base block and a linear model is used for each transition block. The inner HMM has four hidden states: "prev", "next", "curr", "noise". The "prev", "next", "curr" states refer to previous, next and current 5mer in the pore, while "noise" refers to random noise. Each raw current measurement is then emitted from one of these hidden states. The linear model with a large absolute slope is used to model the sharp changes in the transition block.

Given the raw current signal y of a read, we denote the hidden states of the outer hidden HMM by g. y and g are divided into $2K+1$ blocks c, where $y^{(k)}$, $g^{(k)}$ correspond to k th block and $c = (c_1, c_2, ..., c_k, ..., c_{2K+1})$, $c_k \in \{"B", "T"\}$. Note that blocks with odd index are base blocks, i.e. $k = 1, 3, 5, ..., 2K+1$, whereas blocks with even index are transition blocks. The likelihood of HHMM is given by

$$p(y, g) = p(y \mid g)p(g) \tag{1}$$

$$= p(y \mid g)\{\pi_{g_1}^{outer} \prod_{i=2}^{N} T_{g_{i-1}g_i}^{outer}\} \tag{2}$$

$$= \{\prod_{i=1}^{N} p(y_i \mid g_i)\} \{\pi_{g_1}^{outer} \prod_{i=2}^{N} T_{g_{i-1}g_i}^{outer}\} \tag{3}$$

$$= \{\prod_{k=0}^{K} p(y^{(2k+1)} \mid c_{2k+1} = "B")\} \{\prod_{k=1}^{K} p(y^{(2k)} \mid c_{2k} = "T")\} \{\pi_{g_1}^{outer} \prod_{i=2}^{N} T_{g_{i-1}g_i}^{outer}\} \tag{4}$$

where $T_{g_{i-1}g_i}^{outer}$ is the transition matrix of the outer HMM and $\pi_{g_1}^{outer}$ is the probability for the first hidden state. It is obviously seen that the left side of the Eq. 2 are emission probabilities, and the right side are the transition probabilities. It is not possible to directly compute the emission probabilities of the outer HMM (Eq. 3) since there exist dependencies for the current signal

measurements within a base or transition block. Therefore, we use the inner HMM and linear

model (Eq. 4) to handle the dependencies and approximate emission probabilities.

The inner HMM models the transitions between the hidden states "prev", "next", "curr", and

"noise". For "prev", "next", "curr" states, we use the Gaussian distribution as their emission

distribution. Uniform distribution is used as the emission distribution for the "noise" state. Given

these specifications, we can calculate the marginal likelihood of the inner HMM using the

Forward-Backward algorithm, which is used to approximate the emission probabilities of the

base blocks in the outer HMM. Similarly, we can approximate the emission probabilities of the

transition blocks using the likelihood of the standard linear model.

For any given g, we can calculate the joint likelihood (Eq. 1). Therefore, we enumerate

different configurations of g and choose the one with the highest likelihood. Detailed model

description is provided in Supplementary Note 1.

The parameter inference is challenging given the massive data size of fast5 files, which are

generally on the level of terabytes (TB). We developed a GPU-based inference algorithm to

accelerate the inference process. A detailed description of the GPU-accelerated inference

algorithm is provided in Supplementary Note 2.

In the end, we segment the raw current signal of a read into alternating base and transition

blocks, where one or multiple base blocks may correspond to only one 5mer. For each base

block, it has a mean and std parameter (Gaussian distribution). The mean values of the base

blocks are used as input for the downstream alignment tasks.

Alignment of raw signal segment with reference sequence

After segmenting the raw current signal of a read into base and transition blocks using HHMM,

we align the means of base blocks with the 5mer list of the reference sequence.

454 The alignment has three different matching cases. The first case is that one base block

455 matches with one 5mer, which means the base block follows the Gaussian distribution of the

456 given 5mer. Note that the 5mer might have two states: unmodified and modified. The

457 corresponding Gaussian parameters can be found in the 5mer parameter table. The second

458 case is the one base block matches with an indel "-", which means there is an inserted

459 nucleotide in the read. The third case is that an indel (0.0) matches with a 5mer, which means

460 there is a deleted nucleotide in the read.

462 Our score function in the alignment models the matching cases as follows. For the first case,

463 we calculate the probability of the base block mean sampled from the unmodified 5mer

464 Gaussian distribution, as well as the modified 5mer Gaussian distribution. The larger

465 probability is used as the match score in this case. For the second or third case, we treat it as

466 noise and use a fixed uniform distribution to calculate the match score.

468 In our alignment, another significant difference with the classical global alignment algorithm is

469 that one or multiple base blocks could be aligned with one 5mer. Given the base block means

470 $\boldsymbol{\mu} = (\mu_1, \mu_2, ..., \mu_i, ..., \mu_m)$ and 5mer list $\boldsymbol{s} = (s_1, s_2, ..., s_j, ..., s_n)$, we define $(m+1) \times (n+1)$ the score

471 matrix as M (Fig. 2C). The first row and column of M are reserved for indels "0.0" and "-",

472 which represent indels of the base block and 5mer, respectively. We denote the score function

473 by f. The recursion formula of the dynamic programming alignment algorithm is given by

$$M(i,j) = max \begin{cases} M(i-1, j-1) + f(\mu_i, s_j) \\ M(i, j-1) + f(0.0, s_j) \\ M(i-1, j) + f(\mu_i, "-") \\ M(i-1, j) + f(\mu_i, s_j) \end{cases}. \tag{5}$$

475 It can be seen that we can still align μ_i with s_j after we have aligned μ_{i-1} with s_j, which fulfills

476 the special consideration that one or multiple base blocks might be aligned with one 5mer.

There are two different types of alignment algorithms given the score matrix M: the full

alignment algorithm and the partial alignment algorithm (Fig. 2C). The full alignment algorithm

tries to align the full list of base block means with the full list of 5mer list, which is similar to the

classical global alignment algorithm. This is implemented by tracing back from the $(m+1, n+1)$

position of the score matrix. The partial alignment algorithm tries to align the full list of the base

blocks with the first part of the 5mer list. It differs from the full alignment algorithm in two

aspects: (1) no indel is allowed in both the base block means and the 5mer list, and (2) trace

back the maximum value of the last row of the score matrix M. A detailed description of the

full and partial alignment algorithm is provided in Supplementary Note 1.

The output of the alignment algorithm is the eventalign, which contains the pairing between

the base blocks and 5mer list of reference sequences for each read (Fig. 2C).

Modification estimation

After obtaining the eventalign results, we estimate the modification state of each motif using

the 5mer parameter table. If the 5mer is in the modification state, the probability of the base

block mean under the modified 5mer Gaussian distribution should be higher than that

calculated using unmodified 5mer parameters, and vice versa. Since one 5mer may be aligned

with multiple base blocks, we merge all the aligned base blocks and take the weighted mean

as the single base block mean aligned with the given 5mer, which provides us the modification

state of each site of a read. We then pool all reads mapped to the same genomic location on

the reference sequence to get the modification rate of the genomic location, which is the

proportion of reads in modification state. Detailed description of the modification state

estimation is provided in Supplementary Note 1.

GMM for 5mer parameter table re-estimation

To gain better alignment results and more accurate modification estimation, we use GMM to

fine-tune the 5mer parameter table iteratively. As shown in Fig. 2A, the row of the 5mer

parameter table are 5mers and the columns are the mean and std of the unmodified and
modified states. We denote a 5mer by s and its relevant parameters by $\mu_{s,un}$, $\delta_{s,un}$, $\mu_{s,mod}$,
$\delta_{s,mod}$.

Given the alignment results of all reads, we extract all base block means that are aligned to
the same 5mer s on different reads and across different genomic locations with high
modification rates. Next, we fit a two-component GMM to the collected base blocks
corresponding to 5mer s, with the first component mean fixed to $\mu_{s,un}$. From the GMM, we
have the updated $\delta_{s,un}$, $\omega_{s,un}$, $\mu_{s,mod}$, $\delta_{s,mod}$, and $\omega_{s,mod}$, where $\omega_{s,un}$, $\omega_{s,mod}$ are the weights
for unmodified and modified components. Then, we manually update the 5mer parameter table
based on some heuristics such that the modified 5mer distribution is significantly different from
that of unmodified 5mer distribution. Detailed description of the GMM re-estimation process is
provided in Supplementary Note 1.

The re-estimation of 5mer parameter table is only performed on the training data. We initialize
the 5mer parameter table using the 5mer parameter table provided by ONT. Every time after
we gain the updated 5mer parameter table, we run the SegPore workflow from the alignment
again. The process is repeated 3 to 5 times in general, after which the 5mer parameter table
is stabilized. After that, the 5mer parameter table is fixed. For testing data, we estimate the
RNA modification states using the fixed 5mer parameter table.

524 m6A benchmark

The HEK293T wild type (WT) samples were downloaded from ENA database under accession
number PRJEB40872, while the HCT116 samples were downloaded from ENA PRJEB44348.
The reference sequence (Homo_sapiens.GRCh38.cdna.ncrna_wtChrIs_modified.fa) were
downloaded from https://doi.org/10.5281/zenodo.4587661. The ground truth data were
obtained from Supplementary Data 1 of Pratanwanich, P.N. et al. (Pratanwanich et al. 2021).
Fast5 files of the test dataset (mESC WT samples, mESCs_Mettl3_WT_fast5.tar.gz) were

downloaded from NCBI Sequence Read Archive (SRA) database under accession number

SRP166020.

During training, the 5mer parameter table was initialized using ONT. Standard SegPore

workflow is performed on the training data (HEK293T WT samples), where the full alignment

algorithm is used. The 5mer parameter table estimation was iterated five times. During the

training, reads were first mapped to cDNA, then converted to genomic locations on the

reference genome using Ensembl GTF file (GRCh38, v9), after that the same 5mer at different

genomic locations were pooled together. We select 5mers with significant modifications if its

read coverage is greater than 1,500 and the distance between two components means in the

GMM is greater than 5. The modification parameters were specified for ten significant 5mers,

as illustrated in Supplementary Fig. 1A.

With the estimated 5mer parameter table from the training data, we ran SegPore workflow on

the test data. Transcript sequences of GENCODE release version M18 were used as the

reference sequence for mapping, where the GTF file

(gencode.vM18.chr_patch_hapl_scaff.annotation.gtf) downloaded from GENCODE was used

to convert transcript locations to genomic locations. Note that we do not estimate 5mer

parameter table for test data, and the modification states for each read are estimated only

once. Due to the difference between human and mouse, only six out of ten selected 5mers

have m6A annotations in the ground truth of the test data (Supplementary Fig. 1C). For a

genomic location to be considered as a m6A modification site, we require that it must

correspond to one of the six common 5mers and the read coverage must be greater than 20.

For SegPore, the modification rate of each genomic location was used to derive the ROC and

PR curves in the benchmark study.

In the SegPore+m6Anet analysis, we fine-tuned the m6Anet using the SegPore eventalign

results to demonstrate its improved performance on m6A identification. Based on the pre-

trained   m6Anet   network   (https://github.com/GoekeLab/m6anet,   model   version:

HCT116_RNA002), we fine-tuned it using SegPore eventalign results of HCT116 samples.

SegPore eventalign provides the pairing between each genomic location and its

corresponding raw signal segment, from which it generates the normalized mean μ_i, std σ_i,

dwell time l_i . For genomic location i , m6Anet extracts a feature vector $x_i =$

$\{\mu_{i-1}, \sigma_{i-1}, l_{i-1}, \mu_i, \sigma_i, l_i, \mu_{i+1}, \sigma_{i+1}, l_{i+1}\}$ to be used as the input of m6Anet. Feature vectors of

80% genomic locations were used as the training set and the rest 20% were used as the

validation set. We run 100 epochs to fine-tuning m6Anet and selected the model that performs

the best on the validation set.

The ground truth, performances of other methods (Tombo v1.5.1, Nanom6A v2.0, m6Anet

v1.0, and Epinano v1.2.0) of mESCs were obtained through personal communications with

Prof. Luo Guanzheng, who is the corresponding author of the referenced benchmark study

(Zhong et al. 2023).

Inosine identification experiments

Raw nanopore sequencing data of *in virto* transcription data (training data) and H9 human

embryonic stem cells (test data) were downloaded from NCBI Sequence Read Archive under

accession number SRP363295. The training data consists of eight pure-G samples

(Accessions: SRX18177003, SRX14536452, SRX14536451, SRX14536450, SRX14536449,

SRX14536448, SRX14536447, and SRX14536446), eight pure-I samples (Accessions:

SRX18176999,   SRX14535372,   SRX14535371,   SRX14535370,   SRX14535369,

SRX14535368, SRX14535367, and SRX14535366), and three reference sequences for

synthetic RNA can be download from Supplementary Table 5 of the original publication

(Nguyen et al. 2022). The test data consists of ten H9 WT embryo samples (Accessions:

SRX14436756,   SRX14436755,   SRX14436754,   SRX14436753,   SRX14436752,

SRX14448128, SRX14448125, SRX14448129, SRX14604385, and SRX14604391). The

reference sequence for the test data is the human GRCh37 cDNA sequences downloaded

from the Ensembl database.

Standard SegPore workflow was performed on the training data, where four iterations were

used to derive the 5mer parameter table. Considering that there is only one transcript per

sample in the IVT data, the partial alignment algorithm is used in the training. The designed

reference sequences of the IVT data contain 81 different 5mers in the form of XXGXX, where

X is A, C or U/T. We manually classify the 81 5mers into three patterns (Supplementary Fig.

2a), which contain 20, 23, 38 5mers, respectively. For Pattern 2, a two-component GMM is

fitted to the data with the unmodified component mean fixed. For Pattern 3, a single Gaussian

distribution is fitted to the data with the constraint that the std should not exceed 3.0. The final

5mer parameter table after training contains modification parameters for 61 5mers (Pattern 2

and 3).

The derived 5mer parameter table was then used to identify inosine from the test data (H9

data). Ensembl GTF file (GRCh37, v87) was used to convert transcript locations to genomic

locations. For a genomic location to be considered an inosine modification site, its read

coverage must be larger than 10. Due to the availability of data, we can only download the

ground truth on Chromosome 3 and 11 (test_H9_regression_allannotatedsites_0to1.RData)

for the test data from the code repository of the original publication (Nguyen et al. 2022), which

contains the modification rates of 4,934 genomic locations. From these genomic locations, we

selected sites with a modification rate greater than 0.1 as the positive control, and sites with a

modification rate equal to 0 as the negative control. As a result, 1,007 sites were retained from

the ground truth, consisting of 129 positive sites (37 unique 5mers) and 878 negative sites.

Out of the 37 unique 5mers in the positive control of the ground truth, there are 18 overlapping

5mers with the 61 selected 5mers (Pattern 2 and 3) in the training. The sites that match the

18 overlapping 5mers were kept, after that we retained sites with read coverage larger than

10, resulting in 37 positive sites and 241 negative sites. SegPore estimated modification rates

of these sites were extracted to generate Fig. 4C.

RNA structure estimation

The raw DRS data of pri-miR-17~92 is downloaded from NCBI under accession number

PRJNA634693, which contains an unmodified sample (*in vitro* transcription) and several

modified RNA samples treated using 5, 20, 50, 75, 100, 150, or 200 mM AcIm. The IVT sample

(unmodified RNA) and the 150mM AcIm sample (modified RNA) were used in this experiment.

Standard SegPore workflow is performed on both samples and partial alignment algorithm is

used. From the alignment results, we find a large proportion of the reads (~90%,

Supplementary Note 3) do not cover the whole reference sequence. Therefore, we analysis

the alignment end position distribution. For getting more accurate reactivity score in RNA

structure estimation, we fine-tuned the parameters for unmodified distribution and modified

distribution on each site of the reference sequence. Finally, the normalized reactivity score is

fed into the RNAfold (v2.4.13) (Vienna) web server to predict the RNA structure and R-chie

(Tsybulskyi, Mounir and Meyer 2020) is used for displaying base pairing (arc). More details

are provided in Supplementary Note 3.

Data Access

630 The data utilized in this study are obtained from publicly available repositories. Details

631 regarding the accession number and data processing can be found in Methods. The source

632 code is hosted on GitHub (https://github.com/guangzhaocs/SegPore).

Acknowledgements

We would like to thank Prof. Zhijie Tan from Wuhan University for a useful discussion about

the molecule dynamics of Nanopore sequencing, Dr. Dan Zhang from Sichuan University for

helpful tutorials about traditional Nanopore analysis workflows. We would like to thank

Research Council of Finland grants (NO. 335858, 358086) to GC and LC. GC and LC

acknowledge the computational resources provided by the Aalto Science-IT project. We also

thank Prof. Luo Guanzheng for sharing the m6A benchmark baseline results.

640 Author Contributions

641 GC developed the methods and performed the analyses. AV provided advice about statistical

642 modelling and manuscript writing. LC conceptualized and supervised the project. GC and LC

643 co-implemented the SegPore workflow, co-wrote the manuscript. All authors read and

644 approved the manuscript.

645 Competing Interest Statement

646 The authors declare no competing interests.

647 Supplementary Information

Supplementary Figure 1: m6A identification kmer motif statistics.

Supplementary Figure 2: Inosine identification kmer patterns.

Supplementary Note 1: SegPore workflow.

Supplementary Note 2: GPU-accelerated Hierarchical Hidden Markov Model parameter

inference.

Supplementary Note 3: SegPore for RNA structure estimation.

654 References

Agris PF, Narendran A, Sarachan K, Vare VYP, Eruysal E. 2017. The Importance of Being

Modified: The Role of RNA Modifications in Translational Fidelity. *Enzymes* **41**: 1-50.

Bellodi C, McMahon M, Contreras A, Juliano D, Kopmar N, Nakamura T, Maltby D,

Burlingame A, Savage SA, Shimamura A, Ruggero D. 2013. H/ACA small RNA

dysfunctions in disease reveal key roles for noncoding RNA modifications in

hematopoietic stem cell differentiation. *Cell Rep* **3**: 1493-1502.

Boccaletto P, Stefaniak F, Ray A, Cappannini A, Mukherjee S, Purta E, Kurkowska M,

Shirvanizadeh N, Destefanis E, Groza P et al. 2022. MODOMICS: a database of

RNA modification pathways. 2021 update. *Nucleic Acids Res* **50**: D231-D235.

Caldwell CC, Spies M. 2017. Helicase SPRNTing through the nanopore. *Proc Natl Acad Sci*

U S A **114**: 11809-11811.

Chen AY, Owens MC, Liu KF. 2023. Coordination of RNA modifications in the brain and

beyond. *Mol Psychiatry* **28**: 2737-2749.

Craig JM, Laszlo AH, Brinkerhoff H, Derrington IM, Noakes MT, Nova IC, Tickman BI,

Doering K, de Leeuw NF, Gundlach JH. 2017. Revealing dynamics of helicase

translocation on single-stranded DNA using high-resolution nanopore tweezers. *Proc*

Natl Acad Sci U S A **114**: 11932-11937.

Eisenberg E, Levanon EY. 2018. A-to-I RNA editing - immune protector and transcriptome

diversifier. *Nat Rev Genet* **19**: 473-490.

Gao Y, Liu X, Wu B, Wang H, Xi F, Kohnen MV, Reddy ASN, Gu L. 2021. Quantitative

profiling of N(6)-methyladenosine at single-base resolution in stem-differentiating

xylem of Populus trichocarpa using Nanopore direct RNA sequencing. *Genome Biol*

22: 22.

Jain M, Koren S, Miga KH, Quick J, Rand AC, Sasani TA, Tyson JR, Beggs AD, Dilthey AT,

Fiddes IT et al. 2018. Nanopore sequencing and assembly of a human genome with

ultra-long reads. *Nat Biotechnol* **36**: 338-345.

Koh CWQ, Goh YT, Goh WSS. 2019. Atlas of quantitative single-base-resolution N(6)-

methyl-adenine methylomes. *Nat Commun* **10**: 5636.

Kortel N, Ruckle C, Zhou Y, Busch A, Hoch-Kraft P, Sutandy FXR, Haase J, Pradhan M,

Musheev M, Ostareck D et al. 2021. Deep and accurate detection of m6A RNA

modifications using miCLIP2 and m6Aboost machine learning. *Nucleic Acids Res* **49**:

e92.

Lee H, Bao S, Qian Y, Geula S, Leslie J, Zhang C, Hanna JH, Ding L. 2019. Stage-specific

requirement for Mettl3-dependent m(6)A mRNA methylation during haematopoietic

stem cell differentiation. *Nat Cell Biol* **21**: 700-709.

Leger A, Amaral PP, Pandolfini L, Capitanchik C, Capraro F, Miano V, Migliori V, Toolan-

Kerr P, Sideri T, Enright AJ et al. 2021. RNA modifications detection by comparative

Nanopore direct RNA sequencing. *Nat Commun* **12**: 7198.

Li H. 2018. Minimap2: pairwise alignment for nucleotide sequences. *Bioinformatics* **34**: 3094-

3100.

Linder B, Grozhik AV, Olarerin-George AO, Meydan C, Mason CE, Jaffrey SR. 2015. Single-

nucleotide-resolution mapping of m6A and m6Am throughout the transcriptome. *Nat*

Methods **12**: 767-772.

Liu H, Begik O, Lucas MC, Ramirez JM, Mason CE, Wiener D, Schwartz S, Mattick JS,

Smith MA, Novoa EM. 2019. Accurate detection of m(6)A RNA modifications in

native RNA sequences. *Nat Commun* **10**: 4079.

Loman NJ, Quick J, Simpson JT. 2015. A complete bacterial genome assembled de novo

using only nanopore sequencing data. *Nat Methods* **12**: 733-735.

Lorenz DA, Sathe S, Einstein JM, Yeo GW. 2020. Direct RNA sequencing enables m(6)A

detection in endogenous transcript isoforms at base-specific resolution. *RNA* **26**: 19-

28.

Lorenz R, Bernhart SH, Honer Zu Siederdissen C, Tafer H, Flamm C, Stadler PF, Hofacker

IL. 2011. ViennaRNA Package 2.0. *Algorithms Mol Biol* **6**: 26.

Meyer KD, Saletore Y, Zumbo P, Elemento O, Mason CE, Jaffrey SR. 2012. Comprehensive

analysis of mRNA methylation reveals enrichment in 3' UTRs and near stop codons.

Cell **149**: 1635-1646.

Nance KD, Meier JL. 2021. Modifications in an Emergency: The Role of N1-

Methylpseudouridine in COVID-19 Vaccines. *ACS Cent Sci* **7**: 748-756.

Nguyen TA, Heng JWJ, Kaewsapsak P, Kok EPL, Stanojevic D, Liu H, Cardilla A, Praditya

A, Yi Z, Lin M et al. 2022. Direct identification of A-to-I editing sites with nanopore

native RNA sequencing. *Nat Methods* **19**: 833-844.

Nishikura K. 2016. A-to-I editing of coding and non-coding RNAs by ADARs. *Nat Rev Mol*

Cell Biol **17**: 83-96.

Ohira T, Suzuki T. 2024. Transfer RNA modifications and cellular thermotolerance. *Mol Cell*

84: 94-106.

Parker MT, Knop K, Sherwood AV, Schurch NJ, Mackinnon K, Gould PD, Hall AJ, Barton

GJ, Simpson GG. 2020. Nanopore direct RNA sequencing maps the complexity of

Arabidopsis mRNA processing and m(6)A modification. *Elife* **9**.

Pratanwanich PN, Yao F, Chen Y, Koh CWQ, Wan YK, Hendra C, Poon P, Goh YT, Yap

PML, Chooi JY et al. 2021. Identification of differential RNA modifications from

nanopore direct RNA sequencing with xPore. *Nat Biotechnol* **39**: 1394-1402.

Price AM, Hayer KE, McIntyre ABR, Gokhale NS, Abebe JS, Della Fera AN, Mason CE,

Horner SM, Wilson AC, Depledge DP, Weitzman MD. 2020. Direct RNA sequencing

reveals m(6)A modifications on adenovirus RNA are necessary for efficient splicing.

Nat Commun **11**: 6016.

Prieto M, Folci A, Martin S. 2020. Post-translational modifications of the Fragile X Mental

Retardation Protein in neuronal function and dysfunction. *Mol Psychiatry* **25**: 1688-

1703.

Quin J, Sedmik J, Vukic D, Khan A, Keegan LP, O'Connell MA. 2021. ADAR RNA

Modifications, the Epitranscriptome and Innate Immunity. *Trends Biochem Sci* **46**:

758-771.

Siegfried NA, Busan S, Rice GM, Nelson JA, Weeks KM. 2014. RNA motif discovery by

SHAPE and mutational profiling (SHAPE-MaP). *Nat Methods* **11**: 959-965.

Simpson JT, Workman RE, Zuzarte PC, David M, Dursi LJ, Timp W. 2017. Detecting DNA

cytosine methylation using nanopore sequencing. *Nat Methods* **14**: 407-410.

Slotkin W, Nishikura K. 2013. Adenosine-to-inosine RNA editing and human disease.
Genome Med **5**: 105.
Stephenson W, Razaghi R, Busan S, Weeks KM, Timp W, Smibert P. 2022. Direct detection
of RNA modifications and structure using single-molecule nanopore sequencing. *Cell*
Genom **2**.
Stoiber M, Quick J, Egan R, Eun Lee J, Celniker S, Neely RK, Loman N, Pennacchio LA,
Brown J. 2017. De novo Identification of DNA Modifications Enabled by Genome-
Guided Nanopore Signal Processing. *biorxiv* doi:10.1101/094672.
Tsybulskyi V, Mounir M, Meyer IM. 2020. R-chie: a web server and R package for visualizing
cis and trans RNA–RNA, RNA–DNA and DNA–DNA interactions. *Nucleic Acids*
Research **48**: e105-e105.
Yankova E, Aspris D, Tzelepis K. 2021. The N6-methyladenosine RNA modification in acute
myeloid leukemia. *Curr Opin Hematol* **28**: 80-85.
Zhong ZD, Xie YY, Chen HX, Lan YL, Liu XH, Ji JY, Wu F, Jin L, Chen J, Mak DW et al.
2023. Systematic comparison of tools used for m(6)A mapping from nanopore direct
RNA sequencing. *Nat Commun* **14**: 1906.
Zimna M, Dolata J, Szweykowska-Kulinska Z, Jarmolowski A. 2023. The expanding role of
RNA modifications in plant RNA polymerase II transcripts: highlights and
perspectives. *J Exp Bot* **74**: 3975-3986.
759