Logic-based modeling of biological networks with Netflux

Alexander P. Clark[1], Mukti Chowkwale[1], Alexander Paap[1], Stephen Dang[1], Jeffrey J.

Saucerman[1,2*]

[1]Department of Biomedical Engineering, University of Virginia, Charlottesville, VA, United States of

America

[2]Robert M. Berne Cardiovascular Research Center, University of Virginia, Charlottesville, VA, United

States of America

Word Count: 3674

*Correspondence:

Jeffrey J. Saucerman, PhD

Dept. of Biomedical Engineering

University of Virginia

Charlottesville, VA 22903

Email: jsaucerman@virginia.edu

Abstract

Molecular signaling networks drive a diverse range of cellular decisions, including whether to proliferate, how and when to die, and many processes in between. Such networks often connect hundreds of proteins, genes, and processes. Understanding these complex networks is aided by computational modeling, but these tools require extensive programming knowledge. In this article, we describe a user-friendly, programming-free network simulation tool called Netflux (https://github.com/saucermanlab/Netflux). Over the last decade, Netflux has been used to construct numerous predictive network models that have deepened our understanding of how complex biological networks make cell decisions. Here, we provide a Netflux tutorial that covers how to construct a network model and then simulate network responses to perturbations. Upon completion of this tutorial, you will be able to construct your own model in Netflux and simulate how perturbations to proteins and genes propagate through signaling and gene-regulatory networks.

1 Introduction

Biological signaling networks are responsible for a variety of cellular decisions, including growth, proliferation, disease progression, and death. These varied behaviors arise from interactions between hundreds of proteins, genes, and cellular processes. This complexity makes it difficult to understand mechanisms of cellular decisions through reductionist experimental approaches alone. Computational modeling addresses this challenge by integrating known interactions between system components into a framework; one can then use computer simulations to explore biological processes *in silico*, providing a means to rapidly generate testable predictions.

Understanding the signaling involved in biological processes can take decades of rigorous, reductionist cause-and-effect research. For example, a connection between high blood pressure and cardiac hypertrophy (often a precursor to heart failure) has been established for years, but until recently[1] (**Figure 1B**), the complex mechano-signaling pathways that drive this remodeling had not been integrated at a systems level. Over decades, individual studies have connected components (e.g., stretch activating integrin) and explained mechano-signaling pathways (e.g., a multi-protein pathway whereby stretch activates Ras) in cardiomyocytes. Collectively, these studies demonstrate the complex role of mechano-signaling in cardiac hypertrophy, but they do not provide a single mechanistic picture of stretch-induced hypertrophy.

Network models offer a means to integrate the high-quality reductionist building block studies mentioned above into a framework to study the complexity of biological signaling processes (**Figure 1A**). Building block studies identify the nature of interactions, like whether stretch increases or decreases the expression of calcium channels – it increases them. By mining many of these reductionist studies, one can create a network of interactions between species and construct an integrated picture of how individual interactions can lead to an emergent phenotype. For example, **Figure 1B** shows a mechano-signaling network for heart cells that was manually curated using data from over 170 studies [1]. This network includes mechanical Stretch as an input that stimulates several pathways consisting of receptors (AT1R, angiotensin type 1

receptor), ion channels (LTCC, L-type calcium channel), transcription factors (GATA4),

sarcomeric proteins (bMHC, beta myosin heavy chain), and ions (Ca, Calcium). The

interactions can be either activating or inhibiting. For example, the Stretch input signal

increases (denoted as solid arrow) the expression of L-type calcium channels. In

contrast protein kinase G 1 (PKG1) inhibits the expression of L-type calcium channels.

The 125 activating or inhibitory interactions within this network give rise to emergent

phenotypic characteristics, like Cell Area.

Coding these individual interactions into a cohesive network and then simulating genetic

or pharmacologic perturbations allows us to uncover insights that are not apparent

when studying components in isolation. Network modeling can prioritize pathways that

work together or in tension to result in emergent phenomena, such as changes in Cell

Area. By simulating these networks, researchers can explore how different pathways

interact, identify key regulatory nodes, and predict system behavior under various

conditions. For example, through systematic perturbation to the mechano-signaling

network in [1], the authors identify mechanisms by which increased Stretch can

increase Cell Area, a maladaptive change in heart cell physiology. Knowing the

mechanism, they show how a recently approved combination heart failure drug called

Entresto attenuates heart failure progression through distinct, yet synergistic, mechano-

signaling pathways. This systems approach demonstrates how modeling and simulation

can harness the complexity of molecular networks to identify biological mechanisms of

disease progression and explain novel therapeutic approaches.

Despite decades of single-gene cause-effect research, the integration of these findings

into comprehensive models has been hindered in part by the availability of user-friendly

network modeling tools. As the amount of biological data continues to grow, and new

methods/databases make it easy to find connections between molecules, there is a

need for tools that facilitate the development and simulation of biological networks. In

this manuscript, we provide a detailed introduction to Netflux, an intuitive tool for

construction and simulation of biological network models that does not require

programming.

Under the hood, Netflux utilizes a modeling approach termed logic-based differential

equations, which is based on normalized Hill activation/inhibition functions [2]. Such an

approach benefits from providing continuous variables to model gene and protein

concentration, in contrast to traditional Boolean network modeling approaches with

discrete variables. Netflux abstracts these technical considerations and allows users to

construct networks and run simulations without any coding. If you're interested in

learning about the technical implementation of Netflux, more details on the underlying

computational approach of logic-based differential equations can be found in Kraeutler

et al. (2010, [2]). The tool has been used by scientists of various levels and technical

proficiency to develop models of numerous biological networks that have led to

meaningful insights and advances in our understanding of human disease [3–7]. Netflux

has also been used as an educational tool at the undergraduate and high school levels

to introduce the concepts of network biology.

By the end of this article, you will be able to use Netflux to create a biological network

model and then predict how the network responds to perturbations in environmental

conditions, proteins, and genes. We will also discuss advanced Netflux topics and

provide published examples of how models built with Netflux have provided meaningful

insights into biological processes.

Figure 1: A) Individual reductionist studies provide connections between network components. These individual connections can be integrated into a network model. Subsequent perturbation studies can make novel predictions of previously untested genetic/protein perturbations – these come with a mechanistic explanation for the perturbation outcome. **B)** Network model from Tan et al. (2017) shows how complex networks can be constructed through manual curation. Subsequent simulations in this study provide novel insights into a biological process (in this case, cardiomyocyte mechano-signaling).

2 Getting started with Netflux

Installation

Download Netflux from GitHub (https://github.com/saucermanlab/Netflux). It can either

be: option 1) installed as a desktop application, or option 2) opened and run directly

from MATLAB.

Loading a Model

<u>Open</u> the Netflux graphical user interface (GUI, **Figure** 2) by either clicking on the

installed application (option 1) or running the "Netflux.m" file within MATLAB (option 2).

Figure 2: Netflux graphical user interface**.** The Netflux GUI includes four sections
(left) and a plot (right) of species activity over time. The sections are: 1) *Simulation*
includes information about the simulation time, and species that will be plotted in the
panel on the right; 2) *Status* includes information on the state of the loaded model,
and is important to check after loading models and running simulations; 3) *Species*
Parameters includes information about the species initial value (yinit), maximum
value (ymax), and how quickly it can change (tau); 4) *Reaction Parameters* includes
information about a reaction's strength (weight), the steepness of activation (n), and
the half maximal effective concentration (EC50), which are collectively responsible for
producing dynamic changes in species.

Loading the ExampleNet Model

Netflux includes a repository of published network models in the "models" subfolder. We

will first focus on the exampleNet model [2].

<u>Open</u> the "exampleNet.xlsx" file by selecting Open from the File tab within the Netflux

GUI, and then navigating to models/exampleNet.xlsx.

In Netflux, we refer to network genes or proteins as *species*, and the activating or

inhibiting interaction between species as a *reaction*. The ExampleNet model (**Figure**

3A) consists of five species (A, B, C, D, and E) and six reactions, including two input

species (A and B) that feed into the network and can be turned on or off by turning on or

off their respective input reactions.

• **(Input) Reaction 1:** Environmental stimulus that activates Species A.

• **(Input) Reaction 2:** Environmental stimulus that activates Species B.

• **Reaction 3:** Species A activates Species C.

• **Reaction 4**: Species B activates Species D.

• **Reaction 5**: Species A activates, and species B inhibits species E.

• **Reaction 6:** Species E activates species C.

Once loaded, all the network species are displayed in the "Species to plot" box of the

Netflux GUI. Under ***Species Parameters***, <u>verify</u> that the values for time constants

(tau=1), initial values (yinit=0), and maximum values (ymax=1) are the same for each

species. Additionally, under ***Reaction Parameters*** (bottom right of the GUI), <u>verify</u> that

the reaction weight (w=0 or 1), Hill coefficient (n=1.4), and half maximal effective

concentration (EC50=0.5) are preset for each reaction.

Simulating ExampleNet in Response to Environmental Stimuli

The model is ready to be run.

First, <u>select</u> all the species in the "Species to plot" box – this can be done by selecting

the A, holding the "Shift" key, and then selecting E (**Figure** 3B). Follow the steps below

and refer to the GUI in **Figure** 3B to run the model and plot its results:

1) <u>Press</u> the "Simulate!" button. The axes on the right side of the GUI should

change, but none of the species should have an Activity above 0.

2) Click the "Reaction list" to see the reactions that are defined in ExampleNet.
Change the reaction weight for "r1: => A" to 1, then click "Simulate!" again. Now,
between timepoints 10 and 20, species A, C, and E should all increase to an
Activity level of 1 (**Figure** 3C).
3) Simulate washout of A by changing the "r1: => A" reaction weight back to 0, and
then clicking "Simulate!".
4) Simulate stimulation with B by changing the "r2: => B" reaction weight to 1, and
then clicking "Simulate!".
5) Simulate washout of B by changing the "r2: => B" reaction weight back to 0, and
then clicking "Simulate!".
6) Finally, simulate simultaneous stimulation with both A and B by changing their
input reaction weights to 1, and then clicking "Simulate!".
177
178   Execution of these six steps will result in the plot displayed in **Figure** 3D. Before starting
179   a new simulation, it is important to select "Reset Parameters" and "Reset Simulation".

Figure 3: ExampleNet schematic (**A**) and GUI representation (**B**). (**C**) plot of species after Simulations 1 and 2. (**D**) Plot of species after all simulations.

3   Build and simulate a new network model

This section will cover how to build a new model from scratch. The model used in this

section is part of a recently elucidated gene regulatory network that is essential for

proper heart formation [8], visualized in **Figure** 4A. In addition to model construction, we

will simulate the knockout of a gene within this network and compare the results to

experimental data linking dysregulation of this network to congenital heart defects.

Creating the CardiacDevNet Model

First, <u>make a copy</u> of the "exampleNet.xlsx" model in Netflux/models/, and rename it

"cardiacDevNet.xlsx". Note, when building a new model, it is always advised to copy

and then edit a previously developed model (e.g., "exampleNet.xlsx").

Adding the Model Species

This model includes five transcription factor species, with the following known actions

(within this biological context):

- GATA6 – shown to bind an enhancer of NKX2-5 that is accessible in a special
  subset of cardiac progenitor cells found in the anterior second heart field.
- NKX2-5 – well-characterized protein that regulates several genes essential for
  proper heart formation.
- TBX1 – well-characterized protein that regulates several genes essential for
  proper heart formation.
- ISL1 – plays a role in forming the cardiac progenitor pool, but its repression is
  important for cells to continue differentiation towards adult cardiomyocytes.
- PITX2 – known to regulate formation of a region of the heart called the outflow
  tract.

<u>Open</u> "cardiacDevNet.xlsx" in excel or Google Sheets and <u>navigate</u> to the "species" tab.

<u>Edit</u> the ID, name, and Yinit fields to match **Figure** 4A, B. Notice, the Yinit value for ISL1

should start at 1. This is because the subset of specialized cardiac progenitor cells (the

anterior second heart field cells) starts with high levels of ISL1.

Adding the Model Reactions

This model has the following seven reactions (**Figure** 4A, C), including one input

reaction:

• **(Input) Reaction 1:** GATA6 is expressed. This is modeling the expression of
GATA6 that is present within this specialized subset of cardiac progenitor cells.

• **Reaction 2:** GATA6 activates NKX2-5.

• **Reaction 3**: GATA6 activates TBX1.

• **Reaction 4**: NKX2-5 activates TBX1.

• **Reaction 5:** TBX1 activates PITX2.

• **Reaction 6:** NKX2-5 activates PITX2.

• **Reaction 7:** NKX2-5 inhibits the expression of ISL1. In Excel, an exclamation
mark is used to denote that NKX2-5 inhibits ISL1 (**Figure** 4C, ID=r7).

Navigate to the "reactions" tab of "cardiacDevNet.xlsx". Edit the module, ID, Rule, and

Weight to match **Figure** 4C. For the "r1" reaction rule ("=> GATA6"), include a single

quote before typing the equals character (=) to ensure excel properly interprets the

coded interaction.

Figure 4: Model of a cardiac development gene regulatory network. (**A**) CardiacDevNet
schematic. (**B**) Excel sheets for the CardiacDevNet Species and (**C**) Reaction
information. Notice, the ISL1 Yinit value starts at 1 because it is inhibited by NKX25,

which has a Yinit of 0 (**B**, red box)

Simulating Normal Development with CardiacDevNet

Save "cardiacDevNet.xlsx" in excel or export it from Google Sheets as a .xlsx file. Next,

open Netflux by either clicking on the installed application or running the "Netflux.m" file

within MATLAB and then open "cardiacDevNet.xlsx" (see Section 2 for details).

The following steps cover how to run a simulation of the normal cardiac development:

1. Set the simulation time to 2. This step improves visualization of results in this

simulation. It is not always needed.

2. Select all species to plot. This is done by clicking on GATA6, holding the "Shift"

key, and then selecting PITX2.

3. Select the "Simulate!" button. This should change the axes, but there should be

no change in species Activity.

4. Change the simulation time to 8.

5. Select "r1: => GATA6" from the "Reaction list" dropdown and change the weight

to 1.

6. Select the "Simulate!" button. The results should match the solid lines plotted in

Figure 5B.

This simulation shows that NKX2-5, TBX1, and PITX2 increase while ISL1 decreases in

response to an increase in GATA6 (**Figure** 5B, solid lines). These gene expression

dynamics are important for anterior second heart field cells to progress towards mature

outflow tract cardiomyocytes.

Simulating a Gene Knockout withCardiacDevNet

In [8], authors reduce the expression of NKX2-5 – here, we simulate this as a knockout

of the NKX2-5 gene. The next steps discuss how to conduct an *in silico* gene knockout

study using the model (results displayed in **Figure** 5C):

1. Select "Reset Parameters" and "Reset Simulation".

2. <u>Select</u> "NKX25" from the "Species List" dropdown and change the ymax to 0. This change simulates the knockout of NKX2-5.

3. <u>Set</u> the Simulation time to 2.

4. <u>Select</u> the "Simulate!" button.

5. <u>Select</u> "r1: => GATA6" from the "Reaction list" dropdown and change the weight to 1.

6. <u>Set</u> the Simulation time to 8.

7. <u>Select</u> the "Simulate!" button.

This simulation represents the conditions under which NKX2-5 is knocked out – this was done by removing NKX2-5 from the network (Figure **5**). Taken together, the results of the baseline and perturbation simulations predict the following effects of NKX2-5 knockout (**Figure** 5D), which largely agrees with the experiments in [8].

1. NKX2-5 is not expressed. This should be interpreted as a reduction in NKX2-5 expression compared to wildtype. In [8], while still present, NKX2-5 expression is significantly reduced by the removal of an enhancer region that, when bound by the GATA6 transcription factor, increases NKX2-5 expression.

2. ISL1 expression is not suppressed. This again agrees with the significant increase in ISL1 observed when NKX2-5 expression is reduced.

3. There is a lag in TBX1 and PITX2 expression. This can be interpreted as a reduction in expression, in agreement with [8], where TBX1 and PITX2 expression was reduced due to a reduction in NKX2-5.

Figure 5: (A) CardiacDevNet NKX2-5 knockout schematic. **(B),** CardiacDevNet simulation results at baseline. **(C)** CardiacDevNet simulation results after knockout of NKX2-5. **(D)** Change in simulation results at baseline (solid lines) and after NKX2-5 knockout (dashed lines) for the transcription factors: NKX2-5, TBX1, ISL1, and PITX2.

4 Advanced methods and usage

Our simulations with CardiacDevNet illustrate the ease of developing a network model that accurately predicts the outcomes of real-world experiments. While small models such as CardiacDevNet are useful, Netflux has also been used extensively to construct much larger networks, with tens to 100s of proteins, genes, and reactions. Some such networks include: signaling networks for cardiomyocyte hypertrophy [3,9] and apoptosis [4], cardiac fibroblasts [6], macrophages [10], brain endothelial cells [7], mechano-signaling [1], virtual drug screening [11], cardiac differentiation [12], and smooth muscle cells [5]. As networks increase in size and complexity, there are a few additional considerations to be made.

Network Visualization: Netflux provides a tool to export networks in a format that can be loaded into Cytoscape [13], a user-friendly software for network visualization. For example, Cytoscape was used to produce the visualizations in **Figures** 2-4.

Citation Tracking: The Netflux-formatted .xlsx sheets include several columns within the "species" and "reactions" tabs that can be used to keep track of references and metadata. This becomes increasingly important as models grow large and incorporate insights from numerous independent studies.

Model Validation: As noted above, novel network models often draw on many different independent, biologically targeted studies to define the network structure – this provides confidence in model definition. However, experimental validation is critical to build confidence in model predictions. Initial experimental validation is often performed using *in vitro* or *in vivo* perturbation experiments from the literature that were not used to develop the model. Subsequently, the model can be used to design novel experiments that test model predictions under previously untested conditions.

Model Exporting: Netflux also provides functionality for exporting models to MATLAB or

Python, making it possible to run more sophisticated analyses and conduct large-scale,

systematic perturbation studies.

5 Conclusion

Netflux is an accessible tool for constructing and simulating models of biological

networks, requiring no programming experience. In this article, we covered the core

features of Netflux, including model construction, simulation, perturbation, and were

able to produce *in silico* results in agreement with experimental data. While the models

used in this article are small compared to networks from many published studies, the

concepts remain the same. This article (along with information in the GitHub repository)

provides all the information needed to construct your own model and simulate real

experiments. As you embark on building network models, we encourage you to

rigorously validate your model throughout construction. Well-validated models

developed in Netflux can provide both conceptual understanding of biological networks

and specific mechanistic predictions of how your network may respond to new

experimental perturbations.

Acknowledgements

We thank the members of the Saucerman lab for their feedback and contributions to

Netflux, with special thanks to Taylor Eggertsen and Bryce Murillo for their feedback on

this manuscript. Research reported in this publication was supported by the National

Heart, Lung and Blood Institute of the National Institutes of Health under Award Number

T32 HL007284.

References

1. Tan PM, Buchholz KS, Omens JH, McCulloch AD, Saucerman JJ. Predictive model identifies key network regulators of cardiomyocyte mechano-signaling. PLoS Comput Biol. 2017;13: e1005854. doi:10.1371/journal.pcbi.1005854

2. Kraeutler MJ, Soltis AR, Saucerman JJ. Modeling cardiac β-adrenergic signaling with normalized-Hill differential equations: comparison with a biochemical model. BMC Syst Biol. 2010;4: 157. doi:10.1186/1752-0509-4-157

3. Khalilimeybodi A, Paap AM, Christiansen SLM, Saucerman JJ. Context-specific network modeling identifies new crosstalk in β-adrenergic cardiac hypertrophy. PLoS Comput Biol. 2020;16: e1008490. doi:10.1371/journal.pcbi.1008490

4. Grabowska ME, Chun B, Moya R, Saucerman JJ. Computational model of cardiomyocyte apoptosis identifies mechanisms of tyrosine kinase inhibitor-induced cardiotoxicity. J Mol Cell Cardiol. 2021;155: 66–77. doi:10.1016/j.yjmcc.2021.02.014

5. Estrada AC, Irons L, Rego BV, Li G, Tellides G, Humphrey JD. Roles of mTOR in thoracic aortopathy understood by complex intracellular signaling interactions. PLoS Comput Biol. 2021;17: e1009683. doi:10.1371/journal.pcbi.1009683

6. Zeigler AC, Richardson WJ, Holmes JW, Saucerman JJ. A computational model of cardiac fibroblast signaling predicts context-dependent drivers of myofibroblast differentiation. J Mol Cell Cardiol. 2016;94: 72–81. doi:10.1016/j.yjmcc.2016.03.008

7. Gorick CM, Saucerman JJ, Price RJ. Computational model of brain endothelial cell signaling pathways predicts therapeutic targets for cerebral pathologies. J Mol Cell Cardiol. 2022;164: 17–28. doi:10.1016/j.yjmcc.2021.11.005

8. Yamaguchi N, Chang EW, Lin Z, Shekhar A, Bu L, Khodadadi-Jamayran A, et al. An Anterior Second Heart Field Enhancer Regulates the Gene Regulatory Network of the Cardiac Outflow Tract. Circulation. 2023;148: 1705–1722. doi:10.1161/CIRCULATIONAHA.123.065700

9. Ryall KA, Holland DO, Delaney KA, Kraeutler MJ, Parker AJ, Saucerman JJ. Network reconstruction and systems analysis of cardiac myocyte hypertrophy signaling. J Biol Chem. 2012;287: 42259–42268. doi:10.1074/jbc.M112.382937

10. Liu X, Zhang J, Zeigler AC, Nelson AR, Lindsey ML, Saucerman JJ. Network Analysis Reveals a Distinct Axis of Macrophage Activation in Response to Conflicting Inflammatory Cues. J Immunol. 2021;206: 883–891. doi:10.4049/jimmunol.1901444

11. Zeigler AC, Nelson AR, Chandrabhatla AS, Brazhkina O, Holmes JW, Saucerman JJ. Computational model predicts paracrine and intracellular drivers of fibroblast

phenotype after myocardial infarction. Matrix Biol. 2020;91–92: 136–151.
doi:10.1016/j.matbio.2020.03.007

12. Hota SK, Rao KS, Blair AP, Khalilimeybodi A, Hu KM, Thomas R, et al. Brahma
safeguards canalization of cardiac mesoderm differentiation. Nature. 2022;602:
129–134. doi:10.1038/s41586-021-04336-y

13. Shannon P, Markiel A, Ozier O, Baliga NS, Wang JT, Ramage D, et al. Cytoscape:
A Software Environment for Integrated Models of Biomolecular Interaction
Networks. Genome Res. 2003;13: 2498–2504. doi:10.1101/gr.1239303

390