Eliminating the Missing Cone Challenge through Innovative Approaches

Authors

Cody Gillman[1,2], Guanhong Bu[1], Emma Danelius[1,3], Johan Hattne[1,3], Brent Nannenga[4,5], Tamir
Gonen[1,2,3,6]

Affiliations

[1] Department of Biological Chemistry, University of California, Los Angeles, CA, USA.

[2] Molecular Biology Institute, University of California, Los Angeles, Los Angeles, CA 90095, USA.

[3] Howard Hughes Medical Institute, University of California, Los Angeles CA, USA.

[4]Chemical Engineering, School for Engineering of Matter, Transport and Energy, Arizona State University,
Tempe, AZ, USA.

[5]Center for Applied Structural Discovery, Biodesign Institute, Arizona State University, Tempe, AZ, USA.
brent.nannenga@asu.edu.

[6] Department of Physiology, University of California, Los Angeles, CA, USA.

* To whom correspondence should be sent T.G. tgonen@g.ucla.edu

Keyword:

Microcrystal electron diffraction, MicroED, Cryo-EM, FIB milling, cryogenic freezing, plasma FIB/SEM,
pFIB, suspended drop crystallization, missing cone

ABSTRACT

Microcrystal electron diffraction (MicroED) has emerged as a powerful technique for unraveling molecular structures from microcrystals too small for X-ray diffraction. However, a significant hurdle arises with plate-like crystals that consistently orient themselves flat on the electron microscopy grid. If, as is typically the case, the normal of the plate correlates with the axes of the crystal lattice, the crystal orientations accessible for measurement are restricted because the grid cannot be arbitrarily rotated. This limits the information that can be acquired, resulting in a missing cone of information. We recently introduced a novel crystallization strategy called suspended drop crystallization and proposed that this method could effectively address the challenge of preferred crystal orientation. Here we demonstrate the success of the suspended drop crystallization approach in eliminating the missing cone in two samples that crystallize as thin plates: bovine liver catalase and the COVID-19 main protease (Mpro). This innovative solution proves indispensable for crystals exhibiting preferred orientations, unlocking new possibilities for structure determination by MicroED.

1. Introduction

Microcrystal electron diffraction (MicroED) is a cryogenic electron microscopy (cryo-EM) method in which vanishingly small crystals are used for structure determination by electron diffraction (Shi *et al.*, 2013). In MicroED, microcrystalline samples are prepared on cryo-EM grids and diffraction data are collected as a movie on a fast camera in a transmission electron microscope (TEM) while the sample is continuously rotated (Nannenga, Shi, Leslie *et al.*, 2014). This setup allows the data to be processed using standard crystallographic software. The use of micro- and nanosized crystals provides new opportunities for determining previously unattainable structures, and MicroED has been applied to small molecules, natural products, materials, soluble- and membrane proteins, and is gaining popularity for various applications (Bruhn *et al.*, 2021; Mu *et al.*, 2021). For highly symmetric crystals, MicroED routinely yields complete data from single crystals, even for proteins as in the case for proteinase K (Martynowycz *et al.*, 2023) and the adenosine A2a receptor (Martynowycz *et al.*, 2023).

The experimental design of the sample stage in relation to the incoming electrons inherently limits the rotation range that can be used for data collection. At high tilt angles, the electron path through the sample is obstructed by grid bars or other crystals. Moreover, the grid holder itself blocks the electron beam at angles above ~70° so the maximum rotation range is ~140° not the ideal 180°. To address this challenge, numerous datasets must be collected, processed, and screened for merging statistics, aiming at completing reciprocal space (Griner *et al.*, 2019; Gallagher-Jones *et al.*, 2018 Danelius *et al.*, 2023). Some examples include triclinic lysozyme, where data from 16 crystals were merged into a 88% complete dataset (Clabbers

et al., 2022) and the human G-protein coupled receptor vasopressin, also crystallized in P1, where 14
datasets had to be merged to yield 75% completeness (Shiriaeva *et al.*, 2023).

However, certain crystal morphologies pose specific challenges: when the crystals are flat and the
orientation of the crystallographic axes follows the orientation of the plane, the crystal lattice will assume
a preferred orientation because plate-like crystals tend to lie flat on the surface of the sample grid. In
combination with the limited rotation range of the stage, this renders a systematic cone of reciprocal space
inaccessible for data collection, irrespective of the number of datasets merged and the symmetry of the
crystal (Glaeser & Downing, 1993; Stahlberg *et al.*, 2015). This is the case for all examples of 2D crystals
since they can only adopt a single orientation on the EM grid. For such samples, the maximum achievable
completeness is ~86% even if the stage is rotated through the maximum possible range (Glaeser &
Downing, 1993). Thus, the missing cone creates a substantial bottleneck in structure solution for crystals
that adopt a preferred orientation. Missing wedges in reciprocal space result in artifacts in the density, such
as elongated and/or missing or irrecoverable disjoint volumes (Stahlberg *et al.,* 2015). Although common
for micro- and nanosized crystals, this challenge is not unique to MicroED; but is well-known in
transmission electron microscopy. For example, it manifests in cryotomography (Barth *et al.*, 1988), where
whole cells can align to the support grids. It should be noted that the incomplete crystal lattice sampling
due to the missing cone can be eliminated if data from multiple crystals that are randomly oriented on the
grid are combined.

Recently, we reported a new method for crystal growth called suspended drop crystallization
(Gillman *et al.*, 2023). With this approach crystals grow in suspension directly on a grid without any support
film layered over the grid bars. Before data collection, the crystal and the surrounding material is FIB-
milled to a thickness amenable to MicroED. Because no grid support film is present, we postulated that
preferential orientation of crystals would be greatly reduced and that this approach could therefore eliminate
the missing cone problem. Here, we demonstrate this by collecting complete datasets from two samples
that are known for preferred orientation, namely bovine liver catalase, and the COVID-19 main protease
(Mpro).

2. Methods and Materials

2.1.   Protein expression and purification of Mpro

The gene encoding the full-length SARS-COV-2 Mpro was designed into the pGEX-6P-1 vector.
The construct was fused with an N-terminal self-cleaving GST tag and a C-terminal His affinity tag
downstream of a Precision protease cleavage site. *E. coli* strain Rosetta2 (DE3) was transformed with the
expression plasmid for protein expression. An overnight culture was grown in terrific broth at 37 ˚C and

used for inoculating 1 L of culture, which was incubated at 37 ˚C and 225 rpm. Protein expression was

induced by 0.5 mM isopropyl β-d-1-thiogalactopyranoside (IPTG) when the OD_{600} reached 0.7. Expression

was allowed for 16 h at 18 ˚C. The cell pellet was harvested at 8,000 g and kept at -20 ˚C until use. The

frozen cell pellet was thawed at 4 ˚C in lysis buffer (50 mM HEPES-NaOH pH 7.5, 2 mM DTT, 2 mM

EDTA, 2 mM EGTA, 0.1 mg/mL lysozyme and 0.1 mg/mL DNase I). Cells were lysed by sonication at

70% amplitude for 5 min. The cell debris and unbroken cells were removed by centrifuging at 12,000 g and

4 ˚C. The supernatant was directly loaded into a gravity column filled with 1 mL TALON resin (TaKaRa)

pre-equilibrated with the binding buffer (20 mM HEPES-NaOH pH 7.5, 100 mM NaCl and 1 mM DTT).

The column was washed with 25 mL wash buffer (20 mM HEPES-NaOH pH 7.5, 100 mM NaCl, 1 mM

DTT and 10 mM imidazole), then washed with 10 mL Precission protease cleavage buffer (50 mM Tris-

HCl pH 8.2, 150 mM NaCl and 1 mM DTT). Approximately 0.2 mg Precission protease in 3 mL cleavage

buffer was directly added into the TALON resin slurry. The resin slurry was incubated at 4 ˚C for over 16

h with gentle shaking. The tag-cleaved Mpro was collected in fractions while flowing off the resin. The

purified protein was concentrated to 0.6 mL using a 10 kD cut-off Amicon Ultra centrifugal filter

(Millipore). The sample was then loaded into a Superdex 200 Increase 10/300 GL column (Cytiva) pre-

equilibrated with the SEC buffer (20 mM Tris pH 7.8, 100 mM NaCl, 1 mM DTT and 1 mM EDTA). The

collected Mpro fractions were pooled, concentrated using an Amicon Ultra centrifugal filter with 10 kD

cut-off (Millipore), and stored at -80 ˚C until use.

2.2.　Crystallization assays

Catalase was crystallized using procedures based on previously reported methods (Nannenga et al.,

2014). First, a crystalline suspension of catalase from bovine liver (C100; Sigma-Aldrich) was centrifuged

to pellet the crude catalase crystals. The supernatant was decanted and the pelleted crystals were washed in

water and centrifuged again to recollect the catalase crystals. The supernatant was decanted and a solution

of 1.7 M NaCl was added to solubilize the crystalline catalase. Solubilization was performed at room

temperature for 1 h. The freshly solubilized catalase was dialyzed overnight at 4 °C against a solution of 50

mM sodium phosphate (pH 6.3) to allow recrystallization. The catalase crystals were collected and stored

in tubes at 4 °C for an additional 24 h before being washed with water as described above. Catalase crystals

were stored at 4 °C until used for MicroED sample preparation.

The Mpro fraction was thawed and the concentration was adjusted to 5 mg/mL. The mixture was

diluted 1:1 with crystallization mother liquor (0.1 M MES pH 6.5, 20% PEG 3,350 and 5% DMSO).

Crystals grew as plate clusters after 1 to 3 days when incubating at 20 ˚C using hanging vapor diffusion.

Approximately 10 μL of the crystal drops were combined and used for preparation of a micro seeding stock.

1 μL of 2.5 mg/mL Mpro was mixed with 0.1 μL seeding stock and 1 μL of the crystallization condition.

Monodisperse Mpro microcrystal plates were grown after 1 day when incubating at 20 ˚C using hanging
vapor diffusion.

2.3.   EM sample preparation

EM samples were prepared following previously published protocols (Martynowycz *et al.*, 2021).
Typically, carbon-coated (Quantifoil R 2/2) 200-mesh copper grids (Electron Microscopy Sciences) were
negatively glow-discharged at 15 mA for 45 s using a PELCO easiGlow (Ted Pella). The grids were then
loaded into a Leica EM GP2 plunge freezer (Leica Microsystems) set to 20 ˚C and 95% humidity. Using a
micropipette, 2 µL of the crystal drop was transferred to the grid, which was then blotted for 20 s, and
finally plunged into liquid ethane.

For the suspended-drop grids, the crystal slurry was added directly to a 150 mesh count support-
free gold gilder grid (Ted Pella) that was clipped into an autogrid cartridge (Thermo-Fisher). To transfer a
minimal amount of catalase sample to the grid, the sample was first aspirated into a pipet tip, which was
gently dragged across the surface of the grid to deposit the sample. Sample transferred to the grid bars and
was retained by surface tension. For MPro, the grids supporting the suspended crystal drops were blotted
with filter paper from the edge for 2 s. The grids were finally plunged into liquid ethane and stored under
liquid nitrogen until further use.

2.4.   Milling lamellae of catalase suspended crystals

Focused ion beam (FIB) milling followed procedures similar to suspended drop crystallization
(Gillman *et al.*, 2023). The frozen sample containing suspended crystals was loaded into a Thermo-Fisher
Helios Hydra plasma beam FIB (pFIB)/scanning electron microscope (SEM) operating at cryogenic
temperature. The crystal drop was coated with platinum by beam-assisted GIS coating (argon beam at 4
nA, 5 kV) for 1 min to protect the sample from ion and electron beams. A whole-grid atlas of the drop was
acquired with the SEM operating at an accelerating voltage of 0.5 kV and beam current of 13 pA using the
latest version of MAPS software (Thermo-Fisher). The pFIB milling angle was set to 10° from the grid
surface. For the first milling step, in the pFIB view, two 20×20 µm boxes (cleaning cross section milling
pattern) separated by 5 µm were drawn and centered about the site of interest. Bulk material was removed
using the xenon plasma beam set to a current of 4 nA for rough milling, which produced a 10-15 µm long
lamella. The lamella trenches were inspected to ensure that the top and bottom of the lamella were exposed
for subsequent MicroED data acquisition. The second lamella milling step used 1 nA of xenon plasma
current to reach 3.5 µm thickness and 15 µm width. The third milling step was performed with a 0.3 nA
xenon plasma current to narrow the lamella down to 2 µm thickness and 10 µm width. The fourth milling
step was done at 0.1 nA to reach 1 µm thickness. Lastly, the milling ion current was set to 30 pA for final

thickness milling and polishing. A 10 μm wide and roughly 300 nm thick lamella was generated through

the drop of suspended crystals. The lamellae were visualized at 385 nm excitation wavelength with the

iFLM on the Hydra dual-beam instrument.

2.5.   Milling lamellae of Mpro preferred orientation crystals and suspended crystals

157   The vitrified grids were transferred into a Thermo-Fisher Aquilos FIB/SEM instrument operating

at cryogenic temperature. Whole-grid atlases were recorded with the SEM at 5 kV and 1.6 pA using MAPS

software. To protect the samples from the damaging ion and electron beams, the grids were coated with

platinum by sputter coating (Martynowycz *et al.*, 2019*b*). Individual crystals from blotted grids and

suspended drops were identified and aligned to eucentric height using MAPS software. FIB-milling

proceeded as described (Martynowycz *et al.*, 2019*b,a*). A typical crystal identified on the blotted grids was

tilted to a milling angle of 33°. Rough milling used an ion beam current of 300 pA to produce a 4 μm thick

and 5 μm wide lamella. For fine milling, a FIB current of 100 pA was used to reduce the thickness of lamella

to 1 μm. Polishing proceeded at an ion beam current of 50 pA until the thickness reached approximately

350 nm. The final lamella was approximately 3 μm wide. Milling suspended drop samples was similar to

the previously mentioned steps with slight modifications: the sample was tilted to a milling angle of 13°,

and the ion beam current for rough, fine, and final milling was set to 3 nA, 500 pA, and 100 pA, respectively.

2.6.   MicroED data collection

The grids hosting the milled lamellae were rotated 90° and transferred to a cryogenically cooled Thermo-

Fisher Scientific Titan Krios G3i TEM. The Krios was equipped with a field emission gun operating at an

accelerating voltage of 300 kV, a Falcon 4i direct electron detector, and a Selectris energy filter (Thermo-

Fisher). A low magnification atlas of the grid was acquired using EPU (Thermo-Fisher) to locate all milled

lamellae. The stage was moved to the lamella position and while in the "View" settings (SA 3,600×) of

SerialEM (Mastronarde, 2003), the eucentric height was set. The lamellae were manually scanned by

sequentially evaluating electron diffraction (Figure 1) until a crystal site was located. In the "Record"

settings, the following parameters were set for the electron beam in diffraction mode: a beam size of 20 μm

in diameter, a spotsize of 11, and a C2 aperture of 50 μm. These settings resulted in an electron dose rate of

approximately 0.0025 e-/(Å^2·s). Electron-counted MicroED datasets were collected using a Falcon 4i with

the "Record" mode of SerialEM following the protocol described in previously published work (Shiriaeva

et al., 2023). An in-house developed script was applied to insert the Selectris energy filter and automatically

collect continuous-rotation MicroED datasets for 420 s with a slit width of 20 eV and a selected area

aperture diameter of ~2 μm. Autodoc and log files were generated after each data collection to provide

metadata and parameters to use for data processing. For catalase, MicroED data were collected by

continuously rotating the stage at 0.14 ° / s for 420 s, resulting in a rotation range of 60°. For Mpro, typical

datasets from blotted crystals and suspended-drop grids were collected by continuously rotating the stage

at 0.19 ° / s for 420 s, resulting in a rotation range of 80°.

2.7. MicroED data processing and structure determination

Movies were converted to SMV format using the latest version of MicroED tools (Martynowycz *et*

al., 2019*a*; Hattne *et al.*, 2015; Hattne *et al.*, 2023). The converted MicroED datasets were processed with

XDS (Kabsch, 2010*b*). The catalase diffraction dataset was indexed and integrated in space group $P \, 2_1 \, 2_1$

2_1 and unit cell dimensions 68.65, 173.30, 182.78 (a, b, c) (Å) and 90, 90, 90 (α, β, γ) (°), and the Mpro

dataset was indexed and integrated in space group $C \, 2$ with the unit cell parameters of 115.54, 55.53, 45.37

(a, b, c) (Å), 90, 101.07, 90 (α, β, γ) (°). High quality datasets including the missing cone were scaled and

merged in XSCALE (Kabsch, 2010*a*) and converted to MTZ format with supplemental 5% free R column

in XDSCONV (Kabsch, 2010*b*). Phases for the MicroED reflections were determined by molecular

replacement in MOLREP and Phaser (McCoy et al., 2007) using Protein Data Bank (PDB) 3J7B (Nannenga

et al., 2014) as the search model for catalase, and PDB 7K3T (Andi *et al.,* 2022) as the search model for

MPro. The refinement was performed with REFMAC and phenix.refine (Afonine *et al.*, 2012) using

electron scattering factors without restoring missing reflections. Refinement was followed by manual

curation in Coot (Emsley *et al.*, 2010).

3. Results

3.1 Sample preparation and MicroED data collection

To collect data covering all of reciprocal space, sample preparations were screened for randomly

oriented crystals. In addition, the samples were kept at minimal volume to reduce the FIB-milling time and

thereby prevent damaging the crystals in the suspended drops. Initially, 0.3–0.5 µL of crystal slurry was

pipetted onto the support-free grid and spread with a micro-brush. However, pipetting such small volumes

gave inconsistent results using standard micropipettes. The second application method explored was

preparing a droplet of the crystal slurry on a siliconized coverslip and gently touching a support-free grid

to the surface of the crystal slurry, which transferred a fraction of the drop to the grid bars. Although this

improved the consistency of sample preparation, spreading the drop with a micro-brush was still required.

It was finally discovered that gently touching a pipet tip filled with the crystal slurry to the grid bars allows

a minimal volume of the slurry to transfer by capillary motion. This method was highly reproducible and

efficient leading to very small volume. We further evaluated careful blotting from the side with filter paper

to reduce the volume of the sample, which also proved to be successful. The thickness of the samples from

both methods was estimated to be similar to the height of the gold grid bars (10–20 µm thick), as the grid

bars were clearly visible when imaged in SEM. These sample preparations substantially reduced the FIB-

milling times while maintaining the random orientations of the crystals, as illustrated by the improvement

of reciprocal space sampling (Figure 2).

For the catalase suspended crystal sample, a cryogenically cooled Helios pFIB/SEM (Thermo-Fisher) was

used for lamellae milling. Specifically targeting the crystals using an integrated fluorescence microscope

(iFLM) and correlative light electron microscopy (CLEM), as in suspended drop crystallization (Gillman

et al., 2023), was unnecessary because the catalase crystals were at a high concentration in the stock, and

capturing a randomly oriented crystal within the lamella was straightforward. During all milling steps, the

lamella was imaged using the iFLM set to the 385 nm LED to ensure the presence of randomly oriented

crystals. Crystals that appeared as thin rectangles when imaging normal to the grid bars were taken to be in

an ideal orientation for capturing the missing cone of data. For the Mpro suspended crystal sample, a

cryogenically cooled Aquilos FIB/SEM (Thermo-Fisher) was used for lamellae milling. Because the

suspended drop of Mpro crystals was briefly blotted, only a minimal volume of sample was retained by the

grid bars, which allowed for crystal morphological features to be observed and targeted. In contrast to the

instrumental setup used for catalase, the Aquilos used for the Mpro sample does not have the ability to

image the samples using fluorescence. We chose to evaluate our sample using this instrument since it is

more generally accessible. To capture as many crystals as possible, several long lamellae expanding over

the whole grid square were milled, generally containing 2–5 crystals each.

3.2.   Eliminating the missing cone in the MicroED structures of catalase and Mpro

Catalase was the second protein determined by MicroED (Nannenga, Shi, Hattne *et al.*, 2014). A single

crystal yielded relatively high completeness, however, even merging data from five additional crystals could

not eliminate the missing cone. This is because catalase forms flat rectangular plate-like crystals that, when

dispensed on the grid, align with the c*-axis of their lattices normal to the plane of the grid. MicroED data

were collected from a suspended crystal of catalase and merged with the previously published data showing

preferred orientation (Nannenga, Shi, Hattne *et al.*, 2014). Similarly, Mpro yields flat plate-like crystals

with preferred orientations on the grids. In addition, the crystal symmetry of the Mpro crystals is low,

leading to low completeness of our initially collected supported crystals (~60%). These preferred

orientation data were combined with Mpro data collected of the sample in suspension. We produced two

separate datasets for each protein: one "preferred orientation" dataset and one "missing cone eliminated".

These datasets were processed and refined separately, and the observed reflections, statistics, and refined

maps were subsequently compared. Data processing statistics for both "preferred orientation" and "missing

cone eliminated" catalase and Mpro datasets are presented in Table 1.

The zone at $k = 0$ clearly illustrates that a significant amount of the missing cone of reciprocal space

was recovered (Figure 2a, b) for catalase, consistent with the total number of unique reflections increasing

from 15,070 to 18,157 (Table 1) within 4 Å resolution. For Mpro, viewing 2D slices along the *l*-axis, the

missing cone of data was also clearly recovered (Figure 2c, d), increasing the number of unique reflections

from 9,189 to 14,825 (Table 1). As expected, the completeness across the resolution shells of catalase

improved after merging the missing cone dataset with the preferred orientation dataset (Figure 3a),

increasing the overall dataset completeness from 78.8 to 94.9% (Table 1). Similarly, the completeness for

Mpro significantly improved (Figure 3c) from 59.1 to 95.5% (Table 1).

Finally, the density maps resulting from the preferred orientation datasets and the missing cone

eliminated datasets were compared for each protein (Figure 4). Once the missing cone is eliminated, many

regions that were originally poorly resolved show contiguous densities that are easily interpretable. For

each protein sample, several instances are illustrated wherein the improved maps facilitated more precise

positioning of amino acid sidechains during the construction of the molecular models.

4. Conclusions

Here, we report a method that enables direct targeting and capturing of the critical missing cone of

MicroED data for crystals that systematically adopt a preferred orientation on the EM grid. Suspended

crystals of both bovine liver catalase and the COVID-19 main protease Mpro were used as test samples. In

both cases, crystals grew as rectangular plates that would normally lie flat on the carbon support film of the

grid, such that their crystallographic axes would preferentially orient with the normal of the grid. However,

the absence of a support film precluded these crystal plates from having a surface to align with and were

effectively frozen in random orientations as postulated in earlier studies (Gillman et al. 2023). Whereas

typically no amount of data collection and merging can recover the missing cone due to preferred

orientation, crystals of catalase and Mpro were here suspended in essentially random orientations by

removing the support film. Crystals are left exposed for FIB-milling and MicroED collection of complete

datasets, which yield densities that are interpretable and further facilitate modeling and refinement.

Crystals with a systematic preferential orientation are not common, and we estimate that less than 10% of

all protein crystals would fall under this category. The majority of samples will likely adopt random

orientations on the grid and may also have higher crystal symmetry. In such cases, even a single nanocrystal

can be sufficient for a complete structure by MicroED. However, the missing cone creates a substantial

bottleneck in structure solution for crystals that adopt a preferred orientation, and this phenomenon might

be more prevalent for smaller crystal sizes. While the suspended drop crystallization approach described

here eliminated the preferential orientation problem for MicroED, the missing cone problem remains a

prevalent issue in cryotomography (Barth *et al.*, 1988). Even for single particle reconstructions, the sample

may preferentially orient at the water-air interface (Glaeser & Han, 2017) and innovative approaches may

be needed to eliminate the preferential orientation problem.

As the methodologies for MicroED sample preparation are improved and continue to evolve, we

anticipate the method to deliver structures for samples that remain beyond the technological reach of other

structural biology methods. The innovative solution presented here proves indispensable for crystals

exhibiting preferred orientations, unlocking new possibilities for structure determination in MicroED

workflows.

Data availability

Coordinates and maps were deposited in the protein data bank and the EM Data bank (XXXX and YYYY).

Acknowledgments

The authors would like to thank Dr. Steve Halaby for early work on Mpro. This study was supported by the

National Institutes of Health P41GM136508 and the Department of Defense HDTRA1-21-1-0004. The

Gonen laboratory is supported by funds from the Howard Hughes Medical Institute. E.D. thanks the

Wenner-Gren Foundations for their support through the Wenner-Gren Postdoctoral Fellowship.

Figure Legends

Figure 1. MicroED of catalase and Mpro. (a) Electron diffraction frame acquired from catalase. (b)

Ribbon model of catalase. (c) Electron diffraction frame acquired from Mpro. (d) Ribbon model of Mpro.

Figure 2. Recovery of missing reflections in MicroED datasets of catalase and Mpro. (a-b) Catalase.

(a) The *h*0*l* zone of observed reflections to 8 Å resolution in the preferred orientation dataset viewed along

the *k*-axis. (b) The same zone as in (a) for the missing cone eliminated dataset. (c-d) Mpro. (c) The *hk*0 zone

of observed reflections to 2.5 Å resolution in the preferred orientation dataset viewed along the *l*-axis. (d)

The same zone as in (c) for the missing cone eliminated dataset viewed along the *l*-axis. All plots were

rendered with *ViewHKL* from the CCP4 suite.

Figure 3. Completeness for preferred orientation data vs. missing cone eliminated data for catalase

and Mpro. (a) Completeness (%) of catalase, (b) Completeness (%) of Mpro as functions of resolution (Å).

Preferred orientation data in orange, missing cone eliminated data in blue.

Figure 4. Density improvements upon completion of the reciprocal space. Several regions that exhibit significant density improvement are presented. $2mF_o$-DF_c maps are all contoured at 1.2 σ above the mean and carved at 2 Å around the model. On the left in each panel, the preferred orientation map density is compared to that for the missing cone eliminated on the right.

Table 1. Preferred orientation vs. missing cone eliminated dataset statistics for catalase and Mpro

References

Afonine, P. V., Grosse-Kunstleve, R. W., Echols, N., Headd, J. J., Moriarty, N. W., Mustyakimov, M., Terwilliger, T. C., Urzhumtsev, A., Zwart, P. H. & Adams, P. D. (2012). *Acta Crystallogr D Biol Crystallogr* **68**, 352–367.

Andi, B., Kumaran, D., Kreitler, D. F., Soares, A. S., Keereetaweep, J., Jakoncic, J., Lazo, E. O., Shi, W., Fuchs, M. R., Sweet, R. M., Shanklin, J., Adams, P. D., Schmidt, J. G., Head, M. S. & McSweeney, S. (2022). *Sci Rep* **12**, https://doi.org/10.1038/S41598-022-15930-Z.

Barth, M., Bryan, R. K., Hegerl, R. & Baumeister, W. (1988). *Scanning Microsc Suppl* **2**, 277–284.

Bruhn, J. F., Scapin, G., Cheng, A., Mercado, B. Q., Waterman, D. G., Ganesh, T., Dallakyan, S., Read, B. N., Nieusma, T., Lucier, K. W., Mayer, M. L., Chiang, N. J., Poweleit, N., McGilvray, P. T., Wilson, T. S., Mashore, M., Hennessy, C., Thomson, S., Wang, B., Potter, C. S. & Carragher, B. (2021). *Front Mol Biosci* **8**, 648603.

Clabbers, M. T. B., Martynowycz, M. W., Hattne, J. & Gonen, T. (2022). *J Struct Biol X* **6**, 100078.

Danelius, E., Porter, N. J., Unge, J., Arnold F. H., Gonen T. (2023). *J Am Chem Soc* **145**, 7159–7165.

Emsley, P., Lohkamp, B., Scott, W. G. & Cowtan, K. (2010). *Acta Crystallogr D Biol Crystallogr* **66**, 486–501.

Foroughi, L. M., Kang, Y. N. & Matzger, A. J. (2011). *Cryst Growth Des* **11**, 1294–1298.

Gallagher-Jones, M., Glynn, C., Boyer, D. R., Martynowycz, M. W., Hernandez, E., Miao, J., Zee, C.-T., Novikova, I. V, Goldschmidt, L., McFarlane, H. T., Helguera, G. F., Evans, J. E., Sawaya, M. R., Cascio, D., Eisenberg, D. S., Gonen, T. & Rodriguez, J. A. (2018). *Nat Struct Mol Biol* **25**, 131–134.

Gillman, C., Nicolas, W. J., Martynowycz, M. W. & Gonen, T. (2023). *IUCrJ* **10**, https://doi.org/10.1107/s2052252523004141.

Glaeser, R. M. & Downing, K. H. (1993). *Ultramicroscopy* **52**, 478–486.

339   Glaeser, R. M. & Han, B.-G. (2017). *Biophys Rep* **3**, 1–7.

340   Griner, S. L., Seidler, P., Bowler, J., Murray, K. A., Yang, T. P., Sahay, S., Sawaya, M. R., Cascio, D.,
341   Rodriguez, J. A., Philipp, S., Sosna, J., Glabe, C. G., Gonen, T. & Eisenberg, D. S. (2019). *Elife* **8**,
342   e46924.

343   Hattne, J., Reyes, F. E., Nannenga, B. L., Shi, D., Cruz, M. J. de la, Leslie, A. G. W. & Gonen, T. (2015).
344   *Acta Crystallogr A Found Adv* **71**, 353–360.

345   Hattne, J., Shi, D., Glynn, C., Zee, C.-T., Gallagher-Jones, M., Martynowycz, M. W., Rodriguez, J. A. &
346   Gonen, T. (2018). *Structure* **26**, 759--766.e4.

347   Hattne, J., Clabbers, M. T. B., Martynowycz, M. W., Gonen, T. (2023). *Structure* **31**, 1504–1509.

348   Kabsch, W. (2010*a*). *Acta Crystallogr D Biol Crystallogr* **66**, 133–144.

349   Kabsch, W. (2010*b*). *Acta Crystallogr D Biol Crystallogr* **66**, 125–132.

350   Martynowycz, M. W., Clabbers, M. T. B., Hattne, J. & Gonen, T. (2022). *Nat Methods* **19**, 724–729.

351   Martynowycz, M. W., Clabbers, M. T. B., Unge, J., Hattne, J. & Gonen, T. (2021). *Proc Natl Acad Sci U S*
352   *A* **118**, 1–7.

353   Martynowycz, M. W. & Gonen, T. (2021). *STAR Protoc* **2**, 100686.

354   Martynowycz, M. W., Shiriaeva, A., Clabbers, M. T. B., Nicolas, W. J., Weaver, S. J., Hattne, J. & Gonen,
355   T. (2023). *Nat Commun* **14**, 1086.

356   Martynowycz, M. W., Zhao, W., Hattne, J., Jensen, G. J. & Gonen, T. (2019*a*). *Structure* **27**, 545-548.e2.

357   Martynowycz, M. W., Zhao, W., Hattne, J., Jensen, G. J. & Gonen, T. (2019*b*). *Structure* **27**, 1594-
358   1600.e2.

359   Mastronarde, D. N. (2003). *Microscopy and Microanalysis* **9**, 1182–1183.

360   Matricardi, V. R., Moretz, R. C. & Parsons, D. F. (1972). *Science (1979)* **177**, 268–270.

361   McCoy, A. J., Grosse-Kunstleve, R. W., Adams, P. D., Winn, M. D., Storoni, L. C. & Read, R. J. (2007). *J*
362   *Appl Crystallogr* **40**, 658–674.

Mu, X., Gillman, C., Nguyen, C. & Gonen, T. (2021). *Annu Rev Biochem* **90**, 431–450.

Nannenga, B. L., Shi, D., Hattne, J., Reyes, F. E. & Gonen, T. (2014). *Elife* **3**, e03600.

Nannenga, B. L., Shi, D., Leslie, A. G. W. & Gonen, T. (2014). *Nat Methods* **11**, 927–930.

Purdy, M. D., Shi, D., Chrustowicz, J., Hattne, J., Gonen, T. & Yeager, M. (2018). *Proc Natl Acad Sci U S*
A **115**, 13258–13263.

Shi, D., Nannenga, B. L., Iadanza, M. G. & Gonen, T. (2013). *Elife* **2**, e01345.

Shiriaeva, A., Martynowycz, M. W., Nicolas, W. J., Cherezov, V. & Gonen, T. (2023). *Biorxiv: The*
Preprint Server.

Stahlberg, H., Biyani, N. & Engel, A. (2015). *Arch Biochem Biophys* **581**, 68–77.

Sumner, J. B. & Dounce, A. L. (1937). *Science (1979)* **85**, 366–367.

Yonekura, K., Kato, K., Ogasawara, M., Tomita, M. & Toyoshima, C. (2015). *Proceedings of the National*
Academy of Sciences **112**, 3368–3373.

Figure 1

380
381
382

(a)

(b)

(c)

(d)

Figure 2

383
384
385

(a)

(b)

Figure 3

Catalase COVID-19

Pro311–Leu315   Leu141–Cys145

Heme   Gly183–Asp187

386
387   Val72–Lys76   **Figure 4**   Thr280–Ser284
388

Table 1

Statistic	Catalase		COVID-19 MPro	
	Preferred orientation	Missing cone eliminated	Preferred orientation	Missing cone eliminated
# of crystals	1	2	1	4
Spacegroup	$P\,2_1\,2_1\,2_1$	$P\,2_1\,2_1\,2_1$	$C\,2$	$C\,2$
a, b, c (Å)	68.65, 173.30, 182.78	68.65, 173.30, 182.78	115.54, 55.53, 45.37	115.54, 55.53, 45.37
α, β, γ (°)	90, 90, 90	90, 90, 90	90, 101.07, 90	90, 101.07, 90
Resolution (Å)	4.0 (4.1–4.0)	4.0 (4.1–4.0)	2.15 (2.20–2.15)	2.15 (2.21–2.15)
# observations	45,664 (3,381)	89,263 (6,646)	27,905 (2,056)	123,734 (3,457)
Unique reflections	15,070 (1,366)	18,157 (1,317)	9,189 (673)	14,825 (1,038)
R_{obs} (%)	21.6 (31.5)	59.1 (83.9)	13.5 (79.3)	24.1 (88.2)
R_{meas} (%)	26.5 (38.6)	65.2 (92.4)	16.6 (96.9)	25.6 (105.4)
$\langle I / \sigma(I) \rangle$	4.19 (3.07)	2.63 (2.05)	4.86 (1.17)	5.63 (1.11)
$CC_{1/2}$ (%)	94.3 (82.2)	86.4 (58.1)	98.8 (51.6)	98.7 (56.2)
Completeness (%)	78.8 (80.7)	94.9 (96.4)	59.1 (58.4)	95.5 (90.1)
R_{work} (%)	20.96	31.66	22.81	22.63
R_{free} (%)	29.15	35.80	27.12	25.87
RMS bond (Å)	0.0039	0.0038	0.014	0.002
RMS angle (°)	1.0867	1.0391	1.556	0.477
Ramachandran favored / allowed / outlier (%)	91.0 / 8.2 / 0.8	92.0 / 7.2 / 0.8	93.6 / 3.7 / 2.7	94.2 / 3.4 / 2.4