ImmCellTyper: an integrated computational pipeline for systematic mining of

Mass Cytometry data to assist deep immune profiling

Jing Sun[1*~], Desmond Choy[3*], Nicolas Sompairac[3], Shirin Jamshidi[3], Michele Mishto[1-2],

Shahram Kordasti[3-5~]

[1] Centre for Inflammation Biology and Cancer Immunology & Peter Gorer Department of
Immunobiology, King's College London, SE1 1UL London, United Kingdom
[2] Research group of Molecular Immunology, Francis Crick Institute, NW1 1AT London, United
Kingdom
[3] School of Cancer and Pharmaceutical Sciences, King's College London, London, United
Kingdom
[4] Haematology Department, Guy's Hospital, London, United Kingdom
[5] Department of Clinical and Molecular Sciences, Università Politecnica delle Marche, Ancona,
Italy

*These authors contribute equally to this research work
~ corresponding authors

Jing Sun: jing.1.sun@kcl.ac.uk
Shahram Kordasti: shahram.kordasti@kcl.ac.uk

Abstract

Mass cytometry, also known as Cytometry by time-of-flight (CyTOF), is a cutting-edge high-dimensional technology for profiling marker expression at the single-cell level. This technology significantly advances clinical research in immune monitoring and the interrogation of immune cell populations. Nevertheless, the vast amount of data generated by CyTOF poses a daunting challenge for analysis. To address this, we describe ImmCellTyper (https://github.com/JingAnyaSun/ImmCellTyper), a novel and robust toolkit designed for CyTOF data analysis. The analytical framework incorporates an in-house developed semi-supervised clustering tool named BinaryClust, which first characterises main cell lineages, followed by in-depth interrogation for population of interest using unsupervised methods. BinaryClust was benchmarked with existing clustering tools and demonstrated superior accuracy and speed across two datasets comprising around 4 million cells, performing as good as manual gating by human experts. Furthermore, this computational pipeline provides a variety of visualization and analytical tools spanning from quality control to differential analysis, which can be tailored to user's specific needs, aiming to provide a one-stop solution for CyTOF data analysis. The general workflow consists of five key steps: 1) Batch effect evaluation and correction, 2) Data quality control and pre-processing, 3) Main cell lineage characterisation and quantification, 4) Extraction and in-depth investigation of cell type of interest; 5) Differential analysis of cell abundance and functional marker expression (supporting multiple study groups). Overall, ImmCellTyper integrates expert's biological knowledge in a semi-supervised fashion to accurately deconvolute well-defined main cell lineages, while also preserving the potential of unsupervised approaches to discover novel cell subsets and providing a user-friendly toolset to remove the analytical barrier for high-dimensional immune profiling.

Introduction

Mass cytometry or cytometry by time-of-flight (CyTOF) is a powerful high-throughput single-cell technology which employs stable elemental isotopes, as the same manner of fluorophores, to detect cellular proteins of interest. This approach successfully tackles the panel multiplex challenges faced by traditional flow cytometry due to spectral overlap and permits simultaneous measurement of over 40 parameters on millions of cells. To date, CyTOF has been widely applied in basic and translational medical research, such as deep immunophenotyping and characterisation of novel refined cell subsets, immune monitoring of cell-adoptive therapy, and dissecting cell subpopulations from heterogeneous tumour samples [1]. Nonetheless, the advantages of CyTOF come with the problem of handling high-dimensional dataset. Traditional gating strategy for flow cytometry, while still serving as the 'gold standard' for cell population identification in cytometry data, may not be an optimal option for CyTOF data due to its high-dimensional settings. The high-parametric resolution in CyTOF, aimed at revealing previously undiscovered cell subpopulations, leads to a significant increase in the complexity of gating schemas and hierarchical depth, which makes manual gating extremely labour intensive and time-consuming [2]. Therefore, effective computational toolkits and pipelines are entailed for CyTOF data mining and analysis.

Efforts have been directed toward developing means of clustering algorithms to deconvolute a pool of live cell mixture into distinct cell populations, which facilitates CyTOF data analysis. For instance, unsupervised methods, which include flowSOM[3], Phenograph[4], X-shift[5], spade[6], and DensVM[7] etc., often combine with dimension reduction techniques like t-SNE[8], UMAP[9], PCA etc., and require manual annotation of each cluster based on the marker expression patterns indicated by heatmaps. This approach works well to analyse populations in a data-driven manner, with all files concatenated and analysed all at once. Compared to manual gating, it has advantages in terms of convenience, efficiency, and relative unbiasedness from biological preconception, facilitating the detection of novel cell phenotypes for deep phenotyping. However, the unsupervised approaches are not always ideal and suitable for cytometry data. Mathematical clustering does not necessarily have biological meaning, leading to occasional inaccuracies. And several benchmarking studies suggested that the accuracy for these unsupervised tools may not be optimal[10]. Additionally, the technical

uncertainty of results produced by different clustering approaches remains a conundrum.

Even for the same unsupervised method, the discrepancy among different runs without

setting a seed, reduces the reproducibility and may cause confusion, particularly for biologists

with limited computational knowledge. Moreover, manual validation is also essential, as

biological annotation is the inevitable step to provide biological relevant labels for the clusters.

However, this process can be time-consuming and subjective, hindering the automation of

pipelines. This problem is particularly pronounced for a large marker panel and samples with

high heterogeneity, resulting in a higher number of clusters that need to be annotated.

Advances in artificial intelligence have accelerated the development of alternative clustering

methods in a supervised manner for cell type inference. These methods consider the 'ground

truth' or prior knowledge about the marker expression of each given cell types to

automatically label each cell. Currently, a couple of semi-automatic methods have been

developed, such as Linear Discriminant Analysis(LDA)[11], DGCyTOF[12], CyAnno[13], DeepCyTOF[14],

Automated Cell-type Discovery and Classification (ACDC) [15]and Semi-supervised Category

Identification and Assignment(SCINA) [16] etc. ACDC[15] and SCINA[16] use a matrix of pre-defined

markers for each cell type to annotate the clusters showing the same signature. These

methods assume that markers are either expressed or not expressed (binary), which limits

their ability to distinguish cell subtypes with similar phenotypes, particularly non-canonical

cell types that cannot be easily separated linearly. Alternatively, DeepCyTOF and LDA use a

marker expression matrix extracted from manually gated cell types as a training dataset to

build a machine learning model for cell type prediction. This approach has higher precision

and accuracy compared with aforementioned methods[10]. Nonetheless, it can be labour

intensive for preparation of the training set manually. Also, these methods are limited in their

ability to predict novel cell subsets beyond the pre-gated set of cell types and lack a

systematic and comprehensive way to assign the cells which were not identifiable under any

of the gated cell types. New solutions have emerged with algorithms such as DGCyTOF[12] and

CyAnno[13], the former adopts a deep learning classification combined with hierarchical stable-

clustering methods and an iteration calibration system to identify known cell types and assign

novel subsets; while CyAnno is based on a machine-learning framework which allows the

integrative modelling of both 'gated' and 'ungated' cells. Both methods have demonstrated

high accuracy in their test datasets, but unfortunately are not widely used by the research

community, possibly due to the issue for the hassle of training data preparation, the lack of

user-friendliness and implementation challenges for bench researchers.

To address the common drawbacks of current semi-supervised and unsupervised clustering

algorithms and preserve their strengths in discovering both canonical and non-canonical cell

subsets respectively, we propose a strategy implemented in ImmCellTyper for cell

classification named BinaryClust. By considering biologists' prior biological knowledge and

interpretation for canonical cell clusters in a semi-supervised manner, BinaryClust first

automatically characterises the main cell lineages in a fast and accurate way. Subsequently, it

extracts specific cell types of interest for further clustering using unsupervised algorithms to

identify cell subsets including previously unreported non-conventional population. In addition,

this R-implemented pipeline takes advantage of SingleCellExperiment class for data

management, providing an easy-to-use and organized systematic workflow of CyTOF data

handling. The whole pipeline includes quality control and batch effect correction, which helps

to effectively pool datasets from different batches, and ensures the robustness for

downstream analysis. Meanwhile, modules like dimension reduction, semi-supervised and

unsupervised clustering (flowSOM and Phenograph), interactive data visualisation, and

statistical testing for complex study design were also incorporated in this pipeline. Compared

with existing integrated computational workflow, such as CATALYST[17], CapX[18], Cytofkit[19] and

ImmunoCluster[20] which was developed and maintained by our team, this recently developed

toolkit advanced further on coherence, functionality and user-friendliness. Overall, this

approach has the potential to facilitate and smooth the investigation of CyTOF-based

research.

Results

BinaryClust is comparable with manual gating in quantifying the abundances of main cell

lineages.

The core concept for BinaryClust is depicted in Figure1, where a simple user-designed cell

type marker expression matrix is required and serves as a reference to characterise the main

cell lineages, with positive markers indicated in '+', negative markers in '-', and irrelevant

markers in 'A'. K-means(k=2) will be applied to divide the positive and negative cell

population of each marker, then align it to the reference table to infer main cell types. This is

followed by the extraction of population-of-interest for downstream clustering using

unsupervised methods for subpopulation discovery.

To assess the performance of the automated cell type classification and prediction, we

generated a test CyTOF dataset using peripheral blood mononuclear cell (PBMC) samples

from seven patients with myeloproliferative neoplasm (MPN) and two healthy donors,

employing a 37-marker deep immunophenotyping panel (Supplementary Table 1). Manual

gating was performed by two independent experts which identified seven main cell lineages.

These results act as the reference for evaluating the computer-aided methods. The

hierarchical sequential gating strategy was explicitly illustrated in Supplementary Figure 1. We

evaluated the agreement between manual gating results and BinaryClust results regarding

cell frequencies of each population. The mean value was calculated from manual gating

results of two experts to compare with BinaryClust-generated results using Pearson

correlation analysis. As shown in Figure2A, the two methods exhibit a strong correlation with

coefficient(R^2) equals to 1,1,0.99,0.96,0.96,0.99,0.99 for CD4 T cells, CD8 T cells, dendritic

cells, NK cells, monocytes, and gamma delta T cells, respectively (all P <0.0001). And most of

the data points remain close to the line of equality (red line, R^2=1), indicating a high degree of

agreement. Meanwhile, the Bland-Altman plots in Figure 2B also suggest no consistent bias of

manual gating versus BinaryClust across all the identified cell types. The good performance of

BinaryClust was further validated in the influenza dataset published by our group[21], which

contains FCS files from 11 individuals with 6 main immune cell types detected, the average F-

measure and ARI reached 0.98 and 0.91 respectively (Supplementary Figure2A-B).

Figure 1

Figure 1 Schematic diagram of BinaryClust framework. Semi-supervised classification is first performed

on selected markers in the user-defined marker expression matrix to classify and annotate major cell

types. Population-of-interest can be further extracted and explored using unsupervised clustering

methods followed by differential analysis. Figure was generated by BioRender

(https://www.biorender.com/).

Figure 2 Agreement evaluation comparing manual gating and BinaryClust in MPN cohort(n=9). Manual

gating of B cells, CD4 T cells, CD8 T cells, dendritic cells, NK cells, monocytes and gamma delta T cells

were performed by two independent experts using Cytobank, and mean values of the population

percentages were calculated to compare with BinaryClust results. Each dot represents one patient

sample. (A) Scatter plot showing the correlation between the two methods, with the red line

indicating perfect agreement (correlation coefficient = 1); (B) Bland-Altman plots of the two

measurement methods among all the cell populations, with the black line suggesting the mean

observed difference and red dotted lines indicating limits of agreement (1.96 x standard deviations).

BinaryClust achieves high accuracy and speed compared with flowSOM and LDA

To further evaluate

BinaryClust's performance, we compared it with the well-performing unsupervised algorithm

flowSOM and supervised classifier Linear discriminant analysis (LDA). FlowSOM was run on

the same MPN dataset with k value set as 20, followed by manual annotation and cluster

merging to identify the same cell populations as in manual gating and BinaryClust. The cell

frequencies derived from BinaryClust, flowSOM, and manual gating (expert1 and expert2)

were compared using interaction plot (Figure 3). We observed that BinaryClust remains

consistent with manual gating (all P>0.05), whereas flowSOM identified significantly less

Gamma Delta T cells and dendritic cells (P<0.001 and P=0.006, respectively) compared with

the other three measurements. We also increased the initial k value to 40 to improve

accuracy by over clustering then merging clusters [3]. We found that the average frequency for

Gamma Delta T cells and dendritic cells increased to 1.5% and 4.65% respectively but still

remained significantly different (P<0.05) from the other two methods. It is also interesting to

see that although the same gating strategy was applied, different experts obtained results

with slight variation despite no statistical significance. The same findings were confirmed

using boxplot as shown in Supplementary Figure 3.

Figure 3

Figure 3 Comparison of manual gating (manual1 and manual2), BinaryClust and flowSOM clustering

results in MPN cohort(n=9). Interaction plots showing the individual measurement (percentage) of

each study participant with indicated colors by different methods across main cell lineages (B cells,

CD8 T cells, Gamma Delta T cells, NK cells, Dendritic cells, monocytes and CD4 T cells); ANOVA was

used for statistical testing, and significance was marked by asterisk. * P<0.05, **P<0.01, ***P<0.001,

****P<0.0001.

Subsequently, LDA was also tested on the same dataset. Since this method requires a training dataset from manual gating to build a model, we exported the cell events and cluster assignment from Cytobank, then equally partitioned all cells into training and test dataset. Due to the difference in method implementation, we did not include LDA for cell abundance quantification comparison with other methods, since only half of the cells were used for prediction. To ensure an equitable comparison and further evaluate the accuracy, F-measure, and Adjusted Rand Index (ARI) were calculated using manual gating cluster IDs as reference. As indicated in Table 1, for the MPN dataset, BinaryClust achieved high F-measure and ARI in all 7 cell types with an average of 0.94 and 0.91 respectively. The performance remains excellent in influenza dataset as well (average F-measure = 0.98, Supplementary Figure 2C). LDA has equivalent prediction accuracy as BinaryClust with an average F-measure of 0.93 and ARI of 0.90. Both supervised methods outperformed flowSOM (average F-measure=0.75, average ARI=0.66), which is in line with previous benchmarking study on evaluating supervised and unsupervised clustering algorithms[10]. Notably, for cell types that constitute a substantial proportion in the pool like CD4 T cells, CD8 T cells, NK cells, monocytes, and B cells, flowSOM can identify them with high precision and sensitivity, while this is not the case for dendritic cells and gamma delta T cells which account for less than 3% of the whole population (F-measure = 0.51 and 0.15, respectively). Even so, the overall F-measure and ARI for flowSOM considering cell proportion reached 0.81 and 0.80.

Table 1 Precision, recall, F-measure, and ARI of indicated clustering methods.

Method	Gated population	Counts	Cluster Cell Counts	True Positive	Precision	Recall	F-measure	Average F-measure	ARI	Average ARI
Binary Clust2	CD4 T cells	1270041	1232832	1226712	1.00	0.97	0.98	0.94	0.95	0.91
	CD8 T cells	601995	601639	582402	0.97	0.97	0.97		0.95	
	NK cells	389261	380999	376561	0.99	0.97	0.98		0.97	
	Monocytes	576624	625735	568924	0.91	0.99	0.95		0.92	
	B cells	397279	380170	374501	0.99	0.94	0.96		0.95	
	Dendritic cells	135894	86012	84130	0.98	0.62	0.80		0.74	
	TCRgd T cells	87194	73599	73562	1.00	0.84	0.92		0.91	
flowSOM (k=20)	CD4 T cells	1270041	1268929	1226712	0.97	0.97	0.97	0.75	0.90	0.66
	CD8 T cells	601995	692374	571344	0.83	0.95	0.89		0.81	
	NK cells	389261	393646	365403	0.93	0.94	0.93		0.91	
	Monocytes	576624	792447	568284	0.72	0.99	0.85		0.73	
	B cells	397279	405886	390077	0.96	0.98	0.97		0.96	
	Dendritic cells	135894	20832	18254	0.88	0.13	0.51		0.22	
	TCRgd T cells	87194	19720	4967	0.25	0.06	0.15		0.08	
LDA	CD4 T cells	634733	665481	632700	0.95	1.00	0.97	0.93	0.93	0.90
	CD8 T cells	301138	327469	299309	0.91	0.99	0.95		0.92	
	NK cells	194470	202110	187259	0.93	0.96	0.94		0.92	
	Monocytes	288338	301387	282836	0.94	0.98	0.96		0.94	
	B cells	198582	211090	195908	0.93	0.99	0.96		0.94	
	Dendritic cells	68152	90456	61785	0.68	0.91	0.79		0.75	
	TCRgd T cells	43405	43064	39976	0.93	0.92	0.92		0.92	

ARI, Adjusted Rand Index; LDA, Linear discriminant analysis

It has been demonstrated that flowSOM and LDA are among the fastest clustering algorithms without compromising their performance. Here, we compared the speed amongst the three approaches in MPN, Influenza and COVID-19 datasets[22] which contain 2,231,053, 210,933 and

3,862,628 cells respectively. Since LDA requires training data to be executed, we did not run it

on COVID-19 dataset due to the absence of manual gating results. As shown in Figure 4,

BinaryClust exhibited the highest speed in both MPN and Influenza dataset but fell behind

flowSOM slightly in COVID-19 dataset.

Figure 4 Comparison of BinaryClust, flowSOM and LDA on speed. Bar chart showing runtime (in

seconds) of the three methods in three different datasets.

ImmCellTyper pipeline supports interactive data visualisation and comparison among study

groups.

BinaryClust is an important component of ImmCellTyper, a comprehensive integrated pipeline

designed for systematic CyTOF data mining. Hence, we utilised the visualisation functions to

further prove the reliability and robustness of BinaryClust.

BinaryClust inherently considers CyTOF makers as binary distributed which is in most of the

case, but not always. Therefore, it is crucial to check the marker behaviour before running

the pipeline. As shown in Figure 5A, all markers selected for the classification matrix (Figure

5B) displayed a binary distribution implying the suitability for this pipeline. After clustering

(Figure 5C), median marker expression heatmap (Figure 5D) can check the reliability of the

results before proceeding for downstream analysis. In MPN dataset, we projected the cluster

assignment resulted from BinaryClust and manual gating to UMAP (Figure 5E), along with the

expression of the phenotypic markers (Figure 5F and supplementary Figure 4A). High

similarity was observed between BinaryClust and manual gating, whereas slight difference

was found on flowSOM results coloured UMAP on islands of CD8 T cells and CD4 T cells

(Supplementary Figure 4A). FlowSOM appeared to classify cells that were close on spatial

distance into the same cluster, in contrast to prior knowledge-based methods: BinaryClust

and manual gating.

Figure 5

Figure 5 Cell type characterization and visualisation using ImmCellTyper pipeline in MPN dataset(n=9).

(A)Intensity distribution of selected phenotypic markers used for BinaryClust classification, coloured

by sample_id;(B) Pre-defined expression classification matrix for the MPN dataset, '+' indicates

positive, '-' indicates negative and 'A 'suggests 'any';(C) Proportion of the main cell lineages of all cells

in the concatenated FCS files after classification; (D) Median marker expression heatmap of

BinaryClust classification results; (E)UMAP plot of random downsample of 2000 cells per patient

coloured by main cell types based on BinaryClust classification (left) and manual gating results (right).

(F) UMAP plots coloured by normalized expression of indicated markers (CD3, CD4, CD8a, CD20, CD19,

CD14, and CD56) across 2000 cells per sample.

Application of ImmCellTyper pipeline to the COVID-19 dataset demonstrates its versatile

functionalities for comprehensive data analysis

To showcase the analytical and visualisation functions of ImmCellTyper pipeline, we used the

dataset published by Chevrier et al. [22], which described the immune signature of mild and

severe COVID-19 patients in comparison with healthy individuals. There are a total of 82 FCS

files with a 40-plex marker panel focusing on innate immunity in this dataset. An initial

marker expression check was carried out based on the user-defined matrix (Figure 6B) and

displayed in Figure 6A. BinaryClust was then performed and identified 12 cell populations as

expected. We used t-distributed stochastic neighbour embedding(t-SNE) in this dataset for

dimension reduction, coloured by cell types and faceted by disease conditions, which

exhibited substantial immune alteration among healthy control, mild and severe COVID-19

patients (Figure 6C). From the heatmap in Figure 6D, we can have an overview of the marker

expression of each population, which remains consistent with our initial definition indicated

in the expression matrix.

Figure 6

Figure 6 Applying ImmCellTyper pipeline on COVID-19 patient dataset(n=82) published by Chevrier

et.al. (A) Marker intensity distribution of selected phenotypic markers used for BinaryClust

classification, coloured by disease severity(n=22 healthy individuals, 28 mild COVID-19 patients and 38

severe COVID-19 patients);(B)Pre-defined marker expression classification matrix used for BinaryClust;

(C) T-SNE plots, with 1000 cells per sample, were coloured by the main cell types generated by

BinaryClust and faceted by different study groups;(D)The corresponding median marker expression heatmap of BinaryClust results for the COVID-19 dataset.

The abundances of the identified cell types were quantified for each individual study participant in the format of stacked histogram (Figure 7A) and summarized in boxplot (Figure 7B). Compared with healthy volunteers, there are significant immune alterations in COVID-19 patients in B cells, Basophils, cDCs, Monocytes, NK cells, CD8 T cells, Neutrophils and pDCs (all P<0.05), which depicts a similar trend to the original paper, despite slight discrepancies caused by different statistical methods used. Kruskal Wallis test was conducted for this dataset followed by multiple testing correction (Benjamini-Hochberg procedure) and Dunn's test for post hoc analysis, while Chevirer et al. used Mann-Whitney Wilcoxon test corrected by Holm method. We then selected 9 markers (IL-6, PD-L1, VISTA, IDO, TIM-3, TMEM173, GranzymeB, PPARg, Ki-67) as the state markers which can reflect the functional or proliferative status of the immune cell types. Notably, Granzyme B was observed to be significantly highly expressed in COVID-19 patients versus healthy control across all identified immune cell types(all P<0.05), TMEM173 was substantially up-regulated in COVID-19 patients particularly in monocytes, neutrophils, and CD4 T cells; and PD-L1 expression remained low for all cells, indicating the immune system of COVID-19 patients were highly activated without exhaustion regardless of disease severity, which was not explored previously. Since monocytes and neutrophils were of particular interest in the original paper, and the panel also included specific markers for in-depth interrogation, we then extracted the two population and carried out Phenograph(k=60) to investigate the subclusters. As shown in Figure 7D, Phenograph returned 16 and 14 subclusters respectively for monocytes and neutrophils, with heatmap provided in Supplementary Figure 5.

Reanalysis of the COVID-19 dataset demonstrated the concordance of ImmCellTyper pipeline with original reports with additional findings, as well as its versatile interactive data visualisation functionalities.

Figure 7

Figure 7 Quantification and statistical analysis comparing the study conditions in COVID-19

dataset(n=82). (A)Stacked histogram of main cell type composition per individual generated by

BinaryClust, and grouped by study conditions (healthy, mild and severe); (B)Boxplots representing cell

abundance frequencies among the study conditions, faceted by different main cell types;(C) State

marker expression intensities with comparison of the study groups across the main cell types;

(D)Clusters of monocytes and neutrophils were extracted from the whole cells for downstream

interrogation. T-SNE plots with random downsample of 1000 monocyte cells and (E) neutrophils per

sample were coloured by study conditions and Phenograph clustering results(k=60), respectively.

Statistical significance was marked by asterisk. * P<0.05, **P<0.01, ***P<0.001, ****P<0.0001

Discussion

In this study, we present an analytical pipeline named ImmCellTyper for systematic exploration of CyTOF data. This pipeline addresses a comprehensive range of analytical needs encompassing data quality check, batch effects examination/correction, cell type identification, and downstream differential analysis accompanied by high-quality, publishable data visualisations. Furthermore, ImmCellTyper includes an in-house developed, knowledge-based, semi-supervised classifier BinaryClust with high accuracy and speed, and also integrates the well-performing and state-of-the-art unsupervised algorithms (Phenograph and flowSOM). By adopting the strategy of first obtaining the main cell types and then select specific cell types for in-depth interrogation with higher clustering resolution, ImmCellTyper combines the advantages of both supervised and unsupervised clustering algorithms for discovery of both major populations and refined subpopulations. Designed for ease of use, this pipeline features a clear and user-friendly workflow, and is compatible to the widely used pipeline CATALYST, aiming to provide a one-stop solution for CyTOF users.

For validating the robustness of the automated cell characterization function of ImmCellTyper: BinaryClust, we involved two independent datasets (MPN dataset and Influenza dataset) and compared with existing clustering tools flowSOM and LDA. Previous Benchmarking studies indicated that flowSOM was one of the best-performing unsupervised tools in precision, speed and stability, with F-measure ranges from 0.58~0.90 in various datasets[10], and was widely used in high-impact research publications[10,23]. However, the results of flowSOM vary upon the k values set by the users which causes some uncertainty and impairs reproducibility of the results. In contrast, semi-supervised clustering methods like ACDC, DeepCyTOF[14] and LDA outperformed the unsupervised methods in the same benchmarking study. The F-measure obtained by ACDC and LDA ranged from 0.78~0.99, which was significantly higher than unsupervised approaches including Accense, PhenoGraph, Xshift, k-means, flowMeans[24], FlowSOM and DEPECHE[25](F-measure: 0.28~0.93)[23]. In this study, we chose LDA because it has proven to be superior to ACDC and DeepCyTOF in terms of precision and speed[10,11]. The excellent performance of LDA was demonstrated in MPN dataset of this study with F-measure reached 0.93 for around 4 million cells. BinaryClust was comparable in accuracy(F-measure=0.94) but much faster in speed. Both semi-supervised approaches outperformed

flowSOM as expected. Although semi-supervised methods seem to perform better, the

mainstream for CyTOF data analysis still relies on unsupervised methods. The reason for this

might be that most of the semi-supervised methods rely on manual gating as reference and

requires either the manually gated expression matrix or user-defined binary matrix as training

data. This process takes extra time and efforts especially for defining subpopulations, and

may introduce end-user bias. Additionally, the common restriction for all the supervised

methods is that they have limited capability to reveal novel subsets as those are not

predefined in the training pool, which poses a critical challenge for the pursuit of novel

discoveries. Considering all these strength and limitations, as a semi-supervised method,

BinaryClust possesses the advantages of incorporating prior biological knowledge, being

reproducible across runs and accurate on cell type identification. Meanwhile, the input

requirement is a simple matrix of cell population definition based on marker positivity,

avoiding the hassle to manually gate example FCS files. With a deep understanding that

certain CyTOF markers are expressed on a continuum rather than binary manner, this

automated supervised approach will only be used for classification of main cell lineages. The

test datasets in this study contained data from human PBMC samples which represented a

heterogenous pool of immune cells, covering the major types of various immune populations,

and demonstrated excellent performance of BinaryClust on classifying CD4 T cells, CD8 T cells,

gamma delta T cells, NK cells, monocytes, dendritic cells, and B cells. We also recommend

checking marker expression distribution before running the pipeline to ensure accurate

results. After the above step, this pipeline supports cell population extraction for further

dissection into subclusters using unsupervised approaches, which excel in detecting rare and

refined subpopulations. Phenograph is a particularly effective tool for this purpose. By

applying this strategy, our previous work with BinaryClust facilitated the evaluation of the

impact of systematic anti-cancer agents on lymphocyte population in non-small cell lung

cancer patients, as well as the characteristics of autologous T cell products after

manufacturing [26].

Another purpose behind the development of the ImmCellTyper framework is to cater to

general analysis needs, spanning from pre-processing to downstream differential analysis.

There are existing well-established pipelines like CATALYST[17], diffcyt[27], Cytofkit[19], and

ImmunoCluster[20] etc., each of them has its own strength and limitations. One of the

challenges existed in CyTOF data pre-processing is effectively integrating multiple batches,

given the technical differences arising from experiments and instrumental acquisition, which

could result in the separation of clustering across batches and potentially confounding the

signal of interest. In ImmCellTyper pipeline, we provide the functionality for batch effects

examination and incorporated two well-performing batch correction algorithms CytoNorm[28]

and CytofRUV[29] into our framework prior to downstream analysis, which ensures the quality

of the data and, to the best of our knowledge, makes it the first integrated pipeline with this

module. For the downstream analysis, tools like diffcyt and CATALYST group markers into

phenotypic and state makers, enabling the detection of differentially abundant cell clusters

and differential expression of functional markers within each cell population[27]. This well-

recognised strategy has been extensively applied in various studies. But one limitation is that

it directly classifies cells into high-resolution clusters, and cannot automatically merge

subclusters into one major population with similar phenotypes[27]. Our pipeline addresses this

problem via a precise and convenient solution: using the semi-supervised classifier

(BinaryClust) of ImmCellTyper. The two pipelines (CATALYST and ImmCellTyper) are well

compatible, allowing users to leverage their functions together and providing a broader range

of analytical options. On the other hand, Cytofkit has the advantages of the graphical user

interface(GUI) for non-specialists, integration of a variety of clustering(DensVM[7], ClusterX,

FlowSOM, Phenograph), dimension reduction(PCA, ISOMAP, t-SNE) methods, and inference of

the relatedness among cell populations, but it does not support complex study design, group

comparison and statistical testing[19]. Several methods have been developed to fit with the

high-dimensional features of CyTOF data for differential analysis including diffcyt, CellCnn[30],

cydar[31], citrus[32], cyEMD[33] etc. Nonetheless, none of them is applicable to compare more than

two study groups at once which involves multiple testing. Therefore, to accommodate study

designs involving multiple groups, ImmCellTyper does statistics via first applying Kruskal

Wallis test, followed by Benjamin-Hochberg (BH) procedure for multiple testing correction

and post hoc analysis via Dunn's test or pairwise-Wilcoxon test. In cases where the

comparison involves only two groups, Mann-Whitney test will be applied in terms of cell

frequency, as the distribution of CyTOF data generally does not fit for normal distribution.

One limitation of this computational pipeline is that its semi-supervised cluster identification

may not be well-suited for the direct identification of specific subpopulations which are

defined by continuum markers. This is due to the method's reliance on the presumption that

makers are binary distributed. In addition, for users with general interest in charactering

subclusters of each main cell lineage, it can be laborious to first perform BinaryClust then

extract every population for unsupervised clustering. In such scenarios, BinaryClust can be

used in parallel with other clustering methods or pipelines like CATALYST. This allows users to

quickly obtain additional information about main cell types with the accuracy comparable to

manual gating.

In summary, we introduce a novel open-source R-implemented strategy and a versatile

toolbox for CyTOF data analysis. The future direction is to automate the data clean-up,

compensation, and bead normalisation steps. Additionally, we also aim to implement the

whole pipeline into Python, a more accessible programming language for bioinformatics

novices and biologists who wish to perform high-dimensional data analysis independently.

Materials and methods

BinaryClust

Most of the CyTOF markers exhibit log-normal or bi-modal distribution with zero inflation

after arcsinh transformation. Thus, we employ binary classification using k-means to group

cells into negative and positive populations(k=2) for each marker indicated in the user-

defined classification matrix. Here, k-means is an unsupervised clustering algorithm to cluster

the data based on the Euclidean distance among points, which is calculated by the formula

below:

469
$$d(p,q) = \sqrt{(p_1 - q_1)^2 + (p_2 - q_2)^2 + \cdots + (p_n - q_n)^2}$$

470 Then assign each data point into a cluster centroid which is denoted by c_i, and dist()is the

471 Euclidean distance:

$$arg \min_{ci \in C}(ci, x)^2$$

473 By aligning the k-means results with the user-designed classification matrix, cell populations

474 can be subsequently classified and annotated.

R package ImmCellTyper

This computational pipeline is implemented in the R package ImmCellTyper and publicly

available on Github (https://github.com/JingAnyaSun/ImmCellTyper). Instructions for package

installation and function usage can be found in the README file on the Github page. It is

recommended to first examine the unwanted non-biological variation across batches and

perform additional batch normalisation if necessary. Afterwards, import the data into the

second part of the pipeline for downstream analysis. Users are required to prepare all the FCS

files, sample metadata containing the details and grouping information of each sample, panel

metadata with the information of the antibody panel with metal tags used in the experiments,

and cell type classification matrix with phenotypic marker expression in a binary manner of

each cell lineage. All files need to be in the right format to use the pipeline.

ImmCellTyper workflow overview

ImmCellTyper pipeline is composed of seven steps corresponding to two separate sub-

pipelines, as described in Figure 8 and Github vignettes

(https://github.com/JingAnyaSun/ImmCellTyper/tree/main/vignettes):

(1) Sub-pipeline1 (corresponds to Figure 8, workflow step 2): Batch effects evaluation and

correction. Batch effects occur when samples were collected and measured at different sites

or time points, especially for large-scale studies. It is crucial to remove the unwanted variation

which might interfere the true biological differences. After bead normalisation and data

clean-up (Figure 8, workflow step 1), which can be performed using third-party platforms,

such as CyTOF v7.0 system control software and Cytobank, users can systematically examine

batch effects on two levels including marker behaviours and clustering results based on the

method introduced by Trussart et al.[29]If needed, CytoNorm and CytofRUV, which are well-

performing correction algorithms, can be used to align the existing batch effects.

(2) Sub-pipeline2 (corresponds to Figure 8, workflow step 3-7): semi-supervised classification,

differential analysis, and in-depth investigation. When data are cleaned and normalised, they

can be imported into the second part of the pipeline, constructed into a SingleCellExperiment

(SCE) object, and undergo semi-supervised classification to identify the major cell types and

test the differential frequencies or state marker expression among study groups. After that, if

the users have certain interests of specific cell types and pre-design the panel for that, or in

another circumstance, the initial statistics draw the user's attention into a certain cell type,

institutively, further clustering using unsupervised tools like flowSOM or Phenograph should

be conducted with an increased cluster resolution and deeper investigation for cell subsets,

after extracting the cell population of interest. ImmCellTyper pipeline has the same data

storage and infrastructure as CATALYST, therefore all the functions in CATALYST can be

seamlessly used in ImmCellTyper, tailored to user's analytical needs. We do not elaborate on

the basic functions of CATALYST, which can be found in the tutorial vignettes of the

package(https://github.com/HelenaLC/CATALYST).

Workflow steps	Description
Data clean-up and pre-processing	Bead normalisation is first performed on the raw FCS files to correct signal fluctuation of the CyTOF instrument, then FCS files are imported to cytobank for clean-up to exclude doublets and debris etc.
Batch effect evaluation and correction	Samples across different batches will be evaluated on both marker expression level and clustering level for batch effects; If needed, batch correction will be performed using function batchNorm, which provides two well-performing algorithms CytoNorm and CyTOFRUV.
Data transformation and SCE object construction	FCS files and relevant metadata for(samples and panel) will be integrated into one sce object, and FCS data will be transformed using co-factor 5.
Binary classification	BinaryClust will be subsequently performed based on the classification matrix designed by the user.
Differential analysis and population extraction	Differential cell abundance analysis and statistical comparison will be conducted. Then the user can quickly gate certain population of interest for down-stream in-depth analysis.
In-depth interrogation of population of interest	Unsupervised clustering such as flowSOM and Phenograph can be implemented for the extracted population for further clustering.
Differential analysis and statistical comparison	In this pipeline we support multiple study group statistical analysis(n>2) with multiple testing correction and post hoc analysis.

Figure 8 Overall schematic outline of the ImmCellTyper workflow with description for each step.

Batch correction algorithms

The batch effect correction algorithms embedded in the function of 'batchNorm' comprises

CytoNorm, as described by Van Gassen et al.[28] and CytofRUV by Trussart et al.[29]. Both

algorithms rely on anchors (reference samples/technical replicates) across batches to perform

normalisation. CytoNorm uses flowSOM clustering to first identify clusters prior to a

population-specific transformation on the reference samples by computing the quantile

values and aligning them with splines, whereas CytofRUV applies remove unwanted variation

III (RUV-III) to CyTOF data by estimating and eliminating the non-biological variation of the

pseudo-replicates.

Agreement evaluation

To assess the agreement among manual gating, BinaryClust classification and flowSOM

clustering, we used correlation, interaction plot and Bland-Altman analysis. Correlation

evaluates the relationship between two variables which doesn't mean concordance, but if

two methods agree, surely, they should be highly correlated. We compared the results of cell

population frequency generated by experts and BinaryClust using Pearson correlation,

calculated the correlation coefficient and P value, with the line of equality indicating perfect

agreement (red solid line, $R^2=1$) in the plots to help gauge the degree of agreement between

the two methods; Bland-Altman plot refers to a dot plot of the difference between two

variables(y-axis) against the mean of them(x-axis), as described by J.Martian Bland and

Douglas G. Altman in 1986, which represents a graphical magnitude of bias(average of

difference) with 95% confidence interval. The math formula for the limit of agreement is as

below:

$$\text{Limits of agreement} = \text{mean difference observed} \pm 1.96 \times \text{standard deviation}$$

We also used Interaction plot to display the interaction effects of the three methods including

manual gating, BinaryClust classification and flowSOM clustering on the measurement of cell

frequencies to evaluate the agreement.

F-measure

F-measure is a method to assess the accuracy of the clustering method compared to gold

standard, which is manual gating results in this study. It stands for the harmonic mean of the

precision and recall values, which can be calculated using below formula:

$$F - measure \ = \ 2x \ \frac{Precision \ \times \ Recall}{Precison \ + \ Recall}$$

Here, precision represents the positive predictive value: the proportion of true positive

instances divided by the instances classified as positive by the clustering algorithm; recall

evaluates the sensitivity, which is the number of true positive events correctly identified by

the algorithm among all events that belong to the cluster. F-measure ranges from 0 to 1,

where 1 suggests perfect performance and 0 indicates poor precision and recall.

Adjusted Rand Index

Adjusted rand index is a widely used method to measure the similarity between two

clustering results. We used it to assess the agreement between test clustering algorithm and

the gold standard labels which is derived from manual gating. ARI is defined as the following

formula based on a contingency matrix (where n_{ij}, a_i, b_j are values from the contingency table):

$$ARI = \frac{\sum_{ij}\binom{n_{ij}}{2} - \left[\sum_i\binom{a_i}{2}\sum_j\binom{b_j}{2}\right] \big/ \binom{n}{2}}{\frac{1}{2}\left[\sum_i\binom{a_i}{2} + \sum_j\binom{b_j}{2}\right] - \left[\sum_i\binom{a_i}{2} + \sum_j\binom{b_j}{2}\right] \big/ \binom{n}{2}}$$

567
568

ARI ranges from -1 to 1, with 1 indicates a perfect match, 0 means not relevant, and -1

indicates complete mismatch between two clustering results.

Differential analysis

In order to perform the differential analysis of cell abundances and state marker expression

amongst study groups, we consider the number of study groups into two conditions in

function 'StatTest': 1) n=2, Mann-Whitney Wilcoxon analysis will be applied as cell

frequency/marker expression doesn't fit normal distribution; 2) n=3, Kruskal- Wallis test will

be first performed followed by multiple testing correction using BH procedure and post-hoc

analysis(Dunn's test or pairwise Wilcoxon test).

Sample collection and preparation for CyTOF

PBMC samples from MPN patients were requested and obtained from biobank at Guy's

Hospital, under a protocol approved by the KCL Biobank Access Committee (REC18/EE/0025).

Healthy volunteers were recruited at Guy's hospital with informed consent and ethical

approval by King's College Research Ethics Committee (HR-17/18-5960 MOD-20/21-5960) in

accordance with the Declaration of Helsinki. All identifiable information of study participants

were securely stored in a trusted research environment managed by members of the team.

Venous blood samples from healthy volunteers were collected in BD vacutainer EDTA tubes,

and PBMCs were isolated and purified using Ficoll-Hypaque density gradient centrifugation. In

brief, blood was carefully layered onto Ficoll and spined at 460g for 20 minutes at room

temperature (RT) without brake; Upon observing a clear separation of blood components,

PBMCs were then carefully isolated and washed three times with RPMI 1640 medium to

remove other contaminants. Subsequently, the purified PBMCs were cryopreserved in liquid

nitrogen at a density of 1×10^7 cells per vial.

CyTOF Antibody staining

Cryopreserved cells were quickly thawed at 37°C in water bath, suspended in pre-warmed

RPMI 1640 medium, washed three times, and underwent Fc-blocking using human TruStain

FcX (Biolegend) for 10 mins at RT. Given that the antibody panel employs indirect detection of

CD95 using anti-CD95-APC and anti-APC-106Cd, cells were initially stained with anti-CD95-APC

for 30 minutes in a dark place, followed by two washes with 2ml cell staining buffer (CSB).

After the removal of supernatant, cells were resuspended in 300μl CSB and transferred into

the dip tube containing lyophilized antibody mix of Maxpar direct immune profiling assay

(MDIPA, Standard BioTools). Additional antibodies used to study T cell activation, migration,

and exhaustion status (anti-TIM3, anti-PD-1, anti-ICOS, anti-TIGIT, anti-OX40) were also added.

Cells were incubated with the antibody mix for 30 mins at RT in compliance with

manufacturer's instructions, washed twice and fixed using a freshly prepared 1.6%

paraformaldehyde (PFA, Thermo Fisher Scientific) solution for 10 mins at RT. In the end, cells

were washed with CSB twice to remove residual PFA and stained with 125nM Cell-ID

intercalator-Iridium in 1 ml Maxpar Fix and Perm Buffer (Standard BioTools) overnight at 4°C.

The stained cells were frozen down using freezing media (fetal bovine serum containing 10%

DMSO) and stored at -80°C freezer before data acquisition.

On the day for CyTOF acquisition, cryopreserved samples were thawed, washed twice with

1ml CSB, followed by additional two washes with 1ml cell acquisition solution (CAS, Standard

BioTools), and centrifuged at 800g for 5 minutes. Cells were then filtered through a 40 μm cell

strainer to avoid blockage and cell count was determined by Countess automated cell counter

(Invitrogen). EQ four-element calibration beads (Standard BioTools) were added to a final

concentration of $0.5x10^6$ cells/ml to adjust signal fluctuation of the instrument. CyTOF

acquisition was performed on Helios mass cytometer system. For each batch of cell staining

and run, technical replicates from the same healthy donor were included to evaluate and

correct batch effects.

The full antibody panel including the metal tag, clone, and supplier is listed in Supplementary

Table 1.

CyTOF data pre-processing

FCS files were first processed for bead normalisation using CyTOF v7.0 system control

software (Standard BioTools) to correct signal drift during acquisition. Subsequently, the files

were imported into Cytobank (Cytobank Inc.) for data cleaning, with a detailed procedure

illustrated in Supplementary Figure 6. The aim is to remove non-events including debris,

doublets, normalisation (EQ) beads and other undesired events like dead cells. The CD45+ cell

population was pre-gated using Cytobank for down-stream analysis.

Manual gating

Manual gating for major cell populations was performed using Cytobank platform, and

gatingML files were exported and converted into gatingSet object to extract labels of each cell

via the R packages flowWorkspace, openCyto and CytoML. These data were used as reference

for benchmarking computer-aided algorithms.

Dataset availability

In this study, we tested ImmCellTyper pipeline on the MPN cohort with 7 MPN patients and 2 healthy volunteers, influenza cohort with 11 patients and the COVID-19 cohort with 59 COVID-19 patients and 23 healthy volunteers. The FCS files (after clean-up and gating of CD45 population) and metadata of the MPN cohort were deposited in Zenodo (doi: 10.5281/zenodo.10076940); The influenza cohort was published by our lab[21], and the data were stored in Zenodo (doi: 10.5281/zenodo.7982165); The COVID-19 dataset was previously published by Chevrier et al.[22], and the FCS files can be retrieved from Mendeley Data (https://data.mendeley.com/datasets/vyy8ttw7n9/1).

Author contributions

Jing Sun, Conceptualization, Data curation, Software, Formal analysis, Supervision, Validation, Visualisation, Methodology, Writing – original draft, Writing – review and editing, Resources, Experiments; Desmond Choy, Conceptualization, Software, Supervision, Methodology, Resources, Investigation; Nicolas Sompairac, Technical supervision, Resources, Data curation, Writing – review and editing; Shirin Jamshidi, Technical supervision, Resources, Writing – review and editing; Shahram Kordasti, Conceptualization, Resources, Funding acquisition, Supervision, Writing – review and editing, Project administration; Michele Mishto: Writing – review and editing

Competing interests

The authors declare that there are no competing interests exist.

Acknowledgement

This work is supported in part by: Blood Cancer UK [Ref. 22009] and CRUK City of London Centre (CoL) Award [CTRQQR-2021/100004] to MM and SK; JS was supported by the K-CSC scholarship.

We thank BRC flowCore at Guy's Hospital for technical support, Biobank at King's College

London for patient samples; We are thankful for Cynthia Bishop, Katrina Todd, Rosa Andres

Ejarque, Elena Torre, Robert Page, Rita Antunes Dos Reis and Mishto lab members at King's

College London, Daniel Dancer, Thomas Adejumo at Standard Biotools for technical assistance

and sample management, as well as all study participants for their kind support for this

research. Special thanks to Eliezer Van Allen and Jihye Park at Dana Farber Cancer Institute to

review and comment this work.

References

1. Spitzer, M.H., and Nolan, G.P. (2016). Mass Cytometry: Single Cells, Many Features.
Cell *165*, 780-791. 10.1016/j.cell.2016.04.019.
2. Kimball, A.K., Oko, L.M., Bullock, B.L., Nemenoff, R.A., van Dyk, L.F., and Clambey, E.T.
(2018). A Beginner's Guide to Analyzing and Visualizing Mass Cytometry Data. J
Immunol *200*, 3-22. 10.4049/jimmunol.1701494.
3. Van Gassen, S., Callebaut, B., Van Helden, M.J., Lambrecht, B.N., Demeester, P.,
Dhaene, T., and Saeys, Y. (2015). FlowSOM: Using self-organizing maps for
visualization and interpretation of cytometry data. Cytometry A *87*, 636-645.
10.1002/cyto.a.22625.
4. Levine, J.H., Simonds, E.F., Bendall, S.C., Davis, K.L., Amir el, A.D., Tadmor, M.D., Litvin,
O., Fienberg, H.G., Jager, A., Zunder, E.R., et al. (2015). Data-Driven Phenotypic
Dissection of AML Reveals Progenitor-like Cells that Correlate with Prognosis. Cell *162*,
184-197. 10.1016/j.cell.2015.05.047.
5. Samusik, N., Good, Z., Spitzer, M.H., Davis, K.L., and Nolan, G.P. (2016). Automated
mapping of phenotype space with single-cell data. Nat Methods *13*, 493-496.
10.1038/nmeth.3863.
6. Qiu, P., Simonds, E.F., Bendall, S.C., Gibbs, K.D., Jr., Bruggner, R.V., Linderman, M.D.,
Sachs, K., Nolan, G.P., and Plevritis, S.K. (2011). Extracting a cellular hierarchy from
high-dimensional cytometry data with SPADE. Nat Biotechnol *29*, 886-891.
10.1038/nbt.1991.
7. Becher, B., Schlitzer, A., Chen, J., Mair, F., Sumatoh, H.R., Teng, K.W.W., Low, D., Ruedl,
C., Riccardi-Castagnoli, P., Poidinger, M., et al. (2014). High-dimensional analysis of the
murine myeloid cell system. Nature Immunology *15*, 1181-1189. 10.1038/ni.3006.
8. van der Maaten, L., and Hinton, G. (2008). Viualizing data using t-SNE. Journal of
Machine Learning Research *9*, 2579-2605.
9. McInnes, L., and Healy, J. (2018). UMAP: Uniform Manifold Approximation and
Projection for Dimension Reduction. ArXiv e-prints *1802.03426*.
10. Liu, X., Song, W., Wong, B.Y., Zhang, T., Yu, S., Lin, G.N., and Ding, X. (2019). A
comparison framework and guideline of clustering methods for mass cytometry data.
Genome Biology *20*, 297. 10.1186/s13059-019-1917-7.
11. Abdelaal, T., van Unen, V., Höllt, T., Koning, F., Reinders, M.J.T., and Mahfouz, A.
(2019). Predicting Cell Populations in Single Cell Mass Cytometry Data. Cytometry A.
10.1002/cyto.a.23738.

12. Cheng, L., Karkhanis, P., Gokbag, B., Liu, Y., and Li, L. (2022). DGCyTOF: Deep learning
with graphic cluster visualization to predict cell types of single cell mass cytometry
data. PLOS Computational Biology *18*, e1008885. 10.1371/journal.pcbi.1008885.

13. Kaushik, A., Dunham, D., He, Z., Manohar, M., Desai, M., Nadeau, K.C., and Andorf, S.
(2021). CyAnno: a semi-automated approach for cell type annotation of mass
cytometry datasets. Bioinformatics *37*, 4164-4171. 10.1093/bioinformatics/btab409.

14. Li, H., Shaham, U., Stanton, K.P., Yao, Y., Montgomery, R.R., and Kluger, Y. (2017).
Gating mass cytometry data by deep learning. Bioinformatics *33*, 3423-3430.
10.1093/bioinformatics/btx448.

15. Lee, H.C., Kosoy, R., Becker, C.E., Dudley, J.T., and Kidd, B.A. (2017). Automated cell
type discovery and classification through knowledge transfer. Bioinformatics *33*, 1689-
1695. 10.1093/bioinformatics/btx054.

16. Zhang, Z., Luo, D., Zhong, X., Choi, J.H., Ma, Y., Wang, S., Mahrt, E., Guo, W., Stawiski,
E.W., Modrusan, Z., et al. (2019). SCINA: A Semi-Supervised Subtyping Algorithm of
Single Cells and Bulk Samples. Genes (Basel) *10*. 10.3390/genes10070531.

17. Nowicka, M., Krieg, C., Crowell, H.L., Weber, L.M., Hartmann, F.J., Guglietta, S., Becher,
B., Levesque, M.P., and Robinson, M.D. (2017). CyTOF workflow: differential discovery
in high-throughput high-dimensional cytometry datasets. F1000Res *6*, 748.
10.12688/f1000research.11622.3.

18. Marsh-Wakefield, F., Kruzins, A., McGuire, H.M., Yang, S., Bryant, C., Fazekas de St
Groth, B., Nassif, N., Byrne, S.N., Gibson, J., Brown, C., et al. (2019). Mass Cytometry
Discovers Two Discrete Subsets of CD39(-)Treg Which Discriminate MGUS From
Multiple Myeloma. Front Immunol *10*, 1596. 10.3389/fimmu.2019.01596.

19. Chen, H., Lau, M.C., Wong, M.T., Newell, E.W., Poidinger, M., and Chen, J. (2016).
Cytofkit: A Bioconductor Package for an Integrated Mass Cytometry Data Analysis
Pipeline. PLoS Comput Biol *12*, e1005112. 10.1371/journal.pcbi.1005112.

20. Opzoomer, J.W., Timms, J.A., Blighe, K., Mourikis, T.P., Chapuis, N., Bekoe, R.,
Kareemaghay, S., Nocerino, P., Apollonio, B., Ramsay, A.G., et al. (2021).
ImmunoCluster provides a computational framework for the nonspecialist to profile
high-dimensional cytometry data. Elife *10*. 10.7554/eLife.62915.

21. Alimam, S., Ann Timms, J., Harrison, C.N., Dillon, R., Mare, T., DeLavallade, H., Radia,
D., Woodley, C., Francis, Y., Sanchez, K., et al. (2021). Altered immune response to the
annual influenza A vaccine in patients with myeloproliferative neoplasms. Br J
Haematol *193*, 150-154. 10.1111/bjh.17096.

22. Chevrier, S., Zurbuchen, Y., Cervia, C., Adamo, S., Raeber, M.E., de Souza, N.,
Sivapatham, S., Jacobs, A., Bachli, E., Rudiger, A., et al. (2021). A distinct innate
immune signature marks progression from mild to severe COVID-19. Cell Rep Med *2*,
100166. 10.1016/j.xcrm.2020.100166.

23. Liu, P., Liu, S., Fang, Y., Xue, X., Zou, J., Tseng, G., and Konnikova, L. (2020). Recent
Advances in Computer-Assisted Algorithms for Cell Subtype Identification of
Cytometry Data. Front Cell Dev Biol *8*, 234. 10.3389/fcell.2020.00234.

24. Aghaeepour, N., Nikolic, R., Hoos, H.H., and Brinkman, R.R. (2011). Rapid cell
population identification in flow cytometry data. Cytometry A *79*, 6-13.
10.1002/cyto.a.21007.

25. Theorell, A., Bryceson, Y.T., and Theorell, J. (2019). Determination of essential
phenotypic elements of clusters in high-dimensional entities-DEPECHE. PLoS One *14*,
e0203247. 10.1371/journal.pone.0203247.

26. O'Brien Gore, C., Billman, A., Hunjan, S., Colebrook, J., Choy, D., Li, W., Haynes, J.,
Wade, J., Hobern, E., McDonald, L., et al. (2023). Pre-treatment with systemic agents
for advanced NSCLC elicits changes in the phenotype of autologous T cell therapy
products. Mol Ther Oncolytics *31*, 100749. 10.1016/j.omto.2023.100749.
27. Weber, L.M., Nowicka, M., Soneson, C., and Robinson, M.D. (2019). diffcyt: Differential
discovery in high-dimensional cytometry via high-resolution clustering.
Communications Biology *2*, 183. 10.1038/s42003-019-0415-5.
28. Van Gassen, S., Gaudilliere, B., Angst, M.S., Saeys, Y., and Aghaeepour, N. (2020).
CytoNorm: A Normalization Algorithm for Cytometry Data. Cytometry A *97*, 268-278.
10.1002/cyto.a.23904.
29. Trussart, M., Teh, C.E., Tan, T., Leong, L., Gray, D.H., and Speed, T.P. (2020). Removing
unwanted variation with CytofRUV to integrate multiple CyTOF datasets. Elife *9*.
10.7554/eLife.59630.
30. Arvaniti, E., and Claassen, M. (2017). Sensitive detection of rare disease-associated cell
subsets via representation learning. Nature Communications *8*, 14825.
10.1038/ncomms14825.
31. Lun, A.T.L., Richard, A.C., and Marioni, J.C. (2017). Testing for differential abundance in
mass cytometry data. Nat Methods *14*, 707-709. 10.1038/nmeth.4295.
32. Bruggner, R.V., Bodenmiller, B., Dill, D.L., Tibshirani, R.J., and Nolan, G.P. (2014).
Automated identification of stratifying signatures in cellular subpopulations. Proc Natl
Acad Sci U S A *111*, E2770-2777. 10.1073/pnas.1408792111.
33. Arend, L., Bernett, J., Manz, Q., Klug, M., Lazareva, O., Baumbach, J., Bongiovanni, D.,
and List, M. (2022). A systematic comparison of novel and existing differential analysis
methods for CyTOF data. Briefings in Bioinformatics *23*, bbab471.
10.1093/bib/bbab471.
792

Supplementary Figures

Supplemental Figure 1

Supplementary Figure 1 Manual hierarchical gating strategy for main cell linages from human PBMC

samples (MPN dataset, n=9). All .FCS files were cleaned up to remove doublets, normalisation beads

and debris (please refer to the methods for standard clean-up procedure), and pre-gated for CD45+

leukocytes. (A) Serial bi-axial scatter plots representing the gating diagram for T cell subsets (CD4 T

cells, CD8 T cells and gamma-delta T cells), NK cells and dendritic cells based on the indicated

phenotypic markers; (B) Serial bi-axial scatter plot indicating the gating strategy to isolate monocytes

and B cells from leukocytes. All manual gating was done using Cytobank

platform(https://premium.cytobank.org/cytobank/).

Supplementary Figure 2

806
Supplementary Figure 2 Agreement evaluation between ImmCellTyper and manual gating in influenza

dataset(n=11). Manual gating was performed using Cytobank and exported manually. (A) Correlation

plots between ImmCellTyper results and manual gating results concerning percentages in CD4 T cells,

Gamma Delta T cells, dendritic cells, NK cells, CD8 T cells and B cells, with red line indicating perfect

agreement (correlation coefficient =1); (B)Bland-Altman plots of the two measurements in the

indicated populations, with black line suggesting mean difference between measurements and dotted

red line indicating limits of agreement (1.96 x standard deviations). (C) Calculation of precision, recall,

F-measure for ImmCellTyper method in comparison to manual gating in the indicated cell populations.

Supplementary Figure 3

816 **Supplementary Figure 3** Boxplots of the indicated cell percentages generated by different methods.

817 Statistical significance was marked by asterisk. * P<0.05, **P<0.01, ***P<0.001.

Supplementary Figure 4

Supplementary Figure 4 (A) UMAP plots of normalized expression of indicated markers (CD66b,

HLADR, TCRgd, CD20, CD16, CD161) across 2000 cells per sample in MPN dataset;(B) FlowSOM

clustering was performed on the same dataset to compare with BinarClust, k=20 was chosen followed

by manual annotation of each cluster. UMAP plot was projected with merged flowSOM clusters with

biological annotation (downsample 2000 cells per sample) ;(B) The corresponding median marker

expression heatmap after flowSOM clustering and annotation.

Supplementary Figure 5

826 **Supplementary Figure 5** Marker expression heatmap of (A)monocytes and (B) neutrophils generated

827 by Phenograph clustering.

Supplementary Figure 6

830 **Supplementary Figure 6** Clean-up procedure of CyTOF data using Cytobank.

Supplementary Table 1 CyTOF antibody panel for MPN cohort

Antibody	Clone	Metal tag	Manufacturer
Anti-CD45	HI30	89Y	Standard BioTools
Live/dead Indicator	N/A	103Rh	Standard BioTools
Anti-CD95	DX2	APC	Biolegend
Anti-APC	APC003	106Cd	Standard BioTools
Anti-CD196	G034E3	141Pr	Standard BioTools
Anti-OX40	ACT35	142Nd	Standard BioTools
Anti-CD123	6H6	143Nd	Standard BioTools
Anti-CD19	HIB19	144Nd	Standard BioTools
Anti-CD4	RPA-T4	145Nd	Standard BioTools
Anti-CD8a	RPA-T8	146Nd	Standard BioTools
Anti-CD11c	Bu15	147Sm	Standard BioTools
Anti-CD16	3G8	148Nd	Standard BioTools
Anti-CD45RO	UCHL1	149Sm	Standard BioTools
Anti-CD45RA	HI100	150Nd	Standard BioTools
Anti-CD161	HP-3G10	151Eu	Standard BioTools
Anti-CD194	L291H4	152Sm	Standard BioTools
Anti-CD25	BC96	153Eu	Standard BioTools
Anti-CD27	O323	154Sm	Standard BioTools
Anti-CD57	HCD57	155Gd	Standard BioTools
Anti-CD183	G025H7	156Gd	Standard BioTools
Anti-CD185	J252D4	158Gd	Standard BioTools
Anti-TIM-3	F38-2E2	159Tb	Standard BioTools
Anti-CD28	CD28.2	160Gd	Standard BioTools
Anti-CD38	HB-7	161Dy	Standard BioTools
Anti-CD56	NCAM16.2	163Dy	Standard BioTools
Anti-TCRgd	B1	164Dy	Standard BioTools
Anti-PD-1	EH12.2H7	165Ho	Standard BioTools
Anti-CD294	BM16	166Er	Standard BioTools
Anti-CD197	G043H7	167Er	Standard BioTools
Anti-CD14	63D3	168Er	Standard BioTools
Anti-ICOS	C398.4A	169Tm	Standard BioTools
Anti-CD3	UCHT1	170Er	Standard BioTools
Anti-CD20	2H7	171Yb	Standard BioTools

Anti-CD66b	G10F5	172Yb	Standard BioTools 836
Anti-HLA-DR	LN3	173Yb	Standard BioTools
Anti-IgD	IA6-2	174Yb	Standard BioTools
Anti-CXCR4	12G5	175Lu	Standard BioTools
Anti-CD127	A019D5	176Yb	Standard BioTools
Anti-TIGIT	MBSA43	209Bi	Standard BioTools