# Sensory choices as logistic classification

Matteo Carandini, University College London

## Summary

**Logistic classification is a simple way to make choices based on a set of factors: give each factor a weight, sum them, and use the result to set the log odds of a random draw. This operation is known to describe human and animal choices based on value (economic decisions). There is increasing evidence that it also describes choices based on sensory inputs (perceptual decisions). Here I briefly review this evidence and I fit data from multiple studies in multiple species to show that logistic classification can describe a variety of choices. These include sensory choices influenced by stimuli of other modalities (multisensory integration) or by non-sensory factors such as value and recent history. Logistic classification is the optimal strategy if factors are independent of each other, and a useful heuristic in other conditions. Using it to describe sensory choices is useful to characterize brain function and the effects of brain inactivations.**

## Introduction

Many situations require choosing between two or more options based on a set of factors. For instance, in a choice is between walking and driving, the factors may include distance, traffic, chance of rain, cost of fuel, and ease of parking[1]. If the choice is to reach for a berry vs. move to the next bush, the factors may include ripeness, hunger, and ease of reach. How does the brain combine these diverse factors to make a choice?

A large body of research indicates that the brain makes these choices by logistic classification: perform a weighted sum of the factors, use the result to set the (log) odds of a coin, and toss that coin (Figure 1**a**). This approach also works for choices between more than two options (where the coin is replaced by a die, **Box 1**). Logistic classification was invented by multiple statisticians in the secrecy surrounding the Second World War[2]. Three decades later, it was linked to economics and to the theory of choice from mathematical psychology[1]. Since then, it has become a workhorse of statistics and of machine learning[3], and has been found to characterize value-based decisions by humans and animals[4-7] and the corresponding brain activity[5], suggesting that it was discovered by evolution before it was discovered by statisticians.

There is increasing evidence that logistic classification can describe not only choices based on considerations of value (economic decisions) but also choices based on sensory input[2,8,9] (perceptual decisions) and

on additional factors. These factors include trial history[10-20], disparities in value[5-7], brain manipulations such as local inactivations[21-23], and the integration of multiple sensory modalities[24] (multisensory integration).

Here I will briefly review this evidence, and I will argue that logistic classification is an effective description of results that had been analyzed with a different framework (Signal Detection Theory, **Box 2**). I will show that it is an optimal strategy in many conditions, and a useful heuristic in others, perhaps explaining why it is widely implemented by the brains of multiple species.

## Sensory choices between two alternatives

When a choice involves only two alternatives, logistic classification has a particularly simple description (Figure 1**a**). First, give each of the relevant factors $x_1, x_2, \ldots, x_n$ a weight $w_1, w_2, \ldots, w_n$. Second, sum the weighted factors to obtain a *decision variable*

$$z = w_1 x_1 + w_2 x_2 + \cdots + b \qquad \text{Eq. 1}$$

Third, use that decision variable to bias a coin, i.e., to set the probability $p$ that it will return Heads. Specifically, use it as the *log odds* of drawing Heads:

$$\log\left(\frac{p}{1-p}\right) = z \qquad \text{Eq. 2}$$

Fourth, flip the coin.

*Figure 1. **Logistic classification describes sensory choices between two alternatives in monkeys.** **a** Diagram of logistic classification, in the case of 3 factors $x_1$, $x_2$, and $x_3$. **b**. The logistic sigmoid, plotting probability of a choice vs. decision variable. **c**. The logistic sigmoid becomes a line when plotting the odds (in logarithmic scale) vs. the decision variable. **d** A monkey performing the random dots task, indicating whether most dots move Left or Right. **e**. Performance of a monkey performing the task, showing probability of Right choices as a function of coherence (negative for leftward motion, positive for rightward motion). Data were taken from Ref.[9] using a data grabber (grabit.m). Curve shows fit of the logistic classification model. **f** Same data and fit, in log odds.*

This simple process can be written as a single equation (Figure 1**a**):

$$p = \sigma(z) = \sigma(w_1 x_1 + w_2 x_2 + \cdots + b) \qquad \text{Eq. 3}$$

where the function $\sigma(z)$ is the *logistic sigmoid* $\sigma$ (Figure 1**b**)

$$\sigma(z) = \frac{1}{1 + \exp(-z)} \qquad \text{Eq. 4}$$

In statistics, these equations are often used for "logistic regression", i.e. to find the weights $w_1, w_2, \ldots$ and bias $b$ that best relate a matrix of factors $x_1, x_2, \ldots$ to a vector of binary outcomes[3]. The outcomes may be whether births were caesarean[25], loans ended in default, patients had heart attacks, or emails were spam.

We are here interested in the reverse: using the weights as given, to classify a new observation of the factors and thus make a choice. This is best called "logistic classification"[3].

Though it is simple, logistic classification can do an excellent job at summarizing perceptual decisions, for example those made by monkeys in a classic task that probes motion perception. In this task, a monkey views moving dots and estimates whether most of them move Left or Right (Figure 1**d**). The experimenter controls the coherence of the dots, defined as positive if most dots move to the Right and negative if most move to the Left. The psychometric curve, i.e., the probability of Right choices as a function of coherence $x$ can then be fit with a logistic classification model[8,9]:

$$z = Wx + B \qquad \text{Eq. 5}$$

With two free parameters ($W$ and $B$) the model describes accurately how nine values of coherence $x$ determine nine probabilities of choosing Right (Figure 1**e**). Indeed, the logarithms of the odds of the monkey's choices as a function of coherence fall neatly on a line (Figure 1**f**).

## Sensory choices influenced by priors

Making perceptual decisions according to logistic classification is advantageous, because it is the only procedure that accords to Bayes' rule for putting together sensory information with estimates of prior probabilities. To see this, consider a task where a stimulus is on the Left or the Right ($L$ or $R$) with probabilities $P(L)$ and $P(R)$. If an observer receives a sensory input $s$ about the position of the stimulus, the best it can do is to say that the stimulus is on the Right with probability $p = P(R|s)$, the probability that the stimulus $s$ is indeed on the Right. By Bayes' rule, this probability is

$$p = P(R|s) = P(s|R)\, P(R)\, /\, P(s) \qquad \text{Eq. 6}$$

Therefore, the odds that the observer chooses Right are the product of two terms: one that depends on the sensory stimulus (posterior odds) and one that does not (prior odds):

$$\frac{p}{1-p} = \frac{P(R|s)}{P(L|s)} = \frac{P(s|R)}{P(s|L)}\frac{P(R)}{P(L)} \qquad \text{Eq. 7}$$

Taking the logarithm of both sides yields a sum of two terms:

$$\begin{aligned} z &= \log\left(\frac{p}{1-p}\right) \\ &= \log\frac{P(s|R)}{P(s|L)} + \log\frac{P(R)}{P(L)} = f(s) + B \end{aligned} \qquad \text{Eq. 8}$$

In other words, if an observer follows Bayes rule, its decision variable is simply the sum of a function of the stimulus and a constant bias,

$$z = f(s) + B \qquad \text{Eq. 9}$$

where the bias is equal to the log prior odds: $B = \log(P(R)/P(L))$. If the rewards for the two sides are equal, this strategy maximizes the overall reward (see Appendix for proof).

In some lucky cases, $f(s)$ is simply the measure of stimulus strength used in the laboratory. For example, for moving dots the strength is typically measured by their coherence $x$ (with different signs for different directions) and one gets excellent fits[9] by setting $f(x) = Wx$ as in Eq. 5 (Figure 1**d**-**f**). In other cases, however, it can be useful to allow a nonlinear deformation of stimulus strength $x$[10,21], for example via a power nonlinearity $f(x) = Wx^q$ where both the weight $W$ and the exponent $q$ are fit to the data[22]. If $x$ can be negative, it's important to maintain its sign, yielding $f(x) = W\, sign(x)|x|^q$.

These considerations lead to a prediction: that an observer should adjust its bias $B$ (and only the bias) in accordance with the prior probability of the stimuli appearing Left vs. Right. The observer may not be able to estimate true prior probabilities and may set the bias to a higher or lower level than the optimal, but should adjust it at least roughly to that level.

This prediction is verified in humans performing a biased motion discrimination task: if the odds of a stimulus going rightward $p(R)/p(L)$ are 80:20 instead of 50:50 (Figure 2**a**), the observers make more Right choices[26] especially at zero coherence, when the visual stimulus is uninformative (Figure 2**b**). This shift is captured by the logistic classification model (Eq. 5) with the same weight $W$ as the 50:50 case but a larger value of the bias $B$ (Figure 2**b**). The log odds of the choices still fall on a line, and this line is displaced from the 50:50 case (Figure 2**c**).

Analogous results are seen in mice that perform a biased position discrimination task[20] (Figure 2**d**). In this experiment, stimuli are divided in blocks having higher probability on the Left (80:20) or on the Right (20:80). As expected from a Bayesian observer, the psychometric curves measured in the two blocks are displaced from each other (Figure 1**e,f**), such that at zero contrast (when there was no visual stimulus) Right choices were more likely in 20:80 blocks and Left choices more likely in 80:20 blocks. The model (Eq. 5) captures this difference by giving the bias $B$ a positive value in the 20:80 block and a negative value in the 80:20 block, with no changes in the sensory weight $W$.

*Figure 2. **Logistic classification describes choices based on stimulus attributes and probability in monkeys and mice**. **a** A random dots task where a human is told that rightward motion is more likely than leftward motion (blue) or that they are equally likely (gray). **b** Data from an observer showing that probability of choosing Right depends not only on stimulus coherence (abscissa) but also on prior probability (blue vs. gray). Data grabbed from Ref.[26]. Curves show fit of the logistic classification model with same weight w but two different values for the bias b. **c** The same data and curves plotted as odds of choosing Right vs. Left, in logarithmic scale. **d-f** Same, for a mouse indicating whether a visual stimulus appears on the Left or the Right, presented in alternating blocks where Left was more likely (red) or less likely (blue) than Right. Data grabbed from Ref.[20].*

## Sensory choices without evidence

In the absence of sensory evidence, the data presented above exhibit the well-known phenomenon of "probability matching". This phenomenon was demonstrated in non-sensory tasks in multiple species and settings[6,7,27-34]: the probabilities of the observer's choices tend to match the probabilities of those choices being correct. For instance, at zero coherence the human in the 20:80 motion task chose Right with probability close to 0.8 (Figure 2**b**). At zero contrast the mouse in the position task showed a similar tendency though (as is common[7,35]) not as pronounced (Figure 2**e**).

This phenomenon is puzzling because it is suboptimal[28,31]. Indeed, in the absence of evidence, the observer would obtain more rewards by always guessing Right if $P(R) > P(L)$ and always guessing Left otherwise.

The observer, however, does not know that some trials have no evidence. It may thus opt to apply logistic classification (Eq. 8) to all trials. This strategy produces probability matching: if the evidence $s$ is absent or irrelevant, then $f(s) = \log(P(s|R)/P(s|L)) = 0$), yielding

$$p = \sigma\left(\log\frac{P(R)}{P(L)}\right) = \sigma\left(\sigma^{-1}(P(R))\right) = P(R)$$ 

Eq. 10

In other words, if the stimulus is absent or uninformative, the observer makes random choices with probabilities that match the probabilities of those choices being correct.

This derivation suggests a general reason for probability matching beyond sensory choices: the participants use logistic classification as a heuristic, as if there were a correct answer that can be inferred from evidence (present or past stimuli, actions, outcomes, etc) even when this evidence is irrelevant. Indeed, human observers stop performing probability matching if they understand that they are gambling, i.e. guessing an independent random variable[31]. In that case, they turn to the optimal strategy: always choosing the option that is more likely to be rewarded.

## Sensory choices influenced by value

Logistic classification is also the ideal method to combine sensory inputs with considerations of value. In the experiments we examined up to here, the rewards for correct Left and Right choices were the same, and if the probabilities of the Left and Right stimuli were equal, the strategy that maximizes reward is to set the bias $B$ in Eq. 5 to a value close to zero. In general, however, the rewards, $V_L$ and $V_R$, could differ. In that case, one can prove (see Appendix) that the ideal bias $B$ is the logarithm of their ratio:

$$z = Wx + \log\frac{V_R}{V_L} \qquad \text{Eq. 11}$$

In the absence of sensory stimuli, therefore, an optimal logistic classifier should engage in "value matching": it should make a fraction of Right choices that matches the ratio of Right rewards to total rewards. Indeed, if $x = 0$ the probabilities of Right choices should be $p_0 = \sigma(\log(V_R/V_L)) = V_R/(V_R + V_L)$.

There is ample evidence that the brain follows this strategy when making purely economic decisions[5], even though it would yield more reward to always choose the option with higher value. Once again, logistic classification could be the reason for this behavior: the brain may assume that there is relevant evidence $x$ to guide the choice even when there isn't any, so it may obey Eq. 11 even when it is not optimal.

Indeed, the optimal logistic classifier (Eq. 11) correctly describes how observers in multiple species combine sensory signals with considerations of value. In humans performing a position discrimination task

(Figure 3**a**), the psychometric curves exhibit more Right choices when the reward ratio is in favor of Right choices, and more Left choices when it is the other way around[36]. The data are well fit by the logistic classification model (Eq. 5) with a single sensory gain $W$ and different biases $B$ in the two reward conditions (Figure 3**b**). Once again, the impact of stimulus and value are easiest to judge when the data are replotted in terms of log odds (Figure 3**c**): changing the stimulus moves the point along a line, and changing the reward ratios moves the point to a parallel line. Similar results are seen in monkeys doing the random dot motion task (Figure 3**d-f**)[37], and in mice performing the position discrimination task (Figure 3**g-i**)[38]. In all these cases the logistic classification model (Eq. 5) was fit with a single sensory gain $W$ and different biases $B$ in the two reward conditions, and the biases in the two conditions differed by at least as much as predicted by optimality (Eq. 11). In fact, the changes in bias were generally larger than optimal[39], perhaps because of a nonlinear utility scale that disproportionally favors large rewards[5,40].

More generally, logistic classification indicates how one should combine sensory signals and relative reward with relative probability. In the experiments considered above (Figure 3), only the values of Left and Right stimuli were unequal, while their probabilities, $p_L$ and $p_R$, remained equal. If these probabilities differ, then the optimal strategy is to choose a bias $B = \log(p_R/p_L) + \log(V_R/V_L)$. This expression shows how the logarithm of the odds provides a "natural currency for trading off sensory information, prior probability and expected value"[8].

Logistic classification can also capture the effects of changing other task variables. For instance, in an experiment measuring rate discrimination in rats, changes in the ratio of rewards were yoked to changes in the total available reward[23]. Logistic classification provides good fits to those data (Supp Figure 1) with changes not only in bias $B$, but also in sensory weight $W$. The bias may be reflect the ratio of rewards, consistent with optimality (Eq. 11). The sensory weight, instead, may reflect the total available reward, which may affect task engagement[10] and sensory attention[41]. Dynamic changes in parameters can be captured by extending the logistic classification model[42,43].

*Figure 3. **Logistic classification describes choices based on stimulus attributes and value in humans, monkeys, and mice.** **a**. A position discrimination task where the observer indicates whether the top stimulus is to the Right of the bottom one, in conditions where correct Left responses were rewarded less (red) or more (blue) than correct Right responses. **b**. Data from an observer showing that probability of choosing Right depends not only on stimulus offset (abscissa) but also on reward condition (blue vs. red). Data grabbed from Ref.[36]. Curves show fit of the logistic classification model with same weight W but two different values for the bias B. The red and blue ticks in the central axis indicate the intercepts predicted by the optimal strategy. **c**. The same data and curves plotted as odds of choosing Right vs. Left, in logarithmic scale. **d-f**. Same, for a monkey performing a random dots task where stimuli are presented in alternating blocks where correct Left choices were rewarded less (red) or more (blue) than correct Right choices. Data grabbed from Ref.[37]. **g-i** Same, for a mouse indicating whether a visual stimulus appears on the Left or the Right, presented in alternating blocks where correct Left choices were rewarded less (red) or more (blue) than correct Right choices. Data grabbed from Ref.[38].*

## Sensory choices across modalities

Logistic classification can describe not only sensory choices based on a single modality but also those based on multiple modalities (multisensory integration). As shown in Eq. 1, logistic classification naturally accommodates multiple factors as input (Figure 1**a**). If those factors are statistically independent, Bayes' rule predicts that an observer should perform logistic classification based on their sum[24]. To see this, consider the case where there are two sensory stimuli $s_1, s_2$ of different modalities, e.g., vision and audition. In that case, Bayes rule states that the probability of the correct answer being Right given the stimuli is

$$p = P(R|s_1, s_2) = \frac{P(s_1, s_2|R)P(R)}{P(s_1, s_2)} \quad \text{Eq. 12}$$

If the two modalities are independent, $P(s_1, s_2|R) = P(s_1|R)P(s_2|R)$, so

$$
\begin{aligned}
\frac{p}{1-p} &= \frac{P(R|s_1, s_2)}{P(L|s_1, s_2)} \\
&= \frac{P(s_1|R)}{P(s_1|L)} \frac{P(s_2|R)}{P(s_2|L)} \frac{P(R)}{P(L)}
\end{aligned}
\quad \text{Eq. 13}
$$

$$z = \log\left(\frac{p}{1-p}\right) = f_1(s_1) + f_2(s_2) + B \quad \text{Eq. 14}$$

*Figure 4. **Logistic classification describes audiovisual position choices in mice**. **a**. The audiovisual task: images appear on the Left or right, and sounds are emitted at one of 3-5 positions. **b**. Probability that a mouse chooses Right based on the contrast of the visual stimulus (abscissa, negative for stimuli on the Left) and on the position of the auditory stimulus (colors as in a). **c**. Same, for a mouse with higher auditory sensitivity. **d**. Results in a task with 5 auditory positions. **e-g**. The data in b-d, replotted as odds of Right vs. Left choices, in logarithmic scale. The quantities on the abscissa (horizontal plane in g) are compressed (raised to an exponent q<1). Data from Ref.[24]. Therefore, the probability of choosing R is a logistic function $p = \sigma(z)$ with three terms: one that depends on vision, one that depends on audition, and a constant.*

This expression is exceedingly simple, and yet is an excellent description of the choices of mice performing an audiovisual detection task[24]. In this task, a visual pattern appears on the Left or on the Right and a sound is played in one of 3 or 5 positions (Figure 4**a**). If the sound is in the middle it is uninformative, and the task becomes purely visual (Figure 4**b**, *gray*). If it is on the Left or Right, the mouse is more likely to make those choices (Figure 4**b**, *blue* and *red*).

Logistic classification (Eq. 14) describes this behavior accurately, via a simple implementation:

$$z = F_1 s_1^q + F_2 s_2^r + B \qquad \text{Eq. 15}$$

Here, the variables $s_1$ and $s_2$ are visual and auditory attributes, raised to exponents $q, r$ if necessary. The remaining parameters are the visual gain $F_1$, the auditory gain $F_2$, and the bias $B$. The first term describes the responses when the task is purely visual (Figure 4**b**, *gray*), and the second describes the responses when the task is purely auditory (Figure 4**b**, where abscissa is zero). The model provides excellent fits (Figure 4**b**, *curves*), correctly describing the choices not only when the two modalities agree, but also when they contradict each other[24]. Similar results are seen in a mouse that was better at auditory localization, providing higher performance at zero contrast (Figure 4**c**), and in a version of the task with more auditory positions (Figure 4**d**).

Multisensory integration via logistic classification is particularly easy to understand (and indeed to com-

pute) if one considers the log odds of the choices instead of their probability (Figure 4**e-g**). In this representation, and with a slightly different abscissa (plotting $s_1^q$ and $s_2^r$ instead of $s_1$ and $s_2$) logistic classification (Eq. 15) correctly predicts that the log odds fall on parallel lines: changing visual contrast moves the log odds along the lines, and changing the auditory position shifts the log odds to a different line. One way to judge the performance of the model[44,45] for such high-dimensional data is to plot the probability of all points as a function of the predicted decision variable $z$ (Eq. 1) and see if they fall near the logistic curve $\sigma(z)$ (Eq. 4). In this case they do, indicating that the model is a good description of the data (Supp. Figure 2).

Does logistic classification describe multisensory choices in other species and across other modalities? Many studies of multisensory integration indicate that observers are approximately Bayesian[23,24,46-53], at least when all stimuli are presented for the same amount of time[54]. These studies typically analyzed the responses with Signal Detection Theory, which focuses on the slope of the psychometric curves where they are steepest (**Box 2**). The analyses below – applied to three studies that tested various combinations of sensory modalities in various species – show that the entire psychometric curves are consistent with Bayesian integration and thus with logistic classification.

*Figure 5. **Logistic classification describes visuotactile orientation choices in rats**. **a**. Probability of Right choices for a rat performing the orientation discrimination task based on visual cues. **b**. Same, based on tactile cues. **c**. Same, based on stimuli that are both visual and tactile. **d-e**. Same data, plotted as odds of Right vs. Left in logarithmic scale. The quantity on the abscissa is compressed orientation (raised to an exponent q <1). Curves are from the logistic classification model. Data are from Rat 1 in Ref.[53].*

A first test is a study that measured visual and tactile integration in rats[53]. In this study, rats indicated whether the orientation of a stimulus was closer to horizontal or vertical by choosing between Left or Right response ports. The stimulus could be purely

visual or purely tactile (Figure 5**a,b**) or a combination of the two (Figure 5**c**). I applied the logistic classification model to those data with just 4 free parameters: visual gain $F_1$, tactile gain $F_2$, their common exponent $q$ (there was no need for two different exponents),

and bias $B$. The model provided good fits (Figure 5**a-c**), and would have done quite well even with just two free parameters (setting $q = 1$ and $B = 0$, not shown). The model's performance is particularly easy to evaluate if the data are plotted as odds of Right vs. Left choices, in logarithmic scale (Figure 5**d-f**). An additional check on fit quality can be done by verifying that all these data collapse on a single logistic curve when plotted as a function of the predicted decision variable (Supp. Figure 2).

## Sensory choices for multimodal features

In many experiments, it can help to distinguish between stimulus "amplitude" $\alpha$ and "feature" $\phi$. The amplitude (denoted by $\alpha$) is positive and is zero if the stimulus is absent. The feature (denoted by $\phi$) can be positive or negative, and is zero at the threshold between the two choices. For instance, in the motion task (Figure 1**d-f** and Figure 2**a-c**), $\alpha$ is coherence ranging between 0 and 1, and $\phi$ is direction taking the values of ±1 for Right and Left. Similarly, in the position task (Figure 2**d-f**), $\alpha$ is contrast, and $\phi$ is position ±1 for Right vs. Left. For both visual and tactile stimuli in the visuotactile task (Figure 5), instead, $\alpha$ is 0 or 1 (absent or present), and $\phi$ is orientation, ranging from -45 to 45 deg.

If an experiment varies multiple combinations of amplitude and feature, we must define how those combinations affect the stimulus representation. A simple working hypothesis is that the stimulus representation is separable, i.e., it is the product of a function of amplitude and a function of feature: $f(\phi, a) = g(\phi)h(\alpha)$. In the visual system, for example, this hypothesis would be appropriate for orientation[55] but possibly not for temporal frequency[56]. Under this hypothesis, when there are two sensory modalities and the stimuli are described by two amplitudes $\alpha_1, \alpha_2$ and two features $\phi_1, \phi_2$, the model (Eq. 14) becomes

$$z = g_1(\phi_1)h_1(\alpha_1) + g_2(\phi_2)h_2(\alpha_2) + B \quad \text{Eq. 16}$$

As we will see next, this model successfully describes multisensory data obtained in two laboratories, which used different tasks to test integration across different modalities (visual, auditory, and vestibular) in different species (rats, monkeys, and humans). These tasks varied both the amplitudes and the features of two modalities, with multiple offsets between those features. This allows a stronger test of the model than the experiments in the previous section, where the features could only be equal (Figure 4 and Figure 5) or opposite (Figure 4).

In the first task, humans were presented with noisy sequences of visual and auditory stimuli, and judged whether their rate was above a criterion[51,52]. When presented with auditory stimuli alone or visual stimuli alone, the observers did well if the stimulus had high amplitude ("Easy"), and poorly if it had low amplitude ("Hard", Figure 6**a**,**b**). When the easy auditory stimulus was combined with the hard visual stimulus, it largely determined the observer's choices: if the two stimuli disagreed, the observer responded in a manner consistent with the auditory stimulus (Figure 6**c**). Similar results were obtained by combining the hard auditory stimulus with the easy visual stimulus (Figure 6**d**). In both cases the choices were largely determined by the easier stimulus, as expected from a Bayesian observer[46,47]. The original study analyzed these data with Signal Detection Theory (**Box 2**), which focuses on the range where the psychometric curves are steepest, and found the data broadly consistent the observer being Bayesian[52]. A later study found that the psychometric curves of rats in this task and were well fit by logistic curves[23]. It is thus conceivable that these observers may be performing logistic classification.

The choices measured in this task agree with the logistic classification model, with amplitudes and features combined under the separable approximation (Eq. 16). To fit the data, I chose simple linear expressions for the functions: $h_i(\alpha_i) = \alpha_i$, and $g_i(\phi_i) = F_i\phi_i + B_i$ (with $i = 1,2$ denoting visual and auditory modalities). The result is a simple equation:

$$z = \alpha_1(F_1\phi_1 + B_1) + \alpha_2(F_2\phi_2 + B_2) + B \quad \text{Eq. 17}$$

With just 5 free parameters (visual gain $F_1$, visual bias $B_1$, auditory gain $F_2$, auditory bias $B_2$, and overall bias $B$) this function provided good fits to 10 psychometric curves comprising 114 measurements (Figure 6**a-d**, *curves*). As usual, the reasons for this success are easiest to see in terms of log odds. In this scale, the unisensory responses are well fit by lines, which are

steeper for Easy stimuli than for Hard stimuli (Figure 6**e**,**f**). When the steep line is summed to a shallow line in the multisensory responses, its slope and intercept determine the slope and intercept of the resulting line (Figure 6**g**,**h**).

*Figure 6. **Logistic classification describes audiovisual rate choices in humans**. **a** Average choices of a human performing a rate discrimination task based on auditory sequences. The ordinate plots the probability that the observer judges the rate of the sequence to be higher than a reference (10.5 Hz) when stimuli have low amplitude (Hard) or high amplitude (Easy). Curves in this panel and subsequent ones are fits of the logistic classification model. **b**. Same, for visual stimuli. **c**. Same, for stimuli obtained by summing an easy auditory stimulus to a hard visual stimulus, with the rate of the former being lower (blue), equal (green), or higher (red) than the rate of the latter. The abscissa plots the average rate of the visual and auditory stimuli. **d**. Same, for stimuli obtained by summing a hard auditory stimulus to an easy visual stimulus. **e-h**: The same data as a-d, plotted in terms of odds, in logarithmic scale. Data are from Human 1 in Ref.[52].*

In the second task, monkeys judged whether their direction of heading was Left or Right based on visual and vestibular cues[50]. When presented with vestibular stimuli alone, the animals performed well (Figure 7**a**). When presented with visual stimuli alone, they performed better if the dots had high coherence and worse if they had low coherence (Figure 7**b**). When the vestibular stimulus was combined with the hardest visual stimulus (lowest coherence), the vestibular stimulus largely determined the observer's choices (Figure 7**c**). Conversely, when combining the vestibular stimulus with the easy visual stimulus, the visual stimulus largely determined the choices (Figure 7**d**). In both cases the choices were largely determined by the modality that was easier, suggesting that the observers were Bayesian[50]. This suggests that the observers perform logistic classification.

Once again, the data were well fit by the logistic classification model under the simple assumptions of Eq. 17, with $\phi_1$ indicating the visual heading and $\phi_2$ indicating the vestibular heading, both of them raised to an exponent $q$ to capture increased sensitivity around the heading of 0. This function provided good fits to the psychometric curves (Figure 7**a-d**), and once again, the reasons for its success are easiest to see when data and predictions are plotted as log odds (Figure 7**e-h**).

*Figure 7.* **Logistic classification describes vestibulo-visual heading choices in monkeys**. *a Average choices of a monkey performing a heading discrimination task based on unisensory vestibular stimulation. The ordinate plots the probability that the observer judges the heading to be Right. Curves are predictions of the logistic classification model. **b**. Same, for unisensory visual stimuli varying in coherence from 12% (hardest) to 96% (easiest). **c**. Same, for multisensory stimuli obtained by summing the vestibular stimulus to a hard visual stimulus, with the former having a heading left of (blue), same as (green), or right of (red) the latter. The abscissa plots the average heading of the vestibular and visual stimuli. **d**. Same, for stimuli obtained by summing the vestibular stimulus to an easy visual stimulus. e-h: The same data as a-d, plotted in terms of odds, in logarithmic scale. Open symbols indicate values where the probability is close to 0 or 1, where the odds would require a high precision, and are thus likely to lie outside the range of the ordinate*. *Data were grabbed from Ref.[50].*

It is striking that logistic classification describes multisensory choices in so many species, tasks, and modalities, especially considering that the tasks do not perfectly conform to the conditions where logistic classification is optimal. Indeed, in deriving logistic classification (Eq. 13) we assumed the modalities be independent, but in the tasks that we considered the two modalities had positive correlations. For instance, in the audiovisual position task (Figure 4) the modalities agreed more often than they disagreed[24]. More strikingly, in the visuotactile task (Figure 5) the two modalities had a correlation of 1 when both present, because they always had the same orientation. Strong correlations between modalities were present also in the other two tasks (Figure 6 and Figure 7). In these conditions, the additivity at the core of logistic classification may no longer be optimal, and the brain seems may adopt it as a useful heuristic[57].

## Sensory choices influenced by history

A key challenge in making a choice is to weigh only the factors that are relevant: giving weight to irrelevant factors is suboptimal because it decreases the chance of correct answers. And yet, superstitious behavior is widespread. For instance, in sensory tasks where the sequence of stimuli is random, humans[12-16,19,58,59] and animals[10,11,17,18,20,40,60-65] typically act as if it followed some order ("serial dependence").

The logistic classification model can readily capture this serial dependence, by simply including history factors as regressors in addition to the sensory factors[10]. In this framework (Figure 8**a**), choices depend not only on the present sensory stimulus $x(t)$ as in Eq. 5, but also on whether the preceding choice was a success $s$ or a failure $f$:

$$z(t) = Wx(t) + Ss(t-1) \\ + Ff(t-1) + B \qquad \text{Eq. 18}$$

where $s(t) = sign(x(t))$, $f(t) = 0$ if trial $t$ was a success, and $s(t) = 0$, $f(t) = -sign(x(t))$ if it was a failure.

This approach[10] merged the logistic classification approaches that had been used separately for sensory decisions[8] and for history-based decisions[5-7]. The specific form of the equation is just one of various possibilities, chosen for its simplicity. In the many studies that used this approach[10-20,65,66], the history regressors typically extend further in the past, or are expressed in different combinations, such as past choices (regardless of success) or past rewards (regardless of choice).

Figure 8. **Logistic classification describes effects of history. a**. Model of logistic classification where choices are determined not only by a stimulus but also by prior wins or losses (Eq. 18). Adapted from Ref.[10]. The subsequent panels show results of simulations with W = 0.8, S = 2, F = -1, B = 0. **b**. Simulated data showing the probability of R choices as a function of contrast, compared to what would be observed based on the sensory factor alone (dashed). **c**. Same, plotted as the logarithm of the odds. **d-e**. Same as b-c, contingent on previous trial being a success or a failure (red vs. blue) on the L or R (open vs. closed). The dashed curve shows the result that would be observed based on the sensory factor alone. **f**. Distribution of values of the decision variable z, as predicted by the stimuli alone (gray) or by the stimuli plus the history terms (green). **g**. Binned values of the decision variables for the two models, on top of a logistic curve. **h**. Same, plotted as the logarithm of the odds.

If an observer exhibits strong serial dependence, ignoring it will lead to significant underestimates of their stimulus sensitivity. Plotting the performance as a function of the present stimulus yields shallower psychometric curves (fewer correct answers) than would be expected based only on sensory sensitivity $W$ (Figure 8**b,c**). A better estimate of sensitivity (and a measure of the effect of history) is obtained by plotting performance conditional not only on the present stimulus but also on the choice and outcome of the

previous trial (Figure 8**d**). If the effect is additive (as in Eq. 18), it will result in simple shifts of the lines representing the log odds of the choices, because the history factors sum with the fixed bias $B$ to yield a variable overall bias (Figure 8**e**). One can confirm that these history factors are in play by comparing a model that ignores them (Eq. 5) to the model that includes them[45] (Eq. 18). The model that includes them predicts larger positive or negative values for the decision variable $z$ (Figure 8**f**), while providing comparable or superior fits to the actual choices (Figure 8**g**,**h**).

The strength of the history terms varies across individuals and in time[10]. It can change with learning[42] and can be increased or decreased by appropriate design, but it cannot be entirely removed[14]. In humans, it correlates with education[14]: PhD candidates or graduates have strongly negative failure weights (lose-switch) but weak success weights, whereas the rest of the population have positive success weights (win-stay). This correlation is not necessarily causal and may reflect other unmeasured factors.

However, some effects of history are more complex than can be captured by a simple logistic classification model such as Eq. 18. For instance, the effect of past choices is strongest if they were made with low confidence[63], a behavior that is more readily explained by models based on reinforcement learning[38]. Also, engagement in the trial typically fluctuates, and these fluctuations can be captured by allowing the weights to change across trials[42,43]. Variations in engagement will cause concomitant variations in the fractions of successes and failures, so observing data after a success vs. a failure may be a way to gauge the effect of engagement. This phenomenon may explain results observed in rats during rate discrimination[23], where past successes and failures affect not only the overall bias but also the sensory weight $W$, which was slightly higher after a success than after a failure (Supp Figure 1**g**-**l**). Given that successes tend to occur in an engaged state and failures in a disengaged state, the latter effect may be explained by a dependence of sensitivity on engagement.

## Sensory choices during brain manipulations

Logistic classification is a good model not only for how the brain makes decisions, but also for how these decisions are modified by brain manipulations

such as local inactivations[21-24]. Indeed, the effects of inactivating some key brain regions can often be summarized by changes in a few weights, suggesting that the inactivating regions are necessary for processing the corresponding factors.

For example, in mice performing the audiovisual localization task (same as Figure 4), inactivation of the visual cortex decreases the contralateral visual weight, but no other weights. Indeed, optogenetic inactivation of the right visual cortex causes strong deficits in the detection of visual stimuli on the left side, with no effect on visual detection on the right side or on auditory detection on either side (Figure 9**a**). This effect is particularly easy to see when the probabilities are replotted in terms of log odds (Figure 9**b**). To describe these asymmetric effects, it helps to extend Eq. 15 to allow for different weights for stimuli on the left vs. right[24], whether visual ($F_{1L}$ and $F_{1R}$) or auditory ($F_{2L}$ and $F_{2R}$):

$$z = F_{1,L}s_{1,L}^q + F_{1,R}s_{1,R}^q + F_{2,L}s_{2,L} + F_{2,R}s_{2,R} + B \qquad \text{Eq. 19}$$

In principle, the parameters (weights, exponent, and bias) might all vary in the control vs. manipulation condition (see Methods). In practice, however, the model is parsimonious, because the control condition is typically described by fewer parameters (e.g., the weights on the left and right are the same), and because only a few parameters change during brain manipulations[21-24]. For instance, the effects of inactivating right visual cortex (Figure 9**a**,**b**) are described by a single parameter: a smaller weight applied to visual stimuli on the left, $F_{1L}$. This smaller weight results in shallower lines for visual stimuli on the left when responses are plotted in terms of log odds (Figure 9**a**,**b**). This result indicates that right visual cortex is necessary for processing visual on the left, and not for processing visual stimuli on the right or auditory stimuli[24].

By contrast, inactivating right prefrontal cortex reduces both visual weights and auditory weights (regardless of side), and increases bias $B$ thus increasing the proportion of Right choices (Figure 9**c**,**d**). This result indicates that prefrontal cortex processes bilateral visual and auditory signals and promotes contralateral choices[24].

*Figure 9. **Logistic classification describes effects of brain manipulations. a.** Effects of inactivating right visual cortex in mice that perform an audiovisual localization task[24]. Showing the probability of Right choices as a function of visual contrast (abscissa) in the presence of sounds from the Left (blue), center (gray), and Right (red), in control conditions (dashed) and during inactivation (data and continuous curves). The curves are predictions of the model (Eq. 19) allowing only one parameter to change with inactivation: the weight applied to visual stimuli on the left, $F_{1L}$. **b.** Same data, plotted as log odds. **c,d.** Same format, showing the effects of inactivation of the right prefrontal cortex. The model captured them via changes not only in the contralateral visual weight but also in the contralateral auditory weight and in the overall bias. From[24]. **e.** Effects of prefrontal inactivation in a rat performing auditory rate discrimination, showing the probability of choosing "Right" (for high rates) as a function of rate (expressed relative to the reference). **f.** Same data, in log odds. **g-h.** Same, for visual rate discrimination. **i-j** Same, for combined auditory and visual stimuli. From Ref.[23].*

Similar results are seen in rats performing the audiovisual rate discrimination task[23] (same as Figure 6): the control and inactivation conditions are well fit by logistic classification (Eq. 19), and inactivation reduces both auditory and visual weights (regardless of whether stimuli have low or high rate), and increases the bias (Figure 9**e-j**).

## Discussion

A growing body of evidence indicates that the brain uses logistic classification to make choices based on a multitude of factors alone or in combination. These factors include relative value, relative probability, sensory inputs from one or more modalities, recent history, and brain manipulations. To illustrate this body of evidence, I have followed a hybrid approach, in most cases reviewing existing results and in others applying the logistic classification model to data that were previously analyzed with other approaches.

I have also shown that logistic classification is an optimal strategy in many conditions. For instance, it is the only procedure that accords to Bayes' rule for putting together sensory signals with estimates of prior probabilities or with sensory signals from a different modality, and it is the strategy that yields the highest overall reward when the options differ in value or prior probability.

As we have seen, these considerations of optimality provide a potential reason for the puzzling strategies of "probability matching" and "value matching". These strategies seem suboptimal: it would be better to always choose the option that is more likely or has higher value. However, they are fully expected from an optimal logistic classifier if that classifier is unaware that the stimulus is absent. This suggests a reason for probability matching and value matching: the observer does not know that the evidence is irrelevant or absent (i.e. that they are gambling). Rather, they act as if they were performing a task based on some evidence.

In fact, we have seen that logistic classification is also widely used in cases where it is not optimal, for instance when stimuli are absent (and choices exhibit probability matching or value matching) or stimuli of two modalities are not independent. This suggests that logistic classification is a heuristic that the brain implements in a variety of conditions even when it is not strictly optimal[57].

Finally, we have seen that logistic classification is a good model not only for how the brain makes decisions, but also for how these decisions are modified by manipulations such as local brain inactivations. Indeed, the effects of inactivating some key brain regions can often be summarized by changes in a few weights, suggesting that the inactivating regions are necessary for processing the corresponding factors.

Throughout the paper, I have described logistic classification as an addition of factors that each contribute to the log odds of a choice. However, we could have just as easily talked about multiplication of factors, each of which contributes to the odds, and we could have taken the logarithm only after the multiplication. Mathematically, the two are identical but numerically it is easier to deal with log odds that vary, say, between -5 and 5, than with the corresponding odds, which would vary between less than one hundredth and over a hundred (for a natural logarithm). Using firing rates, it seems easier to encode the former than the latter. Indeed, when decoding the activity of neurons in prefrontal cortex the activity seems more commensurate to log odds[11,24].

Going forward, there are at least two areas where there are exciting developments. One promising direction is to develop the temporal aspect of logistic classification in ways that go beyond the well-established drift diffusion model, which is already quite flexible[67] (**Box 3**). For instance, logistic classification can capture the effect of stimulus fluctuations, teasing apart the dynamics of complex cognitive computations[68,69]. At a longer time scale, it seems clear that the weights of the logistic classifier should not be considered to be constant, because they change with factors such as learning and brain state[42,43]. Another promising direction is to use neural data as a predictor. Ultimately, a model of choice should be based on neural data, and a way to start on this path is to add neural activity to task factors[66] such as those considered in this paper. Ultimately, the neural activity should be superior and make any other factor irrelevant[5,70].

## Acknowledgments

I thank my lab colleagues Celian Bimbard, Pip Coen, Tim Sit, Valentin Schmutz, Max Shinn, and Flora Takacs for advice and help in obtaining data. I thank Kenneth D Harris for numerous insights and for suggesting the proof in Box 3. This work was funded by a Wellcome Investigator Award (223144) and an UKRI Pioneer Award (EP/X022366/1). Earlier work was supported by the GlaxoSmithKline / Fight for Sight Chair in Visual Neuroscience.

# Methods

Most of the data were taken from the original papers using a manual data grabber (the MATLAB function *grabit*). In a few cases (noted in the legends of the relevant figures), I accessed the original data.

I then fitted these data with the 2-choice logistic classification model using the MATLAB function *glmfit*. In the case of 3 choices (Box 1), instead, I used the function *mnrfit*.

To describe sensory choices influenced by priors (Figure 2) I fit this equation:

$$p = \sigma(Vv + H(h - 0.5) + B) \qquad \text{Eq. 20}$$

where $v$ is visual strength (coherence for the motion task, contrast for the position task), $h$ is the probability of a Right stimulus (determined by the block), and $V, H, B$ are parameters (visual gain, prior gain, and bias).

To describe sensory choices influenced by value in humans, monkeys, and mice (Figure 3) I fit this Eq.:

$$p = \sigma(Vv + Rr + B) \qquad \text{Eq. 21}$$

where $v$ is visual strength (position, coherence, or contrast, depending on the experiment), $r$ is the relative reward offered for Left vs. Right choices (determined by the block) and $V, R, B$ are parameters (visual gain, reward gain, and bias).

To describe audiovisual position choices in mice (Figure 4) and visuotactile orientation choices in rats (Figure 5) I fit Eq. 15.

To describe audiovisual rate choices in humans (Figure 6) I fit Eq. 17.

To describe vestibulo-visual heading choices in monkeys (Figure 7) I fit the same equation but with an exponent $q$ applied to both $\phi_1$ and $\phi_2$.

To illustrate the effects of stimulus history (Figure 8) I simulated the model in Eq. 18 using the parameters W = 0.8, S = 2, F = -1, B = 0.

To describe the effects of brain manipulations (Figure 9) I modified Eq. 19 to allow not only for different sensitivities on L vs R but also for possible effects of manipulations:

$$z = \sum_{i=1,2} \sum_{j \in \{L}} (F_{ij} + \Delta_{ij})s_{ij} + (B + \Delta_B) \qquad \text{Eq. 22}$$

where the variables $s_{ij}$ are the stimuli, indexed by their modality ($i = 1$ for visual contrast raised to exponent $q$ and $i = 2$ for auditory position), and by their position ($j = L$ or $R$). The parameters $F_{1L}, F_{2L}, F_{1R}, F_{2R}$ are the corresponding weights, and the five $\Delta$ parameters allow for the effects of the brain manipulation on the four weights $F$ and on the bias $B$.

# Box 1. Logistic classification with multiple outcomes

Figure B1. **Logistic classification with more than two choices. a.** Multinomial logistic classification among 3 choices , showing probability of choices 1,2, and 3 (left to right) as a function of z1 (abscissa) and z2 (ordinate), when z3 = 0. **b.** The 3-choice version of the position detection task, where mice choose "Left" or "Right" to indicate stimulus position, and "NoGo" if the stimulus is absent. **c-e.** Probabilities of the three choices for a mouse in this task (Mouse I from Fig. 3 of Ref.[21]), as a function of stimulus contrast. **f-h.** The odds of the three choices relative to the third choice.

The binary logistic classifier is readily extended to the case when the choice involves n classes. First one obtains the decision variables $z_1, z_2, \ldots, z_n$ for each of the possible choices:

$$z = W^T x + B$$

And then one applies a smooth version of the argmax function, called *softmax*:

$$p_i = softmax(z)_i = \frac{\exp(z_i)}{\sum_j \exp(z_j)}$$

For example, if there are 3 possible choices, and we assume for simplicity that z3 = 0, then the probability p1 of the 1st choice is largest when z1 > 0 and z1>z2, and so on, dividing the space of probabilities in three regions where the three choices are more probable than the others (Figure B1**a**).

In a network, the softmax can be thought of as a competitive process among units that each receive one $z_i$ as external input[3]. Because the outputs of softmax sum to 1, an increase in the input to one unit decreases the activity of others. When the difference between the largest $z_i$ and the others is large, this process becomes a winner-take-all.

When there are only two outcomes with probabilities $p_1 = p$ and $p_2 = 1 - p$ the softmax function reduces to a logistic sigmoid $p = \sigma(z)$ with decision variable $z = z_2 - z_1$:

$$p = p_1 = \frac{\exp(z_1)}{\exp(z_1) + \exp(z_2)} = \frac{1}{1 + \exp(z_2 - z_1)} = \sigma(z)$$

A logistic classifier with multiple outcomes can provide excellent fits to psychophysical data[21,22]. For example, consider a 3-choice version of the position detection task[21], where the mouse chooses the stimulus position as "Left" or "Right" if the stimulus is present, and chooses "NoGo" if it is absent (Figure B1**b**). This three-choice design was originally devised in the framework of signal detection theory[71,72] but it is particularly easy to analyze in terms of logistic classification, where it boils down to two equations[21]:

$$z_L = \log\left(\frac{p_L}{p_{NoGo}}\right) = w_{LL}c_L + w_{RL}c_R + B_L$$

$$z_R = \log\left(\frac{p_R}{p_{NoGo}}\right) = w_{LR}c_L + w_{RR}c_R + B_R$$

where $c_L$ and $c_R$ are the stimulus contrasts on the left and right. These equations provide good fits to the mouse choices (Figure B1**c-e**). The working of the model is perhaps easiest to understand by plotting the values of $z_L$ and $z_R$ as a function of contrast (Figure B1**f-h**).

# Box 2. Logistic classification and Signal Detection Theory

*Figure B2. **Logistic classification vs. fitting a cumulative gaussian. a**. Probabilities simulated by a two-alternative logistic classification model (data points and curve). **b**. The same data points, fitted by a cumulative Gaussian with a lapse rate (curve). **c**. Probabilities simulated by a logistic classification model with a slight compression of the stimulus axis (exponent q=0.8). **d**. The same data points, fitted with the cumulative Gaussian with a larger lapse rate (curve).*

Studies of sensory choices typically analyze the data with Signal Detection Theory[73,74] (SDT) rather than with logistic classification. According to SDT, the factor that limits performance and that makes choices variable across trials is sensory noise. In discrimination tasks such as the ones we analyze in this paper, SDT describes performance as follows. First, the observer takes in a sample of the stimulus that is corrupted by noise, where the noise is independent across trials, additive, and typically Gaussian. Second, the observer compares the noisy sample with an internal reference, and makes one choice if the difference between the two is positive, and the other if it is negative. In SDT, therefore, sensory processing is stochastic, whereas decision-making is deterministic. This is the opposite of logistic classification, where sensory processing is deterministic and decision-making is stochastic: choices are made by flipping a coin that has been merely biased by the stimulus.

When describing a single psychometric curve determined by a single factor, the two frameworks are hardly distinguishable[23,75,76]. For example, consider the probabilities of a given choice in a two-alternative task (Figure B2**a**). These were generated by a logistic classification model $p = \sigma(Wx + B)$ , where $x$ is the stimulus and $W, B$ are parameters (sensory weight and bias). The same data can be fitted extremely well by the function commonly used in SDT, the cumulative Gaussian $\Phi((x - \mu)/\sigma)$, where the two parameters $\sigma, \mu$ determine a "threshold" and a "bias" (Figure B2**b**).

Studies that use cumulative Gaussians, however, often focus on the steepest part of the psychometric curve (where the stimulus is near the threshold $\mu$), and consider the two extremes of the curve (where stimuli are easy) to be corrupted by "lapses", i.e. errors due to distraction. The cumulative Gaussian is thus usually fit to the data while allowing for a "lapse rate" $\lambda$ (Figure B2**d**), to obtain

$$p = \lambda + (1 - \lambda)\Phi\left(\frac{x - \mu}{\sigma}\right)$$

Logistic classification, however, can often explain lapses in a different way: the observer may not give enough weight $W$ to the sensory input $x$. Moreover, as shown in multiple occasions in this paper, the observer may process stimulus strength in a nonlinear fashion, further reducing the input $x$. For instance, the same data that required a lapse rate when fitted with a cumulative Gaussian can be fitted with a logistic curve simply by assuming that the sensory input $x$ is the stimulus strength $s$ raised to the power $q < 1$ (a compressive nonlinearity), as we do in multiple examples in this paper (Figure B2**c**). In other cases, one may need a nonlinearity that is even more compressive[10,21]. With this approach, logistic classification can meaningfully describe all points of the psychometric curve, not just the ones near threshold.

These are minor differences, and they could be easily bridged by making minor changes to SDT. For instance, one could extend SDT by introducing a nonlinear representation of the stimulus. Moreover, one could assume that the noise in SDT comes from a logistic rather than a Gaussian distribution, so the cumulative Gaussian curves become logistic curves[74,76,77].

However, logistic classification far outstrips SDT when it comes to representing more general choice environments. For instance, as we show in this paper, logistic classification makes it trivial to add predictors, both sensory and non-sensory; it is readily extended to multiple alternatives; it has a simple linear interpretation that often describes the data; it makes it easy to describe the effects of brain manipulations. Moreover, logistic classification comes straight out of probability theory (with no need to assume additive Gaussian noise or similar) and it incorporates the Bayesian assumption by definition, without having to postulate that an observer keeps track separately of stimulus estimate and confidence. SDT lacks these advantages. For instance, it makes it unwieldy to have more than one or two predictors or more than two choice alternatives.

Because of all these theoretical and practical advantages, logistic classification is increasingly preferred over SDT to describe sensory choices.

# Box 3: Logistic classification and drift diffusion

By itself, logistic classification model says nothing about a decision's time course. The most established model for the time course is the drift diffusion model[2,44,78]. In the model the decision variable does a random walk, going up or down at each step in time depending on the evidence. When the decision variable hits one of the two boundaries, the corresponding decision is made.

If the random walk starts from the middle between the two bounds, then the probability that it will hit one of the bounds (say, the upper one) is given by the logistic function. For a full derivation, see Refs.[44,79]. Here I give a simpler derivation, which is based on a simplified analogy.

In the drift diffusion model, at any moment in time the decision variable can jump by an arbitrary amount based on a probability distribution. Let's consider a simpler system, where at each moment in time the decision variable can only go up or down by 1.

Define $P$ as the probability that it will go up and define $r = P/(1 - P)$. This turns out to be the well-known "gambler's ruin" problem, and it has a simple solution[80]: if the funds of players 1 and 2 are $N_1$ and $N_2$, then the probability that player 1 will win (i.e. that player 2 goes bankrupt) is

$$p = \frac{1 - r^{-N_1}}{1 - r^{-(N_1 + N_2)}}$$

where we have assumed that $r \neq 1$ (the drift is preferentially in one direction). If the two players start with equal amount of money ($N_1 = N_2 = N$), then player 1 will win with probability

$$p = \frac{1}{1 + r^{-N}} = \frac{1}{1 + e^{-N \log(r)}} = \sigma(x)$$

where $x = N \log(r)$. In other words, the probability of hitting a boundary in this random walk is proportional to the logarithm of the odds of going up vs. down in each step.

There are many implementations of the drift diffusion model, and many ways to change it, e.g. by applying a constant bias at each step, or by starting by an unequal starting point, or giving more weight to one of the sensory options[81]. In some of those cases there may not be a closed form Eq. for the probability of hitting a boundary, and the psychometric functions have to be simulated.

# Appendix: Optimal bias given unequal rewards and priors

Here I derive the ideal bias for an observer that performs logistic classification when the rewards for correct left vs. right choices $V_L, V_R$ are unequal, and the prior probabilities of stimuli being on the left or right, $p_L, p_R$ are unequal. My derivation is inspired by an analogous result obtained with signal detection theory using cumulative gaussians[36].

If an observer performs logistic classification based on evidence $x$ with weight $a$, the probability that they will choose Right is $p = P('R'|x) = \sigma(ax + b)$. Here I show that the bias $b$ that maximizes expected value is

$$b = \log\left(\frac{V_R}{V_L}\right) + \log\left(\frac{p_R}{p_L}\right) \qquad \text{Eq. 23}$$

The expected value of a choice is the product of the probabilities of each answer being correct times the corresponding reward:

$$V = V_L P('L' \& x < 0) + V_R P('R' \& x > 0)$$

The evidence $x$ is a random variable with prior probability $p(x)$. We can thus write

$$V = V_L \int_{-\infty}^{0} P('L', x)\, dx + V_R \int_{0}^{\infty} P('R', x)\, dx =$$

$$= V_L \int_{-\infty}^{0} P('L'|x)p(x)dx + V_R \int_{0}^{\infty} P('R'|x)p(x)dx$$

We assume that the prior probability is different between Left and Right, but otherwise flat: $p(x) = p_L/T, x \in [-T, 0]$ and $p(x) = p_R/T, x \in [0, T]$. Later we will set $T \to \infty$. Using the fact that $P('R'|x) = \sigma(ax + b)$ and $P('L'|x) = 1 - \sigma(ax + b) = \sigma(-ax - b)$, we obtain:

$$V = \frac{p_L V_L}{T} \int_{-T}^{0} \sigma(-ax - b)dx + \frac{p_R V_R}{T} \int_{0}^{T} \sigma(ax + b)dx$$

To maximize $V$ we need to find $b$ that such that $dV/db = 0$. We can bring the derivative inside the integrals:

$$\frac{dV}{db} = \frac{p_L V_L}{T} \int_{-T}^{0} \frac{d}{db}\sigma(-ax - b)dx + \frac{p_R V_R}{T} \int_{0}^{T} \frac{d}{db}\sigma(ax + b)dx = 0$$

A nice property of the logistic function is that its derivative has a simple form: $d\sigma(x)/dx = \sigma(x)\sigma(-x)$. Using this property and rearranging the terms, we obtain:

$$\frac{p_R V_R}{p_L V_L} = \frac{\int_{-T}^{0} \sigma(ax + b)\sigma(-ax - b)dx}{\int_{0}^{T} \sigma(ax + b)\sigma(-ax - b)dx}$$

With a change of variable $z = ax + b$ the Eq. becomes

$$\frac{p_R V_R}{p_L V_L} = \frac{1/a \int_{-aT+b}^{b} \sigma(z)\sigma(-z)dz}{1/a \int_{b}^{aT+b} \sigma(z)\sigma(-z)dz} = \frac{\sigma(b) - \sigma(-aT + b)}{\sigma(aT + b) - \sigma(b)} \xrightarrow{T\to\infty} \frac{\sigma(b)}{1 - \sigma(b)}$$

Where in the second equality we have solved the integrals by using the expression for the derivative of $\sigma$ in reverse, and in taking the limit we have used the fact that $\sigma(\infty) = 1$ and $\sigma(-\infty) = 0$. If we now take the logarithm of both sides, and recognize that $\sigma^{-1}(p) = \log p/(1 - p)$, we obtain:

$$log\,\frac{p_R V_R}{p_L V_L} = log\,\frac{\sigma(b)}{1 - \sigma(b)} = \sigma^{-1}\big(\sigma(b)\big) = b$$

which proves the result in Eq. 23.

# Supplementary figures

*Supp Figure 1*. **Logistic classification describes the effects of unequal rewards and of recent history. a.** *Probability of choosing "high" in a task where rats judge the rate of audiovisual stimuli, in conditions where the rewards for correct "high" choices are the same as correct "low" choices (24 μL, black) or higher (36 μL, green). Curves show fits of the logistic classification model where both the sensory weight W and the bias B are allowed to change when the rewards are unequal.* **b.** *Same data and curves, plotted in terms of the logarithmic odds of choosing "high".* **c,d,** *Same, for a cohort of rats that were run in conditions where the rewards for correct "high" choices are the same as correct "low" choices (24 μL, black) or lower (12 μL, green).* **e.** *As predicted by logistic classification under the hypothesis that observers seek to maximize reward, the bias parameter was affected in opposite directions by the two manipulations. The changes in bias predicted by the model (Eq. 11) would be log(12/24)=-0.69 and log(36/24)=0.41.* **f.** *In addition, the sensory weight increased when the ratio of rewards increased, perhaps because the total available reward also increased (abscissa). This may have caused an increase in attention to the task variable.* **g-j.** *Same as a-d for a cohort of rats that were run with equal rewards for "low" and "high" correct choices, distinguishing performance following a "high" choice that was correct (green) or incorrect (red).* **k.** *The bias term followed the predictions of logistic classification with history terms (Eq. 18) in a win-stay lose-switch strategy.* **l.** *The sensory weight was slightly higher after a success than after a failure, possibly because failures tended to occur during behavioral states where the rats were paying less attention to the stimulus. Data were obtained from Fig. 4 of Ref[23].*

*Supp Figure 2.* **Summarizing multiple conditions on a single logistic curve.** *a. Probabilities of Right choices in an audiovisual task (replotted from Figure 4). b. Probabilities of Right choices in a visuotactile task (replotted from Figure 5). Curves in a,b show fits of the logistic classification model. c-d. The same data as a-b, plotted as a function of the decision variable z predicted by the model, plotted on top of a standard logistic curve. e-f. The same data, in log odds.*

# References

McFadden, D. in *Frontiers in Econometrics* (ed Paul Zarembka) Ch. 4, 105-142 (Academic Press, 1973).

Gold, J. I. & Shadlen, M. N. Banburismus and the brain: decoding the relationship between sensory stimuli, decisions, and reward. *Neuron* **36**, 299-308, doi:10.1016/s0896-6273(02)00971-6 (2002).

Goodfellow, I., Bengio, Y. & Courville, A. *Deep Learning*. (MIT Press, 2016).

Cramer, J. S. *The origins of logistic regression* (University of Amsterdam and Tinbergen Institute, Amsterdam, 2002).

Padoa-Schioppa, C. Logistic analysis of choice data: A primer. *Neuron*, doi:10.1016/j.neuron.2022.03.002 (2022).

Lau, B. & Glimcher, P. W. Dynamic response-by-response models of matching behavior in rhesus monkeys. *J Exp Anal Behav* **84**, 555-579 (2005).

Corrado, G. S., Sugrue, L. P., Seung, H. S. & Newsome, W. T. Linear-Nonlinear-Poisson models of primate choice dynamics. *J Exp Anal Behav* **84**, 581-617 (2005).

Gold, J. I. & Shadlen, M. N. Neural computations that underlie decisions about sensory stimuli. *Trends Cogn Sci* **5**, 10-16 (2001).

Huk, A. C. & Shadlen, M. N. Neural activity in macaque parietal cortex reflects temporal integration of visual motion signals during perceptual decision making. *Journal Of Neuroscience.* **25**, 10420-10436, doi:10.1523/JNEUROSCI.4684-04.2005 (2005).

Busse, L. *et al.* The detection of visual contrast in the behaving mouse. *Journal Of Neuroscience.* **31**, 11351-11361, doi:10.1523/JNEUROSCI.6689-10.2011 (2011).

Padoa-Schioppa, C. Neuronal origins of choice variability in economic decisions. *Neuron* **80**, 1322-1336, doi:10.1016/j.neuron.2013.09.013 (2013).

Fründ, I., Wichmann, F. A. & Macke, J. H. Quantifying the effect of intertrial dependence on perceptual decisions. *J Vis* **14**, doi:10.1167/14.7.9 (2014).

Akaishi, R., Umeda, K., Nagase, A. & Sakai, K. Autonomous mechanism of internal choice estimate underlies decision inertia. *Neuron* **81**, 195-206, doi:10.1016/j.neuron.2013.10.018 (2014).

Abrahamyan, A., Silva, L. L., Dakin, S. C., Carandini, M. & Gardner, J. L. Adaptable history biases in human perceptual decisions. *Proc Natl Acad Sci U S A* **113**, E3548-3557, doi:10.1073/pnas.1518786113 (2016).

St. John-Saaltink, E., Kok, P., Lau, H. & de Lange, F. P. Serial Dependence in Perceptual Decisions Is Reflected in Activity Patterns in Primary Visual Cortex. *Journal Of Neuroscience.* (2016).

Urai, A. E., Braun, A. & Donner, T. H. Pupil-linked arousal is driven by decision uncertainty and alters serial choice bias. *Nature communications* **8**, 14637, doi:10.1038/ncomms14637 (2017).

Hwang, E. J., Dahlen, J. E., Mukundan, M. & Komiyama, T. History-based action selection bias in posterior parietal cortex. *Nature communications* **8**, 1242, doi:10.1038/s41467-017-01356-z (2017).

Akrami, A., Kopec, C. D., Diamond, M. E. & Brody, C. D. Posterior parietal cortex represents sensory history and mediates its effects on behaviour. *Nature* **554**, 368-372, doi:10.1038/nature25510 (2018).

Braun, A., Urai, A. E. & Donner, T. H. Adaptive History Biases Result from Confidence-Weighted Accumulation of past Choices. *Journal Of Neuroscience.* **38**, 2418-2429, doi:10.1523/JNEUROSCI.2189-17.2017 (2018).

International Brain Laboratory *et al.* Standardized and reproducible measurement of decision-making in mice. *eLife* **10**, doi:10.7554/eLife.63711 (2021).

Burgess, C. P. *et al.* High-Yield Methods for Accurate Two-Alternative Visual Psychophysics in Head-Fixed Mice. *Cell reports* **20**, 2513-2524, doi:10.1016/j.celrep.2017.08.047 (2017).

Zatka-Haas, P., Steinmetz, N. A., Carandini, M. & Harris, K. D. Sensory coding and the causal impact of mouse cortex in a visual decision. *eLife* **10**, doi:10.7554/eLife.63163 (2021).

Pisupati, S., Chartarifsky-Lynn, L., Khanal, A. & Churchland, A. K. Lapses in perceptual decisions

reflect exploration. *eLife* **10**, doi:10.7554/eLife.55490 (2021).

Coen, P., Sit, T. P. H., Wells, M. J., Carandini, M. & Harris, K. D. Mouse frontal cortex mediates additive multisensory decisions. *Neuron* **111**, 2432-2447 e2413, doi:10.1016/j.neuron.2023.05.008 (2023).

Mor-Yosef, S., Samueloff, A., Modan, B., Navot, D. & Schenker, J. G. Ranking the risk factors for cesarean: logistic regression analysis of a nationwide study. *Obstet Gynecol* **75**, 944–947 (1990).

Hanks, T. D., Mazurek, M. E., Kiani, R., Hopp, E. & Shadlen, M. N. Elapsed decision time affects the weighting of prior probability in a perceptual decision task. *Journal Of Neuroscience.* **31**, 6339-6352, doi:10.1523/JNEUROSCI.5613-10.2011 (2011).

Brunswik, E. Probability as a determiner of rat behavior. *Journal of experimental psychology* **25**, 175 (1939).

Grant, D. A., Hake, H. W. & Hornseth, J. P. Acquisition and extinction of a verbal conditioned response with differing percentages of reinforcement. *Journal of experimental psychology* **42**, 1 (1951).

Hake, H. W. & Hyman, R. Perception of the statistical structure of a random series of binary symbols. *Journal of experimental psychology* **45**, 64 (1953).

Estes, W. K. & Straughan, J. Analysis of a verbal conditioning situation in terms of statistical learning theory. *Journal of experimental psychology* **47**, 225 (1954).

Goodnow, J. J. Determinants of choice-distribution in two-choice situations. *The American Journal of Psychology* **68**, 106-116 (1955).

Herrnstein, R. J. Relative and absolute strength of response as a function of frequency of reinforcement. *J Exp Anal Behav* **4**, 267-272, doi:10.1901/jeab.1961.4-267 (1961).

Vulkan, N. An economist's perspective on probability matching. *Journal of economic surveys* **14**, 101-118 (2000).

Sugrue, L. P., Corrado, G. S. & Newsome, W. T. Matching behavior and the representation of value in the parietal cortex. *Science* **304**, 1782-1787, doi:10.1126/science.1094765 (2004).

Baum, W. M. On two types of deviation from the matching law: bias and undermatching. *Journal of the experimental analysis of behavior* **22**, 231-242 (1974).

Whiteley, L. & Sahani, M. Implicit knowledge of visual uncertainty guides decisions with asymmetric outcomes. *J Vis* **8**, 2 1-15, doi:10.1167/8.3.2 (2008).

Feng, S., Holmes, P., Rorie, A. & Newsome, W. T. Can monkeys choose optimally when faced with noisy stimuli and unequal rewards? *PLoS Comput Biol* **5**, e1000284, doi:10.1371/journal.pcbi.1000284 (2009).

Lak, A. *et al.* Dopaminergic and Prefrontal Basis of Learning from Sensory Confidence and Reward Value. *Neuron* **105**, 700-711 e706, doi:10.1016/j.neuron.2019.11.018 (2019).

Fan, Y., Gold, J. I. & Ding, L. Ongoing, rational calibration of reward-driven perceptual biases. *eLife* **7**, doi:10.7554/eLife.36018 (2018).

Constantinople, C. M., Piet, A. T. & Brody, C. D. An Analysis of Decision under Risk in Rats. *Curr Biol* **29**, 2066-2074 e2065, doi:10.1016/j.cub.2019.05.013 (2019).

Cameron, E. L., Tai, J. C. & Carrasco, M. Covert attention affects the psychometric function of contrast sensitivity. *Vision Research.* **42**, 949-967, doi:10.1016/s0042-6989(02)00039-1 (2002).

Roy, N. A. *et al.* Extracting the dynamics of behavior in sensory decision-making experiments. *Neuron* **109**, 597-610 e596, doi:10.1016/j.neuron.2020.12.004 (2021).

Ashwood, Z. C. *et al.* Mice alternate between discrete strategies during perceptual decision-making. *Nat Neurosci* **25**, 201-212, doi:10.1038/s41593-021-01007-z (2022).

Link, S. W. *The wave theory of difference and similarity*. (Lawrence Erlbaum Associates, 1992).

Roy, N. A., Bak, J. H., Akrami, A., Brody, C. D. & Pillow, J. W. Efficient inference for time-varying behavior during learning. *Advances in Neural Information Processing Systems* **31** (2018).

Alais, D. & Burr, D. The ventriloquist effect results from near-optimal bimodal integration. *Curr Biol* **14**, 257-262, doi:10.1016/j.cub.2004.01.029 (2004).

Ernst, M. O. & Banks, M. S. Humans integrate visual and haptic information in a statistically optimal fashion. *Nature* **415**, 429-433, doi:10.1038/415429a (2002).

Battaglia, P. W., Jacobs, R. A. & Aslin, R. N. Bayesian integration of visual and auditory signals for spatial localization. *J Opt Soc Am A Opt Image Sci Vis* **20**, 1391-1397, doi:10.1364/josaa.20.001391 (2003).

Gu, Y., Angelaki, D. E. & Deangelis, G. C. Neural correlates of multisensory cue integration in macaque MSTd. *Nat Neurosci* **11**, 1201-1210, doi:10.1038/nn.2191 (2008).

Fetsch, C. R., Turner, A. H., DeAngelis, G. C. & Angelaki, D. E. Dynamic reweighting of visual and vestibular cues during self-motion perception. *Journal Of Neuroscience.* **29**, 15601-15612, doi:10.1523/JNEUROSCI.2574-09.2009 (2009).

Raposo, D., Sheppard, J. P., Schrater, P. R. & Churchland, A. K. Multisensory decision-making in rats and humans. *Journal Of Neuroscience.* **32**, 3726-3735, doi:10.1523/JNEUROSCI.4998-11.2012 (2012).

Sheppard, J. P., Raposo, D. & Churchland, A. K. Dynamic weighting of multisensory stimuli shapes decision-making in rats and humans. *J Vis* **13**, doi:10.1167/13.6.4 (2013).

Nikbakht, N., Tafreshiha, A., Zoccolan, D. & Diamond, M. E. Supralinear and Supramodal Integration of Visual and Tactile Signals in Rats: Psychophysics and Neuronal Mechanisms. *Neuron* **97**, 626-639 e628, doi:10.1016/j.neuron.2018.01.003 (2018).

Drugowitsch, J., DeAngelis, G. C., Klier, E. M., Angelaki, D. E. & Pouget, A. Optimal multisensory decision-making in a reaction-time task. *Elife* **3**, doi:10.7554/eLife.03005 (2014).

Busse, L., Wade, A. R. & Carandini, M. Representation of concurrent stimuli by population activity in visual cortex. *Neuron* **64**, 931-942, doi:10.1016/j.neuron.2009.11.004 (2009).

Carandini, M., Heeger, D. J. & Movshon, J. A. Linearity and normalization in simple cells of the macaque primary visual cortex. *Journal Of Neuroscience.* **17**, 8621-8644, doi:10.1523/JNEUROSCI.17-21-08621.1997 (1997).

Gardner, J. L. Optimality and heuristics in perceptual neuroscience. *Nat Neurosci* **22**, 514-523, doi:10.1038/s41593-019-0340-4 (2019).

Fernberger, S. W. Interdependence of judgments within the series for the method of constant stimuli. *Journal of experimental psychology* **3**, 126 (1920).

Leopold, D. A., Wilke, M., Maier, A. & Logothetis, N. K. Stable perception of visually ambiguous patterns. *Nat Neurosci* **5**, 605-609, doi:10.1038/nn0602-851 (2002).

Fischer, J. & Whitney, D. Serial dependence in visual perception. *Nat Neurosci* **17**, 738-743, doi:10.1038/nn.3689 (2014).

Gold, J. I., Law, C. T., Connolly, P. & Bennur, S. The relative influences of priors and sensory evidence on an oculomotor decision variable during perceptual learning. *J Neurophysiol* **100**, 2653-2668, doi:10.1152/jn.90629.2008 (2008).

Lueckmann, J. M., Macke, J. H. & Nienborg, H. Can Serial Dependencies in Choices and Neural Activity Explain Choice Probabilities? *Journal Of Neuroscience.* **38**, 3495-3506, doi:10.1523/JNEUROSCI.2225-17.2018 (2018).

Lak, A. *et al.* Reinforcement biases subsequent perceptual decisions when confidence is low, a widespread behavioral phenomenon. *eLife* **9**, doi:10.7554/eLife.49834 (2020).

Hermoso-Mendizabal, A. *et al.* Response outcomes gate the impact of expectations on perceptual decisions. *Nature communications* **11**, 1057, doi:10.1038/s41467-020-14824-w (2020).

Duque, D. & de la Rocha, J. Isolating perceptual biases caused by trial history during auditory categorization. *bioRxiv,* 2022.2001.2017.476581, doi:10.1101/2022.01.17.476581 (2022).

Seidemann, E. *Neuronal mechanisms mediating conversion of visual signals into perceptual decisions in a direction discrimination task* PhD thesis, Stanford University, (1998).

Shinn, M., Lam, N. H. & Murray, J. D. A flexible framework for simulating and fitting generalized drift-diffusion models. *Elife* **9**, doi:10.7554/eLife.56938 (2020).

Hanks, T. D. *et al.* Distinct relationships of parietal and prefrontal cortices to evidence accumulation. *Nature* **520**, 220-223, doi:10.1038/nature14066 (2015).

Lorteije, J. A. M. *et al.* The Formation of Hierarchical Decisions in the Visual Cortex. *Neuron* **87**, 1344-1356, doi:10.1016/j.neuron.2015.08.015 (2015).

Peixoto, D. *et al.* Decoding and perturbing decision states in real time. *Nature*, doi:10.1038/s41586-020-03181-9 (2021).

Sridharan, D., Steinmetz, N. A., Moore, T. & Knudsen, E. I. Distinguishing bias from sensitivity effects in multialternative detection tasks. *J Vis* **14**, doi:10.1167/14.9.16 (2014).

DeCarlo, L. T. On a signal detection approach to - alternative forced choice with bias, with maximum likelihood and Bayesian approaches to estimation. *J Math Psychol* **56**, 196-207, doi:10.1016/j.jmp.2012.02.004 (2012).

Green, D. M. & Swets, J. A. *Signal detection theory and psychophysics*. (Wiley, 1966).

McNicol, D. *A primer of signal detection theory*. (Psychology Press, 2005).

Ingleby, J. The separation of bias and sensitivity in multiple-choice tasks. *Perception* **2**, 295-305 (1973).

Treisman, M. & Faulkner, A. On the Choice between Choice Theory and Signal Detection Theory. (1985).

DeCarlo, L. T. Signal detection theory and generalized linear models. *Psychol Methods* **3**, 186-205, doi:Doi 10.1037/1082-989x.3.2.186 (1998).

Ratcliff, R., Smith, P. L., Brown, S. D. & McKoon, G. Diffusion Decision Model: Current Issues and History. *Trends Cogn Sci* **20**, 260-281, doi:10.1016/j.tics.2016.01.007 (2016).

Shadlen, M. N., Hanks, T. D., Churchland, A. K., Kiani, R. & Yang, T. in *Bayesian Brain: Probabilistic Approaches to Neural Coding*   (eds Kenji Doya, Shin Ishii, Alexandre Pouget, & Rajesh P.N. Rao) Ch. 10, (2006).

Feller, W. *An Introduction to Probability Theory and its Applications*. 3rd edn, Vol. 1 (John Wiley & Sons, 1968).

Urai, A. E., de Gee, J. W., Tsetsos, K. & Donner, T. H. Choice history biases subsequent evidence accumulation. *Elife* **8**, doi:10.7554/eLife.46331 (2019).