Task-related modulation of event-related potentials does not reflect changes to sensory representations

Reuben Rideaux

School of Psychology, The University of Sydney, Camperdown, Australia
Queensland Brain Institute, The University of Queensland, St Lucia, Australia
corresponding author: reuben.rideaux@sydney.edu.au

ABSTRACT

Attention supports efficient perception by increasing the neural signals of targets while supressing those of distractors. Decades of work studying the event-related potentials of electroencephalography (EEG) recordings have established our understanding of attention in the human brain, but many aspects of this phenomenon remain unknown. Several recent studies suggest that multivariate analyses may provide new insights into how attention shapes the neural representations of stimuli; however, it is unclear whether the increased multivariate decoding accuracy associated with task relevance represents a change in the stimulus representation or an additional cognitive process. To understand what the change in multivariate information that is associated with task relevance reflects, here we used inverted encoding to characterize how task relevance shapes the neural representation of space and colour. For both spatial and feature-based tasks, we found that the change in the EEG recordings associated with task relevance is not related to the stimulus representation. Rather, our findings indicate that this phenomenon reflects an additional cognitive process, such as target recognition.

INTRODUCTION

To efficiently perceive our environment, the brain selectively filters sensory information using a variety of mechanisms, collectively referred to as *attention*. Attention can be captured by salient stimulus properties (i.e., *bottom-up attention*) or directed by goal-driven behaviour (i.e., *top-down attention*). Top-down attention is supported by a network of regions across frontal and parietal cortices (Buschman & Miller, 2007; Suzuki & Gottlieb, 2013; Ungerleider, 2000; Womelsdorf et al., 2008), which influence processing in sensory cortices and thalamus (Brefczynski & DeYoe, 1999; Gandhi et al., 1999; Luck et al., 1997; Motter, 1993; Treue & Maunsell, 1996), for example, by adjusting the tuning profiles of neurons to increase sensitivity for attended features (David et al., 2008; Womelsdorf et al., 2008). This increases the signal-to-noise ratio of neural activity associated with attended, relative to unattended, features (Desimone & Duncan, 1995), and is associated with increased test-retest reliability (Arazi et al., 2019).

Top-down attention is typically categorized into two forms: spatial (attending to a particular spatial location) and feature-based (attending to a specific sensory feature, such as the colour red); however, other attentional processes have been identified, such as object-based attention (Chen, 2012; Duncan, 1984). Note, here we refer to covert spatial attention, i.e., fixating one location while attending to another. While spatial and feature-based attention appear to have common phenomenology, such as producing a shift in tuning preference towards the attended location/feature (David et al., 2008; Womelsdorf et al., 2008), theoretical modelling work and empirical psychophysical evidence in humans suggests that they are supported by distinct neural mechanisms (Herrmann et al., 2012; Ling et al., 2009).

Understanding the neural mechanisms of attention remains a central pursuit in cognitive neuroscience. Among the tools available to study brain activity in humans, arguably the most common method used to investigate attention is electroencephalography (EEG). Hundreds of studies have reported effects of attention on EEG recordings, both in frequency and time domains, some of which are highly robust; however, it is still not entirely clear what neural processes these differences represent.

Studies that leverage data in the frequency domain typically involve presenting

temporally periodic stimuli and using Fourier analysis of the recorded EEG recordings

to estimate power at the stimulus frequency. For example, steady-state visually

evoked potentials (Friman et al., 2007; Norcia et al., 2015) and frequency tagging

(Regan & Heron, 1969). This approach has several benefits, including being robust to

noise (Srinivasan et al., 2006), and has been used to track the focus of attention

(Toffanin et al., 2009). However, it necessarily forfeits the temporal dynamics of signal

changes associated with attention, which can obscure the underlying mechanism.

EEG studies of attention in the time domain usually entail presenting stimuli to

participants and analyzing common periods of neural activity around the presentations

(i.e., epochs), which target the stimulus event-related potentials (ERP). The classical,

univariate, analytical approach has identified ERP components that can be modulated

by task demands associated with attention, e.g., the P3 (Polich & Bondurant, 1997;

Sutton et al., 1965; Verleger, 1988). Univariate analysis of ERPs preserves the

temporal dynamics of changes in the neural signals associated with attention, which

can be used to infer underlying mechanisms. For example, by distinguishing

feedforward from other processes, e.g., lateral and feedback (Zhang & Luck, 2009).

However, it can be challenging to interpret how cognitive processes such as attention

alter the neural representation of stimuli from univariate variations in sensor voltages.

More recently, several studies have used multivariate decoding of EEG

recordings to study attention. Unlike univariate analyses, this method considers the

pattern of signals (across the scalp and/or time) and can be used to measure the

difference between the neural representation of two or more stimuli (Alilović et al.,

2019; Bae & Luck, 2018). This method has been used to study both spatial and

feature-based attention. For example, signals evoked by a range of visual stimuli are

more reliably distinguished (i.e., accurately decoded) from ~200 ms following stimulus

presentation when they share a feature (e.g., colour/orientation) that is task relevant

(Goddard et al., 2022; Grootswagers et al., 2021; Smout et al., 2019). Similarly, task-

relevant visual stimuli can be more accurately decoded when their spatial location is

cued prior to presentation (Foster et al., 2020, 2021). This increased decoding

accuracy is not explained by stimulus expectancy nor engagement of working memory

(Moerel et al., 2022), supporting the notion that it reflects the deployment of attention.

The change associated with task relevance may reflect reduced neural variability of
the stimulus representation (Arazi et al., 2019), for example, through an increase in
the gain of attended features (Luck et al., 1997). However, increased decoding
accuracy could also be produced by an additional cognitive process, which is
prompted by the task relevant (target) stimulus feature and may not reflect feature-
specific changes to the neural representation of the stimulus.

To test whether the influence of task relevance on EEG recordings reflects a
change to the sensory representation of the attended stimulus, here we used a
recently developed implementation of a multivariate analysis known as *inverted*
encoding to decode EEG recordings of responses to coloured stimuli presented at
different spatial locations (Brouwer & Heeger, 2009; Harrison et al., 2023; Rideaux et
al., 2023). Specifically, we used this method to test whether spatial and feature-based
attention change the neural representation of the same stimulus by making either the
spatial location or colour of stimulus task relevant. For both spatial and feature-based
tasks, we replicated the increased decoding accuracy that has been reported in
previous studies (Foster et al., 2020, 2021; Goddard et al., 2022; Grootswagers et al.,
2021; Smout et al., 2019). By comparing the effects associated with spatial and
feature-based attention, we show that the change in the EEG recordings associated
with task relevance is not feature specific. Indeed, our findings indicate that this
phenomenon reflects an additional cognitive process, such as target recognition.

METHOD

Participants. Forty-two neurotypical human adults (mean±standard deviation age, 20.9±2.9 years; 10 males, 30 females, 2 non-binary) participated in the experiment. The data of one participant was omitted from analysis due to excessive eye movements. Sample size was informed by previous studies using similar neural decoding methods (Harrison et al., 2023; Rideaux et al., 2023). Observers were recruited from The University of Sydney and had normal or corrected-to-normal vision (assessed using a standard Snellen eye chart). All participants were naïve to the aims of the experiment and gave informed written consent. The experiment was approved by The University of Sydney Human Research Ethics Committee.

Apparatus. The experiment was conducted in a dark, acoustically and electromagnetically shielded room. The stimuli were presented on a 24-inch ASUS VG248QE Gaming Monitor (ASUS, Taipei, Taiwan) with 1920 x 1080 resolution and a refresh rate of 144 Hz. The monitor was calibrated using a SpyderX Pro (Datacolor, Lawrenceville, NJ). Viewing distance was maintained at 70 cm using a forehead and chinrest, meaning the screen subtended 41.47º x 23.33º (each pixel 1.3' x 1.3'). Stimuli were generated in MATLAB v2020a (The MathWorks, Inc., Matick, MA) using Psychophysics Toolbox (Brainard, 1997; Pelli, 1997) v3.0.18.13 (see http://psychtoolbox.org/). EEG was recorded on a 64 channel BrainVision ActiCap system (Brain Products GmbH).

Stimuli, task, and procedure. The stimuli comprised coloured arcs (inner ring, 0.25º; outer ring, 4.25º) extending 45º polar angle on a mid-grey background. A centrally positioned black fixation dot (radius 0.25º) was presented to reduce eye movements. Trials consisted of 30 arc stimuli (location and colour randomly selected between 0-360º) presented for 0.2 s each, separated by a blank 0.1 s inter-stimulus-interval. The colour angle referenced values that were drawn from a circle in the CIE $L^*a^*b^*$ colour space. This circle was centred in the colour space at ($L = 70$, $a = 20$, $b = 38$) with a radius of 60 (Zhang & Luck, 2008). Participants were then instructed to use the arrow keys to indicate the number of target stimuli that were presented during the preceding sequence. Task accuracy was calculated as the difference between the number of presented and reported targets, with stimuli within 10º of the target location/colour were considered targets. This was repeated 8 times per block. Participants performed

18 blocks of trials (~60 min), receiving feedback on their detection accuracy at the end

of each block. At the beginning of each block, target stimuli were identified as either

those appearing at a defined location or colour, pseudo-randomly counterbalanced

across the session. Target locations/colours were held constant for each participant,

but pseudo-randomly counterbalanced across participants, to approximate a uniform

distribution of target locations/colours between 0-360º.

EEG. The EEG recordings were digitised at 1024 Hz sampling rate with a 24-bit A/D

conversion. The 64 active scalp Ag/AgCl electrodes were arranged according to the

international standard 10–20 system for electrode placement (Oostenveld &

Praamstra, 2001) using a nylon head cap and with an online reference of FCz. Offline

EEG pre-processing was performed using EEGLAB v2021.1 (Delorme & Makeig,

2004). The data were initially down-sampled to 512 Hz and subjected to a 0.1 Hz high-

pass filter to remove slow baseline drifts and a 45.0 Hz low-pass filter to remove high-

frequency noise/artifacts. Data were then re-referenced to the common average

before being epoched into segments around each stimulus (-0.2 s to 1.5 s from the

stimulus onset). The stimuli were presented rapidly ~3 Hz, so epochs contained ERPs

produced by multiple stimuli. However, stimuli were intentionally randomly sampled,

such these additional signals could not provide any information that could be used to

decode the current stimulus.

Neural Decoding. To characterise sensory representations of the stimuli, we used an

inverted modelling approach to reconstruct either the location or the colour of the arcs

from the EEG recordings (Brouwer & Heeger, 2011). A theoretical (forward) model

was nominated that described the measured activity in the EEG sensors given the

location/colour of the presented arc. The forward model was then used to obtain the

inverse model that described the transformation from EEG sensor activity to stimulus

location/colour. For the main decoding analyses, the forward and inverse models were

obtained using a ten-fold cross-validation approach in which 90% of the data were

used to obtain the inverse model on which the remaining 10% were decoded. For the

generalization analyses, the forward and inverse models were obtained using all the

data from one condition and used to decode data from another condition.

Similar to previous work (Brouwer & Heeger, 2009), the forward model

comprised five hypothetical channels, with evenly distributed idealized location/colour

preferences between 0° and 360°. Each channel consisted of a half-wave rectified

sinusoid raised to the fifth power. The channels were arranged such that a tuning curve

of any location/colour preference could be expressed as a weighted sum of the five

channels. The observed EEG activity for each presentation could be described by the

following linear model:

$$\mathbf{B} = \mathbf{WC} + \mathbf{E} \qquad\qquad (1)$$

where $\mathbf{B}$ indicates the (m sensors × n presentations) EEG data, $\mathbf{W}$ is a weight matrix

(m sensors × 5 channels) that describes the transformation from EEG activity to

stimulus location/colour, $\mathbf{C}$ denotes the hypothesized channel activities (5 channels ×

n presentations), and $\mathbf{E}$ indicates the residual errors.

To compute the inverse model, we estimated the weights that, when applied to

the data, would reconstruct the underlying channel activities with the least error. In line

with previous magnetencephalography work (Kok et al., 2017; Mostert et al., 2015),

when computing the inverse model, we deviated from the forward model proposed by

(Brouwer & Heeger, 2009) by taking the noise covariance into account to optimize it

for EEG data, given the high correlations between neighbouring sensors. We then

estimated the weights that, when applied to the data, would reconstruct the underlying

channel activities with the least error. Specifically, $\mathbf{B}$ and $\mathbf{C}$ were demeaned such that

their average over presentations equalled zero for each sensor and channel,

respectively. The inverse model was then estimated using either a subset selected

through cross-fold validation) or all the data in one condition. The hypothetical

responses of each of the five channels were calculated from the training data, resulting

in the response row vector $\mathbf{c}_{train,i}$ of length n_{train} presentations for each channel i.

The weights on the sensors $\mathbf{w}_i$ were then obtained through least squares estimation

for each channel:

$$\mathbf{w}_i = \mathbf{B}_{train}\mathbf{c}_{train,i}^{\mathrm{T}}\left(\mathbf{c}_{\text{train,i}}\mathbf{c}_{train,i}^{\mathrm{T}}\right)^{-1} \qquad (2)$$

188   where $\mathbf{B}_{train}$ indicates the (m sensors × n_{train} presentations) training EEG data.

189   Subsequently, the optimal spatial filter $\mathbf{v}_i$ to recover the activity of the ith channel was

190   obtained as follows (Mostert et al., 2015):

$$\mathbf{v}_i = \frac{\widetilde{\Sigma}_i^{-1}\mathbf{w}_i}{\mathbf{w}_i^{\mathrm{T}}\widetilde{\Sigma}_i^{-1}\mathbf{w}_i} \qquad\qquad (3)$$

191 where $\widetilde{\Sigma}_i$ is the regularized covariance matrix for channel i. Incorporating the noise

192 covariance in the filter estimation leads to the suppression of noise that arises from

193 correlations between sensors. The noise covariance was estimated as follows:

$$\widehat{\Sigma}_i = \frac{1}{n_{\text{train}} - 1} \boldsymbol{\varepsilon}_i \boldsymbol{\varepsilon}_i^{\text{T}} \tag{4}$$

$$\boldsymbol{\varepsilon}_i = \mathbf{B}_{train} - \mathbf{w}_i \mathbf{c}_{train,i} \tag{5}$$

194 where n_{train} is the number of training presentations. For optimal noise suppression,

195 we improved this estimation by means of regularization by shrinkage using the

196 analytically determined optimal shrinkage parameter (Mostert et al., 2015), yielding

197 the regularized covariance matrix $\widetilde{\Sigma}_i$.

198   For each presentation, we decoded location and colour by converting the

199 channel responses to polar form:

$$z = \mathbf{c} \cdot e^{2i\boldsymbol{\varphi}} \tag{6}$$

200 and calculating the estimated angle:

$$\hat{\theta} = \frac{\arg(z)}{2} \tag{7}$$

201 where $\mathbf{c}$ is a vector of channel responses and $\boldsymbol{\varphi}$ is the vector of angles at which the

202 channels peak.

203   Stimulus location and colour properties were sampled from continuous

distributions, but to reliably characterize these features across their dimension, we

grouped presentations into 36 evenly spaced bins from 0-360°, relative to each

participant's attended location/colour. From the decoded locations/colours, we

computed two estimates: *accuracy* and *precision*. Accuracy represented the similarity

of the decoded location/colour to the presented location/colour (Kok et al., 2017), and

was expressed by projecting the mean resultant (averaged across presentations within

the same stimulus location/colour bin) of the difference between decoded and arc

location/colour onto a vector with 0°:

$$\hat{r}_\theta = \text{Re}[\bar{R}], \quad \bar{R} = \frac{1}{n} \sum_{j=1}^{n} \exp\left(i\left(\hat{\theta}_j - \theta\right)\right) \tag{8}$$

212 Precision was estimated by calculating the angular deviation (Zar, 1999) of the

213 decoded locations/colours within each location/colour bin:

$$\hat{\sigma}_\theta = \sqrt{2(1 - |\bar{R}|)} \tag{9}$$

214   and normalized, such that values ranged from 0 to 1, where 0 indicates a uniform

215   distribution of decoded location/colour across all location/colour (i.e., chance-level

216   decoding) and 1 represents perfect consensus among decoded location/colour:

$$\hat{p}_\theta = 1 - \frac{2\hat{\sigma}_\theta}{\sqrt{2}} \qquad (10)$$

Prior to the main neural decoding analyses, we established the sensors that

contained the most location/colour information by treating time as the decoding

dimension and obtaining inverse models for each sensor, using ten-fold cross-

validation. This analysis revealed that location/colour was primarily represented in

posterior sensors (**Fig. 1a**); thus, for all subsequent analyses we only included signals

from the parietal, parietal-occipital, and occipital sensors.

Eye tracking. Gaze direction recordings were epoched to the duration of stimulus

presentations. To reduce the influence of eye movements on the results, stimulus

presentations in which participants' gaze direction exceeded 2° eccentricity from

fixation were omitted from analyses (average±standard deviation omitted

presentations, 4.2±8.0%). The data from one participant was omitted from analyses

due to excessive eye movements, characterized as having exceeded the threshold for

omission on >33% of presentations.

Statistical analyses. Statistical analyses were performed in MATLAB v2020a and

CircStat Toolbox v1.12.0.0 (Berens, 2009). For analyses of parameter estimates as a

function of location/colour and time, a two-dimensional circular-linear cluster

correction was applied to remove spurious significant differences. First, at each

location/colour and time point, the effect size of accuracy/precision was calculated.

Next, we calculated the summed value of these statistics (separately for positive and

negative values) within contiguous featural-temporal clusters of significant values. We

then simulated the null distribution of the maximum summed cluster values using

permutation (n=1000) of the sign or condition labels, for single and paired *t*-test

comparisons, respectively, from which we derived the 95% percentile threshold value.

Clusters identified in the data with a summed effect-size value less than the threshold

were considered spurious and removed. Prior to cluster analysis, we smoothed the

parameter estimates along the feature dimension using a uniform kernel (size, 4).

Data Availability. The EEG data generated in this study have been deposited in the

following OSF database: https://osf.io/3k9cx/

RESULTS

To investigate if attention shapes the neural representation of visual features, we recorded observers' brain activity using EEG while they viewed blocks of rapidly presented coloured arcs. Observers were instructed to report the number of target arcs in each block, which were defined either by their spatial location or colour, as indicated at the beginning of the block (**Fig. 1a**). The location and colour of stimuli were selected at random. Thus, stimuli in target location blocks served to produce brain activity associated with spatial location being task relevant and colour being task irrelevant, and those in target colour blocks produced activity associated with colour being task relevant and spatial location being task irrelevant.

For all analyses of EEG recordings, we used inverted encoding to decode the visual properties (location or colour) of presented stimuli. From the trial-by-trial decoded properties, we derived summary parameter estimates of *accuracy* (the similarity between the decoded and presented stimulus property) and *precision* (the trial-by-trial reliability of the decoded property) as a function of time and property dimension.

We first computed the spatial configuration of the stimulus representation across the scalp by decoding location and colour information separately for each EEG sensor (**Fig. 1b**). We found that both stimulus properties were primarily represented in posterior sensors; however, location information was represented bilaterally while colour information was concentrated at the midline. For both properties, there was higher decoding accuracy for the corresponding task relevant condition across all sensors. The difference in accuracy between task relevant and irrelevant conditions was concentrated at posterior sensors (**Fig. 1c**); however, there was also a cluster of fontal electrodes that showed increased decoding accuracy of location in the task relevant condition, which could indicate the contribution of eye movements. To reduce the possible influence of eye movements, in all subsequent analyses, we omitted trials in which observers' gaze deviated >2° from fixation and only analyzed EEG recordings from posterior sensors (**Fig 1b, c**, white dots).

Figure 1. Experimental design and topographical distribution of stimulus information. a)
Participants viewed blocks of 30 rapidly presented arcs (random polar angle and colour) and were
tasked with reporting the number of target arcs, which were defined by either a particular location or
colour. **b)** Decoding accuracy of the stimulus location (top row) and colour (bottom row) from the EEG
recordings in blocks where the decoded stimulus property was either task irrelevant or relevant,
across sensors. **c)** The difference between task irrelevant and relevant decoding accuracy for location
and colour. White dots in (**b, c**) indicate the sensors from which information was used in all
subsequent analyses.

We next computed decoding accuracy and precision as a function of time and
distance from the target stimulus property. We found that the accuracy of spatial
location increased sharply from ~60 ms following stimulus onset and was relatively
stable across time and robust to additional incoming information, i.e., subsequently
presented stimuli, consistent with previous work (King & Wyart, 2021; Rideaux et al.,
2023; **Fig. 2a**). However, task relevance increased the duration for which decoding
accuracy was sustained, from ~1000 ms to ~1400 ms (**Fig. 2b**). Specifically, task
relevance significantly increased the decoding accuracy of the target stimulus location
from ~200 - 1200 ms following stimulus presentation (**Fig. 2c**). We found a similar
pattern of results for colour. However, the decoding accuracy of colour increased later
(at ~100 ms) than that for location and was only sustained for ~500 ms when task
irrelevant (**Fig. 2d, e**). Further, task relevance significantly increased accuracy for
colour at both the target and opposite-to-target colour, producing a pattern of
increased accuracy in the shape of a Mexican hat wavelet, centered on the target
colour (**Fig. 2f**). The difference in accuracy between task irrelevant and relevant
conditions was larger for colour. This may indicate that attention was more strongly
engaged when detecting colour targets, for example, because it was more challenging
than detecting targets based on location. Indeed, we found that (behavioural) detection
accuracy for targets defined by location was significantly better than when defined by
colour (t_{40}=3.31, p=.002).

Figure 2. Accuracy of the neural representation of location and colour across time. a) A heatmap of the decoding accuracy for all spatial locations in the task irrelevant blocks (relative to participants' target location) as a function of time (relative to stimulus onset); the white outline denotes cluster-corrected regions of statistical significance. The plots above and to the right of the heatmap show the temporal dynamics of accuracy (averaged across all locations) and the location-specific differences in accuracy (averaged across time), respectively. The illustration in the top-right corner indicates the task block/s data used to train (light grey triangle) and test (dark grey triangle) the decoder, and the decoded stimulus property. **b**) Same as (**a**), but for blocks where stimulus location was task relevant. **c**) The difference in decoding accuracy between (**b**) task irrelevant and (**a**) relevant conditions. **d-f**) The same as (**a-c**), but for colour. Note, the shaded regions in the plots positioned above and to the right of heatmaps indicate ±SEM. The temporally averaged accuracy plots do not include data prior to stimulus onset. The colour ranges used in the heatmaps (**a,b,d,e**) are normalized to the minimum and maximum values, to facilitate interpretation of relative differences; the adjacent plots should be used to gauge absolute values. The colour range used in (**c,f**) are normalized to ± absolute maximum value.

For decoding precision, we found a similar pattern of results as those for accuracy (**Fig. 3**). However, decoding precision in the task relevant conditions was only sustained until ~1000 ms following stimulus onset (**Fig. 3b, e**), and the precision of colour did not significantly exceed chance in the task irrelevant condition (**Fig. 3d**).

Figure 3. Precision of the neural representation of location and colour across time. a) A heatmap of the decoding precision for all spatial locations in the task irrelevant blocks (relative to participants' target location) as a function of time (relative to stimulus onset); the white outline denotes cluster-corrected regions of statistical significance. The plots above and to the right of the heatmap show the temporal dynamics of precision (averaged across all locations) and the location-specific differences in precision (averaged across time), respectively. The illustration in the top-right corner indicates the task block/s data used to train (light grey triangle) and test (dark grey triangle) the decoder, and the decoded stimulus property. **b)** Same as (**a**), but for blocks where stimulus location was task relevant. **c)** The difference in decoding precision between (**b**) task irrelevant and (**a**) relevant conditions. **d-f)** The same as (**a-c**), but for colour. Note, the shaded regions in the plots positioned above and to the right of heatmaps indicate ±SEM. The temporally averaged precision plots do not include data prior to stimulus onset. The colour ranges used in the heatmaps (**a,b,d,e**) are normalized to the minimum and maximum values, to facilitate interpretation of relative differences; the adjacent plots should be used to gauge absolute values. The colour range used in (**c,f**) are normalized to ± absolute maximum value.

Consistent with previous work (Goddard et al., 2022; Grootswagers et al., 2021; Smout et al., 2019), we found that task relevance increases and sustains the decoding accuracy of visual properties (spatial location and colour) from EEG recordings from ~200 ms following stimulus onset. We also found that decoding precision increased during this period, demonstrating that task relevance increases the test-retest reliability of the neural signal. The temporal dynamics of the effect appears similar for both spatial location and colour tasks, despite a considerable delay in the emergence of the neural representations of colour, relative to location.

The increase in decoding accuracy associated with task relevance has previously been attributed to improved encoding precision of the target feature (Ungerleider, 2000). If this were true, we would not expect the pattern of activity evoked by a target stimulus property (e.g., up/red) to qualitatively change when

attended, but for it to be elicited more reliably, i.e., less test-retest variability (Arazi et

al., 2019). To investigate this interpretation of the effect of task relevance, we

computed the accuracy and precision of the neural signals in the task relevant

conditions using inverted models trained on data from the task irrelevant conditions.

For both location and colour, we found that task relevance did not significantly increase

decoding accuracy (**Fig. 4a-d**). Rather, task relevance led to a small decrease in

accuracy for spatial location (**Fig. 4b**). By contrast, for both location and colour,

decoding precision was significantly increased by task relevance from ~200 ms around

the target stimulus property (**Fig. 4e-h**). The finding that task relevance increased the

decoding precision, but not the accuracy, of spatial location and colour when using

inverted models trained on the task irrelevant properties, shows that the pattern of

neural activity associated with the task relevance stimulus properties became more

reliable, but qualitatively different from that elicited by the task irrelevant properties.

Figure 4. Generalizability between task irrelevant and relevant neural representations. a) A heatmap of the decoding accuracy for all spatial locations in the task relevant blocks as decoded by a model trained on data from the task irrelevant blocks. Accuracy is shown as a function of location (relative to participants' target location) and time (relative to stimulus onset); the white outline denotes cluster-corrected regions of statistical significance. The plots above and to the right of the heatmap show the location-specific differences in accuracy (averaged across time) and the temporal dynamics of accuracy (averaged across all locations), respectively. The illustration in the top-right corner indicates the task block/s data used to train (light grey triangle) and test (dark grey triangle) the decoder, and the decoded stimulus property. **b)** Same as (**a**), but for the difference between accuracy in task irrelevant and relevant blocks, decoded with a model trained on signals from task irrelevant blocks. **c, d)** Same as (**a, b**), but for colour. **e-h)** Same as (**a-d**), but for decoding precision. Note, the shaded regions in the plots positioned above and to the right of heatmaps indicate ±SEM. The temporally averaged accuracy and precision plots do not include data prior to stimulus onset. The colour ranges used in the heatmaps (**a,c,e,g**) are normalized to the minimum and maximum values, to facilitate interpretation of relative differences; the adjacent plots should be used to gauge absolute values. The colour range used in (**b,d,f,h**) are normalized to ± absolute maximum value.

The qualitative change in the pattern of neural activity associated with a stimulus property being task relevant could reflect an additional cognitive process, e.g., recognition of a target stimulus. If this were true, we would expect that a similar pattern of activity would be produced by both tasks. To test this, we normalized all data to participants' target property, i.e., the target colour and location were positioned 0°, and decoded each stimulus property using an inverted model trained to decode

the other property. On each presentation, the stimulus location and colour were

selected randomly and therefor orthogonal. Thus, as expected, for the task irrelevant

properties we found that decoding accuracy did not significantly exceed chance (**Fig.**

5a, d). By contrast, the accuracy of task relevant properties significantly exceeded

chance from ~200 ms following stimulus onset, particularly at the target property (**Fig.**

5b, e). These results show that the pattern of activity elicited by task relevant demands,

which emerges at ~200 ms following stimulus onset, is not feature specific.

Figure 5. Generalizability between stimulus properties. a) A heatmap of the decoding accuracy for
all spatial locations in the task irrelevant blocks as decoded by model trained to decode colour in the
unattended blocks. Accuracy is shown as a function of location (relative to participants' target
location) and time (relative to stimulus onset); the white outline denotes cluster-corrected regions of
statistical significance. The plots above and to the right of the heatmap show the temporal dynamics
of accuracy (averaged across all locations) and the location-specific differences in accuracy
(averaged across time), respectively. The illustration in the top-right corner indicates the task block/s
data used to train (light grey triangle) and test (dark grey triangle) the decoder, and the decoded
stimulus property. **b**) Same as (**a**), but for blocks where stimulus location was task relevant. **c**) The
difference in decoding precision between (**b**) task irrelevant and (**a**) relevant conditions. **d-f**) The
same as (**a-c**), but for colour. Note, the shaded regions in the plots positioned above and to the right
of heatmaps indicate ±SEM. The temporally averaged accuracy plots do not include data prior to
stimulus onset. The colour ranges used in the heatmaps (**a,b,d,e**) are normalized to the minimum and
maximum values, to facilitate interpretation of relative differences; the adjacent plots should be used
to gauge absolute values. The colour range used in (**c,f**) are normalized to ± absolute maximum
value.

DISCUSSION

Attention supports efficient perception by increasing the neural signals of target locations/features while supressing the those of distractors. The influence of task demands that engage attention can be reliably detected within EEG recordings. Decades of univariate ERP analyses have provided foundational understanding of attention in the human brain, but many aspects of this phenomenon remain unknown. Multivariate analyses may provide a means of addressing these questions. EEG work using multivariate linear decoding has reliably demonstrated increased decoding accuracy for task relevant features from ~200 ms following stimulus onset (Goddard et al., 2022; Grootswagers et al., 2021; Smout et al., 2019), which is not explained by working memory load or expectation (Moerel et al., 2022). While some work indicates that this effect is not linked to feedforward processing (Alilović et al., 2019), other work has used this effect to distinguish between the influence of spatial and feature-based attention on stimulus representation (Goddard et al., 2022). Neurophysiological work in macaque has shown that attention alters the representation of stimuli in sensory cortices (Brefczynski & DeYoe, 1999; Gandhi et al., 1999; Luck et al., 1997; Motter, 1993; Treue & Maunsell, 1996). However, it is unclear whether the increased decoding accuracy from ~200 ms represents a change in the stimulus representation or an additional cognitive process. To understand what the change in multivariate information that is associated with task demands reflects, here we used inverted encoding to characterize how spatial and feature-based tasks shape the representation of space and colour.

We found that task relevance increased decoding accuracy from ~200 ms following stimulus onset, for both spatial location and colour. This result is analogous to those of Moerel et al. (2022), who found that orientation decoding accuracy for colours bars was better when one of the bars was task relevant (e.g., horizontal blue) We further found that the difference in decoding accuracy formed a Gaussian profile when assessed as a function of the distance from the target stimulus property, such that it was maximally improved at the target location/colour. It's likely that in previous studies this pattern of feature-dependent decoding accuracy was obscured by averaging decoding accuracy across stimulus-features (Moerel et al., 2022). We found a similar pattern of results for decoding precision, which provides a direct index

of the test-retest reliability of the neural response. These findings seemed to support

the interpretation that the increased decoding accuracy for task relevant properties

reflects more stable stimulus representations. However, we also found that the task-

related neural information generalized across orthogonal stimulus properties (location

and colour) but not between the same property from task irrelevant to relevant blocks.

These findings provide compelling evidence that the task-related change in ERPs do

not reflect a change in the stimulus representation. Rather, the increased decoding

accuracy of task relevant features from EEG recordings would appear to reflect a

change in the neural representation that is stimulus invariant. A change in the neural

representation of this kind likely reflects an additional cognitive process, such as target

recognition. That is, participants may be comparing the incoming sensory information

with a mnemonic template of the target feature (Myers et al., 2015). While maintaining

this this template does not appear to alter the sensory representation, a match

between the template and the stimulus produced an additional neural response that

was the same regardless of whether the template and stimulus were defined by spatial

location or colour. However, more work is needed to understand the nature of this

additional process.

While our findings may be inconsistent with some interpretations of recent

studies using multivariate analyses (Goddard et al., 2022; Smout et al., 2019), they

are consistent with results from univariate ERP work. In particular, the timing of the

increased decoding (~200 ms following stimulus onset) aligns with the onset of the P3

component (Polich & Bondurant, 1997; Sutton et al., 1965; Verleger, 1988). This

component is reliably modulated by attention (Pfefferbaum et al., 1985), however, its

topographical representation is relatively invariant to input modality (Ji et al., 1999).

The P3 is also modulated by stimulus probability (Duncan-Johnson & Donchin, 1977),

but as we used a uniform distribution of stimuli, this is unlikely to account for our

results. Rather, our findings indicate that the increased decoding accuracy associated

with task relevance, observed from ~200 ms following stimulus onset, reflects a

change in neural activity that is stimulus invariant. The increase seems to align with

the timing of the P3 component and likely represents an additional cognitive process,

such as target recognition. While this signal is not suitable for studying the influence

of attention on stimulus representation, further investigation of the process would

provide further understanding of the cascade of cognitive processes associated with
target detection.

One limitation of the current study is that we did not have a condition in which
attention was directed away from the decoded stimuli, for example, by using a fixation
task. Foster et al. (2021) found that decoding accuracy was higher for stimuli that were
the focus of spatial attention, compared to a those where attention directed away.
While they observed improved decoding accuracy in the earliest stages of sensory
processing (~80 ms), it is unclear to what extent the lingering activity from previous,
correlated, stimuli confounded this result. Here we avoided this confound by
presenting stimuli randomly, such that preceding and subsequent stimuli did not
produce activity that could improve the decoding accuracy of the current stimulus.
While we did not include a condition in which attention was directed away from all
stimuli, in the spatial target condition, participants attention was directed away from
stimuli outside the target location. Thus, if spatial attention altered the sensory
representation of the attended stimuli, we would expect to see improved decoding
accuracy for the target location, relative to other locations, during the feedforward
sweep of the visual cascade, i.e., ~50-100 ms, yet we only observed increased
accuracy later (~200 ms).

Previous EEG work has found evidence that early ERP components are
modulated by task relevance (Zhang & Luck, 2009), suggesting that changes to
feedforward stimulus-evoked activity can be detected with EEG. By contrast, recent
work applying multivariate analyses to EEG recordings found no evidence that spatial
task relevance changed decoding accuracy during feedforward processing (Alilović et
al., 2019). Similarly, here we found no evidence that task relevance (spatial or feature-
based) altered feedforward processing. While our findings urge caution when
interpreting multivariate decoding results, if future work can develop experimental
paradigms that can produce reliable attention-related changes in activity evoked
during feedforward processing, these data-driven analytic techniques combined with
forward modelling may provide key insights into how spatial and feature-based
attention influence sensory processing in humans.

REFERENCES

Alilović, J., Timmermans, B., Reteig, L. C., van Gaal, S., & Slagter, H. A. (2019). No Evidence
that Predictions and Attention Modulate the First Feedforward Sweep of Cortical
Information Processing. *Cerebral Cortex*, *29*(5), 2261–2278.
https://doi.org/10.1093/cercor/bhz038

Arazi, A., Yeshurun, Y., & Dinstein, I. (2019). Neural Variability Is Quenched by Attention.
Journal of Neuroscience, *39*(30), 5975–5985.
https://doi.org/10.1523/JNEUROSCI.0355-19.2019

Bae, G.-Y., & Luck, S. J. (2018). Dissociable Decoding of Spatial Attention and Working
Memory from EEG Oscillations and Sustained Potentials. *The Journal of Neuroscience*,
38(2), 409–422. https://doi.org/10.1523/JNEUROSCI.2860-17.2017

Berens, P. (2009). CircStat: A MATLAB Toolbox for Circular Statistics. *Journal of Statistical
Software*, *31*(10). https://doi.org/10.18637/jss.v031.i10

Brainard, D. H. (1997). The Psychophysics Toolbox. *Spatial Vision*, *10*(4), 433–436.
https://doi.org/10.1163/156856897X00357

Brefczynski, J. A., & DeYoe, E. A. (1999). A physiological correlate of the "spotlight" of visual
attention. *Nature Neuroscience*, *2*(4), Article 4. https://doi.org/10.1038/7280

Brouwer, G. J., & Heeger, D. J. (2009). Decoding and reconstructing color from responses in
human visual cortex. *Journal of Neuroscience*, *29*(44), 13992–14003.
https://doi.org/10.1523/JNEUROSCI.3577-09.2009

Brouwer, G. J., & Heeger, D. J. (2011). Cross-orientation suppression in human visual cortex.
Journal of Neurophysiology, *106*(5), 2108–2119.
https://doi.org/10.1152/jn.00540.2011

Buschman, T. J., & Miller, E. K. (2007). Top-Down Versus Bottom-Up Control of Attention in

the Prefrontal and Posterior Parietal Cortices. *Science*, *315*(5820), 1860–1862.

https://doi.org/10.1126/science.1138071

Chen, Z. (2012). Object-based attention: A tutorial review. *Attention, Perception, &*

Psychophysics, *74*(5), 784–802. https://doi.org/10.3758/s13414-012-0322-z

David, S. V., Hayden, B. Y., Mazer, J. A., & Gallant, J. L. (2008). Attention to Stimulus Features

Shifts Spectral Tuning of V4 Neurons during Natural Vision. *Neuron*, *59*(3), 509–521.

https://doi.org/10.1016/j.neuron.2008.07.001

Delorme, A., & Makeig, S. (2004). EEGLAB: An open source toolbox for analysis of single-trial

EEG dynamics including independent component analysis. *Journal of Neuroscience*

Methods, *134*(1), 9–21. https://doi.org/10.1016/j.jneumeth.2003.10.009

Desimone, R., & Duncan, J. (1995). Neural mechanisms of selective visual attention. *Annual*

Review of Neuroscience, *18*, 193–222.

https://doi.org/10.1146/annurev.ne.18.030195.001205

Duncan, J. (1984). Selective attention and the organization of visual information. *Journal of*

Experimental Psychology: General, *113*(4), 501–517. https://doi.org/10.1037/0096-

3445.113.4.501

Duncan-Johnson, C. C., & Donchin, E. (1977). On Quantifying Surprise: The Variation of

Event-Related Potentials With Subjective Probability. *Psychophysiology*, *14*(5), 456–

467. https://doi.org/10.1111/j.1469-8986.1977.tb01312.x

Foster, J. J., Bsales, E. M., & Awh, E. (2020). Covert Spatial Attention Speeds Target

Individuation. *The Journal of Neuroscience*, *40*(13), 2717–2726.

https://doi.org/10.1523/JNEUROSCI.2962-19.2020

Foster, J. J., Thyer, W., Wennberg, J. W., & Awh, E. (2021). Covert Attention Increases the

Gain of Stimulus-Evoked Population Codes. *The Journal of Neuroscience*, *41*(8), 1802–

1815. https://doi.org/10.1523/JNEUROSCI.2186-20.2020

Friman, O., Volosyak, I., & Graser, A. (2007). Multiple Channel Detection of Steady-State

Visual Evoked Potentials for Brain-Computer Interfaces. *IEEE Transactions on*

Biomedical Engineering, *54*(4), 742–750. https://doi.org/10.1109/TBME.2006.889160

Gandhi, S. P., Heeger, D. J., & Boynton, G. M. (1999). Spatial attention affects brain activity in

human primary visual cortex. *Proceedings of the National Academy of Sciences*,

96(6), 3314–3319. https://doi.org/10.1073/pnas.96.6.3314

Goddard, E., Carlson, T. A., & Woolgar, A. (2022). Spatial and Feature-selective Attention

Have Distinct, Interacting Effects on Population-level Tuning. *Journal of Cognitive*

Neuroscience, *34*(2), 290–312. https://doi.org/10.1162/jocn_a_01796

Grootswagers, T., Robinson, A. K., Shatek, S. M., & Carlson, T. A. (2021). The neural dynamics

underlying prioritisation of task-relevant information. *Neurons, Behavior, Data*

Analysis, and Theory, *5*(1). https://doi.org/10.51628/001c.21174

Harrison, W. J., Bays, P. M., & Rideaux, R. (2023). Neural tuning instantiates prior

expectations in the human visual system. *Nature Communications*, *14*(1), Article 1.

https://doi.org/10.1038/s41467-023-41027-w

Herrmann, K., Heeger, D. J., & Carrasco, M. (2012). Feature-based attention enhances

performance by increasing response gain. *Vision Research*, *74*, 10–20.

https://doi.org/10.1016/j.visres.2012.04.016

Ji, J., Porjesz, B., Begleiter, H., & Chorlian, D. (1999). P300: The Similarities and Differences in

the Scalp Distribution of Visual and Auditory Modality. *Brain Topography*, *11*(4), 315–

327. https://doi.org/10.1023/A:1022262721343

King, J.-R., & Wyart, V. (2021). The Human Brain Encodes a Chronicle of Visual Events at Each

Instant of Time Through the Multiplexing of Traveling Waves. *The Journal of*

Neuroscience, *41*(34), 7224–7233. https://doi.org/10.1523/JNEUROSCI.2098-20.2021

Kok, P., Mostert, P., & de Lange, F. P. (2017). Prior expectations induce prestimulus sensory

templates. *Proceedings of the National Academy of Sciences*, *114*(39), 10473–10478.

https://doi.org/10.1073/pnas.1705652114

Ling, S., Liu, T., & Carrasco, M. (2009). How spatial and feature-based attention affect the

gain and tuning of population responses. *Vision Research*, *49*(10), 1194–1204.

https://doi.org/10.1016/j.visres.2008.05.025

Luck, S. J., Chelazzi, L., Hillyard, S. A., & Desimone, R. (1997). Neural Mechanisms of Spatial

Selective Attention in Areas V1, V2, and V4 of Macaque Visual Cortex. *Journal of*

Neurophysiology, *77*(1), 24–42. https://doi.org/10.1152/jn.1997.77.1.24

Moerel, D., Grootswagers, T., Robinson, A. K., Shatek, S. M., Woolgar, A., Carlson, T. A., &

Rich, A. N. (2022). The time-course of feature-based attention effects dissociated

from temporal expectation and target-related processes. *Scientific Reports*, *12*(1),

Article 1. https://doi.org/10.1038/s41598-022-10687-x

Mostert, P., Kok, P., & de Lange, F. P. (2015). Dissociating sensory from decision processes in

human perceptual decision making. *Scientific Reports*, *5*(1), Article 1.

https://doi.org/10.1038/srep18253

Motter, B. C. (1993). Focal attention produces spatially selective processing in visual cortical

areas V1, V2, and V4 in the presence of competing stimuli. *Journal of*

Neurophysiology, *70*(3), 909–919. https://doi.org/10.1152/jn.1993.70.3.909

Myers, N. E., Rohenkohl, G., Wyart, V., Woolrich, M. W., Nobre, A. C., & Stokes, M. G. (2015).

Testing sensory evidence against mnemonic templates. *eLife*, *4*, e09000.

https://doi.org/10.7554/eLife.09000

Norcia, A. M., Appelbaum, L. G., Ales, J. M., Cottereau, B. R., & Rossion, B. (2015). The

steady-state visual evoked potential in vision research: A review. *Journal of Vision*,

15(6), 4. https://doi.org/10.1167/15.6.4

Oostenveld, R., & Praamstra, P. (2001). The five percent electrode system for high-resolution

EEG and ERP measurements. *Clinical Neurophysiology*, 7.

Pelli, D. G. (1997). The VideoToolbox software for visual psychophysics: Transforming

numbers into movies. In *Spatial Vision* (Vol. 10, Issue 4, pp. 437–442).

https://doi.org/10.1163/156856897X00366

Pfefferbaum, A., Ford, J. M., Weller, B. J., & Kopell, B. S. (1985). ERPs to response production

and inhibition. *Electroencephalography and Clinical Neurophysiology*, *60*(5), 423–

434. https://doi.org/10.1016/0013-4694(85)91017-X

Polich, J., & Bondurant, T. (1997). P300 Sequence Effects, Probability, and Interstimulus

Interval. *Physiology & Behavior*, *61*(6), 843–849. https://doi.org/10.1016/S0031-

9384(96)00564-1

Regan, D., & Heron, J. R. (1969). Clinical investigation of lesions of the visual pathway: A new

objective technique. *Journal of Neurology, Neurosurgery, and Psychiatry*, *32*(5), 479–

483.

Rideaux, R., West, R. K., Rangelov, D., & Mattingley, J. B. (2023). Distinct early and late neural

mechanisms regulate feature-specific sensory adaptation in the human visual system.

Proceedings of the National Academy of Sciences, *120*(6), e2216192120.

https://doi.org/10.1073/pnas.2216192120

Smout, C. A., Tang, M. F., Garrido, M. I., & Mattingley, J. B. (2019). Attention promotes the

neural encoding of prediction errors. *PLOS Biology*, *17*(2), e2006812.

https://doi.org/10.1371/journal.pbio.2006812

Srinivasan, R., Bibi, F. A., & Nunez, P. L. (2006). Steady-State Visual Evoked Potentials:

Distributed Local Sources and Wave-Like Dynamics Are Sensitive to Flicker Frequency.

Brain Topography, *18*(3), 167–187. https://doi.org/10.1007/s10548-006-0267-4

Sutton, S., Braren, M., Zubin, J., & John, E. R. (1965). Evoked-Potential Correlates of Stimulus

Uncertainty. *Science*, *150*(3700), 1187–1188.

https://doi.org/10.1126/science.150.3700.1187

Suzuki, M., & Gottlieb, J. (2013). Distinct neural mechanisms of distractor suppression in the

frontal and parietal lobe. *Nature Neuroscience*, *16*(1), Article 1.

https://doi.org/10.1038/nn.3282

Toffanin, P., de Jong, R., Johnson, A., & Martens, S. (2009). Using frequency tagging to

quantify attentional deployment in a visual divided attention task. *International*

Journal of Psychophysiology, *72*(3), 289–298.

https://doi.org/10.1016/j.ijpsycho.2009.01.006

Treue, S., & Maunsell, J. H. R. (1996). Attentional modulation of visual motion processing in

cortical areas MT and MST. *Nature*, *382*(6591), Article 6591.

https://doi.org/10.1038/382539a0

Ungerleider, S. K. A. L. G. (2000). Mechanisms of Visual Attention in the Human Cortex.

Annual Review of Neuroscience, *23*(1), 315–341.

https://doi.org/10.1146/annurev.neuro.23.1.315

Verleger, R. (1988). Event-related potentials and cognition: A critique of the context updating

hypothesis and an alternative interpretation of P3. *Behavioral and Brain Sciences*,

11(3), 343–356. https://doi.org/10.1017/S0140525X00058015

Womelsdorf, T., Anton-Erxleben, K., & Treue, S. (2008). Receptive Field Shift and Shrinkage in

Macaque Middle Temporal Area through Attentional Gain Modulation. *The Journal of*

Neuroscience, *28*(36), 8934–8944. https://doi.org/10.1523/JNEUROSCI.4030-07.2008

Zar, J. H. (1999). *Biostatistical analysis*. Pearson Education India.

Zhang, W., & Luck, S. J. (2008). Discrete fixed-resolution representations in visual working

memory. *Nature*, *453*(7192), Article 7192. https://doi.org/10.1038/nature06860

Zhang, W., & Luck, S. J. (2009). Feature-based attention modulates feedforward visual

processing. *Nature Neuroscience*, *12*(1), Article 1. https://doi.org/10.1038/nn.2223

649