TimberTracer: A Comprehensive Framework for the Evaluation of Carbon Sequestration by Forest Management and Substitution of Harvested Wood Products.

I. Boukhris[1,2]*, A. Collalti[3,4], S. Lahssini[5], D. Dalmonech[3,4], F. Nakhle[6], R. Testolin[3,7], M. V. Chiriacò[2], M. Santini[2], R. Valentini[1,2]

1. Forest Ecology Lab, Department for Innovation in Biological, Agri-Food and Forest Systems (DIBAF), University of Tuscia, 01100 Viterbo, Italy (rik@unitus.it; issam.boukhris@unitus.it)

2. CMCC Foundation - Euro-Mediterranean Center on Climate Change, Italy (monia.santini@cmcc.it; mariavincenza.chiriaco@cmcc.it)

3. Forest Modeling Lab, Institute for Agriculture and Forestry Systems in the Mediterranean, National Research Council of Italy (CNR-ISAFOM), Via Madonna Alta 128, 06128 Perugia, Italy (alessio.collalti@cnr.it; daniela.dalmonech@isafom.cnr.it)

4. National Biodiversity Future Center (NBFC), 90133 Palermo, Italy

5. Department of Forest Development, National School of Forest Engineers, Salé 11000, Morocco (marghadi@gmail.com)

6. Department of Computer Science, Temple University, Setagaya City, Tokyo, 154-004, Japan (farid.nakhle@tuj.temple.edu)

7. Biome Lab, Department of Biological, Geological and Environmental Sciences, Alma Mater Studiorum University of Bologna, 40126 Bologna, Italy (riccardo.testolin@gmail.com)

* Correspondent author. Email: issam.boukhris@unitus.it

Abstract

Background

Harvested wood products (HWPs) have a pivotal role in climate change mitigation, a recognition solidified in many Nationally Determined Contributions (NDCs) under the Paris Agreement. Integrating HWPs' greenhouse gas (GHG) emissions and removals into accounting requirements relies on typical decision-oriented tools known as wood product models (WPMs). The study introduces the 'TimberTracer' (TT) framework, designed to simulate HWP carbon stock, substitution effects, and emissions from wood decay and bioenergy.

Results

Coupled with the 3D-CMCC-FEM forest growth model, *TimberTracer* was applied to Laricio Pine (*Pinus nigra* subsp. *laricio*) in Italy's Bonis watershed, evaluating three forest management practices (clearcut, selective thinning, and shelterwood) and four wood-use scenarios (business as usual, increased recycling rate, extended average lifespan, and a simultaneous increase in both the recycling rate and the average lifespan) over a 140-year planning horizon, to assess the overall carbon balance of HWPs. Furthermore, this study evaluates the consequences of disregarding landfill methane emissions and relying on static substitution factors, assessing their impact on the mitigation potential of various options. This investigation, covering HWPs stock, carbon (C) emissions, and the substitution effect, revealed that selective thinning emerged as the optimal forest management scenario. Additionally, the simultaneous increase in both the recycling rate and the half-life time proved to be the optimal wood-use scenario. Finally, the analysis shows that failing to account for landfill methane emissions and the use of dynamic substitution can significantly overestimate the mitigation potential of various forest management and wood-use options, which underscores the critical importance of a comprehensive accounting in climate mitigation strategies involving HWPs.

Conclusion

Our study highlights the critical role of harvested wood products (HWPs) in climate change mitigation, as endorsed by multiple Nationally Determined Contributions (NDCs) under the Paris Agreement. Utilizing the 'TimberTracer' framework coupled with the 3D-CMCC-FEM forest growth model, we identified selective thinning as the optimal forest management practice. Additionally, enhancing recycling rates and extending product lifespans effectively bolstered the carbon balance. Moreover, this study emphasizes the necessity of accounting for landfill methane emissions and dynamic product substitution, as failing to do so may significantly overestimate the mitigation potential of implemented projects. These findings offer actionable insights to optimize forest management strategies and advance climate change mitigation efforts.

1. Background

Terrestrial ecosystems play a major role in the global carbon cycle owing to their inherent ability to absorb carbon (C) through photosynthesis and release it through respiration. The terrestrial biosphere provided a net sink for ~21% of carbon dioxide emitted by fossil fuel

burning during the 1990-2021 period (1), with the major part occurring in forests (2). This

climate change mitigation role of forests has been widely recognized by the United Nations

Framework Convention on Climate Change (UNFCCC) being part of the periodical national

greenhouse gas (GHG) inventories well as of many NDCs to the Paris Agreement (79% of the

submitted NDCs covers the forest sector under mitigation targets, according to (3).

Sustainably managed forests offer a dual avenue for GHG mitigation through processes that

are mutually exclusive, namely sequestration and substitution (4). Reducing harvest in

managed forests yields a positive impact on the forest C stock in the short to medium term but

would adversely induce a long-term negative impact on the wood-chain value and a

counterproductive effect specifically on carbon sequestration as aging trees exhibit decreased

growth and carbon use efficiency (5). Conversely, the promotion of wood use would lead to

the substitution of energy-intensive materials (e.g., steel or concrete) or fossil fuels, further

compounded with the storage of carbon within harvested wood products (HWPs) (7). Given

the trade-offs among different options (i.e., carbon sequestration, energy substitution, and

material substitution), the most effective mitigation strategy would be the one that optimally

balances and integrates all the mitigation components (8–10).

The acknowledgement of HWPs as integral to climate change mitigation occurs in many NDCs

submitted by Parties under the Paris Agreement (3,11), within which countries voluntarily set

binding GHG accounting obligations and targets to reduce GHG emissions and increase C

removals (12). The Intergovernmental Panel on Climate Change (IPCC) provides several

approaches for estimating the GHG emissions and removals associated with HWPs and

encourages deviating from the conventional "instantaneous oxidation" approach (i.e., carbon

in harvested biomass is considered as released into the atmosphere immediately after the

harvesting) towards more accurate methods (13,14). The need to integrate and improve carbon

reporting for HWPs into the NDCs commitment, as well as for the regular reporting

requirements, along with scientific and political considerations for defining an optimal forest

mitigation strategy, emphasizes the urgent requirement for enhancements and advancements in

tools that predict the development of C dynamics in HWPs. These tools are technically known

as harvested wood product models (WPMs), and are used to estimate the carbon dynamics of

HWPs and assess their effects on the mitigation of climate change (15).

To accurately project storage and emissions in/from HWPs, models should include components that influence C pools and emissions. Among rarely covered aspects by WPMs are recycling, substitution, bucking allocation, and landfill gas emissions (16,17). The practice of cascading wood products extends their lifespan, consequently delaying the release of GHG emissions into the atmosphere. A study conducted by (18) using theoretical simulations to assess the impact of elevating recycling rates on carbon storage within wood products in the European (EU-28) wood sector and revealed compelling results. Specifically, an increase in the recycling rate from 10% to 20.9% between 2017 and 2030 was projected to yield a notable emission saving of nearly 5 $MtCO_2$ (18). The substitution of materials with high energy requirements for production or the replacement of fossil fuels with less energy-demanding wood can permanently and cumulatively avoid emissions, provided that there is no leakage to other cross-sectors or replacement losses (19). For instance, in a case study comparing two functionally equivalent buildings – one constructed with a wooden frame and the other with a reinforced concrete frame – the manufacturing process emitted 45% less carbon in the wooden structure while also requiring less energy (20), which underscores the importance of considering the substitution effect in the WPMs design. A critical point regarding product substitution is that most analyses assume a constant displacement factor value over time, even though this value may decrease due to factors such as evolving manufacturing methods, improvements in energy efficiency, and the redesign of the energy mix (19,21). Recent studies examining the fundamental assumptions underlying the projection of mitigation benefits related to substitution, including the static nature of displacement factors, have found that this substitution effect has been overestimated by 20% to 96% (22). It is thus essential that future model implementations account for these potential variations. From another perspective, the bucking allocation involves the disaggregation of logs into different HWPs based on quality and dimensional criteria. It is crucial to consider this process when assessing the effects of management (e.g., rotation, thinning intensity or interval). For instance, studies that include the bucking allocation process suggest considering longer rotations for optimizing carbon stock in the forest sector (e.g., see (8)), while those excluding it recommend shorter rotations (e.g., see (23)). This is because models not incorporating the bucking allocation module use predefined default values to allocate harvested volume to HWPs. In principle, the higher the productivity, the greater the quantity of products – a scenario typically observed in shorter forest rotations. In contrast, when the bucking allocation is accounted for, the optimization of C stock would favor the production of HWPs with a longer lifespan, generally derived from larger tree stems – a scenario typically observed in longer rotations modeling analyses (24). In landfills, the

limited availability of oxygen creates unique conditions for the decomposition of major wood
polymers. Under anaerobic conditions, microbial activity breaks down a portion of the
dissolved organic carbon (DOC) into methane (CH4) and carbon dioxide (CO2). While many
models that include landfills primarily estimate C stock, they often overlook the varying global
warming potential of different landfill gases. As a result, solely assessing changes in carbon
stock within landfills is insufficient for accurately estimating total greenhouse gas (GHG)
emissions.

In this paper, we have pioneered the development of an open-source Python-based model,
named *TimberTracer (TT)*, to comprehensively account for the various components that
directly or indirectly influence C pools and emissions – some of which are typically overlooked
by existing forest/vegetation models – and to provide insights into the temporal dynamics of
both carbon storage and emissions associated with HWPs. To assess the climate change
mitigation potential of the entire forest sector, the model can be seamlessly coupled with any
forest growth model, whether individual-tree or stand-based level, such, as e.g., GO+ (25) or
3D-CMCC-FEM (26). The main objective of this study is to examine the impact of forest
management and wood utilization on the mitigation potential of HWPs. Focusing on the *Pinus*
nigra subsp. *laricio* (Poiret) forest located in the experimental Bonis watershed in southern
Italy (27), we employ a carbon modeling framework by combining the 3D-CMCC-FEM with
TimberTracer. This integrated framework is used to simulate the evolution over 140-years of
the HWP stock, carbon emissions, and the substitution effect under three forest management
schemes and four wood-use scenarios, as elaborated in subsequent sections. Furthermore, to
determine the influence of dynamic substitution and methane release from landfills on the
mitigation potential of various forest management and wood-use scenarios, we use two
different model implementations: one that includes methane emissions from landfills and
dynamic product substitution, and another that models solely the carbon stock changes in
landfills while considering static product substitution.

2. Methods

2.1. Wood products modeling, an overview
WPMs are implemented diversely based on their scopes and objectives. An integral model
should include -in principle- these six following components: (i) *bucking allocation,* which
involves the disaggregation of stems into different logs destinated to the production of

differentiated products according to a set of dimensional and quality criteria typically
established by wood industry professionals. Considering this component as an integral part of
the TT model, rather than relying on a priori allocation factors, is crucial for minimizing errors
resulting from simplification; (ii) *industrial processes,* that involve the transformation of raw
wood into finished or semi-finished products, as well as the recycling or disposal of products
when reaching the end of their use. Those processes are characterized by a set of allocation
parameters either derived from expert knowledge, local surveys, or previous studies; (iii)
carbon pools, which refer to the reservoirs of carbon stored in the diverse wood products
currently in use or at disposal sites. HWPs are characterized by an average time in use,
primarily linked to their intended purpose. For instance, construction wood is typically long-
lived compared to pulpwood, given its use in applications that demand high durability and
longevity. In contrast, pulpwood is primarily utilized for paper and pulp production, and its
intended use does not require the same level of longevity; (iv) *product removal,* that refers to
the point in time when products are retired from use. To estimate the product removal rate (also
known as 'decay rate'), C-retention curves are used. They are based on the cumulative function
of a chosen statistical distribution (e.g., Weibull, uniform, linear, and normal distributions)
defined by one or more of the following parameters, e.g., the time when 50% of the initial C-
stock is left (also known as half-life time), the time when 5% of the initial C-stock is left, the
average life, and the maximum decay rate; (v) *recycling,* that involves the transformation of
HWPs after reaching the end of their use into new products. This theoretically induces a
reduction in the decay rate, as an additional amount of products is reinjected after each
projection compared to the scenario when recycling is not considered; and (vi) *substitution,*
which refers to the displacement effect resulting from the use of wood to substitute functionally
equivalent energy-intensive materials or fossil fuels. The major components and processes
described above are graphically illustrated in **Figure 1**.
203

Figure 1: Lifecycle of HWPs - Illustration depicting key stages from production through utilization to end-of-life and natural decay.

2.2. Model description

TimberTracer (TT), a WPM based on the material flow method, was implemented using Python as its programming language. The model is specifically tailored for a comprehensive analysis of wood products, and it encapsulates a robust framework for carbon storage analysis, enabling users to meticulously evaluate the quantity of carbon stored within diverse wood products. Furthermore, TT incorporates temporal insights, enabling stakeholders to scrutinize the evolving patterns of carbon storage and emissions over time. Remarkably, to assess the climate change mitigation potential for the entire forest sector, TT can be seamlessly coupled with theoretically any forest growth model, whether individual-tree or stand-based level, such, as GO+ (25) or 3D-CMCC-FEM (26).

By incorporating all the previously described components (see previous **section 2.1**), TT comprehensively accounts for and simulates the temporal dynamics of GHG emissions and removal across all carbon pools outside the forest, including changes in HWPs and disposal sites. Furthermore, the model considers the substitution effect and captures the temporal dynamics of material and energy substitutions. Additionally, TT offers the flexibility of utilizing both tree- and stand-level inputs, facilitated by its integration of a stand structure generator, enabling the transition from stand state descriptors to tree state descriptors. The TT model offers the ability to simulate the entire carbon accounting process using the function

'run_model()'. Additionally, it is designed to be modular, allowing running various

simulations independently, at specific stages of the C accounting process, as described in

Figure 2. Hereafter, we explicitly introduce each module, outlining its role and the functions

it encompasses.

Figure 2: Flowchart of the TT model. In green the inputs, in red the outputs, in black the
modules, and in blue the functions within the modules. The number of iterations is equal to the
number of management interventions.

235
236
237
238

2.3. Model inputs and requirements

The TT model requires a set of input data for its initialization, including: i- stand structural data

(DBH, height, stand density, basal area, bark thickness, sapwood, and heartwood areas); ii-

forest management data (planning horizon, rotation period, rotation number, thinning age,

thinning intensity, thinning nature); iii- industrial process data (product, priority, number, log

length, log diameter, quality criteria, process efficiency); iv- wood use data (lifespan, recycling

rate, reallocation scheme, displacement factors). Furthermore, TT necessitates the specification

of a well-defined set of parameters mainly required by the dendrometer and the bucking

allocation module (for further information on the model parameters and data inputs, please

refer to the table in **Supplementary 3**).

2.4. Model outputs

The '`run_model()`' function serves as an integrated coordinator, orchestrating the seamless

execution of independently developed modules introduced earlier to generate a comprehensive

output. The model can be run for a planning horizon (PH) that may encompass multiple

rotations (R). The outputs provided include the simulations of carbon stock in HWPs, the

annual and cumulative emissions, the annual and cumulative material and energy substitution,

and the yearly recycling (all expressed in tC ha^{-1}).

2.5. Model structure

The TT model is designed to be modular. In this section, we will introduce each module

individually, explaining the theory and objectives of each (for further information refer to

Supplementary 1).

2.5.1. The structure generator and thinning performing module

TT is designed for compatibility with both tree- and stand-level data, providing, to some

degree, flexibility in data input. This capability is realized through the incorporation of a

structure generator module that implements the statistical distribution (e.g., Weibull

distribution) of the diameter at breast height (DBH) within the stand level. It also assigns trees

to different bio-sociological classes of status (i.e., dominant, co-dominant, intermediate, and

overshadow trees) based on their total tree height, as implemented in the '`dendrometer()`'

function. TT further considers thinning operations, characterized in the model by three

descriptors: type, intensity, and timing, implemented in the `perform_thinning()'`
function, which renders dendrometry information about each individual thinned tree.

2.5.1.1. The structure generator
The transition from stand state descriptors to tree state descriptors would be feasible if the stand
structure is well understood. The latter is typically likened to a statistical distribution. There
are numerous mathematical formulations for statistical distributions in forestry, with one of the
most employed being the Weibull distribution (29). The probability density function of a
Weibull random variable denoted as $X \sim Weibull(sh, sc, loc)$ is:

$$f(x, sh, sc, loc) = \frac{sh}{sc} \times \left(\frac{x-loc}{sc}\right)^{sh-1} \times e^{-\left(\frac{x-loc}{sc}\right)^{sh}} \hspace{2cm} \text{(Equation1)}$$

Where f is the probability density function, x is the random variable, sh represents the shape,
sc denotes the scale, and loc indicates the location.

If the location is not provided, but the shape and scale are (2-parameter Weibull distribution),
then the location will be predicted using the following equation:

$$E(x) = loc + sc \times \Gamma\left(1 + \frac{1}{sh}\right) \hspace{2cm} \text{(Equation2)}$$

$$loc = E(x) - sc \times \Gamma\left(1 + \frac{1}{sh}\right) \hspace{2cm} \text{(Equation3)}$$

Where $E(x)$ is the mathematical expectancy of x and Γ is the gamma function.

After fitting the parameters of the Weibull distribution supposed to represent the structure of
the forest stand at different stages of development, the next step is to compute the number of
trees by each diameter class. For this specific purpose, the cumulative distribution function of
the Weibull function is applied to the concerned diameter class following the equation:

$$N(class) = \left[e^{-\left(\frac{lower\ bound-loc}{sc}\right)^{sh}} - e^{-\left(\frac{upper\ bound-loc}{sc}\right)^{sh}}\right] \times N \hspace{1cm} \text{(Equation4)}$$

Where N represents stand density, and the lower bound and upper bound define the DBH class
interval.

2.5.1.2. The thinning process

A thinning operation involves removing tree stems to benefit a tree or a group of trees deemed

essential to ensure optimal growth conditions (30). It focuses on enhancing wood quality and

stand stability. The thinning intervention can be characterized by three elements: (i) the type of

cut (from the above, from the bottom, or neutral), which denotes the distribution of removed

stems among various diameter categories of standing trees within the stand; (ii) the thinning

intensity which expresses the magnitude of the extraction conducted within the stand. It can be

quantified by both the number of stems harvested and the implementation rate relative to the

before-thinning stand population; (iii) the period, commonly referred to as rotation, is the time

interval between two successive thinning events within the stand. It varies depending on the

tree species, age, and site conditions (31).

Bio-sociological tree status plays an important role in some thinning concepts, for example, for

the selection of thinning trees in thinning from above and below (32). A simplified

classification groups trees into four categories: **i-** dominant trees; **ii-** co-dominant trees; **iii-**

intermediate trees; and **iv-** overshadow trees. This classification consists of the definition of

the position of each tree in terms of its height by reference to the other trees of the stand. As

part of the process, the dominant height of the plot (**$h_{95\%}$**) as well as the height to the base of

the crown (**hc**) are calculated. The classification of the trees into a scale is performed following

the rules presented in the **Table 1**.

Table 1: Bio-sociological status criteria based on the tree height.

Criteria	Bio-sociological status
$hi \geq h_{95\%}$	Dominant tree (1)
$\dfrac{h_{95\%} + hc}{2} \leq hi < h_{95\%}$	Co-dominant tree (2)
$hc \leq hi < \dfrac{h_{95\%} + hc}{2}$	Intermediate tree (3)
$hi < hc$	Overshadow tree (4)

325 The thinning operation follows the approach implemented by (33). For thinning from below

326 and thinning from above, trees belonging to a specific bio-sociological class are prioritized for

327 each thinning type. In the case of neutral thinning, trees are harvested without consideration

328 for their bio-sociological status. Further details are provided in the following.

Thinning from below (4+3) => 2

The process consists of removing trees belonging to the dominated bio-sociological sub-groups. The process of removal is parallel in 4+3 (Overshadow and Intermediate). If the removal amount is not reached by 4+3, the process continues sequentially in sub-group 2 until reaching the required number of trees satisfying the initial condition.

Thinning from above (1+2) => 3

The process consists of removing trees belonging to the dominating bio-sociological sub-groups. The process of removal is parallel in 1+2 (Dominant and Co-dominant). If the removal amount is not reached by 1+2, the process continues sequentially in sub-group 3 until reaching the required number of trees satisfying the initial condition.

Neutral thinning (1+2+3+4)

The process consists of removing trees regardless of the bio-sociological sub-group to which they belong. The process is parallel in 1+2+3+4 and continues until satisfying the required removal amount.

2.5.2. *The bucking allocation module*

TT allocates logs from thinned trees to HWPs, considering determinant factors such as stem log diameter and quality. The qualitative grading of logs involves several criteria, with the proportion of knotted wood and sapwood-to-heartwood ratio being among the most commonly used in the literature (34–36). The bucking allocation is practically implemented within the model through two sequential steps. The first step involves dressing the stem profile of each individual tree using the '`taper_equation()`' function which renders the diameter over bark (dob) at any point along the stem. Simultaneously, the knotted wood profile is dressed using the '`knotted_wood_profile()`' function while the sapwood and heartwood profiles are established with the '`sapwood_profile()`' function. The second step consists of combining the tree stem profile (including taper, knotted wood, sapwood, and heartwood) with the bucking allocation criteria defined by wood industry professionals to disaggregate trees into different logs. This entire process is implemented in the '`bucking_allocation()`' function (please refer to **Supplementary 2** for more information on the bucking allocation criteria).

2.5.2.1. Stem profile generator

To achieve a precise stem profile dressing, the TT uses a comprehensive set of equations, which

will be thoroughly described in this section (see **Figure 3** for a graphical representation of the

stem profile).

The taper profile refers to the degree to which a tree's stem diameter decreases as a function of

height above ground. Taper is often represented by mathematical functions fitted to empirical

data, called taper equations. One such function, attributed to (37) and used by default in the

model is:

$$y(z) = b_1 z + b_2 z + b_3(z - a_1)^2 I_1 + b_4(z - a_2)^2 I_2 \qquad \text{(Equation 5)}$$

where $y = (\frac{dx}{dbh})^2$; dx = is the upper stem diameter over bark (dob) at a given height h of the

tree, $z = 1 - \frac{h}{ht}$ = the complement of the relative height with ht being the tree total height; a_1

and a_2 = join points to be estimated from the data, $I_k = 1$ if $z > a_i$ and 0 otherwise, $k = 1,2$, b_p's

= regression coefficients with, $p = 1, 2, 3, 4$.

The crown base height (h_c) refers to the level of insertion of the last branch of the crown within

the stem, it is generally predicted from the total height using an allometric equation. One such

equation is the power function expressed as follows:

$$h_c = a h_t{}^c \qquad \text{(Equation 6)}$$

where *a* and *b* correspond respectively to the amplitude and the exponent of the relation.

The DBH of a tree could be also predicted from its total height. One such function is the power

function expressed as follows:

$$DBH = alpha \times h_t{}^{beta} \qquad \text{(Equation 7)}$$

where *alpha* and *beta* correspond respectively to the amplitude and the exponent of the relation.

In tree analysis, a crucial step involves shaping the crown base profile to differentiate knotted

from intact wood. To establish this profile, a combination of the three equations (5-7) is utilized.

In practice, the approach entails reconstructing the historical crown base height limits and

considering that the area from the curve towards the bark represents the knotted wood, while

the area from the curve towards the pith represents the intact wood.

$z_c = 1 - a(h_c{}^{c-1})$ (Equation 8)

$d_c = \sqrt{y(z_c)} \times alpha \times [(\frac{h_c}{a})^{\frac{1}{c}}]^{beta}$ (Equation 9)

where z_c represents the complement to the relative height at the level of the crown base and d_c

refers the diameter of the intact wood.

The sapwood profile is determined based on the simplified assumption that the sapwood width

and bark thickness remain constant within the tree level (38). The width of knotted wood, which

naturally varies within the tree level, is calculated as the difference between the diameter at a

specific height obtained from the taper profile and the sum of the sapwood width and bark

thickness.

406
407   Figure 3: Graphical representation of stem longitudinal profile

408
2.5.2.2. Stem disaggregation

Stems are disaggregated into different logs based on specific criteria, typically established by

wood industry professionals. These criteria, tailored to each species, include both dimensions

and quality considerations, and they are organized hierarchically. To elaborate, the model

initially checks if the stem aligns with the criteria for producing a designated log intended for

a specific product. If this is not the case or if the maximum desired number of this specific log

has been reached, the model then advances to the next HWP based on a hierarchy defined by

the user. In TT, log dimensions are characterized by the length and small end diameter of the

log, while log quality is assessed through ratios of knotted wood ($Ø_{KW}$) to heartwood ($Ø_{HW}$)

and knotted wood to small end diameter ($Ø_{SE}$). The model checks these criteria (e.g., $Ø_{SE} \geq 25$

cm, $(\emptyset_{KW} / \emptyset_{HW})^2 \leq 13\%$, and $\emptyset_{KW} / \emptyset_{SE} \leq 30\%$) by implementing a bisection algorithm that

automatically performs the search for the corresponding height validating the given criteria.

2.5.3. The processor module

Logs are processed to match their intended products, employing the standard industry method

for each type of product. The efficiency rate of this industrial transformation, a theoretical

measure, depends on how the processing is done, and this varies based on the targeted product.

In *TT*, the production of HWPs is calculated using the efficiency rate which is product-specific.

Subsequently, any process losses (i.e., 1 – efficiency) are redistributed among other products

according to a scheme defined by the user. This process is implemented in the 'processor()'

function.

2.5.4. The stock and flow module

TT simulates the evolution of carbon in HWPs and disposal sites including both mill and

landfill sites throughout the planning horizon (PH) using the

'total_stock_calculator()' function. After each annual projection, a portion of the

carbon in HWPs undergoes decay based on product-specific decay function (refer to

'compute_D()' in the model). Subsequently, a fraction of the decay is recycled and reinjected

into the HWPs carbon pool (refer to 'compute_R()' in the TT model), another portion is

directed to firewood, while the remaining part is sent to landfills. Furthermore, TT simulates

the evolution of the total emissions resulting from the firewood combustion and the decay of

carbon pool in disposal sites, accounted for as an instantaneous oxidation, using the

'total_emission_calculator()' function.

In TT, the product removal rate (i.e., decay rate) is determined using the cumulative distribution

function (CDF) of a normal distribution, which is defined by its mean and standard deviation.

The mean represents the average lifespan of a product, while the standard deviation reflects the

change in the dynamic decay, typically expressed as a fraction of the average lifespan (e.g., a

fraction of 1/3 as used in (18)). In the following, the CDF formulation is presented.

$CDF(x; \; lifespan, lifespan \times \text{fraction}) = \frac{1}{2} \left[1 + \text{erf} \left(\frac{x - lifespan}{lifespan \times fraction \times \sqrt{2}} \right) \right]$ (Equation 10)

$\text{erf}(x) = \frac{2}{\sqrt{\pi}} \int_0^x e^{-t^2} dt$ (Equation 11)

where CDF is the cumulative distribution function and erf is the error function.

Specifically, emissions from landfills are estimated by TT using two different methods. The

first approach assumes that wood decomposition in landfills occurs under aerobic conditions,

with CO_2 as the only emitted gas (as in Equations 10 and 11). Although this approach may

underestimate the warming potential of emissions, it allows for comparison with alternative

methods. The second approach is a theoretical first-order decay (FOD) model introduced in the

IPCC guidelines (39), which provides yearly estimates of CH_4 and CO_2 emissions. The

following equations present the generation of CH_4 and CO_2 in year t from landfilled wood in a

specific year x.

$Q_{t,x,CH4} = k \times R_x \times L_0 \times e^{-k(t-x)} \times GWP \times C1$;   (Equation 12)

$Q_{t,x,CO2} = k \times R_x \times L_0 \times e^{-k(t-x)} \times (1-f)/f \times C2$ (Equation 13)

where $Q_{t,x,CH4}$ and $Q_{t,x,CO2}$ are, respectively, the amounts of methane and carbon dioxide

generated in year t (in eq tC) by landfilled wood R_x (t); $k = \frac{\log 2}{t0.5}$ represents the methane

generation rate constant (yr^{-1}); t0.5 is the half-life period of the degradation process; L_0 is the

methane generation potential (tCH$_4$ per tonne of landfilled wood); x is the year of wood input,

and t is the current year; GWP = 28 is the global warming potential of CH_4 (in eq CO_2), C1 =

12/44 and C2 = 12/16 are the constants used to convert tCO_2 to tC and tCH_4 to tC, respectively;

and f represents the fraction of C released as CH_4.

2.5.5. The substitution module

TT simulates the climate change mitigation effect in terms of avoided emissions resulting from

the substitution of fossil fuels by bioenergy and energy-intensive materials by wood products.

The carbon mitigation potential is closely linked to the specific solution being substituted and

is calculated using the displacement factor (DF in tCO_2-eq m^{-3}), a measure of the amount of

GHG emissions avoided when wood is used instead of the current solution (40). The

computation of the substitution is perfomed separately for material and energy substituiton

using the 'material_sub()' and 'energy_sub()' functions, respectively. The

substitution is estimated using the following equation:

$substitution = wood\ volume \times DF \times k$ (Equation 14)

where k $= \frac{12}{44}$ is the constant used to convert tCO_2 to tC

3. Case study

3.1. Study area

The Bonis experimental watershed located in the mountain area of Sila Greca (39°28′49″ N, 16°32′07″ E; from 975 to 1330 m a.s.l.) in the Calabria region, southern Italy was chosen as the study area in this work (27,41). Almost 93% of its total area is covered by forests, dominated by ~60 years old Laricio pine stands. The stands were planted in 1958 with an average density of 2425 sapling ha^{-1} (42) and underwent a thinning treatment in 1993 with basal area (BA) removal of 25 % (43). The forest was equipped with 14 circular survey plots, each with a radius of 12 meters, for monitoring since 1993, and they were surveyed until late 2016.

Figure 4: Map of the geographical situation of the Bonis watershed (right sub-figure) inside the Italian territory (left sub-figure).

3.2. Scenarios building

For the management scenarios, we tested three options reflecting different goals. All the options were simulated to take place after 2016, which is the last year of plot surveying. The first option simulates light thinning intensity, corresponding to a 28% reduction of Basal Area (BA) at an interval of 15 years, aiming to reproduce silvicultural interventions favoring natural forest dynamics. An additional production-oriented option, known as clearcut, simulates a complete harvest followed by replanting 80 years after the establishment of the plantation. A third option, representing a more sustainable alternative to clearcutting, simulates a shelterwood. This involves two light thinnings (20% reduction of BA) with a 10-year interval, followed by seed-

favoring cut after 80 years from the original planting (80% reduction in BA) and removal cut

10 years later.

For the wood-use scenarios, four different options were developed. The 'Baseline scenario'

('Business as Usual', BAU) kept the recycling rate and products lifespan values constant. In

the 'Longevity scenario', the lifetime of products was increased by 10 %. In the 'Reuse

scenario', the recycling rate of products was increased by 10%. In the 'Sustainability scenario',

both the lifetime of products and the recycling rate were increased by 10% (See

Supplementary 4 for further details).

Table 2: Forest management and wood use scenarios

Group	Name	Features
Forest management	Selective thinning	28% reduction of BA at an interval of 15 years
	Clearcut	Complete harvest followed by replanting at 80 years.
	Shelterwood	Two light thinning (20% reduction of BA) with 10-year interval, followed by seed-favoring after 80 years (80% of BA) and removal cut 10 years later
Wood use	BAU	Constant recycling rate and product lifespan
	Longevity	10% increase in product lifespan
	Reuse	10% increase in recycling rate
	Sustainability	10% increase in both product lifespan and recycling rate

519
520

3.3. Modeling framework and the required data

The *TT*, a WPM that tracks carbon in HWPs which was extensively introduced in this paper,

was coupled with 3D-CMCC-FEM ('*Three Dimensional – Coupled Model Carbon Cycle –*

Forest Ecosystem Module' v.5.6 BGC (26,27,44–47), a stand-level, biogeochemical,

biophysical, process-based model that annually provides data on the forest state (e.g., density,

DBH, BA, and total height). The integration of the two models was considered as the modeling

framework for achieving the objectives of this study.

The 3D-CMCC-FEM model requires a set of input data for its initialization which includes: (i)

model species parameters set which was derived from a recent work that validated the model

for Laricio pine stand in the Bonis watershed (41); (ii) daily time series of meteorological fields

(e.g. incoming shortwave radiation, maximum and minimum temperature, relative humidity or

vapor pressure deficit, precipitation). For the period from 1958 until 1976 climate data was

derived using the mountain microclimate simulation model MT-CLIM (48) forced by

temperature and precipitation series measured by the nearby Cecita meteorological station

(39°23′51″ N, 16°33′24″ E; 1180 m a.s.l.), while for the period from 1976 to 2005, gridded

climate time series were used. The latter derived from bias-corrected outputs of the regional

climate model COSMO-CLM (49) at around ~8 km horizontal resolution (50,51), and driven

by the general circulation model (GCM) CMCC-CM (52) under historical GHG forcing (41).

Additionally, measured values of global annual atmospheric CO_2 concentration were derived

from (53) and used for the period from 1958 to 2005. A random sampling of both climate and

CO_2 data within the period between 1990 and 2005 was performed as representative of an

additional synthetic period of 90 years assuming unchanging climate and atmospheric CO_2

conditions, to simulate in total 140 years; (iii) stand initialization data for the year 1958 which

included stand density: 2425 saplings ha^{-1}, DBH: 1 cm, height: 1.3 m, age: 4 years, elevation:

1131 m a.s.l., soil texture (clay: 20 %; silt: 26 %, sand: 54 %) and depth: 100 cm (42,54,55).

(41) provides an extensive description of model validation (before and after thinning) at the

Bonis site for both carbon fluxes and stocks such as DBH, stand density and gross primary

productivity (GPP).

In addition, *TT* also requires a set of inputs and parameters necessary for its initialization: i-

the bucking allocation criteria, developed to segregate solid-wood products based on quality

requirements for specific end uses across various wood products, are standardized and can be

applied irrespective of log source and sawmill producer (56). Potential wood products from

Laricio pine stems were inventoried by consulting five sawmill industry experts, and the

amalgamation of all possible products was retained for this study. Furthermore, the bucking

criteria used in this study are those commonly found in the literature (57) (Please refer to Table

1 in **Supplementary 2**); ii- the transformation efficiency of each log category, a geometric

yield as well as the loss reallocation were defined with the assistance of sawmill industry

professionals (Please refer to Tables 2 and 4 in **Supplementary 2**),; iii- for the recycling rate

we suggest that the recycling rate of waste wood products was constant at 10% during the

planning horizon while lifespan of each product was reviewed from published studies (58–64);

iv- displacement factors for the substitution were derived from the literature (40,65) (Please

refer to Table 5 in **Supplementary 2**); v- TT model dendrometry parameters, including stand

structure, crown base height equation, and diameter-to-height parameters, were fitted to the forest data collected from the experimental plots of the Bonis watershed forest, while the taper model and the species density were derived from the literature (66,67).

Additionally to the first implementation which assumes static displacement factor values overtime, we dynamically calculated these factors for each product category in this study, following the approach outlined in (22). Specifically, the substitution factor value was assumed to proportionally follow the dynamic of gross anthropogenic CO_2 emissions. In line with the Paris Agreement's ambition of reaching net-zero emissions around mid-century, (68) estimated the evolution of these gross anthropogenic CO_2 emissions. We used this projection to dynamically update the substitution factors throughout the entire 140-year planning horizon.

Figure 5: carbon modeling framework coupling a forest process-based model (3D-CMCC-FEM) and TT a harvested-wood product model. DBH is the stand mean diameter at breast height, N is the stand density, BA is the stand basal area, H is the stand mean tree height, SA is the sapwood area of the mean tree, HA is the heartwood area of the mean tree, and BT is the bark thickness of the mean tree.

4. Results

4.1. Introduction

In this study, we assess the carbon dynamics within the harvested wood product (HWP) pool, including carbon stock changes, emissions, and the effects of material and fossil fuel substitution. We employ the production approach, which tracks the transfer of carbon from forests to HWPs and covers the wood lifecycle from forest harvest to end-of-life. Our analysis focuses exclusively on the C dynamics within the HWP pool, without evaluating changes in

forest carbon stocks. This approach is versatile, applicable to various system boundaries,
including specific projects and harvest activities of small sizes, including our study scope.
In this simulation, the overall C-balance, calculated as the difference between carbon stored in
HWPs, the avoided emissions as effect of the substitution of material and fossil fuel, and carbon
emissions from HWPs end-life, was estimated for three different forest management schemes
and four wood use scenarios providing insights into the overall carbon balance at each point in
time throughout the projection period. These estimations were derived from the modeling
exercise, relying on both silvicultural itinerary and product utilization over the use and end-use
periods. To analyze the effects of various wood use scenarios on the overall C-balance over
time, we compared each scenario with the business-as-usual (BAU) scenario as benchmark.
Furthermore, to assess the impact of different forest management scenarios on the overall C-
balance over time, we conducted individual comparisons while maintaining the same wood-
use scenario each time. Additionally, the net C-balance, calculated as the difference between
carbon stored in HWPs and C-emissions at the end of their life-cycle, was estimated across the
three forest management schemes and four wood-use options. This concept is significant
because it provides a baseline against which the substitution effect can be measured and can
orient comparative studies where substitution is irrelevant. When estimated dynamically, it
offers insights into the duration of a positive C-balance, which is crucial for evaluating the
effectiveness of HWPs in mitigating climate change. A long-lasting positive C-balance
indicates that carbon is sequestered from the atmosphere and stored in HWPs for extended
periods, thereby delaying or reducing the impact of C-emissions on global warming. Finally,
to assess the impact of considering CH_4 release from landfill sites and the dynamic updating of
substitution factors, we evaluated the effects of incorporating these elements. In this work we
use positive values to represent C-removals while negative ones are C-emissions.
615

Figure 6: Clearcut management among different wood-use scenarios is demonstrated to showcase variations in Harvested Wood Products (HWPs) C-stock, material and energy substitutions, C-emissions, and the **overall C-balance** (tC ha^{-1}). Blue points represent the equalization between HWPs and emissions, while black points indicate neutrality of the overall C-balance. The red dashed line corresponds to the overall C-balance neutrality. Negative values of the overall C-balance indicate positive emissions, while positive values indicate positive C-storage. The red points refer to the value of each variable at the term of the simulation.

625
Figure 7: **Selective thinning management** among different wood-use scenarios is demonstrated
to showcase variations in Harvested Wood Products (HWPs) C-stock, material and energy
substitutions, C-emissions, and the **overall C-balance** (tC ha^{-1}). Blue points represent the
equalization between HWPs and emissions. The red dashed line corresponds to overall C-
balance neutrality. Negative values of the overall C-balance indicate positive emissions, while
positive values indicate positive C-storage. The red points refer to the value of each variable at
the term of the simulation.

633
634

Figure 8: **Shelterwood management** among different wood-use scenarios is demonstrated to showcase variations in Harvested Wood Products (HWPs) C-stock, material and energy substitutions, C-emissions, and the **overall C-balance** (tC ha^{-1}). Blue points represent the equalization between HWPs and emissions, while black points indicate the neutrality of the overall C-balance. The red dashed line corresponds to the overall C-balance neutrality. Negative values of the overall C-balance indicate positive emissions, while positive values indicate positive C-storage. The red points refer to the value of each variable at the term of the simulation.

4.2. Overall carbon balance

The application of wood-use scenarios had distinct effects across different forest management scenarios, yet recurrent patterns can be identified. Among the various forest management scenarios, the sustainability scenario consistently exhibited the lowest C-emissions. To elaborate, over the planning horizon, C-emissions decreased by 69%, 267%, and 40%, respectively, for clearcut, selective thinning, and shelterwood managements compared to the BAU scenario (i.e., –6.1, 1.34, –12.91 tC ha^{-1}). Comparable effects were observed with the

longevity scenario, resulting in a reduction of C-emissions by 60%, 254%, and 35%,
respectively, for clearcut, selective thinning, and shelterwood managements compared to BAU.
The reuse scenario induced the smallest decrease in C-emissions, at 11%, 44%, and 4.6%,
respectively, for clearcut, selective thinning, and shelterwood managements compared to BAU
(see **Tables 3 and 4**).

In the context of forest management, selective thinning exhibited pronounced superiority over
alternative management approaches in all four wood-use scenarios. Under this management
strategy, C-emissions were intensively reduced compared to the BAU scenario for clearcut and
shelterwood management, respectively. Meanwhile, clearcut and shelterwood management
demonstrated nearly equivalent effects across the three wood-use scenarios (see **Tables 3 and**
4).

The overall C-balance exhibits diverse patterns based on the applied forest management.
Specifically, the results consistently demonstrate a positive balance for the selective thinning
management approach throughout the entire planning horizon. However, the clearcut
management reached equilibrium at either year 64 or 65 under BAU and the reuse scenarios,
or under the longevity and sustainability scenarios. The balance remained negative from that
point until a significant harvesting event at year 84. Subsequently, a new equilibrium was
achieved at either year 134 or 138 under BAU and reuse scenarios, or under longevity and
sustainability scenarios. The overall balance remained negative thereafter. In the case of
shelterwood management, the balance consistently remained positive until a first equilibrium
was reached at either year 129, 130, or 133 under BAU, or under the reuse scenario, or under
the longevity and sustainability scenarios. Afterward, the balance remained negative (See
Figures 5-7).

Table 3: The overall carbon balance, encompassing removals, emissions, and substitution
effects from harvested wood products (HWPs) due to wood use and management scenarios, is
expressed in tC ha^{-1}. Negative values indicate net C-emissions, whereas positive values
indicate net C-removals.

Management scenario	Wood use scenario			
	BAU	Reuse	Longevity	Sustainability
Clearcut	–6.1	–5.43	–2.46	–1.88
Selective thinning	1.34	1.93	4.74	4.92

Shelterwood	−12.91	−12.32	−8.39	−7.76

Table 4: Relative difference in the overall C-balance (%) between the baseline scenario (BAU) and the alternative wood-use scenarios.

Management scenario	Wood use scenario		
	Reuse	Longevity	Sustainability
Clearcut	11	60	69
Selective thinning	44	254	267
Shelterwood	4.6	35	40

4.3. Material and energy substitution

Regarding material substitution, we identified a distinct pattern marked by successive phases of a sharp pulse of increase coinciding with thinning or harvesting operations, followed by a positive pseudo plateau. Among the forest management scenarios, the reuse scenario consistently showed the highest material substitution effect averaging 0.62% more than the BAU scenario (i.e., 25.59, 27.12, and 30.46 $tC\ ha^{-1}$; respectively for clearcut, selective thinning and shelterwood). In contrast, the longevity scenario consistently exhibited the lowest potential (averaging 0.53% less than the BAU) while the sustainability scenario demonstrated a comparable effect to the BAU scenario.

For energy substitution, we observed a pattern characterized by successive phases of a moderately intense pulse of increase coinciding with thinning or harvesting operations, followed by a positive slope. Among the management scenarios, the BAU scenario (i.e., 22.10, 22.27, and 28.51 $tC\ ha^{-1}$; respectively for clearcut, selective thinning and shelterwood) consistently exhibited the highest energy substitution effect. In contrast, the sustainability consistently showed the lowest energy substitution effect (averaging 5.25% less than BAU), followed by the longevity scenario (averaging 4.41% less than BAU) and finally the reuse scenario (averaging 0.57% less than BAU).

Table 5: Cumulative material and energy substitutions due to the use of particular scenario (in $tC\ ha^{-1}$) (Material substitution | Energy substitution).

Management scenario	Wood use scenario			
	BAU	Reuse	Longevity	Sustainability
Clearcut	25.59 | 22.10	25.80 | 21.98	25.39 | 21.01	25.59 | 20.91

Selective thinning	27.12 | 22.27	27.22 | 22.12	27.03 | 21.36	26.78 | 21.05
Shelterwood	30.46 | 28.51	30.66 | 28.37	30.31 | 27.30	30.47 | 27.11

4.4. Net carbon balance

Regarding the carbon emissions from firewood and disposal sites, we observed a pattern characterized by a sustained positive slope interrupted by a sharp pulse of increase coinciding with thinning or harvesting operations. Among the management scenarios, the BAU scenario (i.e., –63.90, –67.77, and –85.94 tC ha^{-1}; respectively for clearcut, selective thinning and shelterwood) consistently exhibited the highest C-emissions. In contrast, the sustainability scenario consistently showed the lowest level of emissions (averaging 4.17% less than BAU), followed by the longevity scenario (at 3.64% less than BAU), and finally the reuse scenario (at 0.48% less than BAU).

Regarding the carbon stock of HWPs, it assumes different shapes depending on the type of applied forest management. However, a commonly observed pattern is characterized by a sustained negative slope interrupted by a sharp pulse of increase coinciding with thinning or harvesting operations. Among the management scenarios, the BAU scenario consistently exhibited the lowest HWPs C-stock (i.e., 10.11, 19.72, and 14.06 tC ha^{-1} for clearcut, selective thinning, and shelterwood, respectively). In contrast, the sustainability scenario consistently showed the highest level of C-stock in HWPs (averaging 20% more than BAU), followed by the longevity scenario (at 18.2% more than the BAU), and finally, the reuse scenario (at 1.80% more than BAU).

The duration of positive net C-balance differs significantly across various forest management strategies and slightly among different wood-use scenarios (see **Table 5**). In the case of selective thinning, five positive periods, measured in years, can be observed, with their durations decreasing over time: [20, 6, 6, 3, 1] or [21, 7, 7, 4, 2], respectively, for BAU and the reuse scenarios or the longevity and sustainability scenarios. In the case of clearcut management, two positive periods can be observed with their durations slightly increasing over time: [20, 24] or [21, 25], respectively, for BAU and the reuse scenario or the longevity and sustainability scenarios. Regarding the shelterwood management, four positive periods can be observed with their durations decreasing and then increasing overtime: [20, 3, 3, 19] or [21, 3,

737   3, 20], respectively, for BAU and the reuse scenario or the longevity and sustainably scenarios.

739   Table 6: Duration of positive net C-balance among various forest management and wood-use
740   scenarios (in years).

Management scenario	Wood use scenario			
	BAU	Reuse	Longevity	Sustainability
Clearcut	36	36	41	41
Selective thinning	44	44	46	46
shelterwood	45	45	47	47

4.5. Implementation of dynamic substitution and methane release from landfill

Accounting for dynamic substitution and methane release from landfills had a significant impact on the overall C-balance of harvested wood products (HWPs) across all forest management and wood-use scenarios, leading to a substantial decrease in this balance, ranging from 5- to 39-fold compared to the original projections (see **Figure 9**). Moreover, under this new implementation, all combinations of forest management and wood-use scenarios resulted in a negative overall C-balance, including selective thinning, which had presented a positive overall C-balance under the original implementation (see **Figure 9**).

In contrast, this new implementation had no effect on the ranking of different forest management scenarios, as selective thinning consistently demonstrated superiority over alternative approaches across all wood-use scenarios, followed by clearcut management and, finally, shelterwood management (see **Figure 9**). Similarly, the implementation did not alter the ranking of overall wood-use scenarios, with the reuse scenario showing the minimal climate mitigation potential across all management scenarios, while both the longevity and sustainability scenarios made comparable and higher contributions to C-emissions reduction compared to the BAU scenario (see **Figure 9**).

Figure 9: Comparison of the overall C-balance across forest management and wood use scenarios using two implementations: original (no methane (CH_4) release, static substitution) and alternative (methane (CH_4) release, dynamic substitution). Negative values indicate net C-emissions.

In the following subsections (**4.5.1** and **4.5.2**), the results related to the impacts of dynamic substitution and methane release will be presented individually, respectively.

4.5.1. Effect of dynamic substitution

The implementation of dynamic updating of displacement factors, proportional to the reduction in global emissions consistent with the Paris Agreement, led to a decrease in displacement factors after reaching their maximum (see Figure A.1). This, in turn, resulted in a significant reduction in the substitution effect across all forest management and wood-use scenarios compared to the initial projections that utilized static displacement factors. By the planning horizon (year 140), cumulative material substitution in the dynamic scenario was reduced by 95% to 96% compared to the static substitution scenario, and cumulative energy substitution in the dynamic scenario was reduced by 95% compared to the static substitution scenario (see **Figure 10**).

Figure 10: Comparison of the cumulative sum of material and energy substitutions resulting from the use of a particular forest management and wood-use scenario using two implementations: the original (static substitution) and the alternative (dynamic substitution) (in tC ha^{-1}). The shaded portions of the bars represent the relative contribution of material substitution, while the solid portions represent the relative contribution of energy substitution.

4.6.1. Effect of methane release from landfills

The implementation of methane (CH_4) release from landfills under anaerobic conditions, following the IPCC's theoretical first-order methodology, resulted in a considerable increase in cumulative emissions across all forest management and wood-use scenarios compared to the initial simulations, which only considered wood decomposition in landfills under aerobic conditions. Consequently, by the planning horizon (year 140), cumulative emissions in the new implementation increased by 9.4% to 11% compared to the original implementation (see **Figure 11**).

Figure 11: Comparison of the cumulative emissions resulting from the use of various forest management and wood-use scenarios under two implementations: the original (no methane (CH_4) release) and the alternative (with methane (CH_4) release) (in tC ha^{-1}).

5. Discussions

In this study we presented the underlying theory and principles of TT, a dynamic model of the carbon balance in HWPs. TT has been coupled with 3D-CMCC-FEM with the aim to investigate the effect of different forest management and wood use options on the overall C-balance of HWPs on a real case. Assuming flexibility in both wood utilization and forest management practices, this study case demonstrates that the overall C-balance can be increased by giving preference to multiple light, non-distant cuttings over a few distant intensive cuttings and promoting wood use for material purposes, including the increase of recycling and products lifetime. Additionally, to assess the impact of methane release from landfills under anaerobic conditions and to account for the dynamic nature of displacement factors, we implemented a different model configuration. This approach revealed that considering CH_4 emissions significantly increased total emissions, while the dynamic displacement factors substantially reduced the substitution effect. However, these new considerations did not affect the ranking of different forest management and wood-use options in terms of their climate change mitigation potential.

Among various tested wood-use options, the sustainability scenario, representing the synergistic combination of increased recycling rate and extended product lifetime, demonstrated the highest mitigation potential among all wood use options. Increasing the recycling rate involves reinjecting an additional portion into the existing HWPs carbon stock, positively influencing both the level of HWPs stock and the material substitution effect, considering the new products, as evidenced in prior studies (e.g., (69,70)). The increase in the recycling rate results in a reduction in the portion of decay allocated to firewood, crucial for emission reduction due to the balanced relationship between firewood and recycled wood (e,g., (71)). Furthermore, the extended product lifetime contributes to lowering the decay rate, effectively delaying emissions from HWPs (e.g., (72)). The last point is strongly supported by the equilibrium analysis of the overall C-balance, demonstrating that scenarios with a 10% increase in product lifetime typically reach an overall equilibrium well after the other scenarios (see Results).

As far as forest management options are concerned, selective thinning management with regular cutting of approximately the same stand basal area (i.e., ~11 m^2 ha^{-1}) demonstrated the highest mitigation potential among the studied forest management options. It consistently maintained an overall C-balance above the zero line throughout the ~140-year planning

horizon. Despite periods where carbon emissions exceeded the HWP C-stock, compensatory
effects of material and energy substitution offset this difference. In contrast, shelterwood
management, although prescribing a harvesting of 31.72% basal area higher than selective
thinning (i.e., ~57 m^2 ha^{-1}), experienced an overall C-balance dropping below the zero line
around 130 years, a decade before the end of the planning horizon. This could be attributed to
the timing of a strong thinning (i.e., 33.44 m^2 ha^{-1}) that occurred earlier at the year 84. The
emissions from its decay could not be offset by the last thinning at the year 94 (i.e., 11.51 m^2
ha^{-1}), leading to an overall carbon equilibrium and negative balance thereafter. Despite
demonstrating the highest mitigation potential, selective thinning exhibited the shortest period
in positive net balance among different forest management options (i.e., 38 years compared to
45 and 46 years for clearcut and shelterwood managements, respectively). This suggests that
the option characterized by the longest period in positive net balance may not necessarily
provide the best mitigation potential. Other factors, such as the timing and intensity of
harvesting may come into play. In the case of clearcut and shelterwood managements, the last
cuttings are early and involve intense interventions, causing the decay of almost the entire stock
and justifying the early overall C-balance equilibrium relatively to the planning horizon.

Recent research increasingly questions the static nature of substitution factors, advocating for
a dynamic approach that accounts for technological advancements, improved resource
efficiency, enhanced recycling processes, and better end-of-life management of products (e.g.,
(19,21)). In this study, we adopted a dynamic update of displacement factors proportional to
global anthropogenic emissions, resulting in an 95% to 96% decrease in both material and
energy substitution effects compared to the static model. This substantial reduction underscores
the sensitivity of carbon accounting to substitution effect assumptions and highlights the
critical importance of using dynamic factors that can adapt to real-world changes. Consistent
with our results, (22) demonstrated that applying dynamic displacement factors leads to a
projected 33% reduction in the mitigation effect of wood product substitution in Europe by
2030, and a 96% reduction by 2100, compared to predictions using fixed factors. Similarly,
(19) conducted simulations showing that product substitution would saturate if displacement
factors reached zero within 100 years of the simulation's start, resulting in an 89% reduction in
cumulative substitution effects within 300 years.

Methane emissions from landfills are reported under the waste sector according to IPCC
guidelines for reporting emissions and sinks, which is why the methane effect is often excluded

from the calculation of HWP contributions by most WPMs. However, accounting for methane

emissions is crucial for developing practices that enhance the contribution of HWPs, especially

given methane's high global warming potential. Even a minor underestimation of CH_4 can lead

to a significant and erroneous overestimation of the potential of various mitigation projects. In

this study, including CH_4 release from landfills due to wood decomposition under anaerobic

conditions led to a substantial increase in emissions (in CO2 equivalents), ranging from 9.4%

to 11% compared to the original implementation where methane emissions were not

considered. Consistent with our results, (73) demonstrated that accounting for the global

warming potential of methane emissions reduced the estimated contribution of U.S. forests and

HWPs to GHG mitigation for the year 2005 by more than half (in C-equivalent).

The outcomes of this study are significantly enhanced by the inclusion of the bucking allocation

module in the TT model, which considers the dimensions of logs for the allocation of wood to

HWPs. This is crucial because various products have distinct use and post-use properties,

leading to diverse time dynamics, and a pre-established allocation may not accurately reflect

reality. The role of the bucking allocation was evident across all management options. Each

successive intervention, characterized by a higher mean DBH of the harvested stems than the

precedent due to the stand's growth dynamic, resulted in the newly HWPs stock exhibiting a

slower decay dynamic than the precedent due to the higher portion of long-lived products in

the most recent one. For instance, in the case of clearcut management, two interventions were

made at the years 39 and 84, yielding decay rates of ~2% per year and 1.5% per year,

respectively. The analysis of the bucking allocation in both the initial and subsequent harvests,

reveals that, from the first harvest, the production was limited to short- and medium-lived

HWPs such as paper and particle, while novel categories of long-lived products were

introduced in the second harvest, exemplified by furniture and sawing, which justify the

decrease in the decay rate of the HWPs stock (see **Table A.1**).

These multiple findings align with prior studies in this area. In a theoretical exercise evaluating

the mitigation potential of wood product use in the European forest sector, (18) demonstrated

that increasing each component—whether recycling rate or lifespan—individually by

approximately 20% could result in an 8.9% increase in C-removal by 2030 by reference to the

2017 BAU scenario. Furthermore, the study states that a simultaneous 20% increase in both

average product lifespan and recycling rate could yield a 17.3% increase in carbon removal by

2030. Another recent study by (74) explored the C-storage potential of HWPs in four EU

countries, projecting outcomes from 2020 to 2050 across six alternative scenarios. The findings suggest that prioritizing wood-use for material purposes, while maintaining a constant harvest, yields the highest mitigation benefits in the short to medium term. Moreover, in a continental study (EU-28) focusing on assessing the consequences of implementing policy choices on GHG emissions and removals, it was revealed that the adoption of the cascading scenario of HWPs led to a slight increase in the net balance between emissions and removals from/by HWPs. The balance was simulated to rise from approximately 34 Mt CO_2-eq in the base period around 2010 to just under 40 Mt CO_2-eq in 2030, as documented by (75). In another study aiming to investigate the potential of cascading use of woody biomass in the EU, it was found that GHG emissions could be reduced by 35 $MtCO^2$-eq year^{-1} as a result of implementing the maximum technical potential to increase recycling of waste wood and paper flows (76).

From another perspective, the significance of management has been underscored in numerous studies. In (77), the application of five silvicultural itineraries, derived from translating five alternative management objectives for an even-aged forest, resulted in significantly different outcomes regarding the carbon sequestration by HWPs. In another study, (78) concluded that the method of harvesting is crucial showing further that a regular removal of timber from forest in a way that maintains a continuous canopy is likely to give substantially higher sustained yields and amount of carbon storage than periodical clear-felling. The same study suggests that if the objective was to maximize timber volume yield, the optimal management system would be the regular thinning of forest. A physiological explanation of this could be that the continuous canopy cover with a moderately high leaf area index (~ 4 m^2 m^{-2}) provides high light interception and net primary production (Bouriaud et al., under review). Regular thinning ensures that the forest has lower biomass than an undisturbed forest, and it is continuously growing, resulting in lower maintenance respiration (4). In a different context, (79) demonstrated that selection harvesting was the preferred method compared to clearcutting when the goal was to maximize total carbon storage in the forest landscape and wood products generated from harvesting over an 80-year planning horizon. This preference was justified by the fact that selection harvesting, in contrast to clearcutting, offers the advantage of maintaining the forest close to its maximum biological productivity. Additionally, it provides a consistent and sustainable yield of desirable wood products at set intervals. In contrast, clearcutting involves harvesting stands when their average DBH reaches 10 cm (merchantable dimension), and their yields exceed 50 m^3 ha^{-1}. This practice is more likely to favor the production of

pulpwood due to the smaller size of the harvested trees, which implies a faster decay of the derived products and thus of the HWPs stock.

Limitations and perspectives

Considering the model's sensitivity to inputs and the dependence of results on the approach used for calculating HWPs stock, emissions, and substitution, it is crucial to account for uncertainties associated with these elements (80). The TT model tracks wood throughout its entire lifecycle, from harvesting to disposal sites, thereby encompassing major processes in between. This modeling principle is considered advanced due to its capacity to accurately trace carbon over the lifetime of wood products, providing precise results. However, implementing this principle at the national level poses challenges due to the large number and diversity of HWPs, as well as the substantial amount of the required local data (16). As the amount of data increases, the level of compounded uncertainty proportionally rises. A subsequent phase would involve scrutinizing the sensitivity of various model outputs to the input data.

From another perspective, the grading of logs utilizing the bucking allocation module, as exemplified by the implementation in TT, encounters obstacles due to various factors presumed to impact wood quality — such as strength, knottiness, appearance, stiffness, hardness, and durability. It is almost impossible, using exclusively models, to account for all these factors. As an illustration, the implemented module does not account for the presence of residual branches below the crown base and external defects. Furthermore, it is conceivable that variations in knot distribution exist across different management scenarios. Owing to the omission of this parameter in our model, we assert that the disparities in the proportions of HWP classes could be somewhat undervalued. This conjecture remains subject to empirical verification, yet the current capabilities of TT do not permit the necessary resolution for such details. Therefore, future refinements of the model are imperative to enable a more precise evaluation of these nuances. Furthermore, as demonstrated in (17), the choice of one distribution function over another to simulate product removal from use can significantly influence the resulting carbon stock estimates. The TT model currently utilizes the normal distribution as its default; however, this selection should be reassessed in future analyses.

Given that the maximum climate benefit varies over time for different forest managements (81,82), we raise questions about the relevance of the fixed planning horizon of 140 years in

983   this study and its capacity to appropriately address the underlying research hypothesis. In this
984   context, we may explore in the future the potential of alternative management strategies, such
985   as clearcut and shelterwood, to be optimal for different planning horizons. Furthermore, we
986   may question the assumption that simulations conducted over multiple rotations can effectively
987   control for instantaneous response.
988
Moreover, it is crucial to note that carbon neutrality does not necessarily imply climate
neutrality. When wood is burned or decays, emissions spend some time in the atmosphere
before being sequestered, contributing to climate change in the meantime. In other words, the
timing of emissions and sinks has an impact on the overall cumulative climatic impact (83–
85). Among the factors affecting this timing are the speed of biomass regrowth (rotation period)
and the storage of biomass products (e.g., building, furniture, and paper). Since these factors
are closely linked to forest management practices, the assessment of these practices should not
only consider the carbon balance but also examine the timing of carbon input and output flows.
997
Another question concerns the methodological scheme used in this study. Evaluating the
potential of various forest management and wood-use options in mitigating climate change
necessitates a systemic perspective that considers the diverse pools of the forest sector,
including biomass, soil, and products (86,87). The current study exclusively focuses on the
wood products pool, which may not be directly relevant (or being the only one) for guiding the
decision-making of forest managers. This is particularly important considering that the forest
ecosystem constitutes the major contribution of the forest sector in terms of climate change
mitigation. To exemplify this recent assertion, (9) calculated the emissions and removals linked
to HWPs for the historical period (1992-2012) and future scenarios until 2030 in the EU
(excluding Malta and Cyprus). They utilized FAOSTAT data on forest product production (see
https://www.fao.org/faostat/en/#data/FO). The findings of this research indicate that the
average historical sink of HWPs from 2000 to 2012 accounts for 10% of the sink contained in
the forest pools. This underscores the importance of including non-HWP carbon pools in
decision-making processes as well.
1012
1013   Finally, the results of this use case suggest that shelterwood management is the optimal choice
1014   for optimizing the overall carbon balance of HWPs within the defined planning horizon. The
1015   rationale behind this preference lies partially in the late thinning operation characteristic of this
1016   management scenario, allowing for the C-stock and substitution to counterbalance total

emissions effectively. Notably, this silvicultural practice of partial cutting aligns with natural disturbance–based silviculture, as it mimics natural dynamics by anticipating the imminent mortality of a portion of mature trees (88). Moreover, considering the ongoing rapid changes in many ecosystems and their interaction with natural disturbances, which are expected to be significant and less predictable in the future (89), multi-aged forest management systems offer a promising approach to enhance resistance and resilience, which is attributed to the presence of multiple age classes, providing more potential pathways for post-disturbance management and recovery (90). Within this context, a suggestion arises to guide future studies in accounting for disturbance risks. Neglecting to incorporate such considerations could result in an overestimation of the climate mitigation efficacy associated with various forest management alternatives. The emerging results show that the failure to account for methane release from landfills can lead to an overestimation of the mitigation potential of different options. Efforts to mitigate these emissions could focus on diverting wood products away from landfills by increasing recycling and directing them to incineration facilities, which not only reduce emissions but also capture energy. The results also indicate that considering static substitution factors may overestimate the substitution effect resulting from the use of HWPs over fossil energy or energy-intensive materials. However, we believe that *ceteris paribus*, substitution could play a central supporting role in the absence of a strong mitigation policy.

6. Conclusions

This research emphasizes the pivotal role of harvested wood products (HWPs) in climate change mitigation, as recognized in various Nationally Determined Contributions (NDCs) under the Paris Agreement. Our novel framework, 'TimberTracer', coupled with the 3D-CMCC-FEM forest growth model, enables dynamic assessment of forest management practices and wood-use scenarios, revealing selective thinning as the optimal forest management practice. Additionally, increasing recycling rates and extending product lifespans prove effective in enhancing C-balance. Results show also that failure to account for methane release from landfill and dynamic substitution of HWPs can lead to an overestimation of the mitigation potential of different options. These insights offer valuable guidance for advancing knowledge and optimizing forest management decisions and advancing climate change mitigation efforts.

Data availability

The data resulting from this study is available in both Supplementary Files 1 and 4. Additionally, the output simulation is accessible via the following Zenodo link: https://zenodo.org/records/10692189

Competing interest

Authors have no competing interests as defined by BMC, or other interests that might be perceived to influence the results and/or discussion reported in this paper.

Code availability

TimberTracer is a Python based model for all operating systems (Windows, Linux, and MacOS). It is free and open source (version 1.0.0 with GPL-3 license, requiring Python >= 3x). We openly share our model on GitHub for collaborative research, fostering a community-driven approach to innovation. A tutorial on Google Colab empowers users to harness TimberTracer's capabilities, customize analyses, and integrate it seamlessly into projects. Detailed instructions are available on GitHub (https://github.com/issamyax/TimberTracer), emphasizing TimberTracer's primary objective: providing valuable insights into carbon sequestration, substitution, and emissions progression over time. We encourage users to report any issues and/or desired extensions on our active issues page https://github.com/issamyax/TimberTracer/issues. The 3D-CMCC-FEM model code version 5.6 is publicly available under the GNU General Public Licence v3.0 (GPL) and can be found on the Github platform at https://github.com/Forest-Modelling-Lab/3D-CMCC-FEM.

References

1.   Gulev SK, Thorne PW, Ahn J, Dentener FJ, Domingues CM, Gerland S, et al. Changing state of the climate system. In: Masson-Delmotte V, Zhai P, Pirani A, Connors SL, Péan C, Berger S, et al., editors. Cambridge, United Kingdom and New York, NY, USA: Cambridge University Press; 2021 [cited 2023 Jan 19]. p. 287–422. Available from: https://www.ipcc.ch/report/ar6/wg1/downloads/report/IPCC_AR6_WGI_Chapter02.pdf

2.   Pan Y, Birdsey RA, Fang J, Houghton R, Kauppi PE, Kurz WA, et al. A Large and Persistent Carbon Sink in the World's Forests. Science. 2011 Aug 19;333(6045):988–93.

3.   Crumpler K, Abi khalil R, Tanganelli E, Rai N, Roffredi L, Meybeck A, et al. 2021 (Interim) Global update report: Agriculture, Forestry and Fisheries in the Nationally Determined Contributions [Internet]. Rome, Italy: FAO; 2021 [cited 2024 Jan 9]. 84 p. (Environment and natural resources management working paper). Available from: https://www.fao.org/documents/card/en/c/cb7442en

4.   Schulze ED, Bouriaud O, Irslinger R, Valentini R. The role of wood harvest from sustainably managed forests in the carbon cycle. Ann For Sci. 2022 Apr 7;79(1):17.

5.   Collalti A, Ibrom A, Stockmarr A, Cescatti A, Alkama R, Fernández-Martínez M, et al. Forest production efficiency increases with growth temperature. Nat Commun. 2020 Oct 21;11(1):5322.

6.   Nabuurs GJ, Lindner M, Verkerk PJ, Gunia K, Deda P, Michalak R, et al. First signs of carbon sink saturation in European forest biomass. Nat Clim Change. 2013 Sep;3(9):792–6.

7.   Leskinen P, Cardellini G, González-García S, Hurmekoski E, Sathre R, Seppälä J, et al. Substitution effects of wood-based products in climate change mitigation [Internet]. European Forest Institute; 2018 Nov [cited 2023 Nov 17]. (From Science to Policy). Available from: https://www.efi.int/publications-bank/substitution-effects-wood-based-products-climate-change-mitigation

8.   Pingoud K, Pohjola J, Valsta L. Assessing the integrated climatic impacts of forestry and wood products. Silva Fenn [Internet]. 2010 Dec 31 [cited 2023 Nov 18];44(1). Available from: https://www.silvafennica.fi/article/166

9.   Pilli R, Fiorese G, Grassi G. EU mitigation potential of harvested wood products. Carbon Balance Manag. 2015 Feb 25;10(1):6.

10.   Dugan AJ, Birdsey R, Mascorro VS, Magnan M, Smyth CE, Olguin M, et al. A systems approach to assess climate change mitigation options in landscapes of the United States forest sector. Carbon Balance Manag. 2018 Sep 4;13(1):13.

11.   Di Lallo G, Chiriacò MV, Tarasova E, Köhl M, Perugini L. The land sector in the low carbon emission strategies in the European Union: role and future expectations. Clim Policy. 2023;0(0):1–15.

12.   Grassi G, House J, Dentener F, Federici S, den Elzen M, Penman J. The key role of forests in meeting climate targets requires science for credible mitigation. Nat Clim Change. 2017 Mar;7(3):220–6.

13.   Sato A, Nojiri Y. Assessing the contribution of harvested wood products under greenhouse gas estimation: accounting under the Paris Agreement and the potential for double-counting among the choice of approaches. Carbon Balance Manag. 2019 Nov 26;14(1):15.

14.   Kayo C, Kalt G, Tsunetsugu Y, Hashimoto S, Komata H, Noda R, et al. The default methods in the 2019 Refinement drastically reduce estimates of global carbon sinks of harvested wood products. Carbon Balance Manag. 2021 Dec 11;16(1):37.

15.   Király É, Kis-Kovács G, Börcsök Z, Kocsis Z, Németh G, Polgár A, et al. Modelling Carbon Storage Dynamics of Wood Products with the HWP-RIAL Model—Projection of Particleboard End-of-Life Emissions under Different Climate Mitigation Measures. Sustainability. 2023 Jan;15(7):6322.

16.   Jasinevičius G, Lindner M, Pingoud K, Tykkylainen M. Review of models for carbon accounting in harvested wood products. Int Wood Prod J. 2015 Oct 2;6(4):198–212.

17.   Brunet-Navarro P, Jochheim H, Muys B. Modelling carbon stocks and fluxes in the wood product sector: a comparative review. Glob Change Biol. 2016;22(7):2555–69.

18.   Brunet-Navarro P, Jochheim H, Muys B. The effect of increasing lifespan and recycling rate on carbon storage in wood products from theoretical model to application for the European wood sector. Mitig Adapt Strateg Glob Change. 2017 Dec 1;22(8):1193–205.

19.   Harmon ME. Have product substitution carbon benefits been overestimated? A sensitivity analysis of key assumptions. Environ Res Lett. 2019 Jun;14(6):065008.

20.   Sathre R, Gustavsson L. Using wood products to mitigate climate change: External costs and structural change. Appl Energy. 2009 Feb 1;86(2):251–7.

21.   Howard C, Dymond CC, Griess VC, Tolkien-Spurr D, van Kooten GC. Wood product carbon substitution benefits: a critical review of assumptions. Carbon Balance Manag. 2021 Mar 30;16(1):9.

22.   Brunet-Navarro P, Jochheim H, Cardellini G, Richter K, Muys B. Climate mitigation by energy and material substitution of wood products has an expiry date. J Clean Prod. 2021 Jun 20;303:127026.

23.   Kaipainen T, Liski J, Pussinen A, Karjalainen T. Managing carbon sinks by changing rotation length in European forests. Environ Sci Policy. 2004 Jun;7(3):205–19.

24.   Dalmonech D, Marano G, Amthor JS, Cescatti A, Lindner M, Trotta C, et al. Feasibility of enhancing carbon sequestration and stock capacity in temperate and boreal European forests via changes to management regimes. Agric For Meteorol. 2022 Dec 15;327:109203.

25.   Moreaux V, Martel S, Bosc A, Picart D, Achat D, Moisy C, et al. Energy, water and carbon exchanges in managed forest ecosystems: description, sensitivity analysis and evaluation of the INRAE GO+ model, version 3.0. Geosci Model Dev. 2020 Dec 1;13(12):5973–6009.

26.   Collalti A, Perugini L, Santini M, Chiti T, Nolè A, Matteucci G, et al. A process-based

model to simulate growth in forests with complex structure: Evaluation and use of 3D-CMCC Forest Ecosystem Model in a deciduous forest in Central Italy. Ecol Model. 2014 Jan 24;272:362–78.

27.   Collalti A, Bondo C, Buttafuoco G, Maesano M, Caloiero T, Lucà F, et al. Protocollo di simulazione, calibrazione e validazione del modello 3D-CMCC-CNR-FEM: il caso studio del bacino altamente strumentato del Bonis in Calabria. For - J Silvic For Ecol. 2017 Aug 14;14(1):247.

28.   Matsumoto R, Kayo C, Kita S, Nakamura K, Lauk C, Funada R. Estimation of carbon stocks in wood products for private building companies. Sci Rep. 2022 Oct 27;12:18112.

29.   Cao QV. Predicting Parameters of a Weibull Function for Modeling Diameter Distribution. For Sci. 2004 Oct 1;50(5):682–5.

30.   Sohn JA, Saha S, Bauhus J. Potential of forest thinning to mitigate drought stress: A meta-analysis. For Ecol Manag. 2016 Nov 15;380:261–73.

31.   Cao T, Hyytiäinen K, Tahvonen O, Valsta L. Effects of initial stand states on optimal thinning regime and rotation of Picea abies stands. Scand J For Res. 2006 Oct 1;21(5):388–98.

32.   Fabrika M, Vaculčiak T. Modeling Natural Disturbances in Tree Growth Model SIBYLA. In: Střelcová K, Mátyás C, Kleidon A, Lapin M, Matejka F, Blaženec M, et al., editors. Bioclimatology and Natural Hazards [Internet]. Dordrecht: Springer Netherlands; 2009 [cited 2024 Jan 13]. p. 155–64. Available from: https://doi.org/10.1007/978-1-4020-8876-6_14

33.   Fabrika M, Ďurský J. Algorithms and software solution of thinning models for SIBYLA growth simulator. J For Sci. 2005 Oct 31;51(10):431–45.

34.   Bucket E, Moguedec GL, Mothe FF, Nepveu G. Une modélisation des bilans "environnement" et "produits" de sylvicultures contrastées : cas du chêne sessile. Rev For Fr. 2005;57(3):311.

35.   Longuetaud F, Mothe F, Kerautret B, Krähenbühl A, Hory L, Leban JM, et al. Automatic knot detection and measurements from X-ray CT images of wood: A review and validation of an improved algorithm on softwood samples. Comput Electron Agric. 2012 Jul 1;85:77–89.

36.   Thurner M, Beer C, Crowther T, Falster D, Manzoni S, Prokushkin A, et al. Sapwood biomass carbon in northern boreal and temperate forests. Glob Ecol Biogeogr. 2019;28(5):640–60.

37.   Max T, Burkhart H. Segmented Polynomial Regression Applied to Taper Equations. For Sci. 1976 Sep 1;22:283–9.

38.   Longuetaud F, Mothe F, Leban JM, Mäkelä A. Picea abies sapwood width: Variations within and between trees. Scand J For Res. 2006 Feb 1;21(1):41–53.

39.   IPCC. CH4 emissions from solide waste disposal. In: IPCC Guidelines for National Greenhouse Gas Inventories [Internet]. 2006. Available from: https://www.ipcc-

nggip.iges.or.jp/public/gp/bgp/5_1_CH4_Solid_Waste.pdf

40.   Sathre R, O'Connor J. Meta-analysis of greenhouse gas displacement factors of wood product substitution. Environ Sci Policy. 2010 Apr 1;13(2):104–14.

41.   Testolin R, Dalmonech D, Marano G, Bagnara M, D'Andrea E, Matteucci G, et al. Simulating diverse forest management options in a changing climate on a Pinus nigra subsp. laricio plantation in Southern Italy. Sci Total Environ. 2023 Jan 20;857:159361.

42.   Nicolaci A, Marziliano PA, Pignataro F, Menguzzato G, Iovino F. Fire prevention with thinning operations in black pine reforestations. Results of a study on a regional scale. Ital For E Mont. 2015 Jul 6;70(1):7–21.

43.   Callegari G, Ferrari E, Garfì G, Iovino F, Veltri A. Impact of thinning on the water balance of a catchment in a Mediterranean environment. For Chron. 2003 Apr;79(2):301–6.

44.   Collalti A, Marconi S, Ibrom A, Trotta C, Anav A, D'Andrea E, et al. Validation of 3D-CMCC Forest Ecosystem Model (v.5.1) against eddy covariance data for 10 European forest sites. Geosci Model Dev. 2016 Feb 8;9(2):479–504.

45.   Collalti A, Trotta C, Keenan TF, Ibrom A, Bond-Lamberty B, Grote R, et al. Thinning Can Reduce Losses in Carbon Use Efficiency and Carbon Stocks in Managed Forests Under Warmer Climate. J Adv Model Earth Syst. 2018;10(10):2427–52.

46.   Collalti A, Thornton PE, Cescatti A, Rita A, Borghetti M, Nolè A, et al. The sensitivity of the forest carbon budget shifts across processes along with stand development and climate change. Ecol Appl. 2019;29(2):e01837.

47.   Mahnken M, Cailleret M, Collalti A, Trotta C, Biondo C, D'Andrea E, et al. Accuracy, realism and general applicability of European forest models. Glob Change Biol. 2022;28(23):6921–43.

48.   Thornton PE, Running SW. An improved algorithm for estimating incident daily solar radiation from measurements of temperature, humidity, and precipitation. Agric For Meteorol. 1999 Mar 22;93(4):211–28.

49.   Rockel B, Will A, Hense A. The Regional Climate Model COSMO-CLM (CCLM). Meteorol Z. 2008 Aug 25;347–8.

50.   Bucchignani E, Montesarchio M, Zollo AL, Mercogliano P. High-resolution climate simulations with COSMO-CLM over Italy: performance evaluation and climate projections for the 21st century. Int J Climatol. 2016;36(2):735–56.

51.   Zollo AL, Rillo V, Bucchignani E, Montesarchio M, Mercogliano P. Extreme temperature and precipitation events over Italy: assessment of high-resolution simulations with COSMO-CLM and future scenarios. Int J Climatol. 2016;36(2):987–1004.

52.   Scoccimarro E, Gualdi S, Bellucci A, Sanna A, Fogli PG, Manzini E, et al. Effects of Tropical Cyclones on Ocean Heat Transport in a High-Resolution Coupled General Circulation Model. J Clim. 2011 Aug 15;24(16):4368–84.

53. Meinshausen M, Raper SCB, Wigley TML. Emulating coupled atmosphere-ocean and carbon cycle models with a simpler model, MAGICC6 – Part 1: Model description and calibration. Atmospheric Chem Phys. 2011 Feb 16;11(4):1417–56.

54. Buttafuoco G, Castrignanò A, Busoni E, Dimase AC. Studying the spatial structure evolution of soil water content using multivariate geostatistics. J Hydrol. 2005 Sep 15;311(1):202–18.

55. Moresi FV, Maesano M, Collalti A, Sidle RC, Matteucci G, Scarascia Mugnozza G. Mapping Landslide Prediction through a GIS-Based Model: A Case Study in a Catchment in Southern Italy. Geosciences. 2020 Aug;10(8):309.

56. Jozsa LA, Middleton GR. A DISCUSSION OF WOOD QUALITY ATTRIBUTES AND THEIR PRACTICAL IMPLICATIONS. 1994;

57. CTBA C. Manuel scierie: Techniques et matériels. Centre Technique du Bois et de l'Ameublement; 2001. 400 p.

58. Burschel P, Kürsten E, Larson BC, Weber M. Present role of German forests and forestry in the national carbon budget and options to its increase. Water Air Soil Pollut. 1993 Oct 1;70(1):325–40.

59. Karjalainen T, Kellomäki S, Pussinen A. Role of wood-based products in absorbing atmospheric carbon. Silva Fenn [Internet]. 1994 Jan 1 [cited 2024 Jan 17];28(2). Available from: https://www.silvafennica.fi/article/5398

60. Nabuurs GJ. Significance of wood products in forest sector carbon balances. In: Apps MJ, Price DT, editors. Forest Ecosystems, Forest Management and the Global Carbon Cycle. Berlin, Heidelberg: Springer; 1996. p. 245–56. (NATO ASI Series).

61. E. Skog K, A. Nicholson G. Carbon cycling through wood products: the role of wood and paper products in carbon sequestration. 1998;48(7).

62. Eggers T. The Impacts of Manufacturing and Utilisation of Wood Products on the European Carbon Budget. 2002.

63. Masera OR, Garza-Caligaris JF, Kanninen M, Karjalainen T, Liski J, Nabuurs GJ, et al. Modeling carbon sequestration in afforestation, agroforestry and forest management projects: the CO2FIX V.2 approach. Ecol Model. 2003 Jun 15;164(2):177–99.

64. Pingoud K, Perälä AL, Soimakallio S, Pussinen A. Greenhouse gas impacts of harvested wood products: Evaluation and development of methods. Espoo: VTT Technical Research Centre of Finland; 2003. (VTT Tiedotteita - Meddelanden - Research Notes).

65. Suter F, Steubing B, Hellweg S. Life Cycle Impacts and Benefits of Wood along the Value Chain: The Case of Switzerland. J Ind Ecol. 2017;21(4):874–86.

66. Dias A, Gaspar MJ, Carvalho A, Pires J, Lima-Brito J, Silva ME, et al. Within- and between-tree variation of wood density components in Pinus nigra at six sites in Portugal. Ann For Sci. 2018 Jun;75(2):1–19.

67. Boukhris I, Puletti N, Vonderach C, Guasti M, Lahssini S, Santini M, et al. Comparative analysis of taper models for Pinus nigra Arn. using terrestrial laser scanner acquired data. IForest - Biogeosciences For. 2024 Aug 31;17(4):203–12.

68. Rockström J, Gaffney O, Rogelj J, Meinshausen M, Nakicenovic N, Schellnhuber HJ. A roadmap for rapid decarbonization. Science. 2017 Mar 24;355(6331):1269–71.

69. Pingoud K, Ekholm T, Savolainen I. Global warming potential factors and warming payback time as climate indicators of forest biomass use. Mitig Adapt Strateg Glob Change. 2012 Apr 1;17(4):369–86.

70. Chen C, Habert G, Bouzidi Y, Jullien A, Ventura A. LCA allocation procedure used as an incitative method for waste recycling: An application to mineral additions in concrete. Resour Conserv Recycl. 2010 Oct 1;54(12):1231–40.

71. Gustavsson L, Haus S, Lundblad M, Lundström A, Ortiz CA, Sathre R, et al. Climate change effects of forestry and substitution of carbon-intensive materials and fossil fuels. Renew Sustain Energy Rev. 2017 Jan 1;67:612–24.

72. Churkina G, Organschi A, Reyer CPO, Ruff A, Vinke K, Liu Z, et al. Buildings as a global carbon sink. Nat Sustain. 2020 Apr;3(4):269–76.

73. Skog KE. Sequestration of carbon in harvested wood products for the United States. For Prod J. 2008;58(6).

74. Bozzolan N, Grassi G, Mohren F, Nabuurs GJ. Options to improve the carbon balance of the harvested wood products sector in four EU countries. GCB Bioenergy. 2024;16(1):e13104.

75. Rüter S, Werner F, Forsell N. ClimWood2030, Climate benefits of material substitution by forest biomass and harvested wood products: Perspective 2030 - Final ReportlimWood2030, Climate benefits of material substitution by forest biomass and harvested wood products: Perspective 2030 - Final Report [Internet]. DE: Johann Heinrich von Thünen-Institut; 2016 [cited 2024 Jan 7]. Available from: https://doi.org/10.3220/REP1468328990000

76. Bais-Moleman AL, Sikkema R, Vis M, Reumerman P, Theurl MC, Erb KH. Assessing wood use efficiency and greenhouse gas emissions of wood product cascading in the European Union. J Clean Prod. 2018 Jan 20;172:3942–54.

77. Hennigar CR, MacLean DA, Amos-Binks LJ. A novel approach to optimize management strategies for carbon stored in both forests and wood products. For Ecol Manag. 2008 Aug 10;256(4):786–97.

78. Thornley JHM, Cannell MGR. Managing forests for wood yield and carbon storage: a theoretical study. Tree Physiol. 2000 Apr 1;20(7):477–84.

79. Bourque CPA, Neilson ET, Gruenwald C, Perrin SF, Hiltz JC, Blin YA, et al. Optimizing carbon sequestration in commercial forests by integrating carbon management objectives in wood supply modeling. Mitig Adapt Strateg Glob Change. 2007 Aug 1;12(7):1253–75.

80. Cláudia Dias A, Louro M, Arroja L, Capela I. Comparison of methods for estimating carbon in harvested wood products. Biomass Bioenergy. 2009 Feb 1;33(2):213–22.

81. Guest G, Cherubini F, Strømman AH. Global Warming Potential of Carbon Dioxide Emissions from Biomass Stored in the Anthroposphere and Used for Bioenergy at End of Life. J Ind Ecol. 2013;17(1):20–30.

82. Röder M, Thiffault E, Martínez-Alonso C, Senez-Gagnon F, Paradis L, Thornley P. Understanding the timing and variation of greenhouse gas emissions of forest bioenergy systems. Biomass Bioenergy. 2019 Feb 1;121:99–114.

83. Cherubini F, Peters GP, Berntsen T, Strømman AH, Hertwich E. CO2 emissions from biomass combustion for bioenergy: atmospheric decay and contribution to global warming. GCB Bioenergy. 2011;3(5):413–26.

84. Levasseur A, Lesage P, Margni M, Deschênes L, Samson R. Considering Time in LCA: Dynamic LCA and Its Application to Global Warming Impact Assessments. Environ Sci Technol. 2010 Apr 15;44(8):3169–74.

85. Levasseur A, Lesage P, Margni M, Brandão M, Samson R. Assessing temporary carbon sequestration and storage projects through land use, land-use change and forestry: comparison of dynamic life cycle assessment with ton-year approaches. Clim Change. 2012 Dec 1;115(3):759–76.

86. Grassi G, Fiorese G, Pilli R, Jonsson K, Blujdea V, Korosuo A, et al. JRC Publications Repository. 2021 [cited 2023 Dec 18]. Brief on the role of the forest-based bioeconomy in mitigating climate change through carbon storage and material substitution. Available from: https://publications.jrc.ec.europa.eu/repository/handle/JRC124374

87. Lemprière TC, Kurz WA, Hogg EH, Schmoll C, Rampley GJ, Yemshanov D, et al. Canadian boreal forests and climate change mitigation. Environ Rev. 2013 Dec;21(4):293–321.

88. Bose AK, Harvey BD, Brais S, Beaudet M, Leduc A. Constraints to partial cutting in the boreal forest of Canada in the context of natural disturbance-based management: a review. For Int J For Res. 2014 Jan 1;87(1):11–28.

89. Seidl R, Thom D, Kautz M, Martín-Benito D, Peltoniemi M, Vacchiano G, et al. Forest disturbances under climate change. Nat Clim Change. 2017 Jul 1;7:395–402.

90. O'Hara KL, Ramage BS. Silviculture in an uncertain world: utilizing multi-aged management systems to integrate disturbance†. For Int J For Res. 2013 Oct 1;86(4):401–10.

1433   **Appendix A**

1434

1435   Table A.1: Clearcut management interventions and the products derived from the thinned
1436   wood.

Intervention	Products	Stock (tC)	Decay rate (%)
Thinning	Millsite	1.81	2.02 "(0.26 tC/yr)"
	Paper	2.16	
	Particle	6.88	
	Fire	1,97	
Harvesting	Millsite	5.09	1.47 "(0.93 tC/yr)"
	Paper	5.73	
	Particle	13.83	
	Fire	9.81	
	Furniture	24.89	
	Sawing	2.81	

1437
1438
1439
1440

1441
1442   Figure A.1: Dynamic evolution of substitution factors of different HWPs proportionally to the
1443   evolution of global GHG emissions following the Paris Agreement pathways.