# *TimberTracer*: A Comprehensive Framework for the Evaluation of Carbon Sequestration by Forest Management and Substitution of Harvested Wood Products.

I. Boukhris[1,2]*, A. Collalti[3,4]*, S. Lahssini[5], D. Dalmonech[3,4], F. Nakhle[6], R. Testolin[3,7], M. V. Chiriacò[2], M. Santini[2], R. Valentini[1,2]

1. Forest Ecology Lab, Department for Innovation in Biological, Agri-Food and Forest Systems (DIBAF), University of Tuscia, 01100 Viterbo, Italy (rik@unitus.it; issam.boukhris@unitus.it)

2. CMCC Foundation - Euro-Mediterranean Center on Climate Change, Italy (monia.santini@cmcc.it; mariavincenza.chiriaco@cmcc.it)

3. Forest Modeling Lab, Institute for Agriculture and Forestry Systems in the Mediterranean, National Research Council of Italy (CNR-ISAFOM), Via Madonna Alta 128, 06128 Perugia, Italy (alessio.collalti@cnr.it; daniela.dalmonech@isafom.cnr.it)

4. National Biodiversity Future Center (NBFC), 90133 Palermo, Italy

5. Department of Forest Development, National School of Forest Engineers, Salé 11000, Morocco (marghadi@gmail.com)

6. Department of Computer Science, Temple University, Japan Campus, Setagaya City, Tokyo, 154-004, Japan (farid.nakhle@tuj.temple.edu)

7. Biome Lab, Department of Biological, Geological and Environmental Sciences, Alma Mater Studiorum University of Bologna, 40126 Bologna, Italy (riccardo.testolin@gmail.com)

* Correspondent authors. Emails: issam.boukhris@unitus.it; alessio.collalti@cnr.it

**Abstract**

*Background*

Harvested wood products (HWPs) have a pivotal role in climate change mitigation, a recognition solidified in many Nationally Determined Contributions (NDCs) under the Paris Agreement. Integrating HWPs' greenhouse gas (GHG) emissions and removals into accounting requirements relies on typical decision-oriented tools known as wood product models (WPMs). The study introduces the *TimberTracer* (TT) framework, designed to

simulate HWP carbon stock, substitution effects, and emissions from wood decay and

bioenergy.

*Results*

Coupled with the 3D-CMCC-FEM forest growth model, *TimberTracer* was applied to Laricio

Pine (*Pinus nigra* subsp. *laricio*) in Italy's Bonis watershed, evaluating three forest

management practices (clearcut, selective thinning, and shelterwood) and four wood-use

scenarios (business as usual, increased recycling rate, extended average lifespan, and a

simultaneous increase in both the recycling rate and the average lifespan) over a 140-year

planning horizon, to assess the overall carbon balance of HWPs. Furthermore, this study

evaluates the consequences of disregarding landfill methane emissions and relying on static

substitution factors, assessing their impact on the mitigation potential of various options. This

investigation, covering HWPs stock, carbon (C) emissions, and the substitution effect,

revealed that selective thinning emerged as the optimal forest management scenario. In

addition, a simultaneous 10% increase in both the recycling rate and half-life, under the so-

called "sustainability" scenario, proved to be the optimal wood-use strategy. Finally, the

analysis shows that failing to account for landfill methane emissions and the use of dynamic

substitution can significantly overestimate the mitigation potential of various forest

management and wood-use options, which underscores the critical importance of a

comprehensive accounting in climate mitigation strategies involving HWPs.

*Conclusions*

Our study highlights the critical role of harvested wood products (HWPs) in climate change

mitigation, as endorsed by multiple Nationally Determined Contributions (NDCs) under the

Paris Agreement. Utilizing the *TimberTracer* framework coupled with the 3D-CMCC-FEM

forest growth model, we identified selective thinning as the optimal forest management

practice. Additionally, enhancing recycling rates and extending product lifespan effectively

bolstered the carbon balance. Moreover, this study emphasizes the necessity of accounting for

landfill methane emissions and dynamic product substitution, as failing to do so may

significantly overestimate the mitigation potential of implemented projects. These findings

offer actionable insights to optimize forest management strategies and advance climate

change mitigation efforts.

**1. Background**

Terrestrial ecosystems play a major role in the global carbon cycle owing to their inherent
ability to absorb carbon (C) through photosynthesis and release it through respiration. The
terrestrial biosphere provided a net sink for ~21% of carbon dioxide emitted by fossil fuel
burning during the 1990-2021 period (1), with the major part occurring in forests (2). This
climate change mitigation role of forests has been widely recognized by the United Nations
Framework Convention on Climate Change (UNFCCC) being part of the periodical national
greenhouse gas (GHG) inventories well as of many NDCs to the Paris Agreement (79% of
the submitted NDCs covers the forest sector under mitigation targets, according to (3)).

Sustainably managed forests offer a dual avenue for GHG mitigation through processes that
are mutually exclusive, namely sequestration and substitution (4). Reducing harvest in
managed forests may yield to a positive impact on the forest C stock in the short to medium
term but would adversely induce a long-term negative impact on the wood-chain value and a
counterproductive effect specifically on carbon sequestration as aging trees exhibit decreased
growth and carbon use efficiency (5). Conversely, the promotion of wood use would lead to
the substitution of energy-intensive materials (e.g., steel or concrete) or fossil fuels, further
compounded with the storage of carbon within harvested wood products (HWPs) (7). Given
the trade-offs among different options (i.e., carbon sequestration, energy substitution, and
material substitution), the most effective mitigation strategy would be the one that optimally
balances and integrates all the mitigation components (8–10).

The acknowledgement of HWPs as integral to climate change mitigation occurs in many
NDCs submitted by Parties under the Paris Agreement (3,11), within which countries
voluntarily set binding GHG accounting obligations and targets to reduce GHG emissions
and increase C-removals (12). The Intergovernmental Panel on Climate Change (IPCC)
provides several approaches for estimating the GHG emissions and removals associated with
HWPs and encourages deviating from the conventional 'instantaneous oxidation' approach
(i.e., carbon in harvested biomass is considered as released into the atmosphere immediately
after the harvesting) towards more accurate methods (13,14). Understanding the carbon
dynamics of HWPs is critical for improving future forest-based climate mitigation strategies.
While large-scale models such as CBM-CFS3 and EFISCEN are commonly used for national
reporting under NDCs and GHG inventories, they primarily focus on forest carbon dynamics
and provide only simplified representations of HWP carbon flows. In contrast, stand-level
wood product models (WPM) offer detailed insights into carbon stocks and fluxes at the local

scale, which are essential for refining forest management practices. The WPM developed in
this study is specifically designed for stand-level applications rather than broader-scale
reporting but can contribute to improving methodological approaches for tracking carbon
storage in HWPs at fine spatial scales.

To accurately project storage and emissions in/from HWPs, models should incorporate all
key components that influence C pools and emissions. However, most WPMs rarely account
for all structural components, with aspects such as recycling, substitution, bucking allocation,
and landfill gas emissions, specifically, often being overlooked (15,16). The practice of
cascading wood products extends their lifespan, consequently delaying the release of GHG
emissions into the atmosphere. A study conducted by Brunet-Navarro et al. using theoretical
simulations to assess the impact of elevating recycling rates on carbon storage within wood
products in the European (EU-28) wood sector and revealed compelling results. Specifically,
an increase in the recycling rate from 10% to 20.9% between 2017 and 2030 was projected to
yield a notable emission saving of nearly 5 $MtCO_2$ (17). The substitution of materials with
high energy requirements for production or the replacement of fossil fuels with less energy-
demanding wood can permanently and cumulatively avoid emissions, provided that there is
no leakage to other cross-sectors or replacement losses (18). For instance, in a case study
comparing two functionally equivalent buildings – one constructed with a wooden frame and
the other with a reinforced concrete frame – the manufacturing process emitted 45% less
carbon in the wooden structure while also requiring less energy (19), which underscores the
importance of considering the substitution effect in the WPMs design. A critical point
regarding product substitution is that most analyses assume a constant displacement factor
value over time, even though this value may decrease due to factors such as evolving
manufacturing methods, improvements in energy efficiency, and the redesign of the energy
mix (18,20). Recent studies examining the fundamental assumptions underlying the
projection of mitigation benefits related to substitution, including the static nature of
displacement factors, have found that this substitution effect has been overestimated by 20%
to 96% (21). It is thus essential that future model implementations account for these potential
variations. From another perspective, the bucking allocation involves the disaggregation of
logs into different HWPs based on quality and dimensional criteria. It is crucial to consider
this process when assessing the effects of management (e.g., rotation, thinning intensity or
interval). For instance, studies that include the bucking allocation process suggest considering
longer rotations for optimizing carbon stock in the forest sector (e.g., see (8)), while those

excluding it recommend shorter rotations (e.g., see (22)). This is because models not incorporating the bucking allocation module use predefined default values to allocate harvested volume to HWPs. In principle, the higher the productivity, the greater the quantity of products – a scenario typically observed in shorter forest rotations. In contrast, when the bucking allocation is accounted for, the optimization of C stock would favor the production of HWPs with a longer lifespan, generally derived from larger tree stems – a scenario typically observed in longer rotations modeling analyses (23). In landfills, the limited availability of oxygen creates unique conditions for the decomposition of major wood polymers. Under anaerobic conditions, microbial activity breaks down a portion of the dissolved organic carbon (DOC) into methane ($CH_4$) and carbon dioxide ($CO_2$). While many models that include landfills primarily estimate C stock, they often overlook the varying global warming potential of different landfill gases. As a result, solely assessing changes in carbon stock within landfills is insufficient for accurately estimating total greenhouse gas (GHG) emissions.

In this paper, we have pioneered the development of an open-source Python-based model, named *TimberTracer (TT)*, to comprehensively account for the various components that directly or indirectly influence C pools and emissions – some of which are typically overlooked by existing forest/vegetation models – and to provide insights into the temporal dynamics of both carbon storage and emissions associated with HWPs. To assess the climate change mitigation potential of the entire forest sector, the model can be seamlessly interface with any forest growth model, whether individual-tree or stand-based level, such, as e.g., GO+ (24) or 3D-CMCC-FEM (25). The main objective of this study is to examine the impact of forest management and wood utilization on the mitigation potential of HWPs. Focusing on the *Pinus nigra* subsp. *laricio* (Poiret) forest located in the experimental Bonis watershed in southern Italy (26), we employ a carbon modeling framework by combining the 3D-CMCC-FEM with *TT*. This integrated framework is used to simulate the evolution over 140-years of the HWP stock, carbon emissions, and the substitution effect under three forest management schemes and four wood-use scenarios, as elaborated in subsequent sections. Furthermore, to determine the influence of dynamic substitution and methane release from landfills on the mitigation potential of various forest management and wood-use scenarios, we use two different model implementations: one that includes methane emissions from landfills and dynamic product substitution, and another that models solely the carbon stock changes in landfills while considering static product substitution.

**2. Methods**

*2.1. Wood products modeling, an overview*

WPMs are implemented diversely based on their scopes and objectives. An integral model

should include –in principle– these six following components: (i) *bucking allocation,* which

involves the disaggregation of stems into different logs designated to the production of

differentiated products according to a set of dimensional and quality criteria typically

established by wood industry professionals. Considering this component as an integral part of

the TT model, rather than relying on a priori allocation factors, is crucial for minimizing

errors resulting from simplification; (ii) *industrial processes,* that involve the transformation

of raw wood into finished or semi-finished products, as well as the recycling or disposal of

products when reaching the end of their use. Those processes are characterized by a set of

allocation parameters either derived from expert knowledge, local surveys, or previous

studies; (iii) *carbon pools,* which refer to the reservoirs of carbon stored in the diverse wood

products currently in use or at disposal sites. HWPs are characterized by an average time in

use, primarily linked to their intended purpose. For instance, construction wood is typically

long-lived compared to pulpwood, given its use in applications that demand high durability

and longevity. In contrast, pulpwood is primarily utilized for paper and pulp production, and

its intended use does not require the same level of longevity; (iv) *product removal,* that refers

to the point in time when products are retired from use. To estimate the product removal rate

(also known as 'retirement rate'), C-retention curves are used. They are based on the

cumulative function of a chosen statistical distribution (e.g., Weibull, uniform, linear, and

normal distributions) defined by one or more of the following parameters, e.g., the time when

50% of the initial C-stock is left (also known as half-life time), the time when 5% of the

initial C-stock is left, the average life, and the maximum retirement rate; (v) *recycling,* that

involves the transformation of HWPs after reaching the end of their use into new products.

This theoretically induces a reduction in the retirement rate, as an additional amount of

products is reinjected after each projection compared to the scenario when recycling is not

considered; and (vi) *substitution,* which refers to the displacement effect resulting from the

use of wood to substitute functionally equivalent energy-intensive materials or fossil fuels.

The major components and processes described above are graphically illustrated in **Figure 1**.

214
215 Figure 1: Lifecycle of HWPs - Illustration depicting key stages from production through
216 utilization to end-of-life and natural decay.

217
*2.2. Model description*

*TimberTracer* (TT), a WPM based on the material flow method, was implemented using
Python as its programming language. The model is specifically tailored for a comprehensive
analysis of wood products, and it encapsulates a robust framework for carbon storage
analysis, enabling users to meticulously evaluate the quantity of carbon stored within diverse
wood products. Furthermore, TT incorporates temporal insights, enabling stakeholders to
scrutinize the evolving patterns of carbon storage and emissions over time. Remarkably, to
assess the climate change mitigation potential for the entire forest sector, TT can seamlessly
interface with theoretically any forest growth model, whether individual-tree or stand-based
level, such, as GO+ (24) or 3D-CMCC-FEM (25).

By incorporating all the previously described components (see previous **section 2.1**), TT
comprehensively accounts for and simulates the temporal dynamics of GHG emissions and
removal across all carbon pools outside the forest, including changes in HWPs and disposal
sites. Furthermore, the model considers the substitution effect and captures the temporal
dynamics of material and energy substitutions. Additionally, TT offers the flexibility of
utilizing both tree- and stand-level inputs, facilitated by its integration of a stand structure
generator, enabling the transition from stand state descriptors to tree state descriptors. The TT

model offers the ability to simulate the entire carbon accounting process using the function
'run_model()'. Additionally, it is designed to be modular, allowing running various
simulations independently, at specific stages of the C accounting process, as described in
**Figure 2**. Hereafter, we explicitly introduce each module, outlining its role and the functions
it encompasses.

Figure 2: Flowchart of the TT model. In green the inputs, in red the outputs, in black the
modules, and in blue the functions within the modules. The number of iterations is equal to
the number of management interventions.
245

246
247

2.3. Model inputs and requirements

The TT model requires a set of input data for its initialization, including: i- stand structural

data (DBH, height, stand density, basal area, bark thickness, sapwood, and heartwood areas);

ii- forest management data (planning horizon, rotation period, rotation number, thinning age,

thinning intensity, thinning nature); iii- industrial process data (product, priority, number, log

length, log diameter, quality criteria, process efficiency); iv- wood use data (lifespan,

recycling rate, reallocation scheme, displacement factors). Furthermore, TT necessitates the

specification of a well-defined set of parameters mainly required by the dendrometer and the

bucking allocation module (for further information on the model parameters and data inputs,

please refer to the table in **Supplementary 3**).

*2.4. Model outputs*

The 'run_model()' function serves as an integrated coordinator, orchestrating the

seamless execution of independently developed modules introduced earlier to generate a

comprehensive output. The model can be run for a planning horizon (PH) that may

encompass multiple rotations (R). The outputs provided include the simulations of carbon

stock in HWPs, the annual and cumulative emissions, the annual and cumulative material and

energy substitution, and the yearly recycling (all expressed in tC ha$^{-1}$).

*2.5. Model structure*

The TT model is designed to be modular. In this section, we will introduce each module

individually, explaining the theory and objectives of each (for further information refer to

**Supplementary 1**).

*2.5.1. The structure generator and thinning performing module*

TT is designed for compatibility with both tree- and stand-level data, providing, to some

degree, flexibility in data input. This capability is realized through the incorporation of a

structure generator module that implements the statistical distribution (e.g., Weibull

distribution) of the diameter at breast height (DBH) within the stand level. It also assigns

trees to different bio-sociological classes of status (i.e., dominant, co-dominant, intermediate,

and overshadow trees) based on their total tree height, as implemented in the

'dendrometer()' function. TT further considers thinning operations, characterized in the

model  by  three  descriptors:  type,  intensity,  and  timing,  implemented  in  the

'perform_thinning()'   function, which renders dendrometry information about each

individual thinned tree.

*2.5.1.1. The structure generator*

The transition from stand state descriptors to tree state descriptors would be feasible if the

stand structure is well understood. The latter is typically likened to a statistical distribution.

There are numerous mathematical formulations for statistical distributions in forestry, with

one of the most employed being the Weibull distribution (28). The probability density

function of a Weibull random variable denoted as $X \sim Weibull(sh, sc, loc)$ is:

$$f(x, sh, sc, loc) = \frac{sh}{sc} \times \left(\frac{x - loc}{sc}\right)^{sh-1} \times e^{-\left(\frac{x-loc}{sc}\right)^{sh}}$$    (Equation1)

Where *f* is the probability density function, *x* is the random variable, *sh* represents the shape,

*sc* denotes the scale, and *loc* indicates the location.

If the location is not provided, but the shape and scale are (2-parameter Weibull distribution),

then the location will be predicted using the following equation:

$$E(x) = loc + sc \times \Gamma\left(1 + \frac{1}{sh}\right)$$    (Equation2)

$$loc = E(x) - sc \times \Gamma\left(1 + \frac{1}{sh}\right)$$    (Equation3)

Where *E(x)* is the mathematical expectancy of *x* and $\Gamma$ is the gamma function.

After fitting the parameters of the Weibull distribution supposed to represent the structure of

the forest stand at different stages of development, the next step is to compute the number of

trees by each diameter class. For this specific purpose, the cumulative distribution function of

the Weibull function is applied to the concerned diameter class following the equation:

$$N(class) = \left[e^{-\left(\frac{lower\ bound - loc}{sc}\right)^{sh}} - e^{-\left(\frac{upper\ bound - loc}{sc}\right)^{sh}}\right] \times N$$    (Equation4)

Where *N* represents stand density (ha$^{-1}$), and the lower bound and upper bound define the

DBH class interval.

*2.5.1.2. The thinning process*

A thinning operation involves removing tree stems to benefit a tree or a group of trees deemed essential to ensure optimal growth conditions (29). It focuses on enhancing wood quality and stand stability. The thinning intervention can be characterized by three elements: (i) the type of cut (from the above, from the bottom, or neutral), which denotes the distribution of removed stems among various diameter categories of standing trees within the stand; (ii) the thinning intensity which expresses the magnitude of the extraction conducted within the stand. It can be quantified by both the number of stems harvested and the implementation rate relative to the before-thinning stand population; (iii) the period, commonly referred to as rotation, is the time interval between two successive thinning events within the stand. It varies depending on the tree species, age, and site conditions (30).

Bio-sociological tree status plays an important role in some thinning concepts, for example, for the selection of thinning trees in thinning from above and below (31). A simplified classification groups trees into four categories: i- dominant trees; ii- co-dominant trees; iii- intermediate trees; and iv- overshadow trees. This classification consists of the definition of the position of each tree in terms of its height by reference to the other trees of the stand. As part of the process, the dominant height of the plot ($h_{95\%}$) as well as the height to the base of the crown (hc) are calculated. The classification of the trees into a scale is performed following the rules presented in the **Table 1**.

Table 1: Bio-sociological status criteria based on the tree height.

| Criteria | Bio-sociological status |
|---|---|
| $hi \geq h_{95\%}$ | Dominant tree (1) |
| $\dfrac{h_{95\%} + hc}{2} \leq hi < h_{95\%}$ | Co-dominant tree (2) |
| $hc \leq hi < \dfrac{h_{95\%} + hc}{2}$ | Intermediate tree (3) |
| $hi < hc$ | Overshadow tree (4) |

The thinning operation follows the approach implemented by (32). For thinning from below and thinning from above, trees belonging to a specific bio-sociological class are prioritized

for each thinning type. In the case of neutral thinning, trees are harvested without

consideration for their bio-sociological status. Further details are provided in the following.

Thinning from below (4+3) => 2

The process consists of removing trees belonging to the dominated bio-sociological sub-

groups. The process of removal is parallel in 4+3 (Overshadow and Intermediate). If the

removal amount is not reached by 4+3, the process continues sequentially in sub-group 2

until reaching the required number of trees satisfying the initial condition.

Thinning from above (1+2) => 3

The process consists of removing trees belonging to the dominating bio-sociological sub-

groups. The process of removal is parallel in 1+2 (Dominant and Co-dominant). If the

removal amount is not reached by 1+2, the process continues sequentially in sub-group 3

until reaching the required number of trees satisfying the initial condition.

Neutral thinning (1+2+3+4)

The process consists of removing trees regardless of the bio-sociological sub-group to which

they belong. The process is parallel in 1+2+3+4 and continues until satisfying the required

removal amount.

2.5.2. *The bucking allocation module*

TT allocates logs from thinned trees to HWPs, considering determinant factors such as stem

log diameter and quality. The qualitative grading of logs involves several criteria, with the

proportion of knotted wood and sapwood-to-heartwood ratio being among the most

commonly used in the literature (33–35). The bucking allocation is practically implemented

within the model through two sequential steps. The first step involves dressing the stem

profile of each individual tree using the 'taper_equation()' function which renders the

diameter over bark (dob) at any point along the stem. Simultaneously, the knotted wood

profile is dressed using the 'knotted_wood_profile()' function while the sapwood and

heartwood profiles are established with the 'sapwood_profile()' function. The second

step consists of combining the tree stem profile (including taper, knotted wood, sapwood, and

heartwood) with the bucking allocation criteria defined by wood industry professionals to

disaggregate trees into different logs. This entire process is implemented in the

'bucking_allocation()' function (please refer to **Supplementary 2** for more

information on the bucking allocation criteria).

*2.5.2.1. Stem profile generator*

To achieve a precise stem profile dressing, the TT uses a comprehensive set of equations,

which will be thoroughly described in this section (see **Figure 3** for a graphical

representation of the stem profile).

The taper profile refers to the degree to which a tree's stem diameter decreases as a function

of height above ground. Taper is often represented by mathematical functions fitted to

empirical data, called taper equations. One such function, attributed to (36) and used by

default in the model is:

$y(z) = b_1 z + b_2 z + b_3(z - a_1)^2 I_1 + b_4(z - a_2)^2 I_2$ (Equation 5)

where $y = (\frac{dx}{dbh})^2$ ; dx = is the upper stem diameter over bark (dob) at a given height h of the

tree, $z = 1 - \frac{h}{ht}$ = the complement of the relative height with ht being the tree total height; $a_1$

and $a_2$ = join points to be estimated from the data, $I_k = 1$ if $z > a_i$ and 0 otherwise, $k = 1,2$, $b_p$'s

= regression coefficients with, $p = 1, 2, 3, 4$.

The crown base height ($h_c$) refers to the level of insertion of the last branch of the crown

within the stem, it is generally predicted from the total height using an allometric equation.

One such equation is the power function expressed as follows:

$h_c = ah_t^c$ (Equation 6)

where *a* and *b* correspond respectively to the amplitude and the exponent of the relation.

The DBH of a tree could be also predicted from its total height. One such function is the

power function expressed as follows:

$DBH = alpha \times h_t^{beta}$ (Equation

7)

where *alpha* and *beta* correspond respectively to the amplitude and the exponent of the

relation.

In tree analysis, a crucial step involves shaping the crown base profile to differentiate knotted
from intact wood. To establish this profile, a combination of the three equations (5-7) is
utilized. In practice, the approach entails reconstructing the historical crown base height
limits and considering that the area from the curve towards the bark represents the knotted
wood, while the area from the curve towards the pith represents the intact wood.

409                                                                                          (Equation 8)

410                                                                                          (Equation 9)

where    represents the complement to the relative height at the level of the crown base and
$d_c$ refers the diameter of the intact wood.

The sapwood profile is determined based on the simplified assumption that the sapwood
width and bark thickness remain constant within the tree level (37). The width of knotted
wood, which naturally varies within the tree level, is calculated as the difference between the
diameter at a specific height obtained from the taper profile and the sum of the sapwood
width and bark thickness.

420
421                     Figure 3: Graphical representation of stem longitudinal profile

422
*2.5.2.2. Stem disaggregation*
Stems are disaggregated into different logs based on specific criteria, typically established by
wood industry professionals. These criteria, tailored to each species, include both dimensions
and quality considerations, and they are organized hierarchically. To elaborate, the model

initially checks if the stem aligns with the criteria for producing a designated log intended for

a specific product. If this is not the case or if the maximum desired number of this specific

log has been reached, the model then advances to the next HWP based on a hierarchy defined

by the user. In TT, log dimensions are characterized by the length and small end diameter of

the log, while log quality is assessed through ratios of knotted wood ($\varnothing_{KW}$) to heartwood

($\varnothing_{HW}$) and knotted wood to small end diameter ($\varnothing_{SE}$). The model checks these criteria (e.g.,

$\varnothing_{SE} \geq 25$ cm, $(\varnothing_{KW} / \varnothing_{HW})^2 \leq 13\%$, and $\varnothing_{KW}/ \varnothing_{SE} \leq 30\%$) by implementing a bisection

algorithm that automatically performs the search for the corresponding height validating the

given criteria.

*2.5.3. The processor module*

Logs are processed to match their intended products, employing the standard industry method

for each type of product. The efficiency rate of this industrial transformation, a theoretical

measure, depends on how the processing is done, and this varies based on the targeted

product. In *TT*, the production of HWPs is calculated using the efficiency rate which is

product-specific. Subsequently, any process losses (i.e., 1 – efficiency) are redistributed

among other products according to a scheme defined by the user. This process is

implemented in the 'processor()' function.

*2.5.4. The stock and flow module*

TT simulates the evolution of carbon in HWPs and disposal sites including both mill and

landfill sites throughout the planning horizon (PH) using the

'total_stock_calculator()' function. After each annual projection, a portion of the

carbon in HWPs undergoes retirement based on product-specific decay function (refer to

'compute_D()' in the model). Subsequently, a fraction of the retirement is recycled and

reinjected into the HWPs carbon pool (refer to 'compute_R()' in the TT model), another

portion is directed to firewood, while the remaining part is sent to landfills. Furthermore, TT

simulates the evolution of the total emissions resulting from the firewood combustion and the

decay of carbon pool in disposal sites, accounted for as an instantaneous oxidation, using the

'total_emission_calculator()' function.

In TT, the product removal rate (i.e., retirement rate) is determined using the cumulative

distribution function (CDF) of a normal distribution, which is defined by its mean and

standard deviation. The mean represents the average lifespan of a product, while the standard

deviation reflects the change in the dynamic retirement, typically expressed as a fraction of

the average lifespan (e.g., a fraction of 1/3 as used in (17)). In the following, the CDF

formulation is presented.

$CDF(x;\ lifespan, lifespan \times \text{fraction}) = \frac{1}{2}\left[1 + \text{erf}\left(\frac{x - lifespan}{lifespan\ \times\ fraction\ \times\ \sqrt{2}}\right)\right]$        (Equation

10)

$\text{erf}(x) = \frac{2}{\sqrt{\pi}} \int_0^x e^{-t^2} dt$        (Equation

11)

where CDF is the cumulative distribution function and erf is the error function.

Specifically, emissions from landfills are estimated by TT using two different methods. The

first approach assumes that wood decomposition in landfills occurs under aerobic conditions,

with $CO_2$ as the only emitted gas (as in Equations 10 and 11). Although this approach may

underestimate the warming potential of emissions, it allows for comparison with alternative

methods. The second approach is a theoretical first-order decay (FOD) model introduced in

the IPCC guidelines (38), which provides yearly estimates of $CH_4$ and $CO_2$ emissions. The

following equations present the generation of $CH_4$ and $CO_2$ in year $t$ from landfilled wood in

a specific year $x$.

$Q_{t,x,CH4} = k \times R_x \times L_0 \times e^{-k(t-x)} \times GWP \times C1\ ;$        (Equation

12)

$Q_{t,x,CO2} = k \times R_x \times L_0 \times e^{-k(t-x)} \times (1 - f)/f \times C2$        (Equation

13)

where $Q_{t,x,CH4}$ and $Q_{t,x,CO2}$ are, respectively, the amounts of methane and carbon dioxide

generated in year t (in eq tC) by landfilled wood $R_x$ (t); $k = \frac{\log 2}{t0.5}$ represents the methane

generation rate constant ($yr^{-1}$); t0.5 is the half-life period of the degradation process; $L_0$ is the

methane generation potential ($tCH_4$ per tonne of landfilled wood); $x$ is the year of wood input,

and $t$ is the current year; GWP = 28 is the global warming potential of $CH_4$ (in eq $CO_2$), C1 =

12/44 and C2 = 12/16 are the constants used to convert $tCO_2$ to tC and $tCH_4$ to tC,

respectively; and f represents the fraction of C released as $CH_4$.

*2.5.5. The substitution module*

TT simulates the climate change mitigation effect in terms of avoided emissions resulting

from the substitution of fossil fuels by bioenergy and energy-intensive materials by wood

products. The carbon mitigation potential is closely linked to the specific solution being

substituted and is calculated using the displacement factor (DF in $tCO_2$-eq $m^{-3}$), a measure of

the amount of GHG emissions avoided when wood is used instead of the current solution

(39). The computation of the substitution is perfomed separately for material and energy

substituiton using the '`material_sub()`' and '`energy_sub()`' functions, respectively.

The substitution is estimated using the following equation:

$substitution = wood\ volume \times DF \times k$                                    (Equation

14)

where k $= \frac{12}{44}$ is the constant used to convert $tCO_2$ to tC

**2.6. Case study**

*2.6.1. Study area*

The Bonis experimental watershed located in the mountain area of Sila Greca (39°28′49″ N,

16°32′07″ E; from 975 to 1330 m a.s.l.) in the Calabria region, southern Italy was chosen as

the study area in this work (26,40). Almost 93% of its total area is covered by forests,

dominated by ~60 years old Laricio pine stands. The stands were planted in 1958 with an

average density of 2425 sapling $ha^{-1}$ (41) and underwent a thinning treatment in 1993 with

basal area (BA) removal of 25 % (42). The forest was equipped with 14 circular survey plots,

each with a radius of 12 meters, for monitoring since 1993, and they were surveyed until late

2016.

516
517 Figure 4: Map of the geographical situation of the Bonis watershed (right sub-figure) inside
518 the Italian territory (left sub-figure).

519
*2.6.2. Scenarios building*

For the management scenarios, we tested three options reflecting different goals. All the
options were simulated to take place after 2016, which is the last year of plot surveying. The
first option simulates light thinning intensity, corresponding to a 28% reduction of Basal Area
(BA) at an interval of 15 years, aiming to reproduce silvicultural interventions favoring
natural forest dynamics. An additional production-oriented option, known as clearcut,
simulates a complete harvest followed by replanting 80 years after the establishment of the
plantation. A third option, representing a more sustainable alternative to clearcutting,
simulates a shelterwood. This involves two light thinnings (20% reduction of BA) with a 10-
year interval, followed by seed-favoring cut after 80 years from the original planting (80%
reduction in BA) and removal cut 10 years later.

For the wood-use scenarios, four different options were developed. The 'Baseline scenario'
('Business as Usual', BAU) kept the recycling rate and products lifespan values constant. In
the 'Longevity scenario', the lifetime of products was increased by 10 %. In the 'Reuse
scenario', the recycling rate of products was increased by 10%. In the 'Sustainability
scenario', both the lifetime of products and the recycling rate were increased by 10% (See
**Supplementary 4** for further details).

Table 2: Forest management and wood use scenarios

| Group | Name | Features |
|---|---|---|
| Forest management | Selective thinning | 28% reduction of BA at an interval of 15 years |
| | Clearcut | Complete harvest followed by replanting at 80 years. |
| | Shelterwood | Two light thinning (20% reduction of BA) with 10-year interval, followed by seed-favoring after 80 years (80% of BA) and removal cut 10 years later |
| Wood use | BAU | Constant recycling rate and product lifespan |
| | Longevity | 10% increase in product lifespan |
| | Reuse | 10% increase in recycling rate |
| | Sustainability | 10% increase in both product lifespan and recycling rate |

540
541
*2.6.3. Modeling framework and the required data*

The *TT*, a WPM that tracks carbon in HWPs which was extensively introduced in this paper,

was coupled with 3D-CMCC-FEM ('*Three Dimensional – Coupled Model Carbon Cycle –*

*Forest Ecosystem Module*' v.5.6 BGC (25,26,43–46), a stand-level, biogeochemical,

biophysical, process-based model that annually provides data on the forest state (e.g., density,

DBH, BA, and total height). The integration of the two models was considered as the

modeling framework for achieving the objectives of this study.

The 3D-CMCC-FEM model requires a set of input data for its initialization which includes:

(i) model species parameters set which was derived from a recent work that validated the

model for Laricio pine stand in the Bonis watershed (40); (ii) daily time series of

meteorological fields (e.g. incoming shortwave radiation, maximum and minimum

temperature, relative humidity or vapor pressure deficit, precipitation). For the period from

1958 until 1976 climate data was derived using the mountain microclimate simulation model

MT-CLIM (47) forced by temperature and precipitation series measured by the nearby Cecita

meteorological station (39°23′51″ N, 16°33′24″ E; 1180 m a.s.l.), while for the period from

1976 to 2005, gridded climate time series were used. The latter derived from bias-corrected

outputs of the regional climate model COSMO-CLM (48) at around ~8 km horizontal

resolution (49,50), and driven by the general circulation model (GCM) CMCC-CM (51)

under historical GHG forcing (40). Additionally, measured values of global annual

atmospheric $CO_2$ concentration were derived from (52) and used for the period from 1958 to

2005. A random sampling of both climate and $CO_2$ data within the period between 1990 and

2005 was performed as representative of an additional synthetic period of 90 years assuming

unchanging climate and atmospheric $CO_2$ conditions, to simulate in total 140 years; (iii) stand

initialization data for the year 1958 which included stand density: 2425 saplings $ha^{-1}$, DBH: 1

cm, height: 1.3 m, age: 4 years, elevation: 1131 m a.s.l., soil texture (clay: 20 %; silt: 26 %,

sand: 54 %) and depth: 100 cm (41,53,54). (40) provides an extensive description of model

validation (before and after thinning) at the Bonis site for both carbon fluxes and stocks such

as DBH, stand density and gross primary productivity (GPP).

In addition, *TT* also requires a set of inputs and parameters necessary for its initialization: i-

the bucking allocation criteria, developed to segregate solid-wood products based on quality

requirements for specific end uses across various wood products, are standardized and can be

applied irrespective of log source and sawmill producer (55). Potential wood products from

Laricio pine stems were inventoried by consulting five sawmill industry experts, and the

amalgamation of all possible products was retained for this study. Furthermore, the bucking

criteria used in this study are those commonly found in the literature (56) (Please refer to

Table 1 in **Supplementary 2**); ii- the transformation efficiency of each log category, a

geometric yield as well as the loss reallocation were defined with the assistance of sawmill

industry professionals (please refer to Tables 2 and 4 in **Supplementary 2**),; iii- for the

recycling rate we suggest that the recycling rate of waste wood products was constant at 10%

during the planning horizon while lifespan of each product was reviewed from published

studies (57–63); iv- displacement factors for the substitution were derived from the literature

(39,64) (Please refer to Table 5 in **Supplementary 2**); v- TT model dendrometry parameters,

including stand structure, crown base height equation, and diameter-to-height parameters,

were fitted to the forest data collected from the experimental plots of the Bonis watershed

forest, while the taper model and the species density were derived from the literature (65,66).

Additionally to the first implementation which assumes static displacement factor values

overtime, we dynamically calculated these factors for each product category in this study,

following the approach outlined in (21). Specifically, the substitution factor value was

assumed to proportionally follow the dynamic of gross anthropogenic $CO_2$ emissions. In line

with the Paris Agreement's ambition of reaching net-zero emissions around mid-century, (67)

estimated the evolution of these gross anthropogenic $CO_2$ emissions. We used this projection

to dynamically update the substitution factors throughout the entire 140-year planning
horizon.
598

599
600  Figure 5: carbon modeling framework coupling a forest process-based model (3D-CMCC-
601  FEM) and TT a harvested-wood product model. DBH is the stand mean diameter at breast
602  height, N is the stand density, BA is the stand basal area, H is the stand mean tree height, SA
603  is the sapwood area of the mean tree, HA is the heartwood area of the mean tree, and BT is
604  the bark thickness of the mean tree.

605
**3. Results**

*3.1. Introduction*

In this study, we assess the carbon dynamics within the harvested wood product (HWP) pool,
including carbon stock changes, emissions, and the effects of material and fossil fuel
substitution. We employ the production approach, which tracks the transfer of carbon from
forests to HWPs and covers the wood lifecycle from forest harvest to end-of-life. Our
analysis focuses exclusively on the C dynamics within the HWP pool, without evaluating
changes in forest carbon stocks. This approach is versatile, applicable to various system
boundaries, including specific projects and harvest activities of small sizes, including our
study scope.

In this simulation, the overall C-balance, calculated as the difference between carbon stored
in HWPs, the avoided emissions as effect of the substitution of material and fossil fuel, and
carbon emissions from HWPs end-life, was estimated for three different forest management
schemes and four wood use scenarios providing insights into the overall carbon balance at
each point in time throughout the projection period. These estimations were derived from the
modeling exercise, relying on both silvicultural itinerary and product utilization over the use
and end-use periods. To analyze the effects of various wood use scenarios on the overall C-

balance over time, we compared each scenario with the business-as-usual (BAU) scenario as
benchmark. Furthermore, to assess the impact of different forest management scenarios on
the overall C-balance over time, we conducted individual comparisons while maintaining the
same wood-use scenario each time. Additionally, the net C-balance, calculated as the
difference between the carbon stored in HWPs and C-emissions at the end of their life-cycle,
was estimated across the three forest management schemes and four wood-use options. This
concept is significant because it provides a baseline against which the substitution effect can
be measured and can orient comparative studies where substitution is irrelevant. When
estimated dynamically, it offers insights into the duration of a positive C-balance, which is
crucial for evaluating the effectiveness of HWPs in mitigating climate change. A long-lasting
positive C-balance indicates that carbon is sequestered from the atmosphere and stored in
HWPs for extended periods, thereby delaying or reducing the impact of C-emissions on
global warming. Finally, to assess the impact of considering $CH_4$ release from landfill sites
and the dynamic updating of substitution factors, we evaluated the effects of incorporating
these elements. In this work we use positive sign to represent C-removals while negative one
is C-emissions.
639

641
Figure 6: Clearcut management among different wood-use scenarios is demonstrated to
showcase variations in Harvested Wood Products (HWPs) C-stock, material and energy
substitutions, C-emissions, and the **overall C-balance** (tC ha$^{-1}$). Blue points represent the
equalization between HWPs and emissions, while black points indicate neutrality of the
overall C-balance. The red dashed line corresponds to the overall C-balance neutrality.
Negative values of the overall C-balance indicate positive emissions, while positive values
indicate positive C-storage. The red points refer to the value of each variable at the term of
the simulation.

651
Figure 7: Selective **thinning management** among different wood-use scenarios is
demonstrated to showcase variations in Harvested Wood Products (HWPs) C-stock, material
and energy substitutions, C-emissions, and the **overall C-balance** (tC ha$^{-1}$). Blue points
represent the equalization between HWPs and emissions. The red dashed line corresponds to
overall C-balance neutrality. Negative values of the overall C-balance indicate positive
emissions, while positive values indicate positive C-storage. The red points refer to the value
of each variable at the term of the simulation.

659
660

661
Figure 8: Shelterwood management among different wood-use scenarios is demonstrated to
showcase variations in Harvested Wood Products (HWPs) C-stock, material and energy
substitutions, C-emissions, and the **overall C-balance** (tC ha$^{-1}$). Blue points represent the
equalization between HWPs and emissions, while black points indicate the neutrality of the
overall C-balance. The red dashed line corresponds to the overall C-balance neutrality.
Negative values of the overall C-balance indicate positive emissions, while positive values
indicate positive C-storage. The red points refer to the value of each variable at the term of
the simulation.

670
*3.2. Overall carbon balance*

The application of wood-use scenarios had distinct effects across different forest management

scenarios, yet recurrent patterns can be identified. Among the various forest management

scenarios, the sustainability scenario consistently exhibited the lowest C-emissions. To

elaborate, over the planning horizon, C-emissions decreased by 69%, 267%, and 40%,

respectively, for clearcut, selective thinning, and shelterwood managements compared to the

BAU scenario (i.e., –6.1, 1.34, –12.91 tC ha$^{-1}$). Comparable effects were observed with the

longevity scenario, resulting in a reduction of C-emissions by 60%, 254%, and 35%,

respectively, for clearcut, selective thinning, and shelterwood managements compared to

BAU. The reuse scenario induced the smallest decrease in C-emissions, at 11%, 44%, and

4.6%, respectively, for clearcut, selective thinning, and shelterwood managements compared

to BAU (see **Table 3**).

In the context of forest management, selective thinning exhibited pronounced superiority over

alternative management approaches in all four wood-use scenarios. Under this management

strategy, C-emissions were intensively reduced compared to the BAU scenario for clearcut

and shelterwood management, respectively. Meanwhile, clearcut and shelterwood

management demonstrated nearly equivalent effects across the three wood-use scenarios (see

**Table 3**).

The overall C-balance exhibits diverse patterns based on the applied forest management.

Specifically, the results consistently demonstrate a positive balance for the selective thinning

management approach throughout the entire planning horizon. However, the clearcut

management reached equilibrium at either year 64 or 65 under BAU and the reuse scenarios,

or under the longevity and sustainability scenarios. The balance remained negative from that

point until a significant harvesting event at year 84. Subsequently, a new equilibrium was

achieved at either year 134 or 138 under BAU and reuse scenarios, or under longevity and

sustainability scenarios. The overall balance remained negative thereafter. In the case of

shelterwood management, the balance consistently remained positive until a first equilibrium

was reached at either year 129, 130, or 133 under BAU, or under the reuse scenario, or under

the longevity and sustainability scenarios. Afterward, the balance remained negative (See

**Figures 5-7**).

Table 3: The overall carbon balance, encompassing removals, emissions, and substitution
effects from harvested wood products (HWPs) due to wood use and management scenarios, is
expressed in tC ha$^{-1}$. Negative sign indicate net C-emissions, whereas positive sign indicates
net C-removals.

| Management scenario | Wood use scenario | | | |
|---|---|---|---|---|
| | BAU | Reuse | Longevity | Sustainability |
| Clearcut | –6.1 | –5.43 | –2.46 | –1.88 |
| Selective thinning | 1.34 | 1.93 | 4.74 | 4.92 |

| | | | | |
|---|---|---|---|---|
| Shelterwood | −12.91 | −12.32 | −8.39 | −7.76 |

### 3.3. Material and energy substitution

Regarding material substitution, we identified a distinct pattern marked by successive phases of a sharp pulse of increase coinciding with thinning or harvesting operations, followed by a positive pseudo plateau. Among the forest management scenarios, the reuse scenario consistently showed the highest material substitution effect averaging 0.62% more than the BAU scenario (i.e., 25.59, 27.12, and 30.46 $tC\ ha^{-1}$; respectively for clearcut, selective thinning and shelterwood). In contrast, the longevity scenario consistently exhibited the lowest potential (averaging 0.53% less than the BAU) while the sustainability scenario demonstrated a comparable effect to the BAU scenario.

For energy substitution, we observed a pattern characterized by successive phases of a moderately intense pulse of increase coinciding with thinning or harvesting operations, followed by a positive slope. Among the management scenarios, the BAU scenario (i.e., 22.10, 22.27, and 28.51 $tC\ ha^{-1}$; respectively for clearcut, selective thinning and shelterwood) consistently exhibited the highest energy substitution effect. In contrast, the sustainability consistently showed the lowest energy substitution effect (averaging 5.25% less than BAU), followed by the longevity scenario (averaging 4.41% less than BAU) and finally the reuse scenario (averaging 0.57% less than BAU).

### 3.4. Net carbon balance

Regarding the carbon emissions from firewood and disposal sites, we observed a pattern characterized by a sustained positive slope interrupted by a sharp pulse of increase coinciding with thinning or harvesting operations. Among the management scenarios, the BAU scenario (i.e., –63.90, –67.77, and –85.94 tC ha$^{-1}$; respectively for clearcut, selective thinning and shelterwood) consistently exhibited the highest C-emissions. In contrast, the sustainability scenario consistently showed the lowest level of emissions (averaging 4.17% less than BAU), followed by the longevity scenario (at 3.64% less than BAU), and finally the reuse scenario (at 0.48% less than BAU).

Regarding the carbon stock of HWPs, it assumes different shapes depending on the type of applied forest management. However, a commonly observed pattern is characterized by a sustained negative slope interrupted by a sharp pulse of increase coinciding with thinning or harvesting operations. Among the management scenarios, the BAU scenario consistently

exhibited the lowest HWPs C-stock (i.e., 10.11, 19.72, and 14.06 $tC\ ha^{-1}$ for clearcut, selective thinning, and shelterwood, respectively). In contrast, the sustainability scenario consistently showed the highest level of C-stock in HWPs (averaging 20% more than BAU), followed by the longevity scenario (at 18.2% more than the BAU), and finally, the reuse scenario (at 1.80% more than BAU).

The duration of positive net C-balance differs significantly across various forest management strategies and slightly among different wood-use scenarios (see **Table 4**). In the case of selective thinning, five positive periods, measured in years, can be observed, with their durations decreasing over time: [20, 6, 6, 3, 1] or [21, 7, 7, 4, 2], respectively, for BAU and the reuse scenarios or the longevity and sustainability scenarios. In the case of clearcut management, two positive periods can be observed with their durations slightly increasing over time: [20, 24] or [21, 25], respectively, for BAU and the reuse scenario or the longevity and sustainability scenarios. Regarding the shelterwood management, four positive periods can be observed with their durations decreasing and then increasing overtime: [20, 3, 3, 19] or [21, 3, 3, 20], respectively, for BAU and the reuse scenario or the longevity and sustainably scenarios.

Table 4: Duration of positive net C-balance among various forest management and wood-use scenarios (in years).

| Management scenario | Wood use scenario | | | |
|---|---|---|---|---|
| | BAU | Reuse | Longevity | Sustainability |
| Clearcut | 36 | 36 | 41 | 41 |
| Selective thinning | 44 | 44 | 46 | 46 |
| shelterwood | 45 | 45 | 47 | 47 |

**3.5. Implementation of dynamic substitution and methane release from landfill**

Accounting for dynamic substitution and methane release from landfills had a significant impact on the overall C-balance of harvested wood products (HWPs) across all forest management and wood-use scenarios, leading to a substantial decrease in this balance, ranging from 5- to 39-fold compared to the original projections (see **Figure 9**). Moreover, under this new implementation, all combinations of forest management and wood-use scenarios resulted in a negative overall C-balance, including selective thinning, which had presented a positive overall C-balance under the original implementation (see **Figure 9**).

In contrast, this new implementation had no effect on the ranking of different forest

management scenarios, as selective thinning consistently demonstrated superiority over

alternative approaches across all wood-use scenarios, followed by clearcut management and,

finally, shelterwood management (see **Figure 9**). Similarly, the implementation did not alter

the ranking of overall wood-use scenarios, with the reuse scenario showing the minimal

climate mitigation potential across all management scenarios, while both the longevity and

sustainability scenarios made comparable and higher contributions to C-emissions reduction

compared to the BAU scenario (see **Figure 9**).

Figure 9: Comparison of the overall C-balance across forest management and wood use
scenarios using two implementations: original (no methane ($CH_4$) release, static substitution)
and alternative (methane ($CH_4$) release, dynamic substitution). Negative values indicate net
C-emissions.

In the following subsections (**4.5.1** and **4.5.2**), the results related to the impacts of dynamic

substitution and methane release will be presented individually, respectively.

3.5.1. Effect of dynamic substitution

The implementation of dynamic updating of displacement factors, proportional to the

reduction in global emissions consistent with the Paris Agreement, led to a decrease in

displacement factors after reaching their maximum (see Figure A.1). This, in turn, resulted in

a significant reduction in the substitution effect across all forest management and wood-use

scenarios compared to the initial projections that utilized static displacement factors. By the

planning horizon (year 140), cumulative material substitution in the dynamic scenario was

reduced by 95% to 96% compared to the static substitution scenario, and cumulative energy

substitution in the dynamic scenario was reduced by 95% compared to the static substitution

scenario (see **Figure 10**).

796
797  Figure 10: Comparison of the cumulative sum of material and energy substitutions resulting
798  from the use of a particular forest management and wood-use scenario using two
799  implementations: the original (static substitution) and the alternative (dynamic substitution)
800  (in tC ha$^{-1}$). The shaded portions of the bars represent the relative contribution of material
801  substitution, while the solid portions represent the relative contribution of energy substitution.

802
3.6.1. Effect of methane release from landfills

The implementation of methane ($CH_4$) release from landfills under anaerobic conditions,

following the IPCC's theoretical first-order methodology, resulted in a considerable increase

in cumulative emissions across all forest management and wood-use scenarios compared to

the initial simulations, which only considered wood decomposition in landfills under aerobic

conditions. Consequently, by the planning horizon (i.e., year 140), cumulative emissions in

the new implementation increased by 9.4% to 11% compared to the original implementation
(see **Figure 11**).

811
Figure 11: Comparison of the cumulative emissions resulting from the use of various forest
management and wood-use scenarios under two implementations: the original (no methane
($CH_4$) release) and the alternative (with methane ($CH_4$) release) (in tC ha$^{-1}$).

**4. Discussions**
In this study, we presented the underlying theory and principles of TT, a dynamic model of
the carbon balance in HWPs. TT has been coupled with 3D-CMCC-FEM with the aim to
investigate the effect of different forest management and wood use options on the overall C-
balance of HWPs on a real case. Assuming flexibility in both wood utilization and forest
management practices, this study case demonstrates that the overall C-balance can be
increased by giving preference to multiple light, non-distant cuttings over a few distant
intensive cuttings and promoting wood use for material purposes, including the increase of
recycling and products lifetime. These findings align closely with the principles of
continuous cover forestry and the circular economy approach, emphasizing the role of
sustainable resource management in climate mitigation. Additionally, to evaluate the impact
of methane emissions from landfills under anaerobic conditions and to account for the
dynamic nature of displacement factors, we implemented an alternative model configuration.
This approach revealed that considering $CH_4$ emissions significantly increased total
emissions, while applying dynamic displacement factors substantially reduced the

substitution effect. However, these findings did not alter the relative ranking of forest
management and wood-use strategies in terms of their climate change mitigation potential.

Recent researches increasingly questions the static nature of substitution factors, advocating
for a dynamic approach that accounts for technological advancements, improved resource
efficiency, enhanced recycling processes, and better end-of-life management of products
(e.g., (18,20)). The substantial reduction in substitution effects observed in this study
highlights the sensitivity of carbon accounting to displacement factor assumptions,
reinforcing the need for adaptive modeling approaches. Consistent with our results, (21)
demonstrated that applying dynamic displacement factors leads to a projected 33% reduction
in the mitigation effect of wood product substitution in Europe by 2030, and a 96% reduction
by 2100, compared to predictions using fixed factors. Similarly, (18) conducted simulations
showing that product substitution would saturate if displacement factors reached zero within
100 years of the simulation's start, resulting in an 89% reduction in cumulative substitution
effects within 300 years. These findings emphasize the need for continuous reassessment of
displacement factors to ensure an accurate representation of substitution benefits.

Methane emissions from landfills are reported under the waste sector according to IPCC
guidelines for reporting emissions and sinks, which is why the methane effect is often
excluded from the calculation of HWP contributions by most WPMs. However, accounting
for methane emissions is crucial for developing practices that enhance the contribution of
HWPs, especially given methane's high global warming potential. Even a minor
underestimation of $CH_4$ can lead to a significant and erroneous overestimation of the
potential of various mitigation projects. In this study, including $CH_4$ release from landfills
due to wood decomposition under anaerobic conditions led to a substantial increase in
emissions (in CO2 equivalents), ranging from 9.4% to 11% compared to the original
implementation where methane emissions were not considered. Consistent with our results,
(68) demonstrated that accounting for the global warming potential of methane emissions
reduced the estimated contribution of U.S. forests and HWPs to GHG mitigation for the year
2005 by more than half (in C-equivalent). However, it should be noted that the inclusion of
landfill gas management infrastructure or the adoption of strategies, such as the ongoing EU
initiative aiming to limit municipal waste landfilling to below 10% by 2035 as part of the
broader goal of achieving climate neutrality by 2050, may substantially reduce $CH_4$
emissions. As such, WPMs should account for these considerations (69).

The outcomes of this study are significantly enhanced by the inclusion of the bucking
allocation module in the TT model, which considers the dimensions of logs for the allocation
of wood to HWPs. This is crucial because various products have distinct use and post-use
properties, leading to diverse temporal dynamics, and a pre-established allocation may not
accurately reflect reality. The role of the bucking allocation was evident across all
management options. Each successive intervention, characterized by a higher mean DBH of
the harvested stems than the precedent due to the stand's growth dynamic, resulted in the
newly HWPs stock exhibiting a slower retirement dynamic than the precedent due to the
higher portion of long-lived products in the most recent one. For instance, in the case of
clearcut management, two interventions were made at the years 39 and 84, yielding
retirement rates of ~2% per year and 1.5% per year, respectively. The analysis of the bucking
allocation in both the initial and subsequent harvests, reveals that, from the first harvest, the
production was limited to short- and medium-lived HWPs such as paper and particle, while
novel categories of long-lived products were introduced in the second harvest, exemplified by
furniture and sawing, which justify the decrease in the retirement rate of the HWPs stock (see
**Table A.1**).
881
These multiple findings align with prior studies in this area. In a theoretical exercise
evaluating the mitigation potential of wood product use in the European forest sector, (17)
demonstrated that increasing each component—whether recycling rate or lifespan—
individually by approximately 20% could result in an 8.9% increase in C-removal by 2030 by
reference to the 2017 BAU scenario. Furthermore, the study states that a simultaneous 20%
increase in both average product lifespan and recycling rate could yield a 17.3% increase in
carbon removal by 2030. Another recent study by (70) explored the  C-storage potential of
HWPs in four EU countries, projecting outcomes from 2020 to 2050 across six alternative
scenarios. The findings suggest that prioritizing wood-use for material purposes, while
maintaining a constant harvest, yields the highest mitigation benefits in the short to medium
term. Moreover, in a continental study (EU-28) focusing on assessing the consequences of
implementing policy choices on GHG emissions and removals, it was revealed that the
adoption of the cascading scenario of HWPs led to a slight increase in the net balance
between emissions and removals from/by HWPs. The balance was simulated to rise from
approximately 34 Mt $CO_2$-eq in the base period around 2010 to just under 40 Mt $CO_2$-eq in
2030, as documented by (71). In another study aiming to investigate the potential of
cascading use of woody biomass in the EU, it was found that GHG emissions could be

reduced by 35 MtCO$_2$-eq year$^{-1}$ as a result of implementing the maximum technical potential

to increase recycling of waste wood and paper flows (72).

From another perspective, the significance of management has been underscored in numerous

studies. In (73), the application of five silvicultural itineraries, derived from translating five

alternative management objectives for an even-aged forest, resulted in significantly different

outcomes regarding the carbon storage by HWPs. In another study, (74) concluded that the

method of harvesting is crucial showing further that a regular removal of timber from forest

in a way that maintains a continuous canopy is likely to give substantially higher sustained

yields and amount of carbon sequestration than periodical clear-felling because of the higher

photosynthetic area. The same study suggests that if the objective was to maximize timber

volume yield, the optimal management system would be the regular thinning of forest. A

physiological explanation of this could be that the continuous canopy cover with a

moderately high leaf area index ($\sim 4$ m$^2$ m$^{-2}$) provides high light interception and, at the same

time, net primary production (75). Regular thinning ensures that the forest has lower biomass

than an undisturbed forest, and it is continuously growing, resulting in lower maintenance

respiration (4). In a different context, (76) demonstrated that selection harvesting was the

preferred method compared to clearcutting when the goal was to maximize total carbon stock

in the forest landscape and wood products generated from harvesting over an 80-year

planning horizon. This preference was justified by the fact that selection harvesting, in

contrast to clearcutting, offers the advantage of maintaining the forest close to its maximum

biological productivity because of maintaining the better and more productive trees.

Additionally, it provides a consistent and sustainable yield of desirable wood products at set

intervals. In contrast, clearcutting involves harvesting stands when their average DBH

reaches 10 cm (the common merchantable dimension), and their yields exceed 50 m$^3$ ha$^{-1}$.

This practice is more likely to favor the production of pulpwood due to the smaller size of the

harvested trees, which implies a faster retirement of the derived products and thus of the

HWPs stock.

**Limitations and perspectives**

Considering the model's sensitivity to inputs and the dependence of results on the approach

used for calculating HWPs stock, emissions, and substitution, it is crucial to account for

uncertainties associated with these elements (77). The TT model tracks wood throughout its

entire lifecycle, from harvesting to disposal sites, thereby encompassing major processes in

between. This modeling principle is considered advanced due to its capacity to accurately
trace carbon over the lifetime of wood products, providing precise results. However,
implementing this principle at the national level poses challenges due to the large number and
diversity of HWPs, as well as the substantial amount of the required local data (15). As the
amount of data increases, the level of compounded uncertainty proportionally rises. A
subsequent phase would involve scrutinizing the sensitivity of various model outputs to the
input data. Additionnaly, uncertainty arising from the coupling of 3D-CMCC-FEM and TT
must be carefully considered. Given the feedforward nature of this coupling, the individual
uncertainties of each model reflect their potential impact on the integrated framework outputs
leading, in the best scenario, to compensation errors or, in the worst, to their sum. Model
uncertainties generally stem from three primary sources: parameter values, which represent
process importance; model structure, which defines how these processes are represented; and
the initial state, which sets the starting conditions for the simulation (78,79). These
uncertainties are particularly important as the outputs of 3D-CMCC-FEM serve as inputs for
TT. The dynamics of the 3D-CMCC-FEM model have been extensively studied and are
known to vary across forest development stages and tree species. Early growth is primarily
driven by structural parameters such as plant architecture, light interception, and LAI, which
indirectly influence photosynthesis. As the forest matures, long-term processes such as
carbon allocation, autotrophic respiration, and biomass accumulation become dominant,
influencing overall biomass and net primary productivity (NPP) (45). This time-dependent
uncertainty in model parameters highlights the need for fine-tuning the 3D-CMCC-FEM to
account for different time scales. Moreover, the uncertainty of 3D-CMCC has been evaluated
based on hypotheses representing key physiological processes. For example, in (80), two
plant respiration theories—photosynthesis-dependent and biomass-dependent—were assessed
against observational data. This study revealed that respiration is not fully governed by either
theory, prompting revisions to how 3D-CMCC estimates the respiration.

From another perspective, the grading of logs utilizing the bucking allocation module, as
exemplified by the implementation in TT, encounters obstacles due to various factors
presumed to impact wood quality — such as strength, knottiness, appearance, stiffness,
hardness, and durability. It is almost impossible, using exclusively models, to account for all
these factors. As an illustration, the implemented module does not account for the presence of
residual branches below the crown base and external defects. Furthermore, it is conceivable
that variations in knot distribution exist across different management scenarios. Owing to the

omission of this parameter in our model, we assert that the disparities in the proportions of

HWP classes could be somewhat undervalued. This conjecture remains subject to empirical

verification, yet the current capabilities of TT do not permit the necessary resolution for such

details. Therefore, future refinements of the model are imperative to enable a more precise

evaluation of these nuances. Furthermore, as demonstrated in (16), the choice of one

distribution function over another to simulate product removal from use can significantly

influence the resulting carbon stock estimates. The TT model currently utilizes the normal

distribution as its default set up; however, this selection should be reassessed in future

analyses.

Given that the maximum climate benefit varies over time for different forest managements

(81,82), we raise questions about the relevance of the fixed planning horizon of 140 years in

this study and its capacity to appropriately address the underlying research hypothesis. In this

context, we may explore in the future the potential of alternative management strategies, such

as clearcut and shelterwood, to be optimal for different planning horizons. Furthermore, we

may question the assumption that simulations conducted over multiple rotations can

effectively control for instantaneous response.

Additionally, the substitution effect is subject to considerable uncertainty due to various

methodological and market-related factors. (18) identifies key assumptions that can lead to an

overestimation of substitution benefits, including the use of static displacement factors, the

assumption that no leakage or cross-sectoral material replacement occurs, and the notion

that building longevity and substitution longevity are independent. Similarly, (20) highlight

uncertainties related to market behavior, particularly whether an increase in wood production

translates into higher HWP consumption and whether wood-based materials consistently

remain economically competitive. (83) emphasize the role of market demand, consumer

behavior, and policy frameworks in determining whether substitution benefits can be

realized. (84) considers the socio-economic factors influencing substitution, noting that

cultural preferences and regulatory barriers may limit large-scale adoption of wood products.

Finally, (85) highlight that economic cycles can significantly affect HWP carbon storage, as

market downturns or reduced construction activity may slow wood consumption, temporarily

reducing substitution benefits or even turning HWPs into a net carbon source. These studies

collectively highlight the need for dynamic modeling approaches that account

for technological progress, evolving market conditions, and real-world constraints rather than

relying on simplified, static assumptions.

1001

Moreover, it is crucial to note that carbon neutrality does not necessarily imply climate
neutrality. When wood is burned or decays, emissions spend some time in the atmosphere
before being sequestered, contributing to climate change in the meantime. In other words, the
timing of emissions and sinks has an impact on the overall cumulative climatic impact (86–
88). Among the factors affecting this timing are the speed of biomass regrowth (rotation
period) and the storage of biomass products (e.g., building, furniture, and paper). Since these
factors are closely linked to forest management practices, the assessment of these practices
should not only consider the carbon balance but also examine the timing of carbon input and
output flows.

1011

Another question concerns the methodological scheme used in this study. Evaluating the
potential of various forest management and wood-use options in mitigating climate change
necessitates a systemic perspective that considers the diverse pools of the forest sector,
including biomass, soil, and products (89,90). The current study exclusively focuses on the
wood products pool, which may not be directly relevant (or being the only one) for guiding
the decision-making of forest managers. This is particularly important considering that the
forest ecosystems constitutes the major contribution of the forest sector in terms of climate
change mitigation. To exemplify this recent assertion, (9) calculated the emissions and
removals linked to HWPs for the historical period (1992-2012) and future scenarios until
2030 in the EU (excluding Malta and Cyprus). They utilized FAOSTAT data on forest
product production (see https://www.fao.org/faostat/en/#data/FO). The findings of this
research indicate that the average historical sink of HWPs from 2000 to 2012 accounts for
10% of the sink contained in the forest pools. This underscores the importance of including
non-HWP carbon pools in decision-making processes as well.

1026

Finally, the results of this use case suggest that shelterwood management is the optimal
choice for optimizing the overall carbon balance of HWPs within the defined planning
horizon. The rationale behind this preference lies partially in the late thinning operation
characteristic of this management scenario, allowing for the C-stock and substitution to
counterbalance total emissions effectively. Notably, this silvicultural practice of partial
cutting aligns with natural disturbance–based silviculture, as it mimics natural dynamics by
anticipating the imminent mortality of a portion of mature trees (91). Moreover, considering
the ongoing rapid changes in many ecosystems and their interaction with natural

disturbances, which are expected to be significant and less predictable in the future (92), multi-aged forest management systems offer a promising approach to enhance resistance and resilience, which is attributed to the presence of multiple age classes, providing more potential pathways for post-disturbance management and recovery (93). Within this context, a suggestion arises to guide future studies in accounting for disturbance risks. Neglecting to incorporate such considerations could result in an overestimation of the climate mitigation efficacy associated with various forest management alternatives. The emerging results show that the failure to account for methane release from landfills can lead to an overestimation of the mitigation potential of different options. Efforts to mitigate these emissions could focus on diverting wood products away from landfills by increasing recycling and directing them to incineration facilities, which not only reduce emissions but also capture energy. The results also indicate that considering static substitution factors may overestimate the substitution effect resulting from the use of HWPs over fossil energy or energy-intensive materials. However, we believe that *ceteris paribus*, substitution could play a central supporting role in the absence of a strong mitigation policy.

**5. Conclusions**

This research emphasizes the pivotal role of harvested wood products (HWPs) in climate change mitigation, as recognized in various Nationally Determined Contributions (NDCs) under the Paris Agreement. Our novel framework, 'TimberTracer', coupled with the 3D-CMCC-FEM forest growth model, enables dynamic assessment of forest management practices and wood-use scenarios, revealing selective thinning as the optimal forest management practice. Additionally, increasing recycling rates and extending product lifespans prove effective in enhancing C-balance. Results show also that failure to account for methane release from landfill and dynamic substitution of HWPs can lead to an overestimation of the mitigation potential of different options. These insights offer valuable guidance for advancing knowledge and optimizing forest management decisions and advancing climate change mitigation efforts.

**Data availability**

The data resulting from this study is available in both Supplementary Files 1 and 4. Additionally, the output simulation is accessible via the following Zenodo link: https://zenodo.org/records/10692189

**Competing interests**

Authors have no competing interests as defined by BMC, or other interests that might be perceived to influence the results and/or discussion reported in this paper.

**Code availability**

TimberTracer is a Python based model for all operating systems (Windows, Linux, and MacOS). It is free and open source (version 1.0.0 with GPL-3 license, requiring Python >= 3x). We openly share our model on GitHub for collaborative research, fostering a community-driven approach to innovation. A tutorial on Google Colab empowers users to harness TimberTracer's capabilities, customize analyses, and integrate it seamlessly into projects. Detailed instructions are available on GitHub (https://github.com/issamyax/TimberTracer), emphasizing TimberTracer's primary objective: providing valuable insights into carbon storage, substitution, and emissions progression over time. We encourage users to report any issues and/or desired extensions on our active issues page https://github.com/issamyax/TimberTracer/issues. The 3D-CMCC-FEM model code version 5.6 is publicly available under the GNU General Public Licence v3.0 (GPL) and can be found on the Github platform at https://github.com/Forest-Modelling-Lab/3D-CMCC-FEM.

**Funding**

I.B and R.V were supported by the  National Research Centre for Agricultural Technologies — AGRITECH — PNRR (Italian National Plan of Recovery and Resilience), CN00000022 in WP 4.3 Task 3 Risk management strategies and policies in the context of climate change. A.C and D.D acknowledge the project funded under the National Recovery and Resilience Plan (NRRP), Mission 4 Component 2 Investment 1.4 - Call for tender No. 3138 of December 16, 2021, rectified by Decree n.3175 of December 18, 2021 of Italian Ministry of University and Research funded by the European Union – NextGenerationEU under award Number: Project code CN_00000033, Concession Decree No. 1034 of June 17, 2022 adopted by the Italian Ministry of University and Research, CUP B83C22002930006, Project title "National Biodiversity Future Centre - NBFC

**Authors' contribution**

I.B: Conceptualization, Data curation, Formal analysis, Investigation, Methodology, Resources, Software, Validation, Visualization, Writing – original draft. A.C, S.L, and D.D: Resources, Writing-review & editing. Farid Nakhle: Software, Writing-review & editing. R.T: Resources, Writing-review & editing. MV.C and M.S: Resources, Writing-review & editing. R.V: Conceptualization, Supervision, Formal analysis, Methodology, Writing-review & editing, Funding acquisition.

**Acknowledgements**

I.B. would like to thank the University of Tuscia and the Euro-Mediterranean Center on Climate Change, both based in Italy, for their support in conducting his Ph.D. thesis, supervised by Professor Riccardo Valentini, of which this work is a part.

**Consent for publication**

I hereby grant permission for the publication of my work. I confirm that I have the authority to grant this permission.

**Ethics approval and consent to participate**

I consent and confirm that ethics approval has been obtained.

1137

1138

1139

1140

1141

1142

1143

**References**

1. Gulev SK, Thorne PW, Ahn J, Dentener FJ, Domingues CM, Gerland S, et al. Changing
state of the climate system. In: Masson-Delmotte V, Zhai P, Pirani A, Connors SL, Péan C,
Berger S, et al., editors. Cambridge, United Kingdom and New York, NY, USA: Cambridge
University Press; 2021 [cited 2023 Jan 19]. p. 287–422. Available from:
https://www.ipcc.ch/report/ar6/wg1/downloads/report/IPCC_AR6_WGI_Chapter02.pdf
1150

1151 2. Pan Y, Birdsey RA, Fang J, Houghton R, Kauppi PE, Kurz WA, et al. A Large and
1152 Persistent Carbon Sink in the World's Forests. Science. 2011 Aug 19;333(6045):988–93.
1153

1154 3.Crumpler K, Abi khalil R, Tanganelli E, Rai N, Roffredi L, Meybeck A, et al. 2021
1155 (Interim) Global update report: Agriculture, Forestry and Fisheries in the Nationally
1156 Determined Contributions [Internet]. Rome, Italy: FAO; 2021 [cited 2024 Jan 9]. 84 p.
1157 (Environment and natural resources management working paper). Available from:
1158 https://www.fao.org/documents/card/en/c/cb7442en
1159

1160 4. Schulze ED, Bouriaud O, Irslinger R, Valentini R. The role of wood harvest from
1161 sustainably managed forests in the carbon cycle. Ann For Sci. 2022 Apr 7;79(1):17.
1162

1163 5. Collalti A, Ibrom A, Stockmarr A, Cescatti A, Alkama R, Fernández-Martínez M, et al.
1164 Forest production efficiency increases with growth temperature. Nat Commun. 2020 Oct
1165 21;11(1):5322.
1166

1167 6. Nabuurs GJ, Lindner M, Verkerk PJ, Gunia K, Deda P, Michalak R, et al. First signs of
1168 carbon sink saturation in European forest biomass. Nat Clim Change. 2013 Sep;3(9):792–6.
1169

1170 7. Leskinen P, Cardellini G, González-García S, Hurmekoski E, Sathre R, Seppälä J, et al.
1171 Substitution effects of wood-based products in climate change mitigation [Internet].
1172 European Forest Institute; 2018 Nov [cited 2023 Nov 17]. (From Science to Policy).
1173 Available from: https://www.efi.int/publications-bank/substitution-effects-wood-based-
1174 products-climate-change-mitigation
1175

1176 8. Pingoud K, Pohjola J, Valsta L. Assessing the integrated climatic impacts of forestry and
1177 wood products. Silva Fenn [Internet]. 2010 Dec 31 [cited 2023 Nov 18];44(1). Available
1178 from: https://www.silvafennica.fi/article/166
1179

1180 9. Pilli R, Fiorese G, Grassi G. EU mitigation potential of harvested wood products. Carbon
1181 Balance Manag. 2015 Feb 25;10(1):6.
1182

1183   10. Dugan AJ, Birdsey R, Mascorro VS, Magnan M, Smyth CE, Olguin M, et al. A systems
1184   approach to assess climate change mitigation options in landscapes of the United States forest
1185   sector. Carbon Balance Manag. 2018 Sep 4;13(1):13.

1186
1187   11. Di Lallo G, Chiriacò MV, Tarasova E, Köhl M, Perugini L. The land sector in the low
1188   carbon emission strategies in the European Union: role and future expectations. Clim Policy.
1189   2023;0(0):1–15.

1190
1191   12. Grassi G, House J, Dentener F, Federici S, den Elzen M, Penman J. The key role of
1192   forests in meeting climate targets requires science for credible mitigation. Nat Clim Change.
1193   2017 Mar;7(3):220–6.

1194
1195   13. Sato A, Nojiri Y. Assessing the contribution of harvested wood products under
1196   greenhouse gas estimation: accounting under the Paris Agreement and the potential for
1197   double-counting among the choice of approaches. Carbon Balance Manag. 2019 Nov
1198   26;14(1):15.

1199
1200   14. Kayo C, Kalt G, Tsunetsugu Y, Hashimoto S, Komata H, Noda R, et al. The default
1201   methods in the 2019 Refinement drastically reduce estimates of global carbon sinks of
1202   harvested wood products. Carbon Balance Manag. 2021 Dec 11;16(1):37.

1203
1204   15. Jasinevičius G, Lindner M, Pingoud K, Tykkylainen M. Review of models for carbon
1205   accounting in harvested wood products. Int Wood Prod J. 2015 Oct 2;6(4):198–212.

1206
1207   16. Brunet-Navarro P, Jochheim H, Muys B. Modelling carbon stocks and fluxes in the wood
1208   product sector: a comparative review. Glob Change Biol. 2016;22(7):2555–69.

1209
1210   17. Brunet-Navarro P, Jochheim H, Muys B. The effect of increasing lifespan and recycling
1211   rate on carbon storage in wood products from theoretical model to application for the
1212   European wood sector. Mitig Adapt Strateg Glob Change. 2017 Dec 1;22(8):1193–205.

1213
1214   18. Harmon ME. Have product substitution carbon benefits been overestimated? A sensitivity
1215   analysis of key assumptions. Environ Res Lett. 2019 Jun;14(6):065008.

1216
1217   19. Sathre R, Gustavsson L. Using wood products to mitigate climate change: External costs
1218   and structural change. Appl Energy. 2009 Feb 1;86(2):251–7.

1219
1220   20. Howard C, Dymond CC, Griess VC, Tolkien-Spurr D, van Kooten GC. Wood product
1221   carbon substitution benefits: a critical review of assumptions. Carbon Balance Manag. 2021
1222   Mar 30;16(1):9.

1223
1224   21. Brunet-Navarro P, Jochheim H, Cardellini G, Richter K, Muys B. Climate mitigation by
1225   energy and material substitution of wood products has an expiry date. J Clean Prod. 2021 Jun
1226   20;303:127026.

1227
1228   22. Kaipainen T, Liski J, Pussinen A, Karjalainen T. Managing carbon sinks by changing
1229   rotation length in European forests. Environ Sci Policy. 2004 Jun;7(3):205–19.

1230
1231   23. Dalmonech D, Marano G, Amthor JS, Cescatti A, Lindner M, Trotta C, et al. Feasibility
1232   of enhancing carbon sequestration and stock capacity in temperate and boreal European

forests via changes to management regimes. Agric For Meteorol. 2022 Dec 15;327:109203.

24. Moreaux V, Martel S, Bosc A, Picart D, Achat D, Moisy C, et al. Energy, water and carbon exchanges in managed forest ecosystems: description, sensitivity analysis and evaluation of the INRAE GO+ model, version 3.0. Geosci Model Dev. 2020 Dec 1;13(12):5973–6009.

25. Collalti A, Perugini L, Santini M, Chiti T, Nolè A, Matteucci G, et al. A process-based model to simulate growth in forests with complex structure: Evaluation and use of 3D-CMCC Forest Ecosystem Model in a deciduous forest in Central Italy. Ecol Model. 2014 Jan 24;272:362–78.

26. Collalti A, Bondo C, Buttafuoco G, Maesano M, Caloiero T, Lucà F, et al. Protocollo di simulazione, calibrazione e validazione del modello 3D-CMCC-CNR-FEM: il caso studio del bacino altamente strumentato del Bonis in Calabria. For - J Silvic For Ecol. 2017 Aug 14;14(1):247.

27. Matsumoto R, Kayo C, Kita S, Nakamura K, Lauk C, Funada R. Estimation of carbon stocks in wood products for private building companies. Sci Rep. 2022 Oct 27;12:18112.

28. Cao QV. Predicting Parameters of a Weibull Function for Modeling Diameter Distribution. For Sci. 2004 Oct 1;50(5):682–5.

29. Sohn JA, Saha S, Bauhus J. Potential of forest thinning to mitigate drought stress: A meta-analysis. For Ecol Manag. 2016 Nov 15;380:261–73.

30. Cao T, Hyytiäinen K, Tahvonen O, Valsta L. Effects of initial stand states on optimal thinning regime and rotation of Picea abies stands. Scand J For Res. 2006 Oct 1;21(5):388–98.

31. Fabrika M, Vaculčiak T. Modeling Natural Disturbances in Tree Growth Model SIBYLA. In: Střelcová K, Mátyás C, Kleidon A, Lapin M, Matejka F, Blaženec M, et al., editors. Bioclimatology and Natural Hazards [Internet]. Dordrecht: Springer Netherlands; 2009 [cited 2024 Jan 13]. p. 155–64. Available from: https://doi.org/10.1007/978-1-4020-8876-6_14

32. Fabrika M, Ďurský J. Algorithms and software solution of thinning models for SIBYLA growth simulator. J For Sci. 2005 Oct 31;51(10):431–45.

33. Bucket E, Moguedec GL, Mothe FF, Nepveu G. Une modélisation des bilans "environnement" et "produits" de sylvicultures contrastées : cas du chêne sessile. Rev For Fr. 2005;57(3):311.

34. Longuetaud F, Mothe F, Kerautret B, Krähenbühl A, Hory L, Leban JM, et al. Automatic knot detection and measurements from X-ray CT images of wood: A review and validation of an improved algorithm on softwood samples. Comput Electron Agric. 2012 Jul 1;85:77–89.

35. Thurner M, Beer C, Crowther T, Falster D, Manzoni S, Prokushkin A, et al. Sapwood biomass carbon in northern boreal and temperate forests. Glob Ecol Biogeogr. 2019;28(5):640–60.

1283    36. Max T, Burkhart H. Segmented Polynomial Regression Applied to Taper Equations. For
1284    Sci. 1976 Sep 1;22:283–9.
1285
1286    37. Longuetaud F, Mothe F, Leban JM, Mäkelä A. Picea abies sapwood width: Variations
1287    within and between trees. Scand J For Res. 2006 Feb 1;21(1):41–53.
1288
1289    38. IPCC. CH4 emissions from solide waste disposal. In: IPCC Guidelines for National
1290    Greenhouse Gas Inventories [Internet]. 2006. Available from: https://www.ipcc-
1291    nggip.iges.or.jp/public/gp/bgp/5_1_CH4_Solid_Waste.pdf
1292
1293    39. Sathre R, O'Connor J. Meta-analysis of greenhouse gas displacement factors of wood
1294    product substitution. Environ Sci Policy. 2010 Apr 1;13(2):104–14.
1295
1296    40. Testolin R, Dalmonech D, Marano G, Bagnara M, D'Andrea E, Matteucci G, et al.
1297    Simulating diverse forest management options in a changing climate on a Pinus nigra subsp.
1298    laricio plantation in Southern Italy. Sci Total Environ. 2023 Jan 20;857:159361.
1299
1300    41. Nicolaci A, Marziliano PA, Pignataro F, Menguzzato G, Iovino F. Fire prevention with
1301    thinning operations in black pine reforestations. Results of a study on a regional scale. Ital
1302    For E Mont. 2015 Jul 6;70(1):7–21.
1303
1304    42. Callegari G, Ferrari E, Garfì G, Iovino F, Veltri A. Impact of thinning on the water
1305    balance of a catchment in a  Mediterranean environment. For Chron. 2003 Apr;79(2):301–6.
1306
1307    43. Collalti A, Marconi S, Ibrom A, Trotta C, Anav A, D'Andrea E, et al. Validation of 3D-
1308    CMCC Forest Ecosystem Model (v.5.1) against eddy covariance data for 10 European forest
1309    sites. Geosci Model Dev. 2016 Feb 8;9(2):479–504.
1310
1311    44. Collalti A, Trotta C, Keenan TF, Ibrom A, Bond-Lamberty B, Grote R, et al. Thinning
1312    Can Reduce Losses in Carbon Use Efficiency and Carbon Stocks in Managed Forests Under
1313    Warmer Climate. J Adv Model Earth Syst. 2018;10(10):2427–52.
1314
1315    45. Collalti A, Thornton PE, Cescatti A, Rita A, Borghetti M, Nolè A, et al. The sensitivity of
1316    the forest carbon budget shifts across processes along with stand development and climate
1317    change. Ecol Appl. 2019;29(2):e01837.
1318
1319    46. Mahnken M, Cailleret M, Collalti A, Trotta C, Biondo C, D'Andrea E, et al. Accuracy,
1320    realism and general applicability of European forest models. Glob Change Biol.
1321    2022;28(23):6921–43.
1322
1323    47. Thornton PE, Running SW. An improved algorithm for estimating incident daily solar
1324    radiation from measurements of temperature, humidity, and precipitation. Agric For
1325    Meteorol. 1999 Mar 22;93(4):211–28.
1326
1327    48. Rockel B, Will A, Hense A. The Regional Climate Model COSMO-CLM (CCLM).
1328    Meteorol Z. 2008 Aug 25;347–8.
1329
1330    49. Bucchignani E, Montesarchio M, Zollo AL, Mercogliano P. High-resolution climate
1331    simulations with COSMO-CLM over Italy: performance evaluation and climate projections
1332    for the 21st century. Int J Climatol. 2016;36(2):735–56.

1333
1334 50. Zollo AL, Rillo V, Bucchignani E, Montesarchio M, Mercogliano P. Extreme temperature
1335 and precipitation events over Italy: assessment of high-resolution simulations with COSMO-
1336 CLM and future scenarios. Int J Climatol. 2016;36(2):987–1004.
1337
1338 51. Scoccimarro E, Gualdi S, Bellucci A, Sanna A, Fogli PG, Manzini E, et al. Effects of
1339 Tropical Cyclones on Ocean Heat Transport in a High-Resolution Coupled General
1340 Circulation Model. J Clim. 2011 Aug 15;24(16):4368–84.
1341
1342 52. Meinshausen M, Raper SCB, Wigley TML. Emulating coupled atmosphere-ocean and
1343 carbon cycle models with a simpler model, MAGICC6 – Part 1: Model description and
1344 calibration. Atmospheric Chem Phys. 2011 Feb 16;11(4):1417–56.
1345
1346 53. Buttafuoco G, Castrignanò A, Busoni E, Dimase AC. Studying the spatial structure
1347 evolution of soil water content using multivariate geostatistics. J Hydrol. 2005 Sep
1348 15;311(1):202–18.
1349
1350 54. Moresi FV, Maesano M, Collalti A, Sidle RC, Matteucci G, Scarascia Mugnozza G.
1351 Mapping Landslide Prediction through a GIS-Based Model: A Case Study in a Catchment in
1352 Southern Italy. Geosciences. 2020 Aug;10(8):309.
1353
1354 55. Jozsa LA, Middleton GR. A DISCUSSION OF WOOD QUALITY ATTRIBUTES AND
1355 THEIR PRACTICAL IMPLICATIONS. 1994;
1356
1357 56. CTBA C. Manuel scierie: Techniques et matériels. Centre Technique du Bois et de
1358 l'Ameublement; 2001. 400 p.
1359
1360 57. Burschel P, Kürsten E, Larson BC, Weber M. Present role of German forests and forestry
1361 in the national carbon budget and options to its increase. Water Air Soil Pollut. 1993 Oct
1362 1;70(1):325–40.
1363
1364 58. Karjalainen T, Kellomäki S, Pussinen A. Role of wood-based products in absorbing
1365 atmospheric carbon. Silva Fenn [Internet]. 1994 Jan 1 [cited 2024 Jan 17];28(2). Available
1366 from: https://www.silvafennica.fi/article/5398
1367
1368 59. Nabuurs GJ. Significance of wood products in forest sector carbon balances. In: Apps MJ,
1369 Price DT, editors. Forest Ecosystems, Forest Management and the Global Carbon Cycle.
1370 Berlin, Heidelberg: Springer; 1996. p. 245–56. (NATO ASI Series).
1371
1372 60. E. Skog K, A. Nicholson G. Carbon cycling through wood products: the role of wood and
1373 paper products in carbon sequestration. 1998;48(7).
1374
1375 61. Eggers T. The Impacts of Manufacturing and Utilisation of Wood Products on the
1376 European Carbon Budget. 2002.
1377
1378 62. Masera OR, Garza-Caligaris JF, Kanninen M, Karjalainen T, Liski J, Nabuurs GJ, et al.
1379 Modeling carbon sequestration in afforestation, agroforestry and forest management projects:
1380 the CO2FIX V.2 approach. Ecol Model. 2003 Jun 15;164(2):177–99.
1381
1382 63. Pingoud K, Perälä AL, Soimakallio S, Pussinen A. Greenhouse gas impacts of harvested

wood products: Evaluation and development of methods. Espoo: VTT Technical Research Centre of Finland; 2003. (VTT Tiedotteita - Meddelanden - Research Notes).

64. Suter F, Steubing B, Hellweg S. Life Cycle Impacts and Benefits of Wood along the Value Chain: The Case of Switzerland. J Ind Ecol. 2017;21(4):874–86.

65. Dias A, Gaspar MJ, Carvalho A, Pires J, Lima-Brito J, Silva ME, et al. Within- and between-tree variation of wood density components in Pinus nigra at six sites in Portugal. Ann For Sci. 2018 Jun;75(2):1–19.

66. Boukhris I, Puletti N, Vonderach C, Guasti M, Lahssini S, Santini M, et al. Comparative analysis of taper models for Pinus nigra Arn. using terrestrial laser scanner acquired data. IForest - Biogeosciences For. 2024 Aug 31;17(4):203–12.

67. Rockström J, Gaffney O, Rogelj J, Meinshausen M, Nakicenovic N, Schellnhuber HJ. A roadmap for rapid decarbonization. Science. 2017 Mar 24;355(6331):1269–71.

68. Skog KE. Sequestration of carbon in harvested wood products for the United States. For Prod J. 2008;58(6).

69. Dymond CC. Forest carbon in North America: annual storage and emissions from British Columbia's harvest, 1965–2065. Carbon Balance Manag. 2012 Jul 24;7(1):8.

70. Bozzolan N, Grassi G, Mohren F, Nabuurs GJ. Options to improve the carbon balance of the harvested wood products sector in four EU countries. GCB Bioenergy. 2024;16(1):e13104.

71. Rüter S, Werner F, Forsell N. ClimWood2030, Climate benefits of material substitution by forest biomass and harvested wood products: Perspective 2030 - Final ReportlimWood2030, Climate benefits of material substitution by forest biomass and harvested wood products: Perspective 2030 - Final Report [Internet]. DE: Johann Heinrich von Thünen-Institut; 2016 [cited 2024 Jan 7]. Available from: https://doi.org/10.3220/REP1468328990000

72. Bais-Moleman AL, Sikkema R, Vis M, Reumerman P, Theurl MC, Erb KH. Assessing wood use efficiency and greenhouse gas emissions of wood product cascading in the European Union. J Clean Prod. 2018 Jan 20;172:3942–54.

73. Hennigar CR, MacLean DA, Amos-Binks LJ. A novel approach to optimize management strategies for carbon stored in both forests and wood products. For Ecol Manag. 2008 Aug 10;256(4):786–97.

74. Thornley JHM, Cannell MGR. Managing forests for wood yield and carbon storage: a theoretical study. Tree Physiol. 2000 Apr 1;20(7):477–84.

75. Bouriaud O, Schulze ED, Gregor K, Bourkhris I, Högberg P, Irslinger R, et al. Saturating response of photosynthesis to increasing leaf area index allows selective harvest of trees without affecting forest productivity. EGUsphere. 2024 Oct 29;1–23.

76. Bourque CPA, Neilson ET, Gruenwald C, Perrin SF, Hiltz JC, Blin YA, et al. Optimizing

carbon sequestration in commercial forests by integrating carbon management objectives in wood supply modeling. Mitig Adapt Strateg Glob Change. 2007 Aug 1;12(7):1253–75.

77. Cláudia Dias A, Louro M, Arroja L, Capela I. Comparison of methods for estimating carbon in harvested wood products. Biomass Bioenergy. 2009 Feb 1;33(2):213–22.

78. Van Oijen M, Rougier J, Smith R. Bayesian calibration of process-based forest models: bridging the gap between models and data. Tree Physiol. 2005 Jul 1;25(7):915–27.

79. van Oijen M. Bayesian Methods for Quantifying and Reducing Uncertainty and Error in Forest Models. Curr For Rep. 2017 Dec 1;3(4):269–80.

80. Collalti A, Tjoelker MG, Hoch G, Mäkelä A, Guidolotti G, Heskel M, et al. Plant respiration: Controlled by photosynthesis or biomass? Glob Change Biol. 2020;26(3):1739–53.

81. Guest G, Cherubini F, Strømman AH. Global Warming Potential of Carbon Dioxide Emissions from Biomass Stored in the Anthroposphere and Used for Bioenergy at End of Life. J Ind Ecol. 2013;17(1):20–30.

82. Röder M, Thiffault E, Martínez-Alonso C, Senez-Gagnon F, Paradis L, Thornley P. Understanding the timing and variation of greenhouse gas emissions of forest bioenergy systems. Biomass Bioenergy. 2019 Feb 1;121:99–114.

83. Hurmekoski E, Kunttu J, Heinonen T, Pukkala T, Peltola H. Does expanding wood use in construction and textile markets contribute to climate change mitigation? Renew Sustain Energy Rev. 2023 Mar 1;174:113152.

84. York R. Do alternative energy sources displace fossil fuels? Nat Clim Change. 2012 Jun;2(6):441–3.

85. Johnston CMT, Radeloff VC. Global mitigation potential of carbon stored in harvested wood products. Proc Natl Acad Sci. 2019 Jul 16;116(29):14526–31.

86. Cherubini F, Peters GP, Berntsen T, Strømman AH, Hertwich E. CO2 emissions from biomass combustion for bioenergy: atmospheric decay and contribution to global warming. GCB Bioenergy. 2011;3(5):413–26.

87. Levasseur A, Lesage P, Margni M, Deschênes L, Samson R. Considering Time in LCA: Dynamic LCA and Its Application to Global Warming Impact Assessments. Environ Sci Technol. 2010 Apr 15;44(8):3169–74.

88. Levasseur A, Lesage P, Margni M, Brandão M, Samson R. Assessing temporary carbon sequestration and storage projects through land use, land-use change and forestry: comparison of dynamic life cycle assessment with ton-year approaches. Clim Change. 2012 Dec 1;115(3):759–76.

89. Grassi G, Fiorese G, Pilli R, Jonsson K, Blujdea V, Korosuo A, et al. JRC Publications Repository. 2021 [cited 2023 Dec 18]. Brief on the role of the forest-based bioeconomy in mitigating climate change through carbon storage and material substitution. Available from:

https://publications.jrc.ec.europa.eu/repository/handle/JRC124374

90. Lemprière TC, Kurz WA, Hogg EH, Schmoll C, Rampley GJ, Yemshanov D, et al.
Canadian boreal forests and climate change mitigation. Environ Rev. 2013 Dec;21(4):293–
321.

91. Bose AK, Harvey BD, Brais S, Beaudet M, Leduc A. Constraints to partial cutting in the
boreal forest of Canada in the context of natural disturbance-based management: a review.
For Int J For Res. 2014 Jan 1;87(1):11–28.

92. Seidl R, Thom D, Kautz M, Martín-Benito D, Peltoniemi M, Vacchiano G, et al. Forest
disturbances under climate change. Nat Clim Change. 2017 Jul 1;7:395–402.

93. O'Hara KL, Ramage BS. Silviculture in an uncertain world: utilizing multi-aged
management systems to integrate disturbance†. For Int J For Res. 2013 Oct 1;86(4):401–10.

**Appendix A**

Table A.1: Clearcut management interventions and the products derived from the thinned
wood.

| Intervention | Products | Stock (tC) | Decay rate (%) |
|---|---|---|---|
| Thinning | Millsite | 1.81 | 2.02 "(0.26 tC/yr)" |
| | Paper | 2.16 | |
| | Particle | 6.88 | |
| | Fire | 1,97 | |
| Harvesting | Millsite | 5.09 | 1.47 "(0.93 tC/yr)" |
| | Paper | 5.73 | |
| | Particle | 13.83 | |
| | Fire | 9.81 | |
| | Furniture | 24.89 | |
| | Sawing | 2.81 | |

1502
1503
1504
1505

1506
1507 Figure A.1: Dynamic evolution of substitution factors of different HWPs proportionally to
1508 the evolution of global GHG emissions following the Paris Agreement pathways.