Decoding the Microbiome-Metabolome Nexus: A Systematic Benchmark of Integrative Strategies

Loïc Mangnier[1$], Antoine Bodein[1$], Margaux Mariaz[1], Marie-Pier Scott-Boyer[1], Alban

Mathieu[1] , Neerja Vashist[2], Matthew S. Bramble[3,4], Arnaud Droit[1,5,*]

[1] Centre de Recherche du CHU de Québec-Université, Laval, Université Laval, G1V 4G2, Québec, Canada
[2] Department of Pathology and Laboratory Medicine, UCLA, USA
[3] Center for Genetic Medicine Research, Children's Research Institute, Children's National Hospital, Washington, DC, USA
[4] Department of Genomics and Precision Medicine, The George Washington University of Medicine and Health Sciences, Washington, DC, USA
[5] Département de Médecine Moléculaire, G1V 0A6, Québec, Canada
[$] contribute equally

Loïc Mangnier: loic.mangnier@crchudequebec.ulaval.ca
Antoine Bodein: antoine.bodein@crchudequebec.ulaval.ca
Margaux Mariaz: margaux.mariaz@gmail.com
Neerja Vashist: neerjavashist@ucla.edu
Alban Mathieu: alban.mathieu@crchudequebec.ulaval.ca
Marie-Pier Scott-Boyer: mariepier.scottboyer@crchudequebec.ulaval.ca
Matthew S. Bramble: mbramble@childrensnational.org
* corresponding author: arnaud.droit@crchudequebec.ulaval.ca

Abstract

Background
The exponential growth of high-throughput sequencing technologies was an incredible
opportunity for researchers to combine various -omics within computational frameworks.
Among these, metagenomics and metabolomics data have gained an increasing interest due
to their involvement in many complex diseases. However, currently, no standard seems to
emerge for jointly integrating both microbiome and metabolome datasets within statistical
models.
Results
Thus, in this paper we comprehensively benchmarked nineteen different integrative methods
to untangle the complex relationships between microorganisms and metabolites. Methods
evaluated in this paper cover most of the researcher's goals such as global associations,
data summarization, individual associations, and feature selection. Through an extensive
and realistic simulation we identified best methods across questions commonly encountered
by researchers. We applied the most promising methods in an application to real gut
microbial datasets, unraveling complementary biological processes involved between the two
omics. We also provided practical guidelines for practitioners tailored to specific scientific
questions and data types.
Conclusion
In summary, our work paves the way toward establishing research standards when mutually
analyzing metagenomics and metabolomics data, building foundations for future
methodological developments.

Keywords: multi-omics, metagenomics, metabolomics, benchmark, statistical methods

Background

The recent development of high-throughput sequencing technologies has permitted the

generation of omics data at an exponential scale. Combining different high dimensional

biological datasets within computational models represents a wonderful opportunity for

researchers to better understand the underlying biological mechanisms involved in

diseases[1]. Microorganism-metabolite interactions have gained an increasing interest due to

their potential involvement in a large set of traits. It has been demonstrated that shifts in the

microbiome-metabolome interactions have important implications on individual health [2,3].

Indeed, recent studies for cardio-metabolic diseases [4] or autism spectrum disorders [5] have

shown that the pathoetiology could be explained by a complex interplay between microbes

and host metabolites [6] or by disruptions in the microbiota-derived metabolite processes [7].

Thus, efficiently incorporating microbiome and metabolome data within statistical frameworks

offers critical insights on the complex architecture occurring between diet or lifestyle factors

on the microbe-metabolite recomposition and remains an important challenge to adequately

identify biological pathways, with interesting avenues for clinical applications [8]. However, the

tremendous amount of available statistical models makes the choice of the right method a

daunting task for many researchers. Typical research questions include either the inference

of interactions occurring between species and metabolites or in predicting one omics

borrowing the biological information contained in the other omics [9,10]. On the one hand, the

inference of interactions refers to understanding and identifying the complex relationships

and dependencies between microbial communities and the metabolites they interact with.

This inference aims to uncover causal relationships, dependencies, and mechanisms that

drive microbial-metabolite interactions in biological systems. On the other hand, other multi-

omics integration techniques use multiple types of omics data together to make predictions

about biological phenomena. Advanced machine learning or deep learning methods,

including multi-omics data are often employed to tackle these prediction tasks effectively.

However, while models have been shown to be powerful to predict metabolome levels based

on microbial compositions, they lack the mechanistic interpretation needed for building new

sets of biological hypotheses.

76   Thus, to elucidate the complex entanglement between microorganisms and

metabolites, several strategies can be exploited, each exhibiting associations occurring at

different scales. Indeed, consistent with a recent report from Deek et al., 2024 [11], traditional

workflows include distinct types of analysis, addressing complementary biological questions[2].

Briefly, common pipelines include the detection of *global associations*, *data summarization*,

individual associations, and identification *of core features*. Firstly, researchers are often

interested in determining whether a global association is occurring between the two omics.

For example, one can look for a global change in metabolome levels due to a microbial

recomposition induced by a specific diet or lifestyle[2]. Testing for global associations can be

performed using multivariate methods such as the Procrustes analysis [12], the Mantel test [13],

or the multivariate microbiome regression-based kernel association test (MMiRKAT) [14]. This

step frequently precedes the application of subsequent analyses such as *data*

summarization methods or the *identification of core features* [2]. Then, following approaches

used for single omics, a common research objective is to summarize information contents in

the two omics, facilitating the visualization and interpretation of large-scale biological data [1].

The presence of two types of omics allows the exploitation of the intra- and inter- correlation

existing between features of the two datasets. Application of data summarization methods

including Canonical Correlation Analysis (CCA) [15], Partial Least Square (PLS) [16],

Redundancy Analysis (RDA) [17] or more recently the Multi-Omics Factor Analysis (MOFA2) [18]

is a major step to uncover features explaining a substantial proportion of data variability.

Indeed, applications of data summarization methods have allowed the identification of

taxonomic groups or metabolites involved in Type 2 diabetes [19]. However, both *global*

association and *data summarization* methods fail to provide individual relationships between

one or several microorganisms and metabolites. This aspect remains central to highlight core

features involved in a particular biological context. As an illustration, methods for detecting

individual associations may prove relevant for the identification of bacterial genus associated

with dietary-impacted metabolites [2]. One strategy is to compute a measure of association

between each metabolite-microbiota pair, using either a correlation or a regression model.

Although easily implementable and interpretable, these approaches suffer from lack of power

induced by the number of models fitted, limiting result transferability. An alternative way is to

employ univariate or multivariate feature selection methods to adequately identify key actors

at a large scale. The least absolute shrinkage and selection operator (LASSO) is a method

initially developed to improve predictability while proceeding to feature selection [20]. Indeed,

the LASSO can set coefficients to zero, facilitating identification of core features.

Consistently with this idea, sparse CCA (sCCA) [21] or sparse Partial Least Square (sPLS) [22]

are multivariate penalized methods summarizing data variability while proceeding to feature

selection. However, due to the complex structure of both microbiome and metabolome data,

standard methods fall short of providing unbiased associations, limiting the biological

interpretation of results.

By using either functional gene screening or sequencing analysis, metagenomics

sequencing technologies can provide a general picture of the microbial composition in a

given environment [23]. However, metagenomics data highlight hard-to-analyze

characteristics[24,25]. Indeed, it is now globally accepted that microbiome datasets are over-

dispersed, zero-inflated, highly correlated, and compositional. Without adequate

transformation the inherent compositionality of the data makes the application of standard

methods incorrect, leading to inconsistent results [24–26]. Metabolomics is the comprehensive

study of all metabolites within a biological system, using analytical methods like LC-MS-

based metabolomics to measure metabolite levels and small molecular mass compounds

under specific biological conditions [27] . This field is divided into untargeted metabolomics,

which covers a broad range of metabolites, and targeted metabolomics, which concentrates

on specific metabolites. Metabolomics data shares some features with metagenomics data,

exhibiting over-dispersion and high correlation structures [26]. Thus, interpreting metabolomics

data using statistical analysis requires a particular attention for explicitly accounting for the

data structure needed for robust biological interpretations. Moreover, integrating

metabolomics data into pathway mapping, with other omics data, such as metagenomics,

facilitates the discovery of biomarkers or metabolic signatures involved in diseases. Tools

like MetaboAnalyst provide resources for these analyses [28].

Thus, combining these two omics together within statistical frameworks requires

particular attention. Approaches to deal with compositional data either as an outcome or

explanatory variable have already been proposed [25,29,30], covering applications of global

association methods, data summarization, individual associations, or identification of core

features. Conventional strategies include utilization of standard methods after suitable data

transformations or purely compositional approaches [31–34]. Subsequently, determining which

strategy is the best depending on the research question remains an open problem with major

implications for practitioners.

Despite recent studies proposing to evaluate statistical methods jointly integrating

microbiome and metabolome data, efforts were only made either on literature reviews or on

real-data applications, where the ground truth is missing. This aspect is pivotal for performing

agnostic comparisons required for an unbiased evaluation [11]. This systematic evaluation is

still needed for highlighting best practices required for result interpretability and

reproducibility. To our knowledge there is no systematic benchmark of integrative methods to

link microbiome with metabolome datasets; constantly pushing researchers to make their

choice without any robust comparison. For example, researchers often consider centered

log-ratio or isometric log-ratio transformations when normalizing microbiome data with no

clear insights on which method performs the best. Thus, in this paper, we comprehensively

compared nineteen different integrative methods to decipher the complex entanglement

occurring between microorganisms and metabolites. Methods and strategies were selected

based on a recent report [11], covering most of the researcher's aims, such as *global*

associations, *data summarization*, *individual associations*, or *feature selection* (Figure 1).

Our extensive simulation studies provide insightful lessons on the strengths and limits of

methods commonly encountered in practice. Then, we applied best methods to real data on

the gut microbiome and metabolome for Konzo disease [35], highlighting a complex

architecture between the two omics occurring at different scales. Finally, we provide general

and specific recommendations for researchers depending on the data at-hand and the

research aims, while pinpointing avenues for future methodological developments (Tables 1-

2). A complete user guide with all the related code is provided, facilitating method

applications to other contexts, promoting scientific replicability and reproducibility.

Results

SIMULATION SETUP AND BENCHMARKED METHODS

To adequately simulate realistic simulation scenarios, we generated synthetic microbiome

and metabolome datasets mimicking complex data structures and relationships from three

real metagenomics-metabolomics studies. Globally, datasets were chosen to exhibit different

structures and complexity, covering most scenarios commonly encountered in practice. See

Figure 2 and the Method section (Simulation setup) for additional details on the simulation

setting. We therefore compared nineteen integrative methods for inferring the link between

microorganisms and metabolites occurring at different biological scales (Figure 1). Methods

were presented as follows. First, In the *global associations* subsection we compared the

Procrustes analysis, Mantel test, and MMiRKAT with respect to the Type-I error rate and

power. Second, In the *data summarization* subsection we evaluated four different models

including CCA, PLS, RDA and MOFA2, regarding their capability to recapitulate data

variability across latent factors. Third, in the *individual associations* subsection we compared

four strategies for performing regression-based approaches between compositional

covariates and metabolites, the clr-linear model, the log-contrast, HALLA, and MiRKAT.

Approaches were evaluated based on the Type-I error rate and power. Fourth, in

subsections *univariate feature-selection for compositional predictors* and *multivariate feature-*

selection we compared approaches for identifying core microbes and metabolites, leveraging

both univariate and multivariate feature selection strategies. For univariate frameworks,

depending on the nature of the response, several models were considered. Indeed, when

microorganisms are the explanatory variables, we compared three approaches, the clr-

LASSO, the clr-MLASSO and CODA-LASSO [30]. Nonetheless, for multivariate feature

selection models, we considered sCCA and sPLS. Approaches were evaluated based on

sparsity and reliability. Whenever suitable, we evaluated the impact of data normalizations or

distance kernels on method performance. Details on the methods, data transformations, and

performance metrics were provided in the Methods section. Finally, to highlight

complementary biological insights provided by methods, best approaches were illustrated in

the *real-data application* subsection, exploiting metagenomics and metabolomics data from

Konzo disease.

GLOBAL ASSOCIATIONS

A common question in practice for researchers is to find global associations between two

omics datasets [2]. Thus, we compared three multivariate methods detecting associations

occurring at a global level between microbiome and metabolome, the Procrustes Analysis [12],

the Mantel test [13], and MMiRKAT [14]. Since methods have distinct assumptions with respect

to the underlying data structures, we provided fair method performance evaluations in two

separate settings (See Additional Simulation Settings in the Supplementary Materials). In our

main setting, the Mantel test and Procrustes Analysis exhibited comparable results across

microbiome data normalizations for controlling the false positive rate in the Adenomas and

Konzo scenarios. While in the Autism datasets, the Mantel test considering the Euclidean

distance provided the best control of Type-I error rate; the Procrustes analysis and other

distance kernels showing inflation patterns (Figure 3A.). Nonetheless, methods highlighted

variable powers depending on the scenario, microbiome normalizations and distance kernels

considered (Figure 3B.). Indeed, in the Konzo scenario, the alpha transformation could

detect more than twice fewer associations compared to the CLR or ILR normalizations,

whether the Mantel test or the Procrustes Analysis are considered (Figure 3B.). Additionally,

the Canberra distance showed weakest powers across all the three settings, where no clear

distinction between Euclidean and Manhattan distances could be observed (Figure 3B.). As

an example, in the Adenomas simulation-based scenario, considering the CLR

normalization, both the Manhattan and Euclidean distances offered up to 2.72-fold higher

powers than the Canberra kernel (Power Manhattan = 68%; Power Euclidean = 67%; Power

Canberra = 25%). In an additional scenario with a smaller number of features than

individuals, the Mantel test was on average the best method across microbiome data

normalizations and distance kernels, showing good control of the Type-I error rate and power

(Figures 3C.-3D.). Briefly, when considering the Euclidean distance for the Mantel test, the

method was minimally 1.5 times more powerful than MMiRKAT considering the same

distance kernel or the Procrustes Analysis (Figure 3D.). This result was consistent across

other microbiome normalizations. Our results were confirmed in additional scenarios and

considering other types of correlations (Figures S1-S4). Our findings point to different

method capabilities to detect global associations depending on the data at-hand. Importantly,

our results suggest better performances for the Mantel test regarding both Type-I error rate

and power when compared to MMiRKAT or the Procrustes analysis. Particularly, applying

the Mantel test using the ILR normalization on microbiome data and the log transformation

on metabolites were a robust strategy, offering the best results to detect global associations

in a variety of scenarios.

DATA SUMMARIZATION

Instead of measuring one global association, one can be interested in recapitulating

information contained within the two datasets through latent factors, accounting for the

between- within-correlation [36]. Thus, we compared Canonical Correlation Analysis (CCA) [15],

Regression PLS (PLS-Reg) [16], Canonical PLS (PLS-Can) [16], Redundancy Analysis (RDA) [17],

and Multi-Omic Factor Analysis (MOFA2) [18] across our three main scenarios regarding their

capability to summarize the explained variance contained in the two omics (See Methods).

Regardless of the considered microbiome data normalization, method's performances were

consistent in the three simulation setups (Figure 2E.). For example, RDA exhibited weak

variations of the metabolome explained variances across data normalizations, with standard

errors of 0.003, 0.003, and 0.002, for Adenomas, Autism, and Konzo simulation-based

scenarios. Impacts of the choice of normalization on result variability for other methods were

provided in Figure S5. This result suggests that the normalization used for dealing with

compositionality observed in metagenomics data does not affect the capability of methods to

capture data variability. Importantly, we observed that no methods are unambiguously the

best across data summarizations and simulation settings, where performance seems to

depend on the underlying data structure. However, RDA provided consistent performances

compared to other methods in most scenarios, showing an average explained variance of

52% depending on the omics of interest (Figure 2E.). Moreover, MOFA2 exhibited the

highest variable results spanning from 0% to 100% of explained variances. While surprising,

this result suggests that the underlying data structure is critical for the method performance.

For regression-based methods, such as PLS-Reg or RDA, the integration directionality

impacted the method performances, producing up to 6-fold higher explained variances

(Figure 2E.). We confirmed our findings where considering the original metabolome (Figure

S6). Our results pointed to RDA as the best trade-off to summarize data variability through

latent factors, while PLS-Reg could be exploited when strong assumptions of the effect

direction can be assumed. As a whole, our findings suggested that the RDA or PLS-Reg are

versatile and robust under scenarios commonly encountered in practice, where the choice of

the best method could be driven depending on the research question (See Discussion).

INDIVIDUAL ASSOCIATIONS FOR COMPOSITIONAL PREDICTORS

Studying the relationship between metabolites and microorganisms may represent an

important challenge when accounting for the compositionality induced by microbiome

datasets. Indeed, the perfect correlation brought by the compositionality makes the

application of standard methods incorrect. This is particularly true when species are

incorporated as covariates [24,29]. We therefore compared four equivalent strategies for

studying the global effect of microorganisms on one particular metabolite, HALLA [37], the Log-

contrast model [29], MiRKAT [14] and a linear regression on the CLR transformed microbiome

(referred to as clr-lm). Globally, under the null hypothesis, across our three scenarios,

methods exhibited different behaviors regarding the control of the Type-I error rate, showing

an accurate control in the Adenomas simulation-based setting, or being either conservative

or slightly liberal in the Autism and Konzo simulation-based scenarios (Figure 4A.). We

observed a similar pattern when investigating Pearson's and Spearman's correlation with an

accurate control or modest inflations of false positives depending on the considered setting

(Figure S7). This result suggests a certain discrepancy in method performances to control

the Type-I error rate depending on the underlying data structure. At the nominal 5% level,

methods highlighted weak to modest powers, ranging from 7% to 35% depending on the

method and dataset considered, when these powers were drastically reduced after

correcting for multiplicity (Figure 4B., Figure S8). These results are partially explained by the

simulation setting where a low signal-to-noise ratio was assumed, mimicking complex

microbiome-metabolome relationships. In certain replicate null powers were observed while

in others a high percentage of significant associations (Figure S9). Then, comparing models

to Pearson's and Spearman's pairwise correlations (straight lines in the Figure 4B.), we

found no clear advantage of the Log-contrast, HALLA, MiRKAT or clr-lm over standard

approaches, when higher powers were mainly due to uncalibrated false positive rates.

Interestingly, MiRKAT was robust to microbiome normalization, offering consistent control of

the Type-I error rate and power across CLR, ILR, or alpha transformations (Figure 4; Figure

S10). Collectively, our results align with a poor calibration of the Type-I error rate in our

Konzo and Autism-based scenarios for HALLA, the clr-lm, or log-contrast regression, while

MiRKAT exhibited consistent results across the considered scenarios. For all methods, well-

behaved qqplots suggesting accurate control of false positives were only observed in the

Adenomas simulation-based setting suggesting that the underlying data structure is a key

player of method performances. Our evaluation suggested that MiRKAT offers the best false

positives-power trade-off in all our simulation settings. The pros and cons of each strategy

were further elaborated in the Discussion section.

295

296 UNIVARIATE FEATURE-SELECTION FOR COMPOSITIONAL PREDICTORS

Feature selection methods have gained increasing interest from researchers in order to

identify a subset of microbiota associated with a variable of interest [2,30,38]. However, due to

the compositionality induced by microbiome data, traditional methods have been shown to

lead to incorrect results [24]. Thus, we compared univariate feature selection methods

accounting for compositional predictors, CODA-LASSO [30], clr-LASSO [30] and clr-MLASSO.

First, we evaluated whether methods were able to provide sparse sets of microorganisms

across our three scenarios and found that clr-LASSO or CODA-LASSO exhibited smaller

sparsity than clr-MLASSO, suggesting that the two methods perform better to keep only a

small portion of the original number of species (Figure 5A.). For example, in our Konzo-

based simulation setting, we observed that CODA-LASSO offered the sparsest method with

on average 0.2% of features selected (sd=0.001) compared to 2% (sd=0.003) and 41%

(sd=0.09), for the clr-LASSO and clr-MLASSO, respectively. This result was confirmed in the

two other scenarios with different underlying data structures. Then, we assessed how

accurate the methods are to find true associations, evaluating methods based on specificity

and sensitivity (see Methods). Overall, methods exhibited different patterns of results, with

weak to high sensitivities depending on the method and scenario considered (Figure 5A.). As

an example, under our three simulation settings, CODA-LASSO showed sensibilities of

0.3%, 10%, and 30%, in the Adenomas-based, Autism-based, and the Konzo-based

scenario, respectively, suggesting method performance discrepancies under realistic data

structures. We observed comparable results when considering clr-LASSO or clr-MLASSO.

Additionally, because the great majority of features were non-associated, methods showed

highly specific behaviors. Interestingly, clr-MLASSO due to underlying feature selection

process could be highly sensible at the price of lower sparsity or specificity compared to the

two other methods. Collectively, our results suggest that univariate feature selection methods

must be carefully chosen, depending on the underlying data structure, to accurately select

sparse subset of microbiota associated with metabolites (See Discussion).

MULTIVARIATE FEATURE-SELECTION

MULTIVARIATE FEATURE-SELECTION

Instead of analyzing each feature independently, exploiting information shared across two

omics may represent an interesting avenue to select the most contributive features [39]. Thus,

we compared three methods taking advantage of both intra- and inter-correlation occurring

between features of the two datasets, the regression sparse PLS (sPLS-Reg) [22], the

canonical sparse PLS (sPLS-Can) and the sparse CCA (sCCA) [21], respectively. Across our

three scenarios, either sPLS-Can or sPLS-Reg provided lower sparsity scores compared to

sCCA. Indeed, while sPLS selected on average 12% of the total number of features, sCCA

tends to keep either all or no variables, suggesting a poor method's performance to select

features, as confirmed by the patterns of specificity and sensibility (Figure 5B.). This result is

higher than the upper bound of true associations assumed by the simulation scenario (10%)

suggesting that methods tend to provide a higher proportion of false associations than

expected. Further investigations showed that the difference in sparsity may be explained by

the distribution of the penalty parameters with severe, high or homogeneous penalization

patterns depending on the underlying data structure (Figure S11). Interestingly, both sPLS-

Can or sPLS-Reg exhibited the same behavior, showing important levels of specificity and

modest sensitivities, while sCCA showed inconsistent performances across our three

simulation settings. For example, in the Konzo-based scenario, the two methods offered on

average 12% of signals detected as true when the signal is true (sensitivity), with much

higher variability for sCCA as demonstrated by the shape of the boxplots in Figure 5B. .

Finally, when focusing on sPLS-Reg, we found that directionality of integration did not offer

discrepancy in results, suggesting robustness to the underlying outcome structure. These

results were confirmed when considering metabolites on the original scale (Figure S12).

Collectively, our findings align with the conclusion that multivariate feature-selection methods

perform moderately to discriminate informative to uninformative features when exploiting the

intra-, inter-correlation occurring between omics.

REAL-DATA APPLICATION

Our systematic evaluation of strategies to jointly analyze microbiome and metabolome data

has permitted the identification of the best methods depending on the research question.

Thus, we illustrated best approaches through an application on metabolomics and

metagenomics data of the Konzo disease [35]. We presented the exact workflow in the Konzo

data analysis section and Figure S13. Firstly, we asked whether there is a different pattern of

global association between the two omics in cases and controls and found a stronger

relationship in Konzo-affected individuals (Mantel statistic r: 0.4272;

Spearman's permutation p-value: 9.999e-05) than in healthy individuals (Mantel statistic r:

0.2838; Spearman's permutation p-value: 0.0026997). Then we applied the RDA and found

that the two first components explained roughly 26% of metabolome variability across the

two conditions, while these proportions remained stable when considering microbiome

(Figure 6A.). Moreover, the top-20 most contributing features in each omic on the two first

RDA factors highlighted a large panel of associations between microbiota and metabolites

with distinct patterns of correlations occurring in affected and unaffected subjects (Figure

6B.; Figure S14). For example, in unaffected individuals, RDA identified *mevalonate* as

strongly positively associated with species and *3-hydroxyisobutyrate* exhibiting moderate

negative association with microorganisms. These two metabolites have been shown to be

linked to inflammatory- or oxidative-based processes potentially involved in Konzo [40,41].

Consistently, the application of RDA has allowed the detection of 15 *Prevotella* species

which have a negative correlation with metabolites in unaffected samples whereas they are

positively correlated with metabolites in KONZO affected samples. Moreover,

Bifidobacterium pseudocatenulatum, *B. adolescentis*, and *B. angulatum* are positively

correlated in unaffected samples, whereas *B. pseudocatenulatum*, *B. catenulatum*, *B.*

longum are negative in affected patients. A high number of Streptococcus species have a

positive correlation uniquely in Konzo affected samples. This result points to distinct patterns

of associations between species and metabolites in healthy and affected subjects.

Subsequently we used the sPLS regression and identified 30, and 45 metabolites and 235,

and 130 microorganisms significantly contributing to the two first components, in cases and

controls, respectively (Figure 6C.). Interestingly, of the 130 species kept by the sPLS

regression in healthy individuals, 64% were also found in affected individuals, while 46% of

metabolites were preserved between the two conditions. Interestingly, both *mevalonate* and

3-hydroxyisobutyrate have been found to be contributing metabolites in Konzo-affected

subjects. To investigate the implication of interactions between metabolites and species in

Konzo, we sequentially applied MiRKAT and CODA-LASSO on the subset of unique

metabolites found in affected individuals. Consequently, we found that *mevalonate* and *3-*

hydroxyisobutyrate were significantly associated with 14 and 16 associated species,

respectively both exhibiting a large panel of associations (Figures 6D.-6E.). We identified

species which could play a role in Konzo in affecting oxidative response of the metabolism.

For example, *Desulfovibrio desulfuricans* was positively associated with *mevalonate*,

suggesting that increases in the microbial abundance is associated with an augmentation of

metabolite levels. Also, *Clostridioides difficile* exhibited a consistent effect across *mevalonate*

and *3-hydroxyisobutyrate,* suggesting common microbial dynamics between the two

metabolites*. Clostridioides difficile* has already been reported to have an impact in oxidative

stress-related pathways, potentially involved in Konzo [42]. These associations were missed

when applying the clr-lm regression. We validated our findings at a larger scale by a

systematic network analysis from the clr-lm regression and CODA-LASSO (Figures 6F.; S15-

S17). Our results from metagenomics and metabolomics data from Konzo disease highlight

distinct patterns of interactions between microorganisms and metabolites occurring in both

affected and unaffected individuals, where different microbial dynamics are involved.

Discussion

The integration of microbiome and metabolome datasets within statistical frameworks has become a valuable resource for researchers to comprehensively understand the underlying biological mechanisms involved in diseases. Indeed, recent studies in inflammatory bowel disease [43] or cardiometabolic traits [4] have highlighted that pathoetiology may result in the disruption in the complex architecture occurring between the two omics. Understanding these interactions represent therefore a critical avenue for unraveling the biology of complex phenotypes. However, currently, there are no standards on how to integrate these two omics together, pushing researchers to constantly waste a lot of time in their decision-making process. Thus, deciding which method fits best for a specific biological question remains a daunting task, critically limiting the result interpretations and replicability. In this paper, we extensively benchmarked nineteen existent integrative methods to disentangle microbiome-metabolome interactions covering most of the researcher aims: *global associations*, *data summarization*, *individual associations*, and *feature selection* (Figure 1). Based on a comprehensive and realistic simulation study and a real data application, we highlighted best methods depending on the research question and data at-hand, providing important insights about statistical good practices (Table 1) and avenues for future methodological developments (Table 2). Furthermore, a user guide and all the scripts used in this work are available in the GitHub repository associated with the paper to facilitate reproducibility and further advancements in the field.

When evaluating global association methods, our results have pointed to important lessons for practitioners. Indeed, across our three realistic simulation scenarios, the Mantel test is the most powerful method to find associations occurring at a global scale compared to MMiRKAT and the Procrustes Analysis. Also, the method exhibits an adequate control of Type-I error rate showing robustness across a variety of scenarios, considering several underlying data structures, normalizations, and distance kernels. This is an appealing feature

in practice since choosing the right data transformation or distance metric may represent an

important challenge for practitioners. However, by exploiting regression-based frameworks,

MMiRKAT, unlike the Mantel test, can adjust for confounding factors making the correction

for certain bias induced by individual characteristics, such as age, sex, lifestyle, or even

batch effects, possible [14]. However, the method is unable to deal with scenarios with a larger

number of features than individuals, limiting applications in most multi-omics scenarios, as

pointed by [11]. We therefore recommend using Mantel test in most cases or MMiRKAT

filtering out features based on a feature selection approach when confounding is expected.

The Procrustes Analysis could be exploited to have graphical representations but show no

advantages over the Mantel test or MMiRKAT in our benchmark. Importantly, when using the

Mantel test, our results suggest that the Canberra distance on metabolome data is the

poorest choice for detecting global associations across all our scenarios (Figures 3B.). The

application of the Mantel test in our metagenomics-metabolomics use case for Konzo

disease has permitted to identify distinct patterns of global associations between microbiome

and metabolome occurring in affected and unaffected individuals. Thus, our recommendation

here is to apply Euclidean distance on the transformed microbiome data while applying

Euclidean or Manhattan distances on metabolites in most cases.

Data reduction is often used by practitioners for summarizing information through a

small number of components. Having an efficient method which recapitulates variability

across two omics is critical for facilitating subsequent analyses such as visualization or

clustering . We considered five different methods exhibiting specific features to summarize

omics information and found that in addition to being robust to data normalization, RDA is the

most reliable method showing consistency across simulation scenarios and data

normalizations (Figure 3E.). Interestingly, our results point to important impacts of

directionality when applying regression-based methods, such as PLS-Reg or RDA, with

performances drastically increasing depending on whether species or metabolites are

considered as the outcome. This result could be explained by the underlying complex

structure of microbiome data, strongly impacting the capability of methods to capture data

variability. Consistent with this idea, we observed unpredictable performances for MOFA2

with explained variances going from 0% to 100% in all our scenarios (Figure 3E.). Although

MOFA2 has been shown to capture complex relationships for gene expression or

methylation [44] , our results align with a distinct pattern of performance for metagenomics and

metabolomics data. This behavior is explained by the underlying assumptions of MOFA2,

where the use of the method could be restricted to cases where quasi-normality of data is

expected, since other types of data require statistical approximations [18]. We then applied

RDA to our Konzo dataset and found distinct microbiota-metabolites associations involved in

healthy and affected samples (Figures 6A.-6B.). In unaffected patients the metabolites *3-(4-*

hydroxyphenyl)lactate and *5-hydroxyindoleacetate* are identified in positive correlations and

may be linked to the fermentation process of the *Bifidobacterium spp.* positively correlated in

unaffected samples and negatively correlated in affected samples.

In practice another important question for researchers is to determine the relationship

between microbial communities with a variable of interest [35,45]. However, the underlying

compositional structure of microbiome data is an important challenge for model performance.

In this paper we have compared four methods accounting for the compositionality of

predictors with different strategies, a linear regression applied on the CLR transformed

microbiome data, MiRKAT, the log-contrast model, and HALLA. Compared to correlations,

these methods have not been shown significantly more powerful (Figure 4B.). As already

pointed out in the result section, weak powers are mostly explained by the simulation

scenario where we assumed a low signal-to-noise ratio. This behavior could therefore be

expected in real-data applications. Thus, we recommend applying univariate methods to only

a relevant subset of features, avoiding systematic applications across all metabolite-

microbiota pairs. Also, certain univariate methods suffer from inflations of the Type-I error

rate in our scenarios (Figure 4A.), suggesting that method performances are impacted by the

underlying data structures. For example, the log-contrast model exhibits three different

patterns of results across our three scenarios, showing well calibration, conservative, and

liberal behaviors in our Adenomas-, Autism-, and Konzo- based scenarios (Figure 4A.). Our

general recommendation to the reader is to use MiRKAT, since the method has shown

accurate controls of Type-I error rate across microbiome normalizations, permitting

correction for confounding factors. This is particularly important since the choice of the right

normalization could be difficult. However, microbiome transformations could have critical

impacts on result transferability and interpretability, where CLR provides still-correlated

synthetic features and ILR or alpha reduce the dimensional space [30,31]. This result highlights

the need for new compositional data transformations, keeping the original number of features

while linearly independent (Table 2).

Also, one important contribution of this work is to extensively evaluate feature

selection methods. This is particularly crucial for researchers to accurately select metabolites

and microorganisms involved in a specific biological context. Our results point to moderate

performance of multivariate feature selection methods with inconsistent performances across

scenarios and the data transformations considered (Figures 5B.; Figure S12). The best

performances are achieved for univariate feature-selection methods for compositional

predictors, with CODA-LASSO as a good trade-off between sparsity and classification

performances (Figures 5A.), while being sub-compositional coherent. However, all methods

provide discrepancies in performance regarding the data structure. For example, CODA-

LASSO is strongly affected by the proportion of zeros in microbiome data as suggested by

our results in the Adenomas-based scenario. Thus, we recommend in practice to use CODA-

LASSO for scenarios with microbial predictors after removing taxa with a high proportion of

zeros, to ensure the good performance of the method, whereas sPLS-Reg could be exploited

to select features exploiting the inter-omics correlation. We therefore applied both regression

sPLS and CODA-LASSO on the Konzo dataset. Regression sPLS has permitted the

detection of a distinct set of metabolites and microorganisms in affected and unaffected

individuals (Figure 5C.). From the subset of metabolites contributing to Konzo, CODA-

LASSO has highlighted different microbial dynamics of effects (Figures 5F.; Figure S17).

This result is aligned with the model where microorganisms may be connected to a large set

of metabolites. This complex microbiome-metabolome crosstalk has been shown to be

associated with diseases [6]. However, associations found may result in artifact signals since

most feature selection methods benchmarked in this paper suffer from lack of sparsity and

reliability. This result is aligned with previous reports where authors have shown poor

performances of traditional feature selection models [46]. Indeed, most penalized methods are

built upon cross-validation where small perturbations in data may yield drastic changes in

results. Similarly to [46] extending sparse multivariate or univariate methods to knockoff

framework [47] or stability selection [48] should represent interesting avenues for improving both

sparsity and reliability for compositional data [49] (Table 2).

Although our work is focused on evaluating methods for inferring associations

between metagenomics and metabolomics data, additional work is still required to

comprehensively compare methods in a context of prediction. Indeed, predicting

metabolome levels from microbiome data is a flourishing research topic with critical

implications for clinical applications. Indeed, addressing many challenges, such as

integrating and analyzing diverse omics data types, dealing with high-dimensional data,

addressing data heterogeneity, and developing robust computational models that capture

complex relationships between different molecular layers, could be part of further

investigation.

Although our simulation setup can realistically simulate microbiome and metabolome

data, our framework is limited to the "Normal-to-Anything" framework. However, as

discussed by [50], simulating pure compositional data from a Dirichlet distribution induced only

a small correlation between features, which is often unrealistic regarding the biology of the

microbial communities and metabolites. We therefore promote the correlation, zero-inflation

and overdispersion characteristics over a purely compositional structure, with no major

impacts expected on the conclusions. Also, methods selected through the benchmark

assumed a directionality of effects between species to metabolites, other types of

approaches could be considered depending on the biological question. Indeed, in some

context, linking metabolome to microbiome using models such as the Dirichlet regression

could be achieved[33,34]. We explored the performances of such approaches and found poor

results. While we did not elucidate whether the results were explained by the methods

themselves or the simulation setting, we decided to omit these approaches in the current

version of the benchmark since they are not widely used in practice but could be explored in

future works. Our illustration could identify biological species and metabolites involved in

Konzo-related processes, our application is however limited to intersection-based analyses

between affected and unaffected individuals. We are aware that explicit multi-omics models

incorporating the disease information, such as DIABLO [51] or MDiNE [52] are available.

However, future evaluations of differential multi-omics integrative strategies are required to

mechanistically link microbiome and metabolome to diseases from a dynamic perspective at

large scale (Table 2). We argue this aspect is particularly critical to pinpoint the underlying

biological mechanisms hence facilitating precision medicine applications [53,54]

To summarize, in this paper we provide an extensive benchmark of integrative

statistical methods jointly incorporating metagenomics and metabolomics data to infer

associations between species and metabolites. We hope this work will represent a wonderful

opportunity for the multi-omics community to improve research standards and practices. We

anticipate systematic applications of methods identified through this benchmark, as shown

by our illustration on the Konzo dataset, on unified metagenomics-metabolomics resources[55].

This aspect is pivotal for identifying common and unique species-metabolites interactions

occurring at different scales, required for understanding the underlying biological

mechanisms involved in diseases.

Conclusions

In summary, the present study provides to the multi-omics community one of the largest comprehensive benchmarks of statistical frameworks to jointly integrate metagenomics and metabolomics data. Through an extensive and realistic simulation study, we systematically compared nineteen integrative approaches across most of the research questions encountered in practice. We identified the best methods and illustrated their capability to highlight complementary biological processes involved at different scales with an application to microbiome and metabolome data for Konzo disease. Overall, our study provides a robust and replicable comparative framework of integrative methods. We hope this work will serve as a foundation for setting research standards and the development of new efficient statistical models to mutually analyze metagenomics and metabolomics data.

Key Points

- We systematically evaluated nineteen statistical methods for jointly analyzing metagenomics and metabolomics data across a wide range of scientific questions, including global associations, data summarization, individual associations and feature selection.
- We provided general guidelines for practitioners for properly analyzing microbiome and metabolome data together, facilitating result interpretation and replicability.
- We illustrated the best methods through an application to metagenomics and metabolomics data in the gut for Konzo disease highlighting complementary biological results.

587　**Figure 1: Flowchart of the integrative methods selected across the benchmark and**

588　**their related performance metrics depending on the research question**.

Figure 2: Overview of the simulation setup based on real datasets (**A.**) Three

microbiome-metabolome datasets were selected, each exhibiting different data structures

and correlations. We reported the sample size (N) and the number of features (P), as NxP,

for each dataset. (**B.**) Realistic datasets were simulated using the "Normal-to-

Anything" (NORtA) framework. First, we estimated sparse microbiome and metabolome

correlation networks using SpiecEasi [56]. Second, correlated multivariate Gaussian

distributions were generated for both microbiome and metabolome datasets using the

correlation structures estimated in the previous step. Third, Gaussian distributions were

converted into arbitrary distributions matching the original data

structures (**C.**) Associations between species and metabolites were specified mimicking the

complex entanglement between the two omics. For each dataset, proportions of associated

602   features vary between 1% and 10%, with association strengths randomly picked from a

603   Gaussian distribution.

Figure 3: Performance of the multivariate methods for global associations or data

summarization

(**A.**) QQ-Plot of the Mantel test and the Procrustes Analysis across microbiome

normalizations and distance kernels. For the Mantel test we considered Spearman's method

for computing the global association between the two datasets. P-values for both the Mantel

test and Procrustes Analysis were obtained empirically based on 1,000 replicates. (**B.**)

Power of the Mantel test and the Procrustes Analysis across microbiome normalizations and

distance kernels. For the Mantel test we considered Spearman's method for computing the

global association between the two datasets. P-values for both the Mantel test and

Procrustes Analysis were obtained empirically based on 1,000 replicates. P-values <= 0.05

were considered as significant. (**C.**) QQ-Plot of MMiRKAT, the Mantel test and the

Procrustes Analysis across microbiome normalizations and distance kernels. Points below

the straight line refer to a conservative behavior in the result section. To accommodate

MMiRKAT (fewer number of features than sample size), we considered scenarios with a

smaller number of features in both omics than number of individuals (See supplementary

methods) (**D.**) Power of MMiRKAT, the Mantel test and the Procrustes Analysis across

microbiome normalizations and distance kernels. To accommodate MMiRKAT (fewer

number of features than sample size), we considered scenarios with a smaller number of

features in both omics than number of individuals (See supplementary methods). P-values

for both the Mantel test and Procrustes Analysis were obtained empirically based on 1,000

replicates. P-values <= 0.05 were considered as significant. (**E.**) Proportion of explained

variance for the data summarization methods across different data structures and

normalizations considering the log metabolome. Data summarization methods were

compared considering scenarios with a number of features half the number of individuals

(See supplementary methods).

Figure 4: Performance of the individual association methods for compositional

predictors

To accommodate long running times due to the number of pairs between species and

metabolites we considered scenarios with a number of features half the number of

individuals (See supplementary methods) (**A.**) QQplots of the individual association methods

across our three simulation settings. (**B.**) Power of the individual association methods across

our two main scenarios. P-values <= 0.05 were considered as significant. For the clr-lm

method and HALLA, p-values were combined using ACAT [57] in order to provide similar

comparisons with the log-contrast regression and MiRKAT (See Methods). For MiRKAT, we

reported Type-I error rate and power using the ILR transformed microbiome data and the log

transformed metabolites, while for HALLA we considered the CLR transformed microbiome

and the log metabolome. The straight line represents the background ACAT-combined

647　power using the Spearman's correlation on the CLR microbiome and the log metabolome.

648　Powers were averaged over 1,000 replicates.

Figure 5: Performance of the feature selection methods for providing sparse and

reliable subset of elements across our two scenarios.

(**A.**) Performance of univariate feature selection methods considering microorganisms as

covariates across our three settings. Metabolites were log transformed before running

methods. Performances were calculated on 100 replicates. For CODA-LASSO in the Konzo

scenario, we adapted the simulation setting, selecting 300 species and 600 metabolites for

accommodating running times of the method (See supplementary methods). (**B.**)

Performance of multivariate feature selection methods. Metabolites were log transformed

before running methods. sPLS-Reg1 and sPLS-Reg2 correspond to the sPLS-Reg with

X=microbiome and X=metabolome, respectively.

Figure 6: Application of best strategies highlights complementary biological

interactions between microorganisms and metabolites in Konzo data

(**A.**) Proportion of cumulative explained variance in Metabolome and Microbiome datasets in

both affected and unaffected individuals (**B.**) Top-20 of the most contributing species and

metabolites on the first RDA component in healthy and affected samples. Positive

correlations were identified by a **+**, while negative correlations were identified with a – sign**.**

Projection of metabolites (red) and microorganisms (blue) into the 2D regression sPLS space

in (**C.**) affected and (**D.**) unaffected individuals. Features with null loadings were removed

from the analysis. (**E.**) Coefficients provided by the CODA-LASSO across *mevalonate* and 3-

671   *hydroxyisobutyrate* identified only in Konzo by the regression sPLS. Positive coefficients

672   were identified by a +, while negative coefficients were identified with a – sign (**F.**) Network

673   between *mevalonate* and 3-*hydroxyisobutyrate* and their corresponding associated species

674   found by CODA-LASSO. Positive associations were represented by green edges and

675   negative associations by pink edges.

Scientific Question	Research Aim	Best Method	Pros	Cons	Implementation
Is there any relationship between microorganisms and metabolites at a global level?	Global associations	Mantel Test	Robust to data normalization and distance kernels Computationally efficient	Cannot incorporate covariables to adjust for	`Vegan` R package
Are microbiome and metabolome datasets summarizable through a limited number of components?	Data summarization	RDA	Robust to data normalization and distance kernels	Can only capture linear effects Sensible to directionality	`Vegan` R package
Can we identify associations between metabolites and species?	Individual associations	MiRKAT	Allow adjustment for covariates Robust to microbiome normalization	Limited to few families of generalized linear models	`MiRKAT` R package
Can we identify core microorganisms and metabolites?	Feature selection (univariate)	CODA-LASSO (compositional covariates)	Compositional and sub-compositional coherent No need to data transformation Allow adjustment for covariates	Limited to few families of generalized linear models Long running times in high-dimensional problems	`Coda4microbiome` R package
	Feature selection (multivariate)	sPLS	Flexible framework Efficiently account for within- between- correlation Robust to directionality	Tuning parameters	`mixOmics` R package

Table 1: Summary of best methods depending on the research question

Objective	Methods and Limits	Methodological avenues
Data normalization	- **CLR**: provides still-correlated features in the original space - **ILR**; **alpha**: are "black-box" transformations providing uncorrelated features in a restricted space	Data normalizations providing uncorrelated features in the original space for facilitating result interpretation.
Mechanistic interpretation	- **Log-contrast**; **CODA-LASSO:** unable to provide a mechanistic view of modifications between microbiome and metabolome data	Applications of differential integrative strategies such as DIABLO [51] or Network-based model to jointly study the modifications of microorganism and metabolite co-occurrence networks [52]
Feature selection	- **CODA-LASSO; sPLS:** lack of sparse solutions	Extension to knockoff framework [47] or stability selection [48] for improving feature selection performances

Table 2: Overview of avenues for future methodological developments to jointly analyze metagenomics and metabolomics data. Three research objectives with their corresponding methods were identified as important avenues for future methodological developments.

Methods

Simulation setups

Microbiome and Metabolome data were simulated using the "*Normal to Anything*" approach (NORtA), already used for different multi-omics analyses [50,52,58]. An appealing feature of the NORtA algorithm is to provide a framework capable of simulating data from any marginal distribution while specifying arbitrary correlation structures. Thus, we generated both synthetic microbiome and metabolome data with realistic structures from three different microbiome-metabolome datasets. We selected one high-dimensional metagenomics-metabolomics dataset from a recent study in Konzo disease [35] exhibiting correlated and over-dispersed microbiome counts, while metabolomics data highlight correlated count data. Under this scenario microbiome data were assumed to follow a negative binomial distribution, and metabolome a Poisson distribution. Then, we chose an intermediate-size microbiome-metabolome dataset in Adenomas [59] where species are correlated and zero-inflated counts with a general zero-inflated negative binomial underlying structures, when metabolome were correlated log-normally data. Finally, we picked one small metagenomics-metabolomics from autism spectrum disorder [60], where species have correlated zero-inflated negative binomial structures and metabolites a Poisson distribution. We estimated sparse correlations networks of species or metabolites using SpiecEasi as already used in a variety of contexts [56]. We simulated correlated multivariate Gaussian distributions where the correlation matrices were estimated in the previous step. Normal distributions were converted into any correlated arbitrary distributions using the copula space matching the original data structure. These steps were summarized in Figure 1 of the main manuscript. Several data transformations for both microbiome and metabolome were evaluated across our scenarios to account for data structure. Briefly, we evaluated the impact of three microbiome normalizations (CLR, ILR, and alpha transformations) on method performances. Data normalizations were summarized across methods and simulation scenarios in Table

S1. To evaluate the Type-I error control, we independently generated two datasets under the

null hypothesis of no association between microorganisms and metabolites. Under the

alternative hypothesis, we varied both the number of associations between microorganisms

and metabolites and the strength of associations, mimicking microbiome-metabolome

complex interdependence. Methods were compared under three realistic scenarios, where

both the numbers of features (species or metabolites), the sample size, and the underlying

data structures varied. Technical details on the simulation and additional scenarios were

provided in the supplementary. Under all scenarios we simulated 1,000 replicates.

Simulation setup was summarized in Figure 2.

Statistical Analyses

725   Let's assume X and Y, a matrix of microbiome and metabolome, collected on the same set of

726   samples, of size n x p and n x q, where n is the number of samples, p the number of

727   microbiota and q the numbers of metabolites, respectively. X_{ij} represents the jth

728   microorganism in the ith sample, with $j = 1,2,..,p$, while Y_{ik} is the kth metabolite in the ith

729   sample, where $k=1,2,...,q$. For the sake of simplicity we considered the case where p=q.

Global Associations

In this paper we refer to global association methods, the statistical approaches providing

global associations between microbiome and metabolome data (Figure 2). As already

presented in Deek et al., 2024, we considered three general methods, the Mantel test [13],

MMiRKAT [14], and the Procrustes Analysis [12], considering a variety of data transformations

and distance kernels.

The Mantel test [13] is a statistical framework measuring global correlation between two

datasets measured on the same set of samples. Traditionally, the Mantel test is applied on

distance or dissimilarity matrices. Here we considered three different distance kernels

applied on the original and log-transformed metabolome dataset, Euclidean, Canberra and

Manhattan distances. Also, we applied the Euclidean distance on a normalized microbiome matrix, since this projection leads to more natural interpretations [24] (Table S1). The Mantel test was applied considering either Pearson's or Spearman's correlation, to account for linear and rank-based associations. P-values were obtained empirically based on permutations using 1,000 replicates. The Mantel test was performed using the *vegan* R package.

MMiRKAT is the multivariate extension of MiRKAT providing global association between a distance-transformed microbiome dataset (referred to as kernel function) and a low dimensional continuous multivariate phenotype [14]. Briefly, the model regresses the multivariate outcome in terms of the non-parametric kernel transformed microbiome up to a gaussian error term. Consistent with distance kernels used in the Mantel test, we considered Euclidean, Canberra and Manhattan distances applied on the transformed microbiome data as kernel-based transformations, while the entire original or log transformed metabolome matrix was considered as the outcome (Table S1). Significance testing is performed by computing kernel specific p-values using the exact davies method. MMiRKAT was applied using the `MiRKAT` R package.

Procrustes Analysis is a method facilitating high-dimensional visualisation of two or more datasets. Traditionally, the method linearly translates, scales and rotates principal components minimizing the Euclidean distance between the two omics (referred to as Procrustes superimposition). Since the two datasets have been superimposed inter-omics distances can be computed for each row, where smaller distances refer to higher adequation between the two omics. Formal testing is achieved by empirically computing the p-value using 999 permutation samples, comparing the observed sum of squared deviation (square of the difference between distances of the same sample) and the resampled ones.

As introduced in the *simulation setups* subsection, when applying the global association methods, we normalized microbiome data using CLR, ILR, and alpha transformations, while metabolome data were considered on the original and log scale.

Data Summarization

In this benchmark, we considered 4 distinct data summarization methods, encompassing

CCA, PLS, RDA, and MOFA2. Briefly, all these methods seek to summarize data information

through latent factors.

CCA initially proposed by [15] summarizes the relationship between two datasets by

finding linear combinations of the two matrices maximizing the correlation. CCA was

performed using the `CCA` R package.

Unlike CCA, PLS seeks for linear combinations maximizing the covariance between

the two datasets [16]. Also, in PLS directionality of effect of one matrix on the other can be

taken into account, leading to two general forms of PLS, regression and canonical,

respectively [17]. Thus, canonical PLS and regression PLS were applied with the `mixOmics` R

package.

Moreover, RDA is a two-step procedure, combining multivariate linear regression and

PCA [17]. In the first step, a multivariate linear regression is fitted between each element of the

matrix of responses and the matrix of predictors. Then a PCA is applied on the matrix of

predicted values. RDA was performed using the `vegan` R package.

Finally, MOFA2 is an unsupervised multi-omics framework able to untangle sources

of variability shared by different omics [18]. MOFA2 is a Bayesian probabilistic model able to

find latent factors linking two omics by putting priors on model parameters. We applied

MOFA2 using the related R package `MOFA2` with default parameters.

Except for MOFA2 where the best number of latent factors were chosen by the

model, we kept all the components corresponding to the minimal number of features

observed in one dataset.

Individual associations

When individual relationships are of interest, we consider different regression models taking

into account the compositionality induced by microbiome data as predictors.

Indeed, for microbiota that are explanatory variables, we fitted four different models, a

log-linear regression on the CLR transformed microbiome, a log-contrast model [29],

MiRKAT[14], and HALLA [37].

Formally the log-linear model of the CLR transformed microbiome (referred to as clr-

lm in the Result section) is given by:

$$E(Y_{ik}^* | X_{ij}^*, \beta_j) = \beta_0 + X_{ij}^* \beta_j + \epsilon_i, \forall (j, k)$$

where Y^* is the log transformed metabolome matrix and X^* the CLR transformed

microbiome data. Although the compositionality in the microbiome data is taken into account

using the CLR transformation, the previous model is not robust to the subset of

microorganisms, not preserving the sub-compositionality feature of microbiome data. Thus,

the log-contrast model by imposing a zero-sum constraint on regression coefficient

preserves the scale invariance property needed to ensure the sub-compositionality

characteristic of microbiome data [29]. Formally, the model is given by:

$$E(Y_{ik}^* | X_{i.}, \beta) = X_{i.}\beta + \epsilon_i, \sum_{j=1}^{p} \beta_j = 0$$

Under the log-contrast framework, following [29] we applied the global significance F-test in

order to determine whether there is an association between at least one microorganism and

a given metabolite. The log-contrast model was performed using the *Compositional* R

package. Aligned with the idea of global association, MiRKAT is a statistical framework

exploiting semi-parametric kernel machine regression framework in order to summarize

microbiome relationships [14]. One major feature of MiRKAT compared to other approaches is

permitting the use of several distance kernels at the same time. This is particularly appealing

since it is often unclear in practice which kernel is the more suitable. In our context, we

considered Euclidean, Canberra and Manhattan distances either on original or transformed

microbiome data, while considering the original or log transformed metabolome as outcome.

MiRKAT was applied with the `MiRKAT` R package. Finally, we evaluated HALLA, a

hierarchical All-against-All statistical framework [37]. The model was initially developed to

incorporate both homogeneous and heterogeneous datasets and permits the clustering of

features of different omics adequately controlling the False Discovery Rate. HALLA was

applied through the corresponding *halla* python package with default parameters,

considering the CLR-transformed and original microbiome and the log-transformed and

original metabolome.

Feature Selection: Univariate

Adapted from [30] we considered two different models accounting for compositional predictors,

when fitting models with metabolites as outcomes. Firstly, we considered the CLR-LASSO,

performing the CLR transformation on microbiome data before fitting a univariate or

multivariate LASSO log-linear regression [20]. We referred to LASSO and MLASSO in the

Results section. Formally for a metabolite k, the LASSO log-linear model is given by:

$$\sum_{i=1}^{n}(Y_{ik}^* - \sum_{j=1}^{p} X_{ij}\beta_j)^2 + \lambda \sum_{j=1}^{p} |\beta_j|$$

with Y^* is the log transformed metabolome matrix and X^* the CLR transformed

microbiome data. Best penalty parameters λ were chosen using a 10-fold cross-validation

through a 10 step grid-search from 0.01 to 1. LASSO or MLASSO models were fitted using

the `glmnet` R package.

Then, consistently with the log-contrast model, we applied the coda-LASSO

considering a log-linear response of the metabolome level. Briefly, the coda-LASSO is a

penalized log-contrast model, permitting to select only the most contributive features, with a

zero-sum constraint on regression coefficients, ensuring scale invariance, a property needed

for compositional data. The model considered in the coda-LASSO framework is a direct

extension of the model initially proposed by [61]. This latter fits a two-stage model on all

possible log-ratios between each pair of microbiota, leading to sparse solutions. The R

package `coda4microbiome` with the default parameters were used when applying coda-

LASSO.

Feature Selection: Multivariate

Sparse Canonical Correlation Analysis (sCCA) [21] and sparse Partial Least Squares (sPLS) [22]

are two penalized extensions of CCA and PLS permitting to summarize data information

through latent factors while proceeding to feature selection.

For sCCA we used L1 penalty on the two datasets, only keeping features contributing

on the two first components. Best penalty parameters were found using 25 permutation-

based samples considering a 0.1-step grid search from 0.01 to 1. sCCA were performed

using the `PMA` R package.

Consistently, canonical and regression sPLS were tuned using a 10-fold cross

validation, considering a 5 step grid search ranging from 5 to 25 in our low dimensional

setting and from 10 to 50 in our high dimensional scenario. We maximally kept two

components in order to select the most contributive features. sPLS were applied using the

`mixOmics` R package. For both sCCA and sPLS, features on the two first components with

non-null loadings were considered as informative variables hence were kept to compute the

performance metrics.

Data and Distance Kernel Transformation

Most methods used in practice need either a normalization step or a distance-based transformation in order to be applied properly on compositional or over-dispersed data. Thus, we considered in our main analyses three data normalizations for microbiome and one data transformation for metabolome data. The choice of data normalization depends on the research objective. We referred to specific data and distance kernel transformations for each family of methods in the subsection *Statistical analysis*.

To consider the compositionality of microbiome data while keeping the original number of features, we considered the centered log-ratio transformation (CLR) [62] applied on the original count data. This normalization was considered across all the different considered methods. The CLR transformation computes the log ratio of each microbiota count on the geometric mean for a given individual. Formally, the CLR transformation is given by:

$$CLR(X_j) = \log(\frac{X_j}{g(X)})$$

where $g(X)$ is the geometric mean over all the microorganisms for one sample. This transformation projects the simplex onto a D compositional subspace under a zero-sum constraint [31,63]. By keeping the original number of features the CLR transformation is a one-one transformation, facilitating result interpretation which is an appealing feature in practice. We therefore considered the CLR transformation as the reference normalization when individual associations or feature selection are of interest. However, the CLR transformation does not ensure independence between features and sub-compositionality coherence. This latter represents a major limitation for distance-based methods due to singular covariance matrices. Thus, when distance between features is of interest, we consider the isometric log-

894   ratio (ILR) [32] and alpha transformation [31]. Intuitively, these two transformations project the

895   original D-dimensional space into an independent D-1 quasi-orthogonal space, the main

896   difference laying into the transformation used. The ILR transformation projects the original

897   data onto a Euclidean space. Formally:

898
$$ILR(X_j) = \sqrt{\left(\frac{j}{j+1}\right)} \log\left(\frac{\prod_{j=1}^{D-1} X_j}{X_j + 1}\right)$$

900   While the alpha transformation is a Box-Cox type transformation, where the

901   transformed data follow a multivariate distribution after a suitable alpha-transformation [31].

902   This facilitates the use of traditional multivariate methods. We therefore considered

903   the ILR and alpha transformations when evaluating global associations, and data

904   summarization methods, since the correspondence with the original features does not really

905   matter. Moreover, since the metabolome data have been shown to be log-normally

906   distributed we applied a natural log transform on the original count data [26].

907   Also, we applied different distance kernel transformations before performing some

global association or individual association analyses, highlighting different patterns of

relationships occurring among features. Briefly, we considered Euclidean, Canberra and

Manhattan distances on metabolome matrices of original and log transformed counts, while

considering the Euclidean distance on original and transformed microbiome data.

Interestingly, as presented by [24], the Euclidean distance applied on CLR transformed data

corresponds to the Aitchison distance. This latter has been shown superior to the Bray-Curtis

dissimilarity, representing a true linear relationship, while more stable to data subsetting or

aggregating [24], and will be considered as our reference method here. All data and distance

kernel transformations depending on the method used were summarized in Table S1.

Performance Metrics

Since all the methods considered in this benchmark exploit different statistical

concepts, the outputs cannot be directly compared. Consequently, we opted for several

performance metrics depending on the research question.

Indeed, for global and individual association methods, we systematically evaluated

model performance through Type-I error control and power, since the considered methods

are frequentist frameworks. Briefly, Type-I error control assesses whether a method provides

a good control of false positives at a given significance threshold. In other words, under the

null hypothesis of no association, at a significance threshold equals to 0.05 we maximally

expect 5% of false positives for a method that performs well. A value above the expected

rate is considered as liberal, while a value below conservative. Type-I error control was

evaluated using the quantile-quantile plot of the -log10 of p-values. Similarly, the power is the

capability of a method to detect a significant signal (at a given significance threshold) when

we know that there is an association. In practice, researchers want methods maximizing the

power while accurately controlling the Type-I error.

Data summarization methods were compared based on the proportion of the

explained variance. We refer to explained variance, the amount of data variability kept by

latent factors built by methods.

Moreover, inspired from [46] when univariate and multivariate feature selection

methods were evaluated, we considered sparsity and reliability as primary performance

metrics. For univariate methods sparsity corresponds to the total number of relevant

associations found by the method (here with coefficients different from zero), while reliability

is the capability of a method to accurately discriminate true from false associations between

two features. However, we adapted both sparsity and reliability calculation when considering

multivariate feature selection methods. Indeed, sparsity was computed by the total number of

nonzero coefficients on the total number of features while reliability was adapted to capture

the model performance to keep true contributive variables within the two datasets. Reliability

was evaluated using the specificity and sensitivity. In practice, researchers are looking for

sparse methods with methods discriminating both the true associations from false

associations (high sensitivity) and true non-associations from false non-associations (high

specificity). Performance metrics depending on the considered method were summarized in

Figure 1. Technical details on the performance metric calculation and adaptations were

provided in the next subsections.

Explained Variance

In order to provide fair comparisons between data summarization methods we

extended the redundancy index initially proposed by [64] for Canonical Correlation Analysis

(CCA) [15] to Partial Least Squares (PLS) [16]. Following [64], the redundancy index is the

proportion of explained variance kept in the latent factors. See [64] for more details on the

redundancy index calculation. Although exhibiting structural differences, i.e., CCA maximizes

the correlation while PLS the covariance, we argue that extending the redundancy index to

PLS provides a good proxy of the data variability contained in the components.

Specificity/Sensitivity

When comparing feature selection methods, we used the specificity and sensitivity to

determine the classification performance for the models considered. Briefly, the specificity is

a metric of prediction performance computed based on the ratio between the number of true

negatives and the total number of negative elements. Equivalently, the sensitivity is

computed based on the ratio between the number of true positives and the total number of

positive elements. From a standard confusion matrix:

Predicted/Ground Truth	Non-Associated	Associated

Non-Associated	#True negatives	#False negatives
Associated	#False positives	#True Positives

The specificity is obtained by: #True negatives/(#True negatives + #False positives) and the

sensitivity by: #True positives/(#True positives + #False negatives).

For univariate feature selection methods, the specificity and sensitivity are obtained

using the true set of associations between taxa and metabolites, i.e, with coefficients

different from zero, while for multivariate feature selection methods, metrics are computed

with the true set of associated features, i.e, with loadings different from zero.

Sparsity

When evaluating the feature selection methods, we compared methods using

sparsity. Briefly the sparsity is the method ability to provide the as smaller as possible set of

features, either with coefficients or loadings different from zero, depending on the considered

method.

Formally the sparsity is given by:

987
$$Sparsity = \sum_{i=1}^{p} \frac{I(\beta_i \,! = \, 0)}{p}$$

989   where β is either the coefficient for an association from a univariate feature selection

990 method or corresponds to a loading in a multivariate feature selection. p is the total number

991 of possible associations/features.

P-value combinations

In order to provide fair comparisons across our individual association methods with

compositional predictors, we combined p-values using the Aggregated Cauchy-based test

(ACAT) [57] when CLR-lm, HALLA, and correlations were considered. Indeed, for a large

number of microbiota and metabolites, applying univariate methods can lead to p x q

possible correlations, limiting the statistical power due to multiplicity. Similarly to the log-

contrast model or MiRKAT, in practice one can be interested in having the global association

between one metabolite and several microorganisms. Thus, in order to provide a powerful

method controlling the Type-I error rate well, we combined p-values for all microorganisms in

a given metabolite using ACAT [57], resulting from p p-values. We argue that this approach

may result in more detected signals, since the multiplicity burden is drastically reduced.

Briefly, ACAT is a method combining p-values through a Cauchy distribution.

Formally for one metabolite, the aggregated p-values across the p microbiota can be

approximated by:

$$0.5 - \frac{\arctan(\frac{T}{w})}{\pi}$$

1007

1008

1009   where $T = \sum_{j=1}^{p} w_j \tan(\{0.5 - p_j\}\pi)$.

1010   One important feature of ACAT compared to other aggregation methods, such as

1011   Fisher's method, is that the method can efficiently control the Type-I error rate even in

1012   presence of correlated p-values, while maintaining good power [57]. Also, the method does not

1013   require any resampling step, facilitating its application to large datasets.

Konzo data analysis workflow

Stool samples collected from individuals from study populations in Masi-Manimba (n = 65) and Kahemba (n = 106) regions of the Democratic Republic of the Congo were used for metagenomics and metabolomics assessment, where a proportion of the cohort is affected with Konzo. Shotgun metagenomics sequencing was performed on DNA extracted from ~250mg of stool with the goal of generating ~50 million reads per sample. Data was analyzed following a similar methodology as described previously using Kraken2 and Bracken for taxonomic classifications [35] . Additionally, stool was analyzed by the company Metabolon, harnessing their large in-house repository of rigorously tested and validated metabolites that are used as reference, to detect metabolites present in the samples. Analysis was performed on the 1,098 microorganisms and 1,340 metabolites across the 171 individuals unconditionally of the disease status. Microbiome data at the genus level were normalized using the CLR transformation while metabolome data were log transformed. The workflow was as follows 1) global association, 2) data summarization 3) univariate and multivariate feature selection and 4) individual associations. Moreover, we considered microorganisms as explanatory variables and the microorganisms as outcomes. For global associations, since the number of features exceeds the number of individuals, we performed the Mantel. Then, we applied RDA in order to detect the most contributing microorganisms and metabolites on the first components. Following the same methodology as presented in the Method section, we extracted the core microorganisms and metabolites using the regression sPLS, keeping only the features with nonzero loadings on the two first components. We finally applied the clr-lm regression and CODA-LASSO in order to highlight contributions of microorganisms on metabolites. We summarized the workflow in Figure S13.

1038

Ethics approval and consent to participate

1040   Not applicable

Consent for publication

1042   Not applicable

Availability of data and materials

Codes to reproduce the analyses are available at:

https://github.com/lmangnier/Benchmark_Integration_Metagenomics_Metabolomics. Data to

run the code are available at: https://doi.org/10.6084/m9.figshare.25234915. The simulated

data are produced using the simulate_data.R script available in the same Github repository.

R 4.2.2 is required to reproduce results from the paper. Data for metagenomics and

metabolomics for Autism and Adenomas were available at https://github.com/borenstein-

lab/microbiome-metabolome-curated-data. The metagenomics and metabolomics data for

Konzo disease are available upon request from Matthew S. Bramble.

Competing interests

The authors declare no competing interests.

Funding

Not applicable

Authors' contributions

LM designed, conducted, performed the data analysis, and wrote the manuscript. AB and MM performed the data analysis. AM, AB, MPSB and NV wrote the manuscript. AB, MPSB, MSB, and AD revised the manuscript. All authors read and approved the final version of the manuscript.

Loïc Mangnier is a research fellow in the Arnaud Droit Lab affiliated to the Laval University

Margaux Mariaz is an intern in Biostatistics in the Arnaud Droit Lab affiliated to the Laval University

Neerja Vashist is a postdoctoral fellow in the Arboleda Lab, in the Department of Pathology and Laboratory Medicine at UCLA

Antoine Bodein is a research fellow in the Arnaud Droit Lab affiliated to the Laval University

Marie-Pier Scott Boyer is a research fellow in the Arnaud Droit Lab affiliated to the Laval University

Alban Mathieu is a research fellow in the Arnaud Droit Lab affiliated to the Laval University

Matthew Bramble is an associated professor at The George Washington University School of Medicine and Health Sciences

1075 **Arnaud Droit** is a full professor in the Department of molecular medicine at Laval University

1076

Acknowledgments

1078 We would like to thank members of the Arnaud Droit Lab, particularly Louis-Maël Gueguen,

1079 Thomas Jeanne, and Tania Cuppens for their insightful comments on the manuscript.

1080

References

1. Rohart, F., Gautier, B., Singh, A. & Cao, K. A. L. mixOmics: An R package for 'omics feature selection and multiple data integration. *PLoS Comput. Biol.* **13**, (11 2017).

2. Tang, Z. Z. *et al.* Multi-omic analysis of the microbiome and metabolome in healthy subjects reveals microbiome-dependent relationships between diet and metabolites. *Front. Genet.* **10**, (2019).

3. Vernocchi, P., Chierico, F. D. & Putignani, L. Gut microbiota profiling: Metabolomics based approach to unravel compounds affecting human health. *Frontiers in Microbiology* vol. 7 Preprint at https://doi.org/10.3389/fmicb.2016.01144 (7 2016).

4. Fromentin, S. *et al.* Microbiome and metabolome features of the cardiometabolic disease spectrum. *Nat. Med.* **28**, 303–314 (2 2022).

5. Dan, Z. *et al.* Altered gut microbial profile is associated with abnormal metabolism activity of Autism Spectrum Disorder. *Gut Microbes* **11**, 1246–1267 (9 2020).

6. Lee-Sarwar, K. A., Lasky-Su, J., Kelly, R. S., Litonjua, A. A. & Weiss, S. T. Metabolome-Microbiome Crosstalk and Human Disease. *Metabolites* **10**, (2020).

7. Lavelle, A. & Sokol, H. Gut microbiota-derived metabolites as key actors in inflammatory bowel disease. *Nat. Rev. Gastroenterol. Hepatol.* **17**, 223–237 (2020).

8. Puig-Castellví, F. *et al.* Advances in the integration of metabolomics and metagenomics for human gut microbiome and their clinical applications. *Trends Analyt. Chem.* **167**, 117248 (2023).

9. Noecker, C., Eng, A., Muller, E. & Borenstein, E. MIMOSA2: a metabolic network-based tool for inferring mechanism-supported relationships in microbiome-metabolome data. *Bioinformatics* **38**, 1615–1623 (2022).

10. Reiman, D., Layden, B. T. & Dai, Y. MiMeNet: Exploring microbiome-metabolome

1105 relationships using neural networks. *PLoS Comput. Biol.* **17**, e1009021 (2021).

1106 11. Deek, R. A., Ma, S., Lewis, J. & Li, H. Statistical and computational methods for

1107 integrating microbiome, host genomics, and metabolomics data. *Elife* **13**, (2024).

1108 12. Gower, J. C. Generalized procrustes analysis. *Psychometrika* **40**, 33–51 (1975).

1109 13. Mantel, N. The Detection of Disease Clustering and a Generalized Regression

1110 Approach. *Cancer Res.* **27**, 209–220 (1967).

1111 14. Zhao, N. *et al.* Testing in microbiome-profiling studies with MiRKAT, the microbiome

1112 regression-based kernel association test. *Am. J. Hum. Genet.* **96**, 797–807 (5 2015).

1113 15. Hotellﾐng, H. RELATIONS BETWEEN TWO SETS OF VARIATES. *Biometrika* **28**, 321–

1114 377 (1936).

1115 16. Abdi, H. Partial least squares regression and projection on latent structure regression

1116 (PLS Regression). *Wiley Interdiscip. Rev. Comput. Stat.* **2**, 97–106 (2010).

1117 17. Legendre, Pierre & Louis. *Numerical Ecology.* (2012).

1118 18. Argelaguet, R. *et al.* Multi-Omics Factor Analysis—a framework for unsupervised

1119 integration of multi-omics data sets. *Mol. Syst. Biol.* **14**, (6 2018).

1120 19. Al Bataineh, M. T. *et al.* Uncovering the relationship between gut microbial dysbiosis,

1121 metabolomics, and dietary intake in type 2 diabetes mellitus and in healthy volunteers: a

1122 multi-omics analysis. *Sci. Rep.* **13**, 17943 (2023).

1123 20. Tibshirani, R. Regression Shrinkage and Selection via the Lasso. *J. R. Stat. Soc. Series

1124 B Stat. Methodol.* **58**, 267–288 (1996).

1125 21. Witten, D. M., Tibshirani, R. & Hastie, T. A penalized matrix decomposition, with

1126 applications to sparse principal components and canonical correlation analysis.

1127 *Biostatistics* **10**, 515–534 (7 2009).

1128 22. Chun, H. & Keleˌs, S. K. Sparse partial least squares regression for simultaneous

1129 dimension reduction and variable selection. *J. R. Stat. Soc. Series B Stat. Methodol.* 3–

1130 25 (2009).

1131 23. Pérez-Cobas, A. E., Gomez-Valero, L. & Buchrieser, C. Metagenomic approaches in

1132 microbial ecology: an update on whole-genome and marker gene sequencing analyses.

Microb Genom **6**, (2020).

24. Gloor, G. B., Macklaim, J. M., Pawlowsky-Glahn, V. & Egozcue, J. J. Microbiome

datasets are compositional: And this is not optional. *Front. Microbiol.* **8**, (11 2017).

25. Greenacre, M. Compositional Data Analysis. *Annual Review of Statistics and Its*

Application **8**, 271–299 (2021).

26. Xia, Y. & Sun, J. *Statistical Data Analysis of Microbiomes and Metabolomics.* (American

Chemical Society, 2022).

27. Zhou, B., Xiao, J. F., Tuli, L. & Ressom, H. W. LC-MS-based metabolomics. *Mol.*

Biosyst. **8**, 470–481 (2012).

28. Pang, Z. *et al.* MetaboAnalyst 6.0: towards a unified platform for metabolomics data

processing, analysis and interpretation. *Nucleic Acids Res.* **52**, W398–W406 (2024).

29. Aitchison, J. & Bacon-Shone, J. Log contrast models for experiments with mixtures.

Biometrika **71**, 323–353 (1984).

30. Susin, A., Wang, Y., Cao, K. A. L. & Calle, M. L. Variable selection in microbiome

compositional data analysis. *NAR Genomics and Bioinformatics* **2**, (6 2020).

31. Tsagris, M. *et al.* Improved Classification for Compositional Data Using the α-

transformation. *J. Classification* **33**, 243–261 (2016).

32. Egozcue, J. J., Pawlowsky-Glahn, V., Mateu-Figueras, G. & Barceló-Vidal, C. Isometric

Logratio Transformations for Compositional Data Analysis. *Math. Geol.* **35**, (2003).

33. Hijazi, R. H. & Jernigan, R. W. Modeling Compositional Data Using Dirichlet Regression

Models. *Journal of Applied Probability & Statistics* **4**, 77–91 (2009).

34. Chen, J. & Li, H. Variable selection for sparse Dirichlet-multinomial regression with an

application to microbiome data analysis. *Ann. Appl. Stat.* **7**, 418–442 (3 2013).

35. Bramble, M. S. *et al.* The gut microbiome in konzo. *Nat. Commun.* **12**, (12 2021).

36. Clos-Garcia, M. *et al.* Multiomics signatures of type 1 diabetes with and without

albuminuria. *Front. Endocrinol.* **13**, 1015557 (2022).

37. Ghazi, A. R. *et al.* High-sensitivity pattern discovery in large, paired multiomic datasets.

Bioinformatics **38**, i378–i385 (2022).

38. Scott, D. A. V. *et al.* Bayesian compositional regression with microbiome features via

variational inference. *BMC Bioinformatics* **24**, 210 (2023).

39. Nguyen, Q. P. *et al.* Associations between the gut microbiome and metabolome in early

life. *BMC Microbiol.* **21**, 238 (2021).

40. Nilsen, M. S. *et al.* 3-Hydroxyisobutyrate, A Strong Marker of Insulin Resistance in Type

2 Diabetes and Obesity That Modulates White and Brown Adipocyte Metabolism.

Diabetes **69**, 1903–1916 (2020).

41. Tricarico, P. M., Crovella, S. & Celsi, F. Mevalonate Pathway Blockade, Mitochondrial

Dysfunction and Autophagy: A Possible Link. *Int. J. Mol. Sci.* **16**, 16067–16084 (2015).

42. Weiss, A., Lopez, C. A., Beavers, W. N., Rodriguez, J. & Skaar, E. P. Clostridioides

difficile strain-dependent and strain-independent adaptations to a microaerobic

environment. *Microb Genom* **7**, (2021).

43. Ning, L. *et al.* Microbiome and metabolome features in inflammatory bowel disease via

multi-omics integration analyses across cohorts. *Nat. Commun.* **14**, (12 2023).

44. Palou-Márquez, G., Subirana, I., Nonell, L., Fernández-Sanlés, A. & Elosua, R. DNA

methylation and gene expression integration in cardiovascular disease. *Clin. Epigenetics*

13, 75 (2021).

45. Yang, L. & Chen, J. A comprehensive evaluation of microbial differential abundance

analysis methods: current status and potential solutions. *Microbiome* **10**, 130 (2022).

46. Hédou, J. *et al.* Discovery of sparse, reliable omic biomarkers with Stabl. *Nat.*

Biotechnol. (2024) doi:10.1038/s41587-023-02033-x.

47. Candès, E., Fan, Y., Janson, L. & Lv, J. Panning for Gold: 'Model-X' Knockoffs for High

Dimensional Controlled Variable Selection. *J. R. Stat. Soc. Series B Stat. Methodol.* **80**,

551–577 (2018).

48. Meinshausen, N. & Bühlmann, P. Stability selection. *J. R. Stat. Soc. Series B Stat.*

Methodol. 417–473 (2010).

49. Srinivasan, A., Xue, L. & Zhan, X. Compositional knockoff filter for high-dimensional

regression analysis of microbiome data. *Biometrics* **77**, 984–995 (2021).

50. Hawinkel, S., Mattiello, F., Bijnens, L. & Thas, O. A broken promise: Microbiome
differential abundance methods do not control the false discovery rate. *Brief. Bioinform.*
20, 210–221 (1 2019).

51. Singh, A. *et al.* DIABLO: an integrative approach for identifying key molecular drivers
from multi-omics assays. *Bioinformatics* **35**, 3055–3062 (2019).

52. McGregor, K., Labbe, A. & Greenwood, C. M. T. MDiNE: A model to estimate differential
co-occurrence networks in microbiome studies. *Bioinformatics* **36**, 1840–1847 (2020).

53. Petrosino, J. F. The microbiome in precision medicine: The way forward. *Genome Med.*
10, (2 2018).

54. Talmor-Barkan, Y. *et al.* Metabolomic and microbiome profiling reveals personalized risk
factors for coronary artery disease. *Nature Medicine* vol. 28 295–302 Preprint at
https://doi.org/10.1038/s41591-022-01686-6 (2 2022).

55. Muller, E., Algavi, Y. M. & Borenstein, E. The gut microbiome-metabolome dataset
collection: a curated resource for integrative meta-analysis. *NPJ Biofilms Microbiomes* **8**,
79 (2022).

56. Kurtz, Z. D. *et al.* Sparse and compositionally robust inference of microbial ecological
networks. *PLoS Comput. Biol.* **11**, e1004226 (2015).

57. Liu, Y. *et al.* ACAT: A Fast and Powerful p Value Combination Method for Rare-Variant
Analysis in Sequencing Studies. *Am. J. Hum. Genet.* **104**, 410–421 (3 2019).

58. Wang, Y. & Cao, K. A. L. PLSDA-batch: a multivariate framework to correct for batch
effects in microbiome data. *Brief. Bioinform.* **24**, (3 2023).

59. Kim, M. *et al.* Fecal Metabolomic Signatures in Colorectal Adenoma Patients Are
Associated with Gut Microbiota and Early Events of Colorectal Cancer Pathogenesis.
MBio **11**, (2020).

60. Kang, D.-W. *et al.* Differences in fecal microbial metabolites and microbiota of children
with autism spectrum disorders. *Anaerobe* **49**, 121–131 (2018).

61. Bates, S. & Tibshirani, R. Log-ratio lasso: Scalable, sparse estimation for log-ratio
models. *Biometrics* **75**, 613–624 (2019).

62. Aitchison, J. *The Statistical Analysis of Compositional Data (Monographs on Statistics*

and Applied Probability). (Chapman and Hall, 1986).

63. Tsagris, M. T., Preston, S. & Wood, A. T. A. A data-based power transformation for

compositional data. *arXiv [stat.ME]* (2011).

64. Stewart, D. & Love, W. A general canonical correlation index. *Psychol. Bull.* **70**, 160–

163 (1968).

1223