MacAction: Realistic 3D macaque body animation based on multi-camera markerless motion capture

Lucas M. Martini[1,2*], Anna Bognár[3,4], Rufin Vogels[3,4] and Martin A. Giese[1*]

[1*]Hertie Institute for Clinical Brain Research (HIH) and Centre for Integrative Neuroscience (CIN), University Clinic Tübingen, Tübingen, Germany.
[2]International Max Planck Research School for Intelligent Systems (IMPRS-IS), Tübingen, Germany.
[3]Department of Neuroscience, KU Leuven, Leuven, Belgium.
[4]Leuven Brain Institute, KU Leuven, Leuven, Belgium.

*Corresponding author(s). E-mail(s): lucas.martini@uni-tuebingen.de; giese@uni-tuebingen.de;
Contributing authors: anna.bognar@kuleuven.be; rufin.vogels@kuleuven.be;

Abstract

Social interaction is crucial for survival in primates. For the study of social vision in monkeys, highly controllable macaque face avatars have recently been developed, while body avatars with realistic motion do not yet exist. Addressing this gap, we developed a pipeline for three-dimensional motion tracking based on synchronized multi-view video recordings, achieving sufficient accuracy for life-like full-body animation. By exploiting data-driven pose estimation models, we track the complete time course of individual actions using a minimal set of hand-labeled keyframes. Our approach tracks single actions more accurately than existing pose estimation pipelines for behavioral tracking of non-human primates, requiring less data and fewer cameras. This efficiency is also confirmed for a state-of-the-art human benchmark dataset. An uncanny valley experiment with macaque monkeys demonstrates that animals perceive the generated animations as similar to genuine videos, and establishes an uncanny valley effect for bodies in monkeys.

Introduction

Understanding the neural processing of social vision remains an unresolved problem in the field of neuroscience. Because primates are social animals, their brains have evolved special neural mechanisms for facial and body recognition [1]. The clarification of these mechanisms necessitates experiments with highly controlled visual stimuli that manipulate underlying visual features [2, 3]. For the study of social perception, avatars, as opposed to real-world videos of behaving animals, offer the advantage of precise control of relevant stimulus features and timing. To justify a transfer of the obtained results to real stimuli, such avatars need to exhibit sufficient realism in both shape and motion.

While there has been notable progress in generating dynamic macaque face avatars [4, 5], there have so far been no attempts to create lifelike dynamic monkey body avatars with realistic motion. This gap can be attributed, in part, to the challenges associated with marker-based motion capture in macaques. Not only the reproducible positioning of markers on their dense fur is technically demanding, but also animals typically remove or destroy body-attached markers quickly during grooming. Consequently, various datasets have been specifically constructed to capture poses in images [6–8]. Tracking non-human primates by video is challenging, because of the high-dimensional pose space, the presence of strong occlusions, and the homogeneity of texture induced by fur. Therefore, recent multi-camera approaches have reconstructed 3D poses only by exploiting setups with large numbers of cameras and extensive labeling of keypoints [9–11]. These disadvantages render such approaches infeasible as a basis for the estimation of 3D joint angle trajectories for computer animation, due to the larger number of keypoints and the high accuracy required.

In other animals, the surface model of an avatar was incorporated in the tracking process by supplementing keypoint data with silhouettes, but typically in scenarios of less complex pose spaces [12–14]. Others bypassed the use of commercial animation software entirely by using neural rendering [15], creating photorealistic animations directly from image data [16–18]. Nonetheless, this technique compromises the crucial aspect of exact and separate control of individual stimulus features, as required for a detailed analysis of underlying neural computations.

Even if a computer animation method creates animations that appear realistic to humans, it is not guaranteed that the same applies to monkey observers. When the realism of an animation is continuously increased, an uncanny valley might emerge, where preference for the animation decreases close to the highest levels of realism [19] (Fig. 4b). This phenomenon has been exploited to validate graphics methods to achieve a sufficient level of realism [20]. An uncanny valley has also been demonstrated for macaque observers for static [21] and dynamic monkey faces [5]. Whether such an effect also exists for monkey bodies is unknown.

Solving these challenges, this paper introduces MacAction, the first pipeline to animate actions of macaques from highly accurate 3D markerless motion capture, exploiting commercial animation software. To achieve this goal, we processed calibrated high-resolution multi-camera footage with state-of-the-art pose detectors, interpolating an entire action sequence by a minimum number of labeled keyframes. In this way, our method limits the amount of required hand-labeling, while being applicable to large marker sets as required for computer animation. Achieving realistic single-action animations from 6 cameras becomes feasible with 2 labeled frames per second (LPS), where our method substantially reduces errors compared to other macaque pose estimation methods [22]. Through a behavioral experiment with macaques, we reveal the existence of an uncanny valley for bodies in macaque perception. We demonstrate that the developed animations (Supplementary Videos 1 and 2) elicit distributions of attention comparable to real video footage, making such artificial stimuli suitable for the study of social perception in monkeys.

Results

MacAction: a framework for 3D animation of highly realistic macaque avatars.

To create realistic artificial stimuli that offer a high level of stimulus control, we devised a pipeline that allows to animate a commercial macaque avatar model with 86 joints, requiring the specification of 261 degrees of freedom (including global translation) based on markerless 3D tracking data. This necessitates accurate 3D tracking of a sufficient number of keypoints in order to constrain the high-dimensional body pose, specifically the rotations of the arms, wrists, feet, finger movements, and the tail. In this work, we used a set of 42 keypoints, a number that exceeds the one in previous studies on markerless tracking of macaques by more than factor two [6, 7].

To achieve a maximum degree of realism in the generated stimuli, we also reconstructed the background scenes in 3D computer graphics using 3D modeling software. The modeling of shape primitives, textures, and materials was based on a laser scan of the monkey cage (Fig. 1c).

From 150 minutes of synchronized multi-view video material, we selected three distinct actions, containing a single and multiple macaques: (1) a complex submissive turning movement; (2) a short walk representing emotionally neutral behavior; and (3) a social interaction of two individuals where one monkey grooms the other.

State-of-the-art markerless tracking methods for animals [23, 24] require human annotators to label exemplary postures for training the underlying neural networks. In our case, the required amount of labeling would be enormous, due to the larger number of keypoints and the use of multi-camera data. Thus, reducing the required manual labeling is a key problem to make our approach feasible for applications in neuroscience. Therefore, we developed a software tool, AnimLabel, that simplifies labeling in multi-camera data by propagating constraints from already annotated views to other unlabeled ones. The resulting combinations of multi-camera images and 3D poses served as training examples for state-of-the art markerless tracking algorithms, reconstructing the poses for intermediate unlabeled time points. We first tested DeepLabCut (DLC) [23, 25], a popular image-based tracking algorithm for different animal species. To generate 3D poses, we then processed tracked 2D keypoints from multiple views using Anipose [26]. This enables the application of a spatiotemporally regularized triangulation, wherein 3D keypoints are constrained by an optimal projection across views, their temporal smoothness, and the desirably small variance in distance to neighboring markers. By adjusting the two factors, α_{time} and α_{limb}, we can emphasize the different objectives within the triangulation. We refer to the process of discarding those factors in the triangulation as structural refinement.

We also applied an alternative approach, originally developed for human tracking [27], which integrates the triangulation process into the learning objective of the neural network. Its adoption for animals, the 3-Dimensional Aligned Neural Network for Computational Ethology (DANNCE), outperformed DLC with the same number of cameras for behavioral tracking in rats and mice [24]. Tracking results obtained with these methods were further processed and

mapped onto the skeleton of the macaque avatar. For this purpose, we used custom scripts in Maya for skeleton retargeting, making the pipeline adaptable to different marker configurations. Using smoothed 3D marker trajectories, we were able to compute the poses of the avatar for each time step and to animate the actions in a virtual scene with a sufficiently high framerate (Fig. 1a,b).

Fig. 1 MacAction animates 3D markerless pose tracking to generate realistic synthetic images. a, Pipeline for character animation: Selection of actions from sets of synchronously recorded videos from multiple viewpoints. A neural network-based tracking algorithm predicts keypoint trajectories for all frames of an action (shown in blue) based on a minimal subset of hand-labeled data for training. The retargeting process then maps this motion onto a 3D avatar. The resulting animation can be embedded into a 3D model of the background scene, which can be rendered from any viewpoint. **b,** Generated images of the virtual action over time. **c,** Comparison between corresponding frames from a real video (left), and the simulated virtual scene (right), combining the animated avatar with the 3D background model.

Accurate single-action tracking with minimal labeling

Previous work has used extensive numbers of cameras and labels to realize markerless motion capture for macaques, mainly aiming at behavioral analysis [9]. However, these resources, particularly cameras and labels, are costly, posing a challenge for smaller labs. We, therefore, validated our tracking method with respect to single actions, determining the required number of labeled frames for training pose detectors to perform inter-frame interpolation. This was dependent on the number of cameras used and the tracking algorithm selected.

We first considered the densely hand-labeled submissive action at 4.38 LPS. The DLC 2D landmarks were triangulated using Anipose's spatiotemporally regularized triangulation [26], but omitting temporal and limb constraints. As the pose predictions were relatively noisy, we initialized the triangulation by Random Sample Consensus (RANSAC). With six labeled frames, this method achieved reasonable test error performance (mean error and SD, 18.9 ± 20.8mm), close to DANNCE's voxel resolution. It even outperformed DANNCE when training with double the number of labeled frames (29.3 ± 25.9mm) for the same number of cameras (Fig. 2a,b and Supplementary Fig. 1a). However, the pose trajectories obtained by DANNCE were smoother (Fig. 2e and Supplementary Videos 3 and 4). This was quantified by computing the mean predicted marker speed across the sequence, given as the instantaneous per-joint temporal deviation (IPJTD, Methods), a measure that increases for more jerky trajectories.

We optimized all constraints of Anipose's spatiotemporal triangulation refinement by minimization of the error using six frames and eight cameras (Fig. 2c, left), resulting in significantly smoother trajectories. For optimized parameters, the mean per-joint temporal deviation (MPJTD), a measure for motion prediction quality [28] representing the average IPJTD of the action, reached already with only about a third of the labeled frames the plateau established when using DLC and Anipose on all data of the action (Fig. 2c (right),e and Supplementary Videos 3 and 5).

When grouping the keypoints by body parts, the accuracy was higher for DLC with Anipose's structural refinement than for DANNCE, except for the spine and the mostly occluded right leg, given the same number of cameras and amount of training data. We were able to reduce the remaining errors in DLC by including the optimized temporal constraint in Anipose (Fig. 2d and Supplementary Fig. 1b). Similar results were obtained for the neutral walking behavior, which was labeled less densely in time (2.87 LPS). For the test frames, DLC and Anipose showed smaller prediction errors compared to DANNCE, both with and without temporal refinement of triangulated landmarks (Supplementary Fig. 1c-e).

3D Multi-animal tracking

Beyond validating our method for the tracking of individual animals, we also extended it for the tracking of two monkeys. Because of the many occlusions in scenes with interacting animals this is a particularly challenging problem. We considered a sparsely labeled multi-animal action (0.15 LPS), and implemented an architecture for multi-animal tracking using DLC, which simultaneously identifies both individuals and their keypoints. However, the assignment of keypoints to the individual monkeys is difficult and results in frequent mismatches of markers between different animals across views. To solve this problem, we developed an algorithm (see Supplementary Note) that resolves the assignment of the markers to the individual animals in 3D (Fig. 2g,h). However, this post-processing step was rather costly and not guaranteed to be robust, especially when DLC's predictive accuracy of markers and identities was reduced for so little data. In contrast, DANNCE does not explicitly solve the assignment process but can derive it from similar trained poses and sampling the 3D input volume at different locations for each animal. When we trained the algorithm on more labeled keyframes and cameras, 3D keypoint errors reduced substantially, where the inclusion of additional labeled frames from single action tracking improved the performance (Fig. 2f and Supplementary Fig. 2), favoring the volumetric approach for tracking multiple agents.

Single-action reconstruction in Panoptic Studio

For human pose estimation, volumetric landmark detection [27] has been shown to be superior to post-hoc triangulation methods on the large-scale dataset Panoptic Studio [29]. To test whether this result also translates to tracking single actions of human actors (Fig. 3a), and to see if it aligns with our results for macaques, we extracted two dynamic actions of a single actor and a group action involving six individuals from this data set. For the single actor, DANNCE, trained with six cameras and labeling half of the frames, reached an average error of 37.9 ± 33.5mm (Fig. 3b).

In comparison, DLC achieved a similar error level even with only four cameras and six labeled frames (28.8 ± 47.6mm), where we utilized the direct linear transformation (DLT) for triangulation (Fig. 3b, d). Including additional camera views in the prediction that were not part of the training data increased the error rather than reducing it (Fig. 3c). By optimizing the spatiotemporal parameters of Anipose's triangulation refinement, the prediction error was able

Fig. 2 Single-action pose estimation. a, Euclidean error on test frames that were not in the training fraction (left) and MPJTD for the entire sequence (right) for DLC with RANSAC and structural refinement. The violet horizontal line indicates the spatial resolution (here, ~ 11.72mm) of the volumetric approach, DANNCE. In **a-c, e** and **f** points indicate the arithmetic means, and the vertical lines illustrate the 95% confidence intervals. **b,** Euclidean error for equivalent test frames that were not in the training data fraction (left) and MPJTD for the entire sequence (right) for DANNCE for a maximum of six cameras. **c,** Optimization of Anipose's spatiotemporal parameters for six frames and eight cameras (left). MPJTD for all cameras and training fraction with optimally adjusted parameters for triangulation refinement (right). **d,** Euclidean errors as box plots for keypoints grouped in terms of body parts. The methods were trained with data from six cameras and six annotated frames, using only a subset of all labeled frames of the action (indicated as Partial). The results for DLC are shown with structural refinement only, and applying Anipose's spatiotemporal optimization. As we set $\alpha_{\text{limb}} = 0$, these models are referred to as Time in **d** and **e**. The box plot shows the median with interquartile range (IQR), whiskers at $1.5\times$ the IQR and outliers depicted as diamonds. The arithmetic mean is shown as a white circle. **e,** IPJTD across recorded frames. In addition to the models in **d**, the result for the spatiotemporally refined DLC model for six cameras is shown with all frames used in training (indicated as Full). Labeled frames that were not included in the training set for the partial conditions are indicated by long red vertical lines. The labeled frames that were included in the training set for the partial conditions are indicated by the green vertical lines. **f,** Euclidean error for multi-animal action prediction with DANNCE. **g,** Image of a labeled frame from the multi-animal condition. **h,** The 3D-Disentanglement procedure removes the confusion of keypoints between the two animals. Triangulated predictions before (top) and after disentanglement (bottom).

to fall below the resolution of DANNCE's input volume of 15.625mm (14.0 ± 17.1mm; Fig.3 e,f) even with few cameras and labeled keyframes.

DANNCE matched the mean marker speeds of ground-truth labels only with substantial amounts of training data (Fig. 3b). In contrast, DLC required a lower amount of training data to reach a comparable level of trajectory smoothness (Supplementary Fig. 3a). When fixing the limb constraint in triangulation with Anipose, the temporal adjustment could be decreased as more frames were included in the training set (Fig 3g).

For the tracking of multiple individuals, DANNCE showed lower errors than for the tracking of single individuals (20.3 ± 20.2mm). This was also accompanied by matching the ground-truth mean marker speed with less training data, likely as there are six actors, resulting in six times as many labels per keyframe (Fig. 3h).

Adding frames from the single-actor action to the training dataset did not yield improvements for tracking multiple individuals (Supplementary Fig. 3b). Consistent with our findings for macaques, tracking a single action with limited data was more accurate using the triangulation approach, and including more cameras and keyframes significantly reduced errors in tracking multiple agents with DANNCE.

Uncanny Valley for body perception

To investigate the extent to which the animated avatar is perceived as lifelike by real animals, we recorded the eye movements of eight macaque monkeys, while they were exposed to images and videos of an acting monkey or monkey avatar with different degrees of realism (Fig. 4a). We generated these intermediate degrees of realism in the uncanny valley experiment for emotionally neutral walking and a submissive body action, building upon previous work focused on faces [5].

For eye fixation analysis, we defined areas of interest (AOIs, [30]) based on the monkey silhouette, using Track-Anything [31]. For video analysis, we considered a fixation valid if it remained within all AOIs for its entire duration. We also quantified visual exploration by the stimulus coverage in pixels, derived from eye fixation positions. A group-level analysis of the first trials revealed an uncanny valley in visual exploration (one-way repeated measure analyses of variance (ANOVA): $F(4, 28) = 6.953, p = 0.002$, Fig. 4c, Supplementary Fig. 4a, Supplementary Table 1), with the furless and particularly the gray avatar being perceived the least. An absence of the uncanny valley effect in the results, for example, would be indicated by a lack of the characteristic U-shape in the data or by an inconsistent trend across different levels of realism.

Across all trials, the uncanny valley was less pronounced for the number of fixations on the entire image, the macaque silhouette, and especially for image exploration (Supplementary Fig. 4b,c). These changes in gazing behavior were accompanied by a decrease of fixation counts with an increasing number of trials (Supplementary Fig. 4g), potentially reflecting a decay in the animals' attention to the stimuli. However, the average fixation duration across all trials and subjects showed a reversed uncanny valley with less realistic stimuli being looked at longer (Friedman: $\chi^2(4, n = 8) = 19.3, p = 0.0007$, Fig. 4d). The same trend was observed for fixations falling into the monkey silhouette (Friedman: $\chi^2(4, n = 8) = 13.8, p = 0.008$, Supplementary Fig.4d). Analyzing only the fixation duration of the first trials, the reversed uncanny valley was less prominent for whole image and monkey shape fixations (Friedman: $\chi^2(4, n = 8) = 11.8, p = 0.019$, Friedman: $\chi^2(4, n = 8) = 6.9, p = 0.14$, Supplementary Fig.4e). Overall, these findings demonstrate that monkeys exhibit an uncanny valley effect for bodies. While such effects have been reported for facial stimuli [5, 21], this is the first demonstration for bodies.

Influences of motion, action, and viewpoint

The influences of the different factors in our experimental design were further quantified by generalized linear models (GLM), assuming negative binomial distributions (Methods) to model the response variable, that is, counts of whole image and monkey shape fixations. For both, likelihood-ratio tests for data from initial trials show a significant influence ($p < 0.0001$) of the factor Render and Presentation type (dynamic vs. static). Yet, the interaction of these two factors is not significant ($p = 0.5502$ and $p = 0.8086$, Supplementary Tables 3,4). Except for the uncanny valley of macaque silhouette fixations in static images (Friedman: $\chi^2(4, n = 8) = 7.465, p = 0.1133$ (images), $\chi^2(4, n = 8) = 9.4842, p = 0.0050$ (videos), black curves in Fig. 4f), we found a significant influence of the factor Realism, also for both images and videos in whole image fixations (Friedman: $\chi^2(4, n = 8) = 10.843, p = 0.0284$ (images), $\chi^2(4, n = 8) = 12.662, p = 0.0131$ (videos), Fig. 4e). Subsequent post-hoc analyses, however, did not indicate significant differences between the different levels of Realism for either Presentation type. Consistent with the classical uncanny valley hypothesis (Fig. 4b), where dynamic presentations are preferred over static ones except deep within the uncanny valley, videos were overall fixated more often than static images.

Furthermore, the macaques' gazing behavior was consistent across actions when presented with different degrees of realism. In particular, the neutral action accounted for more fixations than the submissive action in both images

Fig. 3 Results for DANNCE and DLC for single-action reconstruction in Panoptic Studio. a, Illustration of the Panoptic camera setup: a geodesic dome surrounds actors with 31 HD cameras. **b,** Euclidean error on test frames (top) and MPJTD for the entire sequence (bottom) for DANNCE for single actor action tracking. Horizontal lines in the error plots in **b-e** and **h** indicate the resolution (here, 15.625mm) of DANNCE's volumetric approach. The horizontal lines in the MPJTD plots in panels **b,e** and **h** indicate the ground-truth mean marker speeds for the single (0.49m/s) and group (0.19m/s) actions. In **b-h** points indicate the arithmetic means, and the vertical lines illustrate the 95% confidence intervals. **c,** Euclidean error for DLC with DLT triangulation when models trained on a subset of camera views were used to predict on all available views. **d,** Euclidean error for DLC with DLT triangulation if models predict on camera views that were present in training only. **e,** Euclidean error (left) and MPJTD (right) for DLC with DLT-based spatiotemporally optimized triangulation. Models predict on camera views that were present in training only. **f,** Optimization of Anipose's spatiotemporal parameters for six frames and eight cameras. **g,** Optimization of Anipose's temporal adjustment with an optimized spatial constraint, derived from **f** for different numbers of training frames and cameras. **h,** Euclidean error (left) and MPJTD (right) for the multi-actor action prediction with DANNCE.

Fig. 4 Uncanny valley effect for bodies in macaques. a, First row: stimuli for the uncanny valley experiment with different degrees of realism, increasing from left to right. The rightmost stimulus is a real video. Second row: superposition of the monkey silhouettes (for degraded stimuli derived from the avatar with fur) across all frames. Last row: accumulated fixations falling into these dynamic masks for the eight monkey subjects across all trials. **b,** Illustration of the uncanny valley hypothesis in human perception, adopted from [19]. The range of realistic avatars, both static and dynamic, is shaded in dark green. **c,** Box plot of image coverage by fixations in pixels for different render types. Plots in **c, e** and **f** show the results of the first trials only, while panels **d** and **g** show the analysis including all trials. Box plots show the median with interquartile range (IQR), whiskers at $1.5\times$ the IQR, and outliers depicted as diamonds. The arithmetic mean is indicated by a white circle. In **c-f**, arithmetic means are connected by a red line. Statistical significant pair-wise differences are indicated by horizontal lines accompanied with asterisks: $p^* < 0.05$ and $p^{**} < 0.01$. **d,** Box plot of the mean image fixation duration, for each render type. **e,** The number of fixations on the image as a function of render type, shown separately for two presentation types: static (image) and dynamic (video). In **e** and **f**, arithmetic means per condition are connected by black lines, with the overall mean per render type indicated by a red line, omitting the additional white circles. **f,** The number of fixations within the macaque silhouette for the different render and presentation types. **g,** Box plot showing the number of fixations of the macaque silhouette, split by action, render type, and presentation type. Image responses are shown on the left and fixation counts of videos on the right.

and videos (Fig. 4g, Supplementary Table 5). The number of fixations, analyzed separately for different actions, varied significantly across viewpoints (Supplementary Table 6,7 and Supplementary Fig.4f). We also confined the analysis to real footage and the most realistic avatar only. Here, the GLM analysis revealed a significant effect of the displayed action, while the factor Render (real macaque vs. avatar) was not significant, nor were the interactions (Supplementary Table 8). Thus, macaques responded very similarly to the avatar and the real video, showing that the developed method creates animations that appear to be realistic to macaque monkeys.

Discussion

Here we presented MacAction, a tracking and animation system that combines highly accurate 3D markerless motion capture with the animation of a virtual macaque avatar. Animating such unconstrained models necessitates tracking numerous markers in 3D. In contrast to human tracking, for which extensive databases with precise kinematic data are available, creating similarly large databases for monkeys is not economically feasible.

To solve this problem, we established a pipeline for video-based tracking with high accuracy, requiring only minimal hand-labeled data for individual actions. We demonstrated that labeling two frames per second is sufficient to generate realistic 3D animations for complex body actions. Especially with larger marker sets, as required in computer animation, our method significantly reduces the need for labeling larger numbers of images, as common in 3D behavioral analysis [9, 10, 26, 32].

At the same time, we showed that our approach tracked single actions more precisely than other behavioral tracking approaches in macaques, even those including additional sensor devices such as RGB-D cameras [22, 33]. Further, we obtained better results with a method using post-processed triangulation of 2D marker trajectories over 3D volumetric pose estimation for the tracking of individual animals with little data. This performance difference reversed for the tracking of multiple animals, where we expect further improvement by incorporating temporal supervision for volumetric models [28]. Considering the known challenges of tracking macaques [7, 9], our method is likely adaptable to other animals with simpler kinematic structures. This is particularly needed in tracking actions of endangered animal species [34], where data might be scarce and costly to obtain.

MacAction goes significantly beyond the proposal of a new approach for motion tracking. It encompasses the entire process of crafting digital avatars, motion retargeting, scene asset creation, rendering, and ultimately, validating animations with real monkeys. Our eye-tracking data from behavioral experiments showed that macaques respond to our dynamic avatars very similarly as to actual video recordings, supporting the high degree of realism in the developed animation. Notably, by exploiting methods for eye tracking that have been successful in analyzing face stimuli, we established an uncanny valley effect for the observation of bodies in macaques. Such effects had previously been observed in monkeys only for faces [5, 21]. The fact that humans also show uncanny valley effects for bodies [35, 36] supports the hypothesis that neural mechanisms for processing visual stimuli of bodies are shared among different primate species. Therefore, studying macaque monkeys with such highly controlled and realistic visual stimuli is a suitable approach for unraveling the underlying neural principles of social vision.

Methods

Animals and husbandry.

Eight male rhesus monkeys (Macaca mulatta), ranging in age from 5 to 7 years, contributed to this study. The animals are housed in enclosures at the KU Leuven Medical School and experience a natural day-night cycle. Each monkey shares its enclosure with at least one other cage companion. On weekdays, dry food is provided ad libitum, and the monkeys obtain water, or other fluids, during experiments until they are satiated. During weekends, the animals receive water along with a mixture of fruits and vegetables. The animals have continuous access to toys and other forms of enrichment. For experiments unrelated to this paper, the monkeys were implanted with a plastic headpost, attached using ceramic screws and dental cement following standard aseptic procedures and under full anesthesia. Both the animal care and experimental procedures adhere to regional (Flanders) and European guidelines and have been approved by the Animal Ethical Committee of KU Leuven.

Multi-camera recording setup.

We created a 3D model of the surrounding scene in the animal house using a commercial imaging laser scanner (LEICA BLK360). The resulting extracted colored point clouds from multiple scans were registered using Scasa PinPoint (v2.6.0), and further processed with Autodesk Recap 2022. The size of the surrounding cage was (2.1m x 3.1m x 2.3m). Based on these scans, we reconstructed the entire surrounding environment as a 3D model in Maya 2022. The reconstructed scene elements were then imported into the real-time gaming platform Unreal Engine (4.27.1). In this software environment, we created virtual cameras to emulate those we planned to use in the final recordings. Adjustments to these cameras, including their extrinsic position and field of view (FOV), helped to choose appropriate lenses. We determined the focal length in relation to the film size in order to achieve a suitable FOV. We then verified that for the chosen lenses a virtual cube with a side length of 75cm, which represented the macaque's movement space, was fully captured in the FOV. This cube was centrally placed in the virtual cage, and it was captured at a resolution of 2056x2056 pixels by the virtual cameras.

For the real recordings, we employed eight high-resolution machine vision color cameras from IO Industries. Four cameras of the type Victorem 51B163CCX (2464x2056 pixels) and four of the type Victorem 120B68CCX (4112x3008 pixels) were initially positioned at the virtual camera locations. For synchronization and recording, we used two digital video recorders (CORE2CXPLUS) from the same manufacturer, enabling precise synchronization with low-latency TTL signals. Not only were the cameras controlled by TTL signals but also eight LED light panels (StroboMini2, Norka Automation). In this way, the scene was lit in synchrony with global camera shutters, reducing the overall brightness experienced by the subjects significantly. As a result, the cameras' exposure time could be set to as low as 300 microseconds, keeping motion blur effects at a minimal level. Four light panels surrounded the cage horizontally, whereas the rest was placed on top of the cage next to a single camera, producing an orthographic viewpoint. The cage's top was a metal grid. Therefore, we protected the cameras on the top from manipulations by the monkeys using custom plexiglass pieces. The remaining equipment was mounted on tripods outside of the cage. Since the setup was not completely protected against mechanical perturbations, we re-calibrated the optical recording system regularly before each recording session using two different calibration schemes. The first scheme involved a custom ChArUco pattern (39.7cm x 39.7cm, 0.5 marker-to-square ratio, opencv standard 4bit dictionary with 50 markers for ArUco checkers). This pattern was detected by software written in Python (3.9.7) using OpenCV (opencv-python 4.5.5.62 and opencv-contrib-python 4.5.5.62). Additionally, the extrinsics were optimized with bundle adjustment in MATLAB (R2021b). The second calibration method involved a light-emitting wand from Vicon (Active Wand), typically employed for the calibration of a marker-based motion capture system, and corresponding proprietary post-processing software. Both methods achieved subpixel accuracy. After the recordings, we transferred raw video material at high speeds to an external storage system (D5 Thunderbolt 3, Terramaster) with up to 90TB storage, capable of combining up to five SATA disks in different RAID configurations.

MacAction Software.

MacAction was developed using Python 3.9.7 and incorporates several widely used open-source software packages for the scientific community: numpy 1.22.1, aniposelib 0.4.3, matplotlib 3.5.0, opencv-contrib-python 4.5.5.62, opencv-python 4.5.5.62 and scipy 1.7.3. We employed established keypoint estimation software, anipose 1.0.1, deeplabcut 2.2.2 (cuda 11.4 and cudnn 8.2.1) and dannce 1.2.0 (cuda 10.1 and cudnn 7.6.5). Our repository includes code modules

for various functions: video compression, gamma correction, camera calibration, and calibration file conversion. We further developed and provide AnimLabel, a matplotlib based labeling tool to generate 3D poses from simultaneously presented multi-view images. AnimLabel enforces consistent labeling across an arbitrary number of views by including multi-view geometric constraints from calibration data. Epipolar lines are utilized to reduce relevant regions across views to a single line or intersections of lines if a keypoint is labeled in a single or multiple views. To further reduce the labeling effort, we project triangulated landmarks of at least two views into all other perspectives.

In practice, we use at least three hand-labeled markers to reduce uncertainty in the triangulated 3d keypoint position. In this way, labeling effort remains the same, but labeling throughput scales linearly with the number of cameras. We also ensure sufficient labeling accuracy by setting a threshold for the mean reprojection error across labeled views (5 pixels).

Furthermore, the user can crop views to show only relevant image areas, which is especially relevant for high-resolution images. AnimLabel can also export cropped single animal actions per view. Based on a pre-defined spatial margin, we project all markers into the image plane. We then identify the markers that are outmost in the frame, and construct corners of the new frame by moving them parallel to the image plane in 3D, ensuring not to clip other body regions by accident. Data labeled through AnimLabel, can be exported in appropriate formats to both DANNCE and DeepLabCut for multi-view and multi-animal projects. We convert the tracking data from DeepLabCut to Anipose's format for single- and multi-animal tracking. All generated full-body trajectories are then saved in a numpy binary format ('.npy'). For rendering, we use Maya, leveraging its native Python 3 interpreter, mayapy, which allows to import and retarget motion data. In Maya, we could enhance the quality of the motion capture data by interpolation to smoother trajectories, and we exploited calibration data to align virtual cameras with their real-world counterparts.

Datasets.

Macaque animation. Video data of macaques was recorded at 80 frames per second (FPS). From 2.5 hours of recording data, we extracted three distinct actions: a submissive action (3.43s), a neutral action (2.44s), and an interaction of two macaques (93.4s) with 15, 7 and 14 labeled frames, respectively. Based on these labeled frames, we assessed the accuracy of our tracking pipeline in three different scenarios: (1) oversampling a short, complex body movement; (2) providing fewer labels for a concise, simpler action; and (3) fewer labeled time points of a prolonged multi-animal close-interaction sequence.

We labeled an extensive set of 42 body landmarks: 'Jaw', 'lowerLip', 'upperLip', 'lCornerM', 'rCornerM', 'Nose', 'lEye', 'rEye', 'Head', 'lEar', 'rEar', 'Neck', 'lShoulder', 'lElbowOut', 'lElbowIn', 'lWristOut', 'lWristIn', 'lThumb', 'lMidK', 'lMidTip', 'rShoulder', 'rElbowOut', 'rElbowIn', 'rWristOut', 'rWristIn', 'rThumb', 'rMidK', 'rMidTip', 'mid-Spine', 'lHip', 'lKnee', 'lAnkle', 'lBigToe', 'lFootTip', 'rHip', 'rKnee', 'rAnkle', 'rBigToe', 'rFootTip', 'beginTail', 'midTail', and 'tipTail'. This allowed us to infer both the positions and rotations of individual joints in 3D, crucial for controlling a high-quality virtual avatar.

Due to the significant amount of work involved in labeling markers on larger data sets, we limited the number of keypoints to the minimum necessary for animating the chosen avatar model.

Human Benchmark. To evaluate the amount of labeling for multi-view tracking approaches used in this paper, we also utilized a publicly available large-scale data set for humans, the CMU Panoptic dataset [29]. Due to the large number of cameras provided by the dataset, it has significantly contributed to human pose estimation and has led to the development of volumetric triangulation [27], which forms the basis of the DANNCE method [24].

We refrained from evaluating labeling labour on a dataset constructed with physically attached markers ([37], [38]). These keypoints may become salient in images and skew the learning process for markerless tracking, despite the limited number of color vision cameras available. In contrast, the Panoptic Studio dataset provides motion capture data without physical markers, utilizing recordings from 480 VGA, 31 HD, and 10 Kinect v2 RGB+D cameras, evenly distributed in a geodesic dome. Designed to capture human social interactions, it comprises actors engaged in activities such as playing games and instruments, or showing various other types of movements. For comparison with our monkey dataset, we extracted short sequences from movies showing two actions: a complex dance movement, and a clip involving six individuals engaged in simultaneous interactions. Each action consists of 90 frames lasting approximately 3s. We used data from up to 31 HD cameras at a resolution of 1920x1080 pixels.

The volumetric approach of the DANNCE algorithm has the disadvantage of a limited tracking volume. In order to better align the algorithm's accuracy between humans and macaques, we restricted 3D poses to upper body keypoints, hips included. Consequently, the human marker set comprised the following 15 keypoints: 'Neck', 'Nose', 'BodyCenter', 'lShoulder', 'lElbow', 'lWrist', 'lHip', 'rShoulder', 'rElbow', 'rWrist', 'rHip', 'lEye', 'lEar', 'rEye', and 'rEar'. Finally,

we sampled actions over time and across different numbers of cameras to create diverse datasets for benchmarking the tracking algorithms.

Pose estimation.

Single animals. For single-animal pose estimation with DeepLabCut 2.2.2, we fine-tuned a pre-trained ResNet-101 model on the ImageNet dataset using default training configurations. We created the dataset by exporting actions from AnimLabel. Specifically, we included both single and multiple animal actions across views in a label file matching DLC's structure, bypassing its graphical user interface using custom scripts.

After training and inference on a particular view, we consider all 2D keypoint predictions, regardless of their confidence values. In this way, we do not restrict information prior to the triangulation process. We use Anipose's RANSAC triangulation method and optimize the 3D points by spatiotemporally regularized triangulation, an extension that incorporates not only the reprojection error [26]:

$$\mathcal{L} = L_{\mathrm{proj}} + \alpha_{\mathrm{time}}L_{\mathrm{time}} + \alpha_{\mathrm{limb}}L_{\mathrm{limb}},$$

where the respective loss L_{proj} aims at minimizing the distance between the projected 3D markers and the associated 2D predictions over cameras. Since 3D body marker trajectories should be smooth in time and ensure consistent limb lengths, the losses L_{time} and L_{limb} are added, which measure the mean joint deviations over time and with respect to the expected limb lengths between connected keypoints. The parameters α_i in the composite loss allow to adjust the importance of these different factors in the cost function. We refer to the triangulation algorithm for the choice $\alpha_{\mathrm{time}} = \alpha_{\mathrm{limb}} = 0$ as structural refinement, as initial 3D points are optimized and shifted only to yield a consistent projection across views.

For DANNCE, we fine-tuned pre-trained weights of their AVG network architecture on a six-camera setup for rat pose estimation. As with DeepLabCut, we created custom scripts to align the labeling structure with AnimLabel and used the default training configurations. The algorithm requires a prediction of the animal's 3D center of mass (COM), which was determined using quadratic B-spline interpolated hand-labelling (of the 'midSpine' for macaques, and 'Neck' for the upper human body), instead of training a separate COM network within DANNCE. We specified the encapsulating volume size by determining the volume that encompassed all individuals and poses in the dataset, adding an additional safety margin. We did not incorporate any temporal or spatial smoothing, except for potential interpolation of keypoints in the commercial animation software.

Multiple animals. For the multi-animal tracking using DLC, we incorporated an additional re-identification step. This step associates the estimated 2D keypoint trajectories with the corresponding individual, exploiting multi-view consistency constraints. Furthermore, we introduced spatial and temporal smoothness constraints to derive a continuous re-identification of individuals (see Supplementary Algorithm 1). The re-associated 2D projections are then transferred to Anipose's optimization pipeline, where we treat multiple individuals as a single entity without connecting respective skeleton architectures.

With DANNCE, we did not change the overall network architecture as with DLC, but only the COM location in 3D to probe the network. Specifically, each of the two animals is associated with a different COM location. As with single animals, we automatically adapted labeling structures for multi-animal tracking.

Error metrics. To quantify the position accuracy of the tracking, we use the Euclidean distances between the predicted and the ground-truth 3D joint positions. As in [27, 28], we computed the mean per-joint position error (MPJPE):

$$\mathrm{MPJPE}(\mathbf{J}, \hat{\mathbf{J}}) = \frac{1}{N_J} \sum_{j=1}^{N_J} \|\mathbf{J}_j - \hat{\mathbf{J}}_j\|_2,$$

where the vector $\mathbf{J}$ includes the N_j ground-truth 3D keypoint coordinates, and $\hat{\mathbf{J}}$ denotes the corresponding tracking estimate. We average this per-frame error across the entire action to provide an overall error measure for the sequence. In addition, we compute Euclidean errors for specific body parts in the same way, including only the landmarks of those body parts.

Another measure characterizes the smoothness of the tracked trajectories. If the tracking fails, typically the trajectories show jumps and non-smooth transitions, for example, when the triangulation procedure misaligns 2D keypoints

across cameras. Inspired by [28, 39], we define a measure for the temporal smoothness of the predicted action of length T by the mean per-joint temporal deviation (MPJTD):

$$\text{MPJTD}(\hat{\mathbf{J}}) = \frac{1}{T-1} \sum_{t=1}^{T-1} \text{IPJTD}(\hat{\mathbf{J}}),$$

the action's average of the instantaneous per-joint temporal deviation (IPJTD):

$$\text{IPJTD}(\hat{\mathbf{J}}) = \frac{1}{N_J} \sum_{j=1}^{N_J} \|\hat{\mathbf{J}}_{t,j} - \hat{\mathbf{J}}_{t+1,j}\|_2.$$

The IPJTD can be thought of as the instantaneous speed or first-order derivative of the predicted keypoints, where large amounts and jumps are more likely due to erroneous tracking than fast movement.

Animation.

Model. We utilized a commercial macaque avatar model from CGTrader (https://www.cgtrader.com/3d-models/animals/mammal/monkey-fur-rigged). This digital macaque model consists of a mesh with 54,806 vertices, includes 8192x8192 pixel resolution textures, and fur. It is fully rigged, i.e., linked to a hierarchical structure of 86 joints that allows for posing the character with appropriate deformations of the surface structure. It uses linear blend skinning to determine these surface deformations. To enhance the realism of the avatar, we scaled hands and feet to match measurements of one real monkey, derived from triangulated poses of hand-labels. Preliminary eye-tracking results indicated that the animals were specifically interested in the rear part of the observed bodies. Consequently, we refined this area of the model by attaching a pair of testes and two patches of keratinized skin (sciatic protuberances), characteristic of Old World monkeys, using rivet constraints in Maya 2023. Additionally, we utilized the XGen Interactive Groom Editor to modify the fur in this area, aiming for a less dense and shorter fur texture.

Pipeline. Utilizing the tracked 3D keypoint trajectories of all markers, we implemented a customized yet generally applicable interface to the kinematic tree of a digital avatar model in Maya. The keypoints are rescaled to match the dimensions of the avatar, and the character's joint positions and rotations are set to their default states, known as the rest pose. We then position the root joint of the avatar in the scene, and determine the rotations of individual joints along its kinematic tree by solving Euler angle transformations in matrix form consecutively. A detailed description of the approach can be found in the Supplementary Note. In this process, we distinguish between joints of the avatar model with two and three rotational DOFs. For body segments in the avatar with more intermediate joints than tracked keypoints, that is, the spine and tail, we perform a quadratic B-spline interpolation, treating these joints as having two DOFs.

Benchmarking details.

All benchmarking and training procedures were conducted on Nvidia Geforce RTX 3090 and 4090 GPUs. In the datasets, we prioritized cameras that increase view variability.

DLC. We trained a single model across views for each species. Single-animal models were trained for 5000 epochs and multi-animal models for 1000 epochs. All models utilized a ResNet-101 backbone. Data sets with more than five images were divided into 95% training, and 5% testing sets. After training, we predicted 2D landmarks on complete video sequences. These predictions were then converted into 3D trajectories using Anipose.

DANNCE. Our training followed the guidelines provided on https://github.com/spoonsso/dannce/wiki. We trained models across different animal types and dataset sizes, each for 1000 epochs. Due to limited data sizes, we excluded validation samples. For all species, models were trained using a 64x64x64 volume grid, resulting in voxel resolutions of 11.719mm (macaques) and 15.625mm (humans), based on the cubic volume side lengths of 750mm and 1000mm, respectively. For training configurations with less than six cameras, models trained on duplicated camera views.

Uncanny Valley Stimuli.

For the behavioral experiment testing the quality of our animated macaque avatar, we adopted a similar approach as in experiments that showed the presence of an uncanny valley in macaques for faces [5]. According to the uncanny valley hypothesis, variations in the avatar's realism should induce changes in preference, which can be discovered by eye tracking. Starting from the complete avatar model, we created three degraded versions of it: (1) discarding the fur of the model and depicting the avatar with skin texture only; (2) removing the color information of the skin by the replacement of a smooth gray texture; and (3) discarding light reflection properties of the surface structure, by outlining the mesh's edge lines in black on a constant white background. As actions for these stimuli, we used the emotionally neutral walking and the submissive body movement.

For the final animations, we also reconstructed the background scenery, including the cages and lights, as 3D scan-based models of the individual geometric elements in Maya. To reproduce the recording conditions virtually, we positioned rendering cameras according to their real-world counterparts. Due to the remaining shape difference between the real macaque and the avatar, the same motion can result in slightly different trajectories of the corresponding body parts, most apparent in the distal parts of the avatar's limbs. To reduce these differences, we adjusted strongly deviating motion paths in Maya 2023.1 using the Graph Editor tool, ensuring a realistic physical interaction of the avatar with its environment.

Excluding the unnatural viewpoint from the top of the cage, we rendered seven different viewpoints per action and avatar configuration using V-Ray for Maya (v5.20.02). In line with rendered videos, we adjusted real videos to square format and dropped every third frame. As a result, the uncanny valley dataset comprises 70 dynamic stimuli derived from two actions, seven viewpoints, and five levels of realism (including a real video). To distinguish influences of motion and shape in the uncanny valley experiment, we selected from each action a key pose that best represents the particular expression, and extracted the corresponding still images from the videos. This yielded a final set of 140 stimuli, half static and half dynamic. Given the significant influence of the face on eye fixations [40, 41], visible faces were blurred using a Fast Box Blur filter in Adobe After Effects 23.1.0 (https://www.adobe.com/de/products/aftereffects.html). Additionally, parts of the real video showing researchers or body reflections were blurred, ensuring equivalent blurred areas in the rendered videos. The mean luminance of all videos and images were equated, taking into account the gamma function of the display using custom written software.

Eye tracking.

Setup and paradigm. During the experiment, subjects were seated in a primate chair with their heads fixed. For eye tracking, we used an infrared eye tracker (1000 Hz EyeLink CL, SR Research) sampled at 2000Hz in front of 22.5-inch, high-resolution LCD screen (VIEWPixx, 1920x1200 pixels, 120Hz refresh rate), specifically designed for eye fixation experiments. To map the monkey's gaze to the image's pixel space, we conducted a calibration experiment at the beginning of each recording session. In this experiment, a red square fixation target (size = 0.2°) was presented on a gray background at 13 different locations, specified by the x, y coordinates in percentages of the display extent: [10,5], [50,5], [90,5], [35,30], [65,30], [10,50], [50,50], [90,50], [35,70], [65,70], [10,95], [50,95], [90,95].

In each trial, the target appeared at a new location, and the monkey received a juice reward for making a saccade towards the target and maintaining fixation for either 800 (for subjects: C, J, L, N and O) or 1000 ms (for monkey G, H and T). The duration of fixation varied depending on the subject's level of training. On average, we collected 11.9 valid trials at each location, with a minimum of 6 trials. The medians of these fixations at each location were then used to transform gaze coordinates into pixel coordinates, using second-order polynomial transformation (fitgeotrans, MATLAB R2020b). In the subsequent free-viewing test all stimuli had a size of 13.5x13.5° and were presented in a random order for 2.4s with an inter-stimulus interval of 400 ms. The stimuli were centered on the screen and displayed on a gray background having the same luminance level as used during calibration.

There was no fixation target, and the monkeys received a juice reward as long as their gaze remained on the screen, regardless of where they were looking. During a block, each stimulus was presented once, in case the monkey's gaze left the screen area, the stimulus remained on the screen and was not repeated during the same block to minimize the influence of familiarity on the viewing behavior. At least three runs were included from each subject in the analyses, all recorded on the same day. The start and end of the stimulus presentation were signaled by a photodiode detecting luminance changes of a small square located in the corner of the display (invisible to the animal) and placed within the same frame as the stimulus events. Stimulus presentation, event timing, and juice delivery were controlled by an in-house-developed digital signal processing-based computer system, which also sampled the photodiode signal besides vertical and horizontal eye analog signals.

Analysis. TrackAnything [31] (https://github.com/gaomingqi/Track-Anything) was used to define appropriate regions for the eye tracking analysis. This software ran locally on a machine equipped with an NVIDIA GeForce RTX 3090. We tracked masks for all real and avatar stimuli videos. Avatar masks were also used for its degraded variants, since fur-less avatars covered the same or less area in the image. For static images, we extracted the relevant masks out of the segmented videos. Eye tracking data from individual subjects were then visually inspected in MATLAB R2021b to define proper values for fixation analysis with the toolbox EyeMMV [42]. The spatial constraint parameters for the clustering of the fixations were both set to $\sim 0.46°$ in visual degrees.

We required a minimum fixation duration of 180 samples or 90ms, in line with literature on monkey eye tracking, where fixation duration thresholds varied from 50-150ms [5, 43–46]. Inspired by commonly used human eye fixation metrics [30], we defined three measures for a quantification of differences between the conditions: (1) mean fixation duration; (2) number of fixations that fall into dynamic or static body masks, where in videos the fixation was required to be within body masks for the whole fixation duration to be accepted; (3) coverage or stimulus exploration, C. For computing the coverage, we aggregated isotropic Gaussian kernels ($\sigma = 9px \hat{=} 0.244°$) located at eye fixation locations that lay within the image or body shape, represented by the following function over pixel coordinates (x, y):

$$g(x,y) = \sum_{i=1}^{N} e^{-\frac{(x-f_{x_i})^2+(y-f_{y_i})^2}{2\sigma^2}},$$

where N denotes the total number of fixations for a stimulus, and (f_{x_i}, f_{y_i}) is the location of an individual fixation. We then counted image locations, where this function exceeded a fixed threshold:

$$h(x,y) := \begin{cases} 1 & \text{if } g(x,y) \geq e^{-\frac{1}{2}} \\ 0 & \text{otherwise,} \end{cases}$$

resulting in the coverage:

$$C = \sum_x \sum_y h(x,y).$$

For displaying fixations on stimuli (Fig. 4a), we added up the Gaussian kernels at the eye fixation locations, weighted by their respective fixation durations.

Statistical analysis.

Tracking. Euclidean error plots show mean marker Euclidean distances and .95 confidence intervals as vertical lines. Outliers in boxplots are shown as diamonds, and mean values as black outlined white circles. When referring to a specific training configuration in the text, which is characterized by the algorithm, cameras, and labeled keyframes used for training, we present the Euclidean errors in terms of their mean and standard deviation.

Behavioral experiment. We performed one-way repeated measures ANOVA after checking residuals of a linear model for normality and outlier tests in R 4.3.1. Afterwards, we used the rm_anova() function from pingouin 0.5.3 in Python 3.9.7. If Mauchly's test of sphericity was significant, we applied a Greenhouse-Geisser correction. Effect sizes are reproted as generalized eta squared. To identify pairwise differences, we adjusted post-hoc pairwise, two-sided t-tests with Benjamini-Hochberg false discovery rate correction.

To model fixation counts within the whole image and the monkey sihouette, we additionally constructed generalized linear models with Poisson and negative binomial distributions using the package MASS 7.3.60 in R. In line with [47], we also constructed generalized linear mixed effect models (GLMMs) with Poisson and negative binomial distributions with the package lme4 1.1.33. Subject differences in fixation counts were accounted for by a random intercept for each individual.

We employed negative binomial GLMs as these showed no effects of under- and overdispersion, unlike all other models. Therefore, we tested fitted model residuals and simulated residuals with the function testDispersion() and inspected Q-Q plots to assess model fit, using the package DHARMa 0.4.6. Afterwards, we computed likelihood-ratio tests (LRTs) with the package lmtest 0.9.40 for different nested parameter combinations to identify interactions within predictor variables.

We used the non-parametric Friedman test from the scipy.stats 1.9.0 package when normality assumptions were not satisfied, or as an additional test for fixation counts. In cases where a significant effect was detected, we performed post-hoc analyses utilizing the Dunn's test from the package scikit_posthocs 0.7.0, applying a Benjamini-Hochberg false discovery rate correction.

To identify pairwise differences in fixation counts when an action or presentation type variable is varied, we utilized two-sided continuity corrected Wilcoxon signed-rank tests from the package pingouin 0.5.3. We report effect sizes in terms of the common language effect size (CLES).

Data availability

Motion capture data, renderings, eye movement recordings and the virtual scene will be made publicly available upon publication.

Code availability

The MacAction software package will be made publicly available upon publication.

Acknowledgements

Funding was provided by the European Research Council (2019-SyG-RELEVANCE-856495). The authors thank the International Max Planck Research School for Intelligent Systems (IMPRS-IS) for supporting Lucas Martini. We are grateful to S. Polikovsky for helping in the motion capture hardware design and to D. Cicchetti for support in labeling actions. We thank I. Puttemans, A. Hermans, C. Ulens, S. Verstraeten, J. Helin, W. Depuydt, and M. De Paep for technical and administrative support.

Author contributions

The study was designed by M.G., R.V. and L.M. Hardware design and motion capture recordings were done by L.M., A.B., R.V. and M.G. Data annotation, processing, animations and benchmarking were done by L.M. The macaque behavioral experiment was carried out by A.B. Eye fixation analysis was performed by L.M. and A.B. Statistical analysis was done by L.M. The article was written by L.M. with input from all authors.

Competing interests

The authors declare no competing interests.

References

[1] Barrett, L. & Henzi, P. The social nature of primate cognition. *Proc. of the Royal Society B: Biological Sciences* **272**, 1865–1875 (2005).

[2] Rosenberg, A., Cowan, N. J. & Angelaki, D. E. The Visual Representation of 3D Object Orientation in Parietal Cortex. *Journal of Neuroscience* **33**, 19352–19361 (2013).

[3] Chang, L., Bao, P. & Tsao, D. Y. The representation of colored objects in macaque color patches. *Nature Communications* **8** (2017).

[4] Murphy, A. P. & Leopold, D. A. A parameterized digital 3D model of the Rhesus macaque face for investigating the visual processing of social cues. *Journal of Neuroscience Methods* **324** (2019).

[5] Siebert, R. *et al.* A Naturalistic Dynamic Monkey Head Avatar Elicits Species-Typical Reactions and Overcomes the Uncanny Valley. *eNeuro* **7** (2020).

[6] Labuguen, R. *et al.* MacaquePose: A Novel "In the Wild" Macaque Monkey Pose Dataset for Markerless Motion Capture. *Frontiers in behavioral neuroscience* **14** (2021).

[7] Yao, Y. *et al.* OpenMonkeyChallenge: Dataset and Benchmark Challenges for Pose Estimation of Non-human Primates. *International Journal of Computer Vision* **131**, 243–258 (2023).

[8] Ma, X. *et al.* ChimpACT: A Longitudinal Dataset for Understanding Chimpanzee Behaviors. *37rd Conference on Neural Information Processing Systems* (2023). Preprint at https://doi.org/10.48550/arXiv.2310.16447.

[9] Bala, P. C. *et al.* Automated markerless pose estimation in freely moving macaques with OpenMonkeyStudio. *Nature Communications* **11** (2020).

[10] Matsumoto, J. *et al.* Three-dimensional markerless motion capture of multiple freely behaving monkeys for automated characterization of social behavior (2023). Preprint at https://www.biorxiv.org/content/10.1101/2023.09.13.556332v1.

[11] Kaneko, T. *et al.* Establishing an AI-based evaluation system that quantifies social/pathophysiological behaviors of common marmosets (2023). Preprint at https://www.biorxiv.org/content/10.1101/2023.10.16.561623v1.

[12] Zuffi, S., Kanazawa, A., Jacobs, D. & Black, M. J. 3D menagerie: Modeling the 3D shape and pose of animals. *IEEE / CVF Computer Vision and Pattern Recognition Conference (CVPR)* (2017).

[13] Badger, M. *et al.* 3D bird reconstruction: A dataset, model, and shape recovery from a single view. *European Conference on Computer Vision (ECCV)* (2020).

[14] An, L. *et al.* Three-dimensional surface motion capture of multiple freely moving pigs using MAMMAL. *Nature Communications* **14** (2023).

[15] Mildenhall, B. *et al.* NeRF: Representing Scenes as Neural Radiance Fields for View Synthesis. *European Conference on Computer Vision (ECCV)* (2020).

[16] Luo, H. *et al.* Artemis: Articulated neural pets with appearance and motion synthesis. *ACM Transactions on Graphics* **41**, 1–19 (2022).

[17] Wu, S., Li, R., Jakab, T., Rupprecht, C. & Vedaldi, A. MagicPony: Learning Articulated 3D Animals in the Wild. *IEEE / CVF Computer Vision and Pattern Recognition Conference (CVPR)* (2023).

[18] Giebenhain, S., Waldmann, U., Johannsen, O. & Goldluecke, B. Neural Puppeteer: Keypoint-Based Neural Rendering of Dynamic Shapes. *Asian Conference on Computer Vision (ACCV)* **13844**, 239–256 (2022).

[19] Mori, M., MacDorman, K. F. & Kageki, N. The Uncanny Valley [From the Field]. *IEEE Robotics & Automation Magazine* **19**, 98–100 (2012).

[20] Seymour, M., Yuan, L., Dennis, A. & Riemer, K. Have We Crossed the Uncanny Valley? Understanding Affinity, Trustworthiness, and Preference for Realistic Digital Humans in Immersive Environments. *Journal of the Association for Information Systems* **22** (2021).

[21] Steckenfinger, S. A. & Ghazanfar, A. A. Monkey visual behavior falls into the uncanny valley. *Proceedings of the National Academy of Sciences of the United States of America* **106**, 18362–18366 (2009).

[22] Silvernagel, M. P., Ling, A. S., Nuyujukian, P. & FOR THE BRAIN INTERFACING LABORATORY. A markerless platform for ambulatory systems neuroscience. *Science Robotics* **6**, eabj7045 (2021).

[23] Lauer, J. *et al.* Multi-animal pose estimation, identification and tracking with DeepLabCut. *Nature Methods* **19**, 496–504 (2022).

[24] Dunn, T. W. *et al.* Geometric deep learning enables 3D kinematic profiling across species and environments. *Nature Methods* **18**, 564–573 (2021).

[25] Mathis, A. *et al.* DeepLabCut: Markerless pose estimation of user-defined body parts with deep learning. *Nature Neuroscience* **21**, 1281–1289 (2018).

[26] Karashchuk, P. *et al.* Anipose: A toolkit for robust markerless 3D pose estimation. *Cell Reports* **36** (2021).

[27] Iskakov, K., Burkov, E., Lempitsky, V. & Malkov, Y. Learnable Triangulation of Human Pose. *IEEE/CVF International Conference on Computer Vision (ICCV)* (2019).

[28] Li, T., Severson, K. S., Wang, F. & Dunn, T. W. Improved 3D Markerless Mouse Pose Estimation Using Temporal Semi-supervision. *International Journal of Computer Vision* **131**, 1389–1405 (2023).

[29] Joo, H. *et al.* Panoptic Studio: A Massively Multiview System for Social Interaction Capture. *IEEE International Conference on Computer Vision (ICCV)* (2015).

[30] Bylinskii, Z., Borkin, M. A., Kim, N. W., Pfister, H. & Oliva, A. Eye Fixation Metrics for Large Scale Evaluation and Comparison of Information Visualizations. *Eye Tracking and Visualization (ETVIS)* (2015).

[31] Yang, J. *et al.* Track Anything: Segment Anything Meets Videos (2023). Preprint at https://arxiv.org/abs/2304.11968.

[32] Joska, D. *et al.* AcinoSet: A 3D Pose Estimation Dataset and Baseline Models for Cheetahs in the Wild. *IEEE International Conference on Robotics and Automation (ICRA)* 13901–13908 (2021).

[33] Nakamura, T. *et al.* A Markerless 3D Computerized Motion Capture System Incorporating a Skeleton Model for Monkeys. *PLOS ONE* **11** (2016).

[34] Liu, D. *et al.* LoTE-Animal: A long time-span dataset for endangered animal behavior understanding. *Proceedings of the IEEE/CVF international conference on computer vision (ICCV)* 20064–20075 (2023).

[35] Saygin, A. P., Chaminade, T., Ishiguro, H., Driver, J. & Frith, C. The thing that should not be: Predictive coding and the uncanny valley in perceiving human and humanoid robot actions. *Social Cognitive and Affective Neuroscience* **7**, 413–422 (2012).

[36] Brink, K. A., Gray, K. & Wellman, H. M. Creepiness Creeps In: Uncanny Valley Feelings Are Acquired in Childhood. *Child Development* **90**, 1202–1214 (2019).

[37] Sigal, L., Balan, A. O. & Black, M. J. HumanEva: Synchronized Video and Motion Capture Dataset and Baseline Algorithm for Evaluation of Articulated Human Motion. *International Journal of Computer Vision* **87**, 4–27 (2010).

[38] Ionescu, C., Papava, D., Olaru, V. & Sminchisescu, C. Human3.6M: Large Scale Datasets and Predictive Methods for 3D Human Sensing in Natural Environments. *IEEE Transactions on Pattern Analysis and Machine Intelligence* **36**, 1325–1339 (2014).

[39] Pavllo, D., Feichtenhofer, C., Grangier, D. & Auli, M. 3D human pose estimation in video with temporal convolutions and semi-supervised training. *IEEE / CVF Computer Vision and Pattern Recognition Conference (CVPR)* (2019).

[40] Arcaro, M. J., Schade, P. F., Vincent, J. L., Ponce, C. R. & Livingstone, M. S. Seeing faces is necessary for face-domain formation. *Nature Neuroscience* **20**, 1404–1412 (2017).

[41] Vinken, K. & Vogels, R. A behavioral face preference deficit in a monkey with an incomplete face patch system. *NeuroImage* **189**, 415–424 (2019).

[42] Krassanakis, V., Filippakopoulou, V. & Nakos, B. EyeMMV toolbox: An eye movement post-analysis tool based on a two-step spatial dispersion threshold for fixation identification. *Journal of Eye Movement Research* **7** (2014).

[43] Finn, K. R., Crutchfield, J. P. & Bliss-Moreau, E. Macaques preferentially attend to visual patterns with higher fractal dimension contours. *Scientific Reports* **9** (2019).

[44] Guo, K., Li, Z., Yan, Y. & Li, W. Viewing heterospecific facial expressions: An eye-tracking study of human and monkey viewers. *Experimental Brain Research* **237**, 2045–2059 (2019).

[45] Taubert, J., Wardle, S. G., Flessert, M., Leopold, D. A. & Ungerleider, L. G. Face Pareidolia in the Rhesus Monkey. *Current Biology* **27**, 2505–2509 (2017).

[46] Taubert, J. *et al.* Amygdala lesions eliminate viewing preferences for faces in rhesus monkeys. *Proceedings of the National Academy of Sciences* **115**, 8043–8048 (2018).

[47] Carp, S. B. *et al.* Monkey visual attention does not fall into the uncanny valley. *Scientific Reports* **12** (2022).