Title: Scale-Dependent Coding of the Hippocampus in Relational Memory

Authors: Wei Ding[1], Yijing Lin[2], Bo Zhang[1]*, Jia Liu[1]*

Affiliation:

[1]Department of Psychology & Tsinghua Laboratory of Brain and Intelligence,

Tsinghua University, Beijing 100084, China

[2]Faculty of Psychology, Beijing Normal University, Beijing, China

*Correspondence:

bo_zhang@tsinghua.edu.cn (Bo Zhang)

liujiaTHU@tsinghua.edu.cn (Jia Liu)

Abstract

Memory, woven into the very fabric of consciousness, serves as a time-traveling vessel in the mind, using detailed recollections not just for nostalgic reflection but as an abstract map for charting unknown futures. Here, we employed fMRI to investigate how the hippocampus (HPC) encodes detailed experiences into abstract knowledge (i.e., formation) and uses this knowledge for decision making (i.e., utilization) when human participants learned and then utilized spatial-temporal relations in a relational memory task. We found a functional gradient along the anterior-posterior axis of the HPC, characterized by representational similarity and functional connectivity with the autobiographical network. Here, the posterior HPC was more actively engaged in memory formation, whereas the anterior HPC was predominantly involved in memory utilization. Our computational modeling of relational memory further established a causal link between this functional gradient and the HPC's well-documented anatomical gradient, as optimal task performance arose from a combination of a fine-grained representation of past experiences by the posterior HPC and a coarser representation of abstract knowledge for future planning by the anterior HPC. This scale-dependent coding scheme led to the emergence of grid-like, heading direction-like, and place-like units in our neural network model, analogous to those discovered in biological brains. Taken together, our study revealed the HPC's functional gradient in representing relational memory, and further connected it to the anatomical gradient of place cells, supporting a unified framework where both spatial and episodic memory rely on relational representations that integrate spatial localization with temporal continuity.

Keywords: Hippocampus; Relational Memory; Multi-Scale Representation, fMRI, Deep Learning

Introduction

The core function of episodic memory is to remember the past and predict the future (Schacter & Addis, 2007; Addis et al., 2007; Addis et al., 2009; Schacter et al., 2012; Schacter & Madore, 2016; Gershman, 2017; Josselyn & Tonegawa, 2020; Namboodiri & Stuber, 2021). This process apparently relies on different levels of precision during encoding and retrieval stages. Encoding is often tasked with meticulously recording intricate details, necessitating fine-grained representational capacity to capture the nuanced differentiation of individual experiences (Wixted et al., 2018; Borders et al., 2022). In contrast, the retrieval process, especially for decision-making, tends to utilize a more generalized and abstracted memory schema, as this coarse form of recall provides the essential framework required to navigate through decision-making processes without the encumbrance of excessive detail (Evensmoen et al., 2015; Audrain & McAndrews, 2022). However, it is unclear how the brain accomplishes this fascinating interplay between the granular encoding and the abstracted retrieval that underscores the versatility and sophistication of our memory systems.

Recently, a unified theoretical framework has been proposed to associate episodic memory with spatial memory in the hippocampus (HPC) (Cohen & Eichenbaum, 1993; Eichenbaum, 2000; Eichenbaum & Cohen, 2014), evidenced by the abstract cognitive map (Park et al., 2020), cognitive graph (Peer et al., 2021), schema (Farzanfar et al., 2023), and geometry (Nieh et al., 2021). This framework offers a novel perspective on the HPCs role in memory encoding and retrieval by integrating episodic and spatial memory into a cohesive concept of relational memory. Interestingly, a representational gradient of the HPC in spatial scale along its anterior-posterior axis has been identified (Kjelstrup et al., 2008; Brun et al., 2008; Peer et al., 2019). Specifically, place cells in the anterior HPC of primates (or ventral HPC of rodents) show larger receptive fields than those in the posterior HPC (or dorsal HPC of rodents) (Poppenk et al., 2013; Collin et al., 2015; Robinson et al., 2015; Brunec et al., 2018). In addition, functional divisions of labor along this

representational gradient have also been identified. The anterior HPC is more engaged

during autobiographical memory retrieval (Cabeza & St Jacques, 2007; McCormick et

al., 2015; Mazzoni et al., 2019). In contrast, the posterior HPC is preferentially

implicated in both short-term (Fernandez et al., 1998; Giovanello et al., 2009;

Woolley et al., 2015; Zeithamova & Bowman, 2020) and long-term learning (Maguire

et al., 2000; Weisberg et al., 2019; Weisberg & Ekstrom, 2021). Considering these

anatomical and functional divisions, and the different precision levels required

between encoding and retrieval stages, we hypothesize that the posterior HPC, with its

smaller receptive fields and therefore higher precision, may be the site for

fine-grained encoding of detailed experiences into abstract representations (i.e.,

abstract knowledge). In contrast, retrieval of this abstract knowledge may occur in the

anterior HPC, where the larger receptive fields imply a lower precision.

79   To test this hypothesis, we utilized a relational memory (RM) task

(Insa-Cabrera et al., 2011; Tartaglia et al., 2017), where human participants were

tasked with mentally constructing and utilizing a sequence of spatial positions to

predict subsequent positions (Fig. 1). In the task, participants learned the temporal

structure of spatial positions through feedback on random guesses in the beginning

steps of each trial (i.e., the relation formation state). Subsequently, they applied this

learned sequence to accurately predict each position in the sequence in the later steps

of each trial (i.e., the utilization state). Therefore, this task design allowed separate

analysis of neural representations during memory formation and utilization states. In

line with our hypothesis, we found greater involvement of the posterior HPC in the

formation state, while the anterior HPC was more engaged in the utilization state,

aligning with the representational gradient along the anterior-posterior axis of the

HPC. To delve deeper into the underlying mechanism, we developed a hybrid neural

network model combining convolutional and Long Short-Term Memory (LSTM)

components to examine the impact of spatial scale on the formation and utilization

states of memory. Computational modeling established a causal link that the relational

memory's effectiveness hinged on fine-grained encoding and coarse retrieval

representations. In short, our study suggests that the HPC exhibits multi-scale

representations along the anterior-posterior axis tailored to computational demands of

memory at different stages.

Results

Memory formation and utilization states in relational memory task

A series of numeric strings, each composed of digits drawn from the set [1, 2, 3]

and varying in length from 2 to 8, was constructed to represent sequences of locations

for *Good* cues (denoted by a star) and *Bad* cues (denoted by a cross) within a single

iteration, which were allocated to three horizontally aligned boxes on the screen (Fig.

1A). In a trial, sequences for both *Good* and *Bad* cues, derived from different numeric

strings but of equal length, were iteratively presented until reaching a total length of

30 steps, respectively (Fig. 1B). Participants were instructed to place a *Self* marker

(denoted by an avatar) at the anticipated location of the next *Good* cue while avoiding

the location of the *Bad* cue, utilizing feedback from preceding steps. Participants'

performance was assessed by calculating the number of correctly placing the *Self*

marker in the box containing the *Good* cue (i.e., reward) minus the number of

incorrectly placing in the box with the *Bad* cue (i.e., punishment). Through this

process, participants first learned the spatiotemporal relations of both *Good* and *Bad*

cues, then applied this knowledge to predict the locations of the next *Good* and *Bad*

cues. Participants' behavioral performance exhibited a characteristic piecewise-like

progression, initially manifesting a rapid rise in accuracy from random guessing,

followed by a plateau of correct responses (Fig. 1C). This behavioral pattern was

observed in all tested lengths of numeric strings, though a noticeable decrease in

accuracy and a delay in the transition point were observed with increasing length of

the numeric strings (Fig. 1D). To quantify the observation, we evaluated the fitness of

a piecewise linear function to participants' behavioral performance, against various

functions such as logistic, quadratic, logarithmic, and linear functions, using the

coefficient of determination (R^2) as the metric. Consistent with the observation, the

piecewise linear function showed the highest fitness to the behavioral performance

(Fig. 1E; *M* = 0.96, *SD* = 0.26; *p* < 0.05, corrected for multiple comparisons using

permutation) compared to the alternative functions (logistic: [*M* = 0.90, *SD* = 0.04];

quadratic: [*M* = 0.90, *SD* = 0.03]; logarithmic function [*M* = 0.87, *SD* = 0.04]; and

linear function: [*M* = 0.64, *SD* = 0.06]). This piecewise pattern suggests the existence

of two distinct memory states with the task: one primarily pertaining to memory

formation and the other to its subsequent utilization.

Figure 1. Experimental paradigm and behavioral performance. (A) Experimental paradigm of
the RM task. A reward was presented when correctly placing the *Self* marker (avatar) in the same
box (green) with the next *Good* cue (star), while a punishment was given when incorrectly placing
the *Self* marker in the same box (red) with the next *Bad* cue (cross). Participants were encouraged
to maximize reward and avoid punishment. (B) Exemplar sequences for the *Good* and *Bad* cues.
The length of numeric strings is 3. The *Good* cue shows a [Right, Left, Middle] spatiotemporal
sequence, while the *Bad* cue shows a [Left, Middle, Right] sequence. (C) Behavioral performance.
Behavioral performance, averaged across sequences and participants, was improved as a function
of increased steps. (D) The piecewise-like pattern, indexed by solid lines, was observed in all
tested lengths of numeric strings. (E) The highest fitness to the behavioral performance was the
piecewise linear function, as compared to the logistic, quadratic, logarithmic and linear functions.
The dashed grey line denotes the uncorrected threshold of permutation, while the dashed black

line denotes the corrected threshold with multiple comparisons. Error bars represent standard
errors across participants.

Neural correlates of memory formation and utilization

Upon identifying two distinct memory states in the RM task, we further replicated

previous research (Sullivan Giovanello et al., 2004; Olson et al., 2006; Hannula et al.,

2006; Giovanello et al., 2009; Schwarb et al., 2016; Zheng et al., 2024) demonstrating

hippocampal activation in relational integration using representational similarity

analysis (RSA; Kriegeskorte et al., 2006) and functional connectivity (FC) approaches.

In the RSA analysis, we calculated the multivoxel patterns of HPC activity during the

RM task for each trial and constructed a correlation coefficient matrix across trials for

each voxel (see Methods). We found that all subregions of the HPC, including

Dentate Gyrus, Cornu Ammonis, and Subiculum, showed significantly higher

representational similarity in comparisons to the resting state (Fig. S1; initial

threshold: $p < 0.01$, corrected for multiple comparisons by permutation). In the FC

analysis, we designated the HPC as a seed region and computed Pearson's correlation

coefficients between its averaged time course and that of other brain regions during

the RM task (see Methods). We found significantly enhanced FC between the HPC

and the autobiographical network (Svoboda et al., 2006; Burianova et al., 2010),

including the Medial Prefrontal Cortex, Posterior Cingulate Cortex, and Angular

Gyrus, during the task state in comparison to the resting state (Fig. S2; initial

threshold: $p < 0.01$, corrected for multiple comparisons by permutation). Taken

together, these findings align with previous research (Giovanello et al., 2009; Huijbers

et al., 2011; Raichle, 2015; Smallwood et al., 2021), confirming the role of the HPC

in relational memory processing during the RM task.

To investigate the neural representations of the HPC associated with the

formation and utilization of relational memory, the BOLD signal series of the RM

task was segregated into the formation and utilization states, which were

approximately demarcated to have equal temporal durations (see Methods). An RSA

analysis was performed to extract the neural representation profiles for the resting,

formation, and utilization states, respectively (Fig. 2A). As expected, the

representational similarity in the HPC was significantly higher in both the formation

and utilization states than that in the resting state (Fig. 2B & E, initial threshold of $p =$

0.01, corrected for multiple comparisons by permutation).

Interestingly, the peak of the representational similarity in the formation state was

located at the posterior HPC (MNI coordinates = [57, 45, 36], $t(15) = 6.11$, $p < 0.001$,

two-tailed), while in the utilization state, it was identified in the anterior HPC (MNI

coordinates = [58, 57, 26]; $t(15) = 4.05$, $p < 0.001$, two-tailed). This suggests an

association between the functional dissociation in memory states and the anatomical

gradient in the HPC. To quantify this observation, we averaged the representational

similarity along the y axis of MNI coordinate system, which produced a vector

demonstrating the variation in representational similarity along the hippocampal long

axis for each memory state. First, a reverse pattern was observed between the two

memory states, with higher representational similarity of memory formation in the

posterior HPC and for memory utilization in the anterior HPC (Fig. 2C & F; initial

threshold $p = 0.01$, corrected for multiple comparisons by permutation). Second, we

partitioned the HPC into three equal volumetric portions along its long axis (Tompary

& Davachi, 2017) and then performed an ROI analysis to explore the relationship

between memory state and hippocampal gradient. We found that the posterior HPC

showed significantly higher representational similarity as compared to the anterior

HPC during memory formation (Fig. 2D; $t(15) = 2.59$, $p < 0.05$, two-tailed).

Conversely, the anterior HPC showed significantly higher representational similarity

as compared to the posterior HPC during memory utilization (Fig. 2G; $t(15) = 2.66$, p

< 0.05, two-tailed). These findings illustrated a functional division of labor along

hippocampal gradient for the two memory states in relational memory, suggesting that

memory formation particularly relies on the fine-grained representation in the

posterior HPC, while memory utilization preferentially involves the coarser

representation in the anterior HPC.

Figure 2. Function gradient in the HPC. (A) Schematic overview of RSA analysis. Multi-voxel

patterns of the resting, formation and utilization states were extracted by a general linear model

(GLM). The similarity matrix was constructed using a searchlight-based Pearson's correlation of

the multi-voxel patterns among trials. This matrix was fitted with another GLM with states

specified by binary regressors. Within the binary matrix, blue, brown, and green points denote the

"same" state. The estimated parameters of the GLM were then sent to the second-level analyses.

(B) Neural representation of formation state in the HPC. Each point represents a voxel in the left

and right hippocampus, respectively. The value at each point, indexed by t-value, reflects the

contrast in representational similarity from the memory formation relative to the resting state. The

X-, Y-, and Z-axes denote the MNI coordinates of the HPC. Specifically, the Y-axis corresponds

to the hippocampal long axis, with green and purple colors representing the anterior and posterior

HPC, respectively. (C) Variation in representational similarity along the hippocampal long axis

during memory formation. The black line represents the averaged similarity across participants,

with the shaded area denoting standard error. Gray dotted lines indicate the uncorrected thresholds

derived from the 5th and 95th percentiles of the permutation distribution at each coordinate of the

Y-axis, whereas green and purple dotted lines indicate the corrected threshold defined by the

maximum of uncorrected thresholds. (D) ROI analysis of representational similarity between the

anterior and posterior HPC. The representational similarity of memory formation state was

significantly higher in the posterior HPC than that in the anterior HPC. (E – G) Neural

representation of memory utilization state in the HPC. *: $p < 0.05$; Error bars: standard error.

Given the aforementioned evidence of the HPC's division in representational

similarity and its FC with the autobiographical network during the MR task, we

predicted that the posterior HPC should predominantly connect with the

autobiographical network during the formation state, while the anterior HPC should

show stronger FC with this network during the utilization state.

To test this conjecture, we analyzed the FC between the HPC and the

autobiographical network during the formation and utilization states of the RM task,

respectively. Note that the medial temporal lobe was excluded from this analysis to

avoid overlap with the HPC. We found that the posterior HPC showed stronger FC

with the autobiographical network during the formation state (Fig. 3A; initial

threshold $p = 0.01$, corrected for multiple comparisons by permutation), with the FC

peak located at the coordinate [55, 52, 27] ($t(15) = 4.98$, $p < 0.001$, two-tailed).

Conversely, during the utilization state, stronger FC with the autobiographical

network was found in the anterior HPC (Fig. 3B; initial threshold $p = 0.01$, corrected

for multiple comparisons by permutation), with the peak at [57, 61, 23] ($t(15) = 3.29$,

$p < 0.001$, two-tailed). To quantify this observation, a contrast analysis between the

utilization and formation states was performed on FC along the hippocampal long axis.

We found that the FC difference between the two states shifted from negative to

positive along the axis, moving from the posterior to anterior HPC (Fig. 3C; initial

threshold $p = 0.01$, corrected for multiple comparisons by permutation). This

connectivity gradient along the hippocampal long axis was further confirmed by a

significant two-way interaction between the memory state (formation versus

utilization) and the hippocampal gradient (posterior versus anterior) by an ROI

analysis (Fig. 3D; $F(1, 15) = 9.03$, $p = 0.004$). *Post-hoc* t-tests showed that in the

anterior HPC, the FC during the utilization state was significantly higher than that of

the formation state ($t(15) = 5.44$, $p < 0.001$, two-tailed), while a reverse pattern,

though not significant, was found in the posterior HPC ($t(15) = 1.55$, $p = 0.14$,

two-tailed). In summary, the FC analysis also reveals a connectivity gradient of the

HPC with the autobiographical network during the RM task.

Figure 3. Connectivity gradient in the HPC. (A) Difference in FC of the formation state relative

to the utilization state. Pearson's correlation was performed between the mean BOLD signal series

within the autobiographic network and that in each voxel of the HPC for the formation and

utilization states, respectively. The difference in FC was indexed by t-value. (B) Difference in FC

of the utilization state relative to formation state. (C) Difference in FC of the utilization state

relative to the formation state along the hippocampal long axis. (D) FC strength of memory state

(formation versus utilization) and hippocampal gradient (posterior versus anterior) compared to

the rest state revealed a significant interaction. *: $p < 0.05$; Error bars: standard error.

The causal link between functional and anatomical gradients

The findings from both representational similarity and functional connectivity

analyses suggest that the posterior HPC is predominantly involved in memory

formation and the anterior HPC in memory utilization. Interestingly, these function

and connectivity gradients coincide with the anatomical gradient of the HPC, where

the posterior HPC is characterized by a higher density of place cells with smaller

receptive fields, and the anterior HPC by place cells with larger receptive fields.

Specifically, previous studies have shown that the posterior HPC is preferentially

associated to both short- and long-term learning (Fernandez et al., 1998; Giovanello et

al., 2009; Woolley et al., 2015; Zeithamova & Bowman, 2020; Maguire et al., 2000;

Weisberg et al., 2019; Weisberg & Ekstrom, 2021), implying its role in encoding

information into an abstract, fine-grained representation. In contrast, the anterior HPC

is often co-activated with visual sensory regions during autobiographical memory

retrieval (Cabeza & St Jacques, 2007; McCormick et al., 2015; Mazzoni et al., 2019),

implying its involvement in computational processes of visual action at a coarse

precision. Therefore, if there is a causal anatomical-functional link, we would expect

the memory formation to require a fine-grained precision, and the memory utilization

to favor a coarser precision.

To test this hypothesis, we developed a hybrid Convolutional Long Short-Term

Memory (C-LSTM) neural network to simulate how information is encoded and then

retrieved during the RM task (Fig. 4A). The C-LSTM comprises three components: (1)

a convolutional layer for encoding the visual presentation of *Good* and *Bad* cue

sequences, (2) an LSTM layer for abstractly storing the spatiotemporal locations of

these cues, and (3) a transposed convolution layer for predicting the location of the

next *Good* cue through *Self* marker placement. A series of the C-LSTMs, varying the

kernel sizes of the convolutional layers (representing visual-action resolution, VR)

and the hidden sizes of the LSTM layer (representing memory resolution, MR), were

trained. In this context, the MR parameter corresponds to the resolution necessary for

memory formation, and the VR parameter to the resolution required by memory

utilization. Our aim was to determine which combinations of VR and MR yield

optimal performance of the C-LSTM in the RM task.

Computational simulations revealed that both the MR and VR parameters

significantly modulated C-LSTM's performance, which was characterized by the

prediction accuracy of *Good* cue location. Specifically, the performance increased

with the increase of the MR parameter ($F(14, 195) = 13.56$, $p < 0.001$) and as the

decrease of the VR parameter ($F(14, 195) = 4.39$, $p < 0.001$). Additionally, the

interaction between MR and VR was also significant ($F(1, 195) = 1.31$, $p < 0.05$),

suggesting that the increase of MR elevated the slope of the influence of VR on

performance. Therefore, optimal performance was reached by a C-LSTM with a high

MR value combined with a low VR value (Fig. 4B), aligning with our prediction that

memory formation requires a fine-grained representation, while memory utilization

prefers a coarse representation.

To further unveil how spatiotemporal information was encoded and then retrieved

in our model, we extracted the feature maps of each single unit in the transposed

convolution layer, because their responses directly determine model's decision. For

each unit, its weight was retained while the weights of all other units were set to zero.

Accordingly, the output of the deconvolutional layer yielded a feature map of this

single unit. Interestingly, the feature maps of deconvolutional units embedded the

spatial structure of visual stimuli in either the vertical dimension (Fig. 4C, top), the

horizontal dimension (Fig. 4C, bottom), or both the vertical and horizontal dimensions

(Fig. 4C, middle). These hierarchical activity patterns of neural units are analogous to

the place cells, head direction (HD) cells, and grid cells as observed in biological

brains (O'Keefe & Conway, 1978; Taube et al., 1990; Hafting et al., 2005).

Specifically, place-like units showed selective activation for the horizontal target

locations, HD-like units responded with a band-like pattern across the rows vertically

across the space, and grid-like units exhibited the square-like activation patterns

tessellating the entire space (Fig. 4C). To quantitatively identify these three types of

units in the transposed convolution layer and their roles on model decision, we first

applied Fast Fourier Transform (FFT) to identify the spatial frequency of the feature

map of each unit from 225 C-LSTMs (i.e., all possible pairs of 15 VRs with 15 MRs).

Specifically, grid-like units are characterized by the minimum spectral power at

3-cycle from horizontal and vertical axes, HD-like units was expected to show the

spectral power at 1-cycle in the vertical axis, and place-like units would exhibit the

spectral power at 1-cycle in horizontal axes. Second, we equally partitioned C-LSTMs

into three group (i.e., ①②③) according to their performance varied along the

diagonal of VR-MR matrix (Fig. 4B). In this way, the participation of the three types

of units can be accessed by the group of models from poor to optimal performance.

As the result, significant positive correlations were revealed for the number of either

grid-like or place-like units with model performance (Fig. 4D; grid-like unit: $r = 0.38$,

$p < 0.001$; place-like unit: $r = 0.71$, $p < 0.001$). Correspondingly, the FFT power of

these two types of unit significantly increased with model performance (Fig. 4E;

grid-like unit: $F(2, 132) = 70.02$, $p < 0.001$; place-like unit: $F(2, 132) = 177.72$, $p <$

0.001). However, no significant variation of the FFT power was found for HD-like

units among the models with diverse range of performance (Fig. 4D & E; $r = -0.019$,

$p > 0.05$; ANOVA: $F(2, 132) = 1.26$, $p = 0.29$). Therefore, the HD-like units appeared

consistently across models, regardless of performance (Fig. 4E, left); however, the

presence of grid- and place-like units decreased in models with medium performance

and was absent in those with poor performance (Fig. 4E, middle & right). This pattern

suggests a hierarchical emergence in relational memory processing, with HD-like

units appearing first, followed by grid- and place-like units (see also [Wills & Cacucci,

2014] for similar patterns in mice during the development).

Taken together, our computational model demonstrates a causal link between the

multi-scale representations in the HPC and the cognitive states of relational memory.

Importantly, the emergence of grid-like, HD-like, and place-like units in the C-LSTM

implies the essential role of the HPC in processing relational memory, aligning with

observed biological phenomena (O'Keefe & Conway, 1978; Taube et al., 1990;

Hafting et al., 2005).

Figure 4. Computational modeling of memory formation and utilization. (A) Architecture of

the hybrid neural network (C-LSTM). The C-LSTM comprises convolutional layers with an

LSTM. The input to the C-LSTM is the visual stimuli from the RM task, and the output is an image predicting the location of the next *Good* cue (denoted by a star). ConvBlock, FC, and DconvBlock denotes convolution layer, fully connected layer, and deconvolutional layer, respectively. MR denotes the size of the hidden state in the LSTM, while VR denotes the kernel size of the deconvolutional layers. (B) Behavioral Performance of C-LSTM. The performance varied significantly across combinations of MR and VR. Each cell in the matrix indicates model performance for a specific pair of VR and MR, color-coded for prediction accuracy (dark blue: poor; light yellow: optimal). Models outlined in color were chosen for further analyses in (E). (C) Exemplar feature maps from deconvolutional layer units. The feature maps of these units were analogous to the activation patterns of biological head direction cells (top), grid cells (middle), and place cells (bottom). (D) Pearson correlations between FFT power and model performance across unit types. (E) Averaged FFT power across unit types. The presence of the HD-like, grid-like, and place-like units in models with poor ①, medium ②, and optimal ③ performance. Dashed black line denotes regression line. Shaded gray area denotes SE. Error bars: standard error.

Discussion

The hippocampus acts as a bridge between our past and future, enabling us to learn from previous experiences and utilize that knowledge to navigate future challenges (Schacter & Addis, 2007; Addis et al., 2007; Brown et al., 2016; Gershman, 2017; Josselyn & Tonegawa, 2020; Namboodiri & Stuber, 2021). In this study, we used fMRI to investigate how the hippocampal multi-scale representation bridges the two key states of relational memory: formation and utilization. Our study revealed a functional gradient along the anterior-posterior axis of the HPC, characterized by representational similarity and functional connectivity with the autobiographical network. Specifically, the posterior HPC was predominantly involved in memory formation, while the anterior HPC was more actively engaged in memory utilization. Computational modeling of relational memory further established a causal link between the functional gradient and the HPC's well-documented anatomical gradient, as evidenced by the size of place fields progressively decreasing along the anterior-posterior axis (Kjelstrup et al., 2008; Brun et al., 2008; Brunec et al., 2018).

That is, optimal performance in relational memory tasks likely derived from the
fine-grained representation of past experiences by the posterior HPC and the coarser
representation of abstract knowledge for future planning by the anterior HPC. Taken
together, our study not only discovered the HPC's functional gradient for representing
relational memory but also demonstrated its origin from the anatomical gradient of
place cells, hereby echoing a fundamental principle in neuroscience that structure
determines functionality (Suárez et al., 2020; Bassett & Sporns, 2017;
Babaeeghazvini et al., 2021).

The functional division of labor in the HPC has been extensively studied,
evidenced by the involvement of partial hippocampal volumes in a specific memory
task. For example, the retrieval of autobiographical memory selectively activated the
anterior HPC (Cabeza & St Jacques, 2007; Giovanello et al., 2009; Huijbers et al.,
2011; Raichle, 2015; McCormick et al., 2015; Mazzoni et al., 2019; Smallwood et al.,
2021), whereas in long-term learning, only the posterior HPC showed functional and
structural alterations in response to the encoding of spatial knowledge (Maguire et al.,
1997; Maguire et al., 2000; Maguire et al., 2006; Weisberg et al., 2019; Weisberg &
Ekstrom, 2021). Our study further extended these findings by incorporating both
memory formation and utilization in one experimental paradigm, where human
participants learned spatiotemporal sequences (i.e., memory formation) and then
utilized the learned relations for decision making (i.e., memory utilization). This
paradigm is proved efficient to study these two states of relational memory, as
evidenced by the behavioral performance displaying a piecewise-like pattern with a
turning point nicely separating these two states. Further, with two neural markers of
representational similarity within the HPC and functional connectivity between the
HPC and the autobiographical network, a functional gradient of the HPC was
discovered, with the posterior HPC primarily involved in memory formation and the
anterior HPC preferentially engaged in memory utilization.

Our computational modeling further linked this functional gradient to the
anatomical gradient, evidenced by physiological recordings showing a decrease in the
size of place fields along the anterior-posterior axis of the HPC (Poppenk et al., 2013;

Collin et al., 2015; Robinson et al., 2015; Brunec et al., 2018). By directly

manipulating the size of the hidden state in the LSTM (i.e., the resolution for memory

formation) and the kernel size of deconvolutional layers (i.e., the resolution for

memory utilization), we explored the parameter space to identify the model that

yielded the best performance. This blind exploration led us to a model exhibiting

optimal performance in the relational memory task, characterized by a large scale of

deconvolutional kernel size (i.e., low VR) and a small scale of LSTM hidden size (i.e.,

high MR). This observation provides a mechanistic insight into the alignment of the

functional and anatomical gradients. That is, during memory formation, smaller sizes

of place fields may facilitate the construction of high-precision abstract knowledge. In

contrast, during memory utilization, larger receptive fields may facilitate the

prioritization of action-related features over irrelevant ones, possibly through a

mechanism of biased competition (Desimone & Duncan, 1995; Reynolds et al., 1999).

Therefore, the functional and anatomical gradients in the HPC apparently reflect a

computational principle tied to the multi-scale representation by place cells (Poppenk

et al., 2013; Collin et al., 2015; Robinson et al., 2015; Brunec et al., 2018).

Hippocampal place cells are renowned for their pivotal role in creating a

cognitive map of an environment by encoding specific locations and directions during

navigation (Schiller et al., 2015; Epstein et al., 2017). Our study extends these known

functionalities, proposing their significant contribution to both the formation and

utilization of relational memory. The integral role of place cells aligns with the

concept that the HPC provides a unified framework where spatial memory and

episodic memory rely on relational representations that integrate spatial localization

with temporal continuity (Cohen & Eichenbaum, 1993; Eichenbaum, 2000;

Eichenbaum & Cohen, 2014). Consistent with this speculation, our analysis of the

feature maps of single units in the deconvolution layers revealed the presence of

place-like units, as well as HD-like and grid-like units. Critically, the absence of these

units, especially the place-like and grid-like units, significantly impaired the model's

performance in the relational memory task. These self-emerged units in our

computational model, analogous to their biological counterparts essential in

navigation, may constitute the implementational basis for relational representations.

Therefore, our findings not only shed light on a broader application of hippocampal

place cells in relational memory processing but also reinforce the concept of a unified

framework underpinned by these specialized cells in the hippocampus (Epstein et al.,

2017; Whittington et al., 2022; Sorscher et al., 2023).

There are several limitations warranting further investigation. First, our study

suggests a continuous functional gradient along the anterior-posterior axis of the HPC,

contrasting with the view of distinct functionalities for the posterior and anterior

regions. However, this functional gradient, although in alignment with the anatomical

gradient in the size of place fields, may also be influenced by our experimental

paradigm. In the RM task, memory formation and utilization were intertwined; for

example, elements of memory utilization were present even during the formation state

due to task requirements. Similarly, in our fMRI data analysis, the BOLD signal series

were bifurcated into two equal-length segments, the first half as the formation state

and the second half as the utilization state, primarily because a distinct turning point

at the trial level was not prominent. This intermingling nature of the formation and

utilization states may contribute to the observed gradient in both representational

similarity and functional connectivity. Future research is needed to more distinctly

decouple these two states to better depict the functional gradient of the HPC. Second,

the memory formation and utilization states in our study are markedly different from

the states of retrieving the past and imagining the future, which are associated with

scene construction (Gaesser et al., 2013) and engage both the anterior and posterior

HPC (Strange et al., 2014). Future research should aim to characterize relational

memory from multiple dimensions, such as spatial and temporal dimensions, and then

integrate these dimensions to comprehensively understand relational memory in the

hippocampus, hereby offering deeper insights into the multifaceted functional roles of

the HPC. Third, while our model successfully simulated the hippocampal multi-scale

coding at behavioral level, it is important to recognize its limitations in terms of

biological plausibility, especially concerning its anatomical implementation. Future

research should aim to develop models that more accurately resemble the HPC's

actual anatomical structure, thereby bridging the gap between computational

modeling and biological mechanisms of the HPC.

Acknowledgments:

The work was supported by China Postdoctoral Science Foundation (2022M710470,

B.Z.), Beijing Municipal Science & Technology Commission & Administrative

Commission of Zhongguancun Science Park (Z221100002722012), and Double

First-Class initiative Funds for Discipline Construction of Tsinghua University (J.L.).

Author contributions:

J.L. conceived the study. Y.L. developed the task. W.D and Y.L collected the

behavioral and fMRI data. W.D. performed the data analyses under B.Z.'s supervision.

B.Z. developed the C-LSTM network. B.Z. and W.D. performed the network

simulation. W.D., B.Z. and J.L. wrote the paper.

Competing interests:

The authors declare no competing interests.

Data availability:

The data that support the findings of the present study are available from the

corresponding author (J.L.) upon request.

Code availability:

All analyses reported in the present study were conducted with the customized codes

written in Python (version 3.9) and Matlab (version 2021a). The codes will be

available from the corresponding author (J.L.) upon request. The neuroimaging

toolbox and machine learning framework used by the present work are publicly

available as following: FSL (version 6.0, https://fsl.fmrib.ox.ac.uk/fsl/fslwiki),

BrainNet Viewer (version 1.7, https://www.nitrc.org/projects/bnv/), and Torch

(version 1.9, https://pytorch.org/).

References

Addis, D. R., Wong, A. T., & Schacter, D. L. (2007). Remembering the past and imagining the future: common and distinct neural substrates during event construction and elaboration. *Neuropsychologia, 45*(7), 1363–1377. https://doi.org/10.1016/j.neuropsychologia.2006.10.016

Addis, D. R., Pan, L., Vu, M.-A., Laiser, N., & Schacter, D. L. (2009). Constructive episodic simulation of the future and the past: Distinct subsystems of a core brain network mediate imagining and remembering. *Neuropsychologia, 47*(11), 2222–2238. https://doi.org/10.1016/j.neuropsychologia.2008.10.026

Audrain, S., & McAndrews, M. P. (2022). Schemas provide a scaffold for neocortical integration of new memories over time. *Nature Communications, 13*(1), 5795. https://doi.org/10.1101/2020.10.11.335166

Bartels, A., & Zeki, S. (2005). The chronoarchitecture of the human brain—natural viewing conditions reveal a time-based anatomy of the brain. *NeuroImage, 22*(1), 419–433. https://doi.org/10.1016/j.neuroimage.2004.01.007

Birn, R. M., Diamond, J. B., Smith, M. A., & Bandettini, P. A. (2006). Separating respiratory-variation-related fluctuations from neuronal-activity-related fluctuations in fMRI. *Neuroimage, 31*(4), 1536–1548. https://doi.org/10.1016/j.neuroimage.2006.02.048

Brun, V. H., Solstad, T., Kjelstrup, K. B., Fyhn, M., Witter, M. P., Moser, E. I., & Moser, M. B. (2008). Progressive increase in grid scale from dorsal to ventral medial entorhinal cortex. *Hippocampus, 18*(12), 1200–1212. https://doi.org/10.1002/hipo.20504

Burianova, H., McIntosh, A. R., & Grady, C. L. (2010). A common functional brain network for autobiographical, episodic, and semantic memory retrieval. *Neuroimage, 49*(1), 865–874. https://doi.org/10.1016/j.neuroimage.2009.08.066

Brown, T., Carr, V., LaRocque, K., Favila, S., Gordon, A., Bowles, B., Bailenson, J., & Wagner, A. (2016). Prospective representation of navigational goals in the

human hippocampus. *Science, 352,* 1323 – 1326.
https://doi.org/10.1126/science.aaf0784

Bassett, D. S., & Sporns, O. (2017). Network neuroscience. *Nature Neuroscience,*
20(3), 353–364. https://doi.org/10.1038/nn.4502

Brunec, I. K., Bellana, B., Ozubko, J. D., Man, V., Robin, J., Liu, Z. X., &
Moscovitch, M. (2018). Multiple scales of representation along the hippocampal
anteroposterior axis in humans. *Current Biology, 28*(13), 2129–2135.
https://doi.org/10.1016/j.cub.2018.05.016

Babaeeghazvini, P., Rueda-Delgado, L. M., Gooijers, J., Swinnen, S. P., &
Daffertshofer, A. (2021). Brain Structural and Functional Connectivity: A
Review of Combined Works of Diffusion Magnetic Resonance Imaging and
Electro-Encephalography. *Frontiers in Human Neuroscience, 15,* 721206.
https://doi.org/10.3389/fnhum.2021.721206

Borders, A. A., Ranganath, C., & Yonelinas, A. P. (2022). The hippocampus supports
high-precision binding in visual working memory. *Hippocampus, 32*(3),
217–230. https://doi.org/10.1002/hipo.23401

Cohen, N. J., & Eichenbaum, H. (1993). *Memory, amnesia, and the hippocampal*
system. MIT press. https://doi.org/10.5860/choice.31-5148

Conway, M. A., Pleydell-Pearce, C. W., & Whitecross, S. E. (2001). The
neuroanatomy of autobiographical memory: A slow cortical potential study of
autobiographical memory retrieval. *Journal of Memory and Language, 45*(3),
493–524. https://doi.org/10.1006/jmla.2001.2781

Cabeza, R., & St Jacques, P. (2007). Functional neuroimaging of autobiographical
memory. *Trends in cognitive sciences, 11*(5), 219–227.
https://doi.org/10.1016/j.tics.2007.02.005

Chadwick, M. J., Bonnici, H. M., & Maguire, E. A. (2012). Decoding information in
the human hippocampus: a user's guide. *Neuropsychologia, 50*(13), 3107-3121.
https://doi.org/10.1016/j.neuropsychologia.2012.07.007

Collin, S. H., Milivojevic, B., & Doeller, C. F. (2015). Memory hierarchies map onto

the hippocampal long axis in humans. *Nature neuroscience, 18*(11), 1562–1564.

https://doi.org/10.1038/nn.4138

Desimone, R., & Duncan, J. (1995). Neural mechanisms of selective visual attention.

Annual review of neuroscience, 18(1), 193–222.

https://doi.org/10.1146/annurev.ne.18.030195.001205

Eichenbaum, H. (2000). Hippocampus: mapping or memory?. *Current biology,*

10(21), R785–R787. https://doi.org/10.1016/S0960-9822(00)00763-6

Eichenbaum, H., & Cohen, N. J. (2014). Can we reconcile the declarative memory

and spatial navigation views on hippocampal function? *Neuron, 83*(4), 764–770.

https://doi.org/10.1016/j.neuron.2014.07.032

Evensmoen, H. R., Ladstein, J., Hansen, T. I., Møller, J. A., Witter, M. P., Nadel, L.,

& Håberg, A. K. (2015). From details to large scale: The representation of

environmental positions follows a granularity gradient along the human

hippocampal and entorhinal anterior–posterior axis. *Hippocampus, 25*(1),

119–135. https://doi.org/10.1002/hipo.22357

Epstein, R. A., Patai, E. Z., Julian, J. B., & Spiers, H. J. (2017). The cognitive map in

humans: spatial navigation and beyond. *Nature Neuroscience, 20*(11),

1504–1513. https://doi.org/10.1038/nn.4656

Fernandez, G., Weyerts, H., Schrader-Bölsche, M., Tendolkar, I., Smid, H. G.,

Tempelmann, C., ... & Heinze, H. J. (1998). Successful verbal encoding into

episodic memory engages the posterior hippocampus: a parametrically analyzed

functional magnetic resonance imaging study. *Journal of Neuroscience, 18*(5),

1841–1847. https://doi.org/10.1523/JNEUROSCI.18-05-01841.1998

Fox, M. D., Snyder, A. Z., Vincent, J. L., Corbetta, M., Van Essen, D. C., & Raichle,

M. E. (2005). The human brain is intrinsically organized into dynamic,

anticorrelated functional networks. *Proceedings of the National Academy of*

Sciences, 102(27), 9673–9678. https://doi.org/10.1073/PNAS.0504136102

Farzanfar, D., Spiers, H. J., Moscovitch, M., & Rosenbaum, R. S. (2023). From

cognitive maps to spatial schemas. *Nature Reviews Neuroscience, 24*(2), 63–79.

https://doi.org/10.1038/s41583-022-00655-9

Giovanello, K. S., Schnyer, D., & Verfaellie, M. (2009). Distinct hippocampal regions

make unique contributions to relational memory. *Hippocampus, 19*(2), 111–117.

https://doi.org/10.1002/hipo.20506

Gaesser, B., Spreng, R. N., McLelland, V. C., Addis, D. R., & Schacter, D. L. (2013).

Imagining the future: Evidence for a hippocampal contribution to constructive

processing.   *Hippocampus,*   *23*(12),   1150–1161.

https://doi.org/10.1002/hipo.22152

Gershman, S. J. (2017). Predicting the past, remembering the future. *Current Opinion*

in Behavioral Sciences, 17, 7–13. https://doi.org/10.1016/j.cobeha.2017.05.025

Hafting, T., Fyhn, M., Molden, S., Moser, M. B., & Moser, E. I. (2005).

Microstructure of a spatial map in the entorhinal cortex. *Nature, 436*(7052),

801–806. https://doi.org/10.1038/nature03721

Hannula, D. E., Tranel, D., & Cohen, N. J. (2006). The long and the short of it:

relational memory impairments in amnesia, even at short lags. *Journal of*

Neuroscience,   *26*(32),   8352–8359.

https://doi.org/10.1523/JNEUROSCI.5222-05.2006

Huijbers, W., Pennartz, C. M., Cabeza, R., & Daselaar, S. M. (2011). The

hippocampus is coupled with the default network during memory retrieval but

not   during   memory   encoding.   *PLoS   ONE,   6*(4),   e17463.

https://doi.org/10.1371/journal.pone.0017463

Insa-Cabrera, J., Dowe, D. L., Espana-Cubillo, S., Hernández-Lloreda, M. V., &

Hernández-Orallo, J. (2011). Comparing humans and AI agents. *In Artificial*

General Intelligence: 4th International Conference, AGI 2011, Mountain View,

CA, USA, August 3–6, 2011. Proceedings 4 (pp. 122–132). Springer Berlin

Heidelberg. https://doi.org/10.1007/978-3-642-22887-2_13

Jenkinson, M., Smith, S., 2001. A global optimisation method for robust affine

registration of brain images. *Medical image analysis, 5*(2), 143–156.

https://doi.org/10.1016/s1361-8415(01)00036-6

Jenkinson, M., Beckmann, C. F., Behrens, T. E., Woolrich, M. W., & Smith, S. M.

(2012).   Fsl.   *Neuroimage, 62*(2),   782–790.

https://doi.org/10.1016/j.neuroimage.2011.09.015

Josselyn, S. A., & Tonegawa, S. (2020). Memory engrams: Recalling the past and

imagining   the   future.   *Science, 367*(6473),   eaaw4325.

https://doi.org/10.1126/science.aaw4325

Kriegeskorte, N., Goebel, R., & Bandettini, P. (2006). Information-based functional

brain mapping. *Proceedings of the National Academy of Sciences, 103*(10),

3863–3868. https://doi.org/10.1073/pnas.0600244103

Kjelstrup, K. B., Solstad, T., Brun, V. H., Hafting, T., Leutgeb, S., Witter, M. P., ... &

Moser, M. B. (2008). Finite scale of spatial representation in the hippocampus.

Science, 321(5885), 140–143. https://doi.org/10.1126/science.1157086

Kriegeskorte, N., Mur, M., Ruff, D. A., Kiani, R., Bodurka, J., Esteky, H., Bandettini,

P. A. (2008). Matching Categorical Object Representations in Inferior Temporal

Cortex   of   Man   and   Monkey.   *Neuron, 60*(6),   1126–1141.

https://doi.org/10.1016/j.neuron.2008.10.043

Maguire, E. A., Frackowiak, R. S., & Frith, C. D. (1997). Recalling routes around

London: activation of the right hippocampus in taxi drivers. *The Journal of*

Neuroscience, 17(18),   7103–7110.

https://doi.org/10.1523/JNEUROSCI.17-18-07103.1997

Maguire, E. A., Gadian, D. G., Johnsrude, I. S., Good, C. D., Ashburner, J.,

Frackowiak, R. S., & Frith, C. D. (2000). Navigation-related structural change in

the hippocampi of taxi drivers. *Proceedings of the National Academy of Sciences*

of   the   United   States   of   America, 97(8),   4398–4403.

https://doi.org/10.1073/PNAS.070039597

Maguire, E. A., Woollett, K., & Spiers, H. J. (2006). London taxi drivers and bus drivers: A structural MRI and neuropsychological analysis. *Hippocampus, 16*(12), 1091–1101. https://doi.org/10.1002/HIPO.20233

Miyawaki, Y., Uchida, H., Yamashita, O., Sato, M. A., Morito, Y., Tanabe, H. C., ... & Kamitani, Y. (2008). Visual image reconstruction from human brain activity using a combination of multiscale local image decoders. *Neuron, 60*(5), 915-929. https://doi.org/10.1016/j.neuron.2008.11.004

McCormick, C., St-Laurent, M., Ty, A., Valiante, T. A., & McAndrews, M. P. (2015). Functional and effective hippocampal–neocortical connectivity during construction and elaboration of autobiographical memory retrieval. *Cerebral cortex, 25*(5), 1297–1305. https://doi.org/10.1093/cercor/bht324

Mazzoni, G., Clark, A., De Bartolo, A., Guerrini, C., Nahouli, Z., Duzzi, D., ... & Venneri, A. (2019). Brain activation in highly superior autobiographical memory: The role of the precuneus in the autobiographical memory retrieval network. *Cortex, 120*, 588–602. https://doi.org/10.1016/j.cortex.2019.02.020

Nichols, T. E., & Holmes, A. P. (2002). Nonparametric permutation tests for functional neuroimaging: a primer with examples. *Human brain mapping, 15*(1), 1-25. https://doi.org/10.1002/hbm.1058

Namboodiri, V. M. K., & Stuber, G. D. (2021). The learning of prospective and retrospective cognitive maps within neural circuits. *Neuron, 109*(22), 3552–3575. https://doi.org/10.1016/j.neuron.2021.09.034

Nieh, E. H., Schottdorf, M., Freeman, N. W., Low, R. J., Lewallen, S., Koay, S. A., ... & Tank, D. W. (2021). Geometry of abstract learned knowledge in the hippocampus. *Nature, 595*(7865), 80–84. https://doi.org/10.1038/s41586-021-03652-7

O'Keefe, J., & Conway, D. H. (1978). Hippocampal place units in the freely moving rat: why they fire where they fire. *Experimental Brain Research, 31*, 573–590. https://doi.org/10.1007/BF00239813

Olson, I. R., Page, K., Moore, K. S., Chatterjee, A., & Verfaellie, M. (2006). Working memory for conjunctions relies on the medial temporal lobe. Journal of

Neuroscience, *26*(17), 4596–4601. https://doi.org/10.1523/JNEUROSCI.1923-05.2006

Poppenk, J., Evensmoen, H. R., Moscovitch, M., & Nadel, L. (2013). Long-axis specialization of the human hippocampus. *Trends in Cognitive Sciences, 17*(5), 230–240. https://doi.org/10.1016/j.tics.2013.03.005

Philippi, C. L., Tranel, D., Duff, M., & Rudrauf, D. (2015). Damage to the default mode network disrupts autobiographical memory retrieval. *Social Cognitive and Affective Neuroscience, 10*(3), 318–326. https://doi.org/10.1093/scan/nsu070

Peer, M., Ron, Y., Monsa, R., & Arzy, S. (2019). Processing of different spatial scales in the human brain. *Elife, 8*, e47492. https://doi.org/10.7554/eLife.47492

Park, S. A., Miller, D. S., Nili, H., Ranganath, C., & Boorman, E. D. (2020). Map making: constructing, combining, and inferring on abstract cognitive maps. *Neuron, 107*(6), 1226–1238. https://doi.org/10.1016/j.neuron.2020.06.030

Peer, M., Brunec, I. K., Newcombe, N. S., & Epstein, R. A. (2021). Structuring knowledge with cognitive maps and cognitive graphs. *Trends in Cognitive Sciences, 25*(1), 37–54. https://doi.org/10.1016/j.tics.2020.10.004

Reynolds, J. H., Chelazzi, L., & Desimone, R. (1999). Competitive mechanisms subserve attention in macaque areas V2 and V4. *Journal of Neuroscience, 19*(5), 1736–1753. https://doi.org/10.1523/JNEUROSCI.19-05-01736.1999

Raichle, M. E. (2015). The brain's default mode network. *Annual Review of Neuroscience, 38*, 433–447. https://doi.org/10.1146/annurev-neuro-071013-014030

Robinson, J. L., Barron, D. S., Kirby, L. A., Bottenhorn, K. L., Hill, A. C., Murphy, J. E., ... & Fox, P. T. (2015). Neurofunctional topography of the human hippocampus. *Human Brain Mapping, 36*(12), 5018–5037. https://doi.org/10.1002/hbm.22936

Smith, S. M. (2002). Fast robust automated brain extraction. *Human brain mapping, 17*(3), 143-155. https://doi.org/10.1002/hbm.10062

Smith, S. M., Jenkinson, M., Woolrich, M. W., Beckmann, C. F., Behrens, T. E., Johansen-Berg, H., ... & Matthews, P. M. (2004). Advances in functional and

structural MR image analysis and implementation as FSL. *Neuroimage, 23,*

S208-S219. https://doi.org/10.1016/j.neuroimage.2004.07.051

Sullivan Giovanello, K., Schnyer, D. M., & Verfaellie, M. (2004). A critical role for

the anterior hippocampus in relational memory: Evidence from an fMRI study

comparing associative and item recognition. *Hippocampus, 14*(1), 5–8.

https://doi.org/10.1002/hipo.10182

Svoboda, E., McKinnon, M. C., & Levine, B. (2006). The functional neuroanatomy of

autobiographical memory: A meta-analysis. *Neuropsychologia, 44*(12),

2189–2208. https://doi.org/10.1016/j.neuropsychologia.2006.05.023

Schacter, D. L., & Addis, D. R. (2007). The cognitive neuroscience of constructive

memory: remembering the past and imagining the future. *Philosophical*

Transactions of the Royal Society B: Biological Sciences, 362(1481), 773–786.

https://doi.org/10.1098/rstb.2007.2087

Spreng, R. N., & Grady, C. L. (2010). Patterns of brain activity supporting

autobiographical memory, prospection, and theory of mind, and their relationship

to the default mode network. *Journal of cognitive neuroscience, 22*(6),

1112-1123. https://doi.org/10.1162/jocn.2009.21282

Sestieri, C., Corbetta, M., Romani, G. L., & Shulman, G. L. (2011). Episodic memory

retrieval, parietal cortex, and the default mode network: Functional and

topographic analyses. *Journal of Neuroscience, 31*(12), 4407–4420.

https://doi.org/10.1523/JNEUROSCI.3335-10.2011

Schacter, D. L., Addis, D. R., Hassabis, D., Martin, V. C., Spreng, R. N., & Szpunar,

K. K. (2012). The future of memory: Remembering, imagining, and the brain.

Neuron, 76(4), 677–694. https://doi.org/10.1016/j.neuron.2012.11.001

Strange, B. A., Witter, M. P., Lein, E. S., & Moser, E. I. (2014). Functional

organization of the hippocampal longitudinal axis. *Nature Reviews Neuroscience,*

15(10), 655–669. https://doi.org/10.1038/nrn3785

Schiller, D., Eichenbaum, H., Buffalo, E. A., Davachi, L., Foster, D. J., Leutgeb, S., &

Ranganath, C. (2015). Memory and space: Towards an understanding of the

cognitive map. *Journal of Neuroscience, 35*(41), 13904–13911. https://doi.org/10.1523/JNEUROSCI.2614-15.2015

Schacter, D. L., & Madore, K. P. (2016). Remembering the past and imagining the future: Identifying and enhancing the contribution of episodic memory. *Memory Studies, 9*(3), 245–255. https://doi.org/10.1177/1750698016645231

Schwarb, H., Johnson, C. L., McGarry, M. D., & Cohen, N. J. (2016). Medial temporal lobe viscoelasticity and relational memory performance. *Neuroimage, 132*, 534–541. https://doi.org/10.1016/j.neuroimage.2016.02.067

Suárez, L. E., Markello, R. D., Betzel, R. F., & Misic, B. (2020). Linking structure and function in macroscale brain networks. *Trends in Cognitive Sciences, 24*(4), 302–315. https://doi.org/10.1016/j.tics.2020.01.004

Smallwood, J., Bernhardt, B. C., Leech, R., Bzdok, D., Jefferies, E., & Margulies, D. S. (2021). The default mode network in cognition: A topographical perspective. *Nature Reviews Neuroscience, 22*(8), 503–513. https://doi.org/10.1038/s41583-021-00480-4

Sorscher, B., Mel, G. C., Ocko, S. A., Giocomo, L. M., & Ganguli, S. (2023). A unified theory for the computational and mechanistic origins of grid cells. *Neuron, 111*(1), 121–137. https://doi.org/10.1016/j.neuron.2022.09.030

Taube, J. S., Muller, R. U., & Ranck, J. B. (1990). Head-direction cells recorded from the postsubiculum in freely moving rats. I. Description and quantitative analysis. *Journal of Neuroscience, 10*(2), 420–435. https://doi.org/10.1523/JNEUROSCI.10-02-00420.1990

Tartaglia, E. M., Clarke, A. M., & Herzog, M. H. (2017). What to choose next? a paradigm for testing human sequential decision making. *Frontiers in Psychology, 8*, 312. https://doi.org/10.3389/fpsyg.2017.00312

Tompary, A., & Davachi, L. (2017). Consolidation promotes the emergence of representational overlap in the hippocampus and medial prefrontal cortex. *Neuron, 96*(1), 228-241. https://doi.org/10.1016/j.neuron.2017.09.005

Woolrich, M. W., Ripley, B. D., Brady, M., & Smith, S. M. (2001). Temporal
autocorrelation in univariate linear modeling of fMRI data. *Neuroimage, 14*(6),
1370–1386. https://doi.org/10.1006/nimg.2001.0931

Wise, R. G., Ide, K., Poulin, M. J., & Tracey, I. (2004). Resting fluctuations in arterial
carbon dioxide induce significant low frequency variations in BOLD signal.
Neuroimage, *21*(4), 1652-1664.
https://doi.org/10.1016/j.neuroimage.2003.11.025

Woolrich, M. W., Behrens, T. E., Beckmann, C. F., Jenkinson, M., Smith, S. M.
(2004). Multilevel linear modelling for fMRI group analysis using Bayesian
inference. *NeuroImage,* *21*(4), 1732–1747.
https://doi.org/10.1016/j.neuroimage.2003.12.023

Woolrich, M. W., Jbabdi, S., Patenaude, B., Chappell, M., Makni, S., Behrens, T., . . .
Smith, S. M. (2009). Bayesian analysis of neuroimaging data in
FSL. *NeuroImage,* *45*(1), S173–S186.
https://doi.org/10.1016/j.neuroimage.2008.10.055

Wills, T. J., & Cacucci, F. (2014). The development of the hippocampal neural
representation of space. *Current opinion in neurobiology, 24*, 111-119.
https://doi.org/10.1016/j.conb.2013.09.006

Woolley, D. G., Mantini, D., Coxon, J. P., D'Hooge, R., Swinnen, S. P., Wenderoth,
N. (2015). Virtual water maze learning in human increases functional
connectivity between posterior hippocampus and dorsal caudate. *Human Brain*
Mapping, 36(4), 1265–1277. https://doi.org/10.1002/hbm.22700

Wixted, J. T., Goldinger, S. D., Squire, L. R., Kuhn, J. R., Papesh, M. H., Smith, K.
A., Steinmetz, P. N. (2018). Coding of episodic memory in the human
hippocampus. *Proceedings of the National Academy of Sciences, 115*(5),
1093–1098. https://doi.org/10.1073/pnas.1716443115

Weisberg, S. M., Newcombe, N. S., & Chatterjee, A. (2019). Everyday taxi drivers:
Do better navigators have larger hippocampi?. *Cortex, 115*, 280–293.
https://doi.org/10.1101/431155

Weisberg, S. M., & Ekstrom, A. D. (2021). Hippocampal volume and navigational
ability: The map (ping) is not to scale. *Neuroscience & Biobehavioral Reviews,*
126, 102–112. https://doi.org/10.1016/j.neubiorev.2021.03.012

Whittington, J. C. R., McCaffary, D., Bakermans, J. J. W., & Behrens, T. E. J. (2022).
How to build a cognitive map. *Nature Neuroscience, 25*(10), 1257–1272.
https://doi.org/10.1038/s41593-022-01153-y

Zeithamova, D., & Bowman, C. R. (2020). Generalization and the hippocampus:
More than one story?. *Neurobiology of Learning and Memory, 175*, 107317.
https://doi.org/10.1016/j.nlm.2020.107317

Zheng, X. Y., Hebart, M. N., Grill, F., Dolan, R. J., Doeller, C. F., Cools, R., &
Garvert, M. M. (2024). Parallel cognitive maps for multiple knowledge
structures in the hippocampal formation. *Cerebral Cortex*, bhad485.
https://doi.org/10.1093/cercor/bhad485

Methods

Participants

Sixteen participants (mean age 23.00 ± 2.97, 9 female) with normal or corrected-to-normal vision were recruited from Tsinghua University. Informed consent was obtained from each participant before participation in accordance with the experimental protocol approved by the Institutional Review Board of Tsinghua University.

Relational Memory (RM) task

The experimental paradigm was a modified version of a sequential decision making task (Insa-Cabrera et al., 2011; Tartaglia et al., 2017). In each trial, a *Good* and a *Bad* cue were pseudo-ramdomly presented on two out of three horizontal positions of screen after a 10-s fixation. The position of the cues independently varies along 30 consecutive steps. The *Good* and *Bad* cue were never placed in the same position in sequence. Participants were required to predict the next position of the *Good* cue by placing a *Self* marker "avatar" at the anticipated location, and avoid the position of *Bad* cue during 1700 ms. After a self-paced response, feedback is immediately presented for 300 ms with the positive feedback indicated by a green upward arrow and negative feedback represented by a red downward arrow. If the chosen position is neither *Good* nor *Bad*, neutral feedback will be presented. Participants received +1, -1, and 0 virtual coin after positive, negative, and neutral feedback, respectively. If no response was made, the next step will be presented after 2000 ms. Participant's response, feedback, and reaction times were reported during experiment.

The experiment was conducted in two consecutive days. Participants performed the task in behavioral room on day 1 while they completed the task under MRI scanning on day 2, respectively.

The behavioral task employed a four-position design programmed by PsychoPy (version = 2022.1.0), where the length of sequences (i.e., numeric strings) varied from 2 to 8 steps with a step size of 1 and eight repetitions. This design resulted in 56 trials.

The total duration of experiment took approximately one hour. Experimental stimuli

were presented by a 15.4-inch MacBook Pro with a screen resolution of 2880 x 1800

pixels. Participants completed six practice trials prior to the experiment to ensure that

they fully understood the instructions.

The fMRI task was designed with three positions. The length of numeric strings

varied from 2 to 4 steps with a step size of 1 and eight repetitions, resulting in a total

of 24 trials, which were randomly assigned to 4 scanning sessions with 6 trials each

session. The total duration of fMRI experiment took approximately one hour. The

experimental stimuli were presented using a visual/audio stimulation system

(Shenzhen Sinorad SA-9939) with a customized-design (Shenzhen Sinorad Medical

Electronics Co., Ltd) MRI compatible 40" LED liquid crystal display. The distance

between participant and the display was 100 centimeters. The screen resolution was

1024 x 768 pixels. Participants viewed the stimuli with an angled mirror mounted on

the head coil.

MRI Acquisition

BOLD MRI images were acquired using a 3T Siemens Prisma scanner equipped with

a 64-channel phased-array head coil. Functional data were acquired with a

gradient-echo-planar T2* sequence (TR: 2000ms; TE: 34.0ms; matrix size:

$100\times100\times72$; flip angle: 90°; resolution: $2 \times 2 \times 2$ mm^3; FoV = 200mm; number of

slices: 72; slice thickness: 2 mm; slice orientation: transversal). T1-weighted

three-dimensional anatomical images were collected to facilitate registration

(MPRAGE: TR: 2530 ms; TE: 2.27 ms; matrix size: $208\times256\times256$; flip angle: 7°;

resolution: $1\times1\times1$mm^3; number of slices: 208; slice thickness: 1 mm; slice orientation:

sagittal).

fMRI Pre-processing

T1-weighted structural and functional images were analyzed using FSL (FMRIB's

Software Library, version 6.0, http://fsl.fmrib.ox.ac.uk/fsl/; Woolrich et al., 2009;

Smith et al., 2004; Jenkinson et al., 2012). The non-brain tissues of high-resolution T1

images were removed using BET (Smith, 2002). The BOLD signal series of each

scanning session was preprocessed independently using FEAT (FSL's FMRI Expert

Analysis Tool, version 6.0; Woolrich et al., 2001; Woolrich et al., 2004), where

motion correction, slice-timing correction, and high-pass filtering at 100 s were

performed. For representational similarity analysis (RSA), BOLD signal series was

left unsmoothed to preserve fine-grained spatial information (Chadwick et al., 2012).

For functional connectivity (FC) analysis, BOLD signal series were smoothed using a

Gaussian kernel of full width at 5mm half-maximum (FWHM). These preprocessed

functional images of each participant were normalized to standard Montreal

Neurological Institute (MNI-152) template using FSL FLIRT (Jenkinson & Smith,

2001; Jenkinson et al., 2002) before being sent to group-level statistics.

Representational similarity analysis

The functional separation of the HPC was examined by the representational similarity

analysis (Kriegeskorte et al., 2006; Kriegeskorte et al., 2008). First, the BOLD signal

series of task period were subdivided into two temporal intervals with equal duration,

which were labelled as the relational memory formation state and the utilization state,

respectively. Second, a general linear model (GLM) was created for fitting the BOLD

time series of each voxel, where 18 regressors were specified. These regressors

indicated the cognitive states corresponded by the rest, formation, and utilization

periods from each of the six trials, and the six motion parameters were additionally

included as covariates. Third, the multivoxel patterns were extracted from the beta

images using a 6mm radius sphere centered at each voxel of the HPC. Pair-wise

Pearson correlations were performed across the 18 cognitive states. This procedure

resulted in a 18×18 correlation matrix, which was Fisher's r-to-z transformed. Fourth,

two additional GLMs were created to examine the neural representation of memory

formation and utilization states, respectively. Specifically, a binary regressor was used

for each GLM to fit the correlation coefficients of cognitive states, where 1 and 0

denoted "same" and "difference", respectively. A higher beta coefficient of the two

GLMs in any voxel indicated stronger representational similarity for the memory

formation and utilization states. Then, the representational similarity maps were

transformed into MNI space, averaged across sessions, and finally sent to second level

analysis. Identical procedure was applied to the RSA of the rest and task periods.

Functional connectivity analysis

To examine the connectivity separation of the HPC, we computed the connectivity

pattern of the HPC for each of the memory formation and memory utilization states.

Given the brain areas within the autobiographical network intrinsically connect to the

HPC (Conway et al., 2001; Spreng & Grady, 2010; Sestieri et al., 2011; Philippi et al.,

2015; Smallwood et al., 2021), we particularly focused on the connections between

the autobiographical network and the HPC. First, we derived the functional mask of

the autobiographical network by performing a contrast of the hippocampal

whole-brain connectivity map from the task period to the rest period (Fig. S2).

Specifically, a GLM was created to regress out the potential nuisance factors, which

included the six parameters derived from rigid body correction of head motion (Birn

et al., 2006; Wise et al., 2004), the mean time courses within the lateral ventricles, and

the mean time courses within the white matter (Bartels & Zeki, 2005; Fox et al., 2005).

Second, the BOLD signal series of the task and rest periods were extracted through

concatenating the TRs (i.e., 5 TRs) across trials (i.e., 6 trials) independently for each

session. Third, the whole brain connectivity map of the HPC for each of the rest and

task state was computed by performing Pearson correlations between the regional

time courses of the HPC (the HPC mask was obtained from the Harvard-Oxford (HO)

atlas included in FSL) and the BOLD signal series of each voxel of the remaining

brain. Fourth, the contrast in the connectivity of the HPC between the task period and

rest period was performed after Fisher's r-to-z transformation (Fig.S2). This result was

visualized using BrainNet Viewer (version 1.42, https://www.nitrc.org/projects/bnv).

The functional mask of the default mode network was then generated using the

contrast map with the voxels within the medial temporal lobe excluded. Finally, the

connectivity separation of the HPC was examined by computing the Pearson

correlations between the regional time course of default mode network and the time

course of each voxel of the HPC in each of the memory formation and utilization

states, which was extracted by concatenating the TRs (i.e., 15 TRs) across trials (i.e.,

6 trials). The state-dependent connectivity maps of the HPC were transformed into

standard MNI152 space, averaged across sessions after Fisher's r-to-z transformation,

and sent to second level analysis.

Convolutional LSTM (C-LSTM) model

An encoder-decoder network programmed by PyTorch (version = 1.9;

https://pytorch.org/) was built to perform the RM task, where the encoder included a

convolutional layer followed by a fully connected layer, which projected the flattened

output to a long short-term memory (LSTM) layer. The encoder accepted the images

with dimension of 90×40×3 pixels as input and constructed the memory space storing

the sequential relation of experimental stimuli. The decoder included a fully

connected layer followed by a transposed convolution layer, which was used to

generate visual output, indicating the predicted location of the *good* cue. In other

words, the decoder utilized the sequential relations stored by memory space to guide

actions on visual space. To examine the role of coarse / fine-grained scales akin to the

hippocampal ventral-dorsal axis on relational memory formation and utilization, we

modulated the visual resolution (VR), defined by 1/kernel size of convolutional layers

(ranged from 1 to 15) and the memory resolution (MR), defined by the hidden size of

LSTM (ranged from 1 to 15) to examine their influence on model performance. The

kernel size of the convolutional layer was set the same as that of the deconvolutional

layer based on the biological basis of the visual cortex (Miyawaki et al., 2008). In

practice, the kernel size could vary independently, and the variance of the kernel size

of the convolution layer had little effect on the findings (Fig. S3). During training, the

Adam optimizer with a learning rate of 0.001 and a weight decay parameter of 1e-5

were used. The optimization process operates within a batch size of 8, which equals to

the length of sequential images and spanned 1,000 epochs for each kernel size of

convolutional layer and the hidden size of LSTM. The loss function is specified as

Mean Squared Error Loss. To improve the efficiency of network training, the encoder

was independently trained in advance with a fully connected layer as decoder in
predicting the upcoming location, then C-LSTM used the pretrained weights of
encoder, which was fixed during training.

Statistics

The behavioral analysis was performed using Python 3.9 and SPSS 20. The
second level analysis of RSA and functional connectivity analysis were performed
using two tailed one-sample t-test. The generated t-maps used an initial threshold of p
$= 0.01$. If no clusters were revealed, a liberal threshold of $p < 0.05$ was used. The
reliability of the uncorrected clusters was further examined using a non-parametric
statistical inference that does not make assumptions about the distribution of the data
(Nichols & Holmes, 2002). Specifically, 5,000 random sign-flips were performed on
the parametric images of RSA and functional connectivity. The clusters with size
higher than 95% of the maximal suprathreshold clusters from permutation distribution
were reported. Same permutation procedure was applied to evaluate the statistical
model fitness of participant behavior, the variation of the representational similarity
and functional connectivity along hippocampal long axis, and the identification of unit
type in C-LSTM. The main effect of C-LSTM parameter VR and MR and their
interaction on task performance was examined by ANOVA. The unit type of C-LSTM
was determined by computing the spatial frequency in both the horizontal and vertical
dimension from the feature maps using Fast Fourier Transform (FFT). The linear
relationship between the unit type and model performance was examined by Pearson
correlation. ANOVA was employed to examine the significance of the FFT power
variation of unit types relative to model performance.

Supplementary

Figure S1. Representational similarity of rest and memory state. (A) The schema of RSA
analysis. First, the multi-voxel patterns of the rest and memory state were derived by a GLM.
Second, the 12x12 similarity matrix, built through the searchlight-based Pearson correlation of
multi-voxel patterns among trials, was fitted by another GLM, which specified the cognitive state
using binary regressors. The blue and red points in the binary matrix denote "same" between
trial-pair. The estimated parameters of GLM were used for the analysis of (B). (B) The neural
representation of memory relative to rest state. The value in each voxel represents t-value. The
Y-axis corresponds to the coordinates of hippocampal long axis. (C) ROI analysis. The HPC
showed significantly higher similarity in memory state relative to rest state ($t(15) = 33.45$; $p <$
0.001, two-tailed).* denotes the threshold of $p < 0.05$. Error bars denote standard error.

Figure S2. Functional connectivity of HPC in memory state compared to rest state. The
functional connectivity was computed for each participant in both the memory and rest states. A
Pearson correlation was performed between the mean BOLD signal series within the HPC and the
voxel in the rest of brain. A contrast analysis was conducted comparing memory state relative to
rest state. All clusters were corrected by False Discovery Rate (FDR) with a significance threshold
of $p < 0.05$. colorbar denotes t value.
983

985 **Figure S3. Behavioral performance of C-LSTM with fixed convolutional kernel size (CKS).**
986 Across a wide range of CKS values (i.e., varying from 1 to 15 in steps of 2), consistent patterns
987 similar to Fig. 4B emerged. That is, optimal performance was achieved with smaller VR values
988 (i.e., coarse representation during memory utilization) and larger MR values (i.e., fine-grained
989 representation during memory formation). The color coding follows the scheme in Fig. 4B.