Building compositional tasks with shared neural subspaces

Sina Tafazoli[1,*], Flora M. Bouchacourt[1], Adel Ardalan[1], Nikola T. Markov[1], Motoaki Uchimura[1],

Marcelo G. Mattar[3], Nathaniel D. Daw[1,2], Timothy J. Buschman[1,2,*]

[1]Princeton Neuroscience Institute, Princeton University, Princeton, NJ, USA. [2]Department of Psychology, Princeton

University, Princeton, NJ, USA. [3]Department of Psychology, New York University, New York, USA

* Corresponding authors:
Timothy J. Buschman, tbuschma@princeton.edu, and Sina Tafazoli, tafazoli@princeton.edu

Lead contact:
Timothy J. Buschman, tbuschma@princeton.edu

Abstract

Cognition is remarkably flexible; we are able to rapidly learn and perform many different tasks[1]. Theoretical modeling has shown artificial neural networks trained to perform multiple tasks will re-use representations[2] and computational components[3] across tasks. By composing tasks from these sub-components, an agent can flexibly switch between tasks and rapidly learn new tasks[4]. Yet, whether such compositionality is found in the brain is unknown. Here, we show the same subspaces of neural activity represent task-relevant information across multiple tasks, with each task compositionally combining these subspaces in a task-specific manner. We trained monkeys to switch between three compositionally related tasks. Neural recordings found task-relevant information about stimulus features and motor actions were represented in subspaces of neural activity that were shared across tasks. When monkeys performed a task, neural representations in the relevant shared sensory subspace were transformed to the relevant shared motor subspace. Subspaces were flexibly engaged as monkeys discovered the task in effect; their internal belief about the current task predicted the strength of representations in task-relevant subspaces. In sum, our findings suggest that the brain can flexibly perform multiple tasks by compositionally combining task-relevant neural representations across tasks.

Introduction

Humans, and other animals, can combine simple behaviors to create more complex behaviors[5–9]. For example, once we learn to discriminate whether a piece of fruit is ripe, we can reuse this ability as a component of a variety of foraging, cooking, and eating tasks. The ability to compositionally combine behaviors is thought to be central to generalized intelligence in humans[10] and a necessary component for artificial neural networks to achieve

human-level intelligence[11–15]. When artificial neural networks are trained to perform multiple

tasks, they reuse representations and computational components in different tasks[2–4].

Whether the brain similarly reuses sensory, cognitive, and/or motor representations across

tasks, and how these representations may be flexibly combined, remains unknown. To test

this hypothesis, we trained monkeys to perform three different compositionally related tasks.

Monkeys perform three compositionally related tasks

All three tasks followed the same general structure: animals were presented with a visual

stimulus and had to indicate its category with an eye movement (Fig. 1a). The stimuli were

parametric morphs, independently varying in both shape and color (Fig. 1b, see methods for

details). Animals performed three categorization tasks. In the Shape-Axis1 (S1) task, they

categorized the shape of the stimulus and then responded on Axis 1: when the shape was

more similar to a 'bunny', the animal made a saccade to upper-left (UL) target, and when the

shape was more similar to a 'tee', the animal saccaded to the lower-right (LR) target (Fig. 1c,

top row). The Color-Axis2 (C2) task required the animal to categorize the color of the stimulus

and respond on Axis 2: if the color was 'red', they saccaded to upper-right (UR), and if 'green',

they saccaded to lower-left (LL; Fig. 1c, bottom row). Finally, in the Color-Axis1 (C1) task, the

animals categorized the color of the stimulus (as in the C2 task) and responded on Axis 1 (as

in the S1 task; red=LR, green=UL, Fig. 1c, middle row). In this way, the tasks were

compositionally related – C1 can be considered as combining the color categorization sub-

task of C2 with the motor response sub-task of S1.

Overall, both animals performed all three tasks well (Figs. 1e and S1; Monkey Si/Ch:

S1:81%/77%, C1: 83%/78%, C2: 92%/92%; all $p<0.001$, binomial test, see Fig. S1 for

individual animal performance). Animals performed the same task for a block of trials (Fig.

1d). When they reached a behavioral criterion (performance $\geq70\%$), the task would change

(see Methods for details). The animal was not instructed as to the identity of the new task,

although the axis of response always changed between blocks (see Methods). So, animals

had to learn which task was in effect on each new block. This was reflected in the animal's

behavior, which improved over the first 75 trials of the S1 and C1 tasks (Fig. 1f, left,

performance on S1/C1 increased from 0.47/0.62 at trial 15 to 0.71/0.77 at trial 75, both

$p<0.001$, Chi-squared test). As only the C2 task used Axis 2 responses, the animal identified

the task quickly, performing it above chance within 15 trials after the switch (Fig. 1f,

Fig. 1| Monkeys perform three compositional tasks. a, Time course of trial. After a brief fixation (500-800ms), a visual stimulus and four response targets appeared on the screen. Animals reported the category of the stimulus with a saccade to one of the four target locations. **b,** Stimuli were morphs in a two-dimensional feature space that varied in shape (left) and color (right). Stimulus categories are indicated by vertical lines and labels. 50% morph stimuli were randomly rewarded. **c,** Schematic of the task design: Task S1 required categorizing the stimulus based on its shape and responding to Axis 1. Task C2 required categorizing the stimulus based on its color and responding to Axis 2. Task C1 required categorizing the stimulus based on its color and responding to Axis 1. Blue and orange rectangles indicate shared sub-tasks: color categorization subtask between Task C2 and Task C1, and response location sub-task in Task S1 and Task C1. **d,** Example of task transition sequence. Task switches occurred when performance was equal or greater than 70%. Animals were not instructed as to the identity of the upcoming task, although the axis of response switched between blocks. **e,** Average psychometric curve for both animals for the 102/102/51 trials before the switch for S1/C1/C2 tasks respectively. **f,** Average performance of both animals after (left) and before (right) a switch (average window of 15 trials, p < 0.05, 0.01, and 0.001 for thin, medium, and thick lines, respectively; binomial test) **g,** Schematic of locations of neural recordings. **h-i,** To quantify information about task variables in individual neurons, we computed the proportion of variance in neural response uniquely explained by each task variable using the coefficient of partial determination (CPD, average CPD for permuted dataset was subtracted from observed CPD for each neuron. see Methods). Panels show CPD of **h,** color category, **i,** shape category, **j,** task identity, **k,** response direction and **l,** reward. Lines show mean CPDs across all neurons for each region. Regions were omitted if they did not have a significant number of neurons encoding a cognitive variable. **m,** Timecourse of average normalized CPD across all recorded neurons, normalized by maximum value to show temporal order.

performance at 15 trials=0.85, p<0.001, binomial test). Altogether, the animals' behavior

suggests they rapidly identified the change in response axis but slowly integrated feedback

to learn whether S1 or C1 was in effect[16].

Task variables were represented in independent subspaces of neural activity

To understand the neural representations used during each task, we simultaneously recorded

neural activity from five cortical and subcortical regions (Fig 1g): lateral prefrontal cortex

(LPFC; 480 neurons), frontal eye fields (FEF; 149 neurons), parietal cortex (PAR; 64

neurons), anterior inferior temporal cortex (aIT; 239 neurons) and striatum (caudate nucleus;

149 neurons). All five regions represented task-relevant cognitive variables, including the

identity of the current task, the color and shape of the stimulus, the response direction, and

whether a reward was received (Fig. 1h-1l;[17]). The identity of the task was consistently

represented throughout the trial (Figs. 1j and S2). After stimulus onset, information about the

color (Fig. 1h) and shape of the stimulus (Fig.1i) was followed by information about the

direction of the animal's response (Fig. 1l), and then the reward received (Fig. 1k, see Fig.

1m for average time course across all regions).

To understand how each task variable was represented in the neural population, we trained

classifiers to decode the stimulus color, shape, and motor response from the pattern of neural

activity across all neurons (using a pseudo-population to combine neurons from all recording

sessions, see Methods for details). Classifiers trained on LPFC neural activity accurately

decoded the category of the stimulus' color in the C1 and C2 tasks (Fig.2a; 79ms, 87ms after

stimulus onset for C1 and C2, respectively; similar results were seen when controlling for

motor response, Fig. S3a, p<0.001 permutation test). In this way, the classifier defined a

"subspace" within the high-dimensional space of neural activity that represented the color

category of the stimulus input. Similarly, classifiers trained on LPFC activity decoded the

category of the stimulus' shape during the S1 task (Fig. 2b; 100ms after stimulus onset,

p<0.001 permutation test).

Task irrelevant stimulus information was attenuated. In LPFC, classification accuracy about

the shape of the stimulus was reduced during the C1 and C2 tasks (Fig. 2b) and information

about the color of the stimulus was reduced during the S1 task (Fig. 2a). Similarly, task-

relevant information, but not task-irrelevant information, was represented in other regions,

including in higher-order visual cortex (Fig. S3b-c).

The direction of the animal's response could be decoded within each task's response axis

(Fig. 2c, see Methods for details). In LPFC, information about the response occurred after the

stimulus' category (115ms, 133ms after stimulus onset in S1 and C1 tasks, respectively; both

p<0.001, permutation test, see Fig. S4c for C2 task). Similar results were seen in other

regions (Fig. S4a). Altogether, these results suggest that stimulus color category, stimulus

shape category and response direction are broadly represented at the population level in

multiple recorded regions.

104 Neural representations were shared across tasks

To test whether representational subspaces were reused across tasks, we quantified how

well a classifier trained to decode the stimulus' color category or the animals' motor response

in one task generalized to other tasks (Fig. 2d, Methods). Consistent with a shared

representation in LPFC, a classifier trained to decode the color category of a stimulus during

the C2 task was able to significantly decode the stimulus' color category during the C1 task

(Figs. 2e and 2f, 65ms after stimulus onset in LPFC, p<0.001, permutation test). The reverse

was also true: a classifier trained on C1 could decode stimulus's color category during the C2

task (Fig. 2f and S5c, 84ms after stimulus onset, p<0.001, permutation test). Importantly, the

two tasks require different motor responses and so the shared representation reflected the

color category of the stimulus and not the motor response (see Figs. S5a and S6a for further

controls for movement). Although color information was reduced in the S1 task, the weak

color category representation that did exist also generalized between the C1 and S1 tasks

(Fig. S5b).

While color category information was represented in a shared subspace in LPFC, it was

represented in task-specific subspaces in other brain regions (Fig. S7). Generalization was

weaker in FEF, PAR and IT and was delayed with respect to task-specific sensory information

(and was delayed relative to LPFC, Fig. 2g). There was no significant generalization in STR

(although stimulus color category could be decoded from those regions, Fig S3b).

Motor response representations also generalized across tasks. A classifier trained to decode

response direction in the C1 task generalized to decode response direction in the S1 task

(and vice versa; Fig. 2h and 2i, 128/128ms after stimulus onset in LPFC, when training on

S1/C1, testing on C1/S1, respectively, p<0.001, permutation test). Unlike stimulus

information, the motor representation was shared in all regions (Fig. S4b).

Fig. 2| LPFC encodes shared color and response representations. a-c, Accuracy of classifier trained to decode **(a)** color category, **(b)** shape category, and **(c)** motor response from LPFC neural activity. Lines and shading show mean ± s.e.m. over time. Distribution reflects 250 resampled classifiers (see Methods for details). Horizontal bars (top right of each plot) indicate above-chance classification (p < 0.05, 0.01, and 0.001 for thin, medium, and thick lines, respectively; permutation test with cluster mass correction). **d,** Schematic of classifiers used to test whether color category and response location information were shared across tasks (see Methods). **e,** Cross-temporal cross-task classification accuracy in decoding shared color category in LPFC. Trained on C2 task and tested on C1 task. **f,** Cross-task classification accuracy to decode shared color category in C1 task and C2 task in LPFC. **g,** Difference in the onset of color information during C1 task when either decoded from classifiers trained on C1 task versus generalized from C2 task (red star and red x in panels a and f, respectively). **h,** Cross-temporal cross-task classification accuracy in decoding shared response location in LPFC. Trained on S1 task and tested on C1 task. **i,** Cross-task classification accuracy to decode response location in Task C1 and Task S1 in LPFC.

Shared representations were sequentially engaged during a task

So far, our results suggest the representation of both sensory inputs and motor responses were shared across tasks. In this framework, performing a task requires selectively transforming representations from one subspace to another to support each task[18]. Consistent with this, there was a sequential representation of the stimulus color in the shared color subspace followed by the response in the shared motor subspace during the C1 task (Fig. 3a, 63ms difference in onset time of color response using C2 classifier and motor response using S1, p<0.001 t-test).

To directly test whether this reflected the transformation of information between subspaces, we tested whether information about the stimulus color in the shared color subspace predicted the response in the shared response subspace on a trial-by-trial basis (Fig. 3b). Figure 3c shows the correlation between the representation of the stimulus' color category in the C1 task, decoded using the classifier from the C2 task, and the representation of the motor response in the C1 task, decoded using the response classifier from the S1 task (see Methods for details). Correlation was measured across all possible pairs of timepoints,

Figure 3| Shared representations were sequentially transformed during the task. a, Sequential processing of shared color category information and shared response direction information in LPFC. Classifier accuracy was normalized to range between maximum accuracy and baseline 200ms before stimulus. **b,** Schematic showing prediction that shared color representation is transformed to correct response axis (Axis 1) during task C1 **c,** Cross-temporal, trial-by-trial correlation of shared color category encoding (trained on C2 task, tested on C1 task) and shared response location encoding (trained on S1 task, tested on C1 task). **d**, Same as panel b, but correlating shared color category encoding (trained on C2 task, tested on C1 task) and response direction encoding on Axis 2 (trained on C2 task, tested on C1 task). **e,** Average cross-temporal correlation along anti-diagonal axis in panel **c** (shared color encoding in C1 task predicts response direction in S1 task, blue line) and panel **d** (shared color encoding in C1 task predicts response direction in C2 task, red line)**.** The shift of the curve's center towards negative time values reflects the extent to which encoding in the shared color subspace predicts future encoding in the shared response subspace. Dotted lines show mean of gaussian fit to each curve.

quantifying whether color/motor representations at one time point were correlated with

representations at a future time point. The correlation was shifted upward with respect to

diagonal line (36ms before saccade start, Figs.3c and 3e, blue line), indicating that the

encoding in the shared color subspace predicts the future encoding in the shared response

subspace.

Importantly, this transformation was specific to the task: during the C1 task the shared color

representation was not predictive of the associated response direction along Axis 2 (8ms after

saccade start, Figs. 3d and 3e, red line). This is consistent with the shared color

representation being selectively transformed into a motor response along Axis 1, and not Axis

2, when the animal was performing the C1 task. In contrast, when the animals performed the

C2 task, the shared color representation was transformed into a motor response along Axis

2, and not Axis 1 (Fig. S6b-d). Interestingly, there was a negative correlation between the

sensory and motor responses early in the trial, which may reflect suppression of the motor

response during fixation or integration of the stimulus input.

Together, these results suggest tasks sequentially engage shared subspaces, selectively

transforming stimulus representations into motor representations in a task-specific manner.

Shared subspaces are dynamically engaged by task belief

Theoretical modeling suggests shared subspaces could facilitate cognitive flexibility by

allowing the brain to engage previously learned, task appropriate, representational and

computational subspaces[2,3]. If true, then this predicts task-appropriate shared subspaces
should be engaged as the animal discovers the task in effect.

To begin to test this hypothesis, we first measured the animal's internal representation of the
task (i.e., their 'belief' about the task encoded by the neural population). To do so, we trained
a classifier to decode the identity of the task using neural activity in LPFC during the fixation
period (i.e., before stimulus onset,[19]). Training was restricted to the last 75 trials of the S1 and
C1 tasks, when behavioral performance was high (Fig. 1f). We then applied the task classifier
to the beginning of the C1 task blocks to measure the animals' internal belief about the task
as they learned which task was in effect (Fig. 4b-1, see Methods for details).

As noted above, monkeys slowly learned whether the S1 or C1 task was in effect[16].
Consistent with this, the decoder performance increased over trials (Fig. 4c). Interestingly,
animals' rate of learning depended on the sequence of tasks. When switching into a C1 task,
animals learned more quickly when the previous Axis 1 task was C1 compared to S1 (Fig.
4a, purple: C1-C2-C1 task sequence, black: S1-C2-C1; Δ=10.26% change in performance
over first 20 trials, p<0.001, Chi-squared test). A similar pattern was seen for S1: performance
on task sequence S1-C2-S1 was greater than C1-C2-S1 (Fig. S8a, Δ=4.99%, p=0.032, Chi-
squared test). As the C2 task had a unique response axis, it was not affected by the preceding
task (Fig. S8b Δ=1.42% between S1-C2 and C1-C2 sequences, p=0.234, Chi-squared test).

As with behavior, the performance of the task classifier depended on the sequence of tasks
(Fig. 4c-d). During S1-C2-C1 sequences, the classifier was slightly below chance initially,
suggesting a slight encoding of the S1 task, before increasing as the animals learned (Fig.
4c-d, from 45% to 54% from trial 50 to 125, p<0.001 modified Mann-Kendall trend test). On
C1-C2-C1 task sequences, classifier performance was high immediately after the switch to
C1 (60% classifier accuracy on trial 50, p<0.001, t-test) and only slightly increased with trials
(Fig. 4d, purple line; 9% increase from trial 50 to 125, p<0.001 modified Mann-Kendall trend
test). Moreover, the task belief encoding in C1 task was correlated with behavioral
performance in C1 task on the color category task (Fig. 4e, τ=0.53, p=0.002 modified Mann-
Kendall trend test) and anti-correlated with behavioral performance in C1 task on the shape
category task (Fig. S9a, τ=-0.66, p<0.001 modified Mann-Kendall trend test). Together, these
results suggest the monkeys tracked whether the S1 or C1 task was in effect, and that this

Fig. 4| Shared sub-task subspaces are dynamically engaged during task discovery. a, Behavioral performance of monkeys during the C1 task depended on the sequence of preceding tasks. Dashed gray line is 25% chance level. Horizontal bars indicate above chance difference between performance in two sequences($p < 0.05$, 0.01, and 0.001 for thin, medium, and thick lines, respectively; Chi-squared test) **b,** Schematic of classifier tests during task discovery.1: Task identity classifier: train classifier to decode task identity on 75 trials before switch in S1 task and C1 task, test on sliding window of 50 trials starting from switch into C1 task. 2: Color category classifier: train classifier to decode color category on 75 trials before switch in C2 task, test on sliding window of 50 trials starting from switch into C1 task. 3: Shape category classifier: train classifier to decode shape category on 75 trials before switch in S1 task, test on sliding window of 50 trials starting from switch into C1 task. 4: Response direction classifier: train classifier to decode response direction on 75 trials before switch in S1 task, test on sliding window of 50 trials starting from switch into C1 task. Same test trials were used across classifiers. **c,** Classifier accuracy for task identity during -400ms to 0ms period from sample onset. Darker to lighter color show progression in trial blocks of 50 shifted by 5 trials from switch trial in S1-C2-C1 task transition. Horizontal bars indicate above chance trend for classifier accuracy during task discovery ($p < 0.05$, 0.01, and 0.001 for thin, medium, and thick lines, respectively; modified Mann-Kendall test) **d,** Comparison of progression of task identity classifier accuracy in C1-C2-C1 task sequence (purple) and S1-C2-C1 task sequence (black). Average accuracy was computed using population firing rate in -400ms to 0ms before stimulus onset period. **e,** Correlation of behavioral performance and task belief encoding. **f,** As in panel c, but showing classifier accuracy for color category classifier in S1-C2-C1 task transition. **g,** Comparison of progression of color category classifier accuracy in C1-C2-C1 sequences (purple) and S1-C2-C1 sequences (black). Average accuracy was computed using population firing rate in 100ms to 300ms from stimulus onset. **h,** Correlation between task belief encoding and color category encoding (see Methods for details). ($p < 0.05$, 0.01, and 0.001 for thin, medium, and thick lines, modified Mann-Kendall test).**i,j** same as **f,g** but for shape category classifier **k,l** same as **f,g** but for response direction classifier. Classifier accuracy was computed using population firing rate in 200ms to 400ms after stimulus onset.

belief was at least partially maintained between blocks, leading to a bias in the neural

representation and behavior.

Given a measurement of the animal's internal representation of the task, we next asked
whether this representation predicted the strength of representations in the shared color
category and shared motor response subspaces. Similar to the task representation, the
strength of the representation in the shared color subspace increased as the animals
discovered the C1 task (Fig. 4f, Fig. 4b-2, see Methods for details). Like task representations,
color representations depended on task sequence (Fig. 4g). Shared color representations
increased during the C1 task when it followed a S1-C2-C1 sequence (57% to 62%, Δ=5%
from trial 50 to 125, p=0.001 modified Mann-Kendall trend test), but slightly decreased during
C1-C2-C1 sequences (54% to 51%, Δ=3% from trial 50 to 125, p=0.005 modified Mann-
Kendall trend test). This suggests that shared color subspace is dynamically engaged as the
animal updates its belief about the current task. Indeed, the strength of internal task
representation in LPFC during fixation was correlated with the strength of shared color
category representation after onset of the stimulus during learning (Fig. 4h, see Methods for
details).

The animal's behavior and internal representation of the task suggest they initially expected
to perform the S1 task in S1-C2-C1 task sequences. If true, and task representations
modulate the strength of shared subspace representations, then shape information should
initially be strong and then decay as the animal learns the C1 task is in effect. To test this, we
trained a classifier to decode the stimulus' shape category during the last 75 trials of the S1
task, and then tested it as the animal discovered the C1 task (Fig. 4i, Fig. 4b-3, see Methods
for details). In contrast to color, shape representation was significant immediately after the
switch to the C1 task during S1-C2-C1 sequences (56%, p<0.001, t-test) and significantly
decreased as the animal learned (Fig. 4i-j, Δ=5%, p=0.017, modified Mann-Kendall trend
test). A similar pattern was observed during C1-C2-C1 task sequences, although overall
shape information was reduced (Fig. 4j, purple, 54% on trial 50, Δ=3%, p=0.021, modified
Mann-Kendall trend test). Finally, consistent with task belief modulating engagement of shape
representations, belief about the C1 task was inversely correlated with the representation of
shape (Fig. S9b).

In contrast to shared color and shape subspaces, the animals' motor response was stably
decoded in a shared subspace (Fig. 4k-l, Fig. 4b-4, see Methods for details, Δ=0%, p=0.15,
and Δ=1%, p=0.095, for S1-C2-C1 and C1-C2-C1 sequences, respectively; modified Mann-
Kendall trend test; see Methods for details). The representation in the shared response

Fig. 5| Geometry of representations are transformed during flexible behavior. a, Distance between stimuli along color category encoding axis (Methods). Darker to lighter color show progression in trial blocks of 50 shifted by 5 trials from switch trial in S1-C2-C1 sequences. Horizontal bars indicate above chance trend for distance during task discovery (p < 0.05, 0.01, and 0.001 for thin, medium, and thick lines, respectively; modified Mann-Kendall test) **b**, same as (a) but for distance along shape category encoding axis. **c,** Compression Index during trial timeline for three tasks. **d,** Compression Index during task discovery in S1-C2-C1 sequences. **e,** Correlation between task belief encoding and average compression index during 100ms-300ms since stimulus onset (Methods). **f,** Correlation between color category encoding and average compression index during 100ms-300ms since stimulus onset (Methods).

subspace was also not correlated with the strength of internal task representation in LPFC (τ=-0.08, p=0.34, Fig. S9c).

Altogether, these results suggest the animals use their internal belief to selectively engage the relevant shared color and shape subspaces during the C1 task. The task-relevant stimulus subspace (color) was then dynamically projected onto the shared representation of the response.

Task belief scaled representations within the shared subspaces

Previous work suggests the gain of stimulus features can change, depending on their relevance for the current task[20–23]. Indeed, we found task-irrelevant information was attenuated (Fig. 2a, 2b). Furthermore, this attenuation depended on the animals' internal belief about the task: as they discovered the C1 task was in effect, the representation of color category was magnified (Fig. 5a), while shape representation was attenuated (Fig. 5b).

Such amplitude modulation can be thought of as a geometric scaling of stimulus representations along the feature dimensions[20,21,24]. To quantify this, we defined a

'Compression Index' (CPI) as the log of the ratio between the separability of stimuli in (i) the

color subspace and (ii) the shape subspace. Color and shape representations were scaled in

all three tasks. There was greater separation of color representation during C1 and C2 tasks,

and greater separation of shape representations during the S1 task (Fig. 5c). This scaling

changed as animals learned which task was in effect (Fig. 5d). In fact, CPI was positively

correlated with the strength of the task representation and color category encoding in LPFC

(Fig. 5e and 5f, τ=0.58, p=0.0017 and τ=0.58, p=0.0017, respectively).

Together, these results suggest scaling of stimulus information is a common computation

across all the three tasks that can be flexibly engaged based on the monkeys' belief about

the current task, dynamically adjusting the representational geometry of sensory

representations[25–27].

Discussion

Our results suggest the brain can perform a task by compositionally combining a set of

representational subspaces. We found 'shared' subspaces of neural activity in prefrontal

cortex that represented sensory inputs and motor actions across multiple tasks. This

contrasts with previous work that has found high-dimensional, non-linear representations that

'mix' sensory, motor, and task information in a unique way for each task[28,29]. Such non-linear,

high-dimensional, representations are easy to linearly separate, facilitating learning and

performing arbitrary tasks[30]. However, because each task representation is essentially

unique, learning cannot be generalized across tasks[21]. Instead, our results are consistent with

recent theoretical models that suggest neural representations and computational components

are reused across tasks. Shared representational subspaces could speed learning by

allowing knowledge to generalize across tasks[4]. For example, the neural representation (and

associated computations) that were learned to categorize the color of a stimulus during C2

could be generalized to support behavior during C1. Future work is needed to test this

hypothesis as subjects learn new tasks.

While sharing representations across tasks may facilitate generalization between tasks, it

could also lead to interference. One strategy to reduce interference between multiple tasks is

to use orthogonal task representations[31]. Consistent with this, we found task-irrelevant

dimensions were compressed[25,32] as a function of the animals' internal belief about the task

state (Fig. 5). Compression could reduce interference from non-relevant stimulus inputs
(specifically, incongruent stimuli in the task).

Generalization of subspaces across tasks was strongest in prefrontal cortex. This is
consistent with previous work that has found projecting multiple stimuli[33] or memories[34] into
a common subspace within prefrontal cortex can allow a single task to generalize across
stimuli and/or memories[35]. Our results show subspace representations within prefrontal
cortex can be shared across multiple tasks. Of course, other regions may also be involved –
for example, previous work has found generalization of representations in the
hippocampus[33,36].

Our results are consistent with prefrontal cortex acting as a 'global workspace'[37], with different
subspaces of neural activity representing different task-relevant information. In this model,
performing a task requires transforming information from the relevant sensory subspace to
the appropriate motor response subspace. Consistent with this, we found sensory
representations in the category subspace predicted responses in the motor subspace on a
trial-by-trial basis (Fig. 3). The mechanism by which information is transformed between
subspaces remains unknown, although previous work suggests rotation of neural
representations may be one possible mechanism[38,39].

Which subspaces were engaged, and how information was transformed, depended on the
animals' internal belief about the current task (Figs. 3 and 4). This is consistent with
computational models of cognitive flexibility that suggest task representations can act as a
control input to select task-appropriate representations and computations in a neural network
(whether feed-forward[23] or recurrent[2,3,40]). Thus, if the necessary representations already
exist, then learning a new task only requires discovering the appropriate control input – i.e.,
the representation of the task that engages the appropriate representations/computations.
This could dramatically speed learning, either by learning the task representations through
reward feedback[41,42] or recalling it from long-term memory[43].

Altogether, our results suggest the brain can compose a new task by learning the task
representation that flexibly transforms information between representational and
computational subspaces of neural activity.

Acknowledgements

We thank Britney Morea, Neeraja Rajagopalan for assistance with monkeys; Srdjan Ostojic, Carlos Brody, Tatiana Engel and Christopher M. Langdon for thoughtful discussions; Tatiana Engel, Caroline Jahn, Qinpu He, Polina Lamshchinina, Iman Wahle, Seth Akers-Campbel and Junchol Park for feedback on the manuscript and the Princeton Laboratory Animal Resources staff for support. This work was supported by NIH R01MH129492 (T.J.B.).

Author contributions

TJB and ST conceived the project. ST collected experimental data with assistance from NTM, MU and TJB. ST analyzed the data with input from TJB, AA, FMB, MM, and NDD. ST wrote first draft of the paper. ST, TJB, FMB, MM, AA, NDD, NTM and MU edited the paper. TJB acquired funding. TJB supervised the project.

Competing Interests

The authors declare no competing interests.

References

1. Sakai, K. Task Set and Prefrontal Cortex. *Annual Review of Neuroscience* **31**, 219–245 (2008).

2. Yang, G. R., Joglekar, M. R., Song, H. F., Newsome, W. T. & Wang, X.-J. Task representations in neural networks trained to perform many cognitive tasks. *Nat Neurosci* **22**, 297–306 (2019).

3. Driscoll, L., Shenoy, K. & Sussillo, D. *Flexible Multitask Computation in Recurrent Networks Utilizes Shared Dynamical Motifs*. http://biorxiv.org/lookup/doi/10.1101/2022.08.15.503870 (2022) doi:10.1101/2022.08.15.503870.

4. Goudar, V., Peysakhovich, B., Freedman, D. J., Buffalo, E. A. & Wang, X.-J. Schema formation in a neural population subspace underlies learning-to-learn in flexible sensorimotor problem-solving. *Nat Neurosci* 1–12 (2023) doi:10.1038/s41593-023-01293-9.

5. Epstein, R., Kirshnit, C. E., Lanza, R. P. & Rubin, L. C. 'Insight' in the pigeon: antecedents and determinants of an intelligent performance. *Nature* **308**, 61–62 (1984).

6. Ito, T. *et al.* Compositional generalization through abstract representations in human and artificial neural networks. Preprint at http://arxiv.org/abs/2209.07431 (2022).

7. Makino, H. Arithmetic value representation for hierarchical behavior composition. *Nat Neurosci* 1–10

(2022) doi:10.1038/s41593-022-01211-5.

8. Reverberi, C., Görgen, K. & Haynes, J.-D. Compositionality of Rule Representations in Human

Prefrontal Cortex. *Cerebral Cortex* **22**, 1237–1246 (2012).

9. Tenenbaum, J. B., Kemp, C., Griffiths, T. L. & Goodman, N. D. How to Grow a Mind: Statistics,

Structure, and Abstraction. *Science* **331**, 1279–1285 (2011).

10. Frankland, S. M. & Greene, J. D. Concepts and Compositionality: In Search of the Brain's Language of

Thought. *Annu. Rev. Psychol.* **71**, 273–303 (2020).

11. Botvinick, M. *et al.* Reinforcement Learning, Fast and Slow. *Trends in Cognitive Sciences* **23**, 408–422

(2019).

12. Lake, B. M., Ullman, T. D., Tenenbaum, J. B. & Gershman, S. J. Building Machines That Learn and

Think Like People. Preprint at https://doi.org/10.48550/arXiv.1604.00289 (2016).

13. Lake, B. M. & Baroni, M. Human-like systematic generalization through a meta-learning neural

network. *Nature* 1–7 (2023) doi:10.1038/s41586-023-06668-3.

14. Lin, B., Bouneffouf, D. & Rish, I. A Survey on Compositional Generalization in Applications. Preprint

at http://arxiv.org/abs/2302.01067 (2023).

15. Marcus, G. The Next Decade in AI: Four Steps Towards Robust Artificial Intelligence. *arXiv.org*

https://arxiv.org/abs/2002.06177v3 (2020).

16. Bouchacourt, F., Tafazoli, S., Mattar, M. G., Buschman, T. J. & Daw, N. D. Fast rule switching and

slow rule updating in a perceptual categorization task. *eLife* **11**, e82531 (2022).

17. Siegel, M., Buschman, T. J. & Miller, E. K. Cortical information flow during flexible sensorimotor

decisions. *Science* **348**, 1352–1355 (2015).

18. MacDowell, C. J., Libby, A., Jahn, C. I., Tafazoli, S. & Buschman, T. J. Multiplexed Subspaces Route

Neural Activity Across Brain-wide Networks. 2023.02.08.527772 Preprint at

https://doi.org/10.1101/2023.02.08.527772 (2023).

19. Wallis, J. D., Anderson, K. C. & Miller, E. K. Single neurons in prefrontal cortex encode abstract rules.

Nature **411**, 953–956 (2001).

20. Barbosa, J. *et al.* Early selection of task-relevant features through population gating. *Nat Commun*

14, 6837 (2023).

21. Flesch, T., Juechems, K., Dumbalska, T., Saxe, A. & Summerfield, C. Orthogonal representations for

robust context-dependent task performance in brains and neural networks. *Neuron* **110**, 1258-

1270.e11 (2022).

22. Langdon, C. & Engel, T. A. Latent circuit inference from heterogeneous neural responses during

cognitive tasks. 2022.01.23.477431 Preprint at https://doi.org/10.1101/2022.01.23.477431 (2022).

23. Miller, E. K. & Cohen, J. D. An Integrative Theory of Prefrontal Cortex Function. *Annual Review of*

Neuroscience **24**, 167–202 (2001).

24. Takagi, Y., Hunt, L. T., Woolrich, M. W., Behrens, T. E. & Klein-Flügge, M. C. Adapting non-invasive

human recordings along multiple task-axes shows unfolding of spontaneous and over-trained

choice. *eLife* **10**, e60988 (2021).

25. Mack, M. L., Preston, A. R. & Love, B. C. Ventromedial prefrontal cortex compression during concept

learning. *Nature Communications* **11**, 1–11 (2020).

26. Wójcik, M. J. *et al. Learning Shapes Neural Geometry in the Prefrontal Cortex*.

http://biorxiv.org/lookup/doi/10.1101/2023.04.24.538054 (2023) doi:10.1101/2023.04.24.538054.

27. Xue, C., Kramer, L. E. & Cohen, M. R. Dynamic task-belief is an integral part of decision-making.

Neuron (2022) doi:10.1016/j.neuron.2022.05.010.

28. Rigotti, M. *et al.* The importance of mixed selectivity in complex cognitive tasks. *Nature* **497**, 585–

590 (2013).

29. Rouzitalab, A., Boulay, C. B., Park, J., Martinez-Trujillo, J. C. & Sachs, A. J. Ensembles code for

associative learning in the primate lateral prefrontal cortex. *Cell Reports* **42**, (2023).

30. Barak, O., Rigotti, M. & Fusi, S. The Sparseness of Mixed Selectivity Neurons Controls the

Generalization–Discrimination Trade-Off. *J. Neurosci.* **33**, 3844–3856 (2013).

31. Gurnani, H. & Cayco Gajic, N. A. Signatures of task learning in neural representations. *Current*

Opinion in Neurobiology **83**, 102759 (2023).

32. Muhle-Karbe, P. S. *et al.* Goal-seeking compresses neural codes for space in the human

hippocampus and orbitofrontal cortex. *Neuron* **0**, (2023).

33. Bernardi, S. *et al.* The Geometry of Abstraction in the Hippocampus and Prefrontal Cortex. *Cell* **183**,

954-967.e21 (2020).

34. Panichello, M. F. & Buschman, T. J. Shared mechanisms underlie the control of working memory and

attention. *Nature* **592**, 601–605 (2021).

35. Johnston, W. J. & Fusi, S. Abstract representations emerge naturally in neural networks trained to

perform multiple tasks. *Nat Commun* **14**, 1040 (2023).

36. Whittington, J. C. R. *et al.* The Tolman-Eichenbaum Machine: Unifying Space and Relational Memory

through Generalization in the Hippocampal Formation. *Cell* **183**, 1249-1263.e23 (2020).

37. Baars, B. J. Global workspace theory of consciousness: toward a cognitive neuroscience of human

experience. in *Progress in Brain Research* vol. 150 45–53 (Elsevier, 2005).

38. Kaufman, M. T., Churchland, M. M., Ryu, S. I. & Shenoy, K. V. Cortical activity in the null space:

permitting preparation without movement. *Nat Neurosci* **17**, 440–448 (2014).

39. Libby, A. & Buschman, T. J. Rotational dynamics reduce interference between sensory and memory

representations. *Nat Neurosci* **24**, 715–726 (2021).

40. Hummos, A. Thalamus: a brain-inspired algorithm for biologically-plausible continual learning and

disentangled representations. Preprint at http://arxiv.org/abs/2205.11713 (2023).

41. Jahn, C. I., Markov, N. T., Morea, B., Ebitz, R. B. & Buschman, T. J. Learning attentional templates for

value-based decision-making. 2023.07.25.550426 Preprint at

https://doi.org/10.1101/2023.07.25.550426 (2023).

42. Niv, Y. Reinforcement learning in the brain. *Journal of Mathematical Psychology* **53**, 139–154 (2009).

43. Singh, D., Norman, K. A. & Schapiro, A. C. A model of autonomous interactions between

hippocampus and neocortex driving sleep-dependent memory consolidation. *Proc. Natl. Acad. Sci.*

U.S.A. **119**, e2123432119 (2022).

419　<u>Supplemental information</u>

420　Fig. S1

a

Fig. S1| Both monkeys perform the task well. Follows Fig. 1e. Average psychometric curve for (**a**) monkey Ch and (**b**) monkey Si. Behavioral performance is shown for the last 102 trials of a bock for the S1 and C1 tasks and last 51 trials of blocks of the C2 task.

426 # Fig. S2

Task identity information

Time, relative to sample on (s)

Fig. S2| Task identity is represented throughout the trial. Follows Fig. 1m. Normalized CPD for task identity averaged for all regions. Lines and shading show mean± s.e.m.

Fig. S3

a Color category decoding with balanced reward in LPFC

b Color category is encoded in all regions

c Shape category is encoded in all regions

433 **Fig. S3| Color and shape category were decoded in all regions. a,** Follows Fig. 2a. To control for motor movement information when measuring color category cross decoding accuracy, we balanced the number of trials for response direction for each color category. This dissociated color category information from response. We only included the trials that animal responded on the correct response axis, e.g., Axis 1 for task C1 (see Methods). Panel shows time course of classifier accuracy in decoding the color category of the stimulus from LPFC. Decoder was trained on a set of trials that were balanced between rewarded and non-rewarded trials (balancing motor response; see methods for details). **b,** Follows Fig. 2a. Time course of accuracy of classifier in decoding the color category of the stimulus. Classifiers were trained for each task and tested on withheld trials of the same task (colored lines). Columns show color category information for Striatum, IT, FEF, and LIP (moving left to right). **c,** Follows Fig. 2b. Same as (b) but for shape category information. Lines and shading show mean ± s.e.m. classification accuracy after stimulus onset. Distribution reflects 250 iterations of classifiers. Horizontal bars (top right of each plot) indicate above-chance classification (p < 0.05, 0.01, and 0.001 for thin, medium, and thick lines, respectively; permutation test with cluster mass correction).

Fig. S4

a Response direction is encoded in all regions

b Response direction representation is shared between C1 task and S1 task in all regions

c LPFC encodes response direction in C2 task

Fig. S4| Response direction was decoded in all regions. **a,** Follows Fig. 2c. Time course of classifier accuracy to decode response direction for S1 task and C1 task. **b,** Follows Fig. 2i. Time course of cross-task classifier accuracy to cross-decode response direction across S1 and C1 tasks. **c,** Follows Fig. 2c. Time course of classifier accuracy to decode response direction for C2 task in LPFC. Lines and shading show mean ± s.e.m. classification accuracy after stimulus onset. Distribution reflects 250 iterations of classifiers. Horizontal bars (top right of each plot) indicate above-chance classification (p < 0.05, 0.01, and 0.001 for thin, medium, and thick lines, respectively; permutation test with cluster mass correction).

Fig. S5

a Color category decoding between C1 task and C2 task using balanced reward trials

b Color category decoding between S1 task and C1 task in LPFC

c Cross temporal color category decoding between C1 task and C2 task in LPFC

Fig. S5. Color category was cross decoded between tasks in LPFC. a, Time course of accuracy of classifier trained to decode color category on trials of the C1 task, balanced between rewarded and unrewarded trials (i.e., balancing motor responses). Classifier is then tested on the C2 task. Lines and shading show mean ± s.e.m. classification accuracy after stimulus onset. Distribution reflects 250 iterations of classifiers. Horizontal bars (top right of each plot) indicate above-chance classification (p < 0.05, 0.01, and 0.001 for thin, medium, and thick lines, respectively; permutation test with cluster mass correction). **b**, As in Figure 2f, but showing shared color category information between C1 and S1 tasks. Classifiers were trained only on correct trials. **c,** As in Figure 2e, but showing the cross-temporal cross-task classification accuracy in decoding shared color category in LPFC when training on C1 task trials and testing on C2 task trials.

Fig. S6

a Response location is not cross decoded between C1 task and C2 task in LPFC

b Shared color category in C2 task →
response direction in C2 task

c Shared color category in C2 task ✗→
response direction in S1 task

d

Fig. S6| Response direction is not cross decoded between axes. a, Classifiers cannot decode response direction between axes. Classifiers were trained on C1 (left) or C2 (right) task trials to decode response direction and then tested on matched hemifield location trials during the C2 (left) or C1 (right) task. Lines and shading show mean ± s.e.m. classification accuracy after stimulus onset. Distribution reflects 250 iterations of classifiers. Horizontal bars (top right of each plot) indicate above-chance classification (p < 0.05, 0.01, and 0.001 for thin, medium, and thick lines, respectively; permutation test with cluster mass correction). **b,** Shared color category in C2 task was transformed into response on Axis 2 and not Axis 1. As in Fig. 3c, but correlating shared color category encoding (trained on C1 task, tested on C2 task) and response direction encoding on Axis 2 (trained on C2 task, tested on C2 task). **c**, As in Fig. 3d**,** but correlating shared color category encoding (trained on C1 task, tested on C2 task) and response direction encoding on Axis 1 (trained on S1 task, tested on C2 task). **d.** As in Fig. 3e, but average cross-temporal correlation along anti-diagonal axis in panel **b**(shared color encoding in C2 task predicts response direction in C2 task, blue line) and panel **c**(shared color encoding in C2 task predicts response direction in S1 task, red line)**.** Thin and thick red lines in panels **b, c**, **d** indicate p<0.05 and p<0.001, respectively, uncorrected t-test.

Fig. S7

Cross task color category generalization with correct trials

Cross task color category generalization with balanced reward

Fig. S7| Color category was significantly cross decoded in subset of regions. top, Follows Fig. 2f. Cross-task color category decoding for Striatum, IT, FEF and PAR using only correct trials. **Bottom,** Cross-task color category decoding for Striatum, IT, FEF and PAR using only balanced reward trials. Lines and shading show mean ± s.e.m. classification accuracy after stimulus onset. Distribution reflects 250 iterations of classifiers. Horizontal bars (top right of each plot) indicate above-chance classification (p < 0.05, 0.01, and 0.001 for thin, medium, and thick lines, respectively; permutation test with cluster mass correction).

Fig. S8

a Effect of task sequence on S1 task performance

b Effect of task sequence on C2 task performance

456 **Fig. S8| Task sequence modified behavioral performance in S1 task but not
in C2 task. a,** Follows Fig. 4a. Comparison of average behavioral performance of
457 both monkeys in (S1-C2-S1) and (C1-C2-S1) task sequences. Horizontal bars
indicate above chance difference between performance in two sequences,
$p < 0.05$, 0.01, and 0.001 for thin, medium, and thick lines, respectively by Chi-
458 squared test. **b,** Follows Fig. 4a. Comparison of average behavioral performance
of both monkeys in S1-C2 and C1-C2 task sequences.

Fig. S9

a Correlation between task belief and behavioral performance for shape category

τ:-0.66,p<0.001

b Correlation between task belief and shape category encoding

c Correlation between task belief and response direction encoding

τ:-0.08,p=0.34

Fig. S9| Task belief encoding was inversely correlated with behavioral performance for shape category and was not correlated with response location encoding during task discovery. a, Follows Fig. 4e. Correlation between task belief encoding and shape category behavioral performance in C1 task for S1-C2-C1 task sequences. Behavioral performance is plotted relative to the S1 task. Therefore, lower numbers reflect behavior that is more aligned with the C1 task. Negative correlation reflects an increase in C1 task behavior when there is task belief is closer to the C1 task. **b,** Follows Fig. 4k. Correlation between task belief encoding and response direction encoding in C1 task for S1-C2-C1 task sequences. There was a weak correlation between stronger belief encoding and an increase in response direction encoding, but it was not significant. **c,** Follows Fig. 4h. Correlation between task belief encoding and shape category encoding. (p < 0.05, 0.01, and 0.001 for thin, medium, and thick lines, modified Mann-Kendall test).

Methods

Subjects

Two adult male rhesus macaques (*Macaca mulatta*) performed the category response task. Monkeys Si and Ch were between 8 and 11 years old and weighed approximately 12.7 and 10.7 kg, respectively. All experimental procedures were approved by the Princeton University Institutional Animal Care and Use Committee (protocol #3055) and were in accordance with the policies and procedures of the National Institutes of Health.

Behavioral task

Each trial began with the monkeys fixating on a dot at the center of the screen. During a fixation period lasting 500ms–800ms, the monkeys were required to keep their gaze within a circle with a radius of 3.25 degrees of visual angle around the fixation dot. Following the fixation period, the stimulus and all four response locations were simultaneously displayed.

Stimuli were morphs consisting of both a color and shape (Fig. 1a). The stimuli were rendered as three-dimensional models using POV-Ray and MATLAB (Mathworks) and displayed on a Dell U2413 LCD monitor positioned 58 cm from the animal. Stimuli were morphed along circular continua in both color and shape (i.e. drawn from a four-dimensional 'Clifford' torus; Figure 1b). Colors were drawn from a photometrically isoluminant circle in the CIELAB color space, connecting the red and green prototype colors. Shapes were created by circularly interpolating the parameters defining the lobes of the 'bunny' prototype to the parameters defining the corresponding lobes of the 'tee' prototype. The mathematical representation of the morph levels adhered to the equation $X_1^2 + X_2^2 + X_3^2 = P^2$ where X represents the parameter value in a feature dimension (e.g., L, a, b values in CIELAB color space). We chose the radius (P) to ensure sufficient visual discriminability between morph levels. The deviation of each morph level from prototypes (0% and 100%) was quantified using percentage, corresponding to positions on the circular space from $-\pi$ to 0 and 0 to π. Morph levels were generated at eight levels: 0%, 30%, 50%, 70%, 100%, 70%, 50%, 30%, corresponding to $0, \pi/6, \pi/2, 5\pi/6, \pi, -5\pi/6, -\pi/2$ and $-\pi/6$, respectively. 50% morph levels for one feature were only generated for prototypes of the other feature (i.e., 50% colors were only used with 0% or 100% shape stimuli). Stimuli were presented at fixation and had a diameter of 2.5 degrees of visual angle.

The monkeys indicated the color shape category of the stimulus by saccading to one of the
four response locations, each positioned 6 degrees of visual angle from the fixation point at
45°, 135°, 225°, and 315° relative to the vertical line. The animal's reaction time was
determined as the moment of leaving the fixation window in relation to the onset of the
stimulus.

Trials with a reaction time below 150ms were terminated, followed by a brief timeout (200ms).
Correct responses were rewarded with a drop of juice, while incorrect responses resulted in
short timeouts lasting from 1s for monkey Ch and 5s for monkey Si. After the trial finished,
there was an inter-trial interval lasting 2–2.5 seconds before the next trial began.

The animals performed three category-response tasks (Fig. 1c). The Shape-Axis1 (S1) task
required the monkeys to categorize the stimulus by its shape. For a stimulus with a shape
that was closer to the 'bunny' prototype, the animals had to make a saccade to the upper-left
(UL) location to get rewarded. For a stimulus with a shape closer to the 'tee' prototype, the
animals had to make a saccade to the lower-right (LR) location to be rewarded. For ease of
notation, we refer to the combination of the UL and LR target locations as 'Axis 1'. The Color-
Axis1 (C1) task required the monkeys to categorize the stimulus by its color. When a stimulus'
color was closer to 'red' the animals made an eye movement to the LR location and when
closer to 'green' the animals made an eye movement to the UL location. Finally, in the Color-
Axis2 (C2) task the animals again categorized stimuli based on their color but responded to
the upper-right (UR) location for red stimuli and the lower-left (LL) location for green stimuli.
Together, the UR and LL targets formed 'Axis 2'. These set of three tasks were designed to
be related to one another. The C1 and C2 tasks both required categorizing the color of the
stimulus. The C1 and S1 tasks both required responding on Axis 1.

Animals were not explicitly cued as to which task was in effect. However, they did perform
the same task for a block of trials allowing the animal to infer the task based on the
combination of stimulus, response, and reward feedback. Tasks switched when the monkeys'
performance reached or exceeded 70% on the last 102 trials of Task S1 and Task C1 or the
last 51 trials of Task C2. For Monkey Si, block switches occurred when their performance
reached or exceeded the 70% threshold for all morphed and prototype stimuli in the relevant
task dimension independently. For Monkey Ch, block switches occurred when their average
performance at each morph level in the relevant task dimension exceeded the 70% threshold

(e.g., average of all 30% morphs, average of all 70% morphs, and 0% and 100% prototypes
in color dimension were all equal or greater than 70% accuracy in C1 and C2 tasks). In
addition, on a subset of recording days, to prevent Monkey Ch from perseverating on one
task for an extended period of time, the threshold was reduced to 65% over the last 75 trials
for S1 and C1 tasks after the monkey had already done 200 or 300 trials on that block. When
the animal hit the performance threshold, the task switched. This was indicated by a flashing
yellow screen, a few drops of reward, and a long time-out (50 secs).

To ensure even sampling of tasks despite the limited number of trials each day, the axis of
response always changed following a block switch. During Axis 1 blocks, either S1 task or
C1 task was pseudo-randomly selected, interleaved with C2 task blocks. Pseudo-random
selection within Axis 1 blocks ensured that each animal performed at least one block of each
task during each session by avoiding three consecutive blocks of the same task.

Monkeys Si and Ch underwent training for 36 and 60 months, respectively.
Electrophysiological recordings began when the monkeys consistently executed five or more
blocks daily. Further details on the behavioral methods are reported in previous publication [1].

Congruent and incongruent stimuli

The overlap in the response axis for the S1 and C1 tasks meant certain stimuli elicited
congruent responses for both tasks. Specifically, red-tee stimuli and green-bunny stimuli were
"congruent" as they required a saccade to the LR and UL locations, respectively, in both the
C1 and S1 tasks. In contrast, stimuli in the red-bunny and green-tee portion of stimulus space
were "incongruent", as they required different responses during the two tasks (UL and LR in
S1 task; LR and UL in C1 task, respectively). To ensure the animals performed the task well,
80% of the trials included incongruent stimuli. Note, as only the C2 task used Axes 2, there
were no congruent or incongruent stimuli on those blocks.

Analysis of behavioral data

Psychometric curves plot the fraction of trials in which the animals classified the stimulus, at
a specific morph level, as being the same category as the 100% prototype (along the shape
dimension for the S1 task and color dimension for the C1 and C2 tasks). We calculated
average performance per morph level during the last 102/102/51 trials of the S1/C1/C2 task.
The fraction of responses for a given morph level of the task-relevant stimulus dimension was
averaged across all morph levels of the task-irrelevant dimension (e.g., for the C1 task, the

fraction of responses for 70% green stimuli were averaged across all shape morph levels).

Since the stimulus space was circular, we averaged the behavioral response for the two

stimuli at each morph level on each side of the circle (Fig. 1b). Psychometric curves were

quantified by fitting the mean data points with a modified Gauss error function (erf):

566
$$F = \theta + \lambda * \left(\mathrm{erf}\left(\frac{x - \mu}{\sigma}\right) + 1 \right)/2,$$

where erf is the error function, θ is a vertical bias parameter, λ is a squeeze factor, μ is a

threshold, and σ is a slope parameter. Fitting was done in MATLAB with the Maximum

likelihood method (fminsearch.m function).

To calculate performance during task discovery (Fig 1f), we used a sliding window of 15 trials,

stepped 1 trial, to calculate a running average of performance immediately after a switch or

right before a switch. Performance was estimated using trials from all blocks of the same task,

regardless of the identity of the stimulus.

Surgical procedures and electrophysiological recordings

Monkeys were implanted with a titanium headpost to stabilize their head during recordings

and two titanium chambers (19mm diameter) placed over frontal and parietal cortices that

provided access to the brain. The position of the chambers was determined using 3D model

reconstruction of the skull and brain using structural MRI scans. We recorded neurons from

lateral prefrontal cortex (LPFC, Brodmann area 46d and 46v), anterior inferior temporal cortex

(aIT, area TEa), parietal cortex (PAR, Brodmann area 7), the frontal eye fields (FEF,

Brodmann area 8) and the striatum (STR, caudate nucleus).

Two types of electrodes were used during recordings. To record from LPFC and FEF we used

epoxy-coated tungsten single electrodes (FHC Inc., Bowdoin, ME). Pairs of single electrodes

were placed in a custom-built grid with manual micromanipulators that lowered electrode pairs

using a screw. This allowed us to record 20-30 neurons simultaneously from cortical areas

near the surface. To record from deeper regions (PAR, aIT and STR) we used 16ch or 32ch

Plexon V-Probes (Plexon Inc, Dallas, TX). These probes were lowered using the same

custom-built electrode grid through guide tubes. During lowering, we used both structural MRI

scans and the characteristics of the electrophysiological signal to track the position of the

electrode. A custom-made MATLAB GUI tracked electrode depth during the recording

session and marked important landmarks until we found neural activity in the brain region of
interest.

Recordings were acute; up to 50 single electrodes and three V-Probes were inserted into the
brain each day (in some recording sessions one additional V-Probe was also inserted in
LPFC). Single electrodes and V-probes were lowered though the intact dura at the beginning
of recording session and allowed to settle for 2-3 hours before recording. This improved the
stability of our neural recordings. We did not simultaneously record from all five regions in all
recording sessions. We began recording from LPFC and FEF for the first 5-10 days and then
added PAR, STR, and aIT on successive days.

Broadband neural activity was recorded at 40 kHz using a 128-channel OmniPlex recording
system (Plexon Inc., Dallas, TX). We performed 15 recording sessions with monkey Ch and
19 recording sessions with monkey Si. After all recordings were complete, we used electrical
microstimulation in monkey Si, and structural MRI and microstimulation in monkey Ch, to
identify FEF. Electrical stimulation was delivered as a train of anodal-leading biphasic pulses
with a width of 400µs and an inter-pulse frequency of 330Hz. A site was identified as FEF
when electrical microstimulation of ~50µA evoked a stereotyped eye-movement on at least
50% of the stimulation attempts. In Monkey Ch, untested electrode locations were classified
as FEF if they fell between two FEF sites (as confirmed with electrical stimulation) in a region
that was confirmed as being FEF using MRI.

The eye position of the monkeys was recorded at 1 kHz using an Eyelink 1000 Plus eye-
tracking system (SR Research, Kanata, ON). Sample onset was recorded using a photodiode
attached on the screen. These signals, alongside with behavioral events generated during
the task, were recorded as analog inputs into the OmniPlex system.

Signal preprocessing
Electrophysiological signals were filtered using a 4-pole high pass 300Hz Butterworth filter.
To reduce common noise, the median of the signals recorded from all single electrodes in
each chamber was subtracted from the activity of all single electrodes. For V-Probe
recordings, we subtracted the median activity for all channels along the probe from each
channel. To detect spike waveforms, a $4\sigma_n$ threshold was used where σ_n is an estimate of
standard deviation of noise distribution of signal x defined as:

$$\sigma_n = median\left(\frac{|x|}{0.6745}\right)$$

Time points at which the electrophysiological signal (x) crossed this threshold with a negative slope were identified as putative spiking events. Spike waveforms were saved (total length was 44 samples, 1.1ms, of which, 16 samples, 0.4ms, were pre-threshold). Repeated threshold crossing within 48 samples (1.2ms) were excluded. All waveforms recorded from a single channel were manually sorted into single units, multi-unit activity or noise using Plexon Offline Sorter (Plexon Inc., Dallas, TX). Units that were partially detected during a recording session were also excluded. All analyses reported in this manuscript were performed on single units.

To decode saccade time, instantaneous eye speed was calculated as $\sqrt{(\frac{dx}{dt})^2 + (\frac{dy}{dt})^2}$, in which x and y were position of the eye on the monitor at time t. The time point after the stimulus onset at which the eye speed exceeded a threshold of 720 degrees of visual angle per second was taken as the saccade start time.

Statistics and Reproducibility

Independent experiments were performed on two monkeys and the data were combined for subsequent analyses. As detailed below, statistical tests were corrected for multiple comparisons using two-tailed cluster correction unless stated otherwise. Unless otherwise noted, nonparametric tests were performed using 1,000 iterations; therefore, exact p values are specified when $p > 0.001$. Unless stated otherwise, all data were smoothed with a 150ms boxcar.

All analyses were performed in MATLAB 2021b (Mathworks)

Using cluster mass to correct for multiple comparisons

To assess the significance of observed clusters in the time series data, we employed a two-tailed cluster mass correction method [2]. This approach is particularly useful when dealing with multiple comparisons and helps identify clusters of contiguous time points that exhibit statistically significant deviations from the null distribution.

We first generated a null distribution ($NullDist$) by combining shuffling the observed data, breaking the relationship between the neural signal and the task parameter of interest (details of how data was shuffled are included with each test below). The observed data was also

included as a 'shuffle' in the null distribution and the z-score of null distribution for each time
point was calculated. To define significant moments in time, we computed the upper and
lower thresholds based on the null distribution. The thresholds were determined non-
parametrically using percentiles. The resulting thresholds, denoted as
`$p\_thresholdUpper$` and `$p\_thresholdLower$`, serve as critical values for identifying significant
deviations in both tails.

Timepoints of significant signal were identified by finding the moments when the value in each
shuffle within the null distribution or the observed data exceeded the computed thresholds.
These timepoints were then clustered in time, such that contiguous values above the
threshold were summed together. The sum was calculated on the z-transformed values of
each time series. This resulted in a 'mass' of each contiguous cluster in the data. To correct
for multiple comparisons, we took the maximum absolute value of the cluster mass across
time for each shuffle. This resulted in a distribution of maximum cluster masses. Finally, the
two-tailed p-value of each observed cluster was determined by comparing its mass to the
distribution of maximum cluster masses in the null distribution.

Firing rate (FR) calculation
In all analyses, we estimated the firing rate of each neuron by averaging the number of action
potentials within a 100 ms window, stepping the window every 10ms. Changing the width of
the smoothing window did not qualitatively change our results. The time labels in the figures
denote the trailing edge of this moving window (i.e., 0 ms would be a window from 0 ms to
100 ms).

Generalized Linear Model (GLM)
To estimate how much information each neuron carried about task variables, we used a
Generalized Linear Model (GLM) to relate the activity of each neuron (y) to the task variables
at each moment of time. The full model was:

$$y = \beta0 + \beta1 \times Stimulus\ Color\ Category + \beta2 \times Stimulus\ Shape\ Category + \beta3 \times Time$$
$$+ \beta4 \times Task\ Identity + \beta5 \times Motor\ Response\ Direction + \beta6 \times Reward$$

where y is the firing rate of each neuron, normalized by the max firing rate across all trials,
$\beta0, \beta1, ..., \beta6$ are the regression coefficients corresponding to each predictor. Predictors were:

Stimulus Color Category	Color category of the stimulus (categorical variable)
Stimulus Shape Category	Shape category of the stimulus (categorical variable)
Time	The temporal progression within a recording session, normalized between 0 and 1 (continuous variable).
Task Identity	Identity of the task (categorical variable)
Motor Response Direction	Direction of the motor response (categorical variable; Upper-Left, Upper-Right, Lower-Left, or Lower-Right)
Reward	Whether a reward was received following the response (binary variable; 1 for reward, 0 for no reward)

The GLM coefficients (β) were estimated using maximum likelihood estimation as
implemented by MATLAB's lassoglm.m function. Independent models were fit for each time
point. To address potential overfitting, we applied Lasso (L^1) regularization to the GLM
weights with regularization coefficients (lambda) values of [0, 0.0003, 0.0006, 0.0009, 0.0015,
0.0025, 0.0041, 0.0067, 0.0111, 0.0183]. In a separate set of runs, we fit the GLM models to
80% of data and tested on the remaining 20%. The lambda value with maximum R^2 on the
withheld data was used when estimating the coefficient of partial determination (CPD).

Coefficient of Partial Determination (CPD) Calculation
To quantify the unique contribution of each predictor to a neuron's activity we used the
Coefficient of Partial Determination (CPD). This metric quantifies the percent of explained
variance that is lost when a specific factor is removed from the full model. The CPD was
computed by initially fitting the GLM with all the factors (full model) as described above. Then,
each factor was sequentially removed to create a set of reduced models, each of which were
fit to the data. The CPD for each predictor $X(t)$ was calculated as:

694
$$CPD\big(X(t)\big) = \frac{SSE_{reduced} - SSE_{full\,model}}{SSE_{reduced}} \times 100$$

where $SSE_{reduced}$ is the sum of square error due to predictor X, $SSE_{full\ model}$ is the sum of

square error of the full model with all predictors [3].

We used a permutation test to assess whether CPDs for each predictor at each time-point

and for each neuron was significantly larger than expected by chance. To compute a null

distribution for CPD for each predictor, we generated 1000 permuted data sets by randomly

permuting the predictor values relative to the neural activity and refitting the full and reduced

models (as above). The likelihood of the observed CPD was then estimated by computing

the proportion of permuted datasets that yielded a CPD greater than or equal to that of the

observed dataset. To account for multiple comparisons across time-points, we used cluster

correction (detailed above) to estimate corrected p-values for each predictor. Neurons that

had at least one significant cluster (p-value < 0.05) were considered to significantly carry

information about a task variable. To assess if an area had a significant number of neurons

for a given task variable, we used a binomial test against the alpha-level.

For Fig. 1h-l, we compensated for a baseline CPD by subtracting the average permuted CPD

from the observed CPD. For Figs. 1m and S2, we averaged the CPD for each factor across

all recorded neurons and then normalized the resulting CPD curve to its maximum value. This

highlighted the timing of different factors during the trial.

Classifiers

To understand how task variables were represented in the neural population, we trained a

set of binary classifiers to discriminate the vector of firing rates across the neural population

for two different categories of task variables (depending on the variable of interest). Classifiers

were trained with the logistic regression algorithm (as implemented in MATLAB, fitclinear.m

function). In brief, the linear classifier relates x (vector of neural responses) to y (task labels,

either +1 or -1) via a linear equation, with weights(w) and intercept(b):

719
$$f(x) = w^T x + b$$

720   where w and b are optimized to minimize the logistic loss function: $\mathcal{L}[y, f(x)] =$

721    $\frac{-1}{N} \sum_{i=1}^{N} [y_i \log(f(x_i)) + (1 - y_i) \log(1 - f(x_i))]$, where N is the number of samples. Ridge (L^2)

722   regularization with a regularization coefficient $\lambda = 1/60$ was used to minimize over-fitting. The

723   classifier was trained with the Broyden-Fletcher-Goldfarb-Shanno (BFGS) algorithm.

Construction of pseudo-populations

All classifiers were trained on the response of a pseudo-population of responses constructed from neurons across all recording sessions. A separate pseudo-population was constructed for each classifier analysis based on the trial types of interest (described below). To be included in the pseudo-population, each neuron had to be recorded for a minimum number of trials ($N_{train} + N_{test}$) of each type of trial. The firing rate of neurons were concatenated to form a pseudo-population of neurons, aligned in time relative to either the sample onset or saccade onset.

To combine neurons across recording sessions into a single 'trial' of the pseudo-population, we drew trials for each neuron with matching experimental conditions (i.e., matched in terms of reward, color and shape morph level, task identity, and response direction). For instance, when constructing a pseudo-population for classifying the color category, the first 'trial' was constructed by concatenating the neural responses of neurons on trials that were rewarded, had a color morph level of 100, and a shape morph level of 30. If a neuron did not have a trial with an exactly matching stimulus, then a trial that matched the color category and reward would be randomly chosen.

Cross-validation of classifiers

A separate logistic regression classifier was trained and tested on withheld trials for each time point. To estimate variability, the entire analysis was repeated 250 times, with each iteration involving a different partition of trials into training and testing sets. This new set of trials was randomly sampled with replacement (always ensuring test trials were separate from the train trials).

When testing the performance of a classifier trained on the same set of conditions (i.e., training and testing color categorization on the C2 task), the performance of the classifier was taken as the average performance across 10-fold cross-validation. However, as detailed in the main text, many of the classifiers were trained and tested across conditions (e.g., across different tasks or across trials during learning of the task). In this case, the test trials were randomly resampled 10 times for each training set, and the classifier's performance was averaged across folds.

Balancing classifier conditions

To avoid bias in the classifier, we balanced trial conditions to ensure the observed results were not due to other experimental factors. Conditions were balanced in two ways:

1. **Balanced congruency:** classifiers were trained on an equal number of congruent and incongruent trials, resulting in equal number of trials for four stimulus types "green-bunny", "green-tee", "red-bunny" and "red-tee".

2. **Balanced reward**: classifiers were trained on an equal number of rewarded and unrewarded trials, balancing the stimulus identity and response direction on each side of the classifier.

Classifying the color category and shape category of stimuli

'Color' and 'shape' classifiers were trained to decode the stimulus color category or shape category from the vector of activity across the pseudo-population of neurons (Fig. 2a,b). A balanced number of congruent and incongruent stimuli were included in the training data to ensure color and shape information could be decoded independently. Classifiers were trained for each task independently.

Most classifiers were trained on correct trials alone. This maximized trials and ensured the animals were engaged in the task. As many of our analyses were across tasks, this mitigated concerns that motor response information confounded stimulus category information. However, to ensure this was not the case, we controlled for motor response by balancing rewarded and unrewarded trials in a separate set of analysis (Figs. S3a, S5a, and S7).

Classifying response direction

A separate set of 'response' classifiers were trained to decode the motor response from the vector of activity across the pseudo-population of neurons. Response direction was decoded within each axis (e.g., UL vs. LR for Axis 1). When training and testing on the same task (Fig. 2c), we only included trials that the animal responded on the correct axis (e.g., Axis 1 for the S1 and C1 tasks).

For testing whether response direction could be decoded across axes (Fig. S6a), we trained the classifier using trials from Task C1, where the animal responded on Axis 1, and then tested this classifier using trials from Task C2, where the animal responded on Axis 2, and vice versa. To control for stimulus-related information, we balanced rewarded and unrewarded trials for each condition and only included incongruent trials. This ensured that

787 trials from the same stimulus category were present in both response locations. Similar
788 results were seen when balancing for congruency and reward simultaneously, although the
789 low number of incorrect trials for congruent trials resulted in a small set of neurons with the
790 minimum number of train and test trials.

Using permutation tests to estimate the likelihood of classifier accuracy

We used permutation tests to estimate the likelihood the observed classifier accuracy
occurred by chance. To create a null distribution of classifier performance, we randomly
permuted the labels of training data 1000 times. Importantly, only the task-variable of interest
was permuted – permutations were performed within the set of trials with the same identity of
other (balanced) task variables. For example, if trials were balanced for reward, we shuffled
labels within correct trials and within incorrect trials, separately. This ensured the shuffling
only broke the relationship between the task-variable of interest and the activity of neurons.
Shuffling of the labels was performed independently for each neuron before building the
pseudo-population and training classifiers. Neurons that were recorded in the same session
had identical shuffled labels. To stabilize the estimate of the classifier performance, the
performance of the classifier on the observed and each instance of the permuted data were
averaged over 10-folds and 30 to 50 novel iterations of each classifier. The null distribution
was the combination of the permuted and observed values (total N=1001). The likelihood of
the observed classifier performance was then estimated as its percentile within the null
distribution. As detailed above, we used cluster correction to control for multiple comparisons.

Testing classification across tasks

To quantify whether the representation of color, shape, or response direction generalized
across tasks (Fig. 2e,f,h,i), we trained classifiers on trials from one task and then tested the
classifier on trials from another task. For example, to test cross-generalization of color
information across the C1 and C2 tasks, a color classifier was trained on trials from the C2
task was tested on trials from the C1 task (Fig. 2f). To remove any bias due to differences in
baseline firing rate across tasks, we subtracted the mean firing rate during each task from all
trials of that task (at each time point). Similar results were observed when we did not subtract
the mean firing rate.

Cross-temporal classification

To measure how classifiers generalized across time, we trained classifiers to discriminate color category (Fig. 2e and Fig. S5c) or response direction (Fig. 2h) using 100ms time bins of FR data, sliding by 10ms. Classifiers trained on each time bin were then tested on all time bins of the test trials.

Projection onto the encoding axis of classifier

To visualize the high-dimensional representation of task variables, we used the MATLAB predict.m function to project the firing rate response on test trials onto the one-dimensional encoding space defined by the vector orthogonal to the classification hyperplane. In other words, the projection measures the distance of the neural response vector to the classifier hyperplane. For example, to measure the encoding of each color category in the C1 task, we projected the trial-by-trial firing rate onto the axis orthogonal to the hyperplane of the color classifier trained during the C1 task.

Quantifying the impact of task sequence on task discovery

The 'task discovery' period was defined as the first 125 trials after a switch in the task. The monkey's performance increased during this period, as they learned which task was in effect (Fig. 1f). As detailed in the main manuscript, the animal's behavioral performance depended on the sequence of tasks (Fig. 4a), and so we analyzed neural representations separately for two different sequences of tasks:

1. **C1-C2-C1 and S1-C2-S1 block sequence ("same task transition"):** the task on Axis 1 (C1 or S1) repeated across blocks. As shown in the main text, monkeys tended to perform better during these task sequences, as if they were remembering the previous Axis 1 task.

2. **S1-C2-C1 and C1-C2-S1 block sequence ("different task transition"):** the task on Axis 1 changed across blocks. As shown in the main text, monkeys tended to perform worse on these task sequences.

As we were interested in understanding how changes in neural representations corresponded to the animals' behavioral performance, we divided the "different task transition" sequences into two further categories: in 'Low Initial Performance' blocks, the animal's behavioral

performance during the first 25 trials of the block was less than 50% while on 'High Initial
Performance' blocks performance was greater than 50%.

Task belief representation during task discovery

To measure the animal's internal representation of the task (i.e., their 'belief' about the task,
as represented by the neural population), we trained a 'task classifier' to decode whether the
current task was C1 or S1. The classifier was trained on neural data from the last 75 trials of
each task block, when the animal's performance was high (reflecting the animal's accurate
estimate of the task). The number of congruent and incongruent trials were balanced in the
training dataset (24 trials: 3 trials for each of the four stimulus types, in each task). Only
correct trials were used to train and test the classifier. To remove the effect of stimulus
processing, the classifier was trained on neural activity from the fixation period (i.e., before
stimulus onset, Wallis et al., 2001). As we were interested in measuring differences between
tasks, we did not subtract the mean firing rate before training the classifier.

The task classifier was tested on trials from the beginning of blocks of the C1 task. Test trials
were drawn from windows of 50 trials, slid every 5 trials, during learning (starting from trial 1-
50 to trial 76-125). Overlapping test and train trials from the same task were removed. Testing
was done separately for S1-C2-C1 and C1-C2-C1 task sequences (Fig. 4b). As we were
interested in focusing on the learning of the C1 task, we only used S1-C2-C1 task sequences
with 'low initial performance' (see above). Classifiers were tested on pseudo-populations built
from trials within each trial window, with a minimum of 4 test trials (1 trial for each of the four
stimulus congruency types from Task C1). Neurons that did not include the required number
of test trials for all trial windows were dropped. Note that, since we were using a small moving
window of trials during task discovery, we had to trade-off the number of included neurons
and the number of train/test trials for this analysis. In addition, although the number of correct
trials increased as the animal discovered the task in effect, we kept a constant number of
train and test trials in each of the sliding trial windows.

To quantify the animal's belief above the current task, we measured the distance to the
hyperplane of the C1/S1 task classifier. For Fig. 4d, we averaged the performance of the
classifier in pre-stimulus processing window (-400ms to 0ms).

877
878

Correlation between task belief encoding and behavioral performance

To calculate the correlation between the animal's task belief during task discovery and their behavioral performance (Fig. 4e), we used τ statistic in modified Mann-Kendall trend test. This measurement was performed using data from each window of trials and the belief encoding, as estimated from the task classifier, on that same window of trials. As we are working with pseudo-populations of neurons, we estimated the behavioral performance for each window of trials during learning as the average of all the trials in the window. The behavioral performance for each trial was taken as the average of the animal's behavioral performance during the previous 10 trials. This yielded one average performance for each of the 16 trial windows. The task belief was measured for the same trials, using the average distance to the task classifier hyperplane, averaged over the time period from 400ms to 0ms before the onset of the stimulus (note that, as described above, all of these trials are withheld from the training data). Task belief was then taken as the average distance across all trials in a window of trials.

Evolution of color category representation during task discovery

We were interested in quantifying how the shared color representation was engaged as the animal discovered the C1 task (Fig. 4f-g). To this end, we trained a classifier to categorize color using the last 75 trials of the C2 task, when the animal's behavioral performance was high, and then tested it during learning of the C1 task. The classifier was trained on only correct trials and the training data was balanced for congruent and incongruent stimuli (12 trials: 3 trials for each of the four stimulus congruency types). As cross axis response decoding between the C1 and C2 tasks was weak (Fig. S6a), cross-task classifiers are capturing the representation of the color category that is shared between tasks.

Similar to the task classifier described above, the shared color classifier was tested using trials from the C1 task in a sliding window of 50 trials stepped 5 trials, in both the S1-C2-C1 and C1-C2-C1 sequences of tasks (Fig. 4b; as above, only low initial performance blocks were used for the S1-C2-C1 task sequences). We used 4 trials to test the classifier (1 trial for each of the four stimulus congruency types from Task C1). For Fig. 4g, we averaged the performance of the classifier in stimulus processing window (100ms to 300ms).

Evolution of shape category representation during task discovery

We were interested in measuring the change in the representation of the stimulus' shape category as the animal learned the C1 task (Fig. 4i). Our approach followed that of the color category representation described above, and so we only note differences here. We trained a classifier to categorize stimulus shape based on neural responses during the S1 task (limited to the last 75 trials of each block). To ensure the classifier was only responding to shape (and not motor response), we trained the classifier on a balanced set of correct (rewarded) and incorrect (unrewarded) trials (12 trials: 3 trials for each reward condition and for each shape category). The classifier was tested using trials from the C1 task (Fig. 4b). Note that we used the same C1 trials to quantify the representation of shared color category, shape category and task belief. For Fig. 4j, we averaged the performance of the classifier in stimulus processing window (100ms to 300ms).

Evolution of response direction representation during task discovery

To measure the change in response direction representation as the monkey's learned the C1 task, we trained a classifier to categorize the response direction based on the neural response during the S1 task (Fig. 4k; last 75 trials of the block). As above, we used a balanced number of correct and incorrect trials to control for information about the stimulus (12 trials: 3 trials for each reward condition and each response location). The classifier was then tested on correct trials from the C1 task during task learning (Fig. 4b; as above: sliding windows of 50 trials, stepped 5 trials, in S1-C2-C1 and C1-C2-C1; tested on 4 trials: 1 for each reward condition and each response location). For Fig. 4l, we averaged the performance of the classifier in response location processing window (200ms to 400ms).

Classifier statistical test to detect trend during task discovery period

We used a modified Mann Kendall test to quantify the statistical significance of trends in representations during task discovery (Figs. 4-5). The Mann-Kendall test is a non-parametric statistical test used to assess the presence of a monotonic trend in a time series data set[4,5]. It is widely used in environmental and hydrological studies. The null hypothesis is that there is no trend in the data (i.e., the data points are randomly ordered). The alternative hypothesis is that there is a monotonic trend, either increasing or decreasing. The test statistic, denoted as Tau (τ), represents the strength and direction of the trend. The original Mann-Kendall test assumes independence of data points. Here, we use a modified test that accounts for auto

correlations within the data[6]. Specifically, we used Modified_MannKendall_test.m function,
implemented in MATLAB, as described in[7].

To measure significance of trends during task discovery, we first averaged the classifier
accuracy across all repetitions for each time point (Fig. 4c). We then calculated the Mann-
Kendall p-value for each time point. To control for multiple comparisons over contiguous time
points of a trial, we used Benjamini-Hochberg method (fdr_bh.m function, implemented in
MATLAB, as described in [8]).

Transfer of information between subspaces

As detailed in the main text, we were interested in testing the hypothesis that the
representation of the stimulus color in the shared color subspace predicted the response in
the shared response subspace on a trial-by-trial basis (Figs. 3c-e and S6b-d). To this end,
we correlated trial-by-trial variability in the strength of encoding of color and response along
four different classifiers.

First, as detailed above, a shared color classifier was trained to decode color category from
the C2 task and tested on trials from the C1 task. Training data were balanced for in/correct
(un/rewarded, 16 trials: 4 trials for each reward condition and each color category) while test
trials were all correct trials (2 trials: 1 trial for each color category). Both train and test trials
were drawn from the last 50 trials from the block (to ensure the animals were performing the
task well).

Similarly, a second shared response classifier was trained on trials from the S1 task and then
tested on the same set of test trials as the shared color classifier.

A third classifier was trained to decode the response direction on Axes 2, using balanced
in/correct trials from the C2 task. This classifier was tested on the same set of test trials as
the shared color classifier.

Finally, a fourth classifier was trained to decode the shared color representation but was now
trained on correct trials from the C1 task (12 trials: 3 trials for each of the four stimulus
congruency types) and tested on correct trials from C2 task (2 trials: 1 trial for each color
category).

To account for the arbitrary nature of positive and negative labels, we calculated the
magnitude of encoding by flipping the encoding for negative labels. All four classifiers were
trained on 2000 iterations of training and trials. Note, that the first three classifiers were tested
on the same test trials, allowing for trial-by-trial correlations to be measured. Furthermore, all
four classifiers were trained over time, allowing us to measure the cross-temporal correlation
between any pairs of classifiers.

Altogether, these four classifiers allowed us to test three hypothesized correlations that reflect
the transfer of task-relevant stimulus information into representations of behavioral
responses. First, one might expect that, on any given trial before the start of saccade, the
strength and direction of the shared color representation, as estimated by the distance to the
hyperplane of the first classifier, should be correlated with the shared response, as estimated
by the distance to the hyperplane of the second classifier. This correlation is seen in Fig. 3c.

Second, during the performance of the C1 task, one would expect that before the start of
saccade the shared color representation to not be correlated with the response on the Axes
2 predicted by the C2 task. This is quantified by correlating the distance to the hyperplane of
the first classifier and the distance to the hyperplane of the third classifier, as seen in Fig. 3d.

However, one would expect these representations to be correlated when the animal is
performing the C2 task. This is quantified by correlating the distance to the hyperplane of the
fourth classifier and the distance to the hyperplane of the third classifier, as seen in Fig. S6b.

Distance along color and shape encoding axes during task discovery
To understand how the geometry of the neural representation of the color and shape of the
stimulus evolved during task discovery (Figure 5), we measured the distance between the
two prototype colors (red and green) and the two prototype shapes (tee and bunny). Distance
was measured along the encoding axes for each stimulus dimension, taken as the axis that
is orthogonal to the color and shape classifiers (described above). So, for each test trial, the
distance along the color encoding axis was:

$Color\ encoding\ distance = Avg \begin{pmatrix} abs\big(Encoding(Red\ Bunny) - Encoding(Green\ Bunny)\big), \\ abs\big(Encoding(Red\ Tee) - Encoding(Green\ Tee)\big) \end{pmatrix};$

This approach allowed us to calculate the distance along red/green colors while controlling
for differences across shapes. The color encoding distance was estimated for 250 iterations

of the classifiers, allowing us to estimate the mean and standard error of the distance. A
similar process was followed for estimating the shape encoding distance.

To calculate the color and shape encoding distance during task discovery (Fig. 5a, 5b), we
calculated the distance above in the sliding window of 50 trials after the switch into the C1
task.

Compression index (CPI)

Compression index (CPI) was defined as the log of the ratio of average "Color encoding
distance" and average "Shape encoding distance" described above:

$$Compression\ Index(CPI) = \log\left(\frac{avg(Color\ encoding\ distance)}{avg(Shape\ encoding\ distance)}\right)$$

Compression index (CPI) was defined as the log of the ratio of average "Color encoding
distance" and average "Shape encoding distance" described above: to calculate CPI for each
task (Fig. 5c), we computed shape and color encoding distance using all trials of a given task.
Measure shape distance for all three tasks, we trained a classifier to categorize stimulus
shape based on neural responses during the S1 task (limited to the last 75 trials of each
block). To ensure the classifier was only responding to shape (and not motor response), we
trained the classifier on a balanced set of correct (rewarded) and incorrect (unrewarded) trials
(20 trials: 5 trials for each reward condition and for each shape category). Shape encoding
for each task was calculated using 4 trials to test the classifier (1 trial for each of the four
stimulus congruency types).

To measure color distance in S1/C2/C1 task, we trained color category classifier on only
correct trials of C1/C1/C2 task balanced for congruent and incongruent stimuli (20 trials: 5
trials for each of the four stimulus congruency types). Color encoding for each task was
calculated using 4 trials of that task to test the classifier (1 trial for each of the four stimulus
congruency types).

$$Compression\ Index(CPI) = \log\left(\frac{avg(Color\ encoding\ distance)}{avg(Shape\ encoding\ distance)}\right)$$

To track changes in the relative strength of color and shape information during task discovery,
we calculated CPI in a sliding window of 50 trials after the animal's switched into the C1 task
(during S1-C2-C1 sequences of tasks, with low initial performance). Note, since we have

controlled for motor response when calculating shape and color distance, the CPI is not
affected by motor response information[9].

Correlation between task belief encoding and compression index

To correlate the CPI with task belief encoding, we used the same set of C1 test trials to
calculate both CPI and estimate the task identity using the task classifier described above.
CPI values in 100ms-300ms after stimulus onset and belief encoding values in 500ms to
150ms before stimulus onset were averaged for all trials in each trial window and the Mann-
Kendall correlation between the resulting two vectors was calculated (Fig. 5e).

1034

References

1. Bouchacourt, F., Tafazoli, S., Mattar, M. G., Buschman, T. J. & Daw, N. D. Fast rule switching and slow
rule updating in a perceptual categorization task. *eLife* **11**, e82531 (2022).

2. Maris, E. & Oostenveld, R. Nonparametric statistical testing of EEG- and MEG-data. *Journal of*
Neuroscience Methods **164**, 177–190 (2007).

3. Chiang, F.-K. & Wallis, J. D. Neuronal Encoding in Prefrontal Cortex during Hierarchical Reinforcement
Learning. **30**, 12.

4. Kendall, M. G. *Rank Correlation Methods.* (Griffin, Oxford, England, 1948).

5. Mann, H. B. Nonparametric Tests Against Trend. *Econometrica* **13**, 245–259 (1945).

6. Hamed, K. H. & Ramachandra Rao, A. A modified Mann-Kendall trend test for autocorrelated data.
Journal of Hydrology **204**, 182–196 (1998).

7. Aalok, A (2024). Modified-MannKendall-Test (https://github.com/atharvaaalok/Modified-
MannKendall-Test/releases/tag/v2.0), GitHub. January, 2024.

8. Groppe, D (2024). fdr_bh (https://www.mathworks.com/matlabcentral/fileexchange/27418-fdr_bh),
MATLAB Central File Exchange. January, 2024.

9. Flesch, T. *et al.* Are task representations gated in macaque prefrontal cortex? Preprint at
http://arxiv.org/abs/2306.16733 (2023).

1052