Distractor suppression operates exclusively in retinotopic coordinates

Yayla A. Ilksoy[1, 2], Dirk van Moorselaar[1, 2], Benchi Wang [4, 5, 6, 7], Sander A. Los[1, 2] & Jan Theeuwes[1, 2, 3]

[1] Vrije Universiteit Amsterdam, Amsterdam, The Netherlands

[2] Institute Brain and Behavior Amsterdam (iBBA), Amsterdam, the Netherlands

[3] William James Center for Research, ISPA-Instituto Universitario, Lisbon, Portugal

[4] Key Laboratory of Brain, Cognition and Education Sciences (South China Normal University),
Ministry of Education, Guangzhou, China

[5] Institute for Brain Research and Rehabilitation, South China Normal University, Guangzhou,
China

[6] Center for Studies of Psychological Application, South China Normal University, Guangzhou,
China

[7] Guangdong Key Laboratory of Mental Health and Cognitive Science, South China Normal
University, Guangzhou, China

14
15
16
17   Word count: 5405
18
19

Corresponding author: Correspondence should be addressed to Yayla Ilksoy, Department of
Experimental and Applied Psychology, Vrije Universiteit Amsterdam, Van der Boechorststraat 7,
1081 BT Amsterdam, The Netherlands. Email: y.a.ilksoy@vu.nl

Contact information remaining authors: dirkvanmoorselaar@gmail.com;
wangbenchi.swift@gmail.com; s.a.los@vu.nl; j.theeuwes@vu.nl;

Acknowledgments: This research was supported by a NWO Open competition grant

406.21.GO.034 and by a European Research Council (ERC) advanced grant 833029 –

[LEARNATTEND].[1]

---

[1] The authors declare no competing financial interests.

Abstract

Our attention is influenced by past experiences, and recent studies have shown that individuals learn to extract statistical regularities in the environment, resulting in attentional suppression of locations that are likely to contain a distractor (high-probability location). However, little is known as to whether this learned suppression operates in retinotopic (relative to the eyes) or spatiotopic (relative to the world) coordinates. In the current study, two circular search arrays were presented side by side. Participants learned the high-probability location from a learning array presented on one side of the display (e.g., left). After several trials, participants shifted their gaze to the center of the other search array (e.g., located on the right side) and continued searching without any location probability (labelled as "test array"). Due to the saccade, the test array contained both a spatiotopic and a retinotopic matching location relative to the original high-probability location. The current findings show that, following saccadic eye movements, the learned suppression remained in retinotopic coordinates only, with no measurable transfer to spatiotopic coordinates. Even in a rich environment, attentional suppression still operated exclusively in retinotopic coordinates. We speculate that learned suppression may be resolved by changing synaptic weights in early visual areas.

Keywords: Attentional suppression; retinotopic; spatiotopic; statistical learning; saccades

Significance statement

In our daily lives, attention is shaped by past experiences, guiding us to suppress locations that

are likely to contain distractions. While this phenomenon has been studied extensively with

static search displays, the real world is dynamic - we are constantly moving our eyes. This study

addressed this issue by investigating what happens when we learn to suppress a likely

distractor location while making eye movements. Do we suppress the same location in space

(spatiotopic), or does the learned suppression persist relative to our eyes (retinotopic)? The

current findings provide clear evidence of suppression in retinotopic coordinates only.

Introduction

Where and what we attend is not only influenced by the dynamics of sensory input (bottom–

up) and our current goal states (top–down or behavioral relevance) but also heavily influenced

by what we have encountered in the past. One example of selection biases implemented by

selection history comes from recent studies demonstrating that human observers can learn to

extract statistical regularities in the environment resulting in attentional suppression of

locations that are likely to contain a distractor, effectively reducing the amount of distraction

(Wang & Theeuwes, 2018a, 2018b, 2018c). The general idea is that just like top-down, and

bottom-up attention, selection history feeds into an integrated priority (salience) map,

ultimately resulting in a winner-take-all competition that determines the allocation of covert

and overt attention (Theeuwes, 2019; Theeuwes et al., 2022). The notion of learning-induced

plasticity within the spatial priority map is important, as it can explain how lingering biases from

former attentional deployments come about. While it is generally agreed that spatial priority

maps are topographically organized maps of the external visual world (e.g., Bisley & Goldberg,

2010; Fecteau & Munoz, 2006; Thompson & Bichot, 2005), it remains largely unclear how the

"external world" is represented within these maps. As such it remains unclear whether

suppression effects due to statistical learning, which is thought to operate via changes of

weights within the spatial priority map, operate in retinotopic (relative to the eyes) or

spatiotopic (relative to the world) coordinates.

Researchers have identified potential spatial priority map candidates among various

brain regions, such as the superior colliculus (Bisley, 2011; Krauzlis et al., 2013; Noudoost et al.,

2010; Wurtz et al., 2011), caudate nucleus (Kim & Hikosaka, 2013; Yamamoto et al., 2012), and

regions in the posterior parietal (Bisley & Goldberg, 2010; e.g., lateral intraparietal cortex) and

frontal cortices (Thompson et al., 2005; Thompson & Bichot, 2005; e.g., frontal eye field).

Regardless of whether these regions are cortical or subcortical, it is generally accepted that

retinotopy is preserved throughout the brain, suggesting that priority maps are retinotopically

organized. Nevertheless, a topographical representation would be more appropriate as it

reflects the external visual world upon which we act (e.g., Bisley & Goldberg, 2010; Fecteau &

Munoz, 2006; Thompson & Bichot, 2005). If a location is relevant for selection or requires

suppression, it makes sense to connect it to external world coordinates rather than retinal

location. In line with both views, previous studies have shown that both endogenous attention

(Golomb et al., 2008, 2010) and exogenous attention (Mathôt & Theeuwes, 2010a, 2010b) rely

on retinotopic maps, which are progressively transformed into spatiotopic maps following

saccades. Moreover, a recent study by van Moorselaar & Theeuwes (2023) showed that people

can learn to prioritize a likely target location within objects, irrespective of the object's

orientation in space. This implies that statistical learning is not necessarily limited to retinotopic

maps. However, no study to date has explored whether history-driven suppression effects

persist in retinotopic coordinates or transfer to spatiotopic coordinates after eye movements.

In the present study, we adopted the additional singleton task used by Wang and

Theeuwes (2018a) in which the distractor singleton was presented more often in one location

than in all other locations. Critically, this regularity was only present when participants were

performing the task at one side of the display (labelled as "learning array"). After performing

several trials within this learning array (e.g., on the left side), participants shifted their gaze to

another display (e.g., the one on the right) and continued the search task, but now without any

statistical regularities included (labelled as "test array"). Due to the saccadic eye movement

towards the test location, it contained both a spatiotopic matching and a retinotopic matching

location relative to the suppressed location in the learning array. The question then was

whether the learned suppression within the learning array would stay in retinotopic

coordinates, transfer to spatiotopic coordinates, or relies on both coordinate systems.

Experiment 1

Methods

The Ethical Review Committee of the Faculty of Behavioral and Movement Sciences of the Vrije

Universiteit Amsterdam approved the present study. Twenty-four adults (20 women, mean age:

23.8 years old) were recruited for money compensation or course credits. They all signed

informed consent before the study and reported normal or corrected-to-normal visual acuity.

Sample size was predetermined based on previous studies that used similar designs (de Waard

et al., 2022; Ivanov & Theeuwes, 2021; Kong et al., 2020). In these studies, the effect size

(cohen's d) of the critical comparison between the high-probability and low-probability

distractor location was 0.72 or higher. With 24 subjects and alpha = .05, power for this critical

effect would be larger than 0.95.

Apparatus and stimuli Participants were tested in a dimly lit laboratory, with their chin held on

a chinrest located 70 cm away from a 24-in. liquid crystal display (LCD) color monitor. The

experiment was created in *OpenSesame* (Mathôt et al., 2012) and run on a Dell Precision 3640

computer. An eye-tracker (EyeLink 1,000) was used to monitor participants' eye movements

and the sampling rate was set to 1,000 Hz.

A modified additional singleton paradigm was adopted. The visual search display

consisted of six discrete stimuli with different shapes (one circle vs. five diamonds, or vice

versa), each containing a vertical or horizontal gray line (0.2° × 1°) inside (see Figure 1). The

stimuli were presented on an imaginary circle with a radius of 3.5°, centered at the fixation (a

white cross measuring 0.5° × 0.5°) against a black background (RGB: 0/0/0). The radius of the

circle stimuli was 1°, the diamond stimuli were subtended by 1.55° × 1.55°, and each had a red

(RGB: 253/34/34) or green (RGB: 90/174/20) outline.

Figure 1. Stimuli and design. **(A)** An example of a trial sequence. In this example, the fixation switches from left (Search display I) to right (Search display II). The gridlines and placeholders were introduced in Experiment 2 and not present in Experiment 1. **(B)** Possible stimulus locations. The high-probability distractor location was always in the center of the screen (D-0). In the test array, location D-3 (map) represents the spatiotopic location and location D-0 (map) the retinotopic location. The location of the learning array (left or right), and consequently the position of the HP location within the learning array, was counterbalanced across participants.

Experimental design Every trial started with a fixation cross that remained visible throughout

the trial. The fixation cross was presented horizontally at either 3.5° to the left or 3.5° to the

right of the center of the screen. After 500 ms, a search array was presented and centered at

the fixation cross for 2000 ms or until response. Participants searched for one circle (target)

among five diamonds (distractors) or vice versa and responded to the orientation of the line

segment as fast as possible, by pressing the 'up' arrow key for vertical and the 'left' arrow key

for horizontal with their right hand. The inter-trial interval (ITI) was randomly chosen from 350

to 550 ms.

A target was presented in each trial with an equal probability of being a circle or

diamond. A uniquely colored distractor singleton was present in 66.7% of the trials, with the

same shape as the other distractors but with a different color (red or green with an equal

probability). All conditions were randomized within each block. For each search array, the

target could appear at each of the six locations. Importantly, two types of search arrays were

presented: a learning and test array. For the learning array, in the distractor singleton present

condition, the distractor singleton had a high proportion of 63% to be presented at the center

of the display (e.g., the furthest right location of the left search array or the furthest left

location of the right search array). This location is called the high-probability (HP) location. Each

of the other locations independently had a low proportion of 7.4% to contain a distractor

singleton (low-probability location). For the test array, all the locations contained a distractor

singleton equally often (16.7% in distractor-present trials). The target location was determined

randomly on each trial.

The experiment consisted of six blocks of 250 trials each. The first two blocks only

presented the learning array on one side of the display. The position of the learning array (left

or right), and consequently the position of the HP location within the learning array, was

counterbalanced across participants. After the first two blocks, the learning array alternated

with the test array, which was presented on the opposite side of the display. Every few trials,

specifically after a randomly selected sequence of 8, 9, or 10 consecutive trials for the learning

array and 4 or 5 consecutive trials for the test array, a white dot appeared at the previous

fixation location during the ITI period. Following this, participants had to immediately move

their eyes to the other fixation on the opposite side of the display to perform the search task

for the other search array. Crucially, the location at the center of the screen was shared by the

learning and test array: This was the HP location of the learning array and the spatiotopic

location of the test array. The retinotopic location was at the opposite side of the test array

(see Figure 1B for an illustration). In blocks three to six, the learning and test arrays were

presented in 165 and 85 trials, respectively.

166   There were two practice sessions before the experiment started: one practice session of

15 trials with only the learning array that remained in the same location (as in the first two

blocks of the experiment) and one practice session of 40 trials that alternated between the

learning and test array (as in block three to six of the experiment). If participants did not

achieve more than 70% accuracy or were not faster than 1100 ms on average in the practice

sessions, they had to repeat the session. If participants did not respond or made an erroneous

response, a warning message was presented. At the end of the experiment participants were

asked whether they noticed the statistical regularities (subjective measure) and on which

location within the array they thought the HP location was (objective measure). Notably, these

questions were interspersed with unrelated questions that were included to avoid influencing

responses to the study-related questions.

Participants were instructed to fixate on the fixation cross in every trial. A warning

sound was played if eyes deviated from fixation (see Data analysis for further details). Before

every block, the eye tracker was calibrated, and an automatic drift check was performed at the

beginning of every 10 trials.

Statistical analysis Participants with an average accuracy below 2.5 standard deviation from the

overall accuracy were excluded as outliers and replaced. Trials on which the response times

(RTs) were faster than 200 ms and trials on which RTs were faster or slower than 2.5 standard

deviations from the average response time per array per block per participant were excluded

from analyses. Subsequently, participants with an average RT faster than 2.5 standard

deviations of the group mean were excluded as outliers and replaced. Trials in which eyes

deviated from fixation were also excluded. Eye deviations were determined by identifying

instances where fixations extended beyond 2.5° from the fixation cross for more than 75 ms

(Golomb et al., 2008; Mathôt & Theeuwes, 2010a; Talsma et al., 2013). For RT analyses, only

trials with a correct response were included.

The main analysis was separated into two analytical approaches. First, to ascertain that

observers learned to suppress the HP location, learning array RTs and error rates were analyzed

using repeated-measures analysis of variance (ANOVAs) followed by planned comparisons with

paired-sample t-tests. Where sphericity was violated, Greenhouse-Geiser corrected p-values

are reported. To then determine whether the learned attentional bias, once established,

transferred to retinotopic or spatiotopic coordinates, the analysis of the test array included only

data from those participants who exhibited visual statistical learning effect in the learning

array. This effect was characterized by either faster RTs or lower error rates in the HP location

than in the low-probability (LP) distractor location. In contrast to the conventional ANOVA

approach here we relied on linear mixed models (LMMs) and generalized mixed models

(GLMMs) approaches for the RT and error rate analyses respectively, where the data is not

averaged but instead grouped per participant. For the present purposes, this approach has two

main advantages. First, a range of continuous and categorical variables can be added to a single

model such that rather than excluding large subsets of data in a series of control analyses,

which inevitably reduces power (Brysbaert & Stevens, 2018), various control factors that could

potentially modulate the effect of interest can be simultaneously included allowing for a more

refined control. Specifically, in all adopted models Distractor condition (retinotopic location, LP

location and spatiotopic location) was incorporated into the fixed-effects structure as an

ordered factor. In addition to the main effect of interest, the following factors were entered

into the fixed-effects structure: intertrial location distractor and target priming (i.e., whether

the position of a distractor or target repeated from one trial to the next; yes, no), array switch

(i.e., whether the array position was the same as on the previous trial or had switched; yes, no),

target and distractor position (0-5), learning array position (left, right), awareness of the HP

location (response to objective measure, see Procedure and design for further details; correct,

incorrect), target color (red, green), target shape (circle, diamond) and target line orientation

(horizontal, vertical). Second, and most importantly, this approach allowed us to evaluate

whether suppression was best characterized by a model resulting from a gradient centered at

either the retinotopic or the spatiotopic location, indicative of retinotopic or spatiotopic

suppression respectively (see Figure 2A and B), or alternatively by a model in which both

retinotopic and spatiotopic suppression exerted their effects simultaneously (see Figure 2C).

For this purpose, the model included a linear, as well as a quadratic coefficient of Distractor

condition (retinotopic, LP, spatiotopic). The degrees of freedom of all coefficients were

estimated using Satterwaite's method for approximating degrees of freedom and the F

statistics, Z-scores and the corresponding p-values were obtained from the *lmerTest* package

(Kuznetsova et al., 2017) in R (R Core Team, 2018). Alll fixed effects were dummy coded.

following guidelines by Barr et al. (2013), by-participants random intercepts and by-participant

random slopes for Distractor condition were included in the random-effects structure.

Figure 2. The three hypothesized outcomes in the test array. Each bar represents the mean RT or error rate when the distractor
is presented at a certain distractor location (retinotopic, LP and spatiotopic location). **(A)** An increasing slope across retinotopic,
LP and spatiotopic locations suggests retinotopic suppression. **(B)** A decreasing slope across retinotopic, LP and spatiotopic
locations suggests spatiotopic suppression. **(C)** A negative parabola across retinotopic, LP and spatiotopic locations suggests
both retinotopic and spatiotopic suppression.

Transparancy and openness All data and analysis codes are available at https://osf.io/ev7zx/.

The study's design and its analysis were not pre-registered. All data was collected in 2023.

Despite the participant pool being mostly female undergraduate psychology students, the

study's focus on fundamental cognitive processes suggests limited constraints on generality, as

these mechanisms are foundational and likely to generalize across diverse populations. We

anticipate consistent results with different stimuli, provided they elicit a pop-out effect from

both the distractor and target elements.

Results

In total, four participants were excluded and replaced based on their RTs (three participants)

and because too many trials were removed due to eye movements (one participant). Exclusion

of incorrect responses (7.7%), data trimming (3.3%) and trials with eye movements (10.7%)

resulted in an overall loss of 21.7% of the trials for the RT analyses and 14% of the trials for the

error rate analyses.

Learning array Before investigating how distractor suppression remaps following a saccade, we

first examined to what extent distractor learning took place in the learning array. Repeated-

measures ANOVAs with Distractor condition (no distractor, HP location and LP location) as a

within-subject factor revealed a reliable main effect on both mean RTs ($F_{(2, 46)} = 104.709$, $p <$

$.001$, $n_p^2 = .82$; see Figure 3A and 3B) and mean error rates ($F_{(2, 46)} = 32.057$, $p < .001$, $n_p^2 = .58$;

see Figure 3C and 3D). Subsequent planned comparisons showed that relative to no distractor

trials, RTs were slower and error rates were higher when the distractor appeared at the HP or

LP location (all t's > 3.9 and p's < .001). Critically, RTs were faster ($t_{(23)} = 5.27$, $p < .001$) and

error rates were lower ($t_{(23)} = 3.9$, $p < .001$) when the distractor appeared at the HP location

compared to the LP location, indicative of learned attentional suppression at the high

probability distractor location.

Figure 3. RTs (A and B) and error rates (C and D) in Experiment 1 as a function of distractor location for learning arrays. The bars represent the condition means, and each gray dot represents the mean of an individual participant. Error bars represent 95% within-subjects confidence intervals (Morey, 2008). The significance bars represent the planned comparisons with paired-sample t-tests. The diamonds inside the boxplots represent the mean difference scores and the horizontal lines represent the median difference scores. **(A)** RTs in the learning array. The bars show a clear attentional capture effect with slower RTs when the distractor is present. **(B)** The boxplot displays the RT differences between the HP and LP condition in the learning array. Most subjects had faster RTs when the distractor is presented at the HP location compared to the LP location. **(C)** Error rates in the learning array. The bars show a clear attentional capture effect with higher error rates when the distractor is present. **(D)** The boxplot displays the error rate differences between the HP and LP condition in the learning array. Most subjects have lower error rates when the distractor is presented at the HP location compared to the LP location.

Test array After having established reliable suppression within the learning array, we next set

out to establish the dynamics of this learned suppression following a saccade by limiting the

analysis to only those participants that showcased learning within the learning array (*N* = 22 for

RT; *N* = 18 for error rate). We considered three possible scenarios: suppression is retinotopically

organized, spatiotopically organized or a combination of both (see Figure 2). Previous work by

Wang and Theeuwes (Wang & Theeuwes, 2018a, 2018b) showed that not only the HP location

but also its nearby locations were suppressed by learning statistical regularities. In other words,

the location that was furthest away from the HP location showed the smallest spatial gradient

suppression effect. In the current paradigm, the retinotopic and spatiotopic locations are

furthest away from each other. Therefore, in the case of a retinotopic suppression effect, we

expect a gradient from the retinotopic location towards the spatiotopic location. Conversely, if

the suppression effect is spatiotopic, we expect the gradient to occur in the opposite direction.

As visualized in Figure 4A, progression from the retinotopic towards the spatiotopic location

was characterized by a systematic increase in RTs (linear β = 24.00, SE = 8.16, t (21.7) = 2.94, p <

.01), in line with the scenario in Figure 2A. The error rates yielded a similar pattern although the

fitted slope across the retinotopic, LP and spatiotopic locations was not significant (linear β =

0.31, SE = 0.18, z = 1.7, p = .08; quadratic β = -0.25, SE = 0.18, z = -1.38, p = .17; see Figure 4C).

Together these findings demonstrate that the observed statistical learning effect did not

transfer to spatiotopic coordinates, but instead remained in retinotopic coordinates following a

saccade.

Discussion

The current findings show that following a saccadic eye movement, suppression due to

statistical learning remained in retinotopic coordinates only, with no measurable transfer to

spatiotopic coordinates. While this is an important finding, it should be noted that in the

current set-up there were no visual environmental landmarks as the search display was

presented on the background of a blank empty screen. Also, with each saccade, the entire

display shifted from side to side, making the entire visual field move along with the eye

movements. It is therefore possible that the absence of a spatiotopic effect has to do with the

absence of any visual landmarks. To that end, a second experiment was conducted with a grid

and placeholders in the display to create more structure by introducing visual landmarks (see

Figure 1).

Figure 4. RTs (A and B) and error rates (C and D) in Experiment 1 as a function of distractor location for test arrays. **(A)** RTs in the test array. The bars show a systematic increase in RTs across the retinotopic, LP and spatiotopic locations (linear β = 24.00, SE = 8.16, t (21.7) = 2.94, p < .01). (B) The boxplot displays the RT differences between the retinotopic and LP location and the spatiotopic and LP location. (C) Error rates in the test array. While conventional t-tests show that error rates at the retinotopic location are lower relative to the LP location (t (17) = 4.01, *p* < .001), the GLMM showed no significant slope across the distractor locations (linear β = 0.31, SE = 0.18, z = 1.7, *p* = .08; quadratic β = -0.25, SE = 0.18, z = -1.38, *p* = .17) (D) The boxplot displays the error rate differences between the retinotopic and LP location and the spatiotopic and LP location.

Experiment 2a

Methods

Experiment 2a was identical to Experiment 1 except for the following changes. The experiment

was conducted in an online environment on a JATOS server (Lange et al., 2015). To determine a

adequate sample size for Experiment 2, we assessed the statistical power of the variable of

interest (Distractor condition) in detecting a 24 ms increasing slope across the retinotopic, LP

and spatiotopic locations locations, as observed in Experiment 1. Using the *simr* package of

Green & Macleod (2015), the analysis indicated that the power for Distractor condition within

the test array was 84.6% (95% confidence interval, CI [82.21%, 86.78%] in 1,000 simulations) to

detect this slope. Due to the increased noise in online studies, we decided to expand the

sample size by 30%, leading to a total of 32 participants for experiment 2. Additionally, given

the challenging nature of Experiment 2a (see description of the experimental design), which

could potentially increase the noise further, we chose to include 50 participants. Fifty adults (23

women, mean age: 27.9 years old) were recruited for monetary compensation via the online

platform Prolific (www.prolific.co; £10.33). Because the experiment was conducted online, our

control over the experimental settings was restricted, and as a result we report the stimuli in

terms of pixels instead of visual degrees. The search arrays (search radius was 150 pixels;

diamond stimuli were subtended by 56 × 56 pixels, circle stimuli had radius of 45 pixels) were

presented inside a gray-colored grid with 4 × 4 horizontal and vertical lines (see Figure 1A). To

ensure that the grid remained noticeable, we modified the line thickness three times within

each block. At the onset of each block, gridlines were consistently presented with a thickness of

3 pixels. Every 50 trials, the gridline thickness randomly alternated, transitioning between 1, 5,

and 7 pixels. Dark gray placeholders in the form of a circle imposed upon a diamond were

presented at all possible stimulus locations. To ensure that the participants maintained fixation

effectively before initiating saccades, the stimulus display was presented for only 150 ms, which

is a duration that is too short to make any directed eye movements within the search array

(Fischer & Ramsperger, 1984; Fischer & Weber, 1993; Heeman et al., 2019). The experiment

consisted of five blocks of 200 trials each, with the first block only consisting of arrays

presented on one side of the display (either left or right, counterbalanced across participants).

Results

Five participants were identified as outliers and replaced based on their mean accuracy (one

participant) and mean RT (four participants). Furthermore, seven participants with an average

accuracy below 60%, indicative of chance-level performance, were identified and replaced.

Three additional participants were substituted due to stimuli being displayed for over 180 ms

(instead of the intended 150 ms) in more than 50% of the trials, attributable to the refresh rate

of their personal computers. Exclusion of incorrect responses (18.3%) and data trimming (2.1%)

resulted in an overall loss of 20.5% of the trials for the RT analyses and 2.1% of the trials for the

error rate analyses.

Learning array For the learning array, repeated-measures ANOVAs with Distractor condition (no

distractor , HP location and LP location) as within-subjects factor showed a main effect for both

mean RTs (F (2, 98) = 50.093, p < .001, n_p^2 = .51) and mean error rates (F (2, 98) = 97.32, p <

.001, n_p^2 = .67). As before, subsequent planned comparisons revealed slower RTs and higher

error rates when the distractor was presented at the HP location or LP location compared to

the no distractor condition (all t's > 3.3, all p's < .02; see Figure 5A and 5C). Crucially, in

comparison to the LP location, RTs were faster (t (49) = 3.26, p < .01; see Figure 5B), and error

rates were lower (t (49) = 4.92, p < .001; see Figure 5D) at the HP location, indicating attentional

suppression at the high-probability distractor location.

Figure 5. RTs (A and B) and error rates (C and D) in Experiment 2 as a function of distractor location for learning arrays. **(A)** RTs in the learning array. The bars show a clear attentional capture effect with slower RTs when the distractor is present. **(B)** The boxplot displays the RT differences between the HP and LP condition in the learning array. Most subjects had faster RTs when the distractor is presented at the HP location compared to the LP location. **(C)** Error rates in the learning array. The bars show a clear attentional capture effect with higher error rates when the distractor is present. **(D)** The boxplot displays the error rate differences between the HP and LP condition in the learning array. Most subjects have lower error rates when the distractor is presented at the HP location compared to the LP location.

Test array Having established a learned attentional bias in the learning array, we next set out to

examine whether that bias continued to persist in retinotopic coordinates after a saccade is

made in the presence of environmental landmarks by again including only those participants

that demonstrated the hypothesized effect in the learning array (*N* = 38 for RT; *N* = 42 for error

rate). As visualized in Figure 6A, and counter to Experiment 1, the data was no longer

characterized by a linear increase from the retinotopic, to the LP to the spatiotopic location

(linear β = 6.71, SE = 6.13, *t* (38.5) = 1.093, *p* = .28). Instead, RTs were fastest at the LP location

relative to the retinotopic and the spatiotopic location (quadratic β = 21.95, SE = 6.52, *t*

(131.15) = 3.37, *p* < .001), a pattern that is inconsistent with any of the models outlined in

Figure 2. By contrast, error rates did showcase a systematic rise from the retinotopic location

towards the spatiotopic location (linear β = 0.21, SE = 0.1, *z* = 2.2, *p* = .028; see Figure 6C).

Together, these findings again demonstrate that there was no evidence that learned spatial

suppression would be remapped in spatiotopic coordinates following a saccade, not even when

visual landmarks provided more visual structure.

Figure 6. RTs (A and B) and error rates (C and D) in Experiment 2 as a function of distractor location for test arrays. **(A)** RTs in
the test array. The bars show that the RTs are fastest when the distractor is presented at the LP location (quadratic β = 21.95,
SE = 6.52, t (131.15) = 3.37, p < .001), which is inconsistent with any of the expected scerarios. **(B)** The boxplot displays the RT
differences between the retinotopic and LP location and the spatiotopic and LP location. **(C)** Error rates in the test array. The
bars show a systematic increase in error rates across the retinotopic, LP and spatiotopic locations (linear β = 0.21, SE = 0.1, z =
2.2, p = .028) **(D)** The boxplot displays the error rate differences between the retinotopic and LP location and the spatiotopic
and LP location.

Discussion

In Experiment 2a, we added a grid and placeholders to the search display to impose a spatial

reference frame and promote spatiotopic processing. However, as in Experiment 1, there was

no transfer of the learned spatial suppression to the spatiotopic location after eye movements.

If anything, the data suggests that the learned suppression still persisted in retinotopic

coordinates, characterized by a positive error rate slope across the retinotopic towards the

spatiotopic location (in line with the scenario in Figure 2A). But in contrast to Experiment 1, the

slope seemed to be mainly driven by an increase from the LP to the spatiotopic location and not

by the increase from the retinotopic to the LP location. Additionally, this pattern occurred only

for the error rates and not for the RTs. A possible explanation for this discrepancy is that the

stimuli were only presented for 150 ms and not until response, making the task very

challenging. As a result, participants may have been more inclined to make fast guesses,

resulting in less informative reaction times. Experiment 2b addressed this issue by extending

the stimulus display duration to 2000 ms or until a response was made.

Experiment 2b

Methods

Experiment 2b was identical to Experiment 2a, except that the stimuli were presented for 2000

ms or until response (as in Experiment 1). In Experiment 2b, we anticipated the effect size to

fall between that of Experiment 1 and Experiment 2a. This expectation was based on the

controlled environment of Experiment 1 leading to a higher effect size, and the challenging

nature of the task in Experiment 2a resulting in a lower effect size. Thirty-two adults (16

women, mean age: 27.25 years old) were recruited for monetary compensation via the online

platform Prolific (www.prolific.co; £9.25).

Results

One participant was identified as an outlier and replaced based on their average RT. Exclusion

of incorrect trials (9.1%) and data trimming (2.3%) resulted in an overall loss of 11.3% of the

trials for the RT analyses and 2.3% of trials for the error rate analyses.

395
Figure 7. RTs (A and B) and error rates (C and D) in Experiment 3 as a function of distractor location for learning arrays. **(A)** RT
in the learning array. The bars show a clear attentional capture effect with slower RTs when the distractor is present. **(B)** The
boxplot displays the RT differences between the HP and LP condition in the learning array. Most subjects have faster RTs when
the distractor is presented at the HP location compared to the LP location. **(C)** Error rates in the learning array. The bars
demonstrate a pronounced attentional capture effect, indicated by higher error rates when the distractor is present. **(D)** The
boxplot displays the error rate differences between the HP and LP condition in the learning array. The majority of subjects
exhibit lower error rates when the distractor is presented at the HP compared to the LP location.

Learning array For the learning array, repeated-measures ANOVAs with within-subjects factor

Distractor condition (no distractor, HP location and LP location) yielded a main effect for RTs (F

$(2, 62) = 135.29$, $p < .001$, $n_p^2 = .81$) as well as for error rates (F (2, 62) = 66.38, $p < .001$, $n_p^2 =$

.68). Subsequent planned comparisons confirmed that relative to the no distractor condition

RTs were slower and error rates were higher at the HP and LP locations (all t's > 5.7, all p's <

.001; see Figure 7A and 7C). Crucially, participants were faster (t (31) = 6.91, $p < .001$; see Figure

7B) and had lower error rates (t (31) = 5.73, $p < .001$; see Figure 7D) when the distractor

appeared at the HP location compared to the LP location.

Test array Again, we exclusively considered participants who demonstrated a visual statistical

learning effect in the learning array for the analyses conducted on the test array (N = 30 for

both the RT and error rate analyses). Counter to Experiment 2, as visualized in Figure 8A and 8C

respectively, both RT (linear β = 21.87, SE = 10.21, t (31.72) = 2.14, $p = .04$) and error rate (linear

$\beta = 0.52$, SE = 0.12, $z = 4.49$ $p < .001$) were characterized by a systematic increase across the

retinotopic, LP and spatiotopic locations. Together with the previous experiments these

findings show that at least under the present conditions there is no evidence whatsoever that

learned spatial suppression is remapped into spatiotopic coordinates following a saccade.

Discussion

Experiment 2b replicated the results of Experiment 1 and demonstrated that, following eye

movements, suppression effects due to statistical learning remain in retinotopic coordinates,

while there was no transfer of the suppression to spatiotopic coordinates, even when visual

landmarks are present to impose a spatial reference frame.

Figure 8. RTs (A and B) and error rates (C and D) in Experiment 3 as a function of distractor location for test arrays. **(A)** RTs in the test array. Similar to experiment 1, the bars show a positive slope across the retinotopic, LP and spatiotopic locations (linear β = 21.87, SE = 10.21, t (31.72) = 2.14, *p* = .04) **(B)** The boxplot displays the RT differences between the retinotopic and LP location and the spatiotopic and LP location. **(C)** Error rates in the test array. The bars show a systematic increase in error rates across the retinotopic, LP and spatiotopic locations (linear β = 0.52, SE = 0.12, z = 4.49 *p* < .001) **(D)** The boxplot displays the error rate differences between the retinotopic and LP location and the spatiotopic and LP location.

General Discussion

The present study shows that participants learn the statistical regularities presented in the

display and adapt their selection priorities accordingly. More importantly, the current study

provides compelling new evidence that the attentional suppression effect due to statistical

learning operates in retinotopic coordinates rather than spatiotopic coordinates. Following a

saccade to a new location, we see that the same location relative to the eyes is suppressed.

433   These findings provide some important insight about the underlying mechanism. Given

that suppression is only found in retinotopic coordinates, it is possible that learned suppression

is resolved by changing synaptic weights in early visual areas, as the initial input to visual cortex

is retinotopic. Importantly, it has been suggested that the brain exclusively encodes spatial

information within retinotopic maps and does not contain explicit spatiotopic representations

(Golomb et al., 2008; Golomb & Kanwisher, 2012; Mathôt & Theeuwes, 2011). Indeed, it has

been shown that retinotopy is preserved throughout higher visual areas (Golomb & Kanwisher,

2012). A plausible mechanism for representing topographic maps involves the remapping of

retinotopic maps, potentially triggered by eye movement signals, such as a corollary discharge.

Notably, behavioral studies on endogenous attention (Golomb et al., 2008, 2010) and

exogenous attention (Mathôt & Theeuwes, 2010b) reveal a gradual remapping of attention

from retinotopic to spatiotopic coordinates following eye movements. It has been suggested

that the frontal eye field (FEF) is a central source of remapping, with early visual cortices playing

a comparatively minor role (Mathôt & Theeuwes, 2011). Given the findings of the current

study, the question remains as to why this remapping phenomenon does not seem to apply to

the observed suppression effects. This leads to the hypothesis that the suppression effect

observed in the current study may be resolved primarily in early visual cortices, without

extending to the FEF, in contrast to top-down or bottom-up attentional processes.

Alternatively, some studies suggest that only attended items are remapped, which

raises the possibility that suppression effects may not be remapped to spatiotopic coordinates

(Golomb & Mazer, 2021; Gottlieb et al., 1998; Joiner et al., 2011). In other words, it is feasible

that selection history-driven attentional enhancement undergoes similar remapping as

exogenous and endogenous attention, while selection history-driven attentional suppression

remains in retinotopic coordinates. Indeed, van Moorselaar and Theeuwes (2023)

demonstrated that attentional enhancement resulting from statistical learning does not always

rely on a retinotopic reference frame but can also occur within objects, irrespective of the

object's location in space. To test whether history-driven attentional enhancement can be

remapped to spatiotopic coordinates, the current study should be repeated with a likely target

location instead of a likely distractor location.

It is noteworthy that participants exhibited retinotopic suppression not only in

Experiment 1, where eye fixations were regulated, but also in Experiment 2. In the latter case,

the inability to control eye movements during the search meant that the search location

labelled as retinotopic did probably not consistently align with the same location on the

participant's retina. In other words, subjects suppressed the same location with respect to the

fixation cross even when they could freely move their eyes during search. This suggests that the

suppression effect is not only tied to retinotopic coordinates but also extends to a head-

centered egocentric (i.e. self-referenced) representation. Consistent with this observation, Jiang

& Swallow (2013, 2014) conducted a series of experiments demonstrating that attentional

enhancement due to probability cuing is dependent on the participants' viewpoint. Participants

were tasked with locating a T among L's displayed on a tablet mounted on a stand.

Unbeknownst to the participants, the target appeared more frequently in one quadrant

compared to the others. As expected, the study revealed an attentional bias towards the

quadrant that was likely to contain the target. However, intriguingly, when participants moved

around the tablet, the attentional facilitation appeared to move along with the participant's

viewpoint rather than remaining in the spatiotopic location. It is important to note that in these

experiments, each trial began with a fixation dot randomly placed within a central region and

participants were allowed to freely move their eyes during search. This implies that the likely

target location was not learned in a retinotopic manner (i.e., relative to the eyes) but within an

egocentric reference frame (i.e., relative to the head-body). Consequently, it appears that there

is not only a lack of remapping of statistical learning effects from retinotopic to spatiotopic

coordinates following eye movements but also an absence of updating the egocentric reference

frame to an environmentally stable reference frame after body and head movements (but also

see Jiang et al., 2014; Smith et al., 2010; Zheng et al., 2021). Given our continuous eye and body

movements, the practical use of learned attentional biases becomes uncertain when they are

not remapped from retinotopic or egocentric coordinates to spatiotopic coordinates.

In summary, the findings of the current study indicate that, following saccadic eye

movements, suppression effects persist in retinotopic coordinates, with no observed transfer of

suppression to spatiotopic coordinates. It remains unclear whether there are situations in

which implicit attentional biases are remapped to spatiotopic coordinates.

References

Barr, D. J., Levy, R., Scheepers, C., & Tily, H. J. (2013). Random effects structure for confirmatory

hypothesis testing: Keep it maximal. *Journal of Memory and Language*, *68*(3), 255–278.

https://doi.org/10.1016/J.JML.2012.11.001

Bisley, J. W. (2011). The neural basis of visual attention. *The Journal of Physiology*, *589*(1), 49–

57. https://doi.org/10.1113/JPHYSIOL.2010.192666

Bisley, J. W., & Goldberg, M. E. (2010). Attention, intention, and priority in the parietal lobe.

Annual Review of Neuroscience, *33*, 1–21. https://doi.org/10.1146/ANNUREV-NEURO-

060909-152823

Brysbaert, M., & Stevens, M. (2018). Power Analysis and Effect Size in Mixed Effects Models: A

Tutorial. *Journal of Cognition*, *1*(1). https://doi.org/10.5334/JOC.10

de Waard, J., Bogaerts, L., van Moorselaar, D., & Theeuwes, J. (2022). Surprisingly inflexible:

Statistically learned suppression of distractors generalizes across contexts. *Attention,*

Perception, and Psychophysics, *84*(2), 459–473. https://doi.org/10.3758/S13414-021-

02387-X/FIGURES/8

Fecteau, J. H., & Munoz, D. P. (2006). Salience, relevance, and firing: a priority map for target

selection. *Trends in Cognitive Sciences*, *10*(8), 382–390.

https://doi.org/10.1016/J.TICS.2006.06.011

Fischer, B., & Ramsperger, E. (1984). Human express saccades: extremely short reaction times

of goal directed eye movements. *Experimental Brain Research*, *57*(1), 191–195.

https://doi.org/10.1007/BF00231145/METRICS

Fischer, B., & Weber, H. (1993). Express saccades and visual attention. *Behavioral and Brain*

Sciences, *16*(3), 553–567. https://doi.org/10.1017/S0140525X00031575

Golomb, J. D., Chun, M. M., & Mazer, J. A. (2008). The Native Coordinate System of Spatial

Attention Is Retinotopic. *Journal of Neuroscience*, *28*(42), 10654–10662.

https://doi.org/10.1523/JNEUROSCI.2525-08.2008

Golomb, J. D., & Kanwisher, N. (2012). Higher Level Visual Cortex Represents Retinotopic, Not

Spatiotopic, Object Location. *Cerebral Cortex*, *22*(12), 2794–2810.

https://doi.org/10.1093/CERCOR/BHR357

Golomb, J. D., & Mazer, J. A. (2021). *Annual Review of Vision Science Visual Remapping*.

https://doi.org/10.1146/annurev-vision-032321

Golomb, J. D., Pulido, V. Z., Albrecht, A. R., Chun, M. M., & Mazer, J. A. (2010). Robustness of

the retinotopic attentional trace after eye movements. *Journal of Vision*, *10*(3).

https://doi.org/10.1167/10.3.19

Gottlieb, J. P., Kusunoki, M., & Goldberg, M. E. (1998). The representation of visual salience in

monkey parietal cortex. *Nature 1998 391:6666*, *391*(6666), 481–484.

https://doi.org/10.1038/35135

Green, P., & Macleod, C. J. (2015). *SIMR: an R package for power analysis of generalized linear*

mixed models by simulation. https://doi.org/10.1111/2041-210X.12504

Heeman, J., Van der Stigchel, S., Munoz, D. P., & Theeuwes, J. (2019). Discriminating between

anticipatory and visually triggered saccades: Measuring minimal visual saccadic response

time using luminance. *Journal of Neurophysiology*, *121*(6), 2101–2111.

https://doi.org/10.1152/JN.00378.2018/ASSET/IMAGES/LARGE/Z9K0041950090006.JPEG

Ivanov, Y., & Theeuwes, J. (2021). Distractor suppression leads to reduced flanker interference.

Attention, Perception, and Psychophysics, *83*(2), 624–636.

https://doi.org/10.3758/S13414-020-02159-Z/FIGURES/8

Jiang, Y. V., & Swallow, K. M. (2013). Spatial reference frame of incidentally learned attention.

Cognition, *126*(3), 378–390. https://doi.org/10.1016/J.COGNITION.2012.10.011

Jiang, Y. V., & Swallow, K. M. (2014). Changing viewer perspectives reveals constraints to

implicit visual statistical learning. *Journal of Vision*, *14*(12).

https://doi.org/10.1167/14.12.3

Jiang, Y. V., Won, B. Y., Swallow, K. M., & Mussack, D. M. (2014). Spatial reference frame of

attention in a large outdoor environment. *Journal of Experimental Psychology. Human*

Perception and Performance, *40*(4), 1346–1357. https://doi.org/10.1037/A0036779

Joiner, W. M., Cavanaugh, J., & Wurtz, R. H. (2011). Modulation of shifting receptive field

activity in frontal eye field by visual salience. *Journal of Neurophysiology*, *106*(3), 1179–

1190.

https://doi.org/10.1152/JN.01054.2010/ASSET/IMAGES/LARGE/Z9K0091109170009.JPEG

Kim, H. F., & Hikosaka, O. (2013). Distinct Basal Ganglia Circuits Controlling Behaviors Guided by

Flexible and Stable Values. *Neuron*, *79*(5), 1001–1010.

https://doi.org/10.1016/J.NEURON.2013.06.044

Kong, S., Li, X., Wang, B., & Theeuwes, J. (2020). Proactively location-based suppression elicited

by statistical learning. *PLOS ONE*, *15*(6), e0233544.

https://doi.org/10.1371/JOURNAL.PONE.0233544

Krauzlis, R. J., Lovejoy, L. P., & Zénon, A. (2013). Superior colliculus and visual spatial attention.

Annual Review of Neuroscience, *36*, 165–182. https://doi.org/10.1146/ANNUREV-NEURO-

062012-170249

Kuznetsova, A., Brockhoff, P. B., & Christensen, R. H. B. (2017). lmerTest Package: Tests in

Linear Mixed Effects Models. *Journal of Statistical Software*, *82*(13), 1–26.

https://doi.org/10.18637/JSS.V082.I13

Lange, K., Kühn, S., & Filevich, E. (2015). "Just Another Tool for Online Studies" (JATOS): An Easy

Solution for Setup and Management of Web Servers Supporting Online Studies. *PLOS ONE*,

10(6), e0130834. https://doi.org/10.1371/JOURNAL.PONE.0130834

Mathôt, S., Schreij, D., & Theeuwes, J. (2012). OpenSesame: An open-source, graphical

experiment builder for the social sciences. *Behavior Research Methods*, *44*(2), 314–324.

https://doi.org/10.3758/S13428-011-0168-7/FIGURES/4

Mathôt, S., & Theeuwes, J. (2010a). Evidence for the predictive remapping of visual attention.

Experimental Brain Research, *200*(1), 117–122. https://doi.org/10.1007/S00221-009-2055-

3/FIGURES/2

Mathôt, S., & Theeuwes, J. (2010b). Gradual remapping results in early retinotopic and late

spatiotopic inhibition of return. *Psychological Science*, *21*(12), 1793–1798.

https://doi.org/10.1177/0956797610388813/ASSET/IMAGES/LARGE/10.1177_095679761

0388813-FIG2.JPEG

Mathôt, S., & Theeuwes, J. (2011). Visual attention and stability. *Philosophical Transactions of*

the Royal Society B: Biological Sciences, *366*(1564), 516–527.

https://doi.org/10.1098/RSTB.2010.0187

Morey, R. D. (2008). Confidence Intervals from Normalized Data: A correction to Cousineau

(2005). *Tutorials in Quantitative Methods for Psychology*, *4*(2), 61–64.

https://doi.org/10.20982/TQMP.04.2.P061

Noudoost, B., Chang, M. H., Steinmetz, N. A., & Moore, T. (2010). Top-down control of visual

attention. *Current Opinion in Neurobiology*, *20*(2), 183–190.

https://doi.org/10.1016/J.CONB.2010.02.003

Smith, A. D., Hood, B. M., & Gilchrist, I. D. (2010). Probabilistic Cuing in Large-Scale

Environmental Search. *Journal of Experimental Psychology: Learning Memory and*

Cognition, *36*(3). https://doi.org/10.1037/a0018280

Talsma, D., White, B. J., Mathôt, S., Munoz, D. P., & Theeuwes, J. (2013). A Retinotopic

Attentional Trace after Saccadic Eye Movements: Evidence from Event-related Potentials.

Journal of Cognitive Neuroscience, *25*(9). https://doi.org/10.1162/jocn_a_00390

Team, R. C. (2018). *A language and environment for statistical computing. R Foundation for*

Statistical Computing, Vienna, Austria. Available Online: Www. R-Project. Org/(Accessed

on 11 September 2020).

Theeuwes, J. (2019). Goal-driven, stimulus-driven, and history-driven selection. *Current Opinion*

in Psychology, *29*, 97–101. https://doi.org/10.1016/J.COPSYC.2018.12.024

Theeuwes, J., Bogaerts, L., & van Moorselaar, D. (2022). What to expect where and when: how

statistical learning drives visual selection. *Trends in Cognitive Sciences*, *26*(10), 860–872.

https://doi.org/10.1016/J.TICS.2022.06.001

Thompson, K. G., & Bichot, N. P. (2005). A visual salience map in the primate frontal eye field.

Progress in Brain Research, *147*(SPEC. ISS.), 249–262. https://doi.org/10.1016/S0079-

6123(04)47019-8

Thompson, K. G., Bichot, N. P., & Sato, T. R. (2005). Frontal eye field activity before visual search

errors reveals the integration of bottom-up and top-down salience. *Journal of*

Neurophysiology, *93*(1), 337–351.

https://doi.org/10.1152/JN.00330.2004/ASSET/IMAGES/LARGE/Z9K0010542991014.JPEG

van Moorselaar, D., & Theeuwes, J. (2023). Statistical Learning Within Objects. *Psychological*

Science, *34*(4), 501–511. https://doi.org/10.1177/09567976231154804/FORMAT/EPUB

Wang, B., & Theeuwes, J. (2018a). How to inhibit a distractor location? Statistical learning

versus active, top-down suppression. *Attention, Perception, and Psychophysics*, *80*(4), 860–

870. https://doi.org/10.3758/S13414-018-1493-Z/FIGURES/5

Wang, B., & Theeuwes, J. (2018b). Statistical Regularities Modulate Attentional Capture. *Journal*

of Experimental Psychology: Human Perception and Performance, *44*(1), 13–17.

https://doi.org/10.1037/XHP0000472

Wang, B., & Theeuwes, J. (2018c). Statistical regularities modulate attentional capture

independent of search strategy. *Attention, Perception, and Psychophysics*, *80*(7), 1763–

1774. https://doi.org/10.3758/S13414-018-1562-3/FIGURES/6

Wurtz, R. H., Joiner, W. M., & Berman, R. A. (2011). Neuronal mechanisms for visual stability:

progress and problems. *Philosophical Transactions of the Royal Society B: Biological*

Sciences, *366*(1564), 492–503. https://doi.org/10.1098/RSTB.2010.0186

Yamamoto, S., Monosov, I. E., Yasuda, M., & Hikosaka, O. (2012). What and Where Information

in the Caudate Tail Guides Saccades to Visual Objects. *Journal of Neuroscience*, *32*(32),

11005–11016. https://doi.org/10.1523/JNEUROSCI.0828-12.2012

Zheng, L., Dobroschke, J. G., & Pollmann, S. (2021). Egocentric and Allocentric Reference

Frames Can Flexibly Support Contextual Cueing. *Frontiers in Psychology*, *12*.

https://doi.org/10.3389/fpsyg.2021.711890

626